INDEXES TO THE JOURNAL

compiled by the

American Ceramic Society

VOL. 50, NO. 12 DECEMBER 21, 1967

AUTHOR INDEX TO THE JOURNAL

The number in parentheses refers to the *monthly* issue of *The Journal;* the numbers following are the *page* numbers.

Achenbach, G. D., James, W. J., and Gerson, R. Preparation of single-phase polycrystalline $BiFeO_3$, (8) 437.

Adams, R. B., and Stuart, W. I. Effect of adsorbed sulfate and fluoride on the density of hot-pressed beryllium oxide, (12) 685.

Allen, A. W. See Forlano, R. J.

Ampian, S. G. See Miller, J. L., Jr.

Andersen, J. C. See Taylor, K. M.

Anderson, H. U. Initial sintering of rutile, (5) 235–38; see also Payne, D. A.

Anderson, O. L. See Soga, Naohiro.

Anderson, R. C. See Jorgensen, P. J.

Arbel, A. Deformation properties of a polycrystalline KCl–NaCl alloy, (2) 114.

Arend, H., Coufová, P., and Novák, J. Chemical processes during hydrogen reduction of barium titanate crystals, (1) 22–25.

Arlett, R. H., and Robbins, Murray. Growth of stoichiometric $MgAl_2O_4$ single crystals, (5) 273–74.

Arlett, R. H., Robbins, M., and Herkart, P. G. Growth of large sapphire crystals from cryolite, (1) 58.

Aronson, S., Cisney, E., and Gingerich, K. A. Thermal expansion of some cubic refractory compounds of thorium, (5) 248–52.

Atkins, A. G., and Tabor, D. Mutual indentation hardness of single-crystal magnesium oxide at high temperatures, (4) 195–98.

Baak, Tryggve, and Frederick, R. L. Polarography in molten sodium disilicate, (1) 38–42.

Ballman, A. A., Levinstein, H. J., Capio, C. D., and Brown, H. Curie temperature and birefringence variation in ferroelectric lithium metatantalate as a function of melt stoichiometry, (12) 657–59.

Bannister, M. J. Crystallite size measurements on thoria gel, (11) 619–23.

Barmore, W. L. See Cline, C. F.

Barmore, W. L., and Vandervoort, R. R. High-temperature creep and dislocation etch pits in polycrystalline beryllium oxide, (6) 316–20.

Barry, T. L., and Roy, Rustum. Defect characterization in and precipitation from CaO:Yb_2O_3 crystalline solutions, (2) 105–108.

Barry, T. L., Stubican, V. S., and Roy, Rustum. Decomposition kinetics of $CaYb_2O_4$, (7) 375–78.

Bartholomew, R. F., and Kozlowski, T. R. Alkali attack of glass surfaces by molten salts, (2) 108–11.

Baskin, Y. Phase studies in the pseudobinary system UN-UP, (2) 74–76.

Bates, J. L., Hinman, C. A., and Kawada, T. Electrical conductivity of uranium dioxide, (12) 652–56.

Batt, J. A. See Galasso, F. S.

Beall, G. H., Karstetter, B. R., and Rittler, H. L. Crystallization and chemical strengthening of stuffed β-quartz glass-ceramics, (4) 181–90.

Beals, R. J. See Forlano, R. J.

Beard, W. C., and Foster, W. R. High-temperature formation of anatase, (9) 493.

Beeley, P. R. See Snape, E.

Belt, R. F. X-ray topography of Czochralski ruby, (11) 588–93.

Benecke, M. W., Olson, N. E., and Pask, J. A. Effect of LiF on hot-pressing of MgO, (7) 365–68.

Bentle, G. G. Diffusion of zirconium in zirconium hydride, (3) 166–67.

Berard, M. F. See Wirkus, C. D.

Bergeron, C. G., and De Luca, J. P. Crystal growth at bubble surfaces in glass, (2) 116–17.

Bertolotti, R. L., and Fulrath, R. M. Effect of micromechanical stress concentrations on strength of porous glass, (11) 558–62.

Bidwell, L. R. See Wimmer, J. M.

Bigaré, M., Guinier, A., Mazières, C., Regourd, M., Yannaquis, N., Eysel, W., Hahn, Th., and Woermann, E. Polymorphism of tricalcium silicate and its solid solution, (11) 609–19.

Biggers, J. V., and Muan, Arnulf. Activity-composition relations in orthosilicate and metasilicate solid solutions in the system MnO-CoO-SiO_2, (5) 230–35; correction, (12) 689.

Bishay, A. M., and Gomaa, Ibrahim. Radiation-induced defects and structure of barium silicate glasses, (6) 302–307.

Bishay, A. M., and Maklad, M. S. Gamma-induced absorption bands associated with Tl^+, Pb^{2+}, or Bi^{3+} in potassium borate glasses, (10) 503–508.

Blankenship, A. C. See West, R. G.

Blaszyk, P. E. See Riebling, E. F.

Borbas, J. J., Padfield, R. C., and Moscker, E. Density determination of refractories by measurement of gamma-radiation absorption, (8) 421–24.

Borom, M. P., Longwell, J. A., and Pask, J. A. Reactions between metallic iron and cobalt oxide-bearing sodium disilicate glass, (2) 61–66.

Bradt, R. C. Cr_2O_3 solid solution hardening of Al_2O_3, (1) 54–55.

Braski, D. N. See Buckley, J. D.

Bratton, R. J., and Tien, T. Y. Phase transitions in the system $BaTiO_3$-$KNbO_3$, (2) 90–93.

Bright, N. F. H. See Webster, A. H.

Brindley, G. W. See Ficalora, P. J.

Brizes, W. F., and Tobin, J. M. Isolation of the zeta phase in the system tantalum-carbon, (2) 115–16.

Broli, M. See Hagemark, K.

Brown, H. See Ballman, A. A.

Brownell, W. E. See Hunter, Orville, Jr.

Brubaker, B. D. Ductile magnesium oxide whiskers, (11) 624.

Brukl, C. E. See Rudy, Erwin.

Buckley, J. D., and Braski, D. N. Elastic modulus of stabilized zirconia, (4) 220–21.

Burdick, V. L., and Day, D. E. Coordination of aluminum ions in tricalcium aluminate, (2) 97–101.

Burnett, P. See Heuer, A. H.

Cable, Michael, and Rasul, C. G. Spontaneous bubble formation in silicate melts at high temperatures: II, Effect of wet atmospheres and behavior of mixed alkali glasses, (10) 528–31.

Capio, C. D. See Ballman, A. A.

Carlberg, John. See Cline, C. F.

Carrell, M. A., and Wilder, D. R. Sintering study in the partially vitreous As–S–Se system, (11) 604–609.

Carrier, G. B. Discussion of "Transmission electron microscopy of thin glass samples," (12) 686.

Chang, L. L. Y., and Phillips, Bert. Phase transition in the system $CaWO_4$-$SrWO_4$, (8) 434–35.

Chang, L. L. Y., Scroger, M. G., and Phillips, Bert. Condensed phase relations in the systems ZrO_2-WO_3-WO_3 and HfO_2-WO_3-WO_3, (4) 211–15.

Charles, R. J. Activities in Li_2O-, Na_2O-, and K_2O-SiO_2 solutions, (12) 631–41.

Chase, A. B., and Osmer, J. A. Localized cooling in flux crystal growth, (6) 325–28.

Chase, A. B., and Wilcox, W. R. Temperature fluctuations and striations in flux crystal growth, (6) 332–33.

Chatterji, S., and Jeffery, J. W. Discussion of paper "Expansion characteristics of calcium sulfoaluminate hydrates," (12) 687–88.

Chen, J. H. See Redman, M. J.

Chenot, C. F. Phase boundaries in a portion of the system SrO-B_2O_3, (2) 117–18.

Chromý, Stanislav. High-temperature microscopic investigation of tricalcium silicate and dicalcium silicate phases in portland cement clinker, (12) 677–81.

Cisney, E. See Aronson, S.

Cline, C. F., Carlberg, John, and Newkirk, H. W. Ionic conductivity in BeO, (1) 55–56.

Cline, C. F., Newkirk, H. W., Barmore, W. L., and Vandervoort, R. R. Creep-electrical conductivity correlations in polycrystalline beryllium oxide, (4) 221–22.

Coble, R. L. See Roy, S. K.

Cook, R. L. See Greenberg, C. B.

Condit, R. H., and Hashimoto, Yuriko. Self-diffusion of beryllium in polycrystalline beryllium oxide, (8) 425–32.

Conley, R. F. Structural and chemical alterations of delta Fe_2O_3 and their effect on magnetic properties, (3) 124–28.

Coufová, P. See Arend, H.

Cullen, G. V. See Hensler, J. H.

Cullen, G. V., Cutter, I. A., and Hensler, J. H. Hot-pressing of magnesium oxide aggregates, (12) 688–89.

Cutler, I. B. See Johnson, H. B.; Stewart, R. W.

Cutter, I. A. See Cullen, G. V.

Dachille, Frank. See Stewart, D. R.

Darby, W. L. See Galasso, F. S.

Datta, R. K. The system $LiAlGeO_4$-$ZnGeO_4$, (7) 384.

Datta, R. K., and Roy, Rustum. Equilibrium order-disorder in spinels, (11) 578–83; Synthesis of cubic nickel orthosilicate, (12) 684.

Davis, R. S. See Doherty, P. E.

Day, D. E. See Burdick, V. L.; Steinkamp, W. E.

Day, R. B., and Stokes, R. J. Plastic softening of magnesium oxide at high temperatures by nickel oxide addition, (9) 445–48.

Dayal, R. R., Johnson, R. E., and Muan, Arnulf. Stability of mullite as derived from equilibria in the system CoO-Al_2O_3-SiO_2, (10) 537–43.

De Luca, J. P. See Bergeron, C. G.

Diamond, J. J. See Dragoo, A. L.

Doherty, P. E., Lee, D. W., and Davis, R. S. Direct observation of the crystallization of Li_2O-Al_2O_3-SiO_2 glasses containing TiO_2, (2) 77–81.

Douglas, F. C. See Galasso, F. S.

Douglas, R. W., and El-Shamy, T. M. M. Reactions of glasses with aqueous solutions, (1) 1–8.

Dragoo, A. L., and Diamond, J. J. Transitions in vapor-deposited alumina from 300° to 1200°C, (11) 568–74.

Duke, D. A., MacDowell, J. F., and Karstetter, B. R. Crystallization and chemical strengthening of nepheline glass-ceramics, (2) 67–74.

Eastwood, H. K. See Westwood, W. D.

Ehlers, E. G. See McCormick, G. R.

Elmer, T. H., and Nordberg, M. E. Effect of nitriding on electrolysis and devitrification of high-silica glasses, (6) 275–79.

El-Shamy, T. M. M. See Douglas, R. W.

Eppler, R. A., and McLeran, W. A., Jr. Kinetics of opacification of a TiO_2-opacified cover coat enamel, (3) 152–56.

Eysel, W. See Bigaré, M.

Feigelson, R. S. Crystal growth of rare-earth orthoarsenates, (8) 433–34.

Felty, E. J., and Myers, M. B. Thermal expansion of arsenic-selenium glasses, (6) 335–36.

Ficalora, P. J., and Brindley, G. W. Oxidation of magnesiowustite single crystals: II, Dependence on temperature, oxygen pressure, and crystal composition, (12) 662–65.

Fine, M. E. See Hsu, S. E.

Finlayson, K. M., and Williams, J. P. Beta spodumene-silica solid solution in an Li_2O-Al_2O_3-TiO_2-SiO_2 glass-ceramic, (9) 488–89.

Fisher, J. R. See Pearson, A. D.

Forbes, R. L. See Taylor, K. M.

Forlano, R. J., Allen, A. W., and Beals, R. J. Elasticity and anelasticity of uranium oxides at room temperature: I, Stoichiometric oxide, (2) 93–96.

Foster, W. R. See Beard, W. C.

Franklin, A. D. Born model calculation of enthalpies of solution in CaF_2, (12) 648–52.

Fréchette, V. D. See Oel, H. J.

Frederick, R. L. See Baak, Tryggve.

Freund, F. Retention of hydroxyl groups on magnesium oxide, (9) 493–94.

Fries, R. J., and Wahman, L. A. Effect of stoichiometry on the thermal expansion of TaC_x, (9) 475–77.

Fritsche, E. T., and Tensmeyer, L. G. Liquidus in the alumina-rich system La_2O_3-Al_2O_3, (3) 167–68.

Fuchs, Karl. See King, A. G.

Fuerstenau, D. W. See Kapur, P. C.

INDEXES TO THE JOURNAL

compiled by the

American Ceramic Society

VOL. 50, NO. 12 DECEMBER 21, 1967

AUTHOR INDEX TO THE JOURNAL

The number in parentheses refers to the *monthly* issue of *The Journal;* the numbers following are the *page* numbers.

Achenbach, G. D., James, W. J., and Gerson, R. Preparation of single-phase polycrystalline $BiFeO_3$, (8) 437.

Adams, R. B., and Stuart, W. I. Effect of adsorbed sulfate and fluoride on the density of hot-pressed beryllium oxide, (12) 685.

Allen, A. W. See Forlano, R. J.

Ampian, S. G. See Miller, J. L., Jr.

Andersen, J. C. See Taylor, K. M.

Anderson, H. U. Initial sintering of rutile, (5) 235–38; see also Payne, D. A.

Anderson, O. L. See Soga, Naohiro.

Anderson, R. C. See Jorgensen, P. J.

Arbel, A. Deformation properties of a polycrystalline KCl–NaCl alloy, (2) 114.

Arend, H., Coufová, P., and Novák, J. Chemical processes during hydrogen reduction of barium titanate crystals, (1) 22–25.

Arlett, R. H., and Robbins, Murray. Growth of stoichiometric $MgAl_2O_4$ single crystals, (5) 273–74.

Arlett, R. H., Robbins, M., and Herkart, P. G. Growth of large sapphire crystals from cryolite, (1) 58.

Aronson, S., Cisney, E., and Gingerich, K. A. Thermal expansion of some cubic refractory compounds of thorium, (5) 248–52.

Atkins, A. G., and Tabor, D. Mutual indentation hardness of single-crystal magnesium oxide at high temperatures, (4) 195–98.

Baak, Tryggve, and Frederick, R. L. Polarography in molten sodium disilicate, (1) 38–42.

Ballman, A. A., Levinstein, H. J., Capio, C. D., and Brown, H. Curie temperature and birefringence variation in ferroelectric lithium metatantalate as a function of melt stoichiometry, (12) 657–59.

Bannister, M. J. Crystallite size measurements on thoria gel, (11) 619–23.

Barmore, W. L. See Cline, C. F.

Barmore, W. L., and Vandervoort, R. R. High-temperature creep and dislocation etch pits in polycrystalline beryllium oxide, (6) 316–20.

Barry, T. L., and Roy, Rustum. Defect characterization in and precipitation from CaO:Yb_2O_3 crystalline solutions, (2) 105–108.

Barry, T. L., Stubican, V. S., and Roy, Rustum. Decomposition kinetics of $CaYb_2O_4$, (7) 375–78.

Bartholomew, R. F., and Kozlowski, T. R. Alkali attack of glass surfaces by molten salts, (2) 108–11.

Baskin, Y. Phase studies in the pseudobinary system UN-UP, (2) 74–76.

Bates, J. L., Hinman, C. A., and Kawada, T. Electrical conductivity of uranium dioxide, (12) 652–56.

Batt, J. A. See Galasso, F. S.

Beall, G. H., Karstetter, B. R., and Rittler, H. L. Crystallization and chemical strengthening of stuffed β-quartz glass-ceramics, (4) 181–90.

Beals, R. J. See Forlano, R. J.

Beard, W. C., and Foster, W. R. High-temperature formation of anatase, (9) 493.

Beeley, P. R. See Snape, E.

Belt, R. F. X-ray topography of Czochralski ruby, (11) 588–93.

Benecke, M. W., Olson, N. E., and Pask, J. A. Effect of LiF on hot-pressing of MgO, (7) 365–68.

Bentle, G. G. Diffusion of zirconium in zirconium hydride, (3) 166–67.

Berard, M. F. See Wirkus, C. D.

Bergeron, C. G., and De Luca, J. P. Crystal growth at bubble surfaces in glass, (2) 116–17.

Bertolotti, R. L., and Fulrath, R. M. Effect of micromechanical stress concentrations on strength of porous glass, (11) 558–62.

Bidwell, L. R. See Wimmer, J. M.

Bigaré, M., Guinier, A., Mazières, C., Regourd, M., Yannaquis, N., Eysel, W., Hahn, Th., and Woermann, E. Polymorphism of tricalcium silicate and its solid solution, (11) 609–19.

Biggers, J. V., and Muan, Arnulf. Activity-composition relations in orthosilicate and metasilicate solid solutions in the system MnO-CoO-SiO_2, (5) 230–35; correction, (12) 689.

Bishay, A. M., and Gomaa, Ibrahim. Radiation-induced defects and structure of barium silicate glasses, (6) 302–307.

Bishay, A. M., and Maklad, M. S. Gamma-induced absorption bands associated with Tl^+, Pb^{2+}, or Bi^{3+} in potassium borate glasses, (10) 503–508.

Blankenship, A. C. See West, R. G.

Blaszyk, P. E. See Riebling, E. F.

Borbas, J. J., Padfield, R. C., and Moscker, E. Density determination of refractories by measurement of gamma-radiation absorption, (8) 421–24.

Borom, M. P., Longwell, J. A., and Pask, J. A. Reactions between metallic iron and cobalt oxide-bearing sodium disilicate glass, (2) 61–66.

Bradt, R. C. Cr_2O_3 solid solution hardening of Al_2O_3, (1) 54–55.

Braski, D. N. See Buckley, J. D.

Bratton, R. J., and Tien, T. Y. Phase transitions in the system $BaTiO_3$-$KNbO_3$, (2) 90–93.

Bright, N. F. H. See Webster, A. H.

Brindley, G. W. See Ficalora, P. J.

Brizes, W. F., and Tobin, J. M. Isolation of the zeta phase in the system tantalum-carbon, (2) 115–16.

Broli, M. See Hagemark, K.

Brown, H. See Ballman, A. A.

Brownell, W. E. See Hunter, Orville, Jr.

Brubaker, B. D. Ductile magnesium oxide whiskers, (11) 624.

Brukl, C. E. See Rudy, Erwin.

Buckley, J. D., and Braski, D. N. Elastic modulus of stabilized zirconia, (4) 220–21.

Burdick, V. L., and Day, D. E. Coordination of aluminum ions in tricalcium aluminate, (2) 97–101.

Burnett, P. See Heuer, A. H.

Cable, Michael, and Rasul, C. G. Spontaneous bubble formation in silicate melts at high temperatures: II, Effect of wet atmospheres and behavior of mixed alkali glasses, (10) 528–31.

Capio, C. D. See Ballman, A. A.

Carlberg, John. See Cline, C. F.

Carrell, M. A., and Wilder, D. R. Sintering study in the partially vitreous As–S–Se system, (11) 604–609.

Carrier, G. B. Discussion of "Transmission electron microscopy of thin glass samples," (12) 686.

Chang, L. L. Y., and Phillips, Bert. Phase transition in the system $CaWO_4$-$SrWO_4$, (8) 434–35.

Chang, L. L. Y., Scroger, M. G., and Phillips, Bert. Condensed phase relations in the systems ZrO_2-WO_3-WO_3 and HfO_2-WO_3-WO_3, (4) 211–15.

Charles, R. J. Activities in Li_2O-, Na_2O-, and K_2O-SiO_2 solutions, (12) 631–41.

Chase, A. B., and Osmer, J. A. Localized cooling in flux crystal growth, (6) 325–28.

Chase, A. B., and Wilcox, W. R. Temperature fluctuations and striations in flux crystal growth, (6) 332–33.

Chatterji, S., and Jeffery, J. W. Discussion of paper "Expansion characteristics of calcium sulfoaluminate hydrates," (12) 687–88.

Chen, J. H. See Redman, M. J.

Chenot, C. F. Phase boundaries in a portion of the system SrO-B_2O_3, (2) 117–18.

Chromý, Stanislav. High-temperature microscopic investigation of tricalcium silicate and dicalcium silicate phases in portland cement clinker, (12) 677–81.

Cisney, E. See Aronson, S.

Cline, C. F., Carlberg, John, and Newkirk, H. W. Ionic conductivity in BeO, (1) 55–56.

Cline, C. F., Newkirk, H. W., Barmore, W. L., and Vandervoort, R. R. Creep-electrical conductivity correlations in polycrystalline beryllium oxide, (4) 221–22.

Coble, R. L. See Roy, S. K.

Cook, R. L. See Greenberg, C. B.

Condit, R. H., and Hashimoto, Yuriko. Self-diffusion of beryllium in polycrystalline beryllium oxide, (8) 425–32.

Conley, R. F. Structural and chemical alterations of delta Fe_2O_3 and their effect on magnetic properties, (3) 124–28.

Coufová, P. See Arend, H.

Cullen, G. V. See Hensler, J. H.

Cullen, G. V., Cutter, I. A., and Hensler, J. H. Hot-pressing of magnesium oxide aggregates, (12) 688–89.

Cutler, I. B. See Johnson, H. B.; Stewart, R. W.

Cutter, I. A. See Cullen, G. V.

Dachille, Frank. See Stewart, D. R.

Darby, W. L. See Galasso, F. S.

Datta, R. K. The system $LiAlGeO_4$-$ZnGeO_4$, (7) 384.

Datta, R. K., and Roy, Rustum. Equilibrium order-disorder in spinels, (11) 578–83; Synthesis of cubic nickel orthosilicate, (12) 684.

Davis, R. S. See Doherty, P. E.

Day, D. E. See Burdick, V. L.; Steinkamp, W. E.

Day, R. B., and Stokes, R. J. Plastic softening of magnesium oxide at high temperatures by nickel oxide addition, (9) 445–48.

Dayal, R. R., Johnson, R. E., and Muan, Arnulf. Stability of mullite as derived from equilibria in the system CoO-Al_2O_3-SiO_2, (10) 537–43.

De Luca, J. P. See Bergeron, C. G.

Diamond, J. J. See Dragoo, A. L.

Doherty, P. E., Lee, D. W., and Davis, R. S. Direct observation of the crystallization of Li_2O-Al_2O_3-SiO_2 glasses containing TiO_2, (2) 77–81.

Douglas, F. C. See Galasso, F. S.

Douglas, R. W., and El-Shamy, T. M. M. Reactions of glasses with aqueous solutions, (1) 1–8.

Dragoo, A. L., and Diamond, J. J. Transitions in vapor-deposited alumina from 300° to 1200°C, (11) 568–74.

Duke, D. A., MacDowell, J. F., and Karstetter, B. R. Crystallization and chemical strengthening of nepheline glass-ceramics, (2) 67–74.

Eastwood, H. K. See Westwood, W. D.

Ehlers, E. G. See McCormick, G. R.

Elmer, T. H., and Nordberg, M. E. Effect of nitriding on electrolysis and devitrification of high-silica glasses, (6) 275–79.

El-Shamy, T. M. M. See Douglas, R. W.

Eppler, R. A., and McLeran, W. A., Jr. Kinetics of opacification of a TiO_2-opacified cover coat enamel, (3) 152–56.

Eysel, W. See Bigaré, M.

Feigelson, R. S. Crystal growth of rare-earth orthoarsenates, (8) 433–34.

Felty, E. J., and Myers, M. B. Thermal expansion of arsenic-selenium glasses, (6) 335–36.

Ficalora, P. J., and Brindley, G. W. Oxidation of magnesiowustite single crystals: II, Dependence on temperature, oxygen pressure, and crystal composition, (12) 662–65.

Fine, M. E. See Hsu, S. E.

Finlayson, K. M., and Williams, J. P. Beta spodumene-silica solid solution in an Li_2O-Al_2O_3-TiO_2-SiO_2 glass-ceramic, (9) 488–89.

Fisher, J. R. See Pearson, A. D.

Forbes, R. L. See Taylor, K. M.

Forlano, R. J., Allen, A. W., and Beals, R. J. Elasticity and anelasticity of uranium oxides at room temperature: I, Stoichiometric oxide, (2) 93–96.

Foster, W. R. See Beard, W. C.

Franklin, A. D. Born model calculation of enthalpies of solution in CaF_2, (12) 648–52.

Fréchette, V. D. See Oel, H. J.

Frederick, R. L. See Baak, Tryggve.

Freund, F. Retention of hydroxyl groups on magnesium oxide, (9) 493–94.

Fries, R. J., and Wahman, L. A. Effect of stoichiometry on the thermal expansion of TaC_x, (9) 475–77.

Fritsche, E. T., and Tensmeyer, L. G. Liquidus in the alumina-rich system La_2O_3-Al_2O_3, (3) 167–68.

Fuchs, Karl. See King, A. G.

Fuerstenau, D. W. See Kapur, P. C.

Fulrath, R. M. See Bertolotti, R. L.; Hasselman, D. P. H.; Stett, M. A.
Fushimi, Shoichi, and Ikeda, Takuro. Phase equilibrium in the system PbO-TiO_2-ZrO_2, (3) 129–32.

Galasso, F. S., Darby, W. L., Douglas, F. C., and Batt, J. A. Unidirectional solidification of the $BaFe_{12}O_{19}$-$BaFe_2O_4$ eutectic, (6) 333–34.
Gani, M. S. See Standage, A. E.
Garrett, H. J. See Ruh, Robert.
Garton, G., and Wanklyn, B. M. Reinvestigation of the system Na_3AlF_6-Li_3AlF_6, (8) 395–99.
Gerson, R. See Achenbach, G. D.
Gingerich, K. A. See Aronson, S.
Glenn, G. R. X-ray studies of lime-bentonite reaction products, (6) 312–16.
Gomaa, Ibrahim. See Bishay, A. M.
Gordon, R. S., and Kingery, W. D. Thermal decomposition of brucite: II, Kinetics of decomposition in vacuum, (1) 8–14.
Graham, H. C., Tallan, N. M., and Russell, Ralston, Jr. Particle size dependence of the electrical conductivity of NaCl, (3) 156–63.
Graham, P. W. L., and Rindone, G. E. Internal friction peak caused by condensation of water on barium silicate glasses, (6) 336.
Grain, C. F. Phase relations in the ZrO_2-MgO system, (6) 288–90.
Greco, E. J., and Martinelli, J. A. Compositional dependency of laser-induced damage in glass, (5) 270.
Green, J. J. See Maguire, E. A.
Greenberg, C. B., and Cook, R. L. Interfacial reactions in lead oxide-bearing enamel-metal systems, (2) 84–90.
Gruver, R. M. See Kirchner, H. P.
Guinier, A. See Bigaré, M.
Gulden, T. D. Direct observation of nonbasal dislocations in sintered alumina, (9) 472–75.

Haertling, G. H. Properties of hot-pressed ferroelectric alkali niobate ceramics, (6) 329–30.
Hagemark, K., and Broli, M. Equilibrium oxygen pressures over solid solutions of urania-yttria and urania-lanthana at 1100° to 1400°C, (11) 563–67.
Hahn, Th. See Bigaré, M.
Hall, L. L. See Morgan, C. S.
Harris, N. H., and Tennery, V. J. Structural and dielectric investigation of the $PbTiO_3$-$BaZrO_3$ system, (8) 404–407.
Hashimoto, Yuriko. See Condit, R. H.
Hasselman, D. P. H. Relation between macroscopic shear moduli and micromechanical shear stress concentrations of multicomponent materials, (6) 331–32; Approximate theory of thermal stress resistance of brittle ceramics involving creep, (9) 454–57.
Hasselman, D. P. H., and Fulrath, R. M. Micromechanical stress concentrations in two-phase brittle-matrix ceramic composites, (8) 399–404.
Heasley, J. H. See Shaw, R. R.
Hed, A. Z. See Kofstad, P.
Hensler, J. H. See Cullen, G. V.
Hensler, J. H., and Cullen, G. V. Grain shape change during creep in magnesium oxide, (11) 584–85.
Herczog, Andrew. See Layton, M. M.
Herkart, P. G. See Arlett, R. H.
Hertl, W. Fibrous TiC, (11) 630; see also Pultz, W. W.
Hertl, W., and Pultz, W. W. Disproportionation and vaporization of solid silicon monoxide, (7) 378–81.
Heuer, A. H. See Sellers, D. J.
Heuer, A. H., and Burnett, P. Evidence for MgO whisker growth by a vapor-liquid-solid mechanism, (11) 627–28.
Hewson, C. W., and Kingery, W. D. Effect of MgO and $MgTiO_3$ doping on diffusion-controlled creep of polycrystalline aluminum oxide, (4) 218–19.
Hill, D. C. See Vergano, P. J.
Hinman, C. A. See Bates, J. L.
Hoenig, C. L., and Searcy, A. W. Vapor pressure, enthalpy, evaporation coefficient, and enthalpy of activation of the beryllium nitride (Be_3N_2) decomposition reaction, (9) 460–66.
Hoenig, C. L., Stout, N. D., and Nordine, P. C. Knudsen cell studies of the vaporization of gadolinium and gadolinium dicarbide, (8) 385–92.
Hornung, G. See Salt, D. J.
Hosaka, Shinobu. See Imai, Hisashi.
Hsu, S. E., Kobes, W., and Fine, M. E. Strengthening of sapphire by precipitates containing titanium, (3) 149–51.
Hulbert, S. F., and Klawitter, J. J. Kinetics and mechanism of the reaction between zinc oxide and barium carbonate, (9) 484–88.
Hunter, Orville, Jr., and Brownell, W. E. Thermal expansion and elastic properties of two-phase ceramic bodies, (1) 19–22.

Ikeda, Takuro. See Fushimi, Shoichi.
Imai, Hisashi, Hosaka, Shinobu, and Naito, Keiji. Preparation of thorium carbides, (6) 308–11.

James, W. J. See Achenbach, G. D.
Janowski, K. R., and Rossi, R. C. Elastic behavior of MgO matrix composites, (11) 599–603.
Jeffery, J. W. See Chatterji, S.
Johnson, H. B., Miller, G. R., and Cutler, I. B. Dielectric loss in CaF_2 doped with oxygen ions, (10) 526–27.
Johnson, R. E. See Dayal, R. R.
Jones, T. S., Kimura, Shigeyuki, and Muan, Arnulf. Phase relations in the system FeO-Fe_2O_3-ZrO_2-SiO_2, (3) 137–42.
Jorgensen, P. J., and Anderson, R. C. Grain-boundary segregation and final-stage sintering of Y_2O_3, (11) 553–58.

Kapur, P. C., and Fuerstenau, D. W. Dry strength of pelletized spheres, (1) 14–18.
Karstetter, B. R. See Beall, G. H.; Duke, D. A.
Karstetter, B. R., and Voss, R. O. Chemical strengthening of glass-ceramics in the system Li_2O-Al_2O_3-SiO_2, (3) 133–37.
Kawada, T. See Bates, J. L.
Keihn, F. G., and Keplin, E. J. High-temperature thermal expansion of certain group IV and group V diborides, (2) 81–84.
Kelly, A., and Rowcliffe, D. J. Deformation of polycrystalline transition metal carbides, (5) 253–56.
Kelly, P. J., and Laubitz, M. J. Thermoluminescence of alumina, (10) 540–42.
Keplin, E. J. See Keihn, F. G.
Kerr, J. M. Thermal simulation of in-reactor microstructures in ThO_2-UO_2, (9) 449–53.
Kestigian, M. Yttrium-iron garnet single-crystal growth by the combined Czochralski-molten salt solvent technique, (3) 165–66.
Kimura, Shigeyuki. See Jones, T. S.
King, A. G., and Fuchs, Karl. Polishing porous materials, (6) 328–29.
Kingery, W. D. See Gordon, R. S.; Hewson, C. W.
Kirchner, H. P., Gruver, R. M., and Walker, R. E. Chemically strengthened, leached alumina and spinel, (4) 169–73.
Klawitter, J. J. See Hulbert, S. F.
Kleppa, O. J. See Navrotsky, A.
Kobes, W. See Hsu, S. E.
Koester, R. D., and Moak, D. P. Hot hardness of selected borides, oxides, and carbides to 1900°C, (6) 290–96.
Kofstad, P., and Hed, A. Z. Defect structure model for nonstoichiometric CeO_2, (12) 681–82.
Kozlowski, T. R. See Bartholomew, R. F.
Kreglo, J. R., Jr., and Smothers, W. J. Mechanism of creep in MgO brick, (9) 457–60.

Laubitz, M. J. See Kelly, P. J.
Layton, M. M., and Herczog, Andrew. Nucleation and crystallization of $NaNbO_3$ from glasses in the Na_2O-Nb_2O_5-SiO_2 system, (7) 369–75.
Lee, D. W. See Doherty, P. E.
Leipold, M. H. Addenda to impurity distribution in MgO, (11) 628–29.
Leiser, D. B., and Whittemore, O. J., Jr. The system LiI-KI, (1) 60.
Levin, E. M. Structural interpretation of immiscibility in oxide systems: IV, Occurrence, extent, and temperature of the monotectic, (1) 29–38; The system Sc_2O_3-B_2O_3, (1) 53–54; The system Y_2O_3-V_2O_5, (7) 381–82.
Levinstein, H. J. See Ballman, A. A.
Longwell, J. A. See Borom, M. P.
Lowell, C. E. Solid solution of boron in graphite, (3) 142–44.
Luth, W. C. The system $KAlSiO_4$-Mg_2SiO_4-$KAlSi_2O_6$, (4) 174–76.
Lynch, C. T. See Mazdiyasni, K. S.

McCormick, G. R. See Miller, J. L., Jr.
McCormick, G. R., and Ehlers, E. G. Ternary phases in the system MgO-GeO_2-LiF, (8) 438–39.
MacDowell, J. F. See Duke, D. A.
McLearn, W. A., Jr. See Eppler, R. A.
Madden, G. I., and Van Vlack, L. H. Transformation of quartz to tridymite in the presence of binary silicate liquids, (8) 414–18.
Maguire, E. A., and Green, J. J. Magnetic properties of yttrium-gadolinium-iron-aluminum-indium garnets, (4) 208–10.
Maklad, M. S. See Bishay, A. M.
Marcus, J. H. See Ormsby, W. C.
Marlowe, M. O., and Wilder, D. R. Sensitive resonant frequency technique for the study of sintering kinetics, (3) 145–49; Sintering kinetics study using reduced variables, (10) 509–12.
Martinelli, J. A. See Greco, E. J.
Mattox, D. M. Contamination-nucleated crystal growth at bubble surfaces in glass, (12) 683.
Mazdiyasni, K. S., Lynch, C. T., and Smith, J. S. II. Cubic phase stabilization of translucent yttria-zirconia at very low temperatures, (10) 532–37.
Mazières, C. See Bigaré, M.
Mehta, J. M., Riewald, P. G., and Van Vlack, L. H. The system MnSe-MnS, (3) 164.
Mehta, P. K. Expansion characteristics of calcium sulfoaluminate hydrates, (4) 204–208.
Messier, D. R. Vapor pressure of Gd_2O_3 from 2350° to 2590°K, (12) 665–68.
Milberg, M. E. See Otto, K.
Miller, G. R. See Johnson, H. B.
Miller, J. L., Jr., McCormick, G. R., and Ampian, S. G. Phase equilibria in the system GeO_2-Al_2O_3, (5) 268–69.
Moak, D. P. See Koester, R. D.
Moratis, C. J. See Tien, T. Y.
Morgan, C. S., and Hall, L. L. Effect of isostatic pressure on sintering, (7) 382–83.
Mori, T. See Tagai, Hideo.
Moscker, E. See Borbas, J. J.
Muan, Arnulf. See Biggers, J. V.; Dayal, R. R.; Jones, T. S.
Munson, R. A. High-temperature behavior of beryl and beryl melts at high pressure, (12) 669–70.
Myers, M. B. See Felty, E. J.

Naito, Keiji. See Imai, Hisashi.
Navrotsky, A., and Kleppa, O. J. Enthalpy of the anatase-rutile transformation, (11) 626.
Newkirk, H. W. See Cline, C. F.
Newnham, R. E. Crystal structure of $ZrTiO_4$, (4) 216.
Nordberg, M. E. See Elmer, T. H.
Nordine, P. C. See Hoenig, C. L.
Northover, W. R. See Pearson, A. D.
Northrop, D. A. Vaporization of lead zirconate-lead titanate materials, (9) 441–45.
Novák, J. See Arend, H.

Oel, H. J., and Fréchette, V. D. Stress distribution in multiphase systems: I, Composites with planar interfaces, (10) 542–49.
Olson, N. E. See Benecke, M. W.
Ormsby, W. C., and Marcus, J. H. Flow properties of aqueous suspensions containing kaolins of varying degrees of crystallinity, (4) 190–95.
Osmer, J. A. See Chase, A. B.
Otto, K., and Milberg, M. E. Ionic conduction and structure in cesium and thallium silicate glasses, (10) 513–16.

Packard, R. Q. Moisture stress in unfired ceramic clay bodies, (5) 223–29.
Padfield, R. C. See Borbas, J. J.
Pask, J. A. See Benecke, M. W.; Borom, M. P.
Payne, D. A., and Anderson, H. U. Inhibition of grain growth in barium titanate, (9) 491.
Pearson, A. D., Fisher, J. R., and Northover, W. R. Preparation of optical quality glass in small batches, (4) 219–20.
Perrotta, A. J., and Savage, R. O. Beta eucryptite crystalline solutions involving P^{5+}, (2) 112.
Phillips, Bert. See Chang, L. L. Y.
Pierce, G. R. See Seward, T. P. III.
Poulsen, R. G. See Westwood, W. D.
Provance, J. D., and Wood, D. C. Molybdenum phosphate glasses containing Ag_2O or K_2O, (10) 516–20.
Pultz, W. W. Oxidation of submicroscopic fibrous silicon carbide, (8) 419–20; see also Hertl, W.
Pultz, W. W., and Hertl, W. Oxidation kinetics of particulate silicon monoxide, (4) 202–203.

Rasul, C. G. See Cable, Michael.
Redman, M. J., and Chen, J. H. Zinc tellurite glasses, (10) 523–25.
Regourd, M. See Bigaré, M.
Reid, A. F. Calcium ytterbate, $CaYb_2O_4$, an orthorhombic calcium ferrite isomorph, (9) 491–92.
Rhodes, W. H. See Sellers, D. J.
Riebling, E. F. Volume relations in Na_2O-B_2O_3 and Na_2O-SiO_2-B_2O_3 melts at 1300°C, (1) 46–53.
Riebling, E. F., Blaszyk, P. E., and Smith, D. W. Structure of glasses and melts in the Na_2O-GeO_2-B_2O_3 system, (12) 641–47.
Riewald, P. G. See Mehta, J. M.
Rindone, G. E. See Graham, P. W. L.; Stewart, D. R.
Rittler, H. L. See Beall, G. H.
Robbins, Murray. See Arlett, R. H.
Rossi, R. C. See Janowski, K. R.
Rothermel, D. L. Effect of stress on durability of ion-exchanged surfaces, (11) 574–77.
Rotsey, W. B. See Turner, D. N.
Rowcliffe, D. J. See Kelly, A.
Roy, Rustum. See Barry, T. L.; Datta, R. K.; Sarjeant, P. T.
Roy, S. K., and Coble, R. L. Solubility of hydrogen in porous polycrystalline aluminum oxide, (8) 435–36.
Rudy, Erwin, and Brukl, C. E. Lower-temperature modifications of Nb_2C and V_2C, (5) 265–68.
Rudy, Erwin, and Windisch, St. Evidence for zeta Fe_2N-type sublattice order in W_2C at intermediate temperatures, (5) 272–73.
Ruh, Edwin. See Wallace, R. W.
Ruh, Robert, and Garrett, H. J. Nonstoichiometry of ZrO_2 and its relation to tetragonal-cubic inversion in ZrO_2, (5) 257–61.
Russell, Ralston, Jr. See Graham, H. C.

Sadler, A. G. See Westwood, W. D.
Salt, D. J., and Hornung, G. Synthesis and X-ray study of hafnium silicate, (10) 549–50.
Sanvordenker, V. C. Optical and microstructural variations with electric field in barium-strontium titanate ceramics, (5) 261–65.
Sarjeant, P. T., and Roy, Rustum. New glassy and polymorphic oxide phases using rapid quenching techniques, (10) 500–503.
Savage, R. O. See Perrotta, A. J.
Schieltz, J. D., and Wilder, D. R. Anomalous sintering behavior of Y_2O_3, (8) 439–40.
Scroger, M. G. See Chang, L. L. Y.
Searcy, A. W. See Hoenig, C. L.
Secrist, D. R. Compound formation in the systems lithium-carbon and lithium-boron, (10) 520–23.
Seider, R. See Warshaw, S. I.
Seifert, K. E. Electron microscopy of etched plagioclase feldspar, (12) 660–61.

Sellers, D. J., Heuer, A. H., Rhodes, W. H., and Vasilos, T. Alumina crystal growth by solid-state techniques, (4) 217–18.
Seward, T. P. III, and Uhlmann, D. R. Reply to "Discussion of 'Transmission electron microscopy of thin glass samples,'" (12) 687.
Seward, T. P. III, Uhlmann, D. R., Turnbull, David, and Pierce, G. R. Transmission electron microscopy of thin glass samples, (1) 25–29.
Shafrin, E. G., and Zisman, W. A. Effect of adsorbed water on the spreading of organic liquids on soda-lime glass, (9) 478–84.
Shannon, R. D. Topotaxy in decomposition of CrO_3, (1) 56–57.
Shaw, R. R., and Heasley, J. H. Superparamagnetic behavior of $MnFe_2O_4$ and α-Fe_2O_3 precipitated from silicate melts, (6) 297–302.
Shelby, J. E. See Steinkamp, W. E.
Slagle, O. D. Deformation mechanisms in polycrystalline graphite, (10) 495–500.
Smith, D. W. See Riebling, E. F.
Smith, J. S. II. See Mazdiyasni, K. S.
Smith, P. D. See Turner, D. N.
Smothers, W. J. See Kreglo, J. R., Jr.
Snape, E., and Beeley, P. R. Refractory-melt reactions in vacuum induction melting of nickel-base alloys, (7) 349–58.
Soga, Naohiro, and Anderson, O. L. High-temperature elasticity and expansivity of forsterite and steatite, (5) 239–42.
Speidel, D. H. Phase equilibria in the system MgO-FeO-Fe_2O_3: The 1300°C isothermal section and extrapolations to other temperatures, (5) 243–48.
Stahl, D. See Taylor, K. M.
Standage, A. E., and Gani, M. S. Reaction between vitreous silica and molten aluminum, (2) 101–105.
Steinkamp, W. E., Shelby, J. E., and Day, D. E. Internal friction of mixed-alkali silicate glasses, (5) 271.
Stett, M. A., and Fulrath, R. M. Chemical reaction in a hot-pressed Al_2O_3-glass composite, (12) 673–76.
Stewart, D. R., Rindone, G. E., and Dachille, Frank. Heats of solution, density, and refractive index changes in sodium borate glasses subjected to high pressure, (9) 467–72.
Stewart, R. W., and Cutler, I. B. Effect of temperature and oxygen partial pressure on the oxidation of titanium carbide, (4) 176–81.
Stokes, R. J. See Day, R. B.
Stout, N. D. See Hoenig, C. L.
Strasser, A. See Taylor, K. M.
Stuart, W. I. See Adams, R. B.
Stubican, V. S. See Barry, T. L.

Tabor, D. See Atkins, A. G.
Tagai, Hideo. See Zisner, Tuvia.
Tagai, Hideo, Zisner, Tuvia, Mori, T., and Yasuda, E. Preferred orientation in hot-pressed magnesia, (10) 550–51.
Tallan, N. M. See Graham, H. C.; Wimmer, J. M.
Tallan, N. M., Tripp, W. C., and Vest, R. W. Electrical properties and defect structure of HfO_2, (6) 279–83.
Taylor, K. M., Andersen, J. C., Strasser, A., Stahl, D., and Forbes, R. L. Monoxide-type compounds of uranium and plutonium: I, Oxycarbides, (6) 321–25.
Tennery, V. J. See Harris, N. H.; Weirauch, D. F.
Tensmeyer, L. G. See Fritsche, B. T.
Tien, T. Y. See Bratton, R. J.
Tien, T. Y., and Moratis, C. J. Dielectric properties of strontium titanate solid solutions containing niobia, (8) 392–94.
Tobin, J. M. See Brizes, W. F.
Tripp, W. C. See Tallan, N. M.
Turnbull, David. See Seward, T. P. III.
Turner, D. N., Smith, P. D., and Rotsey, W. B. Hertzian stress cracks in beryllia and glass, (11) 594–98.

Uhlmann, D. R. See Seward, T. P. III; Vergano, P. J.

Vandervoort, R. R. See Barmore, W. L.; Cline, C. F.
Van Vlack, L. H. See Madden, G. I.; Mehta, J. M.
Vasilos, T. See Sellers, D. J.
Vergano, P. J., Hill, D. C., and Uhlmann, D. R. Thermal expansion of feldspar glasses, (1) 59–60.
Vest, R. W. See Tallan, N. M.
Voss, R. O. See Karstetter, B. R.
Vratny, F. Tantalum oxide films prepared by oxygen plasma anodization and reactive sputtering, (6) 283–87.

Wahman, L. A. See Fries, R. J.
Walker, R. E. See Kirchner, H. P.
Wallace, R. W., and Ruh, Edwin. Electrical resistivity of refractories, (7) 358–64.
Wanklyn, B. M. See Garton, G.
Warshaw, S. I., and Seider, R. Comparison of strength of triaxial porcelains containing alumina and silica, (7) 337–43.
Webster, A. H., Weston, T. B., and Bright, N. F. H. Effect of PbO deficiency on the piezoelectric properties of lead zirconate-titanate ceramics, (9) 490–91.
Weirauch, D. F., and Tennery, V. J. Electrical, X-ray, and thermal expansion studies in the system $KNbO_3$-$AgNbO_3$, (12) 671–73.
West, R. G., and Blankenship, A. C. Magnetic properties of dense lithium ferrites, (7) 343–49.
Weston, T. B. See Webster, A. H.
Westwood, W. D., Eastwood, H. K., Poulsen, R. G., and Sadler, A. G. Single-crystal ferrite films prepared by cathodic sputtering, (3) 119–23.
Whittemore, O. J., Jr. See Leiser, D. B.
Wiederhorn, S. M. Influence of water vapor on crack propagation in soda-lime glass, (8) 407–14.
Wilcox, W. R. See Chase, A. B.
Wilder, D. R. See Carrell, M. A.; Marlowe, M. O.; Schieltz, J. D.; Wirkus, C. D.
Williams, E. L., Jr., and Wilson, H. H. Low-temperature cementation effects in nickelous nitrate-water-magnesium oxide system, (11) 629–30.
Williams, J. P. See Finlayson, K. M.
Wilms, G. R. Influence of ceramic environment on mechanical properties of metals, (11) 625.
Wilson, H. H. See Williams, E. L., Jr.
Wimmer, J. M., Bidwell, L. R., and Tallan, N. M. Electrical properties and defect structure of a $(0.13YO_{1.5}$-$0.87ThO_2)$ electrolyte, (4) 198–201.
Windisch, St. See Rudy, Erwin.
Wirkus, C. D., Berard, M. F., and Wilder, D. R. Self-diffusion of oxygen in Y_2O_3 and Er_2O_3, (2) 113.
Wittke, J. P. Solubility of iron in TiO_2 (rutile), (11) 586–88.
Woermann, E. See Bigaré, M.
Wood, D. C. See Provance, J. D.
Wyllie, P. J. Phase equilibria in system CaO-CO_2-H_2O and related systems, with implications for crystal growth of calcite and apatite, (1) 43–46.

Yannaquis, N. See Bigaré, M.
Yasuda, E. See Tagai, Hideo.

Zisman, W. A. See Shafrin, E. G.
Zisner, Tuvia. Reactive hot-pressing of magnesium hydroxide, (10) 552; see also Tagai, Hideo.
Zisner, Tuvia, and Tagai, Hideo. Comment on note "Functional relation between creep rate and porosity for polycrystalline ceramics," (9) 489.

SUBJECT INDEX TO THE JOURNAL

Volume 50, 1967

The number in parentheses refers to the *monthly* issue of *The Journal;* the number following is the *page* number.

Absorption, bands, γ-induced, associated with Tl^+, Pb^{2+}, or Bi^{3+} in potassium borate glasses, (10) 503.
frequencies, SiO_4, correlation in $3CaO \cdot Al_2O_3$, (2) 99.
γ-radiation, in determination of refractory density, (8) 421.
optical, γ-induced, in barium silicate glasses, effect of BaO on, (6) 302.
Aggregates, MgO, hot-pressing of, (12) 688.
Alkalis, attack, of glass surfaces by molten salts, (2) 108; extraction, in long-time water-leaching runs on $15K_2O \cdot 85SiO_2$ glass, (1) 5; ions, effect of two types on glass properties, (5) 271.
Alloys, Ni-base, refractory-melt reactions in vacuum induction melting of, (7) 349.
Alumina. See Aluminum, oxide.
Aluminum, effect on self-diffusion of Be in BeO, (8) 425.
ions, coordination in tricalcium aluminate, (2) 97.
molten, reaction with vitreous silica, (2) 101.
oxide. See also *Phase diagrams; Systems.*
Cr_2O_3 solid solution hardening of, (1) 54.
crystals, Cr-doped, flux growth with localized cooling, (6) 327.
effect on internal fractures in porcelain, (7) 337.
effect on liquidus in system La_2O_3-Al_2O_3, (3) 167.
-glass composite, hot-pressed, chemical reaction in, (12) 673.
-glass compositions, elastic moduli as function of density of, (1) 20.
hot hardness to 1900°C, (6) 290.
leached, chemically strengthened, (4) 169.
polycrystalline, effect of MgO and $MgTiO_3$ doping on diffusion-controlled creep of, (4) 218.
Aluminum, oxide (*continued*)
polycrystalline, relation between creep rate and porosity in, (9) 489.
powder, determination of sintering progress by resonant frequency parameter, (3) 148.
single crystal, growth by solid-state techniques, (4) 217.
sintered, direct observation of nonbasal dislocations in, (9) 472.
sintering parameters for, (10) 511.
in solid solution with Ca_3SiO_5, (11) 616.
solubility of H_2 in, (8) 436.
spheres, as dispersions in two-phase composite, (8) 399.
thermoluminescence of, (10) 540.
vapor-deposited, transitions in, (11) 568.
Analysis, glow-curve, of thermoluminescence of Al_2O_3, (10) 540; metallographic and high-temperature X-ray, of system Zr-O, (5) 258; see also *Thermal analysis; X rays.*
Anatase, concentration, in TiO_2 fired enamels, (3) 154; high-temperature formation, (9) 493; -rutile transformation, enthalpy of, (11) 626.
Anodization, glow discharge, for forming Ta oxide thin films, (6) 283.
Antimony, effect on reaction between vitreous SiO_2 and molten Al, (2) 103.
Apatite, crystal growth conditions, (1) 43.
Arsenates, rare earth, crystal growth of, (8) 433.
Atmosphere, effect on compound formation in system UN-UP, (2) 74; wet, effect on bubble formation in silicate melts, (10) 528.

Barium. See also *Systems.*
$BaFe_{12}O_{19}$-$BaFe_2O_4$ eutectic, unidirectional solidification of, (6) 333.
carbonate, kinetics and mechanism of reaction with ZnO, (9) 484.
Barium (*continued*)
-Sr titanate ceramics, optical and microstructural variations with electric field, (5) 261.
titanate, crystals, chemical processes during H_2 reduction, (1) 22.
titanate, inhibition of grain growth in, (9) 491.
Bentonites, -lime reaction products, X-ray studies, (6) 312.
Beryl, and beryl melts, high-temperature behavior at high pressure, (12) 669.
Beryllia. See *Beryllium, oxide.*
Beryllium. See also *Phase diagrams; Systems.*
Hertzian stress cracks in, (11) 594.
nitride, decomposition reaction, characteristics of, (9) 460.
oxide, ionic conductivity in, (1) 55.
polycrystalline, creep-electrical conductivity correlations in, (4) 221.
polycrystalline, high-temperature creep and dislocation etch pits in, (6) 316.
Birefringence. See *Refraction.*
Bismuth, Bi^{3+}, in potassium borate glasses, γ-induced absorption bands from, (10) 503; effect on reaction between vitreous SiO_2 and molten Al, (2) 103; ferrate, single-phase polycrystalline, preparation of, (8) 437.
Bleaching, thermal, of induced absorption in borate glasses, (10) 507.
Borides, hot hardness, to 1900°C, (6) 290.
Born model, calculation, of enthalpies of solution in CaF_2, (12) 648.
Boron, oxide, and TiO_2, anatase formed from at high temperature, (9) 493; solid solution in graphite, (3) 142; see also *Phase diagrams; Systems.*
Brittle materials, thermal stress fracture, effect of stress relaxation by creep, (9) 454.
Brucite, thermal decomposition, II, (1) 8.

Bubbles, formation in silicate melts at high temperatures, II, (10) 528.

Calcite, crystal growth conditions, (1) 43.
Calcium. See also *Phase diagrams; Systems.*
distribution in MgO, (11) 628.
fluoride, Born model calculation of enthalpies of solution in, (12) 648.
fluoride, doped with oxygen ions, dielectric loss in, (10) 526.
oxide, crystalline solutions, precipitation of Yb_2O_3 from, (2) 105.
sulfoaluminate hydrates, expansion characteristics, (4) 204; discussion of, (12) 687.
tricalcium aluminate, coordination of Al ions in, (2) 97.
tricalcium and dicalcium silicate phases in portland cement clinker, (12) 677.
tricalcium silicate, and its solid solutions, polymorphism of, (11) 609.
ytterbate, an orthorhombic calcium ferrite isomorph, (9) 491.
Capacitors, Ta oxide thin film, for circuit applications, (6) 283.
Carbides, hot hardness, to 1900°C, (6) 290; transition metal, polycrystalline, deformation of, (5) 253.
Carbon, effect on metal-refractory reactions, (7) 349; oxidizable, influence on remanent induction, (3) 126; for stabilizing monoxide structure in U and Pu oxycarbides, (6) 321; see also *Graphite; Phase diagrams; Systems.*
Cations, distribution in different coordinations in spinel structure, (11) 578.
Cement, portland, clinker, high-temperature microscopic study of tricalcium and dicalcium silicate phases in, (12) 677; portland, hydration by tobermorite, (6) 312.
Cementation, low-temperature effects, in nickelous nitrate-water-MgO system, (11) 629.
Cerium, dioxide, nonstoichiometric, defect structure model for, (12) 681; effect on absorption bands in borate glasses, (10) 505.
Chromium. See also *Phase diagrams; Systems.*
alloys, effect of ceramic heating element on tensile creep, (11) 625.
content, and depth of penetration in spinel, effect of leaching time, (4) 170.
dioxide, topotaxy in decomposition of, (1) 56.
oxide, solid solution hardening of Al_2O_3, (1) 54.
Clays, bodies, unfired ceramic, moisture stress in, (5) 223.
Coatings, Al_2O_3-Cr_2O_3 solid solution, on 99+% Al_2O_3, flexural strength, (4) 172.
Cobalt, Co_2GeO_4, effect of temperature on cation distribution, (11) 583; ions, in sodium disilicate glass, effect on reactions at iron-glass interface, (2) 61; oxide, activities in (Mn,Co)O solid solutions, (5) 233; correction, (12) 689; see also *Phase diagrams; Systems.*
Composites, Al_2O_3-glass, hot-pressed, chemical reaction in, (12) 673.
MgO-pore and MgO-nickel-pore, Young's and shear moduli of, (11) 599.
with planar interfaces, (10) 542.
two-phase brittle-matrix, micromechanical stress concentrations in, (8) 399.
Conductivity, electrical, of HfO_2, as function of p_{O_2}, (6) 280.
in Mo phosphate glasses containing Ag_2O or K_2O, (10) 516.
in polycrystalline BeO, relation to creep, (4) 221.
of NaCl, particle size dependence, (3) 156.
of ThO_2 containing $YO_{1.5}$, (4) 199.
of UO_2, (12) 652.
Conductivity, ionic, in BeO, (1) 55; in Cs and Tl silicate glasses, relation to structure, (10) 513.
Cooling, localized, in flux crystal growth, (6) 325.
Copper, behavior of PbO-bearing enamels on, (2) 85; see also *Systems.*
Cracks, Griffith, effect of relative size on strength of porous glass, (11) 558; Hertzian stress, in BeO and glass, (11) 594; propagation, in soda-lime glass, effect of water vapor, (8) 407.
Creep, diffusion-controlled, of polycrystalline Al_2O_3, effect of MgO and $MgTiO_3$ doping on, (4) 218.
effect on indentation hardness of MgO, (4) 197.
high-temperature, in polycrystalline BeO, (6) 316.
in MgO, grain shape change during, (11) 584.
in MgO brick, mechanism of, (9) 457.
of polycrystalline BeO, rate-controlling mechanism in, (4) 221.
rate, in polycrystalline ceramics, relation to porosity, comment on note, (9) 489.
relaxation of stress by, effect on thermal stress fracture of brittle materials, (9) 454.
tensile, in Cr alloys, effect of ceramic furnace core on, (11) 625.
Cristobalite, air oxidation of particulate SiO to, (4) 202; precipitation from binary silicate liquids, (8) 414.
Cryolite, growth of large sapphire crystals from, (1) 58.
Cryolithionite, phase, relation of unit cell size to composition, (8) 397.
Crystal chemistry, of nepheline, (2) 67.
Crystallites, size, measurements on thoria gel, (11) 619.
Crystallization, of amorphous alumina, transition path, (11) 571.
controlled, of glass, for making fine-grained ceramics, (2) 67.
of Li_2O-Al_2O_3-SiO_2 glasses containing TiO_2, direct observations, (2) 77.
of silica from beryl, (12) 669.
of $NaNbO_3$ from glasses in system Na_2O-Nb_2O_5-SiO_2, (7) 369.
of stuffed β-quartz glass-ceramics, (4) 181.
Crystals, α-Al_2O_3, sintered, nonbasal dislocations in, (9) 472.
Al_2TiO_5, formed by freezing Al_2O_3-TiO_2 liquid, (3) 150.
$BaTiO_3$, chemical processes during H_2 reduction, (1) 22.
brucite, effect of thickness on reaction rate, (1) 10.
CaF_2, lattice energies to introduce impurities and point defects, (12) 650.
defect structure model, for nonstoichiometric CeO_2, (12) 681.
growth, at bubble surfaces in glass, (2) 116.
contamination-nucleated, at bubble surfaces in glass, (12) 683.
flux technique, relation of temperature fluctuations and striations, (6) 332.
from PbO-PbF_2 flux systems with temperature gradient and localized cooling, (6) 325.
of rare-earth orthoarsenates, (8) 433.
of $Y_3Fe_5O_{12}$, Czochralski-molten salt solvent technique, (3) 165.
perfection, in kaolins, effect on flow properties of aqueous suspensions, (4) 190.
sapphire, growth from cryolite, (1) 58.
single, of magnesiowustite, oxidation of, II, (12) 662.
nearly stoichiometric, of UO_2, electrical conductivity of, (12) 652.
of plagioclase feldspar, electron microscopy of etched surfaces, (12) 660.

Decomposition, of $CaYb_2O_4$, kinetics of, (7) 375.
of CrO_2, topotaxy in, (1) 56.
thermal, of beryl, pressure dependence of, (12) 669.
thermal, of brucite in vacuum, kinetics of, (1) 8.
Defects, characterization in CaO: Yb_2O_3 crystalline solutions, (2) 105; radiation-induced, relation to structure of barium silicate glasses, (6) 302.
Deformation, mechanisms, in polycrystalline graphite, (10) 495; of polycrystalline transition metal carbides, (5) 253; properties, of a polycrystalline KCl-NaCl alloy, (2) 114.
Dehydration, of δ-Fe_2O_3 dried under reduced pressure, (3) 124.
Dendrites, iron content of, vs. distance from glass-iron interface, (2) 65.
Densification, mechanisms, for hot-pressed MgO, (7) 365.
Density, of Al_2O_3, variation with Cr_2O_3 content, (1) 54.
of BeO, hot-pressed, effect of adsorbed sulfate and fluoride on, (12) 685.
composition curves for defective crystalline solutions of Yb_2O_3 in CaO, (2) 106.
effect on elastic modulus of UO_2 at room temperature, (2) 94.
elastic moduli of Al_2O_3-MgO·Al_2O_3 compositions as function of, (1) 20.
equations, for Na_2O·B_2O_3 and Na_2O·SiO_2·B_2O_3 melts, (1) 47.
of forsterite and steatite, relation to elastic constants, (5) 241.
of refractories, determination from γ-radiation absorption, (8) 421.
of sodium borate glasses under high pressure, (9) 467.
of solid solutions of B in graphite, (3) 144.
Devitrification, of high-silica glasses, effect of nitriding on, (6) 275.
Dielectrics, constant, in system $BaTiO_3$-$KNbO_3$, temperature dependence, (2) 91.
loss, in CaF_2 doped with oxygen ions, (10) 526.
properties, of (Ba,Sr)TiO_3 ceramics, effect of phase changes, (5) 263.
properties, of $SrTiO_3$ solid solutions containing niobia, (8) 392.
study, of $PbTiO_3$-$BaZrO_3$ system, (8) 404.
Diffraction. See *Electron diffraction; X rays.*
Diffusion, boundary, role in creep in MgO, (11) 584.
bulk, as rate-controlling mechanism in lead zirconate titanate, (9) 441.
coefficients, calculation from creep deformation of polycrystalline Al_2O_3, (4) 218.
coefficients, determination from creep and electrical conductivity of polycrystalline BeO, (4) 222.
models, for rutile sintering process, (5) 236.
profiles, of glass-iron composite at 950°C in Al_2O_3 crucible, (2) 63.
self-, of Be in polycrystalline BeO, (8) 425.
self-, of O in Y_2O_3 and Er_2O_3, (2) 113.
in Ta sample reacted with C, (2) 115.
volume, of anion, as creep control process in BeO, (6) 316.
of Zr in Zr hydride, (3) 167.
Dilation, from dissolved point defects in CaF_2, (12) 651.
Dislocations, movement of, in BeO, at high temperatures, (6) 319.
Disproportionation, of solid SiO, (7) 378.
Ductility, of MgO whiskers, (11) 624.
Durability, of ion-exchanged surfaces, effect of stress, (11) 574.
Dysprosium, oxide, powder, determination of sintering progress by resonant frequency parameter, (3) 148; oxide, sintering parameters for, (10) 511.

Elasticity, and anelasticity, of stoichiometric uranium oxide at room temperature, (2) 93.
elastic behavior of MgO matrix composites, (11) 599.
high-temperature, of forsterite and steatite, (5) 239.
macroscopic, of multicomponent materials, relation to micromechanical stress, (6) 331.
Elasticity (*continued*)
modulus, of stabilized ZrO_2, (4) 220.
properties, of two-phase ceramic bodies, (1) 19.
Young's modulus, as function of porosity in sintering, (3) 146.
Electrical properties, of HfO_2, relation to defect structure, (6) 279.
of lithium ferrite, (7) 345.
of $(0.13YO_{1.5}$·$0.87ThO_2)$ electrolyte, (4) 198.
of zinc tellurite glasses, (10) 524.
Electrical resistivity. See *Resistivity, electrical.*
Electrolysis, of high-silica glass, effect of nitriding on, (6) 275.
Electrolytes, $(0.13YO_{1.5}$·$0.87ThO_2)$, electrical properties and defect structure, (4) 198.
Electron diffraction, patterns, of $NiFe_2O_4$ films removed from MgO substrates, (3) 121.
Enamels, lead oxide-bearing, reactions with metal, (2) 85; TiO_2-opacified cover coat, kinetics of opacification, (3) 152.
Energy, activation, for creep in BeO, (6) 318.
for creep mechanism in MgO single crystals, (4) 195.
diffusional, of SiO, (4) 202.
for HfO_2 hole mobility, (6) 281.
for shrinkage rate of rutile, (5) 238.
potential, in clay-water system, (5) 229.
Enthalpy, of activation, for TiC, (4) 178.
of anatase-rutile transformation, (11) 626.
of Be_3N_2 decomposition reaction, (9) 460.
of oxygen, in urania, effect of Y(III) and La(III), (11) 566.
of solution, in CaF_2, Born model calculation of, (12) 648.
Entropy, of oxygen, in urania, effect of Y(III) and La(III), (11) 566.
Equilibrium studies, in CaO-CO_2-H_2O and related systems, with implications for crystal growth of calcite and apatite, (1) 43.
of $(Mn,Co)SiO_3$ + SiO_2 + Co at 1250°C, (5) 234.
order-disorder, in spinel, (11) 578.
in system glass-water, (1) 1.
in system PbO-TiO_2-ZrO_2, (3) 129.
in system Sc_2O_3-B_2O_3, (1) 53.
Equipment, for splat quench technique, (10) 501; for thermal simulation of in-reactor microstructures in ThO_2-UO_2, (9) 449.
Erbium, oxide, powder, determination of sintering progress by resonant frequency parameter, (3) 148; oxide, self-diffusion of O_2 in, (2) 113; oxide, sintering parameters for, (10) 511.
Etch pits, dislocation, effect on deformation of polycrystalline BeO, (6) 316.
Ettringite, formation from monosulfate hydrate, effect on expansion of concretes, (4) 204.
Eucryptite, β-, as crystalline phase in Li_2O-Al_2O_3-SiO_2 glass containing TiO_2, (2) 77; β-, crystalline solutions involving P^{5+}, (2) 112.
Evaporation, coefficient, of Be_3N_2 decomposition reaction, (9) 460; coefficient, for Gd_2O_3, (12) 665.
Expansion, characteristics, of calcium sulfoaluminate hydrates, (4) 204; discussion of, (12) 687.
coefficients, molar volume, for sodium borate melts, (1) 49.
thermal, of As-Se glasses, (6) 335.
coefficient, of forsterite and steatite, (5) 239.
of cubic refractory compounds of thorium, (5) 248.
of feldspar glasses, (1) 59.
high-temperature, of group IV and V diborides, (2) 81.
of MgO·Al_2O_3-MgO·Cr_2O_3 solid solutions, (4) 169.
in system $KNbO_3$-$AgNbO_3$, (12) 671.
of TaC_x, effect of stoichiometry on, (9) 475.
of two-phase ceramic bodies, (1) 19.

Feldspar, plagioclase, etched, electron microscopy of, (12) 660.
Ferric, Ferrous, etc. See *Iron.*
Ferroelectric materials, alkali niobate ceramics, hot-pressed, properties of, (6) 329.
Fibrous materials, as reinforcement for refractory composite materials, (11) 630; SiC, oxidation rate of, (8) 420.
Films, alumina, deposition on glass, electron diffraction patterns of, (11) 571; single-crystal ferrite, prepared by cathodic sputtering, (3) 119; thin, of sintered α-Al_2O_3, low-angle boundaries in, (9) 474; see also *Coatings.*
Fining, of glass, for removal of bubbles, (4) 220.
Firing, behavior, of TiO_2-opacified cover coat enamel, model for predicting, (3) 155.
Flow, properties, of aqueous suspensions containing varying degrees of crystallinity, (4) 192.
Fluorides, adsorbed, effect on density of hot-pressed BeO, (12) 685.
Forsterite, high-temperature elasticity and expansivity of, (5) 239.
Fracture, techniques, for preparing thin glass samples for electron microscopy, (1) 25; of Ti-doped sapphire crystals, effect of aging, (3) 151.
Friction, internal, of mixed-alkali silicate glasses, (5) 271; peak caused by condensation of water on barium silicate glasses, (6) 336; of stoichiometric UO_2 at room temperature, (2) 95.
Fuels, irradiated, thermal simulation of microstructures in, (9) 449.
Furnaces, creep-test, with ceramic core, effect on creep in Cr alloys, (11) 625.

Gadolinium, and GdC_2, Knudsen cell studies of vaporization of, (8) 385; oxide, vapor pressure from 2350° to 2590°K, (1) 665.

Gallium, oxide, crystals, flux growth with localized cooling, (6) 327.
Garnets, $Y_3Ga_5O_{12}$, flux growth with localized cooling, (6) 327; yttrium-iron, single-crystal, grown by Czochralski-molten salt solvent technique, (3) 165; Y-Gd-Fe-Al-In, magnetic properties of, (4) 208.
Gases, gas phase anodization, in oxygen glow discharge plasma, (6) 285.
Germanium. See *Phase diagrams; Systems.*
Glass, alkali aluminosilicate, ion-exchanged, leachability as function of surface stress, (11) 574.
-alumina, hot-pressed composite, chemical reaction in, (12) 673.
alumina film deposition on, (11) 571.
As-Se, thermal expansion of, (6) 335.
barium silicate, effect of radiation-induced defects on structure, (6) 302.
barium silicate, internal friction peak caused by condensation of water on, (6) 336.
bubble surfaces in, crystal growth at, (2) 116; (12) 683.
cesium silicate, relation of ionic conduction and structure in, (10) 513.
composite pairs, stress distribution in, (10) 542.
composition, effect on laser-induced damage, (5) 270.
contamination, effect on crystal growth, (12) 683.
feldspar, thermal expansion, (1) 59.
former, melting point of, relation to temperature of monotectic, (1) 33.
Griffith flaws in, effect of relative size on strength of porous glass, (11) 558.
Hertzian stress cracks in, (11) 594.
high-silica, effect of nitriding on electrolysis and devitrification of, (6) 275.
laser-induced damage in, effect of glass composition, (5) 270.
Li_2O-Al_2O_3-SiO_2, containing TiO_2, direct observation of crystallization, (2) 77.
mixed alkali, effect of composition on foaming behavior, (10) 530.
mixed-alkali silicate, internal friction of, (5) 271.
optical, preparation in small batches in Pt crucibles, (4) 219.
porous, effect of micromechanical stress concentrations, (11) 558.
potassium borate, γ-induced absorption bands associated with Tl^+, Pb^{2+}, or Bi^{3+} in, (10) 503.
pure oxide, formation by rapid quenching techniques, (10) 500.
quenched, in system $KAlSiO_4$-Mg_2SiO_4-$KAlSi_2O_6$, isofracts of, (4) 174.
reactions, with aqueous solutions, (1) 1.
reconstructed, effect of nitriding on electrolysis and devitrification of, (6) 275.
samples, preparation for electron microscopy by mechanical thinning and fracturing, (1) 26.
soda borosilicate, as matrix in two-phase composite, (8) 399.
Na_2O·GeO_2·B_2O_3, structure of, (12) 641.
soda-iron-silica, in air, equilibrium Fe^{3+}/Fe^{2+} ratio, (6) 301.
soda-lime, effect of adsorbed water on spreading of organic liquids on, (9) 478.
soda-lime, effect of water vapor on crack propagation in, (8) 407.
in Na_2O-Nb_2O_5-SiO_2 system, nucleation and crystallization of $NaNbO_3$ from, (7) 369.
sodium borate, under high pressure, properties of, (9) 467.
sodium disilicate, metallic Fe and Co_3O_4-bearing, reactions between, (2) 61.
sodium disilicate, reaction with alumina to form nephelite, (12) 673.
spheres, in system As-S-Se, sintering study of, (11) 608.
surfaces, alkali attack by molten salts, (2) 108.
in systems MoO_3-P_2O_5-Ag_2O and MoO_3-P_2O_5-K_2O, areas of good glass formation in, (10) 516.
thallium silicate, relation of ionic conduction and structure in, (10) 513.
thickness, determination from density by electron microscopy, (12) 686.
thin samples, transmission electron microscopy of, (1) 25; discussion of, (12) 686; reply to discussion, (12) 687.
zinc tellurite, (10) 523.
zirconia-silica, effect of NaOH and $NaNO_3$ on durability, (2) 111.
Glass-ceramics, β-quartz stuffed, crystallization and chemical strengthening of, (4) 181.
fine-grained, development from crystallization of Li_2O-Al_2O_3-SiO_2 glasses containing TiO_2, (2) 77.
Li_2O-Al_2O_3-TiO_2-SiO_2, beta spodumene-silica solid solution in, (9) 488.
nepheline, crystallization and chemical strengthening, (2) 67.
in system Li_2O-Al_2O_3-SiO_2, chemical strengthening, (3) 133.
transparent, formation by heat treatment of glasses in Na_2O-Nb_2O_5-SiO_2 system, (7) 369.
Grain boundaries, segregation, in sintering of Y_2O_3, (11) 553.
Grain growth, inhibition in $BaTiO_3$, (9) 491.
Grain shape, change during creep in MgO, (11) 584.
Graphite, particles, on bubble surfaces in glass, as source of crystal nucleation, (12) 683.
polycrystalline, deformation mechanisms in, (10) 495.
in reaction with ThO_2 to form ThC_2, (6) 311.
solid solution of B in, (3) 142.

Hafnia. See *Hafnium, oxide.*
Hafnium. See also *Phase diagrams; Systems.*
borides and carbides, hot hardness to 1900°C, (6) 290.
Hafnium *(continued)*
diboride, high-temperature thermal expansion for, (2) 81.
dioxide, electrical properties and defect structure, (6) 279.
silicate, synthesis and X-ray study, (10) 549.
Hafnon, synthetic, X-ray diffraction data, (10) 550.
Hardness, bulk, as function of concentration of ThO_2 in Y_2O_3, (11) 555.
hot, of borides, oxides, and carbides to 1900°C, (6) 290.
micro-, of Al_2O_3 as function of Cr_2O_3 content, (1) 55.
mutual indentation, of single-crystal MgO at high temperatures, (4) 195.
of sapphire single crystals, effect of Ti additions, (3) 149.
Heat, of solution, of sodium borate glasses under high pressure, (9) 467; treatment, and Na^+-for-Li^+ exchange strengthening, (3) 135.
Humidity, relative, effect on spreading of liquids on glass, (9) 481.
Hydrates, Ca aluminate and Ca silicate, formation from lime-bentonite mixtures, (6) 314; Ca sulfoaluminate, expansion characteristics, discussion of, (12) 687.
Hydrogen, oxidizable, influence on coercivity, (3) 126; solubility in Al_2O_3, (8) 436; reduction, of $BaTiO_3$ crystals, effect of chemical processes, (1) 22.
Hydrogen ion concentration, effect on alkali and silica extraction from $15K_2O$·$85SiO_2$ glass, (1) 4.
Hydroxyls, groups, retention on MgO, (9) 493.

Immiscibility, in oxide systems, structural interpretation, (1) 29; in system Sc_2O_3-B_2O_3, (1) 54.
Impurities, distribution in MgO, (11) 628.
Indium, In_2O_3, crystals, effect of temperature fluctuations on striations in, (6) 333.
Instruments, for measuring hardness at high temperatures, (4) 196.
Ionic conductivity. See *Conductivity, ionic.*
Ions, exchange, in strengthening transparent and opaque stuffed β-quartz glass-ceramics, (4) 188; exchange, surface alkali, effect on glass strength, (11) 574; metal and oxygen, position in $ZrTiO_4$ crystal structure, (4) 216.
Iron. See also *Phase diagrams; Systems.*
oxidation at iron-sodium disilicate glass interface, (2) 61.
oxide, α-Fe_2O_3, superparamagnetic behavior when precipitated from silicate melts, (6) 297.
oxide, delta, effect of structural and chemical alterations on magnetic properties, (3) 124.
solubility in TiO_2, (11) 586.

Kaolins, crystallinity, effect on flow properties of aqueous suspensions containing, (4) 190.
Kinetics, decomposition, of brucite in vacuum, (1) 8.
decomposition, of $CaYb_2O_4$, (7) 375.
of opacification, in TiO_2 cover coat enamel, (3) 152.
oxidation, of particulate silicon monoxide, (4) 202.
oxidation, for single-crystal TiC, (4) 181.
of precipitation of Yb_2O_3 from CaO crystalline solutions, (2) 107.
reaction, for $BaCO_3$ and ZnO, (9) 484.
reaction, for vitreous SiO_2 and molten Al, (2) 102.
sintering, resonant frequency technique for study of, (3) 145.
sintering, study of using reduced variables, (10) 509.
of vaporization of PbO from lead zirconate-lead titanate materials, (9) 490.

Lanthanum, effect on properties of urania, (11) 563; see also *Phase diagrams; Systems.*
Lasers, damage to glass from, effect of glass composition, (5) 270.
Leaching, of Al_2O_3 and spinel, effect on strength, (4) 170; effect on heat-treated alkali borosilicate glass, (12) 686.
Lead. See also *Phase diagrams; Systems.*
oxide, deficiency, effect on piezoelectricity of Pb zirconate-titanate ceramics, (9) 490.
oxide, in enamels, effect on reactions with steel substrate, (2) 84.
in potassium borate glasses, γ-induced absorption bands from, (10) 503.
pyroarsenate, crystal growth, (8) 433.
zirconate-titanate, vaporization of, (9) 441.
Lime, -bentonite reaction products, X-ray studies, (6) 312; see also *Calcium, oxide; Systems.*
Limestone, pellets, relation of dry strength to pellet size, total deformation, and load at failure, (1) 15.
Liquids, organic, on soda-lime glass, effect of adsorbed water on spreading of, (9) 478.
Lithium. See also *Phase diagrams; Systems.*
ferrites, dense, magnetic properties of, (7) 343.
fluoride, effect on hot-pressing of MgO, (7) 365.
metatantalate, ferroelectric, Curie temperature and birefringence variation as function of melt stoichiometry, (12) 657.
phases, in systems Li-C and Li-B, (10) 522.
Luminescence, thermo-, of alumina, (10) 540.

Magnesia. See *Magnesium, oxide.*
Magnesiowustite, single crystals, oxidation of, II, (12) 662.
Magnesium. See also *Phase diagrams; Systems.*
content, and depth of penetration in spinel, effect of leaching time, (4) 171.
hydroxide, reactive hot-pressing of, (10) 552.
Magnesium *(continued)*
oxide, aggregates, hot-pressing of, (12) 688.
as base for producing thin films of $NiFe_2O_4$ by glow discharge sputtering system, (3) 120.
grain shape change during creep in, (11) 584.
hot-pressed, preferred orientation in, (10) 550.
hot-pressing of, effect of LiF on, (7) 365.
impurity distribution in, (11) 628.
and $MgTiO_3$, effect on diffusion-controlled creep of polycrystalline Al_2O_3, (4) 218.
matrix composites, elastic behavior of, (11) 599.
polycrystalline, relation between creep rate and porosity in, (9) 489.
retention of hydroxyl groups on, (9) 493.
single-crystal, mutual indentation hardness at high temperatures, (4) 195.
single crystals, softening at high temperature by NiO addition, (9) 445.
solubility in ZrO_2, (6) 288.
whiskers, ductile, (11) 624.
whiskers, growth by vapor-liquid-solid mechanism, (11) 627.
Magnetic materials, flow diagram for processing, (3) 125.
Magnetic properties, of dense lithium ferrites, (7) 343.
of δ-Fe_2O_3, structural and chemical alterations, (3) 124.
of $MnFe_2O_4$ and α-Fe_2O_3 precipitated from silicate melts, (6) 297.
of single-crystal nickel ferrite films, (3) 122.
of yttrium - gadolinium - iron - aluminum - indium garnets, (4) 208.
Magnetization, vs. temperature for YIG with substitutions of In and Al, (4) 210.
Manganese, ferrite, superparamagnetic behavior when precipitated from silicate melts, (6) 297; see also *Phase diagrams; Systems.*
Mechanical properties, of MgO single crystals, determination by mutual indentation hardness technique, (4) 195.
Melting, vacuum induction, of Ni-base alloys, refractory-melt reactions in, (7) 349.
Melts, Na_2O·B_2O_3 and Na_2O·SiO_2·B_2O_3, volume relations at 1300°C, (1) 46; Na_2O·GeO_2·B_2O_3, structure of, (12) 641.
Metals, effect of ceramic environment on mechanical properties, (11) 625; oxides, alkali, activities with silica, (12) 631.
Micrographs, electron, of nepheline glass-ceramics, (2) 70.
of PbO-bearing enamel-steel fired specimens, (2) 86.
of $PbTiO_3$ crystals grown on bubble surface in a PbO-B_2O_3-TiO_2 glass, (2) 117.
of single-crystal boule of stoichiometric $MgAl_2O_4$ grown by flame fusion with in situ annealing, (5) 274.
Microscopes, electron, in identification of interfacial compounds in PbO-bearing enamel-metal systems, (2) 85.
Microscopy, electron, of etched plagioclase feldspar, (12) 660; electron, transmission, of thin glass samples, (1) 25; discussion of, (12) 686; reply to discussion, (12) 687.
Mineralogical properties, of unfired ceramic bodies from New Zealand, (5) 225.
Molybdenum, trioxide, formation by rapid quenching techniques, (10) 500; see also *Systems.*
Mullite, stability, derived from equilibria in system CoO-Al_2O_3-SiO_2, (10) 537.

Nepheline, ceramics, producing by controlled crystallization of glass, (2) 68.
Nephelite, nucleation in alumina-glass composite, (12) 673.
Nickel. See also *Systems.*
effect on elastic properties of MgO-pore system, (11) 602.
ferrite, single-crystal, films prepared by cathodic sputtering, (3) 119.
$NiAl_2O_4$ and Ni_2GeO_4, effect of temperature on cation distribution, (11) 581.
nickelous nitrate, effect on cementation in MgO, (11) 629.
orthosilicate, cubic, synthesis of, (12) 684.
oxide, effect on softening of MgO single crystals at high temperature, (9) 445.
spheres, effect on strength of soda borosilicate glass, (8) 401.
Niobates, alkali, hot-pressed, ferroelectric behavior, (6) 329.
Niobium, diboride, high-temperature thermal expansion for, (2) 81.
carbide, hot hardness to 1900°C, (6) 290.
hot-pressed, plastic deformation in, (5) 253.
low-temperature modifications of, (5) 265.
oxide, in $SrTiO_3$ solid solutions, dielectric properties, (8) 392.
Nitriding, of high-silica glasses and fused quartz, effect of nitriding, (6) 275.
Nucleation, of Li_2O-Al_2O_3-SiO_2 glasses containing TiO_2, (2) 77; of $NaNbO_3$ from glasses in system Na_2O-Nb_2O_5-SiO_2, (7) 369.

Oils, content, effect on magnetic properties of δ-Fe_2O_3, (3) 127.
Opacification. See *Enamels.*
Optical properties, of ternary compounds in system MgO-GeO_2-LiF, (8) 438; of zinc tellurite glasses, (10) 525.
Orientation, preferred, in hot-pressed MgO, (10) 550.
Oxidation, of magnesiowustite single crystals, II, (12) 662; of submicroscopic fibrous SiC, (8) 419; of TiC, effect of temperature and O_2 partial pressure, (4) 176.

Oxides, hot hardness, to 1900°C, (6) 290; metal, in sodium disilicate solution, determination of concentrations by polarography, (1) 38; stoichiometric uranium, elasticity and anelasticity at room temperature, (2) 93.
Oxygen. See also *Phase diagrams; Systems.*
fugacity, composition of phases in system Mg-Fe-O as function of, (5) 243.
ions, in CaF_2, effect on dielectric loss, (10) 526.
ions, position in $ZrTiO_4$ crystal structure, (4) 216.
partial pressure, effect on defect structure of HfO_2, (6) 280.
partial pressure, effect on high-temperature mechanical properties of unstable oxides, (9) 448.
per cation ratios, and extent of immiscibility in oxide systems, (1) 30.
self-diffusion in Y_2O_3 and Er_2O_3, (2) 113.

Particle size, dependence, of electrical conductivity of NaCl, (3) 156; effect on control of viscous and plastic properties of kaolins, (4) 194; effect on superparamagnetic behavior of $MnFe_2O_4$ and α-Fe_2O_3, (6) 298.
Permittivity. See *Dielectrics, constant.*
Phase diagrams. See also *Systems.*
partial, for system Na_3AlF_6-$LiAlF_6$, (8) 397.
for system SrO-B_2O_3, (2) 118.
for system TiO_2-Fe at 1 atm O_2 pressure, (11) 587.
for system Zr-O, (5) 257.
for system ZrO_2-MgO, (6) 289.
for system, B-C, projected, (3) 143.
CaO-MgO-CO_2-H_2O, (1) 44.
$Ca_3(PO_4)_2$-$Ca(OH)_2$-CaF_2-H_2O and $Ca_3(PO_4)_2$-$Ca(OH)_2$-$CaCO_3$-H_2O, (1) 45.
GeO_2-Al_2O_3, (5) 269.
HfO_2-WO_3, ZrO_2-WO_3, and HfO_2-WO_3, (4) 213.
FeO-Fe_2O_3-SiO_2, projection of liquidus surface in, (3) 137.
FeO-Fe_2O_3-ZrO_2-SiO_2, (3) 141.
La_2O_3-Al_2O_3, alumina-rich, liquidus in, (3) 167.
PbO-ZrO_2, (3) 131.
$PbTiO_3$-$PbZrO_3$, (3) 132.
$LiAlGeO_4$-Zn_2GeO_4, (7) 384.
Li_2O-Al_2O_3-SiO_2-TiO_2, (3) 134.
Li_2O-SiO_2, Na_2O-SiO_2, and K_2O-SiO_2, calculation of activities in, (12) 631.
MgO-FeO-Fe_2O_3, (5) 245.
MnO-CoO-SiO_2, (5) 233.
$KAlSiO_4$-Mg_2SiO_4-SiO_2, (4) 174.
KCl-NaCl, (2) 114.
SiO_2-$LiAlO_2$-$MgAl_2O_4$, isothermal section, (4) 183.
Na_3AlF_6-Al_2O_3, (1) 58.
Ta-C, modification, (2) 116.
Y_2O_3-V_2O_5, (7) 381.
ZrO_2-SiO_2, (3) 138.
ZrO_2-W-WO_3, (4) 215.
ZrO_2-WO_2-WO_3, HfO_2-WO_2-WO_3, and ZrO_2-WO_2-WO_3, (4) 214.
ZrO_2-WO_3, (4) 212.
tentative, for system UN-UP, (2) 76.
Phosphorus, P^{5+}, in β-eucryptite crystalline solutions, (2) 112; see also *Systems.*
Piezoelectricity, of Pb zirconate-titanate ceramics, effect of PbO deficiency, (9) 490.
Pipe, sewer, bodies, moisture stress vs. moisture content, (5) 227.
Plasma, oxygen, anodization, in preparing Ta oxide films, (6) 283.
Platinum, crucible, effect on reactions at iron-glass interface, (2) 61.
Plutonium, oxycarbide, formation from PuO_2 and UO_2, (6) 321.
Polarization, blocking-electrode technique, for determining transference numbers in electrolyte, (4) 198.
Polarography, in molten sodium disilicate, (1) 38.
Polishing, of porous materials, (6) 328.
Polymorphism, of tricalcium silicate and its solid solutions, (11) 609.
Porcelain, triaxial, containing Al_2O_3 and SiO_2, (7) 337.
Pores, as phase in MgO matrix composites, (11) 600; size, effect on strength of porous glass, (11) 560.
Porosity, effect on elastic modulus of UO_2 at room temperature, (2) 94.
effect on self-diffusion of Be in polycrystalline BeO, (8) 425.
effect on sintering of powder of Y, Er, Dy, and Al oxides, (3) 148.
effect on strength of polycrystalline brittle ceramic materials, (8) 399.
of limestone pellets, relation to surface area of powder and compressive strength, (1) 15.
in polycrystalline ceramics, relation to creep rate, comment on note, (9) 489.
Porous materials, polishing of, (6) 328.
Potassium, exchange for Li for strengthening glass-ceramics, (3) 136; fluoride, fused, effect on $BaTiO_3$ crystals grown from, (1) 22; hydroxide, molten, reaction with glass surface, (2) 108; see also *Phase diagrams; Systems.*
Precipitation, of calcite, conditions for, (1) 45.
from CaO:Yb_2O_3 crystalline solutions, (2) 105.
of Co in $(Mn,Co)_2SiO_4$ + $(Mn,Co)SiO_3$ phase assemblage, (5) 233.
of Fe_2O_3, electron micrographs of, (3) 126.
of $MnFe_2O_4$ and α-Fe_2O_3 particles from silicate melts, (6) 298.
solid state, in system KCl-NaCl, (2) 114.
Pressing, hot, effect on chemical reaction in Al_2O_3-glass composite, (12) 673.
of MgO, effect of LiF on, (7) 365.
of MgO, effect on preferred orientation, (10) 550.
of MgO aggregates, (12) 688.
Pressing, hot *(continued)*
reactive, of Mg hydroxide, (10) 552.
variations in, effect on properties of lithium zinc ferrites, (7) 347.
Pressure, effect on high-temperature behavior of beryl and beryl melts, (12) 669.
effect on properties of sodium borate glasses, (9) 467.
isostatic, effect on sintering, (7) 382.
oxygen, equilibrium, over solid solutions of urania-yttria and urania-lanthana, (11) 563.
oxygen partial, effect on oxidation of TiC, (4) 176.
vapor, of Gd_2O_3 from 2350° to 2590°K, (12) 665.

Quartz, β-, solid solutions formed in Li_2O-Al_2O_3-SiO_2-TiO_2 system, (3) 134.
fused, effect of nitriding on electrolysis and devitrification of, (6) 275.
grain size, effect on types of fractures in whiteware body, (7) 337.
β-, stuffed, glass-ceramics, crystallization and chemical strengthening, (4) 181.
transformation to tridymite in presence of binary silicate liquids, (8) 414.
Quenching, splat, in formation of glassy and polymorphic oxide phases, (10) 500.

Radiation, -induced defects, relation to structure of barium silicate glasses, (6) 302.
Reflectance. See *Reflection.*
Reflection, as function of firing conditions, for TiO_2-opacified cover coat enamel, (3) 155.
Refraction, birefringence, of alite and belite in cement clinker, as function of temperature, (12) 677; birefringence, variation in ferroelectric $LiTaO_3$ as function of melt stoichiometry, (12) 657; molar, of Al_2O_3 in CaO-Al_2O_3 compounds, (2) 100.
Refractive index, of sodium borate glasses under high pressure, (9) 467.
Refractivity. See *Refraction.*
Refractories, alumina, high-, electrical resistivity of, (7) 358.
brick, radiation measurement in, (8) 422.
density, determination from γ-radiation absorption, (8) 421.
electrical resistivity of, (7) 359.
magnesia, and magnesia-chrome, electrical resistivity of, (7) 358.
MgO brick, mechanism of creep in, (9) 457.
multicomponent, relation between macroscopic shear moduli and micromechanical shear stress, (6) 331.
periclase, creep mechanism in, (9) 457.
reactions with melt in vacuum induction melting of Ni-base alloys, (7) 349.
Th compounds, comparison of properties, (5) 251.
zircon and stabilized-zirconia, electrical resistivity of, (7) 358.
Zyttrite as, (10) 536.
Resistivity, electrical, of nitrided SiO_2 glass and fused quartz, effect of nitriding temperature, (6) 278; of refractories, (7) 359.
Ruby, Czochralski, X-ray topography of, (11) 588.
Rutile. See also *Titanium, dioxide.*
concentration, in fired TiO_2 enamels, (3) 154.
films, porous, production from oxidation of single-crystal TiC, (4) 180.
initial sintering of, (5) 235.
solubility of iron in, (11) 586.

Salts, molten, as solvent, in growing crystals by Czochralski technique, (3) 165.
Sapphire, alumina film deposition on, (11) 571; crystals, large, growth from cryolite, (1) 58; strengthening by precipitates containing Ti, (3) 149.
Saturation induction, of polycrystalline garnet materials, (4) 208.
Scandium. See *Systems.*
Segregation, grain-boundary, in sintering of Y_2O_3, (11) 553.
Shear modulus, change with temperature for forsterite and steatite, (5) 240; macroscopic, relation to micromechanical shear stress concentrations of multicomponent materials, (6) 331.
Shrinkage, vs. time, for sintering of rutile, (5) 237.
Silicates, liquids, binary, effect on transformation of quartz to tridymite, (8) 414; melts, at high temperatures, spontaneous bubble formation in, II, (10) 528.
Silicon, carbide, submicroscopic fibrous, oxidation of, (8) 419.
dioxide. See also *Phase diagrams; Systems.*
and alkali metal oxides, activities of, (12) 631.
content, effect on crystallization of glasses in system $NaNbO_3$-SiO_2, (7) 372.
effect on internal fractures in porcelain, (7) 337.
extraction from fused silica powder, effect of pH on rate, (1) 4.
β-spodumene, solid solution in Li_2O-Al_2O_3-TiO_2-SiO_2 glass-ceramic, (9) 488.
and TiO_2, anatase formed from at high temperature, (9) 493.
vitreous, reaction with molten Al, (2) 101.
effect on self-diffusion of Be in BeO, (8) 425.
monoxide, disproportionation and vaporization of, (7) 378.
monoxide, particulate, oxidation kinetics of, (4) 202.
Silver, Ag_2O, effect on resistivity of Mo phosphate glasses, (10) 516.
Sintering, behavior, of Y_2O_3, (8) 439.
effect of isostatic pressure on, (7) 382.
final-stage, of Y_2O_3, grain-boundary segregation in, (11) 553.
Sintering *(continued)*
initial, of rutile, (5) 235.
kinetics, resonant frequency technique for study of, (3) 145.
progress, system for describing using reduced variables, (10) 509.
in system As-S-Se, (11) 604.
of thoria gel, effect of crystallite size on, (11) 619.
Sodium. See also *Phase diagrams; Systems.*
borate melts, density and volume relations, (1) 46.
chloride, particle size dependence of electrical conductivity of, (3) 156.
disilicate, molten, polarography in, (1) 38.
exchange for Li for strengthening glass-ceramics, (3) 134.
fluoride, lattice energy needed to dissolve in CaF_2, (12) 648.
hydroxide, molten, reaction with glass surface, (2) 108.
Solidification, unidirectional, of $BaFe_{12}O_{19}$-$BaFe_2O_4$ eutectic, (6) 333.
Solid solutions. See *Solutions, solid.*
Solid state, techniques, in growing alumina crystals, (4) 217.
Solubility, of boron in graphite, effect of hold time, (3) 143.
of H_2 in porous polycrystalline Al_2O_3, (8) 436.
of iron in TiO_2, (11) 586.
of Zr in ZrO_2 from 1200° to 2000°C, (5) 257.
Solutions, of alkali metal oxides and silica, activities in, (12) 631; aqueous, reactions of glasses with, (1) 1; crystalline, of P^{5+} in $LiAlSiO_4$, (2) 112.
Solutions, solid, of B in graphite, (3) 142.
dense, fine-grained, variation of microhardness of Al_2O_3 with increasing Cr_2O_3 in, (1) 54.
formation in system $BaTiO_3$-$KNbO_3$, (2) 90.
MgO-Al_2O_3-MgO-Cr_2O_3, thermal expansion coefficient of, (4) 169.
Mn(Se,S), lattice parameters of, (3) 164.
ortho- and metasilicate, activity-composition relations in system MnO-CoO-SiO_2, (5) 230; correction, (12) 689.
perovskite-type, structural data and melting points, (3) 130.
of β-quartz, (4) 183.
of β-quartz and β-spodumene, formed in Li_2O-Al_2O_3-SiO_2-TiO_2 system, (3) 134.
of $AgNbO_3$ in $KNbO_3$, (12) 671.
of ThO_2-Y_2O_3, as mixed conductors at high O_2 pressures, (4) 199.
of tricalcium silicate, polymorphism of, (11) 609.
of urania-yttria and urania-lanthana, equilibrium oxygen pressures over, (11) 563.
Specific gravity. See *Density.*
Spectra, infrared absorption, of $3CaO$-Al_2O_3, (2) 98.
Spheres, pelletized, dry strength of, (1) 14; stress distribution at points of contact, in BeO and glass, (11) 594; in study of relation of surface area to sintering rate, (11) 604.
Spinels, chemically strengthened, (4) 169.
equilibrium order-disorder in, (11) 578.
$MgAl_2O_4$, stoichiometric single crystals, growth of, (5) 273.
primary phase volume in system K_2O-MgO-Al_2O_3-SiO_2, (4) 174.
$ZnAl_2O_4$-$ZnGa_2O_4$, flux growth with localized cooling, (6) 327.
Spodumene, β-, as crystalline phase in Li_2O-Al_2O_3-SiO_2 glass containing TiO_2, (2) 77; β-, -silica solid solution in Li_2O-Al_2O_3-TiO_2-SiO_2 glass-ceramic, (9) 488; β-, solid solutions formed in LiO_2-Al_2O_3-SiO_2-TiO_2 system, (3) 134.
Spreading, of organic liquids on soda-lime glass, effect of adsorbed water, (9) 478.
Sputtering, reactive, for forming Ta oxide thin films, (6) 283.
Stabilization, cubic phase, of translucent yttria-zirconia at very low temperatures, (10) 532; of ZrO_2 with Y_2O_3 and CaO, (4) 221.
Stability, of mullite, derived from equilibria in system CoO-Al_2O_3-SiO_2, (10) 537.
Steatite, high-temperature elasticity and expansivity of, (5) 239.
Steel, reactions with PbO-bearing enamels, (2) 85.
Stoichiometry, effect on thermal expansion of TaC_x, (9) 475; in $MgAl_2O_4$ single crystals grown by flame fusion, (5) 273; of melt, effect on ferroelectric Curie temperature and birefringence of $LiTaO_3$, (12) 659.
Strain, in MgO, from grain boundary sliding, (11) 584.
Strength, dry, of pelletized spheres, (1) 14.
flexural, of 99+% Al_2O_3 with Al_2O_3-Cr_2O_3 solid solution coatings, (4) 172.
of porous glass, effect of micromechanical stress concentrations, (11) 558.
of triaxial porcelains containing Al_2O_3 and SiO_2, (7) 337.
yield, of MgO at high temperatures, determination from hardness measurements, (4) 195.
Strengthening, chemical, of alumina and spinel, (4) 169.
of glass, by molten salt baths, (2) 109.
of nepheline glass-ceramics, (2) 67.
of stuffed β-quartz glass-ceramics, (4) 181.
of glass-ceramics, by Na^+-for-Li^+ exchange, (3) 134.
of sapphire, by precipitates containing Ti, (3) 149.
Stress, in BeO, effect on creep rate, (6) 318.
concentrations, micromechanical, in two-phase brittle-matrix composites, (8) 399.
distribution in multiphase systems, I, (10) 542.
effect on durability of ion-exchanged surfaces, (11) 574.
micromechanical, effect of concentrations on strength of porous glass, (11) 558.
moisture, in unfired ceramic clay bodies, (5) 223.
relaxation by creep, effect on thermal stress fracture of brittle ceramics, (9) 454.

Stress (*continued*)
release, in chemical strengthening of nepheline glass-ceramics by $K^+ \rightarrow Na^+$ exchange, (2) 72.
-strain diagrams of KCl-NaCl alloy at different temperatures, (2) 114.
tensile and compressive, effect on microstructure of graphite, (10) 495.
Strontium, $(Ba,Sr)TiO_3$ ceramics, optical and microstructural variations with electric field, (5) 261; titanate, solid solutions containing niobia, dielectric properties of, (8) 392; see also *Phase diagrams; Systems.*
Structure, of barium silicate glasses, effect of radiation-induced defects, (6) 302.
in Cs and Tl silicate glasses, relation to ionic conductivity, (10) 513.
crystal, of $ZrTiO_4$, (4) 216.
defect, δ-Fe_2O_3, grown epitaxially with $Al_2Si_2O_5(OH)_4$, (3) 124.
of HfO_2, determination from electrical properties, (6) 279.
of $(0.13YO_{1.5}\cdot 0.87ThO_2)$ electrolyte, (4) 198.
determination, in $BiFeO_3$, (8) 437.
micro-, of $(Ba,Sr)TiO_3$ ceramics, variations with electric field, (5) 261.
of graphite under stress, (10) 495.
in-reactor, of ThO_2-UO_2, thermal simulation, (9) 449.
of silica glass, study by electron microscopy, (1) 27.
of sintered Y_2O_3, effect of ThO_2, (11) 553.
of UO_2, effect of grain size, (2) 96.
of α- and β-quartz, (4) 182.
study, of $PbTiO_3$-$BaZrO_3$ system, (8) 404.
Sulfates, adsorbed, effect on density of hot-pressed BeO, (12) 685.
Sulfur, effect on foaming behavior of silicate melts, (10) 531.
Surfaces, ion-exchanged, effect of stress on durability, (11) 574.
Surface tension, of glass, effect of rh, (9) 482.
Suspensions, aqueous, containing kaolins of varying degrees of crystallinity, flow properties of, (4) 190.
Synthesis, of cubic nickel orthosilicate, (12) 684.
of germania-bearing compounds for piezoelectric and light amplification uses, (5) 268.
of Hf silicate, (10) 549.
of U and Pu oxycarbides, (6) 321.
Systems. See also *Phase diagrams.*
Al_2O_3-Cr_2O_3, solid solutions in, for strengthening alumina, (4) 169.
As-S-Se, partially vitreous, sintering study in, (11) 604.
As-Se, thermal expansion properties of vitreous materials in, (6) 335.
$BaTiO_3$-$KNbO_3$, phase transitions in, (2) 90.
binary borate and silicate showing immiscibility, compositions of modifier-rich liquids in, (1) 31.
boron-carbon, phase diagram, (3) 144.
CaO-CO_2, isobaric section through, (1) 44.
CaO-CO_2-H_2O, phase equilibria in, (1) 43.
CaO-SiO_2-H_2O and CaO-Al_2O_3-H_2O, hydrates formed in, (6) 312.
CaO-Yb_2O_3, hypothetical free energy-composition diagram for, (2) 108.
Ca_2WO_4-$SrWO_4$, phase transition in, (8) 434.
CoO-Al_2O_3-SiO_2, derivation of stability of mullite from equilibria in, (10) 537.
Cu_2O-SiO_2, relation of area-to-volume ratio to amount of liquid and transformation rate, (8) 416.
FeO-Fe_2O_3-ZrO_2-SiO_2, phase relations in, (3) 137.
GeO$_2$-Al_2O_3, phase equilibria in, (5) 268.
HfO_2-WO_2-WO_3, condensed phase relations in, (4) 211.
La_2O_3-Al_2O_3, alumina-rich, liquidus in, (3) 167.
PbO-PbF_2, crystal growth from, (6) 325.
PbO-TiO_2-ZrO_2, phase equilibrium in, (3) 129.
Li-C and Li-B, compound formation in, (10) 520.
$LiAlGeO_4$-Zn_2GeO_4, phase diagram, (7) 384.
$LiAlSiO_4$-$AlPO_4$, crystalline solution in, (2) 112.
LiI-KI, phase diagram, (1) 60.
Li_2O-Al_2O_3-SiO_2, chemical strengthening of glass-ceramics in, (3) 133.
$MgAl_2O_4$-Al_2O_3 and $MgAl_2O_4$-MgO, growth of single crystals from, (5) 273.
MgO-Al_2O_3-MgO-Cr_2O_3, solid solutions in, for strengthening spinel, (4) 169.
MgO-FeO-Fe_2O_3, phase equilibria in: 1300°C isothermal section, (5) 243.
MgO-GeO_2-LiF, ternary phases in, (8) 438.
MgO-SiO_2, Grüneisen constant and parameter δ for nonporous compounds in, (5) 242.
MnO-CoO-SiO_2, activity-composition relations in orthosilicate and metasilicate solid solutions in, (5) 230; correction, (12) 689.
MnSe-MnS, (3) 164.
MoO_3-P_2O_5-Ag_2O and MoO_3-P_2O_5-K_2O, areas of good glass formation in, (10) 516.
multiphase, stress distribution in, I, (10) 542.
nickelous nitrate-water-MgO, low-temperature cementation effects in, (11) 629.
oxide, structural interpretation of immiscibility in, (1) 29.
$KAlSiO_4$-Mg_2SiO_4-$KAlSi_2O_6$, (4) 174.
$KNbO_3$-$AgNbO_3$, electrical, X-ray, and thermal expansion studies, (12) 671.
Sc_2O_3-B_2O_3, (1) 53.
Na_3AlF_6-Li_3AlF_6, reinvestigation, (8) 395.
$Na_2O\cdot GeO_2\cdot B_2O_3$, structure of glasses and melts in, (12) 641.
(Na,K)NbO_3 and (Na,K,Li)NbO_3, ferroelectric behavior, (6) 329.
SrO-B_2O_3, phase boundaries in portion of, (2) 117.
Ta-C, isolation of zeta phase, (2) 115.
UN-UP, pseudobinary, phase studies in, (2) 74.
Y_2O_3-V_2O_5, compounds for color television and for maser materials, (7) 381.

Systems (*continued*)
ZnO-TeO_2, glass formation in, (10) 523.
ZrO_2-MgO, phase relations in, (6) 288.
ZrO_2-WO_2-WO_3, condensed phase relations in, (4) 211.

Tantalum. See also *Phase diagrams; Systems.*
carbide, effect of stoichiometry on thermal expansion, (9) 475.
hot hardness to 1900°C, (6) 290.
hot-pressed, plastic deformation in, (5) 253.
diboride, high-temperature thermal expansion for, (2) 81.
oxide, films, prepared by O_2 plasma anodization and reactive sputtering, (6) 283.
pentoxide, effect on grain growth in $BaTiO_3$, (9) 491.
slabs, chemical analysis before and after annealing, (2) 115.
δ-Ta_2O_5, new metastable high-temperature phase, (10) 500.
Tellurium, dioxide, glass, formation by rapid quenching techniques, (10) 500.
Tl^+, in potassium borate glasses, γ-induced absorption bands from, (10) 503.
Temperature, Curie, of ferroelectric $LiTaO_3$, as function of melt stoichiometry, (12) 657.
dependence, of O_2 diffusion in Y_2O_3 and Er_2O_3, (2) 113.
fluctuations, relation to striations in flux crystal growth, (6) 332.
of the monotectic, in oxide systems, (1) 29.
of thermal arrests in cooling curves, system LiI-KI determined from, (1) 60.
Thermal analysis, differential, of Ta-C alloy, transition from β- to α-Ta_2C, (5) 266; differential, thermogram of W-C alloy containing 32.7 at.% C, (5) 272.
Thermal decomposition. See *Decomposition, thermal.*
Thermal expansion. See *Expansion.*
Thermogravimetry, of glass-metal composites, (2) 61; in study of vaporization of lead zirconate titanate, (9) 441; of system MgO-FeO-Fe_2O_3, (5) 243.
Thermoluminescence. See *Luminescence.*
Thorium, carbides, preparation of, (6) 308.
cubic refractory compounds, thermal expansion of, (5) 248.
oxide, crystals, flux growth with localized cooling, (6) 327.
effect on grain growth in sintering of Y_2O_3, (11) 553.
gel, size distribution in, (11) 619.
-UO_2, thermal simulation of in-reactor microstructures in, (9) 449.
Tile, drain-, bodies, moisture stress vs. moisture content, (5) 227.
Titanium, borides and carbides, hot hardness to 1900°C, (6) 290.
carbide, effect of temperature and p_{O_2} on oxidation of, (4) 176.
fibrous, (11) 630.
hot-pressed, plastic deformation in, (5) 253.
diboride, high-temperature thermal expansion of, (2) 81.
dioxide. See also *Phase diagrams; Rutile; Systems.*
effect on crystallization in Li_2O-Al_2O_3-SiO_2 glasses, (2) 77.
enthalpy of structural modifications in, (11) 626.
as opacifier in cover coat enamel, (3) 152.
precipitate, as strengthening agent for α-Al_2O_3, (3) 150.
Tobermorite, synthetic, formation from lime-bentonite mixtures, (6) 312.
Topotaxy, in decomposition of CrO_2, (1) 56.
Transformation, of quartz to tridymite in presence of binary silicate liquids, (8) 414.
Transitions, phase, in system $BaTiO_3$-$KNbO_3$, temperatures of, (2) 92; in vapor-deposited alumina, (11) 568.
Tridymite, precipitation from binary silicate liquids, (8) 414.
Tungsten. See also *Phase diagrams; Systems.*
borides and carbides, hot hardness to 1900°C, (6) 290.
carbide, hot-pressed, plastic deformation in, (5) 253.
Knudsen cell, for evaporation experiments, (12) 666.
W_2C, evidence for ζ-Fe_2N-type sublattice order in, at intermediate temperatures, (5) 272.
WO_3, glass, formation by rapid quenching techniques, (10) 500.

Uranium. See also *Phase diagrams; Systems.*
dioxide, electrical conductivity of, (12) 652.
dioxide, microstructure alterations in, (9) 449.
oxide, elasticity and anelasticity at room temperature, (2) 93.
oxycarbide, formation from PuO_2 and UO_2, (6) 321.
urania-yttria and urania-lanthana, equilibrium oxygen pressures over solid solutions of, (11) 563.

Vanadium. See also *Phase diagrams; Systems.*
carbide, hot-pressed, plastic deformation in, (5) 253.
pentoxide, glass, formation by rapid quenching techniques, (10) 500.
V_2C, low-temperature modifications of, (5) 265.
Vapor pressure, of Be_3N_2 decomposition reaction, (9) 460.
Vapor transport, potash and silica loss by, in system $KAlSi_2O_6$-Mg_2SiO_4-SiO_2, (4) 175.
Vaporization, of Gd and GdC_2, Knudsen cell studies, (8) 385.
of lead zirconate-lead titanate materials, (9) 441.
of solid SiO, (7) 378.
data for Na_2O ternary melts and SiO_2-B_2O_3 binary melts, (1) 49.
of nitrided SiO_2 glass, sag test for, (6) 276.
relation to particle size and crystallinity in kaolin, (4) 193.

Water. See also *Systems.*
adsorbed, effect on spreading of organic liquids on soda-lime glass, (9) 478.
in clay-water system, specific energy of, (5) 223.
condensation, on barium silicate glasses, as cause of internal friction peak, (6) 336.
vapor, effect on crack propagation in soda-lime glass, (8) 407.
vapor, in silicate melts, effect on foaming behavior, (10) 528.
Weight, loss, kinetics, isothermal, for brucite, (1) 9.
Wetting, in Ni-base alloys, measurement by sessile drop technique, (7) 350.
Whiskers, MgO, ductility of, (11) 624; MgO, growth by vapor-liquid-solid mechanism, (11) 627.
Whitewares, bodies, moisture stress vs. moisture content, (5) 226; body, containing quartz, effect of quartz grain size on fracture types, (7) 337.

X rays, analysis, high-temperature, of Zr-ZrO_2 compositions, (5) 260.
analysis, in identification of interfacial compounds in PbO-bearing enamel-metal systems, (2) 85.
data, for germanium-mullite $(2GeO_2\cdot 3Al_2O_3)$, (5) 269.
data, from zeta layer of carburized tantalum, (2) 116.
diffraction, in identification of crystalline phases in nepheline glass-ceramics, (2) 69.
of lime-bentonite reaction products, (6) 313.
studies in system $BaTiO_3$-$KNbO_3$, (2) 91.
diffraction data, for $5LiAlGeO_4\cdot 4Zn_2GeO_4$, (7) 384.
for MgO-GeO_2-LiF compounds, (8) 438.
for metastable $ScBO_3$ quenched from liquid, (1) 54.
for phases in system Y_2O_3-V_2O_5, (7) 382.
for ThB_4, (5) 249.
for ZrW_2O_8, (4) 212.
diffraction patterns, for barium silicate glasses, (6) 307.
for ettringite-C_4A aqueous reaction products, (4) 205.
for α- and β-Nb_2C, (5) 267.
for $SrO\cdot 3B_2O_3$, (2) 118.
for W_2C(β), (5) 272.
diffractometer traces, for δ-Fe_2O_3, oil converted oxide, and γ-Fe_2O_3, (3) 125.
diffractometer tracings, for forsterite (112) and spinel (311) peaks, (4) 175.
emission measurements, of $3CaO\cdot Al_2O_3$, (2) 97.
patterns, of cleaved (100) face of MgO substrate and $NiFe_2O_4$ films deposited on MgO and glass, (3) 121.
powder diffraction data, for $CaYb_2O_4$, (9) 492; for Y_2O_3-ZrO_2 system, (10) 534.
powder pattern, for Li boride, (10) 522.
study, of Hf silicate, (10) 549.
study, in system $KNbO_3$-$AgNbO_3$, (12) 671.
topography, of Czochralski ruby, (11) 588.

Young's modulus. See *Elasticity.*
Ytterbium, oxide, precipitation from CaO crystalline solutions, (2) 107.
Yttrium. See also *Phase diagrams; Systems.*
fluoride, lattice energy needed to dissolve in CaF_2, (12) 648.
oxide, effect on properties of urania, (11) 563.
powder, determination of sintering progress by resonant frequency parameter, (3) 148.
self-diffusion of O_2 in, (2) 113.
sintering parameters for, (10) 511.
-zirconia, translucent, cubic phase stabilization at very low temperatures, (10) 532.
Y_2O_3, anomalous sintering behavior, (8) 439.
Y_2O_3, grain-boundary segregation in final-stage sintering of, (11) 553.
YVO_4, Eu-doped, for color television and home lighting, (7) 381.

Zinc, ferrite, solid solutions, preparation of, (7) 343.
oxide, crystals, growth by flux technique with localized cooling, (6) 326.
kinetics and mechanism of reaction with $BaCO_3$, (9) 484.
in solid solutions with Ca_2SiO_4, (11) 617.
Zircon, natural, lattice parameters and Hf content, (10) 550.
Zirconia. See *Zirconium, dioxide.*
Zirconium. See also *Phase diagrams; Systems.*
borides and oxides, hot hardness to 1900°C, (6) 290.
diboride, high-temperature thermal expansion for, (2) 81.
diffusion in zirconium hydride, (3) 166.
dioxide, stabilized, elastic modulus of, (4) 220.
dioxide, Y_2O_3-stabilized, cubic phase stabilization in, (10) 532.
oxide, crystals, flux growth with localized cooling, (6) 327.
nonstoichiometry of, relation to tetragonal-cubic inversion in ZrO_2, (5) 257.
porous, polishing of, (6) 328.
titanate, crystal structure, (4) 216.

JOURNAL
of the
American Ceramic Society

A MONTHLY PUBLICATION DEVOTED TO THE ARTS AND SCIENCES RELATED TO THE SILICATE INDUSTRIES

VOLUME 50, 1967

F. P. Reid, *Publisher and General Secretary*
Herbert Insley, *Editor*
Margie K. Reser, *Technical Editor*
M. Geraldine Smith, *Associate Editor*
Olive Scott, *Editorial Assistant*
Mary K. Schaaf, *Editorial Assistant*

Committee on Publications: W. J. Smothers, *Chairman;*
Howard F. McMurdie, Seymour L. Blum, Clarence L. Babcock; and
ex officio members: F. P. Reid, Herbert Insley, Edward E. Mueller

Executive, Editorial, and Advertising Offices: **4055 North High Street, Columbus, Ohio 43214**
Publication Office: **Easton, Pennsylvania**

Officers of the American Ceramic Society, 1967–68

Society Officers

President: JAMES S. OWENS
Champion Spark Plug Co., Ceramic Div.
8525 Butler Ave., Detroit, Mich. 48211
President-Elect: LORAN S. O'BANNON
Battelle Memorial Institute, 505 King Ave.
Columbus, Ohio 43201
Vice Presidents:
HOWARD F. MCMURDIE
National Bureau of Standards, Washington, D. C. 20234
ALFRED W. ALLEN
University of Illinois, Ceramic Engineering Dept.
Urbana, Ill. 61801
J. EARL FRAZIER
Frazier-Simplex, Inc., Box 493, Washington, Pa. 15301
Treasurer: ARTHUR J. BLUME
American Olean Tile Co., Lewisport, Ky. 42351

Division Officers

Basic Science Division

Trustee: FLOYD A. HUMMEL (1969)
Pennsylvania State University
Mineral Industries Bldg., University Park, Pa. 16802
Chairman: RUSTUM ROY, Pennsylvania State University
Research Bldg. 1–112, University Park, Pa. 16802
Chairman-Elect: ALBERT E. PALADINO, JR., Raytheon Co.
Research Div., 28 Seyon St., Waltham, Mass. 02154
Vice Chairman: ORSON L. ANDERSON, Lamont Geological
Observatory, Columbia University, Palisades, N. Y. 10964
Secretary: RALPH CARTER, General Electric Research &
Development Center, Box 1088, Schenectady, N. Y. 12301

Ceramic-Metal Systems Division

Trustee: EUGENE E. BRYANT (1970) Ferro Corp.
4150 E. 56th St., Cleveland, Ohio 44105
Chairman: JACK E. BURROUGHS, SR., General Dynamics Corp.
Grant Lane, Fort Worth, Texas 76101
Vice Chairman: CLIFTON G. BERGERON, University of Illinois
203 Ceramics Bldg., Urbana, Ill. 61801
Secretary: LYNN E. FUSSELL, 435 Crestover Circle
Richardson, Texas 75080 (Texas Instruments, Inc.)
Counselor: JESSE D. WALTON, JR., 2080 Fairway Circle, N.E.
Atlanta, Ga. 30319 (Engineering Experiment Station
Georgia Institute of Technology)
Counselor: HAROLD C. WILSON, Vitreous Steel Products Co.
Box 150, Nappanee, Ind. 46550

Design Division

Trustee: JULES R. GULDEN (1968)
Syracuse China Corp., Syracuse, N. Y. 13201
Chairman: DON SCHRECKENGOST
Design for Industry, Inc., 2617 St. Clair Ave., MC-19
East Liverpool, Ohio 43920
Secretary: DONALD E. FRITH, 1109 W. Clark
Champaign, Ill. 61821 (University of Illinois)

Electronics Division

Trustee: ALEXIS G. PINCUS (1969) IIT Research Institute
10 W. 35th St., Chicago, Ill. 60616
Chairman: RAYMOND J. BROWN, Electro Refractories & Abrasives
Div. of Ferro Corp., Box 151, Crooksville, Ohio 43731
Chairman-Elect: GILBERT GOODMAN, Globe-Union, Inc.
5757 N. Green Bay Ave., Milwaukee, Wisc. 53201
Vice Chairman: MERLE D. RIGTERINK
Bell Telephone Labs., Inc., Murray Hill, N. J. 07971
Secretary: VICTOR J. TENNERY, University of Illinois
205 Ceramics Bldg., Urbana, Ill. 61801

Glass Division

Trustee: CLARENCE L. BABCOCK (1968)
1718 Potomac Dr., Toledo, Ohio 43607 (Owens-Illinois)
Chairman: VINCENT E. J. CHIOCHETTI, Box 101E,
R.R.3, Greensburg, Pa. 15601 (Pittsburgh Corning Corp.)
First Vice Chairman: ALFRED R. COOPER, Case Western
Reserve University, Metallurgy Dept., 10900 Euclid Ave.
Cleveland, Ohio 44106
Second Vice Chairman: JOHN R. HUTCHINS, III
Corning Glass Works, Sullivan Park, Corning, N. Y. 14830
Secretary: FAY V. TOOLEY, 611 W. Oregon
Urbana, Ill. 61801 (University of Illinois)

Materials & Equipment Division

Trustee: JOHN MCLAREN (1969) Box 75
East Liverpool, Ohio 43920 (Sales representative)
Chairman: FRANK J. ZVANUT, Two Country Club Acres
St. Charles, Mo. 63301 (Frank Zvanut Co.)
Chairman-Elect: WILLIAM K. BURRISS, International Minerals
& Chemical Corp., Industrial Minerals Div.
5401 Old Orchard Rd., Skokie, Ill. 60076
Vice Chairman: RICHARD O. HOMMEL, 5 Grandview Ave.,
Apt. 803, Pittsburgh, Pa. 15211 (The O. Hommel Co.)
Secretary: WILLIAM C. MOHR, Product Development Lab.
Refractories Div., Ferro Corp., Box 151
Crooksville, Ohio 43731

Nuclear Division

Trustee: STEPHEN D. STODDARD (1970) 1460 Myrtle St.
Los Alamos, N. M. 87544 (Los Alamos Scientific Lab.)
Chairman: RICHARD M. FULRATH, University of California
264 Hearst Mining Bldg., Berkeley, Calif. 94720
Vice Chairman: JOSEPH H. HANDWERK, 1112 Black Rd.
Joliet, Ill. 60435 (Argonne National Lab.)
Secretary: STEPHEN C. CARNIGLIA, Atomics International Div.
North American Rockwell Corp., 8900 De Soto St.
Canoga Park, Calif. 91304

Refractories Division

Trustee: KENNETH A. BAAB (1970) Bethlehem Steel Corp.
Homer Research Labs., Bethlehem, Pa. 18016
Chairman: THEODORE J. M. PLANJE, University of Missouri
at Rolla, School of Mines & Metallurgy, Rolla, Mo. 65401
Vice Chairman: RALPH C. PADFIELD, 2990 Avon Rd.
Bethlehem, Pa. 18017 (Bethlehem Steel Corp.)
Secretary: WILLIAM D. FITZPATRICK, 412 E. Promenade
Mexico, Mo. 65265 (A. P. Green Refractories Co.)

Structural Clay Products Division

Trustee: GILBERT C. ROBINSON (1969)
Box 91, Clemson, S. C. 29631 (Clemson University)
Chairman: H. HOWARD LUND, Pomona Pipe Products Co.
Winston-Salem Rd., Greensboro, N. C. 27407
Chairman-Elect: ROBERT B. HOCKADAY, Acme Brick Co.
Box 1189, Denton, Texas 76202
Vice Chairman: ROBERT W. RICHARDS, Richards Brick Co.
234 Springer, Edwardsville, Ill. 62025
Secretary: SHERWOOD E. PATEK
Midland Brick & Tile Co., Chillicothe, Mo. 64601

White Wares Division

Trustee: RALPH L. GIBSON (1968) 520 Hill Blvd.
East Liverpool, Ohio 43920 (Taylor, Smith & Taylor Co.)
Chairman: FRED G. SIMMEN, R. R. 3, Oakmont
East Liverpool, Ohio 43920 (Hall China Co.)
Chairman-Elect: MILAN VUKOVICH, JR.
Edward Orton, Jr. Ceramic Foundation, 1445 Summit St.
Box 8446, Sta. A, Columbus, Ohio 43201
Vice Chairman: WILLIAM B. CAMPBELL, 1892 Inchcliff Rd.
Columbus, Ohio 43221 (Ohio State University)
Secretary: DONALD L. HEATH, Coors Porcelain Co.
600 Ninth St., Golden, Colo. 80401

Ceramic Educational Council

Trustee: WILLIS E. MOODY (1968) School of Ceramic Engineering
Georgia Institute of Technology, Atlanta, Ga. 30332
President: DAVID R. WILDER
1212 S. Third St., Ames, Iowa 50010 (Iowa State University)
President-Elect: ALFRED W. ALLEN, University of Illinois
Ceramic Engineering Dept., Urbana, Ill. 61801
Vice President: WILLIS G. LAWRENCE
State University of New York College of Ceramics at
Alfred University, Alfred, N. Y. 14802
Secretary-Treasurer: ROBERT E. MOORE, University of
Missouri at Rolla, School of Mines & Metallurgy
Rolla, Mo. 65401

National Institute of Ceramic Engineers

Trustee: RALPH L. COOK (1968) University of Illinois
209 Ceramics Bldg., Urbana, Ill. 61801
President: WILLARD E. HAUTH, JR., 1218 Blanchard Ave.
Flint, Mich. 48503 (AC Spark Plug Div., General Motors
Corp.)
President-Elect: ROBERT J. BEALS, Argonne National Lab.
Bldg. 212, 9700 S. Cass Ave., Argonne, Ill. 60439
Vice President: MURRAY C. GAUTSCH, M&T Chemicals Inc.
100 Park Ave., New York, N. Y. 10017
Secretary-Treasurer: HAROLD D. PRIOR, Chas. Taylor Sons Co.
Box 14058, Cincinnati, Ohio 45214

TABLE OF CONTENTS

VOLUME 50, 1967

January [No. 1], pp. 1–60

1. R. W. Douglas and T. M. M. El-Shamy: Reactions of Glasses with Aqueous Solutions 1
2. Ronald S. Gordon and W. D. Kingery: Thermal Decomposition of Brucite: II, Kinetics of Decomposition in Vacuum 8
3. P. C. Kapur and D. W. Fuerstenau: Dry Strength of Pelletized Spheres 14
4. Orville Hunter, Jr., and W. E. Brownell: Thermal Expansion and Elastic Properties of Two-Phase Ceramic Bodies 19
5. H. Arend, P. Coufová, and J. Novák: Chemical Processes During Hydrogen Reduction of Barium Titanate Crystals 22
6. T. P. Seward III, D. R. Uhlmann, David Turnbull, and G. R. Pierce: Transmission Electron Microscopy of Thin Glass Samples 25
7. Ernest M. Levin: Structural Interpretation of Immiscibility in Oxide Systems: IV, Occurrence, Extent, and Temperature of the Monotectic 29
8. Tryggve Baak and R. LaMar Frederick: Polarography in Molten Sodium Disilicate 38
9. Peter J. Wyllie: Phase Equilibria in System $CaO–CO_2–H_2O$ and Related Systems, with Implications for Crystal Growth of Calcite and Apatite 43
10. E. F. Riebling: Volume Relations in $Na_2O·B_2O_3$ and $Na_2O·SiO_2·B_2O_3$ Melts at 1300°C 46

Discussions and Notes

Ernest M. Levin: The System $Sc_2O_3–B_2O_3$ 53
R. C. Bradt: Cr_2O_3 Solid Solution Hardening of Al_2O_3 54
Carl F. Cline, John Carlberg, and Herbert W. Newkirk: Ionic Conductivity in BeO 55
R. D. Shannon: Topotaxy in Decomposition of CrO_2 56
R. H. Arlett, M. Robbins, and P. G. Herkart: Growth of Large Sapphire Crystals from Cryolite 58
P. J. Vergano, D. C. Hill, and D. R. Uhlmann: Thermal Expansion of Feldspar Glasses 59
Daniel B. Leiser and O. J. Whittemore, Jr.: The System LiI–KI 60

February [No. 2], pp. 61–118

11. Marcus P. Borom, James A. Longwell, and Joseph A. Pask: Reactions Between Metallic Iron and Cobalt Oxide-Bearing Sodium Disilicate Glass 61
12. D. A. Duke, J. F. MacDowell, and B. R. Karstetter: Crystallization and Chemical Strengthening of Nepheline Glass–Ceramics 67
13. Y. Baskin: Phase Studies in the Pseudobinary System UN–UP 74
14. P. E. Doherty, D. W. Lee, and R. S. Davis: Direct Observation of the Crystallization of $Li_2O–Al_2O_3–SiO_2$ Glasses Containing TiO_2 77
15. F. G. Keihn and E. J. Keplin: High-Temperature Thermal Expansion of Certain Group IV and Group V Diborides 81
16. Charles B. Greenberg and Ralph L. Cook: Interfacial Reactions in Lead Oxide-Bearing Enamel–Metal Systems 84
17. R. J. Bratton and T. Y. Tien: Phase Transitions in the System $BaTiO_3–KNbO_3$ 90
18. Roberto J. Forlano, A. W. Allen, and R. J. Beals: Elasticity and Anelasticity of Uranium Oxides at Room Temperature: I, Stoichiometric Oxide 93
19. Vernon L. Burdick and Delbert E. Day: Coordination of Aluminum Ions in Tricalcium Aluminate 97
20. A. E. Standage and Mary S. Gani: Reaction Between Vitreous Silica and Molten Aluminum 101
21. Thomas L. Barry and Rustum Roy: Defect Characterization in and Precipitation from $CaO:Yb_2O_3$ Crystalline Solutions 105
22. Roger F. Bartholomew and Theodore R. Kozlowski: Alkali Attack of Glass Surfaces by Molten Salts 108

Discussions and Notes

A. J. Perrotta and R. O. Savage: Beta Eucryptite Crystalline Solutions Involving P^{5+} 112
C. D. Wirkus, M. F. Berard, and D. R. Wilder: Self-Diffusion of Oxygen in Y_2O_3 and Er_2O_3 113
A. Arbel: Deformation Properties of a Polycrystalline KCl–NaCl Alloy 114
W. F. Brizes and J. M. Tobin: Isolation of the Zeta Phase in the System Tantalum–Carbon 115
C. G. Bergeron and J. P. De Luca: Crystal Growth at Bubble Surfaces in Glass 116
C. F. Chenot: Phase Boundaries in a Portion of the System $SrO–B_2O_3$ 117

March [No. 3], pp. 119–68

23. W. D. Westwood, H. K. Eastwood, R. G. Poulsen, and A. G. Sadler: Single-Crystal Ferrite Films Prepared by Cathodic Sputtering 119
24. Robert F. Conley: Structural and Chemical Alterations of Delta Fe_2O_3 and Their Effect on Magnetic Properties 124
25. Shoichi Fushimi and Takuro Ikeda: Phase Equilibrium in the System $PbO–TiO_2–ZrO_2$ 129
26. B. R. Karstetter and R. O. Voss: Chemical Strengthening of Glass–Ceramics in the System $Li_2O–Al_2O_3–SiO_2$ 133
27. T. S. Jones, Shigeyuki Kimura, and Arnulf Muan: Phase Relations in the System $FeO–Fe_2O_3–ZrO_2–SiO_2$ 137
28. C. E. Lowell: Solid Solution of Boron in Graphite 142
29. M. O. Marlowe and D. R. Wilder: Sensitive Resonant Frequency Technique for the Study of Sintering Kinetics 145
30. S. E. Hsu, W. Kobes, and M. E. Fine: Strengthening of Sapphire by Precipitates Containing Titanium 149
31. R. A. Eppler and W. A. McLeran, Jr.: Kinetics of Opacification of a TiO_2-Opacified Cover Coat Enamel 152
32. H. C. Graham, N. M. Tallan, and Ralston Russell, Jr.: Particle Size Dependence of the Electrical Conductivity of NaCl 156

Discussions and Notes

J. M. Mehta, P. G. Riewald, and L. H. Van Vlack: The System MnSe–MnS 164
M. Kestigian: Yttrium–Iron Garnet Single-Crystal Growth by the Combined Czochralski-Molten Salt Solvent Technique 165
G. G. Bentle: Diffusion of Zirconium in Zirconium Hydride 166
Edward T. Fritsche and Lowell G. Tensmeyer: Liquidus in the Alumina-Rich System $La_2O_3–Al_2O_3$ 167

April [No. 4], pp. 169–222

33. Henry P. Kirchner, Robert M. Gruver, and Ralph E. Walker: Chemically Strengthened, Leached Alumina and Spinel 169
34. W. C. Luth: The System $KAlSiO_4–Mg_2SiO_4–KAlSi_2O_6$ 174
35. Read W. Stewart and Ivan B. Cutler: Effect of Temperature and Oxygen Partial Pressure on the Oxidation of Titanium Carbide 176

36. G. H. Beall, B. R. Karstetter, and H. L. Rittler: Crystallization and Chemical Strengthening of Stuffed β-Quartz Glass–Ceramics ... 181
37. W. C. Ormsby and J. H. Marcus: Flow Properties of Aqueous Suspensions Containing Kaolins of Varying Degrees of Crystallinity ... 190
38. A. G. Atkins and D. Tabor: Mutual Indentation Hardness of Single-Crystal Magnesium Oxide at High Temperatures ... 195
39. J. M. Wimmer, L. R. Bidwell, and N. M. Tallan: Electrical Properties and Defect Structure of a $(0.13YO_{1.5}\cdot 0.87ThO_2)$ Electrolyte ... 198
40. W. W. Pultz and W. Hertl: Oxidation Kinetics of Particulate Silicon Monoxide ... 202
41. P. K. Mehta: Expansion Characteristics of Calcium Sulfoaluminate Hydrates ... 204
42. E. A. Maguire and J. J. Green: Magnetic Properties of Yttrium–Gadolinium–Iron–Aluminum–Indium Garnets ... 208
43. Luke L. Y. Chang, M. G. Scroger, and Bert Phillips: Condensed Phase Relations in the Systems ZrO_2–WO_2–WO_3 and HfO_2–WO_2–WO_3 ... 211

Discussions and Notes

R. E. Newnham: Crystal Structure of $ZrTiO_4$ ... 216
D. J. Sellers, A. H. Heuer, W. H. Rhodes, and T. Vasilos: Alumina Crystal Growth by Solid-State Techniques ... 217
C. W. Hewson and W. D. Kingery: Effect of MgO and $MgTiO_3$ Doping on Diffusion-Controlled Creep of Polycrystalline Aluminum Oxide ... 218
A. David Pearson, J. R. Fisher, and W. R. Northover: Preparation of Optical Quality Glass in Small Batches ... 219
John D. Buckley and David N. Braski: Elastic Modulus of Stabilized Zirconia ... 220
Carl F. Cline, Herbert W. Newkirk, Willis L. Barmore, and Richard R. Vandervoort: Creep–Electrical Conductivity Correlations in Polycrystalline Beryllium Oxide ... 221

May [No. 5], pp. 223–74

44. R. Q. Packard: Moisture Stress in Unfired Ceramic Clay Bodies ... 223
45. J. V. Biggers and Arnulf Muan: Activity-Composition Relations in Orthosilicate and Metasilicate Solid Solutions in the System MnO–CoO–SiO_2 ... 230
46. Harlan U. Anderson: Initial Sintering of Rutile ... 235
47. Naohiro Soga and Orson L. Anderson: High-Temperature Elasticity and Expansivity of Forsterite and Steatite ... 239
48. David H. Speidel: Phase Equilibria in the System MgO–FeO–Fe_2O_3: The 1300°C Isothermal Section and Extrapolations to Other Temperatures ... 243
49. S. Aronson, E. Cisney, and K. A. Gingerich: Thermal Expansion of Some Cubic Refractory Compounds of Thorium ... 248
50. A. Kelly and D. J. Rowcliffe: Deformation of Polycrystalline Transition Metal Carbides ... 253
51. Robert Ruh and Harold J. Garrett: Nonstoichiometry of ZrO_2 and Its Relation to Tetragonal–Cubic Inversion in ZrO_2 ... 257
52. Viola C. Sanvordenker: Optical and Microstructural Variations with Electric Field in Barium–Strontium Titanate Ceramics ... 261
53. Erwin Rudy and Charles E. Brukl: Lower-Temperature Modifications of Nb_2C and V_2C ... 265

Discussions and Notes

John L. Miller, Jr., George R. McCormick, and Sarkis G. Ampian: Phase Equilibria in the System GeO_2–Al_2O_3 ... 268
Edgar J. Greco and John A. Martinelli: Compositional Dependency of Laser-Induced Damage in Glass ... 270
W. E. Steinkamp, J. E. Shelby, and Delbert E. Day: Internal Friction of Mixed-Alkali Silicate Glasses ... 271
Erwin Rudy and St. Windisch: Evidence for Zeta Fe_2N-Type Sublattice Order in W_2C at Intermediate Temperatures ... 272
R. H. Arlett and Murray Robbins: Growth of Stoichiometric $MgAl_2O_4$ Single Crystals ... 273

June [No. 6], pp. 275–336

54. T. H. Elmer and M. E. Nordberg: Effect of Nitriding on Electrolysis and Devitrification of High-Silica Glasses ... 275
55. N. M. Tallan, W. C. Tripp, and R. W. Vest: Electrical Properties and Defect Structure of HfO_2 ... 279
56. F. Vratny: Tantalum Oxide Films Prepared by Oxygen Plasma Anodization and Reactive Sputtering ... 283
57. Clark F. Grain: Phase Relations in the ZrO_2–MgO System ... 288
58. R. D. Koester and D. P. Moak: Hot Hardness of Selected Borides, Oxides, and Carbides to 1900°C ... 290
59. Robert R. Shaw and James H. Heasley: Superparamagnetic Behavior of $MnFe_2O_4$ and α-Fe_2O_3 Precipitated from Silicate Melts ... 297
60. A. M. Bishay and Ibrahim Gomaa: Radiation-Induced Defects and Structure of Barium Silicate Glasses ... 302
61. Hisashi Imai, Shinobu Hosaka, and Keiji Naito: Preparation of Thorium Carbides ... 308
62. George Rembert Glenn: X-Ray Studies of Lime–Bentonite Reaction Products ... 312
63. Willis L. Barmore and Richard R. Vandervoort: High-Temperature Creep and Dislocation Etch Pits in Polycrystalline Beryllium Oxide ... 316
64. K. M. Taylor, J. C. Andersen, A. Strasser, D. Stahl, and R. L. Forbes: Monoxide-Type Compounds of Uranium and Plutonium: I, Oxycarbides ... 321
65. A. B. Chase and Judith A. Osmer: Localized Cooling in Flux Crystal Growth ... 325

Discussions and Notes

A. G. King and Karl Fuchs: Polishing Porous Materials ... 328
G. H. Haertling: Properties of Hot-Pressed Ferroelectric Alkali Niobate Ceramics ... 329
D. P. H. Hasselman: Relation Between Macroscopic Shear Moduli and Micromechanical Shear Stress Concentrations of Multicomponent Materials ... 331
A. B. Chase and W. R. Wilcox: Temperature Fluctuations and Striations in Flux Crystal Growth ... 332
F. S. Galasso, W. L. Darby, F. C. Douglas, and J. A. Batt: Unidirectional Solidification of the $BaFe_{12}O_{19}$-$BaFe_2O_4$ Eutectic ... 333
E. J. Felty and M. B. Myers: Thermal Expansion of Arsenic–Selenium Glasses ... 335
Paul W. L. Graham and Guy E. Rindone: Internal Friction Peak Caused by Condensation of Water on Barium Silicate Glasses ... 336

July [No. 7], pp. 337–84

66. S. I. Warshaw and R. Seider: Comparison of Strength of Triaxial Porcelains Containing Alumina and Silica ... 337
67. Russell G. West and A. C. Blankenship: Magnetic Properties of Dense Lithium Ferrites ... 343
68. E. Snape and P. R. Beeley: Refractory-Melt Reactions in Vacuum Induction Melting of Nickel-Base Alloys ... 349
69. Richard W. Wallace and Edwin Ruh: Electrical Resistivity of Refractories ... 358
70. Mark W. Benecke, Norman E. Olson, and Joseph A. Pask: Effect of LiF on Hot-Pressing of MgO ... 365
71. M. M. Layton and Andrew Herczog: Nucleation and Crystallization of $NaNbO_3$ from Glasses in the Na_2O–Nb_2O_5–SiO_2 System ... 369
72. Thomas L. Barry, V. S. Stubican, and Rustum Roy: Decomposition Kinetics of $CaYb_2O_4$ ... 375
73. W. Hertl and W. W. Pultz: Disproportionation and Vaporization of Solid Silicon Monoxide ... 378

Discussions and Notes

Ernest M. Levin: The System Y_2O_3–V_2O_5 ... 381

C. S. Morgan and L. L. Hall: Effect of Isostatic Pressure on Sintering 382
R. K. Datta: The System $LiAlGeO_4$–Zn_2GeO_4 384

August [No. 8], pp. 385–440

74. Clarence L. Hoenig, Norman D. Stout, and Paul C. Nordine: Knudsen Cell Studies of the Vaporization of Gadolinium and Gadolinium Dicarbide 385
75. T. Y. Tien and C. J. Moratis: Dielectric Properties of Strontium Titanate Solid Solutions Containing Niobia 392
76. G. Garton and B. M. Wanklyn: Reinvestigation of the System Na_3AlF_6–Li_3AlF_6 395
77. D. P. H. Hasselman and R. M. Fulrath: Micromechanical Stress Concentrations in Two-Phase Brittle-Matrix Ceramic Composites 399
78. Norman H. Harris and Victor J. Tennery: Structural and Dielectric Investigation of the $PbTiO_3$–$BaZrO_3$ System 404
79. S. M. Wiederhorn: Influence of Water Vapor on Crack Propagation in Soda–Lime Glass 407
80. Gerald I. Madden and Lawrence H. Van Vlack: Transformation of Quartz to Tridymite in the Presence of Binary Silicate Liquids 414
81. W. W. Pultz: Oxidation of Submicroscopic Fibrous Silicon Carbide 419
82. J. J. Borbas, R. C. Padfield, and E. Moscker: Density Determination of Refractories by Measurement of Gamma-Radiation Absorption 421
83. Ralph H. Condit and Yuriko Hashimoto: Self-Diffusion of Beryllium in Polycrystalline Beryllium Oxide 425
84. Robert S. Feigelson: Crystal Growth of Rare-Earth Orthoarsenates 433

Discussions and Notes

Luke L. Y. Chang and Bert Phillips: Phase Transition in the System Ca_3WO_6–Sr_3WO_6 434
Salil K. Roy and Robert L. Coble: Solubility of Hydrogen in Porous Polycrystalline Aluminum Oxide 435
G. D. Achenbach, W. J. James, and R. Gerson: Preparation of Single-Phase Polycrystalline $BiFeO_3$ 437
George Robert McCormick and Ernest G. Ehlers: Ternary Phases in the System MgO–GeO_2–LiF 438
J. D. Schieltz and D. R. Wilder: Anomalous Sintering Behavior of Y_2O_3 439

September [No. 9], pp. 441–94

85. David A. Northrop: Vaporization of Lead Zirconate–Lead Titanate Materials 441
86. R. B. Day and R. J. Stokes: Plastic Softening of Magnesium Oxide at High Temperatures by Nickel Oxide Addition 445
87. John M. Kerr: Thermal Simulation of In-Reactor Microstructures in ThO_2–UO_2 449
88. D. P. H. Hasselman: Approximate Theory of Thermal Stress Resistance of Brittle Ceramics Involving Creep 454
89. J. R. Kreglo, Jr., and W. J. Smothers: Mechanism of Creep in MgO Brick 457
90. Clarence L. Hoenig and Alan W. Searcy: Vapor Pressure, Enthalpy, Evaporation Coefficient, and Enthalpy of Activation of the Beryllium Nitride (Be_3N_2) Decomposition Reaction 460
91. Daniel R. Stewart, Guy E. Rindone, and Frank Dachille: Heats of Solution, Density, and Refractive Index Changes in Sodium Borate Glasses Subjected to High Pressure 467
92. T. D. Gulden: Direct Observation of Nonbasal Dislocations in Sintered Alumina 472
93. R. J. Fries and L. A. Wahman: Effect of Stoichiometry on the Thermal Expansion of TaC_x 475
94. Elaine G. Shafrin and W. A. Zisman: Effect of Adsorbed Water on the Spreading of Organic Liquids on Soda–Lime Glass 478
95. Samuel F. Hulbert and Jerome J. Klawitter: Kinetics and Mechanism of the Reaction Between Zinc Oxide and Barium Carbonate 484

Discussions and Notes

K. M. Finlayson and J. P. Williams: Beta Spodumene–Silica Solid Solution in an Li_2O–Al_2O_3–TiO_2–SiO_2 Glass–Ceramic 488
Tuvia Zisner and Hideo Tagai: Comment on Note "Functional Relation Between Creep Rate and Porosity for Polycrystalline Ceramics" 489
A. H. Webster, T. B. Weston, and Norman F. H. Bright: Effect of PbO Deficiency on the Piezoelectric Properties of Lead Zirconate–Titanate Ceramics 490
D. A. Payne and H. U. Anderson: Inhibition of Grain Growth in Barium Titanate 491
A. F. Reid: Calcium Ytterbate, $CaYb_2O_4$, an Orthorhombic Calcium Ferrite Isomorph 491
W. C. Beard and W. R. Foster: High-Temperature Formation of Anatase 493
F. Freund: Retention of Hydroxyl Groups on Magnesium Oxide 493

October [No. 10], pp. 495–552

96. O. D. Slagle: Deformation Mechanisms in Polycrystalline Graphite 495
97. P. T. Sarjeant and Rustum Roy: New Glassy and Polymorphic Oxide Phases Using Rapid Quenching Techniques 500
98. A. M. Bishay and M. S. Maklad: Gamma-Induced Absorption Bands Associated with Tl^+, Pb^{3+}, or Bi^{3+} in Potassium Borate Glasses 503
99. M. O. Marlowe and D. R. Wilder: Sintering Kinetics Study Using Reduced Variables 509
100. K. Otto and M. E. Milberg: Ionic Conduction and Structure in Cesium and Thallium Silicate Glasses 513
101. J. D. Provance and D. C. Wood: Molybdenum Phosphate Glasses Containing Ag_2O or K_2O 516
102. D. R. Secrist: Compound Formation in the Systems Lithium–Carbon and Lithium–Boron 520
103. M. J. Redman and J. H. Chen: Zinc Tellurite Glasses 523
104. Howard B. Johnson, G. R. Miller, and Ivan B. Cutler: Dielectric Loss in CaF_2 Doped with Oxygen Ions 526
105. Michael Cable and C. G. Rasul: Spontaneous Bubble Formation in Silicate Melts at High Temperatures: II, Effect of Wet Atmospheres and Behavior of Mixed Alkali Glasses 528
106. K. S. Mazdiyasni, C. T. Lynch, and J. S. Smith II: Cubic Phase Stabilization of Translucent Yttria-Zirconia at Very Low Temperatures 532
107. R. R. Dayal, R. E. Johnson, and Arnulf Muan: Stability of Mullite as Derived from Equilibria in the System CoO–Al_2O_3–SiO_2 537
108. P. J. Kelly and M. J. Laubitz: Thermoluminescence of Alumina 540
109. H. J. Oel and V. D. Fréchette: Stress Distribution in Multiphase Systems: I, Composites with Planar Interfaces 542

Discussions and Notes

D. J. Salt and G. Hornung: Synthesis and X-Ray Study of Hafnium Silicate 549
Hideo Tagai, Tuvia Zisner, T. Mori, and E. Yasuda: Preferred Orientation in Hot-Pressed Magnesia 550
Tuvia Zisner: Reactive Hot-Pressing of Magnesium Hydroxide 552

November [No. 11], pp. 553–630

110. P. J. Jorgensen and R. C. Anderson: Grain-Boundary Segregation and Final-Stage Sintering of Y_2O_3 553
111. Raymond L. Bertolotti and Richard M. Fulrath: Effect of Micromechanical Stress Concentrations on Strength of Porous Glass 558
112. K. Hagemark and M. Broli: Equilibrium Oxygen Pressures Over Solid Solutions of Urania-Yttria and Urania-Lanthana at 1100° to 1400°C 563

113. A. L. Dragoo and J. J. Diamond: Transitions in Vapor-Deposited Alumina from 300° to 1200°C 568
114. Daphne L. Rothermel: Effect of Stress on Durability of Ion-Exchanged Surfaces 574
115. R. K. Datta and Rustum Roy: Equilibrium Order-Disorder in Spinels 578
116. John H. Hensler and G. V. Cullen: Grain Shape Change During Creep in Magnesium Oxide 584
117. James P. Wittke: Solubility of Iron in TiO_2 (Rutile) 586
118. Roger F. Belt: X-Ray Topography of Czochralski Ruby 588
119. D. N. Turner, P. D. Smith, and W. B. Rotsey: Hertzian Stress Cracks in Beryllia and Glass 594
120. K. R. Janowski and R. C. Rossi: Elastic Behavior of MgO Matrix Composites 599
121. M. A. Carrell and D. R. Wilder: Sintering Study in the Partially Vitreous As–S–Se System 604
122. M. Bigaré, A. Guinier, C. Mazières, M. Regourd, N. Yannaquis, W. Eysel, Th. Hahn, and E. Woermann: Polymorphism of Tricalcium Silicate and Its Solid Solutions 609
123. M. J. Bannister: Crystallite Size Measurements on Thoria Gel 619

Discussions and Notes

Burton D. Brubaker: Ductile Magnesium Oxide Whiskers 624
G. R. Wilms: Influence of Ceramic Environment on Mechanical Properties of Metals 625
A. Navrotsky and O. J. Kleppa: Enthalpy of the Anatase-Rutile Transformation 626
A. H. Heuer and P. Burnett: Evidence for MgO Whisker Growth by a Vapor-Liquid-Solid Mechanism 627
M. H. Leipold: Addenda to Impurity Distribution in MgO 628
Emmett L. Williams, Jr., and Hugh H. Wilson: Low-Temperature Cementation Effects in Nickelous Nitrate–Water–Magnesium Oxide System 629
W. Hertl: Fibrous TiC 630

December [No. 12], pp. 631–702

124. R. J. Charles: Activities in Li_2O-, Na_2O-, and K_2O–SiO_2 Solutions 631
125. E. F. Riebling, P. E. Blaszyk, and D. W. Smith: Structure of Glasses and Melts in the $Na_2O \cdot GeO_2 \cdot B_2O_3$ System 641
126. A. D. Franklin: Born Model Calculation of Enthalpies of Solution in CaF_2 648
127. J. L. Bates, C. A. Hinman, and T. Kawada: Electrical Conductivity of Uranium Dioxide 652
128. A. A. Ballman, H. J. Levinstein, C. D. Capio, and H. Brown: Curie Temperature and Birefringence Variation in Ferroelectric Lithium Metatantalate as a Function of Melt Stoichiometry 657
129. K. E. Seifert: Electron Microscopy of Etched Plagioclase Feldspar 660
130. P. J. Ficalora and G. W. Brindley: Oxidation of Magnesiowustite Single Crystals: II, Dependence on Temperature, Oxygen Pressure, and Crystal Composition 662
131. D. R. Messier: Vapor Pressure of Gd_2O_3 from 2350° to 2590°K 665
132. Ronald A. Munson: High-Temperature Behavior of Beryl and Beryl Melts at High Pressure 669
133. Donald F. Weirauch and Victor J. Tennery: Electrical, X-Ray, and Thermal Expansion Studies in the System $KNbO_3$–$AgNbO_3$ 671
134. Mark A. Stett and R. M. Fulrath: Chemical Reaction in a Hot-Pressed Al_2O_3–Glass Composite 673
135. Stanislav Chromý: High-Temperature Microscopic Investigation of Tricalcium Silicate and Dicalcium Silicate Phases in Portland Cement Clinker 677

Discussions and Notes

P. Kofstad and A. Z. Hed: Defect Structure Model for Nonstoichiometric CeO_2 681
Douglas M. Mattox: Contamination-Nucleated Crystal Growth at Bubble Surfaces in Glass 683
R. K. Datta and Rustum Roy: Synthesis of Cubic Nickel Orthosilicate 684
R. B. Adams and W. I. Stuart: Effect of Adsorbed Sulfate and Fluoride on the Density of Hot-Pressed Beryllium Oxide 685
Gerald B. Carrier: Discussion of "Transmission Electron Microscopy of Thin Glass Samples" 686
T. P. Seward III and D. R. Uhlmann: Reply to "Discussion of 'Transmission Electron Microscopy of Thin Glass Samples'" 687
S. Chatterji and J. W. Jeffery: Discussion of Paper "Expansion Characteristics of Calcium Sulfoaluminate Hydrates," 687
G. V. Cullen, I. A. Cutter, and J. H. Hensler: Hot-Pressing of Magnesium Oxide Aggregates 688
J. V. Biggers and Arnulf Muan: Correction: Activity-Composition Relations in Orthosilicate and Metasilicate Solid Solutions in the System MnO–CoO–SiO_2 (May issue, 1967) 689
Author Index to *The Journal* 690
Subject Index to *The Journal* 692

Instructions for Preparation of Papers and Notes ..... Back Cover, November Journal

CERAMIC ABSTRACTS

December 1967 *SECTION*

Compiled by the American Ceramic Society

AUTHOR INDEX FOR 1967

The reference number in parentheses refers to the monthly issue of *Ceramic Abstracts;* the number following is the page number. The letter B or P preceding the reference number indicates an abstract of (B) a book, bulletin, or separate publication or (P) a patent. The italic letter following the page number indicates the position of the abstract on the page.

Aagaard, L. Preparation of a titania hydrate, P (11) 291*d*.

Abdel-Gawad, A. M. X-ray spectrographic determination of hafnium-zirconium ratio in zirconium minerals, (2) 60*c*.

Abduragimova, L. A. Effect of sodium salts of fatty acids on the viscosity of clay suspensions with ultimately broken-down structure, (7) 162*h*.

Abe, A. Production of semiconductor elements by the diffusion process, P (7) 157*i*.

Abe, H. Nuclear magnetic resonance of ^{61}Ni in nickel ferrite, (9) 241*f*. See Yasuoka, H.

Abe, T., and Tanokami, S. Implosion-proof picture tube, (1) 3*f*.

Abe, Y. See Morita, A.; Naruse, A.

Abeles, B. See Cody, G. D.

Abelmann, R. A., Shequen, W. G., and Smallbone, A. H. Dynamic analysis with X-ray fluorescence, (11) 289*g*.

Abercrombie, W. M., and Wurst, E. C., Jr. Semiconductor contact alloy, P (8) 186*c*.

Abernathy, W. J. Abrasive articles and method of making, P (2) 33*j*.

Abolins, V., and Lukes, R. M. Inorganic molding compositions of the asbestos-orthophosphoric acid type and products produced therefrom, P (9) 225*j*.

Abos, R. L. High temperature resistant member and process for forming, P (2) 44*g*.

Abraham, A. See Tauc, J.

Abrahams, S. C., Hamilton, W. C., and Reddy, J. M. Ferroelectric lithium niobate (IV) single crystal neutron diffraction study at 24°C, (8) 198*f*.

Abrahams, S. C., Levinstein, H. J., and Reddy, J. M. Ferroelectric lithium niobate (V) polycrystal X-ray diffraction study between 24° and 1200°C, (8) 198*h*.

Abrahams, S. C., Reddy, J. M., and Bernstein, J. L. Ferroelectric lithium niobate (III) single crystal X-ray diffraction study at 24°C, (8) 198*c*.

Abraitis, R. I., and Majauskas, J. Gaseous erosion of zirconium oxide refractories (I) refractories in the stream of combustion products, (5) 123*a*.

Abrams, L. V., and Trent, R. M. Metal cleaning, P (9) 217*e*.

Abramson, E. See Brixner, L. H.

Abramyan, A. V. New data on the leaching of silicate glasses, B (7) 171*c*.

Abrasive Developments, Ltd. Centrifugal pumps, P (2) 49*j*.

Abrecht, H., and Lukacs, J. Fired refractory shape and its manufacture, P (9) 225*f*.

Abrikosov, N. Kh. See Bankina, V. F.; Shelimova, L. E.

Accary, A., Blum, P., Bochirol, L., and Caillat, R. Process for the fabrication of fuel elements designed for high-temperature operation, P (10) 260*f*.

Accary, A., and Trouve, J. Method of making bars of a uranium compound and in particular uranium carbide [by continuous casting], P (11) 282*c*.

Acciani, J. O. See Fish, D. H.

Achenbach, G. D., James, W. J., and Gerson, R. Preparation of single-phase polycrystalline $BiFeO_3$, (9) 241*g*.

Achtziger, J. See Cammerer, C.

Acieries Reunies de Burbach-Eich-Dudelange, Soc. Anon. Process for producing bodies of refractory material, P (10) 260*a*. Process for the production of basic refractories, P (8) 182*b*. Process for the production of refractory brick, P (5) 125*b*. Process for the production of refractory materials, P (8) 182*c*.

Acker, E. G., and Hurley, F. R. Process for the preparation of silica gel, P (8) 190*e*.

Ackerman, C. B., and Sullivan, D. J. Alloy-diffused method for producing semiconductor devices, P (7) 156*e*.

Ackermann, C., Gauglitz, R., and Hennicke, H. W. Bourry diagram and drying shrinkage of dry-pressed bodies, (5) 121*j*.

Ackermann, R. J., and Thorn, R. J. Chemical bonding from high temperature studies—sublimation of refractory compounds, B (5) 140*b*.

Acloque, P. H., and Guillemet, C. Method and apparatus for determining surface birefringence in a transparent material employing a prism place adjacent to the surface, P (2) 39*c*.

Acme Abrasive Co. Reinforced grinding wheel and reinforcing structure therefor, P (8) 173*h*.

Adachi, Y., Kato, K., Suwa, Y., and Takehara, T. Manufacture of porcelain objects from blast-furnace slag, P (3) 75*a*.

Adair, R. B. See Browning, J. S.

Adamant Laboratories (Pty.), Ltd. Treatment of pyrophyllite, P (4) 107*d*.

Adami, L. H., and Conway, K. C. Heats and free energies of formation of anhydrous carbonates of barium, strontium, and lead, (1) 19*a*.

Adams, A. B. New development in flatware drying, (9) 228*h*.

Adams, C. E. See Arey, W. F., Jr.

Adams, C. M., Jr. Spreading, penetration, and capillary flow in metallic systems, B (8) 212*a*.

Adams, E. A., Brown, W. F., Jarosi, J. J., and Mook, G. C. Blending of granular materials, P (3) 80*f*.

Adams, M. F. Method of preparing magnesia, P (8) 181*e*.

Adams, M. F., and Huffaker, E. M. Refractory support, P (3) 73*b*.

Adams, N., Mukerjee, T., and Smith, J. M. Semiconductor diode with integrated mounting and small area fused impurity junction, P (4) 102*e*.

Adams, R. J., Weisbecker, H. L., and McDonald, W. J. Effect of abrasion on the specific surface area of metals and glass, (3) 66*e*.

Adamsky, R. F., and LeBlanc, R. E. Nucleation and initial growth of single-crystal films, (1) 24*g*.

Adamson, A. W., Ling, I., Dormant, L., and Orem, M. Physical adsorption on heterogeneous surfaces, (1) 26*g*.

Adamson, P. L. See Fletcher, N. H.

Addamiano, A. Photoluminescence and polytypism in boron doped silicon carbide, (7) 166*d*.

Adeline, B., and Demichel, P. Sintered products, (9) 233*a*.

Adelsberg, L. M., Cadoff, L. H., and Tobin, J. M. Kinetics of the zirconium-carbon reaction above 2000°C, (7) 164*j*.

Adelsberg, L. M., St. Pierre, G. R., and Speiser, R. Origin and identity of the oxide platelets observed in tantalum after oxidation, (7) 166*d*.

Aden Supplies, Inc. Apparatus for expanding heat-expandable ores, P (7) 160*c*. Furnace structure for expanding heat-expandable ores, P (7) 160*a*.

Adkins, J. S. See Wagner, A. E.

Adler, E. J., and Greenberg, H. J. Thermocouple with platinum group metal inner sheath, P (10) 268*d*.

Adler, M. D. W., and Simon, R. A. Drawing sheet glass, P (9) 219*f*.

Adolph, H. Bunzlau clays and some characteristic ware—in retrospect, (2) 53*f*.

A. E. I. John Thompson Nuclear Energy Co., Ltd. See Nuclear Power Plant Co., Ltd.

Aerojet-General Corp. Monitor for air-borne beryllium, P (3) 80*e*.

Agarkov, A. S. See Matveev, M. A.

Agaronova, L. M. Rheological properties of clays with additions of surfactants and electrolyte, (10) 256*g*.

Agency of Industrial Science & Technology. Magnesia fiber product and a method for manufacturing the same, P (8) 181*g*.

Aggarwal, P. S. See Das, S. K.

Agrawal, B. C. See Parthasarathi, M. N.

A. G. Sudschemie. High-melting glass fibers and method, P (7) 149*e*.

Agullo-Lopez, F. Dynamics of plastic flow at constant stress in NaCl single crystals, (10) 270*j*.

Ahlert, R. H. See Milch, A.

Ahmad, I. Volatilization of Na_2O from Alundum tubes in high purity hydrogen, (1) 7*j*.

Ahmed, F. U. See Jain, L. C.

Ahn, K. Y., and Shafer, M. W. Switching properties of europous oxide, (8) 208*e*.

Ahrens, T. J. High-pressure electrical behavior and equation of state of magnesium oxide from shock wave measurements, (1) 19*b*.

Aia, M. A. Phosphor coated articles, P (10) 265*e*.

Aiello, R. See Sersale, R.

Aigron, M. Improvements in tunnel kilns, particularly for drying heavy ceramics, P (7) 160*d*.

Aiken, H. H., Birrell, R. W., Cummins, J. B., and Richards, M. W. Automatic +X-axis detector, marker, sorter, and collector for [quartz] crystal wafer blanks, P (8) 184*a*.

Aiken, Howard, Industries. See Howard Aiken Industries.

Aiken, W. R. Envelope for cathode ray tubes, P (4) 94*d*.

Ainger, F. W. Formation and devitrification of oxides on silicon, (11) 296*b*.

Air Liquide, Soc. Anon. pour l'Etude et l'Exploitation des Procedes Georges Claude. Process of manufacturing a silicocalcareous body of high porosity, P (11) 284*a*.

Air Products & Chemicals, Inc. Method for preparing alumina particles, P (8) 181*d*.

Air Reduction Co., Inc. Forming a resistor with thin, compressed, contact portions, P (5) 127*d*.

Aitcin, P. C. Mineralogical properties of Thomas blast furnace slags and their use in mortars and concrete, (4) 90*j*.

Aiyama, Y. See Tanaka, M.

Aizawa, I. See Oomori, K.

Ajem Laboratories, Inc. Apparatus for handling grit, P (10) 266*c*.

Akasaki, I., and Kobayasi, H. Etching characteristics and light figures of the {111} surfaces of GaAs, (11) 295*j*.

Akashi, T. See Okada, T.

Akatsuka, Y., and Moriguchi, H. Strengths of prepacked concrete and reinforced prepacked concrete beams, (7) 147*a*.

Ake, N. E. See Eisenhower, W. D., Jr.

Akhlestin, E. S. See Dertev, N. K.

Akh'yan, A. M. Effect of glaze composition on deformation of porcelain, (3) 73*j*.

Akimoto, H. See Sugiura, T.

Akmenkalns, I. G., and Lord, P. A. Coupled helical wave structure employing a remanently magnetized ferrite, P (7) 156*b*.

Akselrad, A. Optimum design for a room-temperature pulse-operated GaAs injection laser, (3) 76*e*.

Aksenov, G. I., and Minaev, E. M. Determination of the physicomechanical and technological properties of cermet materials on a single annular specimen, (10) 257*d*.

Aksenov, P. A. See Goryainov, K. E.

Akseneva, E. B., and Tyurin, Yu. M. Tempering of thin [4.5 to 5 mm] glass, (3) 66*i*.

Aktiebolaget Kanthal. Heat-resistant and oxidation-proof materials, P (4) 98*j*, P (9) 225*i*. Sintered bodies of molybdenum silicide, P (5) 125*d*.

Aktiebolaget Motala Verkstad. Apparatus for disintegrating materials by means of liquid jets, P (9) 235*h*.

Aktieselskabet Burmeister & Wain's Maskin-OG. Shot cleaning method for heat exchangers, P (3) 82*b*.

Akunov, V. I. See Belokon, V. V.

Akutsu, C. See Nomura, S.

Alais, M. E., and Moutarde, R. C. Method for making thermocouples, P (1) 11*d*.

Albee, A. L. Phase equilibria in three assemblages of kyanite-zone pelitic schists, Lincoln Mountain Quadrangle, central Vermont, (1) 25*c*.

Albertsson, J. Inorganic ion exchangers, (11) 297*h*.

Albrecht, R. J. Economics of container glass melting, (1) 3*f*.

Albright, M. W. Method of making a surface joint, P (8) 178*d*.

Albright & Wilson, Ltd. Composition for production of ceramics, P (10) 261*c*. Manufacture of ceramics, P (7) 158*e*.

Alcock, C. B. Equilibria and transport in ceramic oxide interfaces, B (2) 61*b*.

Aldenkamp, A. A. Method of manufacturing MnBi magnets, P (8) 185*h*.

Alder, W. R., Housh, L. M., and Van Dreser, M. L. Development of MgO heat exchange media, (8) 179*h*.

Aldinger, R. Ground coat enameling, (7) 147*g*.

Aldrian, A. F. See Horn, H. F.

Aldrich, L. T., Davis, G. L., and James, H. L. Ages of minerals from metamorphic and igneous rocks near Iron Mountain, Michigan, (1) 16*d*.

Aleinikov, F. K., Gabsyte, G., and Nickiene, M. Composition of surface and internal crystallization products of crystalline glass, (5) 118*d*.

Aleinikov, F. K., Paulavichius, R. B., and Parfenov, V. A. Use of ultrathin sections for direct electron microscopic investigations of the fine structure and crystallization of glass, B (9) 246*c*.

Aleixandre Ferrandis, V. Silicoaluminous refractories, B (2) 62*d*.

Aleksandrov, O. M. See Ivanov, V. E.

Alekseev, A. G., Vertsner, V. N., Zhukovskaya, O. V., Podushko, E. V., and Tikhomirov, G. P. Changes in the properties and structure of glass in the system Li_2O-Al_2O_3-SiO_2-TiO_2 during heat treatment over a wide temperature range, B (9) 246*e*.

Alekseev, A. G., and Zasolotskaya, M. V. Certain crystalline phases separating in glasses of the system Li_2O-Al_2O_3-SiO_2 with small amounts of TiO_2, B (9) 246*d*.

Alekseeva, E. A. See Dombrovskaya, N. S.

Alekseeva, N. A. See Kreimer, G. S.

Alekseeva, O. S. See Bokin, P. Ya.

Alekseeva, O. S., Bokin, P. Ya., Govorova, R. A., Korelova, A. I., and Nikandrova, G. A. Structural changes in lithium silicate and lithium aluminosilicate glasses during crystallization and their influence on mechanical properties, B (9) 246*b*.

Alekseevskaya, N. V. See Lakomkin, I. G.

Alexander, E. M. See Searight, C. E.

Alexander, G. B., and Sears, G. W., Jr. Thorium oxide sol, P (8) 182*e*.

Alexander, G. B., Stuart, R. E., and West, S. F. Composition comprising iron-group metal and particulate refractory metal oxide, P (8) 180*h*.

Alexander, G. B., West, S. F., and Yates, P. C. Process of making metal powder compositions wherein some metal grains contain dispersed refractory metal oxide particles, P (7) 153*i*.

Alexander, J. M., Jr. Tablet press, P (11) 289*b*.

Alfano, R. R., and Baird, D. H. Near-infrared rotation in GdIG as a function of temperature, (8) 203*d*.

Alford, H. E. Fibrous reinforcing materials having improved surface characteristics, P (1) 4*j*.

Alford, H. E., and Veatch, F. Lightweight structural units and method for producing, P (1) 5*i*.

Alfred Goslett Co., Ltd. Water closets, P (3) 75*c*.

Ali, M. A., Knapp, W. J., and Kurtz, P. Strength of sintered specimens containing hollow glass microspheres, (4) 93*a*.

Alietti, A. Identification of disordered kaolinites, (4) 108*e*.

Allegheny Ludlum Steel Corp. Coating for the protection of ferrous base alloys at elevated temperatures, P (4) 92*f*.

Allegretti, J. E. Semiconductor product and method for making same, P (9) 232*b*.

Allegretti, J. E., and Fisher, F. O. Doped semiconductor process and products produced thereby, P (8) 184*h*.

Allegrini, A. P. See Goldberg, M. M.

Allen, A. C. Advanced know-how improves container pack, (4) 92*j*. Automation speeds Maytag production, (5) 117*d*. Center floor storage simplifies porcelain enamel flow chart, (1) 2*f*. Centralab invests in facilities for future business, (1) 9*g*. Ceramic fuels speed nuclear age, (4) 96*g*. Ceramics give old materials new properties—the composite concept, (4) 112*g*. Ceramics play major role in new composites, (9) 216*b*. CerCom insulates space crafts, (9) 223*i*. Enameler reorganizes as giant job shop, (4) 91*i*. Fast tile press outpaces glaze line, (4) 99*h*. Ferrites skyrocket Indiana General's production, (9) 229*h*. Flexible porcelain enamel works on all metals, (9) 216*f*. Flotation furnace automates tempering line, (9) 218*c*. Giant china manufacturer diversifies, (4) 99*h*. Glass and ceramics add flexibility to microcircuit design, (5) 126*g*. Introduction to plastic [glass fiber] composites, (9) 218*f*. Japan's largest ceramic manufacturer exports half its production, (4) 99*i*. Kagaku Togyo widens scope with high alumina, (4) 99*i*. Less than 5% defects with direct-on, (1) 2*i*. 150 million feet per year, (4) 99*j*. Open planning speeds tile production, (1) 9*a*. Pilot shop tests new ideas in sanitary ware, (1) 9*a*. Porcelain enamel moves forward in appliance industry, (4) 92*a*. Specialty business grows from glass-making art, (4) 93*a*. Titanate ceramics, (1) 10*c*. Titanates stamped from continuous sheet, (4) 100*c*. Versatility in color keeps this enameler busy, (9) 217*a*. Vibration polishes vitrified china fast and efficiently, (9) 228*f*.

Allen, A. W. See Forlano, R. J.

Allen, Edgar, & Co., Ltd. See Edgar Allen & Co., Ltd.

Allen, F. M. Adjusting mechanism for gyratory crusher bowls, P (11) 291*c*.

Allen, G. W. See Brown, A. E.

Allen, J. W., Shyam, M., and Pearson, G. L. Gunn oscillations in indium arsenide, (8) 199*d*.

Allen, L. R. Process for forming niobium stannide superconductors, P (7) 157*f*.

Allen, L. R., Das, D. K., and Stauffer, R. A. Niobium stannide superconductor product, P (8) 185*e*.

Allen, L. R., and Stauffer, R. A. Method of forming intermetallic superconductors, P (4) 101*f*.

Allen, N. A. See Glaister, R. M.

Allen, R. V., Braman, R. W., McConnell, R. K., Jr., and O'Brien, J. L. Transmission electron microscopy of fine-grained rocks, (2) 51*a*.

Allen, W. C. X-ray method for defining composition of a magnesium spinel, (2) 60*f*.

Allen, W. R. Gyratory crusher and method of crushing and grinding ore, P (7) 160*j*.

Allen-Bradley Co. Welded terminal resistor, P (10) 265*i*.

Allied Chemical Corp. Conversion of caustic soda to soda ash, P (9) 235*f*. Process for cavity wetting, P (11) 289*b*. Production of ultrafine ferric oxide by reacting ferric chloride with nitrogen dioxide, P (11) 292*c*.

Allinson, J. D. Uranium carbide-refractory metal interactions at high temperature, (7) 152*g*.

Allis-Chalmers Mfg. Co. Batch blender, P (11) 288*g*. Cooler for rotary kiln, P (1) 14*i*. Grinding wheels and stones of oxide bonded Bi_2P_2 and method of producing same, P (2) 33*g*. Impact grinding, P (11) 291*h*. Method of flame spraying graphite to produce a low friction surface, P (2) 35*e*. Method and furnace for heat-treating minerals, P (8) 190*i*. Method of sintering aluminum nitride refractories, P (2) 44*c*. Multiple compartment grinding mills, P (4) 106*i*. Rotary kiln with preheater, P (3) 82*b*.

Allnatt, A. R. Concentration of impurities in the surface layers of an ionic crystal, (8) 192*g*.

Allpress, J. G. Crystal structure of barium diuranate, BaU_2O_7, (8) 193*c*.

Alonso, J. J. Geology of bauxite and high alumina materials, B (2) 62*e*.

Alper, A. M., Doman, R. C., and McNally, R. N. Fused refractory castings, P (11) 281*f*.

Alper, A. M., Doman, R. C., and Papa, P. Refractory casting, P (11) 283*b*.

Alper, A. M., and McNally, R. N. Basic refractory, P (7) 152*j*. MgO-B_2O_3 fused cast refractory, P (11) 282*i*. Refractory and furnace lining, P (1) 8*f*, P (3) 73*e*.

Alper, A. M., McNally, R. N., and Papa, P. Magnesium oxide casting, P (10) 259*b*.

Altebrando, P. T. See Gross, S. B.

Altman, R. L. Heat of formation of $MgAl_2O_4$, (8) 199*j*.

Altmann, B. G. See Elmer, J. T.

Altmeyer, G. See Dawihl, W.

Aluminium Laboratories, Ltd. Magnesium hydroxide and method of preparation, P (9) 226*a*. Method of preparing magnesia spinel, P (5) 124*d*. Recovery of magnesium compounds from ores, P (2) 54*d*. Refractory gas seal, P (7) 154*f*.

Aluminum Co. of America. Refractory composition, P (3) 73*d*.

Alvarez-Estrada, D. High alumina refractories, B (2) 62*e*. Stoneware, (5) 125*f*. Zirconium compounds in the refractories industry, B (2) 62*d*.

Alvarez-Estrada, D., and Aza Pendas, S. de. Analysis of a Spanish sintered magnesia, (5) 122*c*.

Alvarez-Estrada, D., and Duran Botia, P. Effect of V_2O_5 on the sintering and grain growth of magnesium oxide, (5) 122*g*.

Alvarez Herrero, C. See Burriel Marti, F.

Alviset, L., and Arle, G. Hot extrusion, (3) 70*f*.

Alyanakyan, S. A. See Reisman, A.

Amalric, P. SOVIREL, (1) 4*e*.

Amans, R. L. Light transmitting electrode including *n*-type semiconductive In_2O_3, P (3) 78*a*.

Amato, I., Colombo, R. L., and Polin, F. Dependence on microstructure of the high temperature properties of uranium oxide-molybdenum and uranium oxide-tungsten cermets, (2) 41*k*.

Amato, I., Colombo, R. L., and Protti, A. M. Pore growth during solarization of sintered UO_2, (7) 152*a*.

Ambrogi, R. R. Molten glass dispensing plunger needle, P (10) 255*j*.

Amelco, Inc. Transistor with elongated base and collector current paths, P (2) 49*d*.

Amelinckx, S. See Spyridelis, J.

American Air Filter Co., Inc. Method and apparatus for making filamentous mats, P (5) 121*b*. Method for making filamentous mats, P (7) 150*b*.

American Can Co. Method of and apparatus for classifying glass bottles, P (4) 94*e*.

American Cement Corp. Apparatus for alkali metal condensation in cement kilns, P (3) 64*b*.

American Concrete Institute, Committee 116. Glossary of terms on cement and concrete technology, (3) 64*c*.

American Concrete Institute, Committee 322. Structural plain concrete (7) 147*d*.

American Cyanamid Co. Oxidation catalyst for hydrocarbon combustion exhaust gases, P (2) 44*j*. Pigment via plasma jet-improved preheater configuration, P (9) 226*c*. Process for the oxidation of $TiCl_4$, P (11) 291*f*. Superconducting compositions, P (4) 102*h*. Water resistant plasters, P (10) 249*d*.

American Gas Association, Inc. Heated-gas system with apparatus for removing gas-borne foreign bodies, P (5) 124*i*.

American Home Products Corp. Method of attaching a metal hypodermic needle to a glass ampoule, P (1) 5*h*.

American Instrument Co., Inc. Method for pneumatically elutriating solid particles, P (3) 81*f*.

American Olean Tile Co., Inc. Tile sheet-backing apparatus, P (3) 75*a*.

American Optical Co. Fiber type energy-conducting structures and method of making same, P (1) 4*i*. Infrared image transmitting fiber devices, P (4) 94*j*. Lens aligning and blocking apparatus, P (1) 5*h*. Lens holder, P (11) 278*d*. Method of making fiber optical image transfer device, P (1) 6*b*. Method of making light-conducting optical component, P (1) 6*d*. Method of making light-conducting optical multifiber structures, P (9) 221*h*. Method of making multichanneled electron multiplier component, P (10) 264*b*. Method of making ophthalmic lens, P (11) 279*d*. Method of sealing fiber optic plates, P (5) 121*g*. Optical resonant cavities, P (5) 121*c*. Radiation absorption heating of a bundle of glass fibers, P (9) 222*c*.

American Pipe & Construction Co. Impact-actuated spring system for producing vibrations in a rotating form, P (5) 130*g*.

American Potash & Chemical Corp. Process for producing rare earth containing glass polishing agents, P (7) 150*d*. Process for treating a gaseous mixture containing titanium dioxide, P (7) 161*b*. Rare earth oxide and vanadate phosphors, P (9) 232*g*. Separately crystallizing boric acid and alkali sulfate from aqueous solution by evaporation at different temperatures, P (11) 292*e*.

American Pulverizer Co. Automatic clearing mechanism for crushers, P (10) 269*i*.

American Radiator & Standard Sanitary Corp. Conveying mechanism for a tunnel kiln, P (11) 290*h*. Kiln car lubrication system, P (9) 235*c*. Kiln and related apparatus, P (11) 290*e*. Method of soldering semiconductor disks, P (2) 48*d*.

American-Saint Gobain Corp. Glass cutter, P (1) 5*e*.

American Smelting & Refining Co. Concentration of asbestos ore, P (9) 235*j*.

American Tansul Co. Amine modified clay and method, P (4) 106*i*.

American Thermocatalytic Corp. Cement composition, P (2) 34*i*.

American Zinc Co. Production of silica lamellas, P (9) 236*c*.

Ames, L. L., and Barrow, R. F. Rotational analysis of absorption bands of CeO, (7) 167*e*.

Ames, S. L., Malagari, F. A., Jr., and Conner, J. R., Jr. Coating for the protection of ferrous base alloys at elevated temperatures, P (4) 92*f*.

Amicon Corp. Refractory coatings for metal surfaces, P (10) 250*f*.

Amirova, S. A., Pechkovskii, V. V., and Kurmaev, R. Kh. Solubility of vanadium trioxide in melts of the chlorides of sodium and potassium, (8) 207*g*.

Ammar, A. A., and Budworth, D. W. Sintering of sodium chloride, B (7) 170*h*.

Amos, K. L. Ball and pebble mills (1), (10) 266*a*; (11), (11) 288*d*.

Ampex Corp. Fluxes for sintering lithium ferrites, P (4) 101*f*.

Ampian, S. G. Lime-soda sinter process—correlation of reaction products with extractability of alumina from anorthosite, (10) 269*d*. See Miller, J. L., Jr.

Amrhein, E. M. Dielectric loss of inorganic and organic glasses in the microwave range, B (2) 61*i*.

Anaconda Wire & Cable Co. Porous-refractory encapsulant for coils and coil encapsulated therewith, P (5) 124*g*. Pyrolyzable enamel from Mn and Co chelates, glass, and siloxane resin, P (3) 65*f*.

Anandan, N. S. See Rao, S. V. K.

Ananich, N. I., and Botvinkin, O. K. Oriented structure of inorganic glasses, B (7) 171*b*.

Anazawa, S. See Urushida, K.

Andersen, A. B. Apparatus for the heat treatment of finely divided materials, P (7) 160*d*.

Andersen, J. C. See Taylor, K. M.

Andersen, W. Cylinder for glass bottle making machine, P (1) 4*h*.

Anderson, A. R., Stickney, T. M., and Gordon, D. W. High temperature measuring devices, P (7) 159*g*.

Anderson, D. E. See Springer, R. H.

Anderson, D. W. Meaning of markings, (10) 247*f*.

Anderson, E. L. Method of and mold for forming hollow articles, P (11) 279*e*.

Anderson, G. S. Apparatus for cathode sputtering including a plasma-confining chamber, P (3) 77*j*.

Anderson, H. G. See Palmer, A. L.

Anderson, H. U. Initial sintering of rutile, (7) 164*d*. See Payne, D. A.

Anderson, J. H. See Parks, G. A.

Anderson, J. R., and Tare, V. B. Reaction of oxygen with evaporated films of lead, (8) 183*h*.

Anderson, J. S. Consequences of nonstoichiometric behavior of refractory materials at high temperatures, B (5) 140*b*.

Anderson, J. T., and Shepherd, R. Preparation of selenides and tellurides, P (5) 128*e*.

Anderson, O. L. Lattice dynamics of glass, B (2) 61*g*, B (7) 171*f*. See Soga, N.

Anderson, P. J., Horlock, R. F., and Avery, R. G. Some effects of water vapor during the preparation and calcination of oxide powders, B (7) 169*i*.

Anderson, P. J., Horlock, R. F., and Oliver, J. F. Interaction of water with the magnesium oxide surface, (7) 164*d*.

Anderson, R. C., and Curran, M. J. Sealing a membrane to a target support metal ring, P (3) 69*e*.

Anderson, R. E. See Goodenough, R. D.

Anderson, R. H. Combined direct viewing storage target and fluorescent screen display structure, P (11) 285*a*. Thin porous storage phosphor layer, P (3) 79*i*.

Anderson, R. M. Flash lamp manufacture, P (5) 120*f*. Method of manufacturing photoflash lamps [exhaust tip], P (8) 178*h*. Photoflash lamp, P (5) 121*d*.

Anderson, W. B. Brickmaking machine and process, P (2) 40*g*.

Anderson, W. G. See Van Dreser, I. L.

Andersson, S. Crystal structure of $NaNb_6O_{15}F$ and $NaNb_6O_{15}OH$, (8) 193*h*. Crystal structure of a new silver vanadium oxide bronze, $Ag_{1-x}V_2O_5$ (x approx 0.32), (8) 193*a*. Two new niobium oxide fluorides formed at high temperature, (8) 210*j*. See Lundberg, M.

Andersson, S., and Astrom, A. Thermal decomposition of NbO_2F, (8) 209*g*.

Andersson, S., and Wadsley, A. D. Crystal structure of $K_2Ti_2O_5$, (3) 84*a*.

Ando, J. X-ray diffraction patterns of various glasses, (4) 93*e*.

Ando, J., and Matsuno, S. Thermal change of phosphate rocks, (3) 82*j*.

Andrae, K. H. Continuous muller, P (3) 80*a*.

Andre, S. N. Ferrite stripline circulator having closed magnetic loop path and centrally located conductive foil overlying radially extending center conductors, P (10) 263*j*.

Andreae Automation Industrielle S. A. Process for equalizing the temperature of a tunnel kiln and tunnel kiln for utilizing the process, P (10) 268*i*.

Andreasen, A. H. M., and Tabakovic, B. Mechanism of the dissolution of a powder, (5) 137*c*.

Andreev, B. S., and Bondarev, D. E. Manufacturing technology of scandium-containing ferrites, (10) 262*h*.

Andreev, N. S. See Aver'yanov, V. I.

Andreev, N. S., and Aver'yanov, V. I. Structural investigations of sodium silicate glasses in the region of metastable phase separation, B (7) 171*h*.

Andreev, N. S., Aver'yanov, V. I., and Porai-Koshits, E. A. Investigation of the structure of low-alkali sodium silicate glasses by the scattering of visible light and by electron microscopy, B (5) 141*h*.

Andreeva, A. B. See Keler, E. K.

Andreeva, T. V., Barantseva, I. G., Dudnik, E. M., and Yupko, V. L. Some physical properties of aluminum nitride, (8) 207*i*.

Andrew, K. F. See Gulbransen, E. A.

Andrews, E. H. Destruction of silicon nitride whiskers by reaction with metals at high temperatures, (9) 223*h*.

Andrievskii, A. I., Karelin, N. N., and Yuskevich, Yu. G. Effect of different oxide additions on the electrical and magnetic properties of copper-manganese ferrites, (10) 262*d*.

Andryukhina, T. D. Dependence of the density of glass on its thermal history, B (7) 171*e*.

Andryushchenko, Yu. I. See Bergman, A. G.

Angell, C. A. Free volume model for transport in fused salts—electrical conductance in glass forming nitrate melts, (8) 198*g*. Success of free volume model for transport in fused salts, (8) 208*d*.

Angell, C. A., and Tomlinson, J. W. Self-diffusion in molten lead and thallous chlorides, (7) 167*f*.

Angstadt, R. L., and Hurley, F. R. Spodumene accelerated portland cement, P (10) 249*d*.

Anokhin, V. Z. See Ugai, Ya. A.

Anritsu Electronic Works, Ltd. Negative resistance semiconductor devices, P (10) 265*c*.

Anselin, F., and Pascard, R. Process for the preparation of metallic nitrides, P (9) 226*j*. Uranium monocarbide-plutonium mononitride nuclear fuel, P (7) 154*f*.

Ansell, G. S. See Cooke, F. W.

Anson, M., and Newman, K. Effect of mix proportions and method of testing on Poisson's ratio for mortars and concretes, (9) 214*h*.

Anstalt fuer technische Entwicklung und Verwertung. Refining agent for steelworks, P (8) 182*b*.

Antal-Boza, J. Slag infiltration into the refractory lining of furnaces, B (5) 141*i*.

Anthes, L. B. Heavy medium separation media and process, P (4) 106*b*.

Anthony, A. M. See Guillot, A.; Loup, J. P.

Anthony, A. M., Guillot, A., Sata, T., and Bourgeois, J. L. Electrical conductivity of pure zirconia and ceramic compounds of zirconium between 1500° and 2400°K. (2) 46*i*.

Anthrop, D. F., and Searcy, A. W. Sublimation and thermodynamic properties of zinc oxide, (8) 208*d*.

Antoniou, A. A. Phase transformations of water in porous glass, (8) 175*i*.

Antonov, G. I. See Minkovich, B. D.

Antonova, L. I. See Eliseev, A. A.

Antonova, N. S. See Kostyukov, H. S.

Aoki, I. Cation distribution in $CuMn_2O_4$, (9) 237*g*.

Aoki, T. See Furukawa, Y.

Aplet, L. J., Jay, E. B., and Sooy, W. R. Effect of surface finish on temperature distribution in optically pumped Nd^{3+} glass laser rods, (5) 135*f*.

Arabadzhan, A. S. See Bergman, A. G.

Arabadzhan, A. S., and Bergman, A. G. Quaternary reciprocal system of the chlorides and bromides of lithium, sodium, and potassium, (7) 167*b*.

Arai, Z., Hayashi, H., Nakamura, Sen-ich, and Azuma, N. Synthesis of titanium nitride from sponge titanium and nitrogen or ammonia, (5) 139*a*.

Araki, H. See Seki, H.

Aranson, S., and Sadofsky, J. Thermodynamic properties of nonstoichiometric thorium monocarbide, (8) 210*f*.

Araujo, R. J. Phototropic glass article and method of making it, P (9) 222*a*.

Araujo, R. J., Eppler, R. A., and Krause, E. F. Phototropic glass article, P (9) 222*a*.

Aravamudan, V., Rao, Y. D. P., and Raghavan, R. Chemical beneficiation of ilmenite, (11) 290*f*.

Aravamudan, V., Sundaram, M., and Palaniappan, R. C. Use of Saurashtra bauxite for production of fused alumina, (11) 291*b*.

ARBED. See Acieries Reunies de Burbach-Eich-Dudelange, Soc. Anon.

Arbel, A. Deformation properties of a polycrystalline KCl-NaCl alloy, (3) 84*g*.

Arcari, A. D. Brick wall panel and method of making, P (10) 256*e*.

Archambault, M. Production of zeolites and lithium salts, P (7) 161*c*.

Archer-Daniels-Midland Co. Liquidless foundry molding process, P (5) 124*b*.

Arcos Corp. Welding flux and method of welding, P (10) 250*g*.

Arend, H., Coufova, P., and Novak, J. Chemical processes during hydrogen reduction of barium titanate crystals, (2) 54*h*.

Arend, H., Suk, K., and Novak, J. Defect structure of oxygen deficient $BaTiO_3$, (10) 270*g*.

Arey, W. F., Jr., and Adams, C. E. Agglomeration of crystalline aluminosilicate zeolites, P (9) 235*g*.

rgano, E. S. See Low, M. J. D.

rgue, G. R., and Stewart, R. F. Electrical [solion] device with closely spaced electrodes and method for making same, P (3) 78*b*.

Arias, A. Apparatus for positioning and loading a test specimen, P (9) 334*c*. Effect of inclusions on grain growth of oxides, (1) 18*g*.

Arin, M. L. See Greenbaum, M. A.

Aring, K., and Sievers, A. J. Thermal conductivity and far-infrared absorption of [single-crystal] UO_2, (8) 209*f*.

Arita, K. See Pastor, R. C.

Ariya, S. M., and Khernburg, M. M. Metal-to-metal binding energy in lattices of unsaturated oxides of elements of supplementary subgroups, (11) 298*e*.

Arkel, A. E. van. Superconductor comprising a niobium substrate having a coating of niobium stannide and particles of a ferromagnetic material, P (11) 287*j*.

Arkhipov, G. G., and Stepanov, G. K. Anodic polarization of a platinum electrode surrounded with hydrogen in molten carbonates, B (1) 30*d*.

Arkless, K. See Evans, A. W.

Arle, G. See Alviset, L.

Arlett, R. H., Di Vita, S., and Smoke, E. J. Methods for controlling the thermal expansion properties of ceramics, P (7) 155*d*.

Arlett, R. H., and Robbins, M. Growth of stoichiometric $MgAl_2O_4$ single crystals, (7) 164*a*.

Arlett, R. H., Robbins, M., and Herkart, P. G. Growth of large sapphire cyrstals from cryolite, (2) 55*c*.

Armour, F. K., and Touzalin, R. E. Refractory-lined blast furnace tuyere, P (11) 283*e*.

Armour & Co. Flexible coated abrasive product, P (10) 247*f*.

Armstrong, R. W. Cleavage crack propagation within crystals by the Griffith mechanism vs. dislocation mechanism, (11) 292*j*.

Armstrong, W. J. See Hess, M. S.

Armstrong, W. M., and Irvine, W. R. Creep of urania base solid solutions, (8) 192*i*.

Armstrong, W. P. See Getty, R. J.

Arnaud, E. Refining agent for steelworks, P (8) 182*b*.

Arndt, H. H., Schaedel, J., and Renner, T. Controllable semiconductor devices with a negative current-voltage characteristic and their manufacture, P (9) 230*a*.

Arndt, H. H., Schaedel, J., and Uebel, H. Process of open-type diffusion in semiconductor by gaseous phase, P (8) 186*a*.

Arnold, C. S., and Rolseth, H. C. Thermal mechanical mineral piercing, P (9) 236*i*.

Arnold, G. P. See Bowman, M. G.

Arntz, F., and Chernow, F. Optical and structural properties of oxidized titanium films, (1) 24*a*.

Aronson, H., and Schaeffler, L. How to make your own glazes (IV) making transparent glazes opaque; (V) line and ladder blends, (4) 90*a*.

Aronson, S., Cisney, E., and Gingerich, K. A. Thermal expansion of some cubic refractory compounds of thorium, (7) 169*c*.

Arridge, R. G. C., and Heywood, D. Freeze-coating of filaments of glass and SiO_2, (7) 148*h*.

Arsenault, R. J. Low-temperature deformation techniques, B (8) 211*i*.

Arshakuni, A. A. See Speranskaya, E. I.

Artamonov, A. Ya. Problem of calibrating porous cermet bearings, (3) 71*c*.

Artamonova, N. V., and Ignatova, V. A. Synthesis of materials in the SiO_2-B_2O_3-Sb_2O_3 system—high-silica foam materials, (2) 57*c*.

Artelt, P. Use of the Schmidt concrete testing hammer for the evaluation of refractory brick, (2) 43*g*.

Artemov, V. R. Nature of the splitting of rhodesite into fibers, (11) 298*a*.

Arthur D. Little, Inc. Method of making composite materials and resulting products, P (5) 130*b*. Refractory coated casting mold, P (2) 35*g*.

Arthur, G., and Coulson, J. A. Physical properties of uranium dioxide-stainless steel cermets, (7) 151*j*.

Arthurs, J. K. See Dunster, D. F. T.

Arzo, F. B. See Balaguer Arzo, F.

Asada, C. Results of service test on electric arc furnace roof constructed of all-rammed high alumina refractory, (11) 281*b*.

Asahi Glass Co., Ltd. Aqueous metal iodide solution for use as an X-ray contrast agent, P (8) 188*a*. Method of and apparatus for automatically cutting a glass ribbon, P (2) 39*b*. Method for the treatment of raw glass material containing easily volatilizable ingredients, P (3) 69*c*.

Asai, T. See Kishii, T.

Asanabe, S. Conduction phenomena in monosilicides of iron group transition elements, (10) 270*h*.

Asano, T. Method for the preparation of cement, P (4) 91*d*.

Asbrink, S. Structure of the spinel $CuMn_2O_4$, (8) 207*j*.

Ascast Corp. Graphite continuous casting mold, P (5) 124*i*.

Aschan, N. Determining the setting time of cement paste, mortar, and concrete with a copper-lead electrode, (9) 214*c*.

Aschkenasy, H. See Hurwitz, M. J.

Ascoli-Bartoli, U., Benedetti-Michelangeli, G., and Lovisetto, L. Faraday-switched ruby laser, (8) 183*i*.

Ashbee, K. H. G. Multiple electron diffraction—application to evaporating UO_{2+x}, (8) 202*i*.

Ashby, M. F., and Ebeling, R. Determination of the number, size, spacing, and volume fraction of spherical second-phase particles from extraction replicas, (8) 194*a*.

Ashkin, A., and Gershenzon, M. Semiconductor light modulators, P (4) 102*e*.

Ashworth, R. Apparatus for laboratory freezing-and-thawing tests on concrete specimens, (11) 274*h*.

Aslanov, L. A., and Kovba, L. M. Trisulfides of barium and tantalum, titanium, and zirconium, (11) 303*a*.

Aslanov, L. A., Simanov, Yu. P., Novoselova, A. V., and Ukrainskii, Yu. M. Variable composition phases in the tantalum-selenium system, (11) 303*b*.

Aslanov, S. M. See Zakharchenko, M. A.

Aslanova, M. S. Properties of inorganic fibers (glass) of different vitreous systems, B (2) 62*c*.

Aslanova, M. S., and Vol'skaya, S. Z. Strength and structure of fibers from borate, cadmium, and lead glasses, B (7) 171*h*.

Asquith, M. Glass article forming apparatus, P (2) 38*g*.

Associated Electrical Industries, Ltd. Ceramic to metal joints, P (1) 3*b*. Electric incandescent lamps, P (2) 38*d*. Glass-to-metal seals, P (1) 10*h*. Method of producing semiconductor devices by employing vitreous material, P (5) 128*i*. Preparation of cermets, P (8) 181*j*. Preparation of selenides and tellurides, P (5) 128*e*. Quartz-to-metal seals, P (9) 232*g*.

Associated Lead Manufacturers, Ltd. Ceramic stains, P (4) 100*a*. Manufacture of antimony trioxide, P (10) 269*f*. Stains for ceramic glazes, P (7) 155*d*.

Associated Portland Cement Manufacturers, Ltd. Hydraulic cement, P (9) 215*h*.

Astbury, N. F. Introduction to pores and properties, (11) 289*j*. See Popper, P.

Astbury, N. F., Moore, F., and Lockett, J. A. Cyclic torsion test for the study of plasticity, (2) 45*j*.

Astrom, A. Crystal structures of $Nb_{12}O_{29}F$ and $Nb_{17}O_{42}F$, (10) 270*e*. See Andersson, S.

Atak, S. See Fuerstenau, M. C.

Ateliers Heuze, Malevez et Simon Reunis Societe Anonyme. Devices for dismounting and remounting [sheet] driving rollers, P (11) 278*d*.

Atkeson, F. V. Method and apparatus for generating currents in molten glass, P (5) 120*j*. Process of annealing glass sheets, P (7) 150*b*.

Atkins, A. G. LPG—its character and properties, (11) 290*d*.

Atkins, A. G., Silverio, A., and Tabor, D. Indentation hardness and the creep of solids, (8) 200*a*.

Atkins, A. G., and Tabor, D. Hardness and deformation properties of solids at very high temperatures, (8) 199*e*. Mutual indentation hardness of single-crystal magnesium oxide at high temperatures, (5) 137*j*.
Atkinson, E. J. Article grouping device, P (2) 38*j*.
Atlas, L. M., Schlehman, G. J., and Readey, D. W. Defects in PuO_{2-x}—density measurements at high temperature, (1) 17*c*.
Atlas Mess- und Analysentechnik G.m.b.H. Method for determining the specific surface of nonuniformly shaped substance by measuring the adsorption of noble gases or inert gases at the specimen to be investigated, P (5) 132*b*.
Atlee, Z. J. See Gager, R. M.
Ato, Y. See Huzimura, R.
Atomenergi A. B. Method for the production of glass, P (5) 121*g*.
Atomic Energy of Canada, Ltd. Method for the production of semiconductor lithium-ion drift [germanium] diodes, P (10) 264*i*. Nuclear fuel elements, P (10) 260*a*.
Atomic Power Development Associates, Inc. Reinforced ceramic fuel elements, P (2) 45*g*.
Aton Pianungs- und Baugesellschaft fuer die Keramische Industrie m.b.H. Indirectly heated tunnel kilns, P (1) 14*j*. Tunnel kiln for the firing of ceramic ware, P (1) 15*c*.
Atsukawa, M., Nishimoto, Y., Iwaiya, Y., and Kuwabara, H. Process of recovering valuable components from red mud, P (7) 161*a*.
Atwell, E. C. Polyvinyl chloride resin glass bond with secondary amino-alkyl silane primer, P (8) 178*e*.
Audesse, E. G. See Palermo, J. J.
Augsburger, H. M. Means for controlling electric currents in a glass furnace, P (9) 220*c*.
August, W. S. Glass-to-metal seals in electronic devices, P (5) 127*e*.
Austerman, S. B., and Chang, R. Diffusion and creep in beryllium oxide, (8) 194*f*.
Austerman, S. B., and Gehman, W. G. Inversion twin—prototype in beryllium oxide, (11) 297*j*.
Austin, J. F. See Baker, C. L.
Austin, L. G. See Klimpel, R. R.
Austin, L. G., and Klimpel, R. R. Theory of grinding operations, (7) 158*g*.
Automated Pottery Machinery, Ltd. Rotary work supporting machine for use in the pottery industry, P (3) 75*d*.
Automatic Electric Laboratories, Inc. Crystal oven heating and control system, P (4) 100*j*.
Automation Products, Inc. Apparatus for measuring viscosity, P (3) 81*c*.
Auzins, P. See Wertz, J. E.
Avarbe, R. G. Thermodynamic stability of monocarbides of transition metals from subgroups IV to VI, (8) 210*h*. See Nikol'skaya, T. A.; Vil'k, Yu. N.
Avarbe, R. G., and Vil'k, Yu. N. Calculation of the temperature and concentration dependence of some thermodynamic functions of NbC_x phases, (8) 191*j*.
Avco Corp. Method of monitoring pressure sintering procedures, P (1) 11*g*. Process for making carbides of fissionable and fertile materials, P (2) 45*b*.
Avdeev, N. Ya. Problems in sedimentation dispersion analysis, (10) 267*e*.
Aveline, M., and Pagano, M. Technique for the use of variable resistance strain gages for measurement of the strains set up in ceramic tile during the setting of the fixing cement, (7) 155*e*.
Aven, M. See Halsted, R. E.
Averbukh, B. D. See Brainina, D. Z.
Avery, F. J. Photoceramic process for producing vitrified photographic images, P (11) 283*j*.
Avery, R. G. See Anderson, P. J.
Avery, W. H. Temperature measuring device, P (7) 159*h*.
Aver'yanov, V. I. See Andreev, N. S.; Porai-Koshits, E. A.; Totesh, A. S.
Aver'yanov, V. I., Andreev, N. S., and Porai-Koshits, E. A. Critical phenomena in sodium silicate glasses, B (2) 62*b*.
Aver'yanov, V. I., and Porai-Koshits, E. A. Electron microscopic investigation of heterogeneous structure and initial crystallization stages of glasses in the system Li_2O-SiO_2, B (5) 141*h*. Electron microscopic investigation of phase separation in glasses of the lithium silicate system, B (7) 171*h*.
Avetisyan, E. M. See Kostanyan, K. A.
Avgustinik, A. I., and Sintsova, I. T. Study of processes preceding crystallization of glasses, B (9) 246*b*.
Avnet-Shaw Corp. Manufacture of ceramic shapes or bodies, P (7) 158*j*.
Axe, J. D. See Weller, P. F.
Axe, J. D., and O'Kane, D. F. Infrared dielectric dispersion of $LiNbO_3$, (8) 183*j*.
Aza Pendas, S. de. See Alvarez-Estrada, D.
Azarov, K. P., Balandina, V. V., and Lyutsedraskii, V. A. State of the transition elements in glass structures, B (7) 171*d*.
Azarov, K. P., Grechanova, S. B., and Shcherbak, T. I. Wetting and bonding of ceramic coatings with metals, (3) 65*a*.
Azbe, V. J. Calcining method and apparatus, P (2) 34*h*. Lime production, P (2) 35*a*.
Azbe Corp. Calcining method and apparatus, P (2) 34*h*. Lime production, P (2) 35*a*.
Azeem, M. Determination of sulfate in the presence of soluble silicate, (5) 130*j*.
Azelitskaya, R. D. See Budnikov, P. P.
Azuma, K., Ohta, K., and Tomita, T. Crystal structure of SiC 39H, (7) 162*a*.
Azuma, N. See Arai, Z.
Baab, K. A. See Osterholtz, C. E.
Baak, N. T. E. A. Method and article formed by sealing alumina ceramic to a metal with a sealant glass, P (10) 255*e*. Method for controlling the rate of devitrification, P (4) 94*i*.
Baak, T., and Frederick, R. L. Polarography in molten sodium disilicate, (2) 37*b*.
Baak, T., and Hornyak, E. J., Jr. Antimony in glass (I,II), (2) 36*c*.
Baas, G., and Tacken, P. J. M. Current leadthrough member, P (1) 4*k*.
Babcock, C. L. Colored glasses and process of manufacture, P (9) 219*c*. See Rapp, J. E.
Babcock, K. See Brixner, L. H.
Babcock & Wilcox Co. Insulating firebrick, P (7) 153*e*. Method of producing ceramic nuclear fuel material having incorporated therein burnable poison, P (8) 181*f*. Process for making nuclear fuel materials, P (8) 182*a*. Process of manufacturing refractory fibers, P (9) 226*i*.
Babcock & Wilcox, Ltd. Apparatus for firing pulverized fuel, P (2) 52*j*. Cyclone furnaces, P (3) 82*b*. Dust feeding means, P (2) 50*b*. Storage means for radioactive fuel elements, P (2) 45*i*. Strip cladding flux, P (5) 117*i*.
Babu, V. H., Sirdeshmukh, D. B., and Bansigir, K. G. Rotation of etch pits on (001) surface of sodium chloride, (8) 206*e*.
Baburek, J., and Stoerr, M. Investigation of the mineralogy and preparation of the kaolins of Ledce (Plzen Basin, Czechoslovakia), (3) 82*j*.
Babushkin, V. I., Matveev, G. M., and Mchedlov-Petrosyan, O. P. Thermodynamics of Silicates, B (5) 142*f*.
Bach, R. O. Lithium oxide having active absorption capacity for carbon dioxide and method of preparing same, P (9) 235*j*.
Bachman, G. S. Element for measurement of furnace wall thickness and temperature, P (5) 132*d*.
Bacle, B. See Calleja, J.
Bacon, F. R., and Calcamuggio, G. L. Effect of heat treatment in moist and dry atmospheres on chemical durability of soda-lime bottles, (10) 251*d*.
Baczewski, A. Epitaxial growth of ZnSe on GaAs, (10) 262*j*.
Bade, E. Method of and apparatus for recovering substances with a high alkali percentage from the flue gases of cement kilns, P (2) 35*b*. See Mueller, H. G.
Badger, A. E. See O'Connell, T. B.; Oelke, W. W.
Badger, A. E., and Herbert, J. W. Apparatus for inhibiting upward rising bubbles in a molten metal bath, P (10) 254*j*.
Badger, A. E., and Schafer, C. B. Means for maintaining sheet width while drawing sheet glass, P (3) 68*d*.
Badische Anilin- & Soda-Fabrik Akt.-Ges. Dyed and printed glass fibers and a process for dyeing and printing glass fibers, P (8) 177*c*. Production of a manganese oxide suitable for the production of ferrites, P (4) 102*j*. Rotary shaft kilns for calcining granular or lumpy materials, P (4) 105*h*.
Badygina, L. I. See Gromakov, S. D.
Badzer, F. G. See Lenton, K. W.
Baertschi, P., Guten, H. R. von, and Zuest, H. E. Method for reprocessing fuel elements with fissionable material in carbide form which are spent in nuclear reactors, P (8) 181*k*.
Baginski, W. A. See Regan, R. E.
Baglietto, M. Relation between technology and ceramic art, (4) 90*a*.
Bagrov, A. A. New model of spherical rotary viscometer for the rheological investigation of highly concentrated, structured, polydisperse systems, (10) 267*j*.
Bahl, J. K. See Moorthy, V. K.
Bahramian, B. See Hughes, B. P.
Bahun, C. J. See Gates, L. E., Jr.
Bai, A. S. See Lainer, D. I.
Baier, E., Deeg, E. W., and Constabel, H. G. Radiochemical investigation of the adsorption of orthophosphate on two ternary borate glasses (I), (10) 253*e*.
Bailey, A. R. Introductory Practical Metallography, B (4) 113*f*. Role of Microstructure in Metals, B (4) 113*f*.
Bailey, B. L. Apparatus and process for continuously making baked and graphitized carbon bodies, P (2) 43*d*.
Bailey, D. F. Molding ceramic composition, P (2) 46*e*.
Bailey, D. J., and Flanagan, W. F. Relation between dislocation density and flow stress in materials deforming by a Peierls-Nabarro mechanism, (10) 271*g*.
Bailey, D. K., and Schairer, J. F. System Na_2O-Al_2O_3-Fe_2O_3-SiO_2 at 1 atmosphere and the petrogenesis of alkaline rocks, (2) 57*h*.
Bailey, T. W. Plural tapered refractory blocks and tightly fitting metal case therefor, P (11) 282*c*. Refractory construction, P (1) 8*e*.
Bailey Meter Co. Multizone furnace temperature and atmosphere control, P (8) 189*c*.
Bair, G. J. General aspects of glass science and technology, (2) 30*f*.
Baird, A. K., and Zenger, D. H. Use of the soft X-ray spectrograph and the electron-probe microanalyzer for determination of elements carbon through iron in minerals and rocks, B (5) 139*h*.
Baird, D. H. See Alfano, R. R.
Bakalar, D. Means and method of sealing glass encapsulated diodes, P (7) 156*h*.
Baker, A. A. See Cratchley, D.
Baker, A. A., and Cratchley, D. Stress-strain behavior and toughness of a fiber-reinforced metal, (9) 216*i*.
Baker, A. A., Mason, J. E., and Cratchley, D. High-strain fatigue studies of a composite material, (9) 216*f*.
Baker, B. H. See Schroth, P.
Baker, B. O., and Wheldon, R. J. Low pressure gas-filled discharge device having an envelope comprising metal parts at different potentials in operation insulated from one another by ceramic members, P (11) 285*j*.
Baker, C., Instruments, Ltd. Illuminating apparatus for a microscope system using polarized light, P (1) 14*d*.
Baker, C. L., and Austin, J. F. Nonreflective glass coatings, P (4) 95*g*.
Baker, D. M. Ceramic supports, P (3) 74*j*.
Baker, E. H. Barium oxide-carbon dioxide system in the pressure range 0.01 to 450 atmospheres, (8) 191*b*.
Baker, J. E., Co. Refractory material, P (7) 154*a*.
Baker, M., and Laurenson, L. Use of a quartz crystal microbalance for measuring vapor backstreaming from mechanical pumps, (9) 234*f*.
Baker, R. N. Apparatus for press forming and tempering of glass, P (1) 4*e*.
Baker, T. C., and Mathias, R. G. Apparatus for measuring the resistivity of molten glass, P (11) 277*h*.
Baker, W. E. See Michaels, A. S.
Baker, W. T. See Tattersall, G. H.
Bakker, W. T., and Lindsay, J. G. Alumina-bonded refractories, (7) 151*b*. Method of preparing magnesia spinel, P (5) 124*d*.
Bakum, S. I. See Safonov, V. V.
Bakumskaya, E. L. See Berezina, S. I.; Bergman, A. G.
Bakyrdzhiev, I. Influence of porosity on the content of structural water in silica gel and its thermal dehydration, (1) 19*g*.
Balaguer Arzo, F. See Del Rio Garcia, J. G.
Balandina, V. V. See Azarov, K. P.
Baldridge, D. B. Laminated glass having electrically operated instrument indicator means embedded in the interlayer, P (8) 177*i*.
Baldwin, L. W. Frost resistance—a discussion, (11) 279*j*.
Baldwin, N. L. See Gantzel, P. K.
Baldwin, T. O. See Young, F. W., Jr.
Bales, W. H. Resistance thermometer and method of making the same, P (10) 268*a*.
Balint, P. Study of the mineralogical composition and ceramic characteristics of Hungarian brick clays, (3) 70*a*.
Ball, D. L. Precipitation of boron nitride from ferrous melts, (10) 258*i*.
Ball, F. C. Children and the wheel, (4) 89*j*. Decorating Pottery with Clay, Slip, and Glaze, B (8) 212*a*. Draping clay in a clay mold, (7) 145*j*.
Ball Brothers Co., Inc. Etching composition and method of etching, P (4) 94*e*. Glass blowing machine having controlled blow pressure, P (1) 5*b*. Glassware and carton handling apparatus, P (4) 94*i*.
Ballard, A. H., and Hendricks, R., Jr. High temperature isostatic pressing, P (1) 12*g*.
Ballass, J. T., and Freedman, B. J. Welding flux, P (11) 276*d*.
Ballass, J. T., Freedman, B. J., and Brodsky, J. C. Welding flux, P (11) 276*c*.
Ballato, A. D. Variable delay line, P (2) 49*f*.
Ballinger, J. G. Humidity sensing apparatus, P (1) 14*c*.
Ballman, A. A. Growth and properties of piezoelectric bismuth germanium oxide $Bi_{12}GeO_{20}$, (9) 239*e*. See Lenzo, P. V.
Ballman, A. A., Laudise, R. A., and Rudd, D. W. Synthetic quartz with a mechanical Q equivalent to that of natural quartz, (5) 139*b*.
Ballman, A. A., Linares, R. C., Jr., and Van Uitert, L. G. Rare earth orthovanadate fluorescent materials, P (7) 157*j*.
Ballman, A. A., and Porto, S. P. S. Niobate maser materials and devices made therefrom, P (2) 48*g*.
Bally, A. O., and Wardale, D. J. S. Gas-fired [regenerative] radiant burner, P (4) 105*e*.
Balmer, G. G., and Colley, B. E. Laboratory studies of the skid resistance of concrete, (4) 90*j*.
Balmer, H., and Gasparac, R. J. [Bowl] adjusting mechanism for gyratory crushers, P (9) 235*j*. Frame for gyratory crushers, P (5) 133*a*.
Bal'shin, M. Yu. Contact section of powder compacts and sintered bodies and the values of their mechanical properties related to the contact section, (5) 134*g*.
Balyuk, S. T., and Zil'berg, E. S. Rapid method for determining Cr_2O_3 content in chromite ores, chrome-magnesite bodies, and refractories, (7) 159*c*.
Balzers Patent- und Lizenz-Anstalt. Zonewise melting of metals and of semiconductors, P (7) 158*c*.
Bamberger, F. C. See Bussey, H. E.
Ban, T. E. Manufacture of expanded shale, P (9) 223*a*. Method of making lightweight aggregate from fly ash, P (9) 223*b*.
Ban, T. E., Thompson, C. D., and Nelson, C. J. Iron-containing flux material for steelmaking process, P (7) 153*f*, P (8) 181*f*.
Ban, Z., and Ogilvie, R. E. Role of iron in the oxidation of molybdenum disilicide, (9) 242*a*.
Banbury, P. C. See Haddad, I. N.

Banbury, P. C., and Haddad, I. N. Energy dependence of anisotropy of defect production in electron irradiated diamond-type crystals (II) theoretical model, (8) 197*d*.
Bancroft, Joseph, & Sons Co. See Joseph Bancroft & Son s Co.
Bandyopadhyay, T., and Saha, P. Hydrothermal growth of quartz (I) experimental methods; (II) growth morphology, (5) 136*f*.
Banerjee, B. K. Some aspects of the structure of iron-containing glasses, B (9) 246*b*.
Banerjee, J. C., Chatterjee, N. B., and Nandi, D. N. Studies on fireclays for refractories, (2) 43*d*.
Banerjee, J. C., De, S. K., and Nandi, D. N. Diaspore as a refractory raw material, (3) 71*f*.
Banin, A. Tactoid formation in montmorillonite—effect on ion exchange kinetics, (4) 111*i*.
Bankina, V. F., and Abrikosov, N. Kh. System Bi_2Te_3-Bi_2Se_3, (8) 208*b*.
Banks, P. B. Method and apparatus for manufacturing thin glass films, P (3) 68*h*.
Banks, W. B. Apparatus for measuring viscosity, P (3) 81*c*.
Banner, J. G. See Loukes, D. G.
Bannikov, G. K., Brusko, G. G., Livshits, A. L., and Sigariov, A. M. Method for producing graphite electrodes, P (1) 8*d*.
Bansigir, K. G. See Babu, V. H.
Banter, J. C. Determination of the refractive index and thickness of oxide films on anodized zirconium from transmission interference measurements, (11) 293*a*.
Banus, M. D., and Lavine, M. C. High pressure synthesis of arsenopyrite-type ternary compounds, (7) 164*c*.
Baraboshkin, A. N. (editor). Electrochemistry of Molten and Solid Electrolytes (Vol. III), B (1) 30*j*. See Lebedeva, K. P.
Barafskas, Ch. See Skulikidis, A.
Baral, L. L. See Cummings, W. P.
Barantseva, I. G. See Andreeva, T. V.
Barany, R. Glass-crystal transformation of nepheline and wollastonite and heat of formation of nepheline, (1) 19*e*.
Barbee, B. H. See Parker, S. G.
Barber, D. J., and Tighe, N. J. Electron microscopy and diffraction of synthetic corundum crystals (II) dislocations and grain boundaries in impurity-doped aluminum oxide, (8) 196*j*.
Barber-Greene Co. Adjusting mechanism for gyratory crusher bowls, P (11) 291*c*. Screen tensioning device, P (5) 130*e*.
Barborka, J. Fluid process for drying glass sand, (2) 52*g*.
Barch, H. W., and Valchar, C. E. Method of press bending vertically supported glass sheets, P (4) 95*d*.
Barclay, W. M. Novel batching jumps production 40%, (9) 218*h*.
Barczak, V. J. See Poellet, A. L.
Bardagov, G. T. Competition in ladle brick production, (4) 96*h*.
Bardash, I. See Siekanowicz, W. W.
Bardin, C. Kaolin of Quessoy (II) exploitation, (7) 160*h*.
Barford, J. C., Dias, P. F., and Glentworth, J. D. Electrostatic powder application, P (9) 233*d*.
Barham, D. See Gravette, N. C.
Barkemeyer, H. R., McAleer, W. J., and Pollak, P. I. Semiconductor process and products produced thereby, P (5) 129*e*.
Barlow, H. D. See Barlow-Whitney, Ltd.
Barlow-Whitney, Ltd., and Barlow, H. D. Apparatus for the heating and melting of materials, P (2) 52*d*.
Barmore, W. L. See Cline, C. F.; Vandervoort, R. R.
Barmore, W. L., and Vandervoort, R. R. High-temperature creep and dislocation etch pits in polycrystalline beryllium oxide, (7) 164*e*.
Barna, A., Barna, P. B., and Pocza, J. F. Design of a new vacuum deposition specimen holder for an electron microscope operating at 10^{-9} torr, (11) 289*e*.
Barna, G. L., and Riley, R. R. Abrasion test for refractories, (10) 256*h*.
Barna, P. B. See Barna, A.
Barnard, B. See Mabbs, F. E.
Barnes Engineering Co. Process of preparing thin film semiconductor thermistor bolometers and articles, P (7) 157*g*.
Barnet, F. R., Lightbody, A., and Lewis, A. Method of forming a glass reinforced filament plastic tape, P (5) 121*c*.
Barnett, C. W. H. Piezoelectric wide bandpass filter with elliptical shape, P (8) 185*h*.
Barnett, J. D., Bennion, R. B., and Hall, H. T. High pressure X-ray diffraction studies on barium (3) 86*e*.
Barnhart, C. L., and Witt, C. H. Bottle sorter, P (9) 219*a*.
Barogenics, Inc. Control of stresses during shock-aided hydrostatic extrusion, P (5) 130*d*. Flash heating apparatus for diamond synthesis from liquid carbon, P (10) 266*h*. High pressure methods and apparatus, P (10) 266*a*.
Baron, V. V. See Savitskii, E. M.
Barr, H. N. Method of sphering refractory oxides, P (1) 8*f*.
Barr, H. N., and Sundquist, L. A. Hollow spherical UO_2 nuclear fuel particles, P (3) 72*g*.
Barr, L. W. See Rothman, S. J.
Barr & Stroud, Ltd. Method for making glass sandwiches primarily for windows of optical instruments, P (4) 95*a*.
Barrall, E. M., II, and Gernert, J. F. High sensitivity differential thermal analysis apparatus and method, P (11) 289*f*.
Barratt, M. S., and Parslow, G. R. Device for the rapid modal analysis of coarse-grained rocks, (8) 187*c*.
Barrer, R. M. Specificity in physical sorption, (1) 29*b*.
Barrer, R. M., and Marshall, D. J. Hydrothermal chemistry of silicates (XII) synthetic strontium aluminosilicates; (XIII) synthetic barium aluminosilicates, (8) 199*g*.
Barrett, C. S. X-ray diffraction, B (8) 211*j*.
Barrett, J. R. See Hiatt, W. R.
Barrett, L. R. See Gravette, N. C.
Barrett, M. F., and Barry, T. I. Nonstoichiometry in neodymium and europium oxides in relation to their interaction with oxygen and hydrogen, (8) 203*f*.
Barrett, W. T. See Sanchez, M. G.
Barrington, A. E., Herzog, R. F. K., and Poschenrieder, W. P. Vacuum system of ion-microprobe mass spectrometer, (3) 81*a*.
Barron, T. H. K., Leadbetter, A. J., Morrison, J. A., and Salter, L. S. Temperature factors and thermodynamic properties of crystals, (9) 242*e*.
Barrot, P. M. E., and Lemardeley, C. Y. L. Gyratory crushers, P (5) 133*b*.
Barrow, R. F. See Ames, L. L.; Cheetham, C. J.
Barry, T. I. See Barrett, M. F.
Barry, T. I., and Lay, L. A. Selective exchange of cation sites in zeolites observed by electron spin resonance of Mn^{2+} (I) Linde X, (8) 206*f*.
Barry, T. L., and Roy, R. Defect characterization in and precipitation from CaO:Yb_2O_3 crystalline solutions, (3) 84*g*.
Barry, T. L., Stubican, V. S., and Roy, R. Decomposition kinetics of $CaYb_2O_4$, (8) 194*f*. Phase equilibria in the system CaO–Yb_2O_3, (1) 25*a*.
Barta, R. Not Boettger but Tschirnhaus inventor of porcelain, (3) 63*j*.
Bartenev, G. M. High-elastic properties and structure of inorganic glasses, B (2) 61*j*. Possibility of obtaining the theoretical strength in glasses, B (2) 61*j*. Results of the Symposium on the Mechanical Properties and Structure of Inorganic Glasses, B (7) 171*g*. See Eremeeva, A. S.; Tarasov, V. V.
Bartenev, G. M., Gorbachev, A. A., and Udovenko, N. G. Study of structural conversions in two- and multicomponent glasses, (10) 253*b*.
Bartenev, G. M., and Izmailova, L. K. Structure and strength of glass fibers, B (7) 171*h*.
Bartenev, G. M., and Zelenev, Yu. V. Relaxation properties of amorphous polymers below and above glass-transition temperatures, B (2) 61*i*.
Barthelemy, R. E. High voltage separation of fine particles, P (7) 160*j*.
Bartholomew, R. F., and Kozlowski, T. R. Alkali attack of glass surfaces by molten salts, (3) 65*h*.
Bartlett, E. S. See Bradley, E. F.
Bartlett, R. W. Growth kinetics of discontinuous thermal oxide films—aluminum, (3) 86*d*. Molybdenum oxidation kinetics at high temperatures, (11) 298*a*.
Bartlett, R. W., and McCamont, J. W. Influence of crystal orientation on the oxidation of tungsten, (9) 239*h*.
Barton, J. T. Rate of flow indicator for mortar, P (8) 174*f*.
Barton, L., and Nicholls, D. High-temperature routes to boron monoxide and diborane, (8) 199*f*.
Barz, G. J., Kueffer, J., Haider, H., Thiele, H., and Ritter, J. Cathode ray tubes, P (11) 284*j*.
Barzakovskii, V. P. See Toropov, N. A.
Basche, M. See Galasso, F. S.
Basche, M., and Schiff, D. New pyrolytic boron nitride, (4) 97*j*.
Basic, Inc. Method of manufacturing basic refractories, P (7) 153*b*. Process for dead-burning dolomite, P (5) 124*j*.
Baskin, M. L. See Kreimer, G. S.
Baskin, M. L., Tret'yakov, V. I., and Chaporova, I. N. Tungsten diffusion in the monocarbides of tungsten, tantalum, titanium, and in the solid solutions TiC-WC and TiC-WC-TaC, (2) 59*e*.
Baskin, M. L., Tumanov, V. I., and Funke, V. F. Elastic modulus of sintered tungsten carbide-cobalt alloys, (3) 85*h*.
Baskin, Y. Phase studies in the pseudobinary system UN-UP, (3) 71*c*.
Baskin, Y., and Shalek, P. D. Synthesis of uranium monophosphide by the phosphine reaction, (8) 208*h*.
Basler, W. G., Kaufman, S. M., and Whalen, T. J. Process for manufacture of glass, P (10) 256*b*.
Basse Sambre Soc. Anon. Etudes-Recherches-Entreprises. Industrial gas burners, P (1) 14*j*.
Basseville, P. See Dubuisson, J.
Bast, C. H. Kiln system and method, P (1) 14*j*.
Bast, J. de, and Gilard, P. Electrical simulation of the relaxation of glass in the transformation range, (11) 276*f*.
Basu, A. N., and Mukherjee, S. K. Interaction of montmorillonite clay and trace element cations—dissociation of Co^{2+}, Ni^{2+}, and Mn^{2+} from the respective clays at different degrees of supersaturation, (9) 240*a*; (III) fixation and release of cations from their respective clay salts, (9) 239*j*.
Basus, Z. Stability of silicon carbide in firing processes, (4) 110*d*.
Batchelder, P. See Burkett, W. E.
Batchelor, C. S., and Jensen, W. R. Composite flame spraying wire, P (10) 250*b*.
Batcheler, J. D. Pyrolytic graphite coating process, P (8) 182*a*.
Bate, G., Morrison, J. R., and Speliotis, D. E. Nondestructive readout magnetic memory, P (11) 287*c*.
Bates, B. H. Increasing the efficiency of muffled tunnel kilns, (2) 41*j*.
Bates, H. E., and Weinstein, M. Solidification of PbTe-SeTe alloys under the influence of ultrasonic agitation, (10) 263*h*.
Batka, K., and Deri, M. Effect of grinding time on the dielectric properties of barium titanate dielectrics, (1) 9*g*.
Batt, J. A. See Galasso, F. S.
Bauduin, A. Apparatus for and process of annealing glass as it is being drawn upwardly, P (3) 67*e*.
Bauer Bros. Co. Cyclonic separator, P (10) 266*g*.
Baum, B. A., Gel'd, P. V., and Suchil'nikov, S. I. Electrical conductivity of molten chromium silicides, (3) 85*a*.
Baum, H. Spark plug having concentric radially spaced electrodes, P (7) 158*b*.
Bauman, F. E., and Costill, H. J. Glass tube gaging and cutting apparatus, P (8) 177*e*.
Bauman, H. D. White pigment, P (11) 292*e*.
Baumann, H. Reactions of silicic acid with o-diphenol polymers in water, (3) 87*i*.
Baun, W. L. Phase transformations at high temperatures in hafnia and zirconia, (4) 109*g*.
Baun, W. L., and Fischer, D. W. Effect of valence and coordination on *K* series diagram and nondiagram lines of magnesium, aluminum, and silicon, B (5) 139*i*.
Bausch & Lomb, Inc. Apparatus for producing optical fiber, P (2) 38*i*. Fiber glass orifice, P (3) 67*c*. Fluorophosphate glasses, P (1) 5*a*. Fusion of glass particles with brief high intensity light flashes, P (11) 278*e*. Glass compositions, P (7) 149*d*. Illuminator, P (1) 5*h*. Light deflector, P (1) 5*h*. Metaphosphate glass, P (9) 220*f*. Method of confining and surfacing end portions of optical fiber bundles for maximum light transmission, P (4) 94*h*. Method of making optical elements from Ba or Mg fluoride containing boron nitride, P (7) 150*c*. Ophthalmic segment glass compositions, P (1) 6*g*. Optical glass, P (1) 6*a*. Optical shutters, P (3) 69*h*. Tungsten oxide-metal metaphosphate glasses, P (1) 6*e*. Vanadium pentoxide-metal metaphosphate glass compositions, P (1) 6*f*.
Bay State Abrasive Products Co. Organic bonded abrasive article, P (2) 33*i*.
Baybutt, W. E. See Murphy, N. A.
Bayer, G. Perovskites, P (7) 157*b*.
Bazinet, W. P., Jr. Method of making light-conducting optical component, P (1) 6*d*.
Beale, J. Mold composition for foundry use, P (5) 124*e*.
Beall, G. H., Karstetter, B. R., and Rittler, H. L. Crystallization and chemical strengthening of stuffed β-quartz glass-ceramics, (5) 118*h*.
Beals, R. J. See Forlano, R. J.
Beals, R. S. See Miller, E. D., Jr.
Beamesderfer, J. W., and Morris, H. H. Acid treatment of calcined kaolin, P (8) 190*b*.
Beanland, F. D. Building slabs, bricks, and other building blocks, P (4) 96*c*.
Beard, W. C., and Foster, W. R. High-temperature formation of anatase, (10) 271*a*.
Beardmore, P. See Chaudhari, P.
Beasley, G. A. See Emerson, S. A.
Beattie, I. R. He/Ne laser Raman spectroscopy, (11) 289*i*.
Beattie, J. R. Apparatus for annealing glass, P (3) 67*a*. Methods and apparatus for producing toughened glass, P (3) 69*e*.
Beatty, R. L., and Beutler, H. Method for preparing actinide oxide fuel particles and article thereof, P (4) 98*f*.
Beaumont, D. H. See Friedman, A. I.
Beaver, E. R., Jr. See Henderson, C. M.
Bechmann, R., and Hearmon, R. F. S. Landolt-Boernstein (New Series), Numerical Data and Functional Relationships in Science and Technology (Group III) Crystal and Solid State Physics (Vol. 1) Elastic, Piezoelectric, Piezooptic, and Electrooptic Constants of Crystals, B (11) 305*c*.
Beck, H. See Kraft, G.
Beck, J. H. Method for continuous gas diffusion, P (1) 11*c*.
Beck, W. F., and Di Bello, P. M. Preparation of soda ash, P (11) 291*d*.
Becke, H. W. See Flatley, D. W.
Beckenbach, K. Double sloping-hearth furnace, P (2) 52*f*.
Becker, C. W., and Foster, R. S. Nonmetallic flotation process, P (4) 106*i*.
Becker, M. See Russell, J. L.
Beckham, R. R. See Browne, C. M.
Beckius, K. Refractories—current use and research, (7) 152*f*.
Beckman, P. Flattening and reversibly bending method of making a thermocouple, P (2) 52*c*.
Beckman Instruments, Inc. Cermet resistance composition and resistor, P (9) 230*g*. Cermet resistance element and material, P (9) 230*h*. Cermet resistance elements and terminal and tap connections therefor, P (9) 230*j*. Electrical terminations for cermet resistance elements, P (9) 230*e*. Electrochemical liquid junction structure and method for producing same, P (2) 38*e*. Fragmentation apparatus for characterization of sample compositions, P (9) 234*d*. Glass electrode with metal frame support and method of making thereof, P (11) 278*a*.

Bedier, R., Carpentier, S., Francois, H., Grand-Clement, A. M., and Meneret, J. Phosphate glass for the dosimetry of X and gamma rays, P (3) 69*i*.
Beechan, C. R. See Padfield, R. C.
Beekenkamp, P. Influence of the coordination number of boron on the properties of alkali borate glasses, B (2) 62*a*.
Beeley, P. R. See Snape, E.
Beer, L. de. Device for regaining diamond grindings (boart) in diamond grinding, P (5) 115*h*.
Beerbower, A., and Kayle, E. L. Emulsifiable glass mold lubricants, P (9) 219*h*.
Beerman, H. P. Pyroelectric infrared radiation detector, (9) 229*h*.
Behnke, G. W., Westcott, R. G., and Wirth, H. A. [Centrifugal] crusher mechanism, P (10) 269*j*.
Behnke, G. W., and Wirth, H. A. Crusher apparatus, P (4) 106*a*.
Behr, H., and Lipke, A. Apparatus for lining converters, P (4) 105*g*.
Behrendsen, W. J. T. Automation of the production line for heavy clay products, (3) 70*b*.
Behrens, R. Four glazes for cone 014, (4) 90*a*. Short glaze formulary, (4) 90*b*.
Beke, B., and Kiss, I. Theoretical study of the grinding process, (5) 129*j*.
Beke, B., and Opoczky, L. Structural changes during grinding of clinker to extreme fineness, (11) 275*b*.
Beketov, A. R. See Strekalovskii, V. N.
Belasco, M., and Wende, P. T. Semiconductor contact alloy, P (9) 232*a*.
Belbeoch, B., Laredo, E., and Perio, P. X-ray examination of quenched oxides of uranium of the type UO_3, (9) 243*a*.
Belentepe, Y. C., Carmi, A., Kiehl, H. R., and Rodgers, H. G. Fluid impinging glass forming apparatus, P (7) 149*c*. Glass forming method, P (9) 220*d*.
Belkov, A. F. See Budnikov, P. P.
Bell, A. N., Gauss, L. H., Jr., and Spremulli, P. F. Means for measuring the electrical resistance of molten glass in a tank, P (1) 5*j*.
Bell, R. See Trinklein, R. L.
Bell, R. O. See Weinstein, M.
Bell Telephone Laboratories, Inc. Amplification oscillation and mixing in a single piece of bulk semiconductor, P (11) 284*h*. Barrier diode with metal contact and method of making, P (3) 77*d*. Devices utilizing lithium metagallate, P (2) 47*c*. Elastic wave devices utilizing mixed crystals of potassium tantalate-potassium niobate, P (3) 77*j*. Electrolytic treatment of quartz, P (11) 285*h*. Encapsulations and methods and apparatus for making encapsulations, P (11) 285*h*. Fabrication of a semiconductive device with closely spaced electrodes, P (5) 127*b*. Ferrimagnetic garnet compositions, P (3) 78*h*. High field superconducting magnet consisting of a niobium-zirconium composition, P (1) 10*i*. Integrated circuit device and method, P (10) 264*e*. Method for fabricating printed circuit components, P (3) 78*g*. Method for making electrical components, P (9) 231*f*. Method of making integrated semiconductor devices, P (5) 128*b*. Method of making semiconductor integrated circuit elements, P (3) 78*j*. Method for preparing stabilized barium titanate and capacitor, P (3) 79*c*. Niobate maser materials and devices, P (2) 48*g*. Optical devices utilizing Faraday rotation, P (8) 178*d*. Optical modulator employing the dichroic absorption of antiferromagnetic NiF_2, P (8) 188*d*. Piezoelectric quartz crystal units, P (2) 48*j*. Piezoelectric quartz elements, P (10) 265*e*. [Plasma glow] method for making electrode connections to potassium tantalate-niobate, P (9) 231*g*. Polarization process for ceramics, P (7) 157*e*. Preparation of cerium-containing glasses, P (4) 95*b*. Process for electropolishing both sides of a semiconductor simultaneously, P (3) 79*b*. Process for the growth of ordered lithium ferrite, P (5) 128*h*. Rare earth orthovanadate fluorescent materials, P (7) 157*j*. Resonant and antiresonant vibratory members attached to a crystal, P (8) 186*c*. Semiconductor contacts and protective coatings for planar devices, P (2) 49*e*. Semiconductor device and method of making, P (1) 11*f*. Semiconductor diode and method of making, P (7) 158*b*. Semiconductor light modulators, P (4) 102*e*. Single crystal quartz filter elements, transducers, and delay lines, P (7) 158*d*. Stabilization of silicon semiconductor surfaces, P (11) 287*h*. Stress sensing semiconductive devices, P (1) 12*a*. Thermocompression wire attachments to quartz crystals, P (4) 102*j*. Vapor deposition mask, P (2) 49*f*.
Bellaire, M. Stick figures for underglaze decoration, (5) 116*c*.
Bellay, M. G. du, and Sanlaville, J. Process for making an anhydrous alumina product consisting principally of alpha alumina from alumina hydrate, P (11) 282*d*.
Bellott, E. M., and Haft, H. H. Filament mount and heat shield structure for electric incandescent lamp, P (2) 47*g*.
Bellrock Gypsum Industries, Ltd. Plaster compositions, P (3) 64*g*.
Beloborodova, S. S. See Nagornyi, A. I.
Belogorskaya, N. V. See Vereshchagina, V. I.; Zakharchenko, M. A.
Belokon, V. V., and Akunov, V. I. Removal of iron from quartz sand by grinding it in a counterflow mill, (8) 189*g*.
Belov, B. F. See Novokhatskii, I. A.
Belski, R. C. See Goodenough, R. D.
Belton, G. R., and McCarron, R. L. Volatilization of tungsten in the presence of water vapor, (9) 243*d*.
Belyaev, A. K. See Il'ina, N. Y.
Belyaev, G. I., Smakota, N. F., and Es'kov, A. S. Relation between electromotive force, acidity, and certain properties of enamel glasses, B (9) 246*a*.
Belyaev, I. N., and Chikova, N. N. Systems of the chromates, molybdates, and tungstates of rubidium, cesium, and lead, (11) 302*a*.
Belyaev, I. N., and Golovanova, T. G. Phase diagram of the system Cs_2CO_3-(Cs_2O)-V_2O_5, (4) 109*b*.
Belyavskaya, L. M. Influence of gamma radiation on the structure of glass, B (4) 113*c*.
Belyavskaya, L. M., Siryak, A. I., and Terent'eva, N. V. Influence of gamma-irradiation on conductivity of sodium silicate glasses, B (9) 245*j*.
Belyustin, A. A. See Shul'ts, M. M.
Belyustin, A. A., and Pisarevskii, A. M. Structural state of iron in glass, B (9) 246*b*.
Benassi, R. Humidifying device for clay products, P (5) 130*f*.
Benda, H. Electronic semiconductor device of the four-layer junction type, P (1) 10*c*.
Bendix Corp. Attaching leads to semiconductors, P (7) 156*f*. Ceramic transducer assembly, P (7) 156*j*. Composite article of bonded refractory metal and a ceramic, P (11) 281*a*. Ductile molybdenum composition containing a spinel dispersion, P (8) 181*a*. Ductile tungsten composition containing a spinel dispersed uniformly throughout, P (8) 181*a*. Duo resist process, P (8) 184*i*. High temperature ceramic-metal seal, P (2) 47*i*.
Bendy, W. R. Cement production in a rotary kiln, P (5) 116*d*. Method and apparatus for rotary kiln control with a calcining rate meter, P (7) 160*e*.
Bendy Engineering Co. Cement production in a rotary kiln, P (5) 116*d*. Method and apparatus for rotary kiln control with a calcining rate meter, P (7) 160*e*.
Benecke, M. W., Olson, N. E., and Pask, J. A. Effect of LiF on hot-pressing of MgO, (8) 195*e*.
Benedetti-Michelangeli, G. See Ascoli-Bartoli, U.
Beneke, J. A., Kelleher, C. J., and Maguire, S. G. Unloader for green ceramic ware, P (2) 46*g*.
Benjamini, E. A. See Waring, W.
Benkel, E. Potentiometric studies on caustic burned magnesite and its properties as a binder in hardened magnesium oxychloride cement, (11) 275*g*.
Bennett, H., and Marshall, K. Analysis of chrome-bearing materials (II) determination of silica and lime, (5) 130*h*.
Bennett, M. R., and Cathers, G. I. Method of separating UF_6 from bromine fluorides, P (9) 226*b*.
Bennion, R. B. See Barnett, J. D.
Benson, C. A., and Hart, A. L. Method of and apparatus for classifying glass bottles, P (4) 94*e*.
Benson, G. M. Core element [graphite] for a breeder nuclear reactor, P (9) 225*d*.
Bentall, E. H., & Co., Ltd. Silo or bin unit for storage and drying of granular materials, P (1) 13*a*.
Bentle, G. G. Diffusion of zirconium in zirconium hydride, (4) 107*h*.
Bentolila, J., and Cornuault, P. Method for manufacture of low permeability carbonaceous products, P (1) 7*j*.
Bentolila, J., Dubief, L., and Price, M. S. T. Method of extruding carbon articles, P (9) 226*c*.
Benton, K. R. See Sears, J. H.
Benz, R., and Bowman, M. G. Some phase equilibria in the uranium-nitrogen system, (2) 56*h*.
Berard, M. F. See Wirkus, C. D.
Berbesson, H. Heavy clay based prefabrication, (7) 150*h*.
Bercaw, J. W. See Lykken, W. H.
Berenshtein, P. L., and Rokhvarger, E. L. Comparative factors of different methods of setting wall tile for glost firing, (3) 73*i*.
Berezhnoi, A. S. Principles in the search for new refractories, (7) 152*d*. Systems with titanium dioxide and prospects of their use in new technology, (11) 302*c*.
Berezhnoi, A. S., and Gul'ko, N. V. Subsolidus structure of the systems CaO-MgO-Cr_2O_3-Al_2O_3, CaO-MgO-Cr_2O_3-SiO_2, and CaO-Cr_2O_3-Al_2O_3-SiO_2, (5) 138*f*.
Berezina, S. I. See Bergman, A. G.
Berezina, S. I., Bergman, A. G., and Bakumskaya, E. L. Ternary reciprocal system of the fluorides and chlorides of lithium and potassium, (2) 57*f*.
Berg, K. M., and Robertson, J. A. Production of a high-porosity refractory, P (7) 153*j*.
Berg, M. See Zollman, J. A.
Berg, P. W., and Perera, V. Improvements in control of reducing furnace atmospheres, (4) 105*e*.
Berger, D. F. See Knupp, R. C.
Berger, G. See Keller, W.
Berger, J. E., Zobel, C. R., and Engler, P. E. Laser as light source for optical diffractometers—Fourier analysis of electron micrographs, (1) 13*j*.
Berger, R. Decoration resistant to detergents—or detergents suitable for decoration, (7) 154*g*. Lead-free colors for porcelain and glass, (3) 74*c*.
Berger, S. B., and Rubinstein, C. B. Optical devices utilizing Faraday rotation, P (8) 178*d*.
Bergeron, C. G., and De Luca, J. P. Crystal growth at bubble surfaces in glass, (3) 65*i*.
Berghezan, A. I. Metal ceramic compositions, P (3) 72*i*.
Bergman, A. G. See Arabadzhan, A. S.; Berezina S. I.; Bogatova, E. I.; Il'yasov, I. I.
Bergman, A. G., and Andryushchenko, Yu. I. System Li, K, Pb ‖ Cl, Br, (8) 208*i*. Ternary system of the bromides of potassium, lithium, and lead, (2) 57*f*.
Bergman, A. G., and Arabadzhan, A. S. Reciprocal system of the chlorides and bromides of lithium and silver, (1) 27*b*. Reciprocal system of the chlorides and bromides of lithium and sodium, (1) 27*c*.
Bergman, A. G., Berezina, S. I., and Bakumskaya, E. L. Stable cross sections of the quaternary reciprocal system of the fluorides and chlorides of lithium, sodium, and potassium, (1) 20*f*.
Bergman, A. G., Kozachenko, E. L., and Berezina, S. I. System Li, Na ‖ F, Cl, (8) 209*a*.
Bergman, H. P., and Stiegler, R. W., Jr. Method of making a semiconductor by selective impurity diffusion, P (11) 286*j*.
Bergmann, R. J. See Hemstock, G. A.
Bergna, H. E., and Simko, F. A., Jr. Molded amorphous silica bodies and molding powders for manufacture of same, P (4) 106*h*.
Bergstrom, B. H., Edens, W. W., and Revolinsky, E. Batch blender, P (11) 288*g*.
Bergstrom, J. W. See MacIver, B. A.
Bergwerksverband G.m.b.H. Treatment of powdered materials, P (1) 13*c*.
Bering, B. P., Dubinin, M. M., and Serpinsky, V. V. Theory of volume filling for vapor adsorption, (2) 57*g*.
Berkenblit, M. See Reisman, A.
Berkenblit, M., Cheroff, G., Hochberg, F., and Reisman, A. Process for fabricating reproducible photoconductors, P (10) 265*g*.
Berkes, J. S., and White, W. B. Optical spectra of nickel in alkali tetraborate glasses, (5) 119*i*.
Berkman, A. S., and Mel'nikova, I. G. Filter ceramics for purifying nickel solutions, (3) 65*c*.
Berkowitz-Mattuck, J. B. High-temperature oxidation (I) thermal conductivity method for oxidation measurements, (3) 80*h*; (II) molybdenum silicides, (11) 297*a*. See Kaufman, L.
Berl, K. Enamel ashtrays for outdoors (I); (II) combining enameled metal and casting stone, (4) 89*j*. Enameled belts, (5) 115*j*. Jewelry from enamel lumps, (4) 90*b*.
Berlin, I. E. See Kolchin, O. P.
Berman, R., and Brock, J. C. F. Effect of isotopes on lattice heat conduction (1) lithium fluoride, (8) 195*c*.
Bernhardt, W. See Zagar, L.
Bernier, M. Preparation of sinterable beryllium oxide through decomposition of beryllium hydroxide, (1) 27*e*.
Bernshtein, D. G., and Nemirovskii, L. R. Use of chromatic pyrometer to measure temperature in the sintering zone, (10) 249*c*.
Bernstein, J. L. See Abrahams, S. C.
Bernuth, G. von, Jantsch, O., and Krockow, D. Multilayer junction semiconductor devices such as controlled rectifiers and transistors containing electropositive protective coating, P (8) 185*d*.
Berry, J. M. See Mehan, R. L.
Berry, J. S., Jr. See Richards, N. E.
Berry, K. L. Brookite fibers and their preparation, P (11) 291*c*.
Berry, K. L., and Wetzel, R. H. Process for producing a fibrous titanium dioxide containing material, P (10) 265*j*.
Berry, R. D. See Rhys, D. W.
Berry, R. W. See Schwartz, N.
Berry, T. F., and Bruce, R. W. Simple method of determining the grindability of ores, (3) 81*d*.
Bersan, J. See Rossin, R.
Bersano, T. Apparatus for the continuous air-cooling or heating of granulated materials, P (7) 158*h*.
Bersticker, A. C., Sweo, B. J., and Snow, J. D. Sources of bubble producing gases in glazes, (1) 9*e*.
Bertelsen, B. I. See Maissel, L. I.
Berthier, R. M. Use of rhyolitic pumice for making heating insulating and refractory concrete, P (3) 73*c*.
Bertini C., J. Refractories quality, (5) 123*j*.
Bertoldi, G. Bloating of clay an bloated clay products, (3) 70*b*.
Bertoli, G. M. Casing with pulsating internal wall for mills, mixers, and similar equipment, P (4) 106*j*.
Bertorelli, O. L. See Mays, R. K.
Bertozzi, G., and Sternheim, G. Surface tension of liquid nitrate systems, (8) 208*d*.
Beru-Werk Albert Ruprecht. Process of producing spark plug insulators by dry pressing, P (11) 284*b*.
Beryllium Corp. Protective coating for beryllium metal, P (4) 92*e*.
Beryloy, Ltd. Method for the chemical beneficiation of beryllite, P (4) 106*d*.
Berzin, R. Ya. See Eiduk, Yu. Ya.
Besen, H. Turbidity of optical glass in relation to heat treatment, B (9) 245*h*.
Besenbruch, G. See Kana'an, A. S.
Beshers, D. N. Anelastic techniques—iron, a case history, B (8) 211*j*.
Besore, C. D., and Pirkle, R. O. Moisture proof connector for spark plugs, P (10) 265*c*.

Bessent, R. G., and Hayes, W. Electron nuclear double resonance of divalent thulium in calcium fluoride, (8) 196*c*.
Bessonov, A. F. See Strekalovskii, V. N.; Strelov, K. K.
Bessonov, A. F., Strekalovskii, V. N., Neuimin, A. D., and Ust'yantsev, V. M. Investigation of the oxidation of uranium dioxide by high-temperature conductometric, X-ray diffraction, and continuous weighing methods, (11) 297*b*.
Bessonov, A. F., and Ust'yantsev, V. M. Effect of the state of the surface layers of particles on the sintering of magnesite powder, (10) 257*f*. High temperature apparatus for the simultaneous measurement of electrical resistivity and X-ray diffraction analysis of oxides, (11) 296*i*.
Best, G. R. Method of forming thin film resistors, P (2) 48*h*. Thermal printing wafer and method for making the same, P (11) 288*a*.
Best, H. S., and Bowser, R. E. Semiconductor terminals and methods, P (10) 265*c*.
Best, H. S., and Edelson, N. M. Method of attaching leads to thin films, P (2) 48*e*.
Best, W. H. Radiant burner utilizing flame quenching phenomena, P (1) 15*c*.
Bestul, A. B. Volume relaxation of As_2O_3 in the glass transformation region, B (2) 61*j*. See Chang, S. S.
Beteiligungs- und Patentverwaltungs G.m.b.H. Apparatus for lining converters, P (4) 105*g*. Process for the centrifugal separation of minerals, P (9) 236*f*.
Bethlehem Steel Corp. Automatic expendable thermocouple lance, P (9) 234*c*. Low carbon steel alloy for vitreous enameling, P (2) 35*i*.
Beucherie, P., Payrissat, M., and Wurm, J. G. Process for the preparation of nuclear fuel carbides, P (10) 260*h*.
Beucherie, P., and Wurm, J. G. Furnace for the manufacture of fissile and/or fertile nuclear fuel carbides, P (4) 98*h*. Process for the production of monocrystals of uranium carbide, P (10) 260*b*.
Beumel, O. F., Jr. See Verdieck, R. G.
Beutler, H. See Beatty, R. L.
Bever, M. B. See Chaudhari, P.; Robinson, P. M.
Beyer, D. S., and Thornton, C. G. Apparatus for fabricating alloyed junction semiconductor assemblies, P (3) 77*a*.
Beyersdorfer, K., and Hammer, J. Quality control of glaze frits by determination of their flow behavior, (3) 74*g*.
Beyersdorfer, P. Properties of the surface of fine particles with special reference to the specific surface, (11) 299*g*.
Bhappu, R. B. See Deju, R. A.; Fuerstenau, M. C.
Bhat, R. See Moorthy, V. K.
Bhatia, M. L. See Ghosh, R. K.
Bhattacharya, S. K., and Sinha, B. C. Rapid method for the estimation of silica in magnesite and calcareous materials, (2) 51*c*.
Bhaumic, M. L. Versatile laser and its principle, (8) 184*a*.
Bhushan, B., Das, B., and Sen, S. Zircon opacifiers—their preparation and performance in glazes, (8) 182*h*.
Biard, J. R., and Pittman, G. E. Semiconductor radiant diode, P (3) 79*e*.
Bichowsky, F. von. Process for the preparation of a titanate containing lithium and potassium, P (9) 232*b*.
Bick, D. E. Mills for comminuting material, P (9) 236*c*.
Bickford, E. D. Plant growth lamp, P (2) 49*a*.
Bickler, D. B., and Rauschenbach, H. S. Simulation of solar radiation, P (10) 265*e*.
Bickley Furnaces, Inc. Preheater for furnaces, P (1) 15*b*.
Bicknell, R. W., Joyce, B. A., Neave, J. H., and Smith, G. V. Epitaxy of silicon on alumina—structural effects, (8) 197*a*.
Bidwell, L. R. See Wimmer, J. M.
Biedermann, G., and Chow, J. T. Hydrolysis of metal ions (LVII) hydrolysis of the $Fe(III)$ ion and the solubility product of the $Fe(OH)_{2.70}Cl_{0.30}$ in 0.5M $(Na^+)Cl^-$ medium, (11) 297*c*.
Biedermann, W. See Hanisch, H.
Biegler, H., Neugebauer, W., and Kempers, H. Production of finely divided amorphous silica, P (7) 161*c*.
Bielawski, C. A. See Theodore, J. G.
Bierbrauer, G. [Body] preparation in small fine-ceramic plants, (9) 228*a*.
Biermann, W. J. Method for the chemical beneficiation of beryllite, P (4) 106*d*.
Bierstedt, P. E. See Borchardt, H. J.
Bieth, T. C. Purifying apparatus for separating solid particles from a gas, P (2) 50*b*.
Bigg, P. H. International system of units (SI Units), (4) 112*i*.
Biggers, J. V., and Muan, A. Activity-composition relations in orthosilicate and metasilicate solid solutions in the system MnO-CoO-SiO_2, (7) 161*f*.
Bikerman, J. J. Solid-to-solid adhesion, B (8) 212*a*.
Bilisoly, J. P. Synthetic crystalline zeolite compositions and preparation thereof, P (9) 236*i*.
Billick, I. H., Schulz, M., and Weiss, G. H. Calculation of moments of molecular weight distribution from sedimentation equilibrium data, (7) 162*f*.
Billings, D. D. See Manring, W. H.
Billington, E. W., and Huxley, A. S. Measurements of the flow properties of two types of thixotropic fluid, (7) 165*g*.
Billmeyer, F. W., Jr., and Saltzman, M. Principles of Color Technology, B (5) 141*e*.
Bills, J. L., and Cotton, F. A. Heat of formation of germanium dioxide, (8) 199*j*.
Binder, R. J. Apparatus and process for preparing semiconductor rods, P (9) 230*f*.
Bingham, C. R. Thermocouple comprising intimately twisted wires, P (8) 188*h*.
Binns, C. F., and McMahon, J. F. (reviser). Potter's Craft, B (11) 305*a*.
Birch, R. E. Refractories in transition, (2) 42*g*.
Birchenall, C. E., and Williams, J. M. Self-diffusion on nearly pure metallic surfaces, B (9) 245*f*.
Birks, J. B., and Hart, J. (editors). Progress in Dielectrics (Vol. 6), B (11) 305*f*.
Birrell, R. W. See Aiken, H. H.
Bischoff, F. Apparatus for vapor deposition of silicon, P (11) 284*h*.
Bishay, A., and Kinawi, A. Absorption spectra of iron in phosphate glasses and ligand field theory, B (2) 62*b*.
Bishay, A. M., and Gomaa, I. Radiation-induced defects and structure of barium silicate glasses, (7) 148*e*.
Bishay, A. M., and Maklad, M. S. Gamma-induced absorption bands associated with Tl^+, Pb^{1+}, or Bi^{1+} in potassium borate glasses, (11) 276*i*. Radiation induced optical absorption in lead borate glasses in relation to structure changes, (2) 37*d*.
Bishop, A. E., and Mayaud, E. E. Method of making luminescent screens, P (2) 48*j*.
Bishui, B. M., Dhar, R. N., and Prasad, J. Estimation of kaolinite in clays by infrared method, (8) 187*d*.
Bissell, C. L. See Duke, F. R.; King, L. A.
Biswas, A. B. See Sabane, C. D.
Bittmann, C. A., and Sah, Chih-Tang. High frequency transistors, P (1) 10*f*.
Bittner, H. J., and Jacobs, L. Glass pressing machine, P (11) 278*c*.
Bixler, H. J. See Michaels, A. S.
Bizon, P. See Gebauer, J.
Bizyaeva, M. K. See Chikanov, N. D.
Bjorklund, C. W. See Holley, C. E., Jr.
Blachere, J. R. Desulfurization of pyrite, (1) 6*h*.
Black, H. R., Co. Apparatus for removing solids and semisolid materials from solutions, P (1) 12*i*.
Black, H. R., Hutson, C., Stanesa, E., Kezar, N. P., Walsh, W., Morrison, J. A., and Simons, L. Apparatus for removing solids and semisolid materials from solutions, P (1) 12*i*.
Black, J. Correlation of electrical measurements with chemical analysis in zinc- and cadmium-diffused GaAs, (3) 84*g*.
Black, L. V., and McKelvey, H. E. Glass sheet bending mold with pivoted end sections, P (2) 38*h*.
Blackman, S. N. Method of marking mercury glass thermometers, P (8) 178*h*.
Blackmar, R. J. See Cook, A. M.
Blackwell, C. R. See Blackwell, S. C.
Blackwell, S. C., and Blackwell, C. R. Apparatus for use in throwing and turning potter's clay, P (3) 64*a*.
Blaine, J. C. Method and apparatus for consolidating batch, P (3) 68*c*.
Blair, G. E., Hamblen, D. P., and Weidel, R. A. Vanadium pentoxide-metal metaphosphate glass compositions, P (1) 6*f*.
Blair, R. See O'Bryan, H. M., Jr.
Blake, F. L. Treating of surfaces of semiconductor elements, P (8) 186*c*.
Blake, R. L., Hessevick, R. E., Zoltai, T., and Finger, L. W. Refinement of the hematite structure, (1) 28*b*.
Blakely, J. M. See Li, Che-Yu.
Blanc, R. Device for measuring the transconductance and output conductance of a transistor, P (7) 156*b*.
Blanchard, R., Bochirol, L., Moreau, C., Philippot, J., and Blum, P. Process for the densification of carbonaceous bodies, P (9) 226*g*.
Bland, J. T. See Kelly, B. T.
Blank, J. M., and Russell, V. A. Nucleation and crystal growth of silicon on sapphire, (1) 24*b*.
Blankenship, A. C. See West, R. G.
Blankenship, C. L. See Schoenlaub, R. A.
Blankenship, M. G. Apparatus for aligning hollow articles, P (1) 4*b*.
Blasse, E. F. See Palmer, R. C.
Blasse, G. New compounds with perovskite-like structures, (8) 203*h*.
Blaszczak, K. See Pampuch, R.
Blau, R., Sedlak, B., and Phillips, R. M. Yttrium iron garnet preselectors, P (4) 103*b*.
Blauer, J., Greenbaum, M. A., and Farber, M. Heat and entropy of formation of boron(I) fluoride(*g*), (8) 199*i*.
Blavat, H. See Lacroix, R.
Blaze, J. E., Jr. Process of manufacturing refractory fibers, P (9) 226*i*.
Blazek, R. J., and Buck, I., Jr. Method for making an electroluminescent device, P (8) 185*f*.
Blazey, K. W. See Woolley, J. C.
Blech, I. A., and Meieran, E. S. X-ray topography of single crystal NiO, (9) 243*h*.
Blickensderfer, R. Nomograph for density of powder compacts, (7) 169*h*.
Blin, C. Research on a simple control method for use in clay pits, (5) 131*e*.
Blin, C., and Levandowsky, L. Wollastonite and its chief uses in the ceramic industry, (7) 160*j*.
Blinov, V. A. Influence of high pressure on the structure of glass, B (7) 171*h*.
Blin-Stoyle, A. E. See Catling, H. W.
Blin-Stoyle, A. E., and Richards, E. E. Spectrographic analysis of Mycenaean and Minoan pottery (II) method and interim results, (11) 274*f*.
Bloch, D., and Chaisse, F. Effect of pressure on emf of [copper-constantan] thermocouples, (7) 159*e*.
Bloch, D., Feron, J. L., Georges, R., and Jacobs, I. S. Field-dependent magnetic susceptibility of MnO, (8) 198*j*.
Blocher, J. M., Jr. See Oxley, J. H.; Powell, C. F.
Blocher, J. M., Jr., Browning, M. F., and Dayton, R. W. Coated nuclear reactor fuel particle of UO_2 and method of making the same, P (3) 72*e*.
Block, S. See Robbins, C.
Bloem, J., and Steinmaier, W. Method of manufacturing a semiconductor device by vapor deposition, P (10) 264*f*.
Blokh, K. I. Relaxation theory of glass formation and strength of glass fibers, B (7) 171*h*.
Blokhin, S. M. See Vainshtein, E. E.
Blomberg, R. N. Alumina titanate bonded magnesia, P (8) 180*d*.
Blondel, R. C. M. F. See Societe Francaise de Produits Hypo-Metallurgiques.
Blood, C. M. See Bruin, H. J. de.
Blood, W. R. See Bulcraig, W. R.
Bloom, M. C., Newport, G. N., and Fraser, W. A. Steel corrosion mechanisms—growth and breakdown of protective films in high-temperature aqueous systems—15%NaOH at 316°C, (4) 92*b*.
Bloor, D. Discussion of "Infrared absorption spectrum of silicon dioxide," (1) 18*c*.
Bloos, F. D. See Fang, J. H.
Blubaugh, O. J. Belt conveyor weighing apparatus, P (10) 266*g*.
Bluehmke, P. See Wolf, F.
Bluemel, F. Modern style of tiled stoves, (7) 145*j*.
Blum, N. A. See Schieber, M.
Blum, P. See Accary, A.; Blanchard, R.
Blum, P., Bochirol, L., and Moreau, C. Process for the fabrication of bodies formed by dispersion of refractory material within a pyrocarbon matrix which is impervious to gases, P (7) 153*g*.
Blum, P., and Vaugoyeau, H. Nuclear fuel material of $U_3Cs_2Si_2$ and method of preparation, P (11) 282*a*.
Blum, P. L., and Morlevat, J. P. Ternary diagram uranium-carbon-oxygen, (7) 168*i*.
Blum, S. E. See Weiser, K.
Blum, W. See Reppich, B.
Bluvshtein, M. N. See Keler, E. K.
Bluvshtein, M. N., and Boricheva, V. N. Zonal change in the properties of magnesite brick after service in the roof of an open-hearth furnace, (9) 225*i*.
Board of Trustees of Schools for Industrial Education of Newark, New Jersey, Administering Newark College of Engineering. Process for purifying colloidal particles for subsequent structural analysis with an electron microscope, P (8) 188*c*.
Boardman, G., and Worrall, W. E. Adsorption mechanisms of certain dyes on clays, (1) 16*i*.
Bobkova, N. M. Kinetics of glass structure formation during the melting process, B (9) 246*c*.
Bobrov, V. S. See Shul'ts, M. M.
Boby, Robert, Ltd. See Robert Boby, Ltd.
Bochirol, L. See Accary, A.; Blanchard, R.; Blum, P.
Bochkarev, G. S. See Zaitsev, L. M.
Bock, G. von. Rhenish pottery art—exhibition in Frechen, (9) 213*j*
Bockemuehl, R. R. See Kauppila, J. E.
Bockris, J. O'M. See Nagarajan, M. K.; Tricklebank, S. B.
Bockris, J. O'M., Yoshikawa, S., and Richards, S. R. Diffusion of unlike ions into liquid sodium chloride, (8) 194*i*.
Boddy, P. J. Kinetics of anodic dissolution of germanium, (7) 164*f*.
Bodenheimer, W., Heller, L., and Yariv, S. Organometallic clay complexes (VII) thermal analysis of montmorillonite-diamine and glycol complexes, (5) 137*b*.
Boehm, H. P. See Schneider, M.
Boehme, H. J. See Schwiete, H. E.
Boeing Co. Method of bonding sheets of metal, P (9) 217*a*. Neutron dosimeter comprising nickel oxide with lithium as an impurity, P (8) 185*e*. Thermal measuring apparatus, P (2) 52*b*.
Boes, D. J., Johnston, W. D., and Moberly, L. E. Electrically conductive solid lubricant members and process and apparatus employing them, P (5) 127*i*.
Boes, D. J., and Moberly, L. E. Electrically conductive solid lubricant members and process and apparatus employing them, P (4) 101*b*.
Boettcher, S. A. Why not try free-abrasive machining? (8) 173*f*.
Boettner, G. B., and Fanning, E. F. Glass melting furnace with bubblers, P (10) 255*f*.
Boev, E. I. See Markovskii, L. Ya.
Bogatova, E. I., Kislova, A. I., and Bergman, A. G. Reciprocal system of the pyrophosphates and molybdates of lithium and potassium, (11) 300*j*.
Bogdanova, I. V. Photometric titration of CaO, MgO, and Fe_2O_3 in cement materials by complexometric methods, (9) 215*e*.

Boggs, L. R. Method and apparatus for making continuous lengths of threaded fiber reinforced resin articles, P (2) 39*d*. Method and apparatus for making elongated articles of fiber reinforced resin material, P (5) 121*a*.

Boggs, W. E., Kachik, R. H., and Pellissier, G. E. Effect of crystallographic orientation on the oxidation of tin, (3) 85*a*. Effect of oxygen pressure on the oxidation of zone-refined iron, (11) 294*c*.

Boggum, P. Uses of fused silica, (5) 124*b*.

Boggum, P., and Glaser, W. Chrome-containing brick in the glass industry for use in the regenerator or as blocks for the melting tank, (9) 223*j*.

Bohling, W. C. See Norton, C. L., Jr.

Bohn, E. M. See Sturcken, E. F.

Boicey, C. R. See Goeckel, H. F.

Boicey, J. H. Apparatus for producing a laminated assembly, P (5) 120*a*.

Boissonnet, L. A. Machine for scoring and cutting ceramic mosaics, P (5) 125*j*.

Bokin, P. Ya. See Alekseeva, O. S.

Bokin, P. Ya., and Govorova, R. A. Surface strength by grinding and the mechanical properties of certain glasses and crystalline glass materials, B (5) 141*j*.

Bokin, P. Ya., Korelova, A. I., Govorova, R. A., Alekseeva, O. S., and Nikandrova, G. A. Mechanical properties and microstructure of lithium silicate glasses at different stages of crystallization, B (5) 141*j*. Relation between certain mechanical properties and microstructure of crystallized lithium silicate glasses, B (5) 141*j*.

Bokros, J. C., Goeddel, W. V., Chin, J., and Price, R. J. Pyrolytic carbon coated particles for nuclear applications, P (4) 99*e*.

Boldrini, P. See Loopstra, B. O.

Bolin, S. R. See Dess, H. M.

Bolk, A., Meerman, W. C. P. M., and Buysman, P. J. Method of making a casting mold, P (11) 282*c*.

Bolland, R. Y. H. H. Fluid quenching apparatus for producing a differentially toughened zone in a toughened glass, P (5) 120*g*.

Bollerman, P. V. See Nutter, G. D.

Bollmann, W., and Hennig, G. R. Electron microscope observations of irradiated graphite single crystals, (2) 55*c*.

Bol'shakov, K. A., Bul'onkov, N. A., Rastorguev, L. N., and Tsirlin, M. S. Mg_3Si–Mg_3Sb_2 system, (1) 22*j*.

Bol'shakov, K. A., Bul'onkov, N. A., Rastorguev, L. N., Umanskii, Ya. S., and Tsirlin, M. S. Mg_2Sn–Mg_3Sb_2 system, (1) 23*a*.

Boltax, A., and Handwerk, J. H. (editors). Nuclear Applications of Nonfissionable Ceramics—Proceedings of Conference, May 1966, Washington, B (5) 140*c*.

Bomberger, H. B., Jr. Methods for the elevated temperature protection of metallic surface and coatings therefor, P (4) 92*d*.

Bombled, J. P. Rheological studies of raw cement pastes (I,II), (2) 34*i*.

Bon, C. K. See Neipert, M. P.

Bonar, K. M., Cunningham, J. L., and Walther, F. H. Stability of commercial refractories in vacuum, (8) 180*c*.

Bonazoli, R. P. See Palermo, J. J.

Bond, R. L., Pinchin, F. J., and Jenkins, M. J. Method of forming graphite articles, P (4) 98*d*.

Bondar, I. A. Influence of a third component on phase separation in certain binary silicate systems, B (5) 141*i*.

Bondar, I. A., and Toropov, N. A. Preparation and properties of rare-earth silicates and aluminates, (10) 271*d*.

Bondarev, D. E. Causes of fast response in ferrites with a square hysteresis characteristic, (10) 261*j*. See Andreev, B. S.

Bonetti, G. See Locardi, B.

Bonham, R. D. Charles Lakofsky, (5) 115*j*.

Bonin, G. E. Grinding and polishing method and apparatus, P (3) 68*a*.

Bonis, L. J., Bruyn, P. L. de, and Duga, J. J. (editors). Fundamental Phenomena in the Materials Sciences (Vol. 3) Surface Phenomena—Proceedings of the Third Symposium, Boston, January 1965, B (9) 245*c*.

Bonis, L. J., and Hausner, H. H. (editors). Fundamental Phenomena in the Materials Sciences (Vol. 2) Surface Phenomena—Proceedings of the Second Symposium, Boston, January 1964, B (8) 212*d*.

Bonis, L. J., Sandven, O. A., and Manning, B. Method of heating and forming powdered metals, P (10) 259*g*.

Bonnet, R. E. See Highberg, C. W.

Bonnybridge Silica & Fireclay Co., Ltd. Burner block, P (8) 180*f*.

Bonorino, F. G. Soil clay mineralogy of the Pampa plains, Argentina, (8) 207*f*.

Booe, J. M., and Hood, J. T. Electrical capacitor with a boron nitride dielectric, P (1) 10*b*.

Booher, R. B. Electrical printing using stencil and moving slot powder metering means, P (5) 120*e*.

Book, N. Apparatus for disintegrating materials by means of liquid jets, P (9) 235*h*.

Booker, G. R. See Hall, C. R.

Booker, G. R., and Stickler, R. Small particles in silicon, (4) 109*h*.

Boolen, R. F. See Mills, L. E.

Boone, F. H. See Quentin, R. J.

Booshin, A. N. See Kotelnikov, G. R.

Boow, J. Viscosity of fused boric oxide, (10) 254*c*.

Borbas, J. J., Padfield, R. C., and Moscker, E. Density determination of refractories by measurement of gamma-radiation absorption, (9) 223*g*.

Borchardt, H. J. Luminescent compositions containing europium and the oxyanion-yielding ingredient aluminum, gallium, or germanium, P (2) 47*j*. Selected luminescent molybdates and tungstates of Sc, La, Eu, Gd, and Lu, P (9) 232*g*.

Borchardt, H. J., and Bierstedt, P. E. $Gd_2(MoO_4)_3$—a ferroelectric laser host, (5) 136*f*.

Borchert, W., and Petzenhauser, I. Formation of osumilite in various silicate systems, (8) 198*d*.

Borchhardt, D. See Wolf, F.

Bordeaux, J., and Scott, D. R. Temperature sensor, P (2) 52*a*.

Borel, J. P. See Cornaz, P.

Borgman, V. A., Gurkovskii, E. V., and Chistoserdov, V. G. Influence of variations of glass structure on photosensitivity, B (9) 246*a*.

Borgolte, T. Regeneration of the hydrochloric acid pickling bath, (10) 250*f*.

Boricheva, V. N. See Bluvshtein, M. N.

Borisov, A. F. See Dertev, N. K.; Zadumin, V. I.

Borisov, A. F., and Zadumin, V. I. Thermoelectric effects and structure of sodium silicate glasses, B (4) 113*c*.

Borisova, Z. U., and Doinikov, L. I. Investigation of vitreous $As_2Se_3I_y$ compositions, B (7) 171*g*.

Borisova, Z. U., Myuller, R. L., and Tsai, T. C. Electrical conductance of glasslike $GeSe_2$, (3) 66*f*.

Borkowski, C. J. See Fox, R. J.

Born, G. E., Gutheil, H. H., and Painter, G. Apparatus for sealing hollow glass parts, P (3) 67*g*.

Bornemann, G. A., and McIlhenny, W. F. Preparation of high purity magnesium oxide from magnesium salt solutions, P (11) 282*c*.

Bornstein, N. S., Hirakis, E. C., and Friedrich, L. A. Diffusivity data on the formation of niobium carbide surface films, (11) 293*b*.

Borom, M. P., Longwell, J. A., and Pask, J. A. Reactions between metallic iron and cobalt oxide-bearing sodium disilicate glass, (3) 87*i*.

Boronenkov, B. N. See Shurygin, P. M.

Borovec, Z. See Konta, J.

Borovik, E. S., and Yakovleva, H. G. Magnetic properties of binary systems of mixed lead-barium and lead-strontium ferrites, (1) 22*a*.

Borst, D., and Mittereder, F. X. Transverse heat absorption from a drawn glass sheet subsequent to roll forming, P (3) 69*h*.

Borst, R. E. Recognizing and defining a computer problem, B (11) 303*h*.

Borst, R. L. Mineralogical study of some Lower Devonian (Helderberg) rocks of the Central Hudson Valley, New York, (7) 165*e*.

Bortz, S. A. Explosive formed ceramic parts? (2) 49*j*. Influence of surface conditions on the strength of ceramics, B (2) 61*h*.

Borusevich, L. K., and Gladyshevskii, E. I. X-ray study of alloys in the system Mo-Re-C, (2) 60*f*.

Bosch, H., and Gonsior, T. Determination of aluminum oxide in chrome ore and chrome-magnesite brick, (3) 70*j*.

Bosomworth, D. R. Far infrared optical properties of $LiNbO_3$, (11) 295*b*.

Bosshart, R. E. See Feldman, F. J.

Botden, T. P. J. See Klomp, J. T.

Botden, T. P. J., Klomp, J. T., and Ven, A. J. C. van der. Ceramic article with sintered metallic layer and flux, P (7) 156*h*.

Botia, P. D. See Duran Botia, P.

Botvinkin, O. K. Diversity of glass structures, B (7) 171*f*. See Ananich, N. I.

Botvinkin, O. K., and Zaporozhskii, A. I. Nature of coexisting groups in the structure of quartz glass, B (9) 245*g*.

Bouchard, G. H., Tartakoff, A., and Homer, H. H. Electric lamp coating comprising agglomerates of silica coated with a pigment, P (8) 184*i*.

Bouchard, R. J. Spinel to defect NiAs structure transformation, (10) 272*a*.

Boulton, J. F., and Eardley, R. P. Preparation of analysis samples of hard materials with a boron carbide mortar, (8) 187*g*.

Bour, T. C. Method and apparatus for improving homogeneity of viscous liquids, P (10) 255*a*.

Bouraoui, A., and Mering, J. Diameter of the elementary atomic layers in strained carbon between 1000° and 2000°C, (2) 54*i*.

Bourdeau, R. G. Process of preparing boron carbide from boron halide and a hydrocarbon, P (10) 260*i*. See Powell, H. W.

Bourgeaux, M. See Lajarte, S. D. de.

Bourgeois, J. L. See Anthony, A. M.

Bouvier, G. Ceramic and tar bonded brick furnace lining, P (11) 281*j*. See Hodl, F.

Bouxain, J. See Fripiat, J. J.

Bovarnick, B., and Flood, H. W. Method of making composite materials and resulting products, P (5) 130*b*.

Bowden, F. P., and Brookes, C. A. Frictional anisotropy in nonmetallic crystals, (11) 296*g*.

Bowden, F. P., and Hanwell, A. E. Friction of clean crystal surfaces, (11) 296*e*.

Bowden, J. J. Flux used in the making of steel, P (8) 181*c*.

Bowers, R. W. Method of bonding, P (4) 101*b*.

Bowling, J. E., Jr. See Moore, R. W.

Bowman, A. L. See Bowman, M. G.

Bowman, H. A., and Schoonover, R. M. Cartesian diver as a density comparator, (10) 267*a*.

Bowman, J. Refractory and method of making, P (2) 45*e*, P (9) 227*e*.

Bowman, M. G. See Benz, R.

Bowman, M. G., Hull, D. E., Whitman, W. G., Arnold, G. P., and Bowman, A. L. High temperature neutron diffraction furnace, (1) 13*g*.

Bowman, R. G. Apparatus for ceramic work in prosthetic dentistry, P (1) 9*a*.

Bowser, R. E. See Best, H. S.

Box, S. Partially ionic model for alkaline earth oxide modules, (3) 87*j*.

Boyce, W. A. Quartz tube coating, P (11) 287*j*.

Boyd, F. R., and Schairer, J. F. System $MgSiO_3$–$CaMgSi_2O_6$, (2) 57*f*.

Boyd, G. D., and Patel, C. K. N. Enhancement of optical second-harmonic generation (SHG) by reflection phase matching in ZnS and GaAs, (8) 197*f*.

Boyd, G. E. See Chase, J. W.

Boyer, J. L. Compression bonded semiconductor device, P (9) 230*a*.

Boyer, J. T. See Maloney, T. C.

Boyer, W. H. See Hildinger, W. M.

Boykin, O. F. See Daily, A. M.; Faber, W. M., Sr.

Bracco, D. J. See Jaworowski, R. J.

Bradbury, E. J., Sutton, C. R., and Worn, D. K. Composite neutron-absorbing materials for control-rod and screening applications, (3) 70*j*.

Bradbury, R. A. See O'Connor, J. R.

Bradfield, G. Sensitive weighing apparatus, P (10) 268*b*.

Bradford, I. T. See Cooper, A. R.

Bradley, D. Total hemispherical emittance of coated wires, (4) 112*e*.

Bradley, E. F., Bartlett, E. S., Ogden, H. R., and Jaffee, R. I. Coatings for columbium base alloys, P (3) 65*c*.

Bradley, W. W. See Burns, R. M.

Bradshaw, S. E., and Wilkes, J. G. Method for forming a tetragonal crystalline oxide coating on germanium, P (11) 286*g*.

Bradt, R. C. Cr_2O_3 solid solution hardening of Al_2O_3, (2) 54*f*. See Cooke, F. W.

Bradu, G. M., and Grosborne, P. F. Cathode ray tube envelope, P (7) 149*j*.

Brady, E. L. (editor). National Standard Reference Data System—status report, April 1966, (4) 112*h*.

Brady, L. G. Enclosure means in a glass sheet drawing apparatus, P (9) 219*c*.

Braekken, H. Two higher phase transitions of WO_3, (2) 59*g*.

Bragin, B. A. See Nagornyi, A. I.

Brailovskii, V. B. See Mazurin, O. V.

Brailovskii, V. B., Rozenblyum, M. Ya., and Mazurin, O. V. Polarization of high-alkali commercial glasses adjacent to an electrode, B (4) 113*d*.

Braiman, J. See Comado, S. J.; Sparrow, L. R.

Brainina, D. Z., Averbukh, B. D., Zhuravleva, M. G., and Chufarov, G. I. Equilibrium in the reduction of a manganese-zinc ferrite by hydrogen, (4) 107*j*.

Braithwaite, C. J. R. Petrology of middle Devonian limestones in South Devon, England, (1) 25*d*.

Brajer, E. J. Process for fabricating miniature capacitors, P (1) 11*c*.

Braman, R. W. See Allen, R. V.

Bran & Luebbe Komm. Ges. Pumping of suspensions, P (1) 13*a*.

Brander, R. W. Epitaxial growth of silicon carbide, (3) 75*i*.

Brander, R. W., Lamb, D. R., and Rundle, P. C. Electronic conduction in thermally grown silicon dioxide films, (5) 126*f*.

Brandt, M. O. Lens aligning and blocking apparatus, P (1) 5*h*.

Brandt, W. O. Modernization of small plants, (3) 80*a*.

Braniecki, E. L., Jr. Semiconductor devices with layer of silicon monoxide and germanium mixture and methods of fabricating them, P (9) 232*b*.

Branin, P. B. Method of making phosphor screens, P (8) 185*g*.

Braniski, A. Refractory products chemically bonded with barium aluminate refractory cement, (5) 123*j*. Strontium cements, (7) 147*c*.

Braski, D. N. See Buckley, J. D.

Brassart, F. A. See Gulbransen, E. A.

Brassfield, H. C. See Turner, P. P.

Bratschun, W. R. Process for producing dense ceramic of lead zirconate-titanate, P (5) 128*i*.

Bratton, R. J., and Tien, T. Y. Phase transitions in the system $BaTiO_3$-$KNbO_3$, (3) 76*f*.

Brau, M. J. See Hilton, A. R., Jr.

Braun, A. B. See Fitch, F. T.

Braun, A. B., and Fitch, F. T. Microspheres containing colloidal carbon, P (10) 259*i*.

Braun, G., and Kovacs, A. J. Variations of the glass transition temperature in binary systems by statistical distribution, B (2) 61*i*.

Braun, M. J. Forming a resistor with thin, compressed contact portions, P (5) 127*d*.

Braunstein, A. I., Braunstein, M., and Picus, G. S. Voltage dependence of the barrier heights in Al_2O_3 tunnel junctions, (5) 139*c*.

Braunstein, A. L., and Braunstein, M. Thin film negative resistance device, P (8) 186*c*.

Braunstein, J. See Thomas, C.

Braunstein, M. See Braunstein, A. I.; Braunstein, A. L.

Bray, A., and Calcatelli, A. Vacuum deposited films at high temperature, (2) 47*e*.

Bray, D. T., La Grange, L. D., Merten, U., and Park, C. D. Fuel cell having zirconia-containing electrolyte and ceramic electrodes, P (4) 101*g*.

Bray, P. J. Nuclear magnetic resonance studies of glass structure, B (9) 245*g*.

Brayman, J. Control of stresses during shock-aided hydrostatic extrusion, P (5) 130*d*.
Brayshaw Furnaces, Ltd. Radiant tubes for furnaces, P (1) 15*c*.
Bre, M. Manufacture of complex aluminous metal-glass products of high strength, P (4) 94*b*. Method of changing the equilibrium thickness of a glass sheet being formed on a molten metal bath, P (8) 177*h*.
Breakiron, R. L., and Dyrenforth, W. P. High tension separation of materials, P (9) 235*h*.
Breckenridge, F. C. United States standard for the colors of signal lights, (3) 66*j*.
Bredig, M. A. See Lichter, B. D.
Brekhovskikh, S. M., Grinshtein, Yu. L., Landa, L. M., and Chubkina, N. I. Influence of nuclear radiations on structure and phase changes of glass-ceramics, B (9) 246*a*.
Brekhovskikh, S. M., Viktorova, Yu. N., Zelentsov, V. V., and Zelentsova, S. A. Influence of the chemical properties of certain elements on the optical stability of glasses to radiation, B (9) 245*h*.
Bremser, A. H., and Nelson, J. A. Phosphate bonding of zirconia, (4) 97*a*.
Bresker R. L. See Voronin, N. I.
Bresker, R. I., Voronin, N. I., and Khrycheva, D. D. Effect of impurities in silicon carbide on the properties of heating elements, (5) 122*c*.
Breton, E. J. Corrosion-inhibited sintered composite of a metal matrix with occluded cement, P (10) 249*a*.
Brewer, L., and Rosenblatt, G. M. Thermodynamics of suboxide vaporization, (4) 112*e*.
Brewster, G. F. Glass compositions, P (7) 149*d*. Ophthalmic segment glass compositions, P (1) 6*g*.
Brezny, B. Phase changes in the system periclase-wustite during heating in air, (2) 55*a*.
Brezny, B., and Smutny, Z. Mechanism of the formation of a direct bond between chrome spinel and periclase, (8) 180*c*.
Briancon, D. See Thery, J.
Brichard, E., Lambert, M., and Malicheff, A. Method and tank furnace for glassmaking, P (8) 178*i*.
Brichard, E., and Plumat, E. Process and apparatus for forming glass sheets on a molten metal bath, P (8) 178*e*.
Briere, J. M. E. A. Continuous dryer for ceramic products, P (2) 52*d*.
Briggs, W. S. See Magee, J. S.
Bright, N. F. H. See Coats, A. W.; Heyding, R. D.; Webster, A. H.
Bril, A. See Wanmaker, W. L.
Bril, A., and Wanmaker, W. L. Fluorescent properties of some europium-activated phosphors, (7) 155*j*.
Bril, A., Wanmaker, W. L., and Laat, C. D. J. C. de. Fluorescent properties of red-emitting europium-activated phosphors with cathode ray excitation, (9) 229*i*.
Brill, R. H. Great glass slab from ancient Galilee, (11) 273*j*.
Brinck, J. K. See Cleland, R. L.
Brindlinger, O. H. Heating device, particularly for kilns firing heavy ceramics, P (7) 160*b*.
Brinkerhoff, G. E. See Walther, F. H.
Brinsmead, K. H. See Fischman, J. L.
Brion, H. See Levecque, M.
Brisse, F., and Knop, O. Pyrochlores (II) investigation of $La_2Ce_2O_7$ by neutron diffraction, (7) 166*j*.
Brissette, L. A. See Spriggs, R. M.
Brite, D. W., and Sump, K. R. Cermet materials and process of making, P (1) 7*b*.
British Aluminium Co., Ltd. Method for manufacturing solid current conducting elements, P (8) 181*c*.
British Ceramic Research Association. Manufacture of blocks primarily for building, P (5) 122*b*. Structural elements having a facing of ceramic tiles, P (1) 6*j*.
British Glass Industry Research Association and Mattocks, G. R. Furnaces for glass manufacture and a method of operation thereof, P (4) 105*e*.
British Industries Corp. Method of manufacturing a foundry core, P (8) 181*b*.
British Petroleum Co., Ltd. Methods of and apparatus for monitoring viscosity, P (9) 234*e*. Sight glass, P (8) 179*b*.
British Plaster Board (Holdings), Ltd. Improvements in gypsum plasters, P (2) 35*a*.
British Titan Products Co., Ltd. Apparatus for pulverizing, P (8) 190*b*. Fluid bed process for producing rutile pigment and reducing pigment accretion, P (2) 54*b*. Fluidized bed process for producing pigmentary titanium dioxide with reduced accretion therein, P (10) 269*f*. Fluidized bed process for the production of titanium dioxide, P (8) 190*e*. Grinding solids in liquid, P (4) 103*g*. Oxidation of silicon tetrahalides, P (1) 16*a*. Process for milling of particulate solids in liquids, P (10) 266*g*. Process for the production of pigment from conditioned and calcined titanium dioxide particles, P (11) 292*a*. Production of alkyl titanates, P (9) 236*a*. Production of titanium dioxide, P (1) 16*b*, P (11) 292*b*. Titanium dioxide pigments, P (10) 270*b*. Titanium pigments, P (3) 83*f*. Treatment of particulate solids, P (5) 133*b*.
Brix Corp. Brick wall panel and method of making, P (10) 256*e*.
Brixner, L. H. Luminescent molybdate and tungstate compositions, P (11) 285*j*. Red luminescent composition product and process, P (4) 102*j*. Single crystalline calcium-aluminate, $CaLnAl_4O_{25}$, (11) 300*i*. Study of the calcium molybdate-rare earth niobate systems, (4) 110*e*. Thermoelectric compositions of $Nb_{2-x}Ta_{1-x}Si_xGe_{1-x}$, P (4) 103*a*.
Brixner, L. H., and Abramson, E. Luminescent properties of the rare earth vanadates, (9) 240*i*.
Brixner, L. H., and Flournoy, P. A. Calcium orthovanadate $Ca_3(VO_4)_2$—a new laser host crystal, (9) 228*j*.
Brixner, L. H., Flournoy, P. A., and Babcock, K. Note on calcium orthovanadate, (3) 87*c*.
Brizes, W. F., and Tobin, J. M. Isolation of the zeta phase in the system tantalum-carbon, (3) 86*a*.
Brock, J. C. F. See Berman, R.
Brocklehurst, J. E. Method of testing graphite, P (2) 44*d*.
Brockman, F. G. Method of manufacturing a magnetic member having a coating of crystalline ferromagnetic material having uniaxial magnetic anisotropy, P (5) 128*f*.
Brockway Glass Co., Inc. Automatic lehr unloader, P (7) 149*i*. Coating composition and glassware coated with the same, P (1) 4*g*. Corrosion retarding fluorine treatment of glass surfaces, P (8) 176*j*. Glass to glass adhesives, P (11) 278*b*. Glassware orienting device on glazing machine, P (3) 67*j*. Infrared heat control for glass forming molds, P (10) 255*g*. Method of increasing the durability of glassware, P (1) 6*b*. Method of treating opal glass surfaces, P (2) 39*e*.
Broderick, J. P. See Quaas, J. F.
Broderick, R. L., and Porteus, C. Weigh feeder system, (5) 130*b*.
Brodov, V. G. See Kuznetsov, V. G.
Brodsky, J. C. See Ballass, J. T.
Brody, T. P., and Kunig, H. E. High-gain InAs thin-film transistor, (9) 229*a*.
Bron, V. A. Some crystal-chemical relations in the activated sintering of highly refractory oxides in solid phase, (5) 138*g*.
Bron, V. A., and Semavina, K. P. Chrome-alumina concretes and shapes, (9) 223*i*.
Bron, V. A., and Semkina, N. V. Factors determining the activated recrystallization sintering of aluminum oxide, (5) 136*d*.
Bronnes, R. L., Hughes, R. C., and Sweet, R. C. Metallizing nonmetals, P (11) 286*d*.
Bronstein, J. See Volterra, V.
Brooker, E. J. See Harris, D. C.
Brookes, C. A. See Bowden, F. P.
Brookes, C. J. Australian ceramic industry, (11) 303*e*.
Brookman, J. W. See Vogel, M. J.
Brossard, D. J. See Charpentier, M.
Broussard, G. R. Method of making semiconductor devices, P (10) 264*c*.
Brown, A. E., and Allen, G. W. Ultrasonic flow measurement, (7) 150*e*.
Brown, A. E., and Fischer, R. J. Method of firing ceramics, P (2) 48*g*.
Brown, A. H., and Hanson, C. Effect of oscillating electric fields on coalescence in liquid + liquid systems, (7) 162*f*.
Brown, A. W. Production of polarizing elements, P (3) 69*c*.
Brown, C. E. Strip transmission line ferrite filter-limiter having a ferrite sphere positioned beneath overlapping conductors, P (2) 49*a*.
Brown, C. J., Jr. Increasing the melting rate of glass batch, P (9) 220*a*.
Brown, D., Douglas, R. W., Nath, P., and Paul, A. Redox equilibria in glasses—reply, (5) 119*c*.
Brown, D. M. See Gray, P. V.
Brown, D. R. Case history of filter press control test, B (1) 30*c*.
Brown, G. E., Jr. Coaxial disk and cylindrical rotor refining apparatus, P (9) 219*c*.
Brown, G. J. See Harper, F. C.
Brown, G. N. Process and apparatus for impacting and elutriating solid particles, P (7) 158*k*.
Brown, G. N., and Stenborg, W. D. Method and apparatus for solids blending, P (8) 186*j*.
Brown, H. W. Incandescent electric lamps, P (8) 177*k*.
Brown, J. F. W., Cronin, M. E., and Stevenson, J. A. Sparking plug electrodes, P (10) 265*g*.
Brown, J. J., and Hummel, F. A. Phase equilibria and manganese-activated luminescence in portions of the system $Zn(PO_3)_2$-$Cd(PO_3)_2$-$Mg(PO_3)_2$, (3) 87*a*. Phase equilibria and manganese-activated luminescence in the systems CdO-P_2O_5 and $Zn_2P_2O_7$-$Cd_2P_2O_7$—summary for the system ZnO-CdO-P_2O_5, (7) 166*i*.
Brown, L. H., and Dede, J. B., Jr. Method for cold molding pitch bonded shaped carbon bodies, P (3) 72*j*.
Brown, L. T. Method of feeding mixed colorants to glass in the forehearth, P (10) 255*g*.
Brown, M., and Murphy, E. G. Measurements of the self-diffusion coefficient of uranium hexafluoride [at 0° to 70°C], (7) 165*i*.
Brown, R. M. See Pirogov, Y. A.
Brown, R. S., and Gulliver, H. W. Manufacture of semiconductor devices, P (9) 231*d*.
Brown, W. F. See Adams, E. A.
Brown, Boveri & Cie Akt.-Ges. High voltage insulator filled with semiconductive foam containing gas under superatmospheric pressure, P (9) 231*c*.
Browne, C. M., and Beckham, R. R. Method and apparatus for forming a film on a glass surface, P (5) 120*j*.
Brownell, W. E. Dryer operation, B (8) 212*d*. Structure of clay minerals, B (1) 30*b*. See Hunter, O., Jr.
Brownell, W. E., Kenna, J. L., and Witko, P. P., Jr. Staining of mortar by manganese colored brick, (1) 6*h*.
Browning, J. S. See Millsaps, F. W.
Browning, J. S., and Adair, R. B. Flotation of mica, P (10) 269*e*. Selective flotation of mica from Georgia pegmatites, (1) 28*b*. Selective flotation of mica from pegmatites, (4) 106*f*.
Browning, M. F. See Blocher, J. M., Jr.; Oxley, J. H.
Brownlow, A. D. See Champlin, J. B. F.
Brownson, J. S. Method of making a heterojunction semiconductor device, P (11) 286*j*. Three-point probe method for electrical characterization of epitaxial films, (3) 81*h*.
Bruce, C. F., and Phair, E. Degassing of glass tubes, (9) 217*g*.
Bruce, R. W. See Berry, T. F.
Bruchmann, H. See Estes, J. F.; Smith, L. W.
Brueckner, E. New light on the shaping of bodies, (7) 155*a*.
Brueckner, R. Effect of mechanical vibration on the flow properties of kaolin-water mixtures, (7) 154*i*.
Bruegger, W. Electric tunnel kiln for firing hard porcelain in a reducing atmosphere, (8) 189*a*.
Bruhl, D. A., Jr., and Counts, W. E. Cermet resistance composition and resistor, P (9) 230*g*.
Bruin, H. J. de. Method for [platinum] bonding beryllium oxide to graphite, P (4) 98*c*.
Bruin, H. J. de, Watson, G. M., and Blood, C. M. Cation self-diffusion and electrical conductivity in polycrystalline beryllium oxide, (5) 134*j*.
Brukl, C. E. See Rudy, E.
Brunauer, S. See Mikhail, R. Sh.
Brunswick Corp. Means for measuring the specific gravity of liquids and solutions, P (10) 268*d*.
Brush Beryllium Co. Vacuum fired beryllia ware, P (4) 99*e*.
Brusko, G. G. See Bannikov, G. K.
Bruyn, P. L. de. Some aspects of classical surface thermodynamics, B (9) 245*e*. See Bonis, L. J.
Bryan, A. R. Means for holding kiln brick within a rotary kiln, P (10) 259*e*.
Bryant, B. E. Method of increasing the viscosity of magnesia cements, P (11) 275*f*.
Braynt, E. E., and Gugeler, A. L. Coating metal with a clayless suspension of ceramic slips, P (4) 92*e*.
Bryantsev, B. A. See Toropov, N. A.
Brzozowski, W. S., Gauk, W., and Fiszdon, ?. Ceramic materials for MHD generators, (2) 46*i*.
BTU Engineering Corp. Method for continuous gas diffusion, P (1) 11*c*.
Buchkremer, H. Europe reports progress in whiteware fast firing, (4) 99*h*.
Buchner, S. Test methods and strength study of ceramic grinding wheels, (5) 115*f*.
Buck, G. See Fischer, K.
Buck, I., Jr. See Blazek, R. J.
Buckley, D. H., and Johnson, R. L. Metallic film diffusion for boundary lubrication, P (8) 181*h*.
Buckley, J. D., and Braski, D. N. Elastic modulus of stabilized zirconia, (5) 135*c*.
Budd, S. M. Redox equilibria in glasses—comments on papers, (5) 119*c*.
Buddington, A. F., and Lindsley, D. H. Iron-titanium oxide minerals and synthetic equivalents, (1) 20*i*.
Budnikov, P. P., Azelitskaya, R. D., and Prikhodchenko, N. A. Improvement in construction properties of cement, (9) 214*d*.
Budnikov, P. P., Bulavin, I. A., and Belkov, A. F. Replacing feldspar by alkaline waste in industrial porcelain, (3) 82*i*.
Budnikov, P. P., and El'-Rafii, E. A. Magnesite refractory with high CaO content, (7) 151*h*.
Budnikov, P. P., and Khvostenkov, S. I. Study of the kinetics of hardening of cements by the electrochemical method, (4) 91*a*.
Budnikov, P. P., Kostyukov, N. S., and Morgunov, N. N. Thermal electromotive force in electrotechnical porcelain, (5) 125*i*.
Budnikov, P. P., and Lyutsedarskii, V. A. Study of the reaction of iron with certain enamel melts, (5) 117*h*.
Budnikov, P. P., and Maslennikova, G. N. Effect of quartz on the mechanical strength of electrotechnical porcelain, (10) 261*f*.
Budnikov, P. P., Shakhmagon, N. V., and Entin, Z. B. Effect of sodium silicofluoride on the viscosity of clinker liquid phase, (9) 214*j*.
Budnikov, P. P., Tresvyatskii, S. G., and Kushakovskii, V. I. Binary phase diagrams of UO_2 with Al_2O_3, BeO, and MgO, (3) 83*i*.
Budrin, D. V., Suchkov, V. D., and Yaroshenko, Yu. G. Rapid determination of coefficients of temperature conductivity and heat transfer of refractories, (5) 123*h*.
Budworth, David, Ltd. See David Budworth, Ltd.
Budworth, D. W. See Ammar, A. A.
Buessem, W. R. Electroceramics today, (7) 155*i*.
Buettel, H. Method of sealing contact reeds in a glass tube, P (2) 39*b*.
Buffet, J. Hot working of materials, P (11) 281*g*.
Bugai, V. I. New method of determining deformations in cast and cermet materials, (2) 50*g*.
Bugenis, C. K. See Preuss, L. E.
Bugi, J. New processes for the fabrication of special ceramics, (3) 80*a*.
Bui, V. T. See Ramalho, R. S.
Buie, J. L. Dielectric isolation for monolithic circuit, P (8) 184*h*.
Buketov, E. A., Mekler, L. I., Nadirov, E. G., Nashinkin, A. S., and Trofimova, L. D. Study of the system tellurium-tellurium dioxide, (4) 111*c*.
Buketov, E. A., Pashinkin, A. S., Ugorets, M. Z., Muldagalieva, R. A., and Sapozhnikov, R. A. Thermal stability of silver selenite, (11) 302*g*.
Bukun, N. G. See Ukshe, E. A.
Bulavin, I. A. See Budnikov, P. P.

Bulcraig, W. R., and Blood, W. R. Television tube assemblies, methods of forming such assemblies, and implosion guards therefor, P (7) 150*f*.

Bullard, R. L., Hasbrouck, R. A., Schlemmer, P. S., and Thun, R. E. Fabrication of cermet film resistors to close tolerances, P (7) 156*d*.

Bullough, V. L., and Kibby, R. M. Manufacture of shaped carbon bodies, P (9) 226*b*. Method of manufacturing shaped carbon bodies, P (2) 44*b*.

Bul'onkov, N. A. See Bol'shakov, K. A.

Bundy, F. P. Plural wedge-shaped graphite mold with heating electrodes, P (10) 260*c*.

Bunge, F. H., and Vaughan, H. H. Use of kiln gas for production of magnetic iron oxide, P (2) 54*c*.

Buntenbach, F., Buntenbach. M., and Stautz, K. Highly hydration stable sinters of dolomite, magnesite, lime, or the like, P (1) 7*f*.

Buntenbach, M. See Buntenbach, F.

Bura, P. Parametric amplification with superconducting films, (4) 100*j*.

Burch, C. R. Apparatus for separating solid materials in liquid suspensions, P (3) 80*d*.

Burdick, V. L., and Day, D. E. Coordination of aluminum ions in tricalcium aluminate, (3) 64*b*.

Bureau d'Etudes Industrielles Fernand Courtoy S.A. Composite structures made by bonding ceramics, cermets, alloys, heavy alloys, and metals of different thermal expansion coefficient, P (2) 43*i*. Methods of making bonded structures, P (5) 128*c*.

Burger, W. Wobbe index, its importance in industrial firing processes, and possibilities of their control by its use, (2) 52*i*.

Burger Eisenwerke Akt.-Ges. Processes for the decorative enameling of domestic appliances, P (8) 174*j*.

Burggraaf, A. J. Strengthening of glass by ion exchange (II) stress formation and stress relaxation after ion exchange in alkali aluminosilicate glasses in connection with structural changes in the glass, (2) 37*a*. See Spoor, W. J.

Burke, J. E. Modern developments in ceramic oxides and glasses, (11) 303*f*.

Burke, O. W., Jr. Silica pigments and preparation thereof, P (5) 133*k*. Silica pigments and process for producing same, P (11) 292*f*.

Burke, O. W., Jr., and Jackson, C. B. Silica pigments and preparation thereof, P (1) 16*c*, P (9) 236*g*.

Burke, O. W., Jr., and Kizer, J. A. A. Method and means for reducing fouling of equipment in the preparation of precipitated silica pigment, P (9) 236*a*.

Burkett, W. E., and Batchelder, P. Method for making burned clay building products, P (7) 150*i*.

Burkhardt, P. J., and Gregor, L. V. Kinetics of the thermal oxidation of silicon in dry oxygen, (1) 21*j*.

Burklo, D. C. Suspended refractory brick, P (1) 8*g*. See Reynolds, C. B.

Burklo, D. C., and Miller, C. H. Suspended refractory units, P (1) 8*h*.

Burlington Industries, Inc. Polyvinyl chloride resin glass bond with secondary amino-alkyl silane primer, P (8) 178*e*.

Burmeister, J. Crystal growth of wustite, $Fe_{1-x}O$, (7) 162*j*.

Burnham, K. D., and Wainer, E. Potential uses of wet processed wollastonite, (4) 106*c*.

Burns, R. M., and Bradley, W. W. Protective Coatings for Metals, B (11) 306*b*.

Burns, S. J., and Webb, W. W. Plastic deformation during cleavage of LiF, (7) 166*d*.

Burov, G. V. See Strekalovskii, V. N.

Burrell, D. C. Trace elements in marine waters by atomic absorption spectrophotometry, (10) 267*j*.

Burress, G. T. See Stone, R. L.

Burriel Marti, F., and Alvarez Herrero, C. Complexometric determination of iron, aluminum, calcium, and magnesium in cements and clays (III), (4) 90*h*.

Burroughs Corp. Apparatus for use in handling ferrite cores, P (3) 77*c*. Gaseous cold cathode indicator tube having a segmented electrode and an insulating shield plate, P (1) 10*f*. Glow cathode indicator tube having memory, P (8) 184*d*. Insulating gate thin film transistor having a thin insulating layer overlapping a thick insulating layer, P (8) 184*h*. Semiconductor [multiple-zone] switch devices, P (5) 129*e*.

Burtch, F. W., and Muirhead, J. F. Aqueous solutions of devitrifiable glasses, methods of using, and products thereof, P (10) 254*f*.

Burton, M. S. See Ritter, J. E., Jr.

Burwell, B. Process for producing pure fused vanadium oxide from ammonium metavanadate, P (10) 269*j*. Process for recovering pure vanadium oxide from low grade vanadium ores or concentrates, P (3) 83*c*.

Burzynski, A. J., and Martin, R. E. Preparation of silica gel, P (9) 236*e*.

Busby, T. S. Importance of research for better use of refractories in glass furnaces, (5) 123*c*. Report on the symposium on refractories, (5) 123*a*.

Bussey, H. E., Gray, J. E., Bamberger, F. C., Rushton, E., Russell, G., Petley, B. W., and Morris, D. International comparison of dielectric measurements, (3) 76*b*.

Bustamante, R. L. Bulb assembly, P (1) 10*h*.

Butenko, V. A., Dudavskii, I. E., Kolesnik, M. I., and Sokolov, I. N. Highly refractory cements containing iron scale, (4) 97*c*.

Butler, G. See Di Stefano, V. N.

Butler, J. F. Diffused junction diodes of PbSe and PbTe, (4) 100*c*.

Butler, J. F., Calawa, A. R., and Harman, T. C. Diode lasers of $Pb_{1-y}Sn_ySe$ and $Pb_{1-x}Sn_xTe$, (11) 293*c*.

Butler, J. K. Ferrite tuned coaxial cavity [resonator] apparatus, P (2) 47*f*.

Butler, K. H., Koury, F., and Waymouth, J. F. High pressure discharge device having a fill including iodine, mercury, and at least one rare earth metal, P (10) 264*c*.

Butler, R. C. Refractory binders and molds made therefrom, P (7) 154*c*. Refractory binding material and refractory molds made therefrom, P (2) 45*a*.

Butt, Yu. M., Timashev, V. V., Vysotskii, D. A., and Panina, N. S. Firing portland cement charges at high temperatures (up to 2273°K), (9) 214*c*.

Butterworth, B., and Carter, E. F. Laboratory tests and the durability of brick (VIII) frost dilatometry—modified methods, (5) 121*j*.

Buysman, P. J. See Bolk, A.

Buzhinskii, I. M., Khomyakov, A. N., Sabaeva, E. I., and Kirillova, I. I. Study of structural changes in glasses and crystalline glass materials by various methods, B (9) 246*e*.

Bychkov, V. P. See Kuznetsov, V. G.

Byfield, D. R., and Reintjes, G. G. Apparatus for lining [rotary] kilns, P (4) 105*h*.

Bylander, E. G. Reproducible preparation of $Sn_{1-x}Pb_xTe$ epitaxial films with moderate carrier concentrations, (10) 263*e*.

Byrer, T. G. See King, B. W., Jr.

Byrns, A. C. Process for the production of refractory hard metal borides, P (9) 227*d*.

Bystrand, F. See Mansikka, K.

Bystrikov, A. S. Nature of $\alpha \rightleftharpoons \beta$ transformations of quartz, (8) 203*a*.

Bystrova, K. A. See Tumanov, V. I.

Cabannes, F. Diffuse reflection and emission of certain sintered white oxides, (1) 17*h*.

Cable, M. See Clarke, A. R.; Cooper, A. R.

Cable, M., and Rasul, C. G. Spontaneous bubble formation in silicate melts at high temperatures (II) effect of wet atmospheres and behavior of mixed alkali glasses, (11) 277*c*.

Cable, T. H., Jr., Hinds, G. W., and Koepplin, W. J. Process for melting and refining glass batch, P (11) 279*a*.

Cabot Corp. Apparatus and process for the production of metal oxides, P (9) 235*i*. Tar-bonded refractories containing pine tar, P (11) 283*d*.

Cabri, L. J. See Kracek, F. C.

Caddes, D. E., Quate, C. F., and Wilkinson, C. D. W. Conversion of light to sound by electrostrictive mixing in solids, (8) 183*g*.

Cadenhead, D. A. Neutron irradiation and surface homogeneity of graphitic materials, (2) 55*h*.

Cadoff, L. H. See Adelsberg, L. M.

Cadwell, R. F. See Klein, M. V.

Cail, D. See Oxley, G. H.

Caillat, R. See Accary, A.

Calandrello, N. A., Hill, J., and Royan, J. Bonded contacts for gold-impregnated semiconductor devices, P (4) 100*g*.

Calawa, A. R. See Butler, J. F.

Calbick, C. J. Interaction of electron beams with thin films, B (11) 305*f*.

Calcamuggio, G. L. See Bacon, F. R.

Calcatelli, A. See Bray, A.

Calcatelli, A., and Cerutti, G. Temperature coefficients of resistance of evaporated thin films, (2) 47*d*.

Caldwell, M., Hayhurst, A., and Webster, R. Role of titania in bauxite refractories, (9) 224*d*.

Calgon Corp. Phosphate glass composition, P (2) 39*i*.

Calhoun, F. L. Bottle inspection system, P (3) 67*j*.

Calhoun, W. A. See Hill, T. E., Jr.

California Institute Research Foundation. Surface barrier indium arsenide transistor, P (2) 49*b*.

California Metal Enameling Co. Reflex reflecting article for use as a sign or the like, P (1) 3*c*.

Callaby, D. R. Effect of *a* domains on the movement of *c* domain walls in $BaTiO_3$, (8) 195*f*.

Callahan, J. L., and Knipple, W. R. Attrition resistant solid catalysts, P (11) 281*h*.

Callanan, Sister J. E., and Smith, N. O. Crystallographic studies of NH_4Cl-NH_4Br solid solutions, B (5) 139*f*.

Callander, A. H., Lampson, M. L., and Nitsche, J. E. Method and apparatus for manufacturing glass beads, P (3) 68*g*.

Calleja, J. Nominal and actual content of hydraulically active materials in cements, (9) 215*b*. Plaster content of portland cement, (4) 91*b*.

Calleja, J., and Bacle, B. Determination of free silica in cement raw materials, (4) 90*h*.

Callow, A. E. See Evans, A. W.

Caloric Corp. Radiant buner, P (5) 132*g*.

Calvelo, A., and Pereira, E. High temperature laboratory furnace, (4) 105*e*.

Calvert, J. P. See Kruger, J.

Camarata, F. J. Press sealing apparatus, P (3) 69*j*.

Cambridge Thermionic Corp. Adjustable capacitor with moving dielectric, P (2) 47*f*.

Cameron, D. I. Oxygen potential diagram summarizing Fe-Mn-SiO equilibria at 1600°C, (3) 87*i*.

Cammerer, C., and Achtziger, J. Estimation of the effect of moisture on the thermal conductivity of structure and insulating materials, (3) 80*i*.

Campbell, D. S. See Stirland D. J.

Campbell, J. J. See Pawel, R. E.

Campbell, R. B. See Chu, T. L.

Campbell, R. H., and Tobin, R. E. Core and cylinder strengths of natural and lightweight concrete, (7) 146*j*.

Campbell, W. J. Thermal expansion of magnesium oxide—an interlaboratory study, (4) 111*e*.

Campbell, W. W. See Leatham, E.; Pack, A. H.; Tvergaard, A. M.

Campbell, W. W., Leatham, E., and Pack, A. H. Material handling, P (4) 98*c*.

Campbell, W. W., and Rossi, C. E. Heat transfer unit, P (7) 153*c*.

Campbell Chain Co. Chain for rotary kilns, P (1) 14*j*.

Canadian Industries, Ltd. Nonglossy surface coatings, P (10) 250*e*.

Canadian Patents & Development, Ltd. Ceramic capacitors, P (10) 263*c*. Particle classifier, P (9) 236*d*. Synthetic plaster set retarder, P (5) 117*b*.

Canadian Refractories, Ltd. Production of direct bonded basic brick, P (4) 99*c*. Spalling-resistant refractory brick, P (4) (4) 99*b*.

Cancela, G. D. See Dios Cancela, G.

Canfield, J. M., and Cutchen, J. T. Effect of ionized impurities on the current from shock-loaded quartz, (5) 135*h*.

Cannon, P. Graphite-catalyst charge assembly for the preparation of diamond, P (8) 173*i*.

Cannon, W. A. See Toy, M. S.

Capacho-Delgado, L. See Manning, D. C.

Cape, A. T. Means for preventing flashback in powder melting torches, P (1) 3*d*.

Cape, J. A. See Geller, S.; Kuendig, W.

Caplan, B. Bulk conveying of free flowing solids, (11) 288*e*.

Caplan, D., and Cohen, M. Scaling of Fe-26Cr alloys at 870° to 1200°C, (11) 300*f*.

Caprio, M. J., and Krisleit, R. F. Refractory composition, P (3) 73*d*.

Capriz, G., and Laratta, A. Extrusion of non-Newtonian bodies, B (7) 170*d*.

Capshaw, L. E. See Horton, T. P.

Carbond Corp. Abrasive tools and methods of making such tools, P (7) 145*h*.

Carbone Corp. Carbon and carbon-graphite bearings with antifriction surface, P (4) 98*d*.

Carbonisation Enterprise et Ceramique and Soubrier, J. L. Hydraulically or pneumatically operated reversing apparatus for regenerative furnaces, P (2) 52*j*.

Carborundum Co. Abrasive coated backing of sheathed synthetic fiber yarns, P (8) 173*g*. Ceramic compositions and process of making same, P (5) 124*e*, P (10) 259*f*. Composition including a carbide and a boride and tool made thereof, P (8) 173*h*. Heavy medium separation media and process, P (4) 106*b*. High beta thermistors, P (11) 285*f*. Organophilic and hydrophobic particles and their preparation, P (10) 260*b*. Polybenzimidazole resin bonded abrasive articles, P (10) 247*g*. Process of fireproofing a blend of ceramic fibers and acrylic resin fibers by heating in an oxidizing atmosphere, P (3) 72*g*. Production of refractory bodies, P (5) 125*d*. Refractory bodies and compositions and methods of making, P (9) 227*b*. Resin bonded abrasive articles containing olivine [as pore-forming material], P (10) 247*k*. Segmental [diamond] abrasive wheel, P (3) 63*h*.

Carborundum Co., Ltd. Cupola or like furnaces, P (1) 14*i*.

Cargill, G. S., III. See Walford, L. K.

Carithers, M. D. See Meaders, J. C.

Carl, D. G., and Steigelman, H. A. Method for increasing scratch resistance of a glass surface with a pyrolyzing treatment and a coating of an olefin polymer, P (9) 221*e*.

Carl Strutz & Co., Inc. Workpiece supporting and registering apparatus for bottle decorating apparatus, P (7) 150*f*.

Carl-Zeiss-Stiftung (trading as Jenaer Glaswerk Schott & Gen.). Barium borosilicate glass, P (8) 176*i*. Glass, P (10) 255*d*. Glass filaments, P (5) 120*a*. Glass suitable for solid body lasers, P (9) 220*g*. Molded devitrified glass elements, P (8) 178*a*. Optical glass, P (1) 6*a*, P (5) 121*c*, P (7) 150*a*. Optical glass and its production, P (4) 95*i*. Treating glass, P (8) 179*b*. See Jenaer Glaswerk Schott & Gen.

Carlberg, J. See Cline, C. F.

Carleton, H. R., and Soref, R. A. Modulation of 10.6μ laser radiation by ultrasonic diffraction, (10) 271*e*.

Carlson, H. F. See Naslund, E.

Carlson, W. G., Radus, R. J., and Moratis, C. J. Magnetic ceramic material, P (3) 78*c*.

Carlyle, R. L., and Johnson, W. E. Composition for the lamination of glass by means of epoxy resinous materials, P (9) 219*d*.

Carmi, A. Glass press mold sensing and indicating means, P (3) 67*i*. See Belentepe, Y. C.

Carnall, E., Jr., Hatch, S. E., Ladd, L. S., and Parsons, W. F. Method of molding magnesium fluoride, P (3) 68*j*.

Carnall, E., Jr., Hatch, S. E., and Parsons, W. F. Optical studies on hot-pressed polycrystalline CaF_2 with clean grain boundaries, B (2) 61*e*.

Carnevale, E. H., and Lynnworth, L. C. Ultrasonic measurement apparatus, P (8) 188*j*.

Carniglia, S. C. Grain boundary and surface influence on mechanical behavior of refractory oxides—experimental and deductive evidence, B (2) 61*h*.

Carothers, J. N., and Hurka, R. J., Jr. Process for removing impurities from by-product gypsum, P (9) 216*a*.

Carpco Research & Engineering, Inc. High tension separation of materials, P (9) 235*h*.
Carpenter, C. L., and Wendell, C. B. Apparatus and process for the production of metal oxides. P (9) 235*i*.
Carpenter, J. C. See Urmetz, W. W.
Carpentier, S. See Bedier, R.
Carr, K. L. Reciprocal stripline ferrite phase shifter having a folded center conductor, P (2) 49*d*.
Carraro, G., Domenici, M., and Zucca, T. Neutron diffraction research on vitreous silica, B (2) 61*g*.
Carrell, M. A., and Wilder, D. R. Visible and near-infrared absorption of uranium in sodium silicate glass, (7) 149*d*.
Carrier Corp. Method of applying a protective coating to a metallic structure, P (8) 174*h*.
Carrier Engineering Co., Ltd. Coating apparatus, P (1) 12*e*.
Carrison, L. C. See Sclar, C. B.
Carruthers, T. G., and Wheat, T. A. Hot-pressing of kaolin and of mixtures of alumina and silica, B (7) 170*b*.
Carson, F. J. See Leflet, H. A., Jr.
Carson, F. J., and Leflet, H. A., Jr. Apparatus for press bending glass sheets, P (3) 67*e*.
Carson, F. J., and Ritter, G. F., Jr. Apparatus for press bending glass sheets, P (10) 254*c*.
Carter, E. F. See Butterworth, B.
Carter, G. See Grant, W. A.
Carter, G. F. Cr-Fe diffusion coating ferrous metal substrate, P (3) 65*d*.
Carter, J. R. See Comer, J. J.
Carter, S. J. Tungsten carbide brazing, P (4) 92*f*.
Cartwright, J. K., and Hutchison, W. R. Apparatus for distributing and screening particulate material, P (1) 12*g*.
Cary, H. B. Arc welding with ac power and cored electrode, P (7) 147*h*.
Casalot, A. See Hagenmuller, P.
Casey, H. C., Jr., and Kaiser, R. H. Room temperature super-radiance radiation in *n*-type GaAs by continuous electron-beam excitation, (5) 138*c*.
Casey, J. J., and Garnache, R. R. Semiconductor method and device, P (11) 287*e*.
Cash, T. P. See Holt, J. P.
Casini, L. Process for making listels and ornamental moldings by an improved extruding device, P (11) 289*a*.
Castells, L. D. See Dalmau Castells, L.
Castrucci, P. P., Folsom, R. M., and Pieczonka, W. A. Fabrication of semiconductor devices, P (1) 10*d*.
Cataphote Corp. Apparatus for making glass beads, P (2) 38*e*. Colorless high index glass compositions, P (3) 67*a*. High titanate glass beads, P (3) 68*b*. Method for manufacturing glass beads, P (9) 221*c*. Yellow glass bead compositions, P (3) 69*i*.
Catharin, P. Measurement of the deformation of standard prisms with the elastograph, (7) 146*g*.
Cathers, G. I. See Bennett, M. R.
Catherwood, R. F. E. Controlling fluid flow, P (10) 268*c*.
Catling, H. W. Minoan and Mycenaean pottery—composition and provenance, (11) 274*a*. Spectrographic analysis of Mycenaean and Minoan pottery (I) introductory note, (11) 274*f*. See Millett, A.
Catling, H. W., and Millett, A. Study in the composition patterns of Mycenaean pictorial pottery from Cyprus, (11) 274*a*. Study of the inscribed stirrup-jars from Thebes, (11) 274*a*.
Catling, H. W., Richards, E. E., and Blin-Stoyle, A. E. Composition and provenance of Mycenaean and Minoan pottery, (11) 274*f*.
Cave, E. F. Method of making a composite insulator-semiconductor wafer, P (3) 78*i*, P (4) 101*h*. See Roswell, A. E.
Cawood Wharton & Co., Ltd. Study of a tunnel kiln after operation for almost two years at 1750°C, (7) 160*b*.
CBN Corp. Apparatus for producing pigmentary silica, P (2) 53*i*.
Cecil, T. A. See Goldberg, M. M.
Ceinturet, M. Ceramic engineer and his development, (9) 244*a*.
Celanese Coatings Co. Alkali metal silicate coating compositions, P (10) 250*b*.
Celotex Corp. Apparatus for making rigid mineral fiber panels, P (9) 219*e*.
Cementation Co., Ltd. Clay grouts, P (7) 150*h*. Silicate grouts, P (3) 64*g*, P (7) 154*c*.
Central Mfg. District. Expanded perlite and method for the formation thereof, P (9) 235*g*. Method for the formation of perlite structures, P (9) 223*b*.
Centre d'Etude de l'Energie Nucleaire. Production of monocrystalline high melting refractory materials and equipment therefor, P (3) 73*a*.
Centre d'Etudes Scientifiques et Techniques. See Electricite de France.
Centre National de la Recherche Scientifique. Apparatus for recording and regulating temperature during differential thermal analysis, P (8) 188*j*. Device for measuring the transconductance and output conductance of a transistor, P (7) 156*b*. Differential thermal microanalysis apparatus, P (2) 52*a*. Methods and devices for heating substances by means of radiant energy and plasma heat sources, P (4) 105*f*. Single crystal production, P (4) 103*j*.
Centre Technique des Tuiles et Briques. Charging and discharging installation for a ceramic dryer, P (11) 280*b*. Continuous drying of ceramic products, P (11) 290*h*.
Cerberus Akt.-Ges. Bonding of a ceramic part to a metallic part, P (5) 127*a*
Cerny, L. See Husa, V.
Cerrai, E., and Ghersini, G. Spectrophotometric determination of thorium with Arsenazo III in the organic phase after extraction with di-(2-ethylhexyl)-orthophosphoric acid, (8) 188*d*.
Cerutti, G. See Calcatelli, A.
Ceskoslovenska Akademie Ved. Semiconductor component with a *pn* junction and cooled by a Peltier cell, P (1) 11*e*.
Chaisse, F. See Bloch, D.
Champion Spark Plug Co. Ceramic sealing structure, P (3) 77*e*. Continuous heat treat furnace with a conveyor, P (10) 268*f*.
Champlin, C. S. Infrared heat control for glass forming molds, P (10) 255*g*.
Champlin, J. B. F., Thomas, R. D., and Brownlow, A. D. Laboratory testing and evaluation of porous permeable rock for nuclear waste disposal, (10) 257*e*.
Chan, F. L. Some observations on the use of certain analyzing crystals for the determination of silicon and aluminum, B (5) 139*i*. Spot test detection of sulfide in minerals, (8) 188*h*.
Chan, K. M., and Riley, J. P. Determination of molybdenum in natural waters, silicates, and biological materials, (2) 50*f*.
Chandler, H. W. Method of separating hafnium from zirconium, P (1) 15*i*.
Chandrasekharaiah, M. S. Dissociation energies of alkaline earth oxides, (8) 195*b*.
Chang, J. J. Method of making semiconductor integrated circuit elements, P (3) 78*j*.
Chang, K. K. N., Liu, S. G., and Prager, H. J. Infrared radiation from bulk GaAs, (8) 200*g*.
Chang, L. L., Esaki, L., and Jona, F. Electron tunneling from metal to InSb, (8) 196*e*.
Chang, L. L. Y., and Phillips, B. Phase transition in the system Ca_3WO_6-Sr_3WO_6, (9) 241*d*.
Chang, L. L. Y., Scroger, M. G., and Phillips, B. Condensed phase relations in the systems ZrO_2-WO_2-WO_3 and HfO_2-WO_2-WO_3, (5) 134*f*.
Chang, R. See Austerman, S. B.; Robertson, W. M.
Chang, S. S., and Bestul, A. B. Change in the heat capacity of boron trioxide during the glass transformation, (8) 175*b*.
Chanowitz, H. Method of and an apparatus for making sealed switches, P (9) 220*h*.
Chanowitz, H., and Weinreich, G. F. Method of and apparatus for making sealed switches, P (2) 39*e*.
Chao, H. C. See Hosford, W. F., Jr.
Chao, P. J., and Zupan, J. High temperature coatings for columbium alloys, P (11) 276*b*.
Chapin, A. F. Abrasive product, P (5) 115*g*.
Chapman, G. C., Jr., and Henry, K. M. Solder glass compositions and method of sealing therewith, P (3) 69*f*.
Chapman, I. D. See Hair, M. L.
Chapman, I. D., and Hair, M. L. Adsorption of ammonia on fluorine-containing porous glass, (1) 16*g*.
Chaporova, I. N. See Baskin, M. L.
Charbonnages de France. Method of and apparatus for grinding granular nonagglutinant materials, P (1) 12*i*.
Charles, J. P. Application and results of plastic refractory in soaking pits, (7) 151*c*.
Charlesworth, D. Primitive glass furnace in Cairo, (11) 274*d*.
Charpentier, M. See Levecque, M.
Charpentier, M., and Brossard, D. J. Apparatus for producing fine glass fibers, P (5) 119*j*.
Charschan, S. S., and Westgaard, H. Apparatus for processing materials in a controlled atmosphere, P (3) 77*b*.
Charvat, F. R. Basic refractory bricks, P (4) 98*c*.
Chas. Elbreder & Co., Inc. Free flowing treatment of glass beads, P (3) 67*e*.
Chas. Pfizer & Co., Inc. Method of preparing calcite and the product thereof, P (8) 190*c*. Process for reducing deterioration in equipment handling molten materials, P (2) 45*f*.
Chasanov, M. G. See Nelson, P. A.
Chase, A. B., and Osmer, J. A. Localized cooling in flux crystal growth, (7) 165*e*.
Chase, A. B., and Wilcox, W. R. Temperature fluctuations and striations in flux crystal growth, (7) 168*h*.
Chase, J. W., and Boyd, G. E. Radiolytic decomposition of crystalline alkali metal and alkaline earth bromates, B (9) 244*d*.
Chase-Shawmut Co. Electric fuse with separate quartz fillers having different grain sizes, P (3) 77*j*. High interrupting capacity fuses having casings of inorganic material, P (3) 78*a*.
Chassevent, L. E., and Goulounes, N. Method and apparatus for calcining gypsum in two stages, P (7) 147*e*.
Chattahoochee Brick Co. Brickmaking machine and process, P (2) 40*g*.
Chatterjee, B. See Murthy, H. P. S.
Chatterjee, N. B. See Banerjee, J. C.
Chatterjee, N. B., and Panti, B. N. Mullite refractories from clay-bauxite or quartz-bauxite mixes, (2) 42*b*.
Chatterji, S., and Jeffery, J. W. Volume expansion of hardened cement paste due to the presence of dead-burned CaO, (2) 34*f*; reply to discussion, (11) 274*h*.
Chattopadhyay, D., Dutta, M., Mandal, S. S., and Roy, S. B. Conduction behavior of mica at elevated temperatures, (8) 183*f*.
Chaudhari, P., Beardmore, P., and Eever, M. B. Thermodynamic properties of amorphous and hexagonal selenium, (2) 38*b*.
Chaudy, K. C. X-ray investigation of bentonites from Bhadres and Hathiki-Dhani, Barmer district, (8) 189*j*.
Chebotareva, T. E. Spectra of potassium silicate glasses and their relation to structure, B (9) 245*c*.
Chebukov, M. F., and Dolinskaya, N. G. Clinker formation in highly siliceous charges, (9) 214*a*.
Cheetham, C. J., Gissane, W. J. M., and Barrow, R. F. Electronic spectrum of the BeS molecule, (1) 18*d*.
Chekhovskoi, V. Ya. Thermodynamic properties of corundum, a standard substance in calorimetry, (8) 210*e*. See Kirillin, V. A.
Chemcut Corp. Method of etching aluminum, P (1) 3*a*.
Chemically Prestressed Concrete Corp. Expansive cements and components thereof, P (5) 116*f*.
Chemische Fabrik Kalk G.m.b.H. Process for production of orthophosphates, P (8) 190*g*.
Chemische Werke Huels Akt.-Ges. Pumping and generating liquid media, P (5) 130*e*.
Chem-Met-Andersen Engineering Co. Cylinder for glass bottle making machine, P (1) 4*h*.
Chen, J. H. See Redman, M. J.
Cheney, R. F., Clare, L. P., and Cooper, D. G. Method and apparatus for infiltrating porous bodies, P (7) 157*a*.
Cheng, Hu-ming. See Li, Chia-chih.
Chenot, C. F. Phase boundaries in a portion of the system SrO-B_2O_3, (3) 87*j*.
Cherbuy, J., and Maurice, J. Electrical resistance coatings and their manufacture, P (11) 285*e*.
Cherdron, E. See Rueter, H.
Cherepanov, G. P. See Galin, L. A.
Cherneva, E. F., and Florinskaya, V. A. Infrared spectra of lithium silicate glasses and their relation to structure, B (9) 245*c*.
Chernin, M. A. Grooved reflector lamp, P (3) 68*a*.
Chernina, L. L. Composition and structure of baddeleyite-corundum refractory with the optimum glass resistance, (3) 70*j*.
Chernogorenko, V. B. See Grankovskii, I. G.
Chernow, F. See Arntz, F.; Courtens, E.
Chernow, F., Courtens, E., Douma, M., and Goodman, L. High-resistivity *p*-type cadmium sulfide, (9) 239*g*.
Chernyshev, K. S. See Erman, L. Ya.
Cheroff, G. See Berkenblit, M.
Chertkov, A. A. See Malyuchkov, O. T.
Cherubin, P. Vaporizing burners for liquid fuels, P (1) 15*a*.
Cheseldine, D. M. Anodic oxidation of titanium in formic acid electrolytes, (3) 83*h*.
Chesney, J. See Heilmann, P. E.
Chevron Research Co. Flange forming fixture and method, P (3) 67*d*. High sensitivity differential thermal analysis apparatus and method, P (11) 289*i*. Method of depositing metals on siliceous supports, P (9) 235*j*.
Chiang, Y. See Smothers, W. J.
Chicago Aerial Industries, Inc. Process for manufacturing fiber optic devices [shape transducers], P (2) 40*b*.
Chicago Boiler Co. Sealing means for rotary agitator of a grinding and dispersing mill, P (9) 236*g*.
Chikanov, N. D., Palkin, A. P., and Bizyaeva, M. K. Thermal investigation of the system Na, K ‖ $AlCl_4$,Ta(Nb)Cl_4, (2) 58*j*.
Chikhachev, Y. N. See Kotelnikov, G. R.
Chikova, N. N. See Belyaev, I. N.
Child, M. S. Model for adiabatic reactive molecular collisions, (1) 23*i*.
Chin, G. Y. Slip-induced directional order theory for B2-type superlattices, (11) 301*a*.
Chin, Hsue-wen. See Shiau, Y. C.
Chin, J. See Bokros, J. C.; Goeddel, W. V.
Chiola, V., and Vanderpool, C. D. Preparation and luminescence of molybdenyl phosphate, (11) 299*e*.
Chiotti, P. See Robinson, W. C.
Chiotti, P., Robinson, W. C., and Kanno, M. Thermodynamic properties of uranium oxycarbides, (11) 302*a*.
Chisholm, R. S., Sleighter, G. E., and Ernsberger, F. M. Method of strengthening glass by ion exchange and articles therefrom, P (2) 39*d*.
Chistoserdov, V. G. See Borgman, V. A.
Chistoserdov, V. G., and Kozlova, M. A. Peculiarities of glass crystallization at temperatures near t_g, B (9) 246*b*.
Chiyoda Kako Kensetsu Kabushiki Kaisha and Kureha Kagaku Kogyo Kabushiki Kaisha. Flameless radiant burner, P (10) 268*g*.
Choffat, H. See Cornaz, P.
Choi, D. M., and Palmour, H., III. Fractographic evidence of multiple slip in deformed hot-pressed spinel, B (2) 61*k*.
Chomat, L. Improvements in rolling hearths, P (11) 290*d*. Supplying secondary air to furnace burners, P (11) 290*h*.
Chour, Z. See Potuzak, V.
Chow, J. T. See Biedermann, G.
Chrdileli, O. G. See Kutateladze, K. S.
Christensen, A. N. Crystal structures of HoOOH, ErOOH, and YbOOH, (8) 194*c*. Hydrothermal preparation of some rare earth trihydroxides and rare earth oxide hydroxides, (11) 297*e*. Reinvestigation of the crystal structure of YOOH, (8) 206*c*. Single crystal X-ray diffraction study of $Mn(OH)_2$, (8) 207*b*.
Christensen, A. N., Rasmussen, S. E., Nevald, R., and Frank, V. Structure of InOOH, (10)2 72*f*.
Christensen, F. L., and Mabey, D. H. Diamond milling cutters, P (5) 115*h*.
Christensen, K. E. H. See Sagen, G.
Christensen Diamond Products Co. Diamond milling cutters, P (5) 115*h*.
Christian, G. D. See Feldman, F. J.

Christian, R. G., and Leck, J. H. Viscosity gage for pressure measurement in the range 10^{-4} to 10^{-4} torr, (2) 51*g*.
Christian, W. E. Coated abrasives, P (11) 273*g*.
Christova, R., and Kruschevska, A. Chromatographic separation of metals by elution with ammonium sulfate—determination of magnesium, calcium, and strontium in waters, (4) 104*c*.
Christy, C. M. Refractory shape and process of making same, P (7) 154*b*.
Christy Firebrick Co. Refractory shape and process of making same, P (7) 154*b*.
Chromalloy Corp. Method for bonding a sintered refractory carbide body to a metalliferous surface, P (1) 7*i*.
Chrysler Corp. Process for preparing sheet metal surfaces with dry lubricant coatings, P (4) 92*e*.
Chrystall, R. S. B. Thermal expansion of iron pyrites, (7) 169*b*.
Chu, Chih-wei, and Shiau, Y. G. Investigations of the dual function of electron-acidic catalyst (III) reactivity and poisoning of nickel sulfide on silica alumina, (1) 15*f*.
Chu, G. P. K., and Davis, H. M. Improvement of vitreous coatings through the understanding of the behavior of hydrogen in the ceramic-metal system, (4) 91*j*.
Chu, J. C. Nuclear reactor with improved moderator material, P (11) 282*b*.
Chu, T. L., and Campbell, R. B. Chemical etching of silicon carbide with hydrogen, (11) 284*g*.
Chu, T. L., and Gavaler, J. Silica films, P (2) 49*g*.
Chu, T. L., Gavaler, J. R., Gruber, G. A., and Kao, Y. C. Novel technique for the deposition of silica films, (4) 100*i*.
Chu, T. L., and Gruber, G. A. Doped silica films, (8) 195*c*.
Chu, T. L., and Tallman, R. L. Water vapor as an etchant for silicon, (4) 100*e*.
Chubb, P. A. Treatment of sand and other industrial minerals, P (4) 107*d*.
Chubb, W., Getz, R. W., and Townley, C. W. Diffusion in uranium monocarbide, (8) 194*j*.
Chubkina, N. I. See Brekhovskikh, S. M.
Chufarov, G. I. See Brainina, D. Z.; Shabalina, O. K.
Chukhlantsev, V. G., and Galkin, Yu. M. Study of the BaO-ZrO_2-SiO_2 system at subsolidus temperatures, (5) 138*c*.
Chukreeva, E. I. See Ignatova, T. S.
Chvala, M. A. See Gromakov, S. D.
Chvatal, T. Binding agent for refractories and its manufacture, P (10) 259*d*.
Chwalek, E. J. See Upton, L. O.
Chzhan, Sii-Tsuy. See Duderov, G. N.
Chzhan, Tszu-lyan. See Fedorov, P. I.
Ciapetta, F. G. See Magee, J. S., Jr.
Ciba, Ltd. Atmosphere-resisting electrical insulators, P (10) 261*h*. Filter presses, P (3) 80*c*. Finely dispersed carbides and process for their production, P (11) 281*c*.
Cicchelli, C. D. Method for making abrasive segments for saws, P (4) 89*h*.
Cierva Viudes, P. de la. Refractory clays, B (2) 62*d*.
Cihelka, J. See Husa, V.
Cincinnati Shaper Co. Compacting press with selective ejection, P (11) 288*h*.
Cintride, Ltd. Abrasive elements, P (7) 145*h*.
Ciotti, J. A. See Schwabe, W. E.
Cisney, E. See Aronson, S.
Claassen, G. R. Method and apparatus for press bending glass sheets, P (8) 177*f*.
Clancy, J. V., and McLaughlin, W. T. Centrifugal spraying equipment, P (1) 12*d*.
Claps, W. A. See Coulter, W. H.
Clare, C. P., & Co. Method of and apparatus for making sealed switches, P (2) 39*e*, P (9) 220*h*.
Clare, L. P. See Cheney, R. F.
Clare, T. E. Gaseous flow through sintered beryllia, (4) 96*j*.
Claridge, M. A., Jones, P. M., and Wigginton, R. J. Process of particulate matter separation, P (11) 291*f*.
Clark, C. B. Petrology of the reactions of fused cast alumina refractories with metals and slags, (2) 42*c*.
Clark, G. W. See Finch, C. B.
Clark, H. E., and Moore, D. G. Rotating cylinder method for measuring normal spectral emittance of ceramic oxide specimens from 1200° to 1600°K, (2) 51*d*.
Clark, J. A. Light deflector, P (1) 5*h*.
Clark, J. E., and Ross, I. M. Encapsulations and methods and apparatus for making encapsulations, P (11) 285*h*.
Clark, W. P. Controllable ferrite phase shifter having means to cool the ferrite, P (11) 285*b*.
Clarke, A. R., and Cable, M. Gas chromatograph for analyzing single bubbles in glass, (11) 276*j*.
Clarke, B. L. See Harper, F. C.
Clarke, F. K. Method of making a miniature lens, P (2) 39*h*.
Class, W., Iannucci, A., and Nesor, H. Some innovations and observations on high pressure diffractometry, (5) 131*f*.
Claudet, A. Research on the methods of detecting heterogeneity in earthenware bodies after firing, (5) 131*d*.
Clawson, A. R. See Wieder, H. H.
Clawson, A. R., and Wieder, H. H. Fabrication of magnetoresistive semiconductor film devices, P (11) 285*a*.
Claxton, K. T., and Strickland-Constable, R. F. Reactions of carbon with carbon dioxide activated by low voltage electrons, (2) 55*i*.
Clay, D. B., and Jamieson, R. M. Porcelain enamel adherence to low-carbon steel (I), (10) 250*a*.
Clayton, R. N. See Northrop, D. A.
Clearfield, A. Process for the production of cubic crystalline zirconia, P (10) 270*a*.
Cleek, G. W. Glass research at the National Bureau of Standards, (8) 175*d*.
Cleland, R. L. Adsorption from nonelectrolyte solutions on porous 96% silica (Vycor) glass, (8) 175*b*.
Cleland, R. L., Brinck, J. K., and Shaw, R. K. Effects of adsorption on diffusion in porous (Vycor) glass, (8) 175*j*.
Clements, J. F. Characteristics of refractory insulating materials, (2) 41*e*.
Clendinning, W. R. Process for applying a protective coat of silicon carbide to refractory metals, P (8) 174*j*.
Clendinning, W. R., and Gray, F. L. Thermionic energy converter [SiC-C], P (9) 232*f*.
Cleverly, R. B. Machine and method for automatically fabricating multiple unit assemblies of individual pieces, P (9) 228*g*.
Clevite Corp. Electroless plating of gold, P (5) 127*j*.
Clews, F. H. See Owen, V. J.
Clifford, A. F., and Jaffe, J. Alumina supported copper oxide-rare earth oxide catalyst compositions, P (2) 43*c*.
Cline, C. F., Carlberg, J., and Newkirk, H. W. Ionic conductivity in BeO, (2) 55*c*.
Cline, C. F., Newkirk, H. W., Barmore, W. L., and Vandervoort, R. R. Creep-electrical conductivity correlations in polycrystalline beryllium oxide, (5) 134*h*.
Clinton, S. D. See Haas, P. A.
Clinton, S. D., Haas, P. A., Hirth, L. J., and Kleinsteuber, A. T. Process for preparing oxide gel microspheres from sols, P (3) 83*a*.
Clock, G. E., Rieke, J. K., and Stroiwas, E. Electroluminescent structure with improved [organic] protective transparent film, P (5) 127*j*.
Cloppet, R. Process for the production of molybdenum dioxide, P (11) 292*a*.
Cloud, P. E., Jr. Bauxite deposits of the Anniston, Fort Payne, and Ashville areas, northeast Alabama, (8) 189*e*.
Clougherty, E. V. See Kaufman, L.
Clyne, M. A. A., McKenney, D. J., and Thrush, B. A. Rate of combination of oxygen atoms with oxygen molecules, (7) 167*d*.
Coates Brothers & Co., Ltd. Improvements to furnaces, P (11) 290*d*.
Coaton, J. R. See Wright, J. W. T.
Coats, A. W., and Bright, N. F. H. Kinetics of the thermal decomposition of pyrite, (3) 86*a*.
Coats & Clark, Inc. Traveler having a wear resistant element, P (3) 75*b*.
Coble, R. L. See Roy, S. K.
Coburn, O. W., Suddarth, J. M., and Ganther, F. E. Automatic lens grinding machine, P (3) 67*i*.
Coburn Mfg. Co., Inc. Automatic lens grinding machine, P (3) 67*i*.
Cochardt, A. W. Ferrite magnets, P (4) 101*f*. Methods of making ferrite magnets, P (8) 185*c*. Permanent magnet materials having a strontium ferrite base and processes for their preparation, P (8) 185*g*. Two-phase ferrite magnet composition and method for preparing same, P (11) 288*d*.
Cochrane, H., and Rudham, R. Heats of immersion of alpha and gamma alumina, (7) 164*a*.
Cochrane, R. C. Measures for Progress—A History of the National Bureau of Standards, B (8) 212*d*.
Cockayne, B., and Gasson, D. B. Yttrium aluminum garnet single crystals—polishing, etching, and dislocation distribution, (10) 272*i*.
Cody, G. D., and Abeles, B. Thermoelectric device having silicon-germanium alloy thermoelement, P (1) 12*a*.
Coenen, M. Density of cord glasses at high temperatures, (10) 251*f*. Effect of anisotropy on the relaxation of silicate glasses, B (2) 61*j*.
COFELEC. See Compagnie des Ferrites Electroniques.
Coffin, L. B. Ceramic composition, P (5) 122*b*. Permeable ceramic mold material, (1) 9*a*.
Cofran, L. L. Resin bonded abrasive articles containing olivine [as pore-forming material], P (10) 247*h*.
Coghill, H. D. See Halsted, R. E.
Cohen, A. J. Method of making clay aggregate from raw clay, P (8) 179*g*. Phototropic glass and method, P (1) 6*b*.
Cohen, B. G., and Logan, R. A. Semiconductor device and method of making, P (1) 11*f*.
Cohen, D., and Walter, A. J. Neptunium pentoxide, (8) 203*e*.
Cohen, H. M. Process for manufacture of coated superconductive ribbons, P (9) 232*a*.
Cohen, J. Bonding process, P (4) 100*g*. Detector properties of photon-modulated tunneling, (10) 262*c*. Photo-modulated tunneling, (10) 271*c*.
Cohen, J. B., and Hilliard, J. E. (editors). Local Atomic Arrangements Studied by X-ray Diffraction—Proceedings of a Symposium Sponsored by the Physics and Chemistry of Metals Committee of the Institute of Metals Division, the Metallurgical Society, American Institute of Mining, Metallurgical, and Petroleum Engineers, Chicago, February 1965, B (9) 245*g*.
Cohen, M. See Caplan, D.
Cohen, M. G. See Dixon, R. W.
Cohn, M. I., and Perdue, R. D. Flotation method and apparatus, P (5) 133*i*.
Coke, H. W. Method of treating quartz sands, P (2) 54*d*.
Colby, L. J., Jr. Kinetics of reaction of uranium monocarbide with water, (11) 297*f*.
Colchagoff, R. D. Neck mold and plunger unit for glass forming apparatus, P (5) 121*c*.
Colchagoff, R. D., and Mumford, E. H. Glass forming apparatus, P (11) 278*a*.
Cole, F., Modreski, E. L., and Van Tilburg, R. W. Method and apparatus for making ceramic or vitreous articles, P (8) 177*c*.
Cole, H. See Procter, J. P.
Cole, H. G. Method of making multichanneled electron multiplier component, P (10) 264*b*.
Cole, T. See Lambe, J.
Coleman, E. H., and Elkins, G. H. J. Method and apparatus for gas analysis, P (2) 52*a*.
Coless, T. L. Submerged arc flux composition and method of making the same, P (8) 174*j*. Submerged-arc welding composition, P (9) 217*e*.
Colin, R. See Drowart, J.; Verhaegen, G.
Colin, R., Drowart, J., and Verhaegen, G. Mass-spectrometric study of the vaporization of tin oxides, (1) 22*h*.
Colley, B. E. See Balmer, G. G.
Collier, T. J. Treated glass fibers and methods for treating glass fibers to improve the bonding relation with epoxy resins, P (11) 279*g*.
Collins, C. C., and Gill, W., Jr. 27 different jobs by barrel finishing (I), (7) 145*f*; (II), (8) 186*i*.
Collins, C. V. See Ostertag, W.
Collins, C. V., and Ostertag, W. Single-crystal preparation of cubic rare earth tungsten bronzes, (1) 28*c*.
Collins, D. A. Preparation of thin film indium antimonide from bulk indium antimonide, P (11) 287*d*.
Collins, D. R., and Sah, C. T. Effects of X-ray irradiation on the characteristics of metal-oxide-silicon structures, (9) 238*j*.
Collins, D. R., Schroder, D. K., and Sah, C. T. Gold diffusivities in SiO_2 and Si using the MOS structure, (8) 198*i*.
Collins, G. A., Jr. Composite metal-ceramic article and method for making same, P (4) 92*g*.
Colombo, R. L. See Amato, I.
Colombo, U. P. Process for recovering iron, titanium, and aluminum from the red slurries obtained in processing bauxite by the Bayer process, P (4) 107*a*.
Colombo, U. P., and Sironi, G. Process for the production of iron sponge and the recovery of titanium and aluminum from red slurries of bauxite, P (4) 107*d*.
Colovos, G. See Vassiliadis, C.
Colson, H. D. See Rapp, R. A.
Colton, E. Method of flame spraying graphite to produce a low friction surface, P (2) 35*e*.
Columbia Broadcasting System, Inc. Method of cataphoretic deposition of luminescent materials, P (8) 185*b*.
Columbian Carbon Co. Process for forming aggregates of powdered materials, P (5) 130*d*.
Comado, S. J., Sparrow, L. R., and Braiman, J. Plated packaging for electronic components, P (8) 185*h*.
Comer, J. J., Croft, W. J., Kestigian, M., and Carter, J. R. X-ray and electron microscope study of the compound $PbAl_{12}O_{19}$, (9) 243*i*.
Commissariat a l'Energie Atomique. Dosimetric glasses, P (3) 67*b*. Fabrication of sintered compounds based on uranium and plutonium, P (2) 43*j*. Improvements in processes for radioactive labeling, P (2) 44*h*. Method of making bars of a uranium compound and in particular uranium carbide [by continuous casting], P (11) 282*c*. Methods and devices for determining the mean radius of pores in microporous barriers, P (2) 52*a*. Nuclear fuel material of $U_3C_2Si_2$ and method of preparation, P (11) 282*a*. Phosphate glass for the dosimetry of X and gamma rays, P (3) 69*i*. Process for the densification of carbonaceous bodies, P (9) 226*g*. Process for the fabrication of bodies formed by dispersion of refractory material within a pyrocarbon matrix which is impervious to gases, P (7) 153*g*. Process for the fabrication of fuel elements designed for high-temperature operation, P (10) 260*f*. Process for the preparation of metallic nitrides, P (9) 226*j*. Radioactive ceramic source of stontium fluorapatite and method of manufacture, P (10) 270*b*. Refractory products, P (3) 73*b*. Refractory products, especially for nuclear fuels, and their method of manufacture, P (2) 45*g*. Sintered pollucite radioactive source and method of production, P (11) 292*a*. Uranium monocarbide-plutonium mononitride nuclear fuel, P (7) 154*f*.
Commonwealth Scientific & Industrial Research Organization. High intensity atomic spectral lamps, P (5) 127*g*. Suspensions of silicate layer minerals and products made therefrom, P (9) 236*h*.
Communaute Europeenne de l'Energie Atomique. High temperature furnace, P (2) 52*i*.
Compagnie des Ateliers et Forges de la Loire. Method of making porous refractory products, P (9) 226*f*.
Compagnie des Ferrites Electroniques. Nickel and nickel-zinc ferrites and their fabrication, P (2) 48*f*.
Compagnie du Filage des Metaux et des Joints Curty. Hot working of materials, P (11) 281*g*.
Compagnie Francaise des Matieres Colorantes. Bright pigments, P (4) 99*j*.
Compagnie Francaise du Methane. Drying clay products and apparatus therefor, P (11) 290*b*.

Compagnie Francaise Thomson-Houston. Equipment and process for depositing a layer of carbon, P (5) 124*f*. Metallization of ceramics and ceramic assembly fabricated by this process, P (2) 48*c*. Metallizing coating for ceramics consisting of very pure oxides, P (7) 156*i*.

Compagnie Generale d'Electricite. Helical-walled waveguides, P (2) 47*h*.

Compagnie Generale de Telegraphie Sans Fil. Electron discharge device with external mode suppression means which separate wanted from unwanted modes and allow for dissipation of unwanted modes, P (3) 78*f*. Ferrite composition based on lithium ferroaluminate, P (10) 263*i*. High resistivity [Li-Mn] ferrite composition, P (7) 156*g*.

Compagnie de Saint-Gobain. Apparatus for producing fibers from thermoplastic material, P (2) 38*k*. Apparatus for producing fine glass fibers, P (5) 119*j*. Apparatus for the production of fibers from organic or inorganic thermoplastic materials, P (2) 38*j*. Electrically resistant glass compositions, P (3) 67*b*. Fiber glass [sheet] product and method of making it, P (9) 219*i*. Formation of glass mats, P (9) 220*a*. Glass compositions, P (5) 120*j*. Machine for severing glass, P (4) 94*c*. Manufacture of complex-aluminous metal-glass products of high strength, P (4) 94*b*. Manufacture of glass fibers, P (8) 177*j*. Manufacture of glass sheet, P (1) 5*j*. Manufacture of silica glass, P (10) 255*h*. Metal pieces as parts for contact with molten glass, P (1) 5*b*. Metallic elements adapted to come in contact with melted glass, P (8) 177*a*. Method and apparatus for conveying a glass sheet on a molten metal bath, P (9) 220*f*. Method of and apparatus for cutting lengths of glass from a ribbon of glass, P (7) 149*h*. Method and apparatus for determining surface birefringence in a transparent material employing a prism place adjacent to the surface, P (2) 39*c*. Method of and apparatus for forming flat glass on a liquid bath, P (9) 220*h*. Method and apparatus for severing glass panels, P (5) 121*b*. Method of changing the equilibrium thickness of a glass sheet being formed on a molten metal bath, P (8) 177*h*. Method of producing a glass object having a system of stresses therein, P (3) 69*a*. Process and apparatus for drawing a glass sheet, P (2) 39*f*. Process and apparatus for the manufacture of fiber mats, P (4) 95*c*. Rotatable current baffle in glass flow furnace, P (9) 222*c*. Vitreous materials containing mica, P (8) 179*b*.

Comptoir Lyon-Alemand Louyot & Cie. Fusion processes for the manufacture of metals and alloys employed in contact with molten materials, P (10) 255*c*.

Compton, D. M. J., Lyons, V. J., and McDade, P. J. Semiconductor compound crystals, P (5) 129*a*.

Comstock, R. L., Raymond, J. J., Nilsen, W. G., and Remeika, J. P. Spin-wave spectrum of gadolinium iron garnet, (9) 242*j*.

Comte, G. Helical-walled waveguides, P (2) 47*h*.

Conair, Inc. Method of transporting material and device therefor, P (7) 158*g*.

Condas, G. A., and Yee, J. H. Evidence of distant-pair recombination process in the green-edge emission of CdS at 4.2° and 77°K, (9) 239*c*.

Conde, C. S. See Sanchez Conde, C.

Condit, R. H. See Holt, J. B.

Condit, R. H., and Hashimoto, Y. Self-diffusion of beryllium in polycrystalline beryllium oxide, (9) 242*e*.

Condit, R. H., and Holt, J. B. Technique for studying oxygen diffusion and locating oxide inclusions in metals by using the proton radioactivation of oxygen-18, (4) 104*e*.

Condolios, E. Process and apparatus for the sorting of two or more materials, P (4) 103*i*.

Condon, H. F. Pipe coupling for joining pipe sections of varying size, P (4) 95*b*.

Conklin, T. H. See Theodorou, D. G.

Conley, R. F. Structural and chemical alterations of delta Fe_2O_3 and their effect on magnetic properties, (4) 100*d*.

Conner, J. R., Jr. See Ames, S. L.

Connolly, J. D. See Crow, R. F.

Connolly, T. M., and Graham, N. C. Jaw crusher, P (9) 235*i*.

Conrad, F., and D'Aprix, R. Glassblowing and R&D, (1) 3*i*.

Conrad, H., and Frederick, S. Effect of dislocation density on low-frequency noise in germanium, (10) 262*f*.

Conrad, K. Inspecting glass containers with lasers, P (5) 120*e*.

Conradty, C. Method of screw connecting carbon or graphite electrodes, P (9) 226*a*.

Conroy, J. E., Jr. Continuous calcination of gypsum, P (5) 116*e*.

Conroy, J. E., Jr., and Jorgensen, J. S. Apparatus for continuous calcination of gypsum, P (5) 116*b*.

Consolidated Controls Corp. Resistance thermometer system, P (4) 105*a*.

Consolidated Electronics Industries Corp. Method of making glass capsules for electrical components, P (1) 6*c*.

Consortium fuer Elektrochemische Industrie G.m.b.H. Producing and regulating translatory movement in the manufacture of semiconductor bodies, P (11) 287*i*.

Constabaris, G. See Kuendig, W.

Constabel, H. G. See Baier, E.

Contemporary Research, Inc. Production of dispersion hardened materials, P (2) 45*b*.

Conti, R., Toussaint, C. J., and Vos, G. Application of X-ray diffraction analysis to uranium ceramics (I) quantitative analysis of the binary mixture UO_2-U_3O_8, (8) 179*i*.

Continental Can Co., Inc. Photoelectric glassware inspecting device, P (2) 39*i*.

Continental Carbon Co. Method and apparatus for calcining inorganic hydrates, P (10) 268*g*.

Continentale Erz-Ges. m.b.H. Process for making refractories for industrial furnaces, P (2) 45*c*.

Conway, K. C. See Adami, L. H.

Conwell, E. M., and Vassell, M. O. Variation of drift velocity with field in GaAs, (11) 303*c*.

Cook, A. M. Firing of grinding wheels and the like in a tunnel furnace, P (9) 213*f*. Pulpstones and method of making, P (1) 1*f*.

Cook, A. M., and Blackmar, R. J. Vertical kiln for continuous grain calcination, P (1) 15*a*.

Cook, C. F., Jr. See Kohn, J. A.

Cook, C. F., Jr., and Nye, W. F. Morphological features of hexagonal ferrites, (9) 241*b*.

Cook, C. G. Metal vapor lamp having a heat reflecting coating of calcium pyrophosphate, P (9) 220*e*.

Cook, C. W. See Doud, W. O.

Cook, D. F., and Cosper, D. F. Method of making symmetrical switching diode, P (4) 102*a*.

Cook, E. J. Gaseous microwave switching tube apparatus, said tube including closely packed solid ceramic alumina spheres, P (10) 264*a*.

Cook, I. D. Cone-type crushers with shock pad between frame and adjustment ring, P (11) 291*d*.

Cook, M. D. See Smoot, T. W.

Cook, R. J., and Whiffen, D. H. Electron nuclear double resonance study of a nitrogen center in diamond, (11) 295*b*.

Cook, R. L. See Greenberg, C. B.

Cook Electric Co. High temperature measuring devices, P (7) 159*g*.

Cooke, F. W., Bradt, R. C., DeVries, R. C., and Ansell, G. S. Dielectric aging and microstructure in the system $BaTiO_3$-$CaTiO_3$, (1) 9*g*.

Cooke's (Finsbury), Ltd. Fiber glass laminates, P (9) 219*i*.

Cookfair, A. S. Patents as a source of information for the glass industry (I, II), (3) 66*d*.

Cooper, A. R. See Gosselin, J. P.; Haggerty, J. S.; Kreider, K. G.

Cooper, A. R., Cable M., and Bradford, I. T. Model study of the mixing of viscous liquids in a crucible, (10) 252*g*.

Cooper, C. F. Pores and thermal conductivity, (11) 299*j*.

Cooper, C. F., and Miskin, S. F. A. Slip-casting kinetics of alumina by gamma-ray absorption, B (7) 170*c*.

Cooper, D. G. See Cheney, R. F.

Cooper, D. P., Jr. Incandescent lamp with TaC filament and cyanide-radical producing and halogen atmosphere, P (1) 11*a*.

Cooper, H. W. See Evitts, H. C.

Cooper, J. E. See Duncan, J. E.

Cooper, J. R. See Parodi, J. A.

Cooper, R. C. See Donnelly, J. F.

Cooper, R. H. Clay structures, P (5) 133*h*.

Coors Porcelain Co. Method for manufacturing ceramic substrates for electrical circuits, P (9) 231*f*.

Cope, G. R., Hauth, C. R., and Hyde, J. Tundish ladles, P (10) 261*a*.

Cope, L. H., and Warmer, R. J. Manufacture of cermet bodies, P (11) 281*i*.

Copeland, J. A. Switching and low-field breakdown in *n*-GaAs bulk diodes, (9) 230*c*.

Copeland, L. E. See Mikhail, R. Sh.

Copeland, R. P. Open hearth furnace roof, P (9) 235*a*.

Copenhefer, J. E. Method and apparatus for making filamentous mats, P (5) 121*b*.

Coper, K. Method of making glass capsules for electrical components, P (1) 6*c*.

Copley, G. J. Internal friction studies of the dehydration of sheet glass, (9) 218*e*.

Copley, S. M., and Pask, J. A. Deformation of polycrystalline ceramics, B (2) 61*e*.

Coppersmith, F. M. See Vahrenkamp, G. J.

Copson, R. L. See Lauder, W. B.

Copson, R. L., Howard, C. J., and Hecklinger, C. F. Conversion of caustic soda to soda ash, P (9) 235*f*.

Corbett, R. B. Sintered carbides, P (9) 227*f*.

Cordfunke, E. H. P., and Debets, P. C. Preparation and properties of a new monohydrate of uranium trioxide, α-$UO_3 \cdot H_2O$, (8) 205*i*.

Corhart Refractories Co. Basic refractory, P (7) 152*j*. Ceramic refractory, P (2) 43*g*. Ceramic refractory bodies, P (2) 43*h*. Magnesium oxide casting, P (10) 259*b*. MgO-B_2O_3 fused cast refractory, P (11) 282*i*. Refractory casting, P (11) 283*b*. Refractory and furnace lining, P (1) 8*f*, P (3) 73*e*.

Cornaz, P., Choffat, H., Parot, M., and Borel, J. P. Electronic resonance study of a paramagnetic center in amorphous silicon monoxide, B (2) 61*k*.

Cornelissen, J. Glass strength and surface treatment, (5) 119*b*. Method of manufacturing glass articles having a high mechanical strength, P (3) 68*h*.

Cornell, R. M. See Williamson, G. K.

Cornell Aeronautical Laboratory, Inc. Composition of matter containing plutonium dioxide and plutonium phosphate, P (11) 281*b*. Surface temperature measuring device, P (9) 234*f*.

Cornely, K. W. Cement composition, P (2) 34*i*.

Corning Glass Works. Aluminosilicate glass, P (7) 149*e*. Apparatus for aligning hollow articles, P (1) 4*b*. Barium titanate materials, P (11) 284*i*. Coating perforate articles, P (2) 38*a*. Cooking apparatus with cooking vessel centering and holding means, P (8) 176*j*. Cutting tool, P (10) 254*j*. Diffusing lens for spotlights with axially oriented filaments, P (10) 255*a*. Digital ultrasonic delay line, P (4) 101*a*. Display device [phototropic glass], P (9) 219*f*. Drawing sheet glass, P (9) 219*f*. Edge form grinding, P (8) 177*c*. Electrical capacitor manufacture, P (7) 149*b*. Electrically conductive abrasive bodies, P (7) 145*g*. Electroless copper plating on ceramic material, P (4) 101*d*. Encapsulated impedance element, P (5) 127*j*. Enclosed electronic device, P (11) 285*i*. Fluid impinging glass forming apparatus, P (7) 149*c*. Fluorescent glass and method of making it, P (9) 219*j*. Fused refractory castings, P (11) 281*f*. Gas-fired [regenerative] radiant burner, P (4) 105*e*. Glass article and method of making it, P (3) 67*f*. Glass-ceramic body and method of making it, P (1) 5*b*. Glass electrode apparatus and process for making same, P (5) 120*a*. Glass electrode and method of making the same, P (2) 38*g*. Glass forming method, P (9) 220*d*. Glass melting furnace with bubblers, P (10) 255*f*. Glass press mold sensing and indicating means, P (3) 67*i*. Glass-sealed electrical resistor, P (5) 127*e*. Grinding and polishing method and apparatus, P (3) 68*a*. Heat-absorbing glass, P (9) 220*j*. Humidity sensing element, P (5) 120*d*. Iridizing method, P (10) 255*k*. Manufacture of cathode ray tubes for color television, P (8) 177*i*. Manufacture of silica-sheathed silicon carbide fibers and the product thereof, P (10) 259*d*. Means for measuring the electrical resistance of molten glass in a tank, P (1) 5*j*. Means for supporting glass tubing during drawing, P (1) 5*a*. Method and apparatus for coating electrical components, P (7) 156*j*. Method and apparatus for making ceramic or vitreous articles, P (8) 177*c*. Method and apparatus for manufacturing glass beads, P (3) 68*g*, P (8) 177*d*. Method for applying electrical conductors on a smooth vitreous surface and article, P (7) 157*c*. Method of attaching leads to thin films, P (2) 48*e*. Method of decorating semicrystalline bodies, P (8) 177*j*. Method for electrophoretic separation of materials in a localized area, P (11) 288*j*. Method for etching glass, P (1) 5*i*. Method for forming glass wafers, P (3) 68*d*. Method of forming a moisture-collecting coating of porous glass, P (1) 5*j*. Method of forming thin film resistors, P (2) 48*h*. Method of making electrical capacitors, P (4) 101*i*. Method of making an electrically heated immersible [ceramic] warming unit, P (10) 264*j*. Method of making high strength glass articles, P (4) 95*b*. Method of making high strength nepheline crystalline glass, P (8) 178*b*. Method of making a phototropic glass article, P (5) 121*d*. Method of making synthetic mica bodies, P (9) 221*a*. Method of and mold for forming hollow articles, P (11) 279*e*. Method of producing composite semicrystalline articles, P (9) 221*d*. Method of producing an electrical capacitor, P (3) 79*d*. Method of producing thin flakes of metal oxide, P (11) 291*j*. Method for reshaping glass articles, P (3) 69*b*. Method of shaping a continuous glass tube, P (11) 279*f*. Methods for forming materials of high purity by fusion, P (5) 128*a*. Modified Zn_2SiO_4 compositions, P (10) 265*b*. Molding comminuted nonplastic inorganic material, P (10) 266*c*. Molten glass dispensing plunger needle, P (10) 255*j*. Packaged electronic device, P (8) 185*c*. Phosphorescent opal glasses, P (4) 95*a*. Phototropic glass article and method of making it, P (9) 222*a*. Semiconductor terminals and method, P (10) 265*c*. Sheet forming apparatus, P (11) 279*e*. Short-duration light source comprising an electron irradiated transparent insulating body, P (2) 40*c*. Split mold operating mechanism, P (9) 222*e*. Street light refractor, P (8) 179*b*. Tan ophthalmic glass, P (3) 69*g*. Thermal printing wafer and method for making the same, P (11) 288*a*. Transparent devitrified strengthened glass article and method of making it, P (2) 40*b*. Workpiece handling apparatus, P (11) 279*k*.

Cornuault, P. See Bentolila, J.

Corson, B. L. Moving pallet sintering apparatus and method, P (10) 268*h*.

Corson, B. L., and Pfau, J. H. Lightweight aggregate, P (11) 280*a*.

Corson, G. & W. H., Inc. Lightweight aggregate, P (11) 280*a*. Moving pallet sintering apparatus and method, P (10) 268*h*.

Corwin, R. E., and Pence, E. A. Prestressed spherical electroacoustic transducer, P (8) 185*j*.

Cosgrove, L. A. Method for preparing alumina particles, P (8) 181*d*.

Coslett, V. E. High voltage electron microscopy, (7) 159*g*.

Cosper, D. F. See Cook, D. F.

Coss, P. Microscopic examination of fused cast alumina refractories, (4) 97*k*.

Costill, H. J. See Bauman, F. E.

Cotton, F. A. See Bills, J. L.

Coufova, P. See Arend, H.

Coulson, J. A. See Arthur, G.

Coulter, J. R., Jr. Flow-through sample apparatus for use with electrical particle study device, P (11) 289*h*.

Coulter, W. H., Hogg, W. R., Moran, J. P., and Claps, W. A. Particle studying device pulse analyzer, P (3) 81*k*.
Coulter, W. H., and Siegelman, A. Particle distribution plotting apparatus, P (10) 268*a*.
Coulter Electronics, Inc. Aperture tube structure for particle study apparatus, P (4) 104*h*. Flow-through sample apparatus for use with electrical particle study device, P (11) 289*h*. Particle distribution plotting apparatus, P (10) 268*a*. Particle studying device pulse analyzer, P (3) 81*k*.
Coumans-Schepers, N. V. Processes for firing molded objects in continuously operating furnaces, P (4) 105*h*.
Counts, C., and Counts, R. Potter's journey through the southern highlands, (4) 90*b*.
Counts, R. See Counts, C.
Counts, W. E. See Bruhl, D. A., Jr.
Counts, W. E., and Kelly, W. T. Cermet resistance element and material, P (9) 230*h*.
Courtens, E. See Chernow, F.
Courtens, E., and Chernow, F. Contact barriers on insulating CdS, (1) 9*h*.
Courtney-Pratt, J. S. Cathode ray tube with composite multiple glass fiber face, P (9) 219*a*.
Covington, A. K., and Lilley, T. H. Silver ion response of some sodium-aluminum-silicate glass electrodes, (11) 277*b*.
Cowles, R. J. See Smith, L. W.
Cowles Chemical Co. Alkali metal silicates and method for producing the same, P (2) 46*a*.
Cowley, E. R., and Cowley, R. A. Anharmonic interactions in alkali halides (II), (1) 16*f*.
Cowley, R. A. See Cowley, E. R.
Cox, B., and Roy, C. Transport of oxygen in oxide films on zirconium determined by the nuclear reaction ^{17}O ($^{3}He,\alpha$)^{16}O, (5) 139*a*.
Cox, D. See Duggin, M. J.
Cox, D. E. See Shirane, G.
Cox, J. D., and Harrop, D. Thermodynamic properties of fluorine compounds (III) enthalpies of formation of hydrofluoric acid solutions, (2) 58*d*.
Cox, J. T., and Hass, G. Antireflection coatings for optical and infrared optical materials, B (11) 305*j*.
Cox, K. E. See Long, R. S.
Cox, N. L. Ferromagnetic chromium dioxide and preparation thereof, P (1) 15*f*.
Cox, R. H. See Williams, E. W.
Cramer, H. A. See Johnston, W. R.
Cranch, G. E., and Shinko, J. S. Method for continuous graphitization of carbonaceous thread, P (8) 190*h*.
Cranco Engineering, Ltd. Tensioning of sieves, screens, and the like, P (11) 289*b*.
Crandon, H. D. See Granitsas, G. A.
Cratchley, D. See Baker, A. A.
Cratchley, D., and Baker, A. A. Silica fiber reinforced aluminum, (3) 65*f*.
Craumer, H. S. Glass devices for volatile memories, (1) 3*j*.
Crawford, J. H., Jr. Radiation stability of nonmetallic structures, (3) 87*i*.
Crawley, W. P. Process of fireproofing a blend of ceramic fibers and acrylic resin fibers by heating in an oxidizing atmosphere, P (3) 72*g*.
Cremer, G. Design characteristics of a new tunnel kiln with an internal width of 6 meters, (2) 52*e*.
Crespi, G. Refractory metallurgic composition and products, and method of obtaining same, P (2) 45*d*.
Criscione, J. M., and Litz, L. M. Method of purifying titanium diboride, P (8) 181*g*.
Criscione, J. M., Volk, H. F., and Smith, A. W. Protection of graphite from oxidation at 2100°C, (1) 7*g*.
Croft, W. J. See Comer, J. J.
Croitoru, Z. Space charges in dielectrics, B (11) 305*g*.
Crombie, P. Increase demand for flint clay prompts calcining facility, (4) 105*j*.
Cromer, W. R., and Molbach, A. Lamp bulb assorting apparatus, P (9) 220*b*.
Cronin, G. R., and Haisty, R. W. Preparation of semi-insulating gallium arsenide by chromium doping, (3) 76*i*.
Cronin, M. E. See Brown, J. F. W.
Crook, D. N. See Tauber, E.
Croom, H. C. How to manufacture special brick shapes, (9) 222*h*.
Cross, D. L. See Eubank, W. R.
Cross, L. E. See Perry, F. W.
Crouzet. Device for measuring forces by application of the Hall effect, P (2) 47*b*.
Crow, R. F., Hime, W. G., and Connolly, J. D. Analysis of portland cement by atomic absorption, (10) 247*j*.
Crowder, B. L., Morehead, F. F., and Wagner, P. R. Efficient injection electroluminescence in ZnTe by avalanche breakdown, (7) 162*i*.
Crowder, T. E. Method of determining the particle size distribution of a powder, P (10) 268*d*.
Crowe, W. G. Solid abrasive article, P (1) 1*f*.
Crowley, M. S. Hydrogen-silica reactions in refractories, (8) 179*j*. Refinery use of refractories, (5) 123*i*.
Crownover, J. W. Torsional mode ceramic bandpass filter, P (4) 103*a*.
Crucible Steel Co. of America. Methods for the elevated temperature protection of metallic surface and coatings therefor, P (4) 92*d*.
Crystalonics, Inc. Epitaxial transistor and method of manufacture, P (9) 230*h*.
Csakvary, T. Sintered electrical contact members, P (8) 186*e*.
Csetenyi, J. Deterioration of aluminosilicate refractories by fly ash and slag of power stations, (3) 70*i*.
CSF. See Compagnie Generale de Telegraphie Sans Fil.
CTS Corp. Electrical component and method of making the same, P (8) 184*j*. Electrical resistance element, P (5) 127*h*. Electrical resistance element and method of making the same, P (10) 263*e*. Precision resistance element and method of making the same, P (9) 226*g*.
Cubaud, J. C., Murat, M., and Eyraud, C. Thermal evolution of CPAC portland cement pastes at 25° to 1000°C—differential thermal and dilatometric analyses, (2) 34*a*.
Cubicciotti, D. High-temperature chemical stability, B (9) 244*f*.
Cuhra, B., and Gruner, K. Method of production of aqueous silver suspensions applied for only one heating operation, P (5) 126*c*.
Culler, V. E. Short-duration light source comprising an electron irradiated transparent insulating body, P (2) 40*c*.
Cullinan Refractories, Ltd. Manufacture of large refractory block, P (8) 181*g*. Method of lining furnaces and like vessels, and apparatus therefor, P (8) 181*b*. Refractory brick, P (5) 125*e*.
Culp, J. D. See Jackson, R. E.
Cumberland, J. R. Glass thickness gage, P (9) 220*h*.
Cummings, H. B. Recuperator tubes, P (7) 154*a*.
Cummings, W. P., Baral, L. L., and Laudone, J. A. Process for preparing a desiccant pellet, P (4) 107*c*.
Cummings, W. W. See Dugger, D. L.
Cummins, H. Z. See Shapiro, S. M.
Cummins, J. B. See Aiken, H. H.
Cunningham, J. A. Air-oxide isolated integrated circuits, (7) 155*h*.
Cunningham, J. A., and Johnson, R. H. Low capacitance planar diode, P (8) 185*a*.
Cunningham, J. A., and Williams, R. P. Metallic contacts for semiconductor devices, P (11) 286*c*.
Cunningham, J. L. See Bonar, K. M.; Ryan, J. R.; Snellman, R.
Cunningham, M. B., and Dunlap, C. K., Jr. Forming tube for glass fibers, P (9) 220*b*.
Cunningham, R. T. See Scotti, V. G.
Cunningham, T. W. Ball mill or the like, P (4) 103*d*.
Cuomo, J. J., and Gambino, R. J. Arc process for forming high melting point compounds, P (9) 230*g*.
Cupery, M. E. See Marshall, W. J.
Curn, F. Method of preparing a diamond tool, P (2) 33*i*.
Curran, M. J. See Anderson, R. C.
Currie, T. E. Predicting life expectancy of laundry porcelain enamels, (2) 35*f*.
Currin, C. G., and Hood, J. S., Jr. Automatic apparatus for measuring resistivity of semiconductors, P (7) 156*g*.
Curry, N. A. See Timmer, W. F.
Curry, R. H. See Kestigian, M.
Curtis, B. J., and Graffenberger, H. Floating zone crystal growth of lanthanum hexaboride, (7) 163*j*.
Cusano, D. A., and Sormberger, R. L. Heterojunction electroluminescent devices, P (10) 264*b*. Semiconductor photovoltaic devices, P (3) 79*e*.
Cutchen, J. T. Polarity effects and charge liberation in lead zirconate titanate ceramics under high dynamic stress, (5) 126*e*. See Canfield, J. M.
Cutler, I. B. See Johnson, H. B.; Kovalenko, E. N.; Stewart, R. W.; Winkler, E. R.
Cuvelier, M. Conveying mechanism for a tunnel kiln, P (11) 290*h*. Kiln and related apparatus, P (11) 290*e*.
Cybriwsky, A. Wide temperature range four point probe device for measuring electrical resistivity, (1) 14*b*.
Cyprus Mines Corp. Fast fire tunnel kiln, P (8) 189*c*.

Dabas, M. S. See Verma, M. R.
Dachille, F. See Stewart, D. R.
d'Adrian, V. L. D. High alkali earth oxide glass bead composition, P (5) 120*c*.
Dagerhamn, T. X-ray study on solid solutions of oxygen in hafnium, (3) 88*b*. See Holmberg, B.
Dagnall, R. M., Thompson, K. C., and West, T. S. Investigation of some experimental parameters in atomic fluorescence spectrophotometry, (4) 104*h*.
Dailly, D. F. Ceramic thermochemistry (I) simple approach to basics, (8) 192*g*; (II) chemical reduction in brick, (9) 222*h*.
Daily, A. M., Boykin, O. F., and Hartman, C. W. Electrical resistance element and method of making, P (10) 263*e*.
Dale, J. R. Compound semiconductor device and method of alloying, P (1) 10*j*.
Dale Electronics, Inc. Electrical resistor having a core element with high heat dissipating properties, P (3) 78*a*.
Dalmau Castells, L. Silicon carbide as a refractory material, B (2) 62*d*.
Damm, J. Z. Dichroism in R bands induced in gamma-irradiated potassium chloride crystals, B (9) 244*g*.
Dams, H. C. M. Mechanization in the enamel industry, (9) 216*c*.
Dancy, E. A., and Derge, G. J. Electrical conductivity of FeO_x-CaO slags, (9) 238*b*.
Dancy, E. A., Everett, L. H., and McCade, C. L. Standard free energy of formation of cerium and praseodymium monocarbides, (4) 110*d*.
Dane, A. H. See Miller, A. E.
Daniels, B. K. Phase change of zinc sulfide and the stacking sequence of a new 66R polytype, (8) 204*f*.
Danielson, G. E., Jr. See DeMaria, A. J.
Danielsson, L. Adsorption of a number of elements from HNO_3-HF and H_2SO_4-HF solutions by cation and anion exchange, (8) 191*a*.
Danielsson, U. Conduction calorimeter studies of the heat of hydration of portland cement, (7) 146*g*.
Danilkin, V. I., and Fedorov, A. P. Influence of the structure of certain alkali glasses on injection currents, B (9) 246*a*.
Danilkin, V. I., Kudryavtsev, L. A., and Ivanov, V. A. Transport of positive sodium and potassium ions in a direct electric field at molten salt-alkali glass-vacuum interfaces, B (4) 113*d*.
Danilova, E. P. See Ostrikov, M. S.
D'Aprix, R. See Conrad, F.
Darby, W. L. See Galasso, F. S.; Layden, G. K.
Darland, W. G., Jr. See Powers, R. A.
Darrow, K. A. Method for the production of diamond compact abrasives, P (5) 115*h*.
Darrow, K. A., and Hull, E. H. Electrical discharge cleaning and coating process, P (9) 233*c*. Preparation of elongated needlelike diamond having electrically conductive properties, P (7) 145*h*.
Darrow, K. A., and Wentorf, R. H., Jr. Process for doping a diamond in a gaseous electrical discharge, P (8) 185*j*.
Darrow, W. L., and Hsiao, C. Refining of ferrophos, P (5) 133*g*.
Das, B. See Bhushan, B.
Das, C. R. Measurement of durability of glass and glass enamels—methods for the complete analysis of water extract, (3) 80*i*. Reaction between borate glass and attacking agents—action of water on the glasses in the system Na_2O-B_2O_3, (10) 253*g*. Study of the effect of glass composition on the retention of fluorine and on opacity, (8) 176*e*.
Das, D. K. See Allen, L. R.
Das, S. K., and Aggarwal, P. S. Effects of some minor additions on sintering of titania, (4) 107*h*.
Dash, W. C., and Taft, E. A., Jr. Epitaxial growth of semiconductor devices, P (8) 184*b*.
D'Asto, E. G. Coated chimney, P (1) 7*d*.
Dates, H. F., and Davis, J. K. Iridizing method, P (10) 255*h*.
Datta, R. K. System $LiAlGeO_4$-Zn_2GeO_4, (8) 208*i*.
Dauknys, V. See Pranckevicius, G. A.
Davern, W. See Ing, S. W., Jr.
Davey, D. G., and Stutske, W. A. Molten glass feeder tube centering and drive, P (10) 256*a*.
Davey, J. E. Electrical characteristics of epitaxial germanium films vacuum deposited on semi-insulating GaAs up to thicknesses of 10^4 A, (4) 100*f*.
David Budworth, Ltd. Fuel vaporizing burner arrangements, P (2) 52*h*.
Davidge, R. W. See Newey, C. W. A.
Davidovich, J. G. See Fialkov, A. S.
Davidovich, N. M., and Dorin, V. A. Electrical studies of TiO_{2-x} diffusion layers on titanium, (3) 85*d*.
Davidson, C. R., Jr. See Wheeler, R. W.
Davidson, J. M. See Helm, J. W.
Davies, B. Degree of direct bonding in brick of magnesia and chrome ore, P (9) 225*d*. See Havranek, P. H.
Davies, B., and Hanson, D. C. Glass tank structure with a regenerator chamber, P (9) 235*a*.
Davies, C. N. Movement of dust particles near a horizontal cylinder containing a sampling orifice, (8) 187*f*.
Davies, G. T. Aerofoil blade for use in a hot fluid stream, P (8) 174*i*.
Davies, N. C. See Needham, J. G.
Davies, T. J., and Evans, P. E. Preparation and examination of mixtures of aluminum nitride and uranium mononitride, (7) 152*b*.
Davis, C. W., Sr. Laminated glass, P (2) 38*i*.
Davis, F. W. Method of producing ceramic nuclear fuel material having incorporated therein burnable poison, P (8) 181*f*.
Davis, G. L. See Aldrich, L. T.
Davis, H. M. See Chu, G. P. K.
Davis, J. Etching process, P (3) 78*g*.
Davis, J. K. See Dates, H. F.
Davis, M. P., and Palmour, H., III. Grain boundary sliding in alumina bicrystals, B (2) 61*f*.
Davis, R. S. See Doherty, P. E.
Davis, R. S., Engelke, J. L., and Mattuck, J. B. Refractory coated casting mold, P (2) 35*g*.
Davis, T. D., and Watson, A. D. Crusher feeding apparatus, P (10) 269*c*.
Davy, J. R. Manufacture of calcium aluminate optical glass, P (11) 278*e*.
Davy, J. R., and Hope, A. J. N. Method for making glass sandwiches primarily for windows of optical instruments, P (4) 95*a*.
Davy & United Engineering Co., Ltd. Method and apparatus for charging furnaces or the like, P (1) 15*a*.
Dawihl, W. See Klingler, E. A.
Dawihl, W., and Frisch, B. System α-alumina at low water vapor pressures, (8) 208*j*.
Dawihl, W., and Klingler, E. Resistance of single crystal alumina and sintered alumina bodies to corrosion by inorganic acids, (8) 180*i*. Sintered alumina and the dependence of its aging behavior on surfactants, (2) 42*i*.

Dawihl, W., Klingler, E., and Altmeyer, G. Determination of the elastic limit of sintered alumina bodies at room temperature and under local compression, (2) 41*i*.

Dawson, P. H. Secondary electron emission yields of some ceramics, (2) 56*a*.

Day, D. E. See Burdick, V. L.; Steinkamp, W. E.

Day, F., Froberg, M. L., and Holschlag, J. B. Apparatus for processing filament-forming mineral materials, P (9) 210*j*.

Day, F., and Stalego, C. J. Method and apparatus for producing foliated or flake glass, P (9) 220*j*.

Day, H. P. See Holt, J. P.

Day, H. R., Jr. See Herrick, C. S.

Day, R. B., and Stokes, R. J. Grain boundaries and the mechanical behavior of magnesium oxide, B (2) 61*g*. Plastic softening of magnesium oxide at high temperatures by nickel oxide addition, (10) 271*c*.

Dayal, R. R., Johnson, R. E., and Muan, A. Stability of mullite as derived from equilibria in the system CoO-Al_2O_3-SiO_2, (11) 301*f*.

Dayton, R. W. See Blocher, J. M., Jr.

De, S. K. See Banerjee, J. C.

Deacon, R. F., Miskin, S. F. A., and Ladell, B. J. Gas entrapment during the sintering of magnesia in argon, (2) 41*h*.

Deal, B. E. See Mead, C. A.

Deal, B. E., Grove, A. S., Snow, E. H., and Sah, C. T. Observation of impurity redistribution during thermal oxidation of silicon using the MOS structure, (9) 241*h*.

Deal, B. E., and Sklar, M. Thermal oxidation of heavily doped silicon, (11) 302*f*.

Dean, J. Mold design for ceramic casting, P (2) 46*c*.

Dean, J., and Dunn, P. R. Ceramic mold, P (2) 46*b*.

Dear, W. N. Burner reactor apparatus, P (4) 105*i*.

De Batist, R. Room temperature elastic constants of single crystal U_4O_9, (8) 206*d*.

De Bell & Richardson, Inc. Method and apparatus for applying glass-resin coupling composition to glass, P (1) 5*b*.

Debenham, W. S. Developments in the use of direct-bonded brick, (2) 41*d*.

Debets, P. C. See Cordfunke, E. H. P.

Decker, H., Maeder, H. J., and Wehren, P. Grinding mill of the swinging type with a plurality of grinder drums, P (7) 160*i*.

Deckers, J. M. Molecular beam—a research tool for the chemist, (1) 14*b*.

Dede, J. B., Jr. See Brown, L. H.

Deeg, E. W. Photosensitive device using glass of arsenic, sulfur, and halogen, method of using, and method of making the glass, P (8) 185*g*. Some properties of tempered glass, (2) 37*h*. See Baier, E.

Deeg, E. W., Faulstich, M., and Neuroth, N. Glass as a material for solid-state lasers, (10) 252*e*.

Deeglas Fibres, Ltd. Apparatus for spinning molten glass, P (3) 67*h*.

Deer, W. A., Howie, R. A., and Zussman, J. Introduction to the Rock-Forming Minerals, B (11) 304*f*.

De Fries, R. M. See Yeh, Tsu-Hsing.

De Geer, H. H. Hot top, P (4) 98*a*. See Edstrom, J. O.

Degen, M. G., and Toropov, N. A. Spherulites in certain silicate glasses, B (9) 246*b*.

Degreve, F. See Drowart, J.

Degtyareva, E. V. See Kainarskii, I. S.

Degtyareva, E. V., and Kukhtenko, V. A. Experience with the use of a vibromill for determining the abradability of refractories, (5) 122*i*.

De Havilland Aircraft Co., Ltd. Method of and a testing agent for testing articles and components for flaws and like surface discontinuities, P (3) 81*g*.

De Havilland Aircraft Co., Ltd., and Norton Grinding Wheel Co., Ltd. Protective flame sprayed coatings, P (4) 92*f*.

Deju, R. A., and Bhappu, R. B. Chemical interpretation of surface phenomena in silicate minerals, (4) 107*e*. Modified electrophoresis apparatus, (4) 104*j*. Surface properties of silicate minerals, (4) 111*d*.

De Keersmaecker, J. Apparatus for manufacturing glass ribbon on a molten metal bath, P (8) 176*f*.

Dekker, P. Comparison of various types of enameling furnaces, (10) 249*i*.

Deksnys, A., Paukste, J., Sakalauskaite, D., Tolutis, V., and Jasutis, V. Physical properties of thin CdTe-metal (In, Cu, Au) films, (5) 126*i*.

Delamarre, C., and Perez y Jorba, M. Lime-hafnium oxide system, (1) 21*f*.

Delavignette, P. See Heerschap, M.; Spyridelis, J.

Delfosse, J. M. See Fripiat, J. J.

Dell, R. M. See Wheeler, V. J.

Dell, R. M., and Wheeler, V. J. Chemical reactivity of uranium trioxide (II) UO_3 hydrates, (5) 134*d*.

Delott, R. B. Spray pickling promotes uniform steel preparation, (9) 216*h*.

Deloye, F. X. Microporous chalk mortar composition, P (9) 215*j*.

Del Rio Garcia, J. G., and Balaguer Arzo, F. Improvements in ceramic kilns, P (2) 53*c*.

De Luca, J. P. See Bergeron, C. G.

Demaison, R. J. Furnace repair gun, P (10) 250*j*.

Demarest, H. M., Jr. See Harrell, W. C.

DeMaria, A. J. See Stetser, D. A.

DeMaria, A. J., Ferrar, C. M., and Danielson, G. E., Jr. Mode locking of Nd^{3+}-doped glass laser, (1) 10*c*.

Demas, N. P. Process of manufacture of incandescent lamp, P (11) 279*h*.

Dembovskii, S. A. Crystallization of glass in the Se-As_2Se_3 system, (3) 65*j*.

DeMeis, W. M., and Fischer, A. G. Improved method for growing II-VI crystals from the vapor phase, (11) 297*e*.

De Ment, E. R. See Lewis, C. J.

Demer, L. J. See Walker, W. W.

Demichel, P. See Adeline, B.

Demishev, G. K. Glass structure and structural stresses, B (7) 171*g*. Heterodynamism of silicate glass, B (7) 171*f*.

Demkina, L. I. Summary of the Symposium on Optical Properties of Glasses, B (9) 245*e*.

Den, Fen-syan. See Meerson, G. A.

Denker, S. P., and Meyer, J. Pressure casting of refractory ceramics, (1) 7*g*.

Dennis, J. S. See Phelps, G. W.

Dennis, P. J. Thermostatic switch, P (1) 12*b*.

Denny, A. D. Producing high temperature calcium silicates, P (8) 190*g*.

Denson, N. M., and Waage, K. M. Some bauxite and clay deposits in northeastern Alabama, (8) 189*i*.

Dentists' Supply Co. of New York. Refractory mold, P (5) 125*b*.

Denton, R. T. Elastic wave devices utilizing mixed crystals of potassium tantalate-potassium niobate, P (3) 77*j*.

Deo, P. G., and Sharma, S. D. Dislocation nucleation in sodium chloride crystals, (8) 195*a*.

DePaolis, M. V., Jr. See Senhouse, L. S., Jr.

Depew, H. A. See Quinn, P. D.

Derbyshire, S. W. See Stadelmaier, H. H.

Derge, G. J. See Dancy, E. A.; Tadsen, V. S.

Deri, M. Ceramic research in the field of industrial high temperature technology, (2) 60*i*. Correlations between structure and electrical properties of titania–containing polycrystalline semiconductors, (1) 9*i*. Ferroelectric Ceramics, B (9) 244*h*. Recent research in the field of dielectrics and semiconductors, (1) 10*e*. See Batka, K.

Dermatis, S. N. See Killias, H. R.

Dernier, P. D. See Marezio, M.

Dersin, H., and Sirtl, E. Method for the production of semiconductor dendrites, P (5) 128*j*.

Dertev, N. K., and Voronkova, Z. P. Electrochemical method for determining diffusion coefficients of silicate melts, B (4) 113*e*.

Dertev, N. K., Voronkova, Z. P., Borisov, A. F., and Akhlestin, E. S. Use of an electrochemical method for studying the structure of silicate melts, B (9) 246*a*.

Descarsin, M. Manufacture of glass, P (11) 278*f*.

Deschamps, A. Ferromagnetic materials and methods of fabrication, P (3) 78*i*, P (11) 285*d*.

De Shetler, L. C., and Mumford, E. H. Cylinder mounting on I.S. type glassware forming machine, P (8) 177*b*.

Deshko, Yu. I. See Gusarov, A. D.

Deslattes, R. D., Torgesen, J. L., Paretzkin, B., and Horton, A. T. Preliminary studies on the characterization of solution-grown ADP crystals, B (5) 139*i*.

Despic, A. R. See Drazic, D. M.

Dess, H. M., and Bolin, S. R. Czochralski growth and properties of yttrium vanadate crystals, (10) 262*a*.

Dettmar, H. K., Lode, W., and Mare, E. Light scattering and particle size distribution of spherical particles (I) theory, (3) 86*c*.

Deutsche Edelstahlwerke Akt.-Ges. Annealing furnace of the continuous type and a method of annealing therein, P (1) 14*j*. Process for thermal compensation of permanent magnetization systems by the use of a ferrite, P (11) 287*h*.

Deutsche Erdoel Akt.-Ges. Process for the manufacture of boron-free graphite, P (1) 8*h*.

Deutsche Gold- und Silber-Scheideanstalt vorm. Roessler. Adhesives, cements, trowelling, and coating compositions, P (4) 91*c*. Aqueous suspensions of aluminum oxide and the production thereof, P (8) 190*c*. Manganese and aluminum containing pink pigments for glazes and underglazes, P (10) 261*e*. Measuring resistance, P (2) 48*a*. Preparation of a mixture of zirconia and silica, P (3) 83*g*. Process and apparatus for consolidating substances in powder form, P (2) 50*b*. Process for the continuous production of granular sodium monoxide using metallic sodium introduced in molten form, P (2) 54*b*. Process for making silicon carbide, P (5) 124*j*. Process for modifying calcium carbonate, P (9) 236*g*. Process for preparing a hydrophobic wet-precipitated silica, P (9) 236*g*. Process for producing silicon carbide, P (4) 99*b*. Process for the purification of highly dispersed oxides of silicon, aluminum, titanium, and/or zirconium, P (9) 236*j*. Process for separating mixtures of substances, P (1) 13*c*. Production of finely divided amorphous silica, P (7) 161*c*. Production of mixtures of zirconium oxide and silicic acid, P (4) 99*d*. Recovery of zirconium compounds from alkali metal zirconium silicates, P (1) 16*b*.

Deutsche Tafelglas Akt.-Ges. Glass melting vats having refractory bricks containing chromium oxide, P (1) 5*f*. Method and apparatus for bending glass panes, P (1) 5*c*.

Devanarajanan, S., and Easwaran, K. R. K. Thermal expansion of ferroelectrics—lithium hydrazinium sulfate, (8) 183*i*.

DeVilbiss Co. Method and apparatus for electrostatic deposition of coating materials, P (4) 92*a*.

De Vore, G. C., and Kamerer, J. W. Glass sheet bending mold, P (9) 220*g*.

DeVries, R. C. Epitaxial growth of CrO_2, (8) 197*i*. See Cooke, F. W.; Rodbell, D.

Dewell, E. H. Process for making nuclear fuel materials, P (8) 182*a*.

Dewey, J. L. See McMinn, C. J.

Dew-Hughes, D. Hard superconductors, (10) 262*b*.

Dezelic, G. See Kratohvil, J. P.

Dhar, R. N. See Bishui, B. M.

Diaconis, N. S. See Metzger, J. W.

Diamant Boart. Cutting disks, P (1) 1*f*.

Diamond, S. See Ormsby, W. C.

Diamond, S., White, J. L., and Doich, W. L. Effects of isomorphous substitution in hydrothermally synthesized tobermorite, (1) 18*j*.

Diamond Alkali Co. Preparation of thoria sols by electrodialysis, P (1) 16*a*. Process for producing sodium carbonate from sodium bicarbonate obtained by the ammonia-soda process, P (11) 291*j*.

Dias, P. F. See Barford, J. C.

Di Bello, P. M. See Beck, W. F.

Dibrov, G. D. See Ostrikov, M. S.

Dibrov, G. D., Drobasheva, T. I., and Ostrikov, M. S. Hydration of portland cement clinker and of its component minerals in the presence of small amounts of alkali sulfates, (4) 90*h*.

Dichter, J. Glass ampoule manufacture, P (4) 94*f*. Glass tube feeding devices, P (11) 278*d*.

Dick, N. T. Strip cladding flux, P (5) 117*i*.

Dickens, B. Bonding in Pb_3O_4 and structural principles in stoichiometric lead oxides, (8) 191*g*. Bonding in red PbO, (8) 191*h*. Bonding in the yellow form of lead monoxide, (8) 191*h*.

Dickens, P. G., and Whittingham, M. S. Recombination of oxygen atoms on oxide surfaces (II) catalytic activities of the alkali metal tungsten bronzes, (1) 27*f*.

Dickson, D. C., Jr. *Pn* junction having bulk breakdown only and method of producing same, P (7) 157*e*.

Dickson, R. W. Anomaly in Young's modulus and internal friction of $5SrTiO_3$-$3La_{2/3}TiO_3$ below 100°C, (1) 16*j*.

Dickson Electronics Corp. Treating of surfaces of semiconductor elements, P (8) 186*c*.

Didier-Werke Akt.-Ges. Heating chamber walls, particularly the backwalls of Siemens-Martin furnaces, P (8) 189*a*. Lining for installations for the degasification of metals, P (9) 225*j*. Linings for blast furnace shafts, P (10) 259*b*. Process for preparation of sintered magnesia, P (5) 125*b*. Refractory brick with one or more plates, P (11) 283*a*. Refractory bricks, preferably basic, for industrial furnaces, P (10) 260*f*. Suspended refractory brick, P (11) 283*b*.

DiDomenico, M., Jr. See Remeika, J. P.

Diefendorf, R. J. High temperature capacitor, P (10) 264*c*. Method of forming pyrolytic graphite sheets, P (4) 106*d*. Method of forming a sheet, P (7) 153*i*. Refractory pyrolytic materials, B (5) 140*c*.

Dierksheide, D. H., and Trudeau, U. P. Glassware handling apparatus, P (9) 220*h*.

Dierssen, G. H. See O'Dell, E. W.

Dietert, H. W. Physical properties testing apparatus, P (8) 188*d*. Structure for and method of cooling granular material, P (9) 233*d*. Temperature controlled structure for and method of cooling granular material, P (10) 261*a*.

Dietert, Harry W., Co. See Harry W. Dietert Co.

Dietrich, W. See Kotsmid, F.; Vescia, M.

Dietz, W. See Wirth, H.

Dietzel, A. See Oel, H. J.

Diggens, G. W. Electrolytic capacitor comprising glass-to-metal and resilient pressure seal combination, P (9) 230*f*.

Dike, M. A. Method of preparing magnetic memory device, P (8) 185*a*.

Dildilian, A. T. See Nicholas, E. W.

DiLeonardo, V. C. See Dodge, N. B.

Dill, J. G. Method for making an electrical capacitor, P (9) 231*e*.

Diller, R. E., and Steiner, C. Method for producing and handling elongated tubular items, P (7) 150*j*.

Dillon, E. L. Expanding role of computer in geology, (11) 303*e*.

Dillon, J. F., Jr., Gyorgy, E. M., and Remeika, J. P. Magnetostriction of silicon-doped yttrium iron garnet (YIG), (9) 240*d*.

Dimitriev, Ya. B. See Marinov, M. R.

Dingle, H. E. Reactivity of barium carbonate in combating scumming in structural clay products, (10) 256*f*.

Dinkel, P. E. Hydraulic cement panel with low density core and fiber reinforced high density surface layers, P (2) 34*j*.

Dionis'ev, S. D. See Il'yasov, I. I.

Dionne, G. F. See Novack, M. A., Jr.

Dios Cancela, G. See Gonzalez Garcia, S.

Disegna, W. L. See Erickson, H.

Dislich, H., and Jacobsen, A. Glass-plastic laminates as light conducting systems, (10) 252*g*.

Di Stefano, V. N., Skrivan, J. F., and Butler, G. Pigment via plasma jet-improved preheater configuration, P (9) 226*e*.

Distillers, Ltd. Preparation of an antimony oxide-tin oxide catalyst composition and the product thereof, P (7) 153*f*.

Ditmars, D. A. See Douglas, T. B.

Ditmars, D. A., and Douglas, T. B. Relative enthalpy of BeO-Al_2O_3 from 273° to 1173°K—thermodynamic properties from 273° to 2150°K, (11) 300*b*. Relative enthalpy of BeO-3Al_2O_3 from 273° to 1173°K—thermodynamic properties from 273° to 2150°K, (11) 300*c*.
Ditrick, N. H. Insulated-gate field-effect semiconductor device, P (5) 127*h*. Stabilizing coatings for semiconductor devices, P (10) 265*g*.
Ditterich, K. See Kolb, F.
Di Vita, S. See Arlett, R. H.; Fischer, R. J.
Dixon, R. W., and Cohen, M. G. New technique for measuring magnitudes of photoelastic tensors and its application to lithium niobate, (8) 203*a*.
Dixon, S., Jr. Microwave power limiter utilizing a planar ferrite sphere [Mn-ZnY], P (8) 185*c*.
Dixon, W. S. See Wilson, C. B.
Dmitrenko, G. E. Degrees of stable diagonals in a sixfold reciprocal system of twelve salts L,N,H‖ X,Y,Z,T, (11) 293*j*. Possible types of reciprocal systems from twelve salts A,B,C‖ X,Y,Z,T, (11) 299*a*.
Dmitriev, V. I. See Kostyukov, N. S.
Dmitrieva, G. G. See Okorokov, S. D.
Dobbin, W. J., Lessor, A. E., Jr., and Maddocks, F. S. Method of manufacturing multilayer microcircuitry including electropolishing to smooth film conductors, P (8) 185*i*.
Dobrott, R. D. See Williams, E. W.
Dobrovol'skii, K. A. See Toropov, N. A.
Dobrzhanskii, G. F. See Erman, L. Ya.
Dobson, C. D. Semiconductor device having *pn* junction defined by the boundary between two intersecting semiconductor layers, P (11) 287*d*.
Dobychin, D. P. Influence of aluminum oxide on the structure of sodium borosilicate glasses and of porous glasses obtained from them, B (7) 171*b*. Possibility of controlling the structure of porous glasses, (3) 66*d*.
Dockerty, S. M. Sheet forming apparatus, P (11) 279*e*.
Dodd, A. E. Basic science and the traditional ceramic industries, (2) 60*h*, (11) 292*i*.
Dodd, D. M. See Remeika, J. P.
Dodd, D. M., and Fraser, D. B. Optical determinations of OH in fused silica, (2) 55*j*.
Dodd, J. R. Processes of conversion of aragonite to calcite with examples from the Cretaceous of Texas, (7) 166*i*.
Dode, M. See Pialoux, A.
Dodge, N. B., Powers, W. H., and DiLeonardo, V. C. Automatic reflectance microscopy of refractories, (8) 179*f*.
Dodson, V. H., Jr., and Serafin, F. G. Cement additives composed of ethanolamine salts, P (10) 249*a*.
Doering, W. E., and Kegg, R. R. Transparent reinforced glass pipe, P (8) 179*b*.
Doerner, H. See Erlenstaedt, G.
Doerr, F. H. Use of the electron microanalyzer in glass laboratories, (10) 253*j*.
Doerre, E. See Klingler, E. A.
Doherty, P. E., Lee, D. W., and Davis, R. S. Direct observation of the crystallization of Li_2O-Al_2O_3-SiO_2 glasses containing TiO_2, (3) 66*b*.
Dohman, E. J., Shaler, R. G., and Rinehimer, W. A. Amine modified clay and method, P (4) 106*i*.
Dohmen, H. G. Crystal growth, P (3) 77*h*.
Dohmen, H. G., and Sims, H. A. Control of crystal size, P (3) 77*f*.
Doi, M. Comparative study of results obtained with fireclay runner brick and SiC-containing (20%) runner brick used for making killed steel, (9) 223*g*.
Doinikov, L. I. See Borisova, Z. U.
Dolch, W. L. See Diamond, S.
Dolgina, G. Z., and Markevich, E. P. Stabilized magnesite-dolomite brick in converter linings, (9) 224*h*.
Dolinskaya, N. G. See Chebukov, M. F.
Dollimore, D., and Nicholson, D. Thermal decomposition of oxalates (III) decomposition and surface properties of zinc oxalate, (8) 209*h*.
Dolomitwerke G.m.b.H. Highly hydration stable sinters of dolomite, magnesite, lime, or the like, P (1) 7*f*. Manufacture of tar impregnated refractories, P (10) 259*d*. Manufacturing of consolidated heat-treated refractory shaped bodies, P (10) 259*e*. Process for the manufacture of stabilized sintered dolomite, P (4) 107*b*. Sintered material, P (10) 260*i*.
Doman, R. C. See Alper, A. M.
Domange, L. See Golabi, S. M.
Dombrovskaya, N. S., and Alekseeva, E. A. New types of singular stars of sixfold reciprocal systems, (8) 203*c*.
Domenici, M. See Carraro, G.
Dominey, D. A., Morley, H., and Young, D. A. Kinetics of the decomposition of nickel oxalate, (1) 21*c*.
Domingues, L. P. See Furlong, L. R.
Dominion Engineering Works, Ltd. Autogenous grinding mill, P (3) 83*a*.
Dominion Magnesium, Ltd. Purifying device for magnesium production retort, P (7) 154*a*.
Dominion Tar & Chemical Co., Ltd. Dehydration of gypsum, P (9) 235*f*. Production of calcium sulfate hemihydrate, P (7) 147*d*.
Donald, D. K. See Lambe, J.
Donath, F. A. See Fruth, L. S., Jr.
Donneaud, P. Some applications of the ionic conductivity of zirconia, (2) 47*c*.
Donnelly, J. F., and Cooper, R. C. Optically variable one-way mirror, P (1) 6*a*.
Donnelly, J. W. Glass forming apparatus with self-accommodating and universal plungers, P (9) 220*d*.
Donnelly Mirrors, Inc. Optically variable one-way mirror, P (1) 6*a*.
Donotti, S. New high performance de-airing extruder for semistiff clay, (9) 232*i*.
Donovan, D. R., and Murphy, J. A. High temperature furnace conveyor system, P (7) 160*b*.
Doo, V. Y. Methods of producing single crystals on polycrystalline substrates and devices using same, P (10) 265*a*. Thin silicon film growth on polycrystalline alumina ceramic, (4) 100*d*.
Doolittle, H. D., and Ettre, K. S. Ceramic-metallizing tape, P (3) 77*e*.
Doremus, R. H. Exchange and diffusion of ions in glass, (8) 175*c*.
Dorin, V. A. See Davidovich, N. M.
Dorm, E. See Marinder, B. O.
Dormant, L. See Adamson, A. W.
Dorokhov, V. I. See Ivanov, V. E.; Verkhorobin, L. F.
Dorokhova, M. L. See Ivanov, A. O.; Leko, V. K.
Doronin, L. K., Mikhailov, N. V., and Rebinder, P. A. Heat resistance of sand concrete, (10) 248*h*.
Dorsey, F. E. See Fuller, R. A.
Dortmund-Horder Huttenunion Akt.-Ges. Refractory linings for chambers for degasifying metals, P (2) 45*d*.
Dosch, W. Inner crystalline absorption of water and organic substances of tetracalcium aluminate hydrate, (8) 174*c*.
Doss, R. N., Jain, V. K., and Sircar, A. Dielectric properties of porcelain under high alternating fields, (8) 182*h*.
Doty, W. R. Flange forming fixture and method, P (3) 67*d*.
Dotzer, R. See Sandmann, H.
Doubek, J. See Hayer, M.
Doucouret, B. Ceramic industry in western Africa, (9) 244*a*.
Doud, W. O., and Cook, C. W. Glassware and carton handling apparatus, P (4) 94*i*.
Dougal, A. A. See Ferry, D. K.
Douglas, F. C. See Galasso, F. S.
Douglas, R. W. Relaxation processes in glasses, B (2) 61*i*. See Brown, D.; Moriya, Y.; Nath, P.; Steele, F. N.
Douglas, R. W., and El-Shamy, T. M. M. Reactions of glasses with aqueous solutions, (2) 37*h*.
Douglas, R. W., Nath, P., and Paul, A. Oxygen ion activity and its influence on the redox equilibrium in glasses—correction, (5) 119*j*.
Douglas, T. B. See Ditmars, D. A.
Douglas, T. B., and Ditmars, D. A. Measured relative enthalpy of anhydrous crystalline AlF_3 from 273° to 1173°K and derived thermodynamic properties from 273° to 1600°K, (11) 298*b*.
Doulton & Co., Ltd. Ceramic compositions, P (9) 228*g*. Molding ceramic composition, P (2) 46*c*.
Douma, M. See Chernow, F.
Dow Chemical Co. Acid-wetted expandable phosphorus containing graphite composition and method of preparation, P (10) 259*c*. Clay structures, P (5) 133*h*. Composition for the lamination of glass by epoxy resinous materials, P (9) 219*d*. Electroluminescent structure with improved [organic] protective transparent film, P (5) 127*j*. Extraction of lithium values from brines containing calcium salts in the presence of ammonia, P (5) 133*i*. Inhibition of corrosivity of sulfuric acid on carbon steel, P (8) 174*j*. Method of hot topping using [acid-treated] vermicular graphite, P (7) 153*j*. Method of increasing the viscosity of magnesia cements, P (11) 275*f*. Method of lithium recovery, P (5) 133*c*. Method of producing solid solutions of the carnallite type, P (7) 161*a*. Nonmetallic flotation process, P (4) 106*i*. Preparation of high purity magnesium oxide from magnesium salt solutions, P (11) 282*c*. Process for producing expanded graphite, P (9) 227*c*. Process for producing magnesium hydroxide and a noncontaminated effluent solution, P (3) 83*b*. Process for production of magnesium hydroxide and calcium chloride, P (4) 107*e*. Process for removing iron from phosphoric acid, P (7) 148*a*. Recovery of lithium from lithium-bearing ores, P (4) 107*b*. Recovery and separation of cesium and rubidium fluorides using alcohols, P (5) 133*f*. Scale removal, ferrous metal passivation, and compositions therefor, P (5) 117*g*. Slaking process, P (5) 117*a*. Solvent extraction process for the recovery of Be values, P (9) 236*h*. Titanium dioxide pigment and preparation thereof, P (10) 270*b*.
Dow Corning Corp. Automatic apparatus for measuring resistivity of semiconductors, P (7) 156*g*. Hydrophobic silica as a grinding aid, P (10) 266*a*. Integrated circuit using oxide insulated terminal pads on a SiC substrate, P (5) 127*i*. Process for making stable silicone rubber interlayers for glass, P (7) 150*b*, 150*f*.
Dowley, A., and Meadows, F. W. Method of and apparatus for drying pottery, P (11) 290*e*.
Downey, R. M. Apparatus for forming mineral fibers, P (9) 233*b*.
Dowty Rotol, Ltd. Mills for comminuting material, P (9) 236*c*.
Drake, C. F. See Sterling, H. F.
Drake, C. F., and Ellington, K. L. Method of passivating semiconductor devices, P (4) 102*b*.
Drangeid, S. M. Method of reshaping fabricated infrared-generating devices such as electric lamps, P (7) 150*e*.
Drazic, D. M., Despic, A. R., and Maglic, G. A. S. New methods of obtaining fuel cell electrodes (II) oxygen powder electrode, (5) 126*h*.
Dreckman, H. See Wilson, C. B.
Drennan, J. G. Bottle metering mechanism, P (1) 4*g*. Bottle sorting machine and method, P (1) 4*g*.
Dresher, W. H. See Naumann, A. W.
Dresner, J., and Lanyon, H. P. D. Photoconductive device incorporating stabilizing layers on the face of the selenium layer, P (7) 157*d*.
Dressler, P. d'H. Roller hearth tunnel kilns, P (10) 268*j*.
Driel, G. A. H. van, Esveldt, C. J., and Flinsenberg, P. J. Method for making a ferromagnetic memory core, P (3) 78*i*. Method of making memory core, P (4) 101*j*.
Drift, A. van der. See Haan, E. F. de.
Drobasheva, T. I. See Dibrov, G. D.
Drobot, D. V. See Korshunov, B. G.
Drosdziok, H. See Ziehr, G.
Drowart, J. See Colin, R.; Verhaegen, G.
Drowart, J., Colin, R., and Exsteen, G. Mass-spectrometric study of the vaporization of lead monoxide, (1) 22*f*.
Drowart, J., Degreve, F., Verhaegen, G., and Colin, R. Thermochemical study of the germanium oxides using a mass spectrometer, (2) 58*b*.
Dr. Spiess G.m.b.H. Process for treating raw materials and intermediate products to eliminate iron salts, P (3) 83*c*.
Drum, C. M. Measurements of spontaneous bending attributed to surface stresses in thin crystals of aluminum nitride, (.) 22*d*. See Jaccodine, R. J.
Drum, E. W. See Williams, H. A.
Drumheller, C. E. Field effect semiconductor device and method of forming same, P (8) 184*b*.
Drummeter, L. F., Jr., and Hass, G. Solar absorptance and thermal emittance of evaporated coatings, B (11) 305*j*.
Drummond, W. W. Apparatus for producing glass fibers, P (2) 38*i*. Method of and apparatus for feeding a substantially untwisted multifilament strand, P (3) 68*f*. See Irwin, W. T.
Dryon, J. M. C. Devices for dismounting and remounting [sheet] driving rollers, P (11) 278*d*.
Dubansky, A., Gottstein, O., and Stochi, V. Melting of minerals and rocks by high frequency heating, (10) 268*i*.
Dubief, L. See Bentolila, J.
Dubinin, M. M. See Bering, B. P.
Du Bose, M. J. Complete continuous wet mica grinding process, P (9) 235*j*.
Dubova, O. A. See Galdina, N. M.
Dubrovo, S. K. Dependence of the coefficient of thermal expansion of gallosilicate and aluminosilicate glasses on their composition, (3) 66*a*.
Dubrovo, S. K., Lileev, I. S., Mozheiko, V. I., and Shmidt, Yu. A. Glasses with increased heat resistance for chemical laboratory equipment, (3) 66*h*.
Dubrovskaya, L. B., Shveikin, G. P., and Gel'd, P. V. Phase components of the system tantalum-carbon, (4) 109*a*. System Ta-Ta_2O_5, (8) 209*d*.
Dubuisson, J., and Basseville, P. Surface reoxidation phenomena in certain ceramics with a nonstoichiometric perovskite structure, B (2) 61*d*.
Duby, P., and Kellogg, H. H. Transport numbers in pure molten $AgNO_3$ and AgCl by a simplified weighing method, (7) 160*e*. Transport numbers in pure molten silver nitrate and lead bromide by the balance method, (8) 2'0*g*.
Duc, X. N. Thermal conductivity of stabilized zirconia at high temperatures, (2) 57*i*.
Dudavskii, I. E. See Butenko, V. A.
Duderov, G. N., and Chzhan, Sii-Tsuy. Relation between the solubility of alumina, quartz, and kaolin grog in feldspathic melts and the firing temperature of the mixtures, (4) 97*f*.
Duderov, I. G., and Poluboyarinov, D. N. Effect of porosity and structure of corundum refractories on their thermal conductivity, (9) 224*a*.
Dudnik, E. M. See Andreeva, T. V.
Duembgen, G. See Haul, R.
Dufaure de Lajarte, S. See Lajarte, S. D. de.
Duff, R. H. See Passmore, E. M.
Duffee, H. W. See Pearson, A. J.
Duga, J. I. See Bonis, L. J.
Dugger, D. L., Stanton, J. H., Irby, B. N., McConnell, B. L., Cummings, W. W., and Mastman, R. W. Exchange of twenty metal ions with the weakly acidic silanol group of silica gel, (8) 197*g*.
Duggin, M. J., Cox, D., and Zwell, L. Structural studies of the carbides (Fe,Mn)$_3$C and (Fe, Mn)$_5$C$_2$, (7) 168*a*.
Duke, B. W. See Dyer, H. N.
Duke, D. A., MacDowell, J. F., and Karstetter, B. R. Crystallization and chemical strengthening of nepheline glass-ceramics, (3) 65*j*.
Duke, F. R. See King, L. A.
Duke, F. R., and Bissell, C. L. Direct current measurement of fused salt conductivity (II) KCl-LiCl, (3) 84*i*.
Duke, J. B. Method of reducing clay viscosity, P (9) 236*b*. See Jacobs, D. A.
Duncan, J. E. Neutral brown heat absorbing glass composition, P (4) 95*f*.
Duncan, J. E., and Cooper, J. E. Bronze-smoke ophthalmic glass composition, P (4) 93*j*. Bronze-smoke segment glass, P (3) 67*j*.
Duncan, J. K. Apparatus for precision fiberization, P (5) 119*i*.
Duncan, M. E. See McNabb, A.

Duncan Research. Apparatus for precision fiberization, P (5) 119*i*.
Dundee Cement Co. Device for removing clinker from [rotary kiln] thermocouple probe, P (9) 215*g*.
Dunfee, H. See Prins, K.
Dunlap, C. K., Jr. See Cunningham, M. B.
Dunlee Corp. X-ray diffraction tube, P (1) 12*a*.
Dunn, P. R. See Dean, J.
Dunning, L. M. Vitreous enamels for hot water tanks, P (2) 35*h*.
Dunster, D. F. T., and Arthurs, J. K. Process for passivating planar semiconductor devices, P (7) 157*g*.
Du Pont de Nemours, E. I., & Co. Abrasion resistant refractory material, P (2) 43*b*. Abrasive product, P (5) 115*g*. Abrasive resinous polymer compositions and their preparation, P (4) 89*f*. Alumina titanate bonded magnesia, P (8) 180*d*. Bonding telluride-containing thermoelectric modules, P (4) 100*k*. Brookite fibers and their preparation, P (11) 291*c*. Catalyst aggregates of crystallites, P (8) 180*g*. Composition comprising iron-group metal and particulate refractory metal oxide, P (8) 180*h*. Corrosion-inhibited sintered composite of a metal matrix with occluded cement, P (10) 249*a*. Cr-Fe diffusion coating ferrous metal substrate, P (3) 65*d*. Diamond reinforced coatings and method of preparing same, P (4) 89*g*. Encapsulated electrical component, P (7) 156*c*. Ferromagnetic chromium dioxide and preparation thereof, P (1) 15*f*. Glass frits and enamels having esterified surfaces and their preparation, P (10) 255*c*. Luminescent compositions containing europium and the oxyanion-yielding ingredient aluminum, gallium, or germanium, P (2) 47*j*. Luminescent molybdate and tungstate compositions, P (11) 285*j*. Method and apparatus for photometric analysis, P (5) 132*a*. Method and apparatus for solids blending, P (8) 186*j*. Molded amorphous silica bodies and molding powders for manufacture of same, P (4) 106*h*. Nacreous glass flake pigment compositions, P (10) 256*a*. Pigmentary TiO_2 manufacture, P (2) 54*a*. Process and apparatus for impacting and elutriating solid particles, P (7) 158*h*. Process of forming protective coatings on columbium and tantalum using a fluidized bed, P (5) 117*f*. Process for forming a refractory coating on aluminum, P (7) 148*a*. Process for impregnating glass fiber mat with methyl methacrylate polymer, P (2) 40*b*. Process of making metal powder compositions wherein some metal grains contain dispersed refractory metal oxide particles, P (7) 153*i*. Process for preparing hollow refractory particles, P (4) 99*a*. Process for producing fibrous alkali metal titanates, P (9) 232*c*, P (10) 265*i*. Process for producing a fibrous titanium dioxide containing material, P (10) 265*j*. Protected columbium or tantalum article, P (5) 117*g*. Protective coating composition, P (2) 35*f*. Radiant heating devices, P (9) 235*a*. Red luminescent composition product and process, P (4) 102*j*. Refractory shapes, P (4) 99*a*. Selected luminescent molybdates and tungstates of Sc, La, Eu, Gd, and Lu, P (9) 232*g*. Tetragonal silicon and germanium disulfides and their preparation, P (9) 232*f*. Thermoelectric compositions of $Nb_2Ta_{1-x}Si_yGe_{1-y}$, P (4) 103*a*. Thorium oxide sol, P (8) 182*e*.
Dupuydenus, C., and Mollon, P. Review of modern ceramics, (9) 244*a*.
Duran Botia, P. See Alvarez-Estrada, D.
Durelli, A. J., and Parks, V. J. Photoelastic stress analysis on the bonded interface of a strip with different end configurations, (7) 159*a*.
Duro-Test Corp. Method and apparatus for manufacturing fluorescent lamps, P (3) 68*f*.
Dusenbery, E. B. Ancient glass from the cemeteries of Samothrace, (11) 273*i*.
Dutt, G. N. Limestone prospects of Tundapathar-Ambala district, Punjab, (8) 189*h*.
Dutta, A. See Sen, P. C.
Dutta, M. See Chattopadhyay, D.
Dutz, H. Properties of a selective sodium electrode, (10) 253*d*.
Duwell, E. J. Mica pigments, P (7) 161*d*.
Duwez, P. Crystalline structures, B (9) 244*e*.
Dvorak, V., and Janovec, V. Angular energy dependence of a 180° domain wall in $BaTiO_3$, (11) 292*h*.
D'yachkov, P. N., Zagainov, G. G., et al. Concrete lining for steel ladle of the teapot type, (7) 151*f*.
Dyck, W. E. Process for removing float glass carryover on steel rolls, P (11) 279*b*.
Dye, R. W. See Karpenko, I.
Dyer, H. N., Sprague, J. W., Duke, B. W., Marshall, C. W., and Henderson, L. A. Coated abrasives, P (10) 247*g*.
Dygalo, M. I., Kochetova, A. P., and Vasil'eva, K. F. Production of shapes from semiacid raw materials by semidry pressing, (5) 123*g*.
Dyke, W. P., and Grundhauser, F. J. X-ray tube having field emission cathode and evaporative anode in combination with electrical pulser means, P (7) 158*c*.
Dylgerov, V. D. See Prokin, A. I.
Dynamidon-Werk Engelhorn & Co. G.m.b.H. Process for making highly refractory products, P (10) 260*f*.
Dynamit Nobel Akt.-Ges. Process for the manufacture of insulating and refractory bricks and linings, P (3) 72*j*. Process for the manufacture of purified calcium oxide, P (9) 236*f*.
Dyrenforth, W. P. See Breakiron, R. L.
Dyson, J. & J., Ltd. Aluminosilicate refractories, P (1) 7*a*.
Dyson, J. R. See Jones, T. G.
Dzhadzhanashvili, O. S. See Kutateladze, K. S.
Dzierzanowski, F. J. See Haden, W. L., Jr.

Eagle, D. F., and Mallinson, J. C. Coercivity of γ-Fe_2O_3 particles, (8) 192*e*.
Eagle Chemical Co. Siliceous dental filling, P (10) 261*g*.
Eagle-Picher Co. Method for manufacturing porcelain enamel frit, P (1) 3*a*.
Eakins, W. J. Method and apparatus for applying glass-resin coupling composition to glass, P (1) 5*b*.
Eardley, R. P. See Boulton, J. F.
Eargle, F. L. Does packaged brick pay on the job site? (9) 222*i*.
Earl, J. A. Ceramic material, P (5) 120*c*. High temperature electrical insulating material, P (1) 10*j*.
Earl, K. C. See Theodorou, D. G.
Eason, M. D., Lakin, J. R., and Payne, G. Possible uses of elastic-modulus determination for materials testing, (2) 42*f*.
Eastman Kodak Co. Lenses for focusing infrared utilizing elements of silicon and of zinc sulfide, P (5) 120*f*. Method of molding magnesium fluoride, P (3) 68*j*.
Eastwood, H. K. See Westwood, W. D.
Easwaran, K. R. K. See Devanarajanan, S.
Eaton, E. P., Jr. Carbon and carbon-graphite bearings with antifriction surface, P (4) 98*d*.
Eaton, J. J. Method of making electrical capacitors, P (4) 101*i*.
Ebeling, R. See Ashby, M. F.
Eberhart, J. G. Estimation of the surface tension of metal oxides, (7) 163*b*.
Ebhardt, H. Method of producing sintered electrodes, P (9) 226*j*.
Ebina, A. See Murao, T.
Eckart, D. W. See Kohn, J. A.
Eckstein, B. Experimental findings on the disorder model of vitroids, B (2) 61*f*.
Economy, J. Boron nitride fibers, (10) 256*j*.
Edagawa, H., Morita, Y., and Inuishi, Y. Al redistribution in thermally oxidized Si surface, (5) 134*a*. Optical absorption of thermally oxidized Si oxide film, (5) 137*a*.
Edel'man, I. E. See Perli, S. B.
Edelson, N. M. See Best, H. S.
Edens, W. W. See Bergstrom, B. H.
Edgar Allen & Co., Ltd. Feed preheating for rotary kiln and like installations and preheaters therefor, P (1) 14*i*.
Edgerton, Germeshausen & Grier, Inc. Method of making thermoluminescent manganese-activated calcium fluoride, P (2) 48*j*.
Edington, J. W. See Klein, M. J.
Edington, J. W., and Klein, M. J. Slip and fracture in single crystals of thoria, (4) 109*g*.
Edisbury, J. R. Practical Hints on Absorption Spectrometry (Ultra-Violet and Visible), B (5) 140*i*.
Edison Instruments, Inc. High-frequency ultrasonic [piezoelectric] generators, P (9) 231*b*.
Edmiston, W. A., and Grace, R. E. Kinetics of near-equilibrium reduction of wustite, (9) 240*d*.
Edshammar, L. E. Crystal structure of Ru_4Al_{13}, (8) 193*h*.
Edstrom, J. O., and De Geer, H. H. Hot top composition for casting molds, P (4) 98*b*.
Edward & Jones, Ltd. Filter press trays, P (3) 80*b*.
Edwards, A. Method and apparatus for purifying the molten bath of a glass sheet forming operation, P (11) 278*j*. See Loukes, D. G.
Edwards, D. G., Posner, A. M., and Quirk, J. P. Repulsion of chloride ions by negatively charged clay surfaces (I) univalent cation Fithian illites, (7) 167*j*; (II) univalent cation montmorillonites, (7) 167*a*; (III) di- and trivalent cation clays, (7) 167*b*.
Edwards, F. J. Attachment of inserts and fixing devices to pieces of vitreous silica, glass, etc., P (7) 149*i*.
Edwards, R. A. Refractory shape with embedded channel shape reinforcement, P (2) 45*g*.
Effenberg, A., and Poeschmann, H. Measurement of the elasticity of enamels, (9) 216*i*.
Efimenko, L. N., Nechiporenko, E. P., and Pavlov, V. N. Oxidation of tungsten disilicide, (3) 87*g*.
Efimov, A. I. See Vasil'kova, I. V.
Efimov, A. M. See Khar'yuzov, V. A.
Efimov, A. M., and Kokorina, V. F. Certain properties and structure of oxygen-free glasses containing heavy elements of group IV, B (7) 171*g*.
Efimov, Yu. V. See Savitskii, E. M.
Egelstaff, P. A. Study of noncrystalline solids and liquids by inelastic neutron scattering, B (2) 61*g*.
Eger, V. G. See Klyucharov, Ya. V.
Ehlers, E. G. See McCormick, G. R.
Ehlert, R. C. See Mattson, R. A.
Ehlert, R. C., and Mattson, R. A. Characteristic X-rays from boron and beryllium, B (5) 139*h*.
Ehrenreich, L. C. See Wise, D. C.
Ehringer, H. J. Thoriated tungsten filament or wire and method of making same, P (1) 12*b*.
Ehrlich, J. R. Glare reducing of glass, P (10) 255*d*.
Eichler, B., and Owen, J. Refractories for basic oxygen vessels, (2) 42*e*.
Eick, H. A. See Galloway, G. L.
Eick, H. A., and Kihlborg, L. Crystal structure of V_2MoO_8, (10) 270*d*. Crystal structure of $VOMoO_4$, (10) 270*d*.
Eidel'man, E. A. See Gromakov, S. D.
Eiduk, Yu. Ya., Sedmal, U. Ya., and Berzin, R. Ya. Structure of aluminosilicophosphate glasses, B (7) 171*e*.
Eilerman, G. E. Method of forming glass fibers, P (2) 39*g*.
Einstein, E. See Leatham, E.; Scott, R. K.
Eisenberg, A., and Sasada, T. Molecular weight dependence of the glass transition temperatures in sodium phosphate polymers, B (2) 61*f*.
Eisenhower, W. D., Jr., Noll, W. S., and Ake, N. E. Semiconductor [multiple-zone] switch devices, P (5) 129*e*.
Eisenman, G. (editor). Glass Electrodes for Hydrogen and Other Cations—Principles and Practice, B (9) 245*g*.
Eisenwerk Weserhuette, A. G. Jaw crushers, P (3) 83*d*.
Ekdahl, W. G. Apparatus for forming fibrous products, P (10) 254*i*.
Eklund, W. M. See Reynolds, C. B.
Elbreder, C. H. Free flowing treatment of glass beads, P (3) 67*e*.
Elbreder, Chas., & Co., Inc. See Chas. Elbreder & Co., Inc.
Elco Corp. Connector with glass substrate, P (2) 47*b*.
Elden, H. S. Dry powder for wallboard joint treatment, P (5) 116*f*.
Eldon Industries, Inc. Heating element, P (8) 184*f*.
Electra Mfg. Co. Method of manufacturing and attaching nonelectrolytic tantalum capacitors, P (3) 79*a*. Precision electrical resistor, P (2) 49*b*.
Electricite de France and Centre d'Etudes Scientifiques et Techniques. Use of rhyolitic pumice for making heat insulating and refractory concrete, P (3) 73*c*.
Electro Refractaire. Improvements in the manufacture of fused cast refractories containing mineral oxides, P (5) 124*a*.
Electro Refractories & Abrasives Corp. Refractory body and method of making, P (3) 73*c*.
Electroglas, Inc. Diffusion [resistance] furnace, P (4) 105*c*.
Electronatom Corp. Integrated mechanical filter and [wet] electrostatic precipitator system for broad spectrum purification, P (8) 186*g*. Integrated pollution control system, P (8) 186*h*.
Electro-Optical Systems, Inc. Device for forming negative ions from iodine gas and a lanthanum boride contact ionizer surface, P (11) 285*d*.
Elektroschmelzwerk Kempten G.m.b.H. Continuous process for the purification of boron nitride, P (8) 180*j*. Flotation process for the purification of silicon carbide, P (8) 181*c*. Method for producing molded bodies, P (2) 44*c*.
Elemelt, Ltd. Glass melting, P (4) 105*f*.
Elfstrom, M. Crystal structure of Ni_2P_4, (8) 193*j*.
Elgillani, D. A. See Fuerstenau, M. C.
Eliason, J. R. Montmorillonite exchange equilibria with strontium-sodium-cesium, (1) 23*c*.
Eliason, S. H. See Ziselberger, A. E.
Eliason, S. H., Jr. See Ziselberger, A. E.
Elin-Union Akt.-Ges. fuer elektrische Industrie. Method of producing sintered electrodes, P (9) 226*j*.
Eliseev, A. A. See Luzhnaya, N. P.; Slavnova, G. K.
Eliseev, A. A., Yarembash, E. I., Kuznetsov, V. G., Vigileva, E. S., Reshchikova, A. A., and Antonova, L. I. Tellurides of lanthanum, (8) 209*g*.
El'kin, G. B. See Ginzburg, D. B.
Elkins, G. H. J. See Coleman, E. H.
Ellinger, F. H. See Holley, C. E., Jr.
Ellington, K. L. See Drake, C. F.
Elliot, A. G. See Lavendel, H. W.
Elliott, K. L. Tensioning of sieves, screens, etc., P (11) 289*b*.
Elliott, R. J., Hayes, W., Jones, G. D., Macdonald, H. F., and Sennett, C. T. Localized vibrations of H^- and D^- ions in the alkaline earth fluorides, (8) 201*d*.
Ellis, D. A. See Long, R. S.
Ellis, J. L., and Tarkan, S. E. Carbides with machinability, (2) 33*g*. Method for bonding a sintered refractory carbide body to a metalliferous surface, P (1) 7*i*.
Ellis, W. C. See Treuting, R. G.
Ellis, W. L., and Ruck, G. E. Automatic lehr unloader, P (7) 149*i*.
Ellsiepen, E., and Wuhrer, J. Manufacture of tar impregnated refractories, P (10) 259*d*.
Elman, I. B. Copper alloy for glass molds, (2) 36*h*.
Elmat Corp. Crystal growing apparatus, P (11) 285*b*. Crystal growth sampler, P (11) 285*c*.
Elmer, J. T., and Altmann, B. G. Refractory products and method, P (10) 260*h*.
Elmer, T. H. See Mochel, E. L.
Elmer, T. H., and Nordberg, M. E. Effect of nitriding on electrolysis and devitrification of high-silica glasses, (7) 148*f*.
El'-Rafii, E. A. See Budnikov, P. P.
El-Shahat, R. M., and White, J. Phase-equilibrium relations in spinel-silicate systems (II) pseudosystems $MgAl_2O_4$-$MgCr_2O_4$-$CaMgSiO_4$, $MgFe_2O_4$ - $MgCr_2O_4$ - $CaMgSiO_4$, $MgAl_2O_4$-$MgFe_2O_4$-$CaMgSiO_4$, and $MgAl_2O_4$-$MgFe_2O_4$-$MgCr_2O_4$-$CaMgSiO_4$, (1) 25*i*; (III) ternary

system $MgAl_2O_4$-$MgFe_2O_4$-Ca_2SiO_4 and the quaternary system $MgAl_2O_4$-$MgFe_2O_4$-$MgCr_2O_4$-Ca_2SiO_4; (IV) pseudoternary system $MgAl_2O_4$-$MgCr_2O_4$-$Ca_2MgSi_2O_8$, (4) 109*c*.

El-Shamy, T. M. M. See Douglas, R. W.

Elston, J. Crystal structure of oxides and their neutron irradiation behavior at 80°C, (1) 17*i*.

Eltro G.m.b.H. & Co. Ges. fuer Strahlungstechnik. Manufacture of an infrared reflective pigment, P (8) 190*g*.

Elyard, C. H. Ceramic thermochemistry: Discussion—interaction of sodium with glass, (8) 192*g*.

Emblem, H. G., and Fothergill, E. W. Method of making shell molds, P (3) 72*a*.

Emblem, H. G., and Oxley, C. E. Refractory binder comprising organic silicates, P (10) 260*d*.

Emblem, H. G., and Trow, S. A. Production of refractory objects, P (8) 182*d*.

Emeis, R. Electronic semiconductor device, P (1) 10*b*. Encapsuled [monocrystalline] semiconductor device with lapped surface connector, P (1) 10*c*. Encapsuled semiconductor with alloy-bonded carrier plates and pressure maintained connectors, P (1) 10*d*. Semiconductor device with pressure maintained nonbonded connectors, P (1) 11*f*. Semiconductor devices with terminal contacts and their production, P (3) 79*e*.

Emeis, R., and Hoffmann, A. Semiconductor *pn* junction devices and their manufacture, P (4) 102*f*.

Emele, O. Filter press with means for automatic detachment of the filter cakes, P (3) 80*b*.

Emerson, S. A., and Beasley, G. A. Method of making molds for multifocal ophthalmic lenses, P (4) 93*c*.

Emerson Electric Co. Temperature measurement by sublimation of layers of radioactive material, P (10) 268*c*.

Emery, E. See Murthy, M. K.

Emhart Corp. Apparatus for moving glass containers onto a moving conveyor, P (8) 176*h*. Glassware annealing method, P (8) 177*f*. Mold holder for glassware forming machine, P (1) 6*f*.

Emidy, T. J., and Northrop, D. P. Method and apparatus for manufacturing fluorescent lamps, P (3) 68*f*.

Emma, L. C. See Tuthill, E. J.

Emslie, R. S., Gulledge, H. C., Lewis, G. L., and Willcox, O. B. Process for producing fibrous alkali metal titanates, P (9) 232*c*.

Endow, N., and Pasternak, R. A. Physisorption of xenon and krypton on glass and on molybdenum films, (2) 36*j*.

Engbert, W. Method of forming a transistor by diffusing recombination centers and device produced thereby, P (8) 185*d*.

Engebretson, G. R., and Mooi, J. Hydrocarbon conversion process and catalytic contact material therefor, P (8) 190*f*.

Engel, E. G., Rowland, B. W., and Torok, A. Selective separation of heterogeneous particles, P (4) 107*b*.

Engel, G. T. See Town, J. W.

Engel, K. See Send, A.

Engel, M. J. See Metzger, J. W.

Engel, W. H., III. See Karpenko, I.

Engel, W. T., and Heflich, H. G. Machine for cutting glass tubes, P (9) 220*c*.

Engelhard Hanovia, Inc. Apparatus for grinding, P (3) 67*c*.

Engelhard Industries, Inc. Noble metal thermocouple having base metal compensating leads, P (9) 234*f*, P (10) 268*a*. Thermocouple with platinum group metal inner sheath, P (10) 268*d*. Thermocouple having tungsten-rhenium alloy leg wires, P (4) 105*a*.

Engelke, J. L. See Davis, R. S.

Engelthaler, K. See Engelthaler, Z.

Engelthaler, Z., and Engelthaler, K. Principles of the manufacture of lightweight refractories by the foam process, (7) 152*c*.

Englander, R. A., and McVeigh, G. S. Apparatus for transporting cylindrical articles, P (1) 12*j*.

Engler, P. E. See Berger, J. E.

English, P. E. Measurements in combustion systems, (11) 290*d*.

English Clays Lovering Pochin & Co., Ltd. Filter presses, P (1) 12*e*. Process for whitening clays, P (3) 83*d*.

English Electric Co., Ltd. Ceramic panels and components, P (2) 46*c*. Devitrified glass-ceramics and their production, P (7) 149*b*. Method of making bonded metal-ceramic elements, P (9) 217*a*.

English Electric Valve Co., Ltd. Method and apparatus for manufacturing thin glass films, P (3) 68*h*.

Engstrom, I. Crystal structure of Rh_2Si_3, (8) 193*c*.

Enlows, H. E., and Oles, K. F. Authigenic silicates in marine Spencer formation at Corvallis, Oregon, (7) 162*a*.

Entin, Z. B. See Budnikov, P. P.

Epik, A. P. See Samsonov, G. V.

Eppler, R. A. Viscosity of molten B_2O_3, (1) 4*j*. See Araujo, R. J.

Eppler, R. A., and McLeran, W. A., Jr. Kinetics of opacification of a TiO_2-opacified cover coat enamel, (4) 92*a*.

Epstein, D. W. See Ramberg, E. G.

Epstein, G. Filament winding puts strength where needed, (4) 93*i*.

Epstein, G., Hribar, V. F., and Smallen, H. Where nonmetallic composites are used, (9) 225*h*.

Erben, J. Konrad Quillmann—Ceramics 1966 Exhibition in Jahrhunderthalle, Frankfurt, (3) 63*i*.

Erbsloh & Co. Geisenheimer Kaolinwerke. Method of treating clay and clay produced thereby, P (7) 161*c*.

Erdey, L. See Paulik, F.

Erdmann, J. C., and Jahoda, J. A. Inert thermometer, (1) 13*h*.

Eremeeva, A. S. See Tarasov, V. V.

Eremeeva, A. S., and Bartenev, G. M. High-elastic properties of organic and inorganic glasses in relation to their structure, B (7) 171*h*.

Eremenko, V. N. Surface and contact phenomena in metallic systems and their technological applications. (10) 250*h*. See Lukashenko, G. M.; Naidich, Yu. V.

Eremenko, V. N., and Lukashenko, G. M. Thermodynamic properties of magnesium antimonide, (11) 302*g*.

Eremenko, V. N., Naidich, Yu. V., and Lavrinenko, I. A. Study of consolidation processes in sintering in the presence of a liquid phase, (4) 110*f*.

Eremenko, V. N., Nizhenko, V. I., and Sklyarenko, L. I. Wetting of aluminum oxide by chromium oxide by chromium-nickel melts, (10) 259*b*.

Eremenko, V. N., and Tolmacheva, Z. I. 1200°C isothermal section of the phase diagram of the quasi-ternary system TiC-Ni-Cr, (8) 210*i*.

Eremenko, V. N., and Velikanova, T. Ya. Type of crystallization and composition of the higher molybdenum carbide, (8) 211*c*.

Erickson, H., and Disegna, W. L. Method for the manufacture of catalytically active clay, P (11) 282*d*.

Erie Resistor, Ltd. Barium titanate dielectrics, P (9) 230*g*.

Erie Mfg. Co. Magnetic separator for mixtures of magnetic and nonmagnetic material, P (3) 80*c*.

Erlank, A. J. See Gurney, J. J.

Erlenstaedt, G., and Doerner, H. Screen with spring supported vibratory drive, P (10) 266*h*.

Erman, L. Ya., Gal'perin, E. L., Kolchin, I. K., Dobrzhanskii, G. F., and Chernyshev, K. S. System Bi_2O_3-MoO_3, (11) 301*e*.

Ermolaeva, E. V., and Skorobogatova, I. V. Infrared transmission spectra of aluminosilicate melts quenched to the glassy state, B (9) 245*f*.

Ermolenko, N. N. Network formers and modifiers, B (7) 171*g*.

Ernsberger, F. M. Strength and strengthening of glass (I, II), (2) 37*j*. See Chisholm, R. S.; Hess, A. R.

Ernst Leitz G.m.b.H. Glass, P (3) 67*f*. Optical glasses, P (3) 69*h*.

Ervin, G., Jr., and Smalley, A. K. Control of stoichiometry in the growth of crystals of uranium monocarbide, (8) 192*h*.

Erwin, E. G. Baths, P (1) 12*j*.

Erwin, L. R., McCallum, D. W., and Gieser, R. H. Method of applying a protective coating to a metallic structure, P (8) 174*h*.

Erznkyan, E. A. See Kostanyan, K. A.

Esaki, L. Cryogenic Hall-effect semimetal electronic element, P (5) 127*f*. Semimetal *pn* junction devices, P (5) 129*f*. See Chang, L. L.

Eschen, F. W. Friction composition for high energy service, P (4) 98*f*.

Esch-Werke KG. Gyroscopic crusher [portable] of shallow height, P (11) 291*g*.

Es'kov, A. S. See Belyaev, G. I.

Espevik, S. See Kofstad, P.

Espinosa, G. P. See Geller, S.

Espinosa, G. P., and Geller, S. Ferrimagnetic garnet compositions, P (3) 78*h*.

Esso Production Research Co. Electrode system having a potential electrode embedded within a current electrode for measuring the electrical resistivity of a porous rock sample, P (4) 104*i*. Process of infiltrating diamond particles with metallic binders, P (3) 63*f*. Tungsten carbide compositions, method, and cutting tool, P (4) 89*g*.

Esso Research & Engineering Co. Agglomeration of crystalline aluminosilicate zeolites, P (9) 235*g*. Emulsifiable glass mold lubricants, P (9) 219*h*. Fuel cell electrode, P (2) 44*a*. Molded carbon bodies, P (2) 44*e*. Synthetic crystalline aluminoborosilicate zeolites and preparation thereof, P (9) 236*i*. Synthetic crystalline zeolite compositions and preparation thereof, P (9) 236*i*. Synthetic zeolites, P (10) 270*a*.

Esterowitz, L., and Noonan, J. Two-step excitation in erbium-doped cadmium fluoride, (2) 59*h*.

Estes, J. F. See Smith, L. W.

Estes, J. F., and Bruchmann, H. Porous ceramic bodies and composite members and methods of making, P (2) 46*f*.

Estes, N. N. See Hackerman, N.

Estes, N. N., and Kemp, G. T. Electrochemical linear detector and porous electrode therefor, P (3) 78*c*. Electrodes for electrochemical logarithmic detector units, P (4) 101*c*.

Estrada, D. A. See Alvarez-Estrada, D.

Estrada, E. See Meggers, B. J.

Esveldt, C. J. See Driel, G. A. H. van.

Esvelt, H. See Santen, J. G. van.

Etablissements Merlin & Gerin Soc. Anon. Process and apparatus for machining hollow insulators, P (11) 284*b*. Process and apparatus for rough shaping a soft-paste blank for the production of ceramic objects, P (11) 284*b*.

Etemad, G. A. Oxidation and mechanical performance of tungsten at high temperatures and high pressures, (1) 2*g*.

Ettmayer, P. See Kieffer, R.

Ettre, K. S. See Doolittle, H. D.

Eubank, W. R. Solid state switching device, P (7) 158*a*.

Eubank, W. R., and Cross, D. L. Solid state switching device, P (7) 158*a*.

Eubank, W. R., and Walker, G. A. Solid state switching device, P (7) 158*d*.

Eugeler, W. E. See Garfinkel, M.

Eugster, H. P., and Smith, G. I. Mineral equilibria in the Searles Lake evaporites, California (1) 23*e*.

Euratom. See European Atomic Energy Community.

European Atomic Energy Community—Euratom. Furnace for the manufacture of fissile and/or fertile nuclear fuel carbides, P (4) 98*h*. Process for the preparation of nuclear fuel carbides. P (10) 260*h*. Process for the production of monocrystals of uranium carbide, P (10) 260*b*.

Eutectic Welding Alloys Corp. Alloy powder for flame spraying, P (11) 276*d*. Flux-coated carbide welding rod, P (10) 250*c*. Method for producing carbide containing materials, P (5) 115*f*.

Evans, A. G. See Pratt, P. L.

Evans, A. W., Arkless, K., and Peacock, J. Fluidized bed process for producing pigmentary titanium dioxide with reduced accretion therein, P (10) 269*f*.

Evans, A. W., Callow, A. E., and Peacock, J. Fluid bed process for producing rutile pigment and reducing pigment accretion, P (2) 54*b*.

Evans, C. See Meggers, B. J.

Evans, D. L. Crystallization of carnegieite in a CdO-TiO_2 nucleated glass, B (2) 61*f*.

Evans, E. B. Scaling of yttrium in air, (1) 28*j*.

Evans, E. H. See Swanson, H. E.

Evans, G. S. High-ouput fluorescent lamp with improved phosphor-coated glass structure that defines a recombination surface and enhances lumen maintenance, P (11) 285*g*.

Evans, H. T., Jr. Note on anomalous dispersion and Evans's X-ray study of tetragonal barium titanate, (7) 166*c*.

Evans, M. H. Method of grinding and cooling cement, P (11) 275*e*.

Evans, P. E. Activation energy for grain growth in alumina, B (2) 61*g*. See Davies, T. J.

Evans, R. J. See Revesz, A. G.

Everett, L. H. See Dancy, E. A.

Every, R. L. Preparation of transition metal oxide-metal electrodes, (10) 263*c*.

Evitts, H. C., Cooper, H. W., and Flaschen, S. S. Rates of formation of thermal oxides of silicon, (3) 76*a*.

Evstrop'ev, K. K., Kondrat'eva, B. S., and Petrovskii, G. T. Nature of conductivity of beryllium fluoride glasses, (4) 93*j*.

Evstrop'ev, K. K., and Pavlovskii, V. K. Microstructure of one-alkali and two-alkali germanate glasses, B (9) 245*j*.

Evstrop'ev, K. K., Pavlovskii, V. K., and Ivanov, A. O. Diffusion of sodium ions in sodium germanate glasses, B (4) 113*e*.

Evstrop'ev, K. S. History of research on the electrical properties of glasses, B (4) 113*a*. Summary of the Symposium on the Electrical Properties and Structure of Glass, B (9) 245*i*. See Ivanov, A. O.

Evstrop'ev, K. S., and Yakhkind, A. K. Optical glass, P (3) 69*f*.

Ewing, C. T. See Walker, B. E.

Ewing, R. E., and Greene, P. E. Influence of vapor composition on the growth rate and morphology of gallium arsenide epitaxial films, (7) 155*h*.

Ewing, W. H. Method and apparatus for producing strand package, P (2) 39*e*.

Exsteen, G. See Drowart, J.; Verhaegen, G.

Exton Development Co. Process for ornamenting glass articles, P (10) 256*d*.

Eyraud, C. Kinetics and mechanism of solid-state reactions, (8) 201*i*. See Cubaud, J. C.

Eyring, H. See Gabrysh, A. F.

Faber, W. M., Sr., Francis, G. L., Holmes, C. L., and Boykin, O. F. Electrical resistance element, P (5) 127*h*.

Fabriques Reunies de Lampes Electriques (Soc. Anon.). Method of filling electric incandescent lamps, discharge tubes, etc., with gas and sealing them, P (7) 150*a*.

Facincani, E. See Poggi, L. A.

Fadeev, V. N. See Fedorov, P. I.

Fadeev, V. N., and Fedorov, P. I. System TlCl-$TlCl_3$, (11) 301*i*. Vapor pressure in the system In-$InCl_3$, (4) 112*b*.

Faessle, F. See Rueter, H.

Fahey, J. R. Metallized semiconductor support and mounting structure, P (3) 78*d*. Transistor housing containing packed, earthy, nonmetallic, electrically insulating material, P (1) 12*c*.

Fahn, R. Intracrystalline swelling and dye absorption of acid treated montmorillonite, (3) 86*i*. See Hofstadt, C. E.

Faile, S. P., and Roy, D. M. Solubilities of Ar, N_2, CO_2, and He in glasses at pressures to 10 kbars, (1) 4*d*.

Faile, S. P., Schmidt, J. J., and Roy, D. M. Irradiation effects in glasses—suppression by synthesis under high-pressure hydrogen, (9) 218*f*.

Faille, M. della, Kimpe, C. de, and Fripiat, J. J. Effect of dehydroxylation on the morphology and texture of chrysotiles, (11) 293*j*.
Fainberg, E. A. See Zertsalova, I. N.
Fainberg, E. A., and Grechanik, L. A. Electrical properties of high-lead glasses reduced in hydrogen, B (4) 113*g*.
Fairbanks, D. F. Hard superconductor clad with metal coating, P (7) 156*f*.
Fairchild Camera & Instrument Corp. Circuit element totally encapsulated in glass, P (9) 230*j*. Epitaxially growing layers of semiconductor through openings in oxide mask, P (4) 101*e*. Field-effect transistors, P (10) 264*a*. High frequency transistors, P (1) 10*j*. Method of making isolated epitaxial field-effect device, P (3) 78*i*. Method of making solid-state circuitry, P (8) 185*h*. Surface gradient protected high breakdown junctions, P (11) 287*j*. Surface-passivated alloy semiconductor devices and method for producing them, P (11) 287*j*.
Fairfield, J. M. See Sprokel, G. J.
Falkenthal, A., and Presser, H. Method of preparing photosensitive resistive coatings, P (9) 217*c*.
Falkenthal und Presser Kom.-Ges. Method of preparing photosensitive resistive coatings, P (9) 217*c*.
Fan, G. J. See Greiner, J. H.
Fanderlik, I. Study of changes in the spectral characteristics of Rosal type sunglasses in the transformation interval, (10) 253*a*.
Fanderlik, M. Dependence of the elasticity modulus of glasses in the system Na_2O-B_2O_3 on their composition, B (7) 171*c*. Dependence of the elastic modulus on the structure of alkali borate glasses, (3) 66*a*.
Fang, F. See Silvestri, V. J.
Fang, J. H., and Bloss, F. D. X-Ray Diffraction Tables, B (2) 62*e*.
Fanning, E. F. See Boettner, G. B.
Fannon, J. J., Jr. Heating apparatus and method, P (7) 160*a*.
Farbenfabriken Bayer Akt.-Ges. Building material compositions for the manufacture of water-repellent products, P (8) 174*a*. Calcined pigments from kaolin, P (7) 160*j*. Crystalline solid solutions with silicon dioxide structures as host compounds, P (1) 10*j*. Iron oxide pigments containing manganese, P (1) 15*h*. Molecular sieve formed bodies hardened with a binding agent, P (3) 83*f*. Production of alkali metal borohydrides, P (2) 54*b*. Production of barium carbonate from barium sulfate, P (5) 133*e*. Production of bonded molecular sieve pellets, P (3) 83*b*. Production of calcium silicate fillers, P (5) 133*e*. Production of finely dispersed calcium carbonate, P (2) 54*c*, P (9) 236*i*. Production of finely dispersed calcium silicate fillers, P (8) 190*f*. Production of glass fiber-strengthened thermoplastic synthetic resins, P (8) 178*i*. Production of molecular sieve granules, P (3) 83*c*. Production of silica-bonded bead granules from solids in powder form, P (8) 187*a*. Production of silica bonded zeolitic molecular sieve granules, P (4) 107*a*. Viscometer, P (2) 52*b*.
Farber, M. See Blauer, J.; Greenbaum, M. A.; Yates, R. E.
Farbwerke Hoechst Akt.-Ges. Process for the application of finely crystalline phosphate layers on metal surfaces, P (10) 250*e*.
Faria, S. Photoconductivity excitation spectra of (Cd,Zn)S:Ag,Cu,Cl and (Cd,Zn)(S,Se):Ag, Cu,Cl, (1) 26*e*.
Farkas, R. F. Coating perforate articles, P (2) 38*a*.
Farkass, I. Problems of producing a clean surface by outgassing in ultrahigh vacuum, B (8) 212*i*.
Farrell, J. B., and Haas, P. A. Oxidation of nuclear-grade graphite by nitric acid and oxygen, (10) 258*e*.
Farrow, T. J. Conductive mold rack for electrocleaning mold parts, P (4) 94*b*. Method and apparatus for electroforming split glassware molds, P (2) 39*d*.
Faruqi, F. A., Okuda, S., and Williamson, W. O. Effect of introducing air bubbles on the rheology of aqueous kaolin suspensions, (7) 154*i*.
Fataliev, S. A. Specific features of mineral formation during firing of charges with limestone of different structures, (10) 248*g*.
Faucher, J. A., and Koleske, J. V. Glass transitions of organic compounds (I) lower aliphatic alcohols, (5) 119*b*.
Faulhaber, G. See Vescia, M.
Faulstich, M. See Deeg, E. W.
Faust, J. W., Jr. See John, H. F.
Fawcett, J. D. Aspects concerning American brick and pipe machines, (11) 279*j*.
Fawcett, J. J., and Yoder, H. S., Jr. Phase relations of chlorites in the system MgO-Al_2O_3-SiO_2-H_2O, (1) 26*b*.
Fawcett, W. E. Applying carbide coatings by adhesive bonding, (9) 216*b*.
Fay, M. J. See Mueller, W. M.
Feder, H. M. See Rudzitis, E.; Settle, J. L.
Federer, J. I. See Lundy, T. S.
Fedorko, A. S. See Keloglu, Yu. P.
Fedorov, A. E. See Nekrasov, K. D.
Fedorov, A. P. See Danilkin, V. I.
Fedorov, N. F. See Toropov, N. A.
Fedorov, P. I. See Fadeev, V. N.; Mokhosoev, M. V.
Fedorov, P. I., and Chzhan, Tszu-lyan. Interaction between indium chloride and sodium chloride, (4) 108*h*.
Fedorov, P. I., and Fadeev, V. N. Fusibility diagram of the system In-$InCl_3$, (4) 108*a*.
Fedorov, P. I., and Il'ina, N. I. Interaction of the chlorides of indium, potassium, copper(I), silver, and thallium(I), (8) 200*j*.
Fedorov, T. F. See Gladyshevskii, E. I.; Kuz'ma, Yu. B.
Fedorov, T. F., and Gladyshevskiĭ, E. I. Phase equilibria in ternary systems of transition metals of groups IV and V and carbon, (8) 205*a*.
Fedorov, T. F., and Kuz'ma, Yu. B. Phase equilibria in the system zirconium-chromium-carbon, (10) 271*h*.
Fedorov, T. F., Kuz'ma, Yu. B., and Gorshkova, L. V. Phase equilibria in the ternary system zirconium-molybdenum-carbon, (10) 271*i*.
Fedorovskii, Ya. A. Role of catalysts in volume crystallization of glass, B (9) 246*c*.
Fedoseev, A. D. See Sipovskii, D. P.
Fedoseev, D. V. See Galin, L. A.; Ryabov, V. A.
Fedows-Fedotowsky, L. Process of coating a silicon semiconductor with indium using an ion beam, P (3) 79*a*.
Fehr, G. K. See Martin, D. M.
Feigelson, R. S. Crystal growth of rare-earth orthoarsenates, (9) 237*f*.
Feild, A. L., Jr. See Gulbransen, E. A.
Feingold, E. See Sutton, W. H.
Feinstein, L., and Weiss, M. E. Double-ended tube, P (5) 127*g*.
Feiser, C. F., Jr. Chain for rotary kilns, P (1) 14*j*.
Feitknecht, W. Influence of particle size on the mechanism of solid-state reactions, (8) 200*d*.
Felder, J. L. Method of producing vitreous clay products, P (7) 158*g*.
Fel'dgandler, G. G. Use of refractory concretes and ramming mixes in the iron and steel industry, (7) 152*h*.
Feldman, F. J., Bosshart, R. E., and Christian, G. D. Sensitivity of manganese determination by atomic absorption spectrometry using four solvents, (10) 267*h*.
Feldman, R. Temperature measurement by sublimation of layers of radioactive material, P (10) 268*c*.
Feldman, R. F. See Ramachandran, V. S.
Feldman, R. F., and Ramachandran, V. S. Influence of $CaSO_4 \cdot 2H_2O$ on the hydration character of $3CaO \cdot Al_2O_3$, (11) 275*a*.
Feldmann, K., Harnisch, H., Kandler, J., and Gerhardt, W. Process for the manufacture of rounded powdered magnetite particles, P (7) 161*e*.
Felici, N. J., and Tholome, R. Spray-coating apparatus, P (1) 13*b*.
Felker, D. E., and Fowler, G. S. Method and apparatus for assembling wires in a plurality of apertured parts, P (1) 5*b*.
Felker Mfg. Co. Method for making abrasive segments for saws, P (4) 89*k*.
Fellner & Ziegler G.m.b.H. Preheaters for revolving tubular kilns, P (2) 53*e*. Rotary tube furnace for calcining or burning cement, magnesia, limestone, etc., P (10) 269*a*.
Felmada, S. A. Process of the manufacture of an abrasive substance and the substance obtained, P (2) 33*j*.
Felten, E. J. Composition dependent order-disorder phenomena in $CoNb_{2-x}Ta_xO_6$ and $NiNb_{2-x}Ta_xO_6$, (9) 237*b*.
Felty, E. J., and Myers, M. B. Thermal expansion of arsenic-selenium glasses, (7) 149*d*.
Fenner, E., and Ferckel, S. Flame spraying of powdered ceramic materials, (3) 65*d*.
Fentzke, A. D. See Norton, C. L., Jr.
Feofilov, P. P. See Karapetyan, G. O.
Feraday, M. A. Nuclear fuel elements, P (10) 260*a*.
Ferckel, S. See Fenner, E.
Ferer, H. D., and Stirling, H. T. Upgraded siliceous composition, P (11) 279*g*.
Fergason, L. A. Method for trace analysis with an electron microprobe, B (5) 139*g*
Ferguson, J., and Wood, D. L. Optical modulator employing the dichroic absorption of antiferromagnetic NiF_2, P (8) 188*d*.
Ferguson, K. A. Can we simplify wheel markings? (11) 273*f*.
Fern, R. See Peart, R. F.
Fernandez Veiguela, D. See Garcia Ramos, G.
Feron, J. L. See Bloch, D.
Ferrandis, V. A. See Aleixandre Ferrandis, V.
Ferranti, Ltd. Coating of semiconductor bodies with silicon dioxide, P (8) 184*f*. Phosphor fiber faceplate for cathode-ray tubes, P (7) 157*c*.
Ferrar, C. M. See DeMaria, A. J.
Ferretti, A. See Rogers, D. B.
Ferrigno, T. H. Clay coated with haloalkyl phosphorus ester and polyester resins containing the same, P (3) 83*b*. Colloidal clay coated with acrylic acid-polyallyl sucrose copolymer, P (7) 160*b*. Kaolin clay coated with neutralized monomeric *N,N*-diallylmelamine and polyester resins containing the same, P (4) 106*c*.
Ferris, E. A. Method for assembly of semiconductor devices, P (2) 48*d*.
Ferro Corp. Apparatus for distributing and screening particulate material, P (1) 12*g*. Apparatus for reducing particle concentration in volume of liquid, P (7) 158*k*. Apparatus for trimming ceramics, P (10) 266*f*. Coating metal with a clayless suspension of ceramic slips, P (4) 92*e*. Refractory body and method of making same, P (10) 260*e*. Vitreous enamels for hot water tanks, P (2) 35*h*.
Ferrotec, Inc. Reciprocal stripline ferrite phase shifter having a folded center conductor, P (2) 49*d*.
Ferry, D. K., and Dougal, A. A. Microwave emission from bulk *n*-type indium arsenide, (3) 76*d*.
Fesenko, V. V. See Gordienko, S. P.
Fessler, T. E., Smith, A. B., and Vincent, J. S. Method of forming thin window [lithium] drifted silicon charged particle detector, P (7) 157*d*.
FETOK G.m.b.H. Improvement of tunnel kilns, P (2) 53*a*. Process for producing thin sheets of plastic ceramic materials, P (5) 130*e*. Tunnel kiln, P (10) 269*a*. Tunnel kiln car, P (2) 53*d*.
Feuerstanger, A. E., Hagenlocher, A. K., and Solomon, A. L. Preparation and properties of thin barium titanate films, (4) 100*b*.
Fezenko, I. See Laurent, B.
Fialkov, A. S., Davidovich, J. G., and Pakhomov, L. G. Method for heat treatment of graphite articles, P (1) 7*j*.
Fiber Glass Industries, Inc. Glass fabric with particulate material and pile yarns penetrating the same, P (8) 177*d*.
Fibers Unlimited, Inc. Coaxial disk and cylindrical rotor refining apparatus, P (9) 219*c*.
Fibreglass, Ltd. Apertured body for the passage of molten glass, P (7) 149*f*. Products made of mineral fibers, P (8) 178*i*.
Fickes, R. E. Glass sheet tempering apparatus, P (3) 67*j*.
Fiedler, A. See Naeser, G.
Fiegel, L. J. See Mohanty, G. P.
Field, A. Abrasive disk unit, P (5) 115*g*.
Field, P. E. See Seward, R. P.
Field Emission Corp. X-ray tube having field emission cathode and evaporative anode in combination with electrical pulser means, P (7) 158*c*.
Fighera, C. Manufacture of facing tiles or bricks for building, P (10) 256*f*.
Filby, J. D., and Nielsen, S. Low-temperature epitaxy of silicon by sublimation onto thin alloy layers, (10) 262*f*.
Filipovich, V. N. Characteristics of crystallization of glass during formation of glass-ceramics, B (5) 141*g*. Relation between melt, glass, and glass-ceramic structures, B (5) 141*g*. Relations among the structures of melts and glasses and their crystallization product, B (7) 171*f*. Some aspects of the formation of new phases in melts and glasses, B (5) 141*h*. See Kalinina, A. M.
Filipovich, V. N., and Kalinina, A. M. Critical amorphization radius of crystals, B (5) 141*g*.
Filsinger, E. J. Edge trim element for ceramic wall construction, P (7) 155*c*.
Finch, C. B., and Clark, G. W. Single-crystal growth of cerium dioxide from lithium ditungstate solvent, (4) 109*d*.
Finch, W. F., and Mehal, E. W. Preparation of $GaAs_xP_{1-x}$ by vapor phase reaction, (3) 87*f*.
Fine, M. E. See Hsu, S. E.; Koch, F. B.
Finger, L. W. See Blake, R. L.
Finicle, R. L. Radioactive spheroids coated with pyrolytic graphite, P (5) 125*e*.
Finlayson, K. M., and Williams, J. P. Beta spodumene silica solid solution in an Li_2O-Al_2O_3-TiO_2-SiO_2 glass-ceramic, (10) 270*e*.
Finn, A. E. Basic oxygen steelmaking vessels, P (4) 98*b*. Nozzle construction with thermally expanding refractory insert, P (11) 282*j*. Prefabricated taphole assembly for metallurgical furnaces, P (10) 260*d*.
Finnie, L. N. Structures and compositions of the silicides of ruthenium, osmium, rhodium, and iridium, (5) 138*a*.
Firer, M. Ya. See Zalizniyak, D. V.
Firkins, G. & A., Ltd. Means for transporting and handling finely divided material, P (3) 80*d*.
Firma Hermann Recknagel. Device for transferring fresh clay moldings coming from a cutter to a support in a brick plant, P (11) 280*c*.
Firnhaber, M. S. Apparatus for manufacturing glass fibers, P (10) 254*b*.
Firth Cleveland, Ltd. Drying apparatus, P (2) 52*h*.
Fischer, A. G. See DeMeis, W. M.
Fischer, D. W. See Baun, W. L.
Fischer, H. C. Chemical admixture for hydraulic cementitious mixtures, P (2) 34*j*.
Fischer, J. J. Materials feeding and blending, P (11) 288*f*.
Fischer, K., and Buck, G. Brick press, P (11) 280*b*.
Fischer, P. Isostatic pressing of stoneware pipes, (9) 222*i*.
Fischer, P., and Mueller, H. A. Measurement of the progress of densification during the drying and firing of ceramic bodies, (5) 131*g*.
Fischer, R. J. See Brown, A. E.
Fischer, R. J., and Di Vita, S. Single crystal barium titanate, P (1) 11*h*.
Fischman, J. L., and Brinsmead, K. H. Method of manufacturing a foundry core, P (8) 181*b*.
Fish, D. H., and Acciani, J. O. Immersion thermocouple assembly, P (3) 81*d*.
Fisher, B., and Tannhauser, D. S. Phase diagram of cobalt monoxide at high temperatures, (7) 166*h*.
Fisher, C. D. Apparatus for mixing particulate materials, P (11) 288*f*. Attrition mill apparatus, P (1) 15*e*, P (4) 106*i*. Mixer, P (8) 186*j*.
Fisher, F. O. See Allegretti, J. E.
Fisher, H. E., Frye, E. C., Jr., Hicks, M. K., and Schraeder, C. R. Method of junction passivation and product, P (4) 101*g*.

Fisher, J. R. See Pearson, A. D.
Fisher, J. V. See Vickery, R. C.
Fishwick, J. H. Spodumene aids fast firing, improves bodies, (9) 228*b*.
Fismer, W. L. Plate self-shifter for filter presses, P (5) 130*c*.
Fister, K. G. Field effect semiconductor device with polar polymer covered oxide coating, P (3) 78*i*.
Fiszdon, J. See Brzozowski, W. S.
Fitch, F. T. See Braun, A. B.; Flack, H. P.; Smith, J. G.
Fitch, F. T., and Braun, A. B. Preparation of microspheres of urania and other materials, P (10) 260*c*.
Fitch, F. T., Sanchez, M. G., and Vanik, M. C. Hydrous oxide sol of urania and thoria and process, P (10) 259*a*.
Fitch, F. T., and Smith, J. G. Preparation of aquasols of crystalline zirconia and/or hafnia, P (2) 45*a*. Thorium silicate hydrosols, P (3) 75*a*. Uranium dioxide-yttrium oxide-zirconium dioxide aquasol process and product, P (10) 261*a*. Uranium trioxide sol process, P (9) 227*i*.
Fitzer, E., Rubisch, O., and Selka, F. Contact layer for a silicon-containing material, P (5) 127*e*. Method for producing a contact layer on a silicon-containing material, P (1) 8*b*.
Fitzgerald, A. G., and Mannami, M. Electron diffraction from crystal defects—Fraunhofer effects from plane faults, (8) 196*i*.
Fitzgerald, A. G., Mannami, M., Pogson, E. H., and Yoffe, A. D. Structure of zinc selenide crystals and defects introduced during growth, (8) 208*a*.
Fitzgerald, J. V. Flexible ceramic tile unit, P (8) 183*a*.
Fitzgerald, L. M. Deformation of single crystals and polycrystals of high-melting materials, B (2) 61*f*.
Fitzgibbon, G. C. See Huber, E. J., Jr.
Flack, H. P. See Smith, J. G.
Flack, H. P., Smith, J. G., and Fitch, F. T. Apparatus for producing sol microspheres, P (11) 288*f*.
Flahaut, J. See Golabi, S. M.
Flanagan, T. B., and Goldstein, M. K. Radiation-induced solid state crystallization process, (8) 206*a*.
Flanagan, W. F. See Bailey, D. J.
Flanary, J. R., Goode, J. H., and Wall, G. C. Pyrohydrolysis of carbide-type nuclear fuels, P (1) 8*b*.
Flanders, P. J. Metamagnetic effects in hematite, (8) 202*c*.
Flanigen, E. M., and Taylor, A. M. Flux-melt method for growing single crystals having the structure of beryl, P (11) 281*c*.
Flaschen, S. S. See Evitts, H. C.
Flaschen, S. S., and Gnaedinger, R. J., Jr. Process of forming an inorganic glass coating on semiconductor devices, P (4) 102*i*.
Flatley, D. W., Becke, H. W., and Stolnitz, D. Group III-V compound transistor, P (9) 230*f*.
Fleck, D. C. See Kesterke, D. G.
Fleck, R. N. Process for preparing a crystalline zeolite, P (4) 107*b*.
Flemings, M. C. See Piwonka, T. S.
Flemming, H., and Kuhne, G. Machine for making short fibers from glass, P (8) 177*i*.
Fletcher, E., and Stroud, D. E. Glass distribution means for a rotary fiber-forming apparatus, P (11) 278*j*.
Fletcher, J. M., Hyde, K. R., and Roberts, F. Manufacture of refractory compounds, P (10) 259*c*.
Fletcher, K. E., Midgley, H. G., and Moore, A. E. Data on the binary system $3CaO \cdot Al_2O_3$-$Na_2O \cdot 8CaO \cdot 3Al_2O_3$ within the system CaO-Al_2O_3-Na_2O, (3) 84*d*.
Fletcher, N. H., and Adamson, P. L. Structure and energy of crystal interfaces (1) formal development, (8) 207*e*.
Flex-O-Lite Mfg. Corp. Method of and apparatus for production of glass beads by use of a rotating wheel, P (7) 149*j*.
Flexon, J. D., and Frisk, N. E. Glass furnace bottom wall construction, P (5) 120*b*.
Flinn, P. A. Applications of the Moessbauer effect to problems in materials science, B (8) 211*j*.
Flinner, V. D. See Fulton, H. A.
Flinsenberg, P. J. See Driel, G. A. H. van.
Floerke, O. W., and Lachenmayr, H. Differential thermal analysis and X-ray investigation of aluminum phosphate, (5) 135*e*.
Flood, H. W. See Bovarnick, B.
Florinskaya, V. A. Study of the structure of glass by various physical methods, B (7) 171*f*. See Cherneva, E. F.; Pozubenkov, A. F.
Flotow, H. E., and Osborne, D. W. Thermal contact with powdered samples for low temperature calorimetry, (1) 14*g*.
Flournoy, P. A. See Brixner, L. H.
Flowers, L. C., and Marschik, D. Electroluminescent lamp structure having the phosphor particles dispersed in a modified cyanoethylated polyvinyl alcohol resin, P (7) 156*b*.
Floyd, I. J. See Lewis, J. C.
Floyd, J. R., Royce, D. V., Jr., and Lippman, A., Jr. Alumina improves properties of whiteware bodies, (9) 228*a*.
Fluegel, E. Radiation pyrometer TSM 63, (3) 81*c*.
Fluid Energy Processing & Equipment Co. Method and apparatus for drying wet pulverulent material in a gaseous path, P (11) 288*h*. Method and means for pulverizing and drying solids, P (8) 190*b*.
Flur, B. L. Process for cathodically sputtering a ferromagnetic thin film of a nickel-iron-molybdenum alloy, P (5) 128*f*. See Maissel, L. I.
Flyagin, V. G. See Ignatova, T. S.
Flynn, W. W. See Pakalns, P.
FMC Corp. Clay bleaching, P (3) 83*b*. Preparation of soda ash, P (11) 291*d*. Production of a high-porosity refractory, P (7) 153*j*. Refining of ferrophos, P (5) 133*g*. Slowly soluble phosphate glasses, P (11) 279*f*. Tableware sorter, P (9) 228*h*.
Focht, R. M. Metal encased refractory brick and method of making, P (2) 44*j*. Universal brick plating machine, P (3) 73*c*.
Foex, M. Measurement of solidification temperatures of the refractory oxides, (7) 151*i*. Methods and devices for heating substances by radiant energy and plasma heat sources, P (4) 105*f*.
Foldes, S., and Levinstein, M. A. Coated columbium or tantalum base metal, P (3) 65*b*.
Folloni, M., and Giammetti, F. Pyroxene formation in magnesite-chrome refractories in glass furnace regenerator walls, (10) 258*c*.
Folsom, R. M. See Castrucci, P. P.
Fomenko, V. S. See Samsonov, G. V.
Fondymakin, B. I., and Solinov, F. G. Variation of the thermal conductivity of glass in the SiO_2-Li_2O-Al_2O_3-ZrO_2 system during crystallization, (4) 93*c*.
Foner, S. See Schieber, M.
Fontana, E. H., and Plummer, W. A. Study of viscosity-temperature relations in the GeO_2 and SiO_2 systems, (1) 29*a*.
Fontana, M. H. Process for making carbides of fissionable and fertile materials, P (2) 45*b*.
Foote Mineral Co. Ceramic product and its preparation, P (1) 9*b*. Preparation of lithium aluminum hydride, P (11) 291*b*.
Forber, W. E. Apparatus for molding glass articles, P (5) 119*i*.
Forbes, D. H. See Wilcox, W. R.
Forbes, D. W. A. Solder glass seals in semiconductor packaging, (10) 253*i*.
Forbes, R. L. See Taylor, K. M.
Forcadell, A. P. Glass tile system, P (7) 149*c*.
Forchheimer, O. L. See Paul, R. A.
Ford, M. W. Semiconductor device, P (9) 232*a*.
Ford Motor Co. Apparatus for press forming and tempering of glass, P (1) 4*e*. Optical method for the inspection of a transparent object for defects including comparing light energy at two stations, P (9) 221*i*. Process for manufacture of glass, P (10) 256*b*.
Forlano, R. J., Allen, A. W., and Beals, R. J. Elasticity and anelasticity of uranium oxides at room temperature (I) stoichiometric oxide, (3) 85*i*.
Formanek, J., and Kucera, M. Study of air currents during the drawing of glass fibers, (3) 66*h*.
Formigoni, N. P. See Joyce, B. D.
Forney, H. B., Line, L. E., Jr., and Muller, C. S. Method of making thermoelectric initiators of semiconductor material, P (7) 157*h*.
Foseco International, Ltd. Fireproof heat-insulating materials, P (10) 259*h*. Mold composition for foundry use, P (5) 124*e*. Production of casting molds, P (5) 125*c*.
Foseco Trading Akt.-Ges. Refractory and exothermic compositions, P (7) 154*e*.
Fossati, C. G. Metallizing [vacuum] apparatus, P (10) 264*g*.
Foster, F. J. See Rothberg, H. M.
Foster, H. R., Jr. See Reburn, W. T.
Foster, J. P., and Reynik, R. J. Use of vacuum-evaporated gold films to investigate the oxidation mechanism of metals, (9) 242*j*.
Foster, K. J., and McFarlane, L. Improved ventilation and methods efficiency in the McIntyre assay department, (4) 112*h*.
Foster, L. H., and Gray, J. H. Method of forming a moisture-collecting coating of porous glass, P (1) 5*j*.
Foster, N. F., and Rozgonyi, G. A. Zinc oxide film transducers, (3) 77*g*.
Foster, R. S. See Becker, C. W.
Foster, W. R. See Beard, W. C.
Foster Wheeler, Ltd. Furnaces, P (2) 52*i*.
Fostoria-Fannon, Inc. Heating apparatus and method, P (7) 160*a*.
Fothergill, E. W. See Emblem, H. G.
Fouladi, J. See Fuerstenau, D. W.
Fousek, J., and Safrankova, M. Equilibrium domain structure of $BaTiO_3$, (11) 295*g*.
Fousek, J., Safrankova, M., and Kaczer, J. New dew method for revealing ferroelectric domains, (8) 203*i*.
Fowkes, F. M. Relation of the attractive forces at interfaces to wetting, spreading, adsorption, and long-range attractive forces, B (8) 212*a*.
Fowler, A. B. Coupled semiconductor injection laser devices, P (5) 127*f*.
Fowler, G. S. See Felker, D. E.
Fowler, H. See Rathgeber, R. F.
Fowler, H. L. Filter plate separator, P (4) 103*f*.
Fowler, P. H. Piezoelectric ceramic transformer, P (4) 102*g*.
Fox, G. F. Mixers, P (11) 289*a*.
Fox, R. J., and Borkowski, C. J. Surface-barrier diode for detecting high energy particles and method for preparing same, P (8) 186*a*.
Fox, T. U. See Lyon, J. E.
Foxon, C. T. B., and Rider, J. G. Systematic errors in dislocation densities measured by thin film electron microscopy, (8) 209*f*.
Fradeneck, R. J. Automatic expendable thermocouple lance, P (9) 234*c*.
Francesconi, A. See Pierini, G.
Francis, G. L. See Faber, W. M., Sr.
Francois, H. See Bedier, R.
Frank, L. See Goslee, D. E.
Frank, R. I., and Simmons, J. G. Insulating gate thin film transistor having a thin insulating layer overlapping a thick insulating layer, P (8) 184*h*.
Frank, V. See Christensen, A. N.
Frank, W., and Kutsche, D. Advantages of glass as a noncatalyst in apparatus, (10) 250*j*.
Frankel, J. I. Incineration of process wastes, (1) 12*e*.
Frankel, R. B. See Schieber, M.
Frankenberger, R. Use of oxygen in clinker burning, (11) 275*c*.
Franklin, A. D., and Sparks, D. J. Electric fields produced in cubic crystals by point defects, (7) 162*j*.
Franklin, W. S. Compression ceramic-metal seal, P (5) 127*d*.
Franklin Institute of the State of Pennsylvania. Shaped fine particle ferrites and their preparation, P (1) 11*g*.
Franks, J. Solid state image converting display device, P (11) 287*h*.
Frans, R. D. Method and furnace for heat-treating minerals, P (8) 190*i*.
Franzen, E. F. Exothermic hot top insert, P (1) 7*e*.
Fraser, D. B. Electrolytic treatment of quartz, P (11) 285*h*. See Dodd, D. M.
Fraser, G. L., and Piel, T. F. Forehearth construction, P (3) 67*d*.
Fraser, H. D., and Unglert, M. C. Mercury vapor lamp seasoning and sealing method, P (3) 68*c*.
Fraser, R. P. Electrostatic spraying [gun] apparatus, P (8) 174*j*.
Fraser, R. S., and Jone, P. Y. Gypsum castings and method of producing the same, P (5) 116*g*.
Fraser, W. A. See Bloom, M. C.
Frazier, A. W. See Taylor, A. W.
Frazier, H. D. Method of forming diode with high resistance substrate, P (5) 127*j*.
Frechette, V. D. See Oel, H. J.
Frederick, R. L. See Baak, T.
Frederick, S. See Conrad, H.
Frederikse, H. P. R., Schooley, J. F., Thurber, W. R., Pfeiffer, E., and Hosler, W. R. Superconductivity in ceramic mixed titanates, (8) 183*i*.
Fredley, J. C., and Sleighter, G. E. Method of annealing sheets of glass on a decreasing temperature gas support, P (10) 255*i*. Method and apparatus for tempering glass sheets on a gas support bed, P (3) 68*a*.
Freedman, B. J. See Ballass, J. T.
Freeman, I. L., and Smith, R. G. Moisture expansion of structural ceramics (I) unrestrained expansion, (5) 122*a*.
Freeport Sulphur Co. Acid treatment of calcined kaolin, P (8) 190*b*.
Freiman, A. Alkali metal silicate coating compositions, P (10) 250*b*.
French, R. R. Dry beneficiation of gypsum, (4) 105*j*.
Frenchtown Porcelain Co. Ceramic products and process of making same, P (3) 74*i*.
Freud, P. J. High pressure as a research tool for solid-state physics, (9) 239*f*.
Freund, F. Kaolinite-metakaolinite, a model of a solid with extremely high lattice defect concentrations, (8) 201*c*. Retention of hydroxyl groups on magnesium oxide, (10) 271*j*.
Freund, F., and Gentsch, H. Liberation of hydrogen during the dehydration of single crystals of magnesium and aluminum hydroxides and kaolinite, (8) 201*a*.
Frey, A. See Meyer-Simon, E.
Freysinger, H. L. See Lykken, W. H.
Frid, S. A. See Novikov, G. I.
Fridrich, E. G. Electric lamp manufacture, P (5) 120*c*. See Jaffe, M. S.
Friedberg, A. L. See Pirogov, Y. A.
Friedemann, H. C. Bibliography on surface phenomena (selected references, 1963–1965), B (8) 212*a*.
Friedman, A. I., and Beaumont, D. H. Fluorescent lamp coating, P (7) 156*c*.
Friedrich, L. A. See Bornstein, N. S.
Friedrich Siemens Industrieofenbau G.m.b.H. Cross circulation kiln, P (2) 52*e*.
Fries, R. J., and Wahman, L. A. Effect of stoichiometry on the thermal expansion of TaC_x, (10) 271*a*.
Frieser, R. G. Donor diffusion into GaAs from group VI compounds, (11) 293*c*.
Fringhian, B. Method for producing rugous and abrasive surfaces and product thereof, P (5) 115*g*.
Fripiat, J. J. See Faille, M. della.
Fripiat, J. J., Delfosse, J. M., and Bouzain, J. Tonometer for measuring the activity of water in clay pastes, (5) 131*k*.
Frisby, H. See Levavasseur, G.
Frisch, B. Energy processes in the adsorption and desorption of water vapor on oxide and metal powders, (5) 135*j*. See Dawihl, W.
Frischat, G. H., and Oel, H. J. Diffusion of neon in a glass melt, (11) 276*g*. Transport processes in glassy and crystalline $Na_2O \cdot 2CaO \cdot 3SiO_2$, (10) 253*g*.
Frisk, N. E. See Flexon, J. D.
Frison, E. See Guyot, P.
Fritsche, E. T., and Tensmeyer, L. G. Liquidus in the alumina-rich system La_2O_3-Al_2O_3 (4) 108*c*.
Fritsche, R. Batch weigh system, (5) 129*g*.
Fritz, K. Continuous annealing furnace, P (3) 82*b*.

Froberg, M. L. See Day, F.

Fronek, R. Results of measuring the grindability of clinkers and clinker mixtures, (9) 215*i*.

Frost, J. G. Negative replication for electron microscopy study of carbonates, (10) 267*h*.

Frugoli, D. M. See Gifford, R. O.

Fruth, L. S., Jr., Orme, G. R., and Donath, F. A. Experimental compaction effects in carbonate sediments, (7) 163*d*.

Frye, E. C., Jr. See Fisher, H. E.

Fu hikami, N. Magnetic anisotropy of magnetoplumbite, $BaFe_{12}O_{19}$, (9) 240*a*.

Fuchs, D. Photoelastic investigation of the principal normal stresses and inversion temperature in compressed glass lead-through seals, (10) 253*c*.

Fuchs, E. Automatic temperature measurement and control, (5) 132*d*.

Fuchs, K. See King, A. G.

Fuchs, L. H. Djerfisherite, alkali copper-iron sulfide—a new mineral from enstatite chondrites, (1) 15*e*.

Fuchs, R. J. Slowly soluble phosphate glasses, P (11) 279*f*.

Fueki, K., and Wagner, J. B., Jr. Oxidation of nickel in the range 900° to 1400°C, (11) 299*a*.

Fuerstenau, D. W. See Kapur, P. C.; Smolik, T. J.

Fuerstenau, D. W., and Fouladi, J. Degree of mixedness and bulk density of packed particles, (10) 266*b*.

Fuerstenau, M. C., and Atak, S. Lead activation in sulfonate flotation of quartz, (4) 106*a*.

Fuerstenau, M. C., Rice, D. A., Elgiliani, D. A., Atak, S., and Bhappu, R. B. Role of iron in the flotation of some silicates, (4) 106*c*.

Fuertig, H. See Wolf, F.

Fuertig, H., and Wolf, F. Study of the properties of ion-exchanged type A molecular sieves (I) gas absorption; (II) X-ray diffraction and electron microscopy; (III) infrared spectrography, (9) 235*f*.

Fuge, R. Spectrophotometric determination of vanadium in rocks, (8) 188*f*.

Fuji Denki Kogyo Kabushiki Kaisha. Method and apparatus for making spherical granules, P (1) 12*j*.

Fuji Shashin Film Kabushiki Kaisha. Crystalline glass and methods for making, P (10) 254*j*.

Fujii, K., and Ishido, Y. Vitrification of silica gels, (8) 211*g*.

Fujikawa, K., Sukegawa, T., and Nishizawa, Jun-Ichi. Silver-lead alloy contacts containing dopants for semiconductors, P (5) 129*a*.

Fujimoto, F., and Howie, A. Diffuse scattering in electron diffraction patterns, (1) 17*j*.

Fujishiro, I. See Hukuo, N.

Fujita, R. See Masuda, M.

Fujitsu, Ltd. Method of manufacture of silicon [mesa] transistor, P (11) 286*e*.

Fukuda, Y. Electronic states in perturbed two-dimensional graphite lattice, (9) 239*a*.

Fukunaga, J. See Yoshida, N.

Fukuoka, N. See Uchida, E.

Fukuoka Tokushugarasu Kabushiki Kaisha. Manufacture of glass spherules, P (8) 177*a*.

Fukuzaki, F. Process and apparatus for manufacturing elongated glass products, P (5) 121*f*.

Fulk, W. F. See Smock, G. E.

Fullam, H. T. See Lam, H. K. H.

Fuller, H. C. Process for decomposing manganese sulfate to form manganous oxide and sulfur dioxide, P (4) 106*j*.

Fuller, M. See Smith, R. W.

Fuller, R. A., Dorsey, F. E., and Kulig, C. W. Glassware annealing method, P (8) 177*f*.

Fuller Co. Kiln system and method, P (1) 14*j*.

Fulrath, R. M. Controlled microstructure of refractory bodies, B (5) 140*c*. See Hasselman, D. P. H.

Fulton, H. A., Obrecht, C. D., and Flinner, V. D. Toilet with deformable water seal trap, P (5) 126*c*.

Funaki, K. See Shimizu, Y.

Funk, J. See Tuttle, M. A.

Funke, G. Reduction of waste and rejects in the heavy clay products industry, (3) 70*g*.

Funke, V. F. See Baskin, M. L.; Tumanov, V. I.

Furlong, L. R., and Domingues, L. P. Sintering of yttrium oxide, (1) 28*h*.

Furuichi, R., Sato, N., and Okamoto, G. Study of the dissolution property of aged ferric oxides in sulfuric acid solution, (4) 110*f*. Study of the structure change of precipitated ferric oxide during aging in water, (4) 111*b*.

Furukawa, G. T., and Saba, W. G. Heat capacity and thermodynamic properties of BeO·$3Al_2O_3$, from 15° to 390°K, (8) 199*k*.

Furukawa, M. See Miyamoto, O.

Furukawa, Y., Kajiyama, K., and Aoki, T. Copper diffused gallium arsenide *pn* junctions, (4) 100*d*.

Furumi, K. See Miyatake, K.

Furuseth, S., and Kjekshus, A. Properties of α-MnS and MnS_2, (8) 205*g*.

Fuschillo, N. See Gimpl, M. L.

Fushimi, S. See Ikeda, T.

Fushimi, S., and Ikeda, T. Phase equilibrium in the system PbO-TiO_2-ZrO_2, (4) 109*f*.

Fyler, N. F. Cathode ray tube including faceplate comprising tapered fiber optical elements mounted in an opaque mosaic, P (5) 127*c*. Method of making a glass sheet having spaced wires therein, P (5) 121*c*.

Gabor, C. D. See O'Donnell, J. M.

Gabor, T. Epitaxial growth of gallium arsenide on germanium substrates (I) relation between fault formation in gallium arsenide films and the surface of their germanium substrate; (II) deterioration of the {111} surface of germanium at 570° to 850°C; (III) deposition on high index planes and on curved surfaces, (3) 85*g*.

Gabrysh, A. F., Eyring, H., Lo, Mei-Kuo, Hardy, S., and Yates, J. Gamma-ray induced defect bleaching in pressure deformed single crystal α-Al_2O_3, (1) 19*c*.

Gabrysh, A. F., Lo, Mei-Kuo, Pan, Lin-Sen, and Eyring, H. Some mechanical and optical properties of gamma-irradiated α-Al_2O_3 spheres subjected to 30 kbars, (2) 56*f*.

Gabsyte, G. See Aleinikov, F. K.

Gadalla, A. M. M., and White, J. Equilibrium relations in the system CuO-Cu_2O-CaO, (1) 18*f*. Equilibrium relations in the system CuO-Cu_2O-ZrO_2, (1) 18*g*.

Gadiyar, H. S. See Ram, P.

Gado, P. X-ray powder diffraction study of the $WO_3 \rightleftharpoons W_{20}O_{58}$ shear transformation, (2) 60*a*.

Gado, P., Holmberg, B., and Magneli, A. Tungsten tantalum and tungsten niobium oxides of the $M_nO_{2n-2}(ReO_3)$ series, (8) 210*h*.

Gado, P., and Imre, L. $WO_{2.88}$, a new phase with shear structure in the W-O system, (2) 59*b*.

Gado, P., and Magneli, A. Shear structure of $WO_{2.88}$, a tungsten oxide, (8) 206*h*. Studies on structural defects in wolfram trioxide—influence of minor additions of tantala or niobia, (7) 168*b*.

Gaffney, L. J., and Holowaty, M. O. Investigation of the effects of burden constituents on blast furnace refractory linings, (10) 257*b*.

Gager, R. M., Atlee, Z. J., and Perry, J. T. X-ray diffraction tube, P (1) 12*a*.

Gager, W. B. See Klein, M. J.

Gagliano, L. J. and Moore, E. L. Process for the preparation of cadmium yellow pigments, P (11) 291*g*.

Gaidelis, V. See Viscakas, J.

Gaidzhurov, P. P. See Ponomarev, I. F.

Gaiger, J. Recent problems experienced on sheet iron enamels with some practical solutions, (4) 92*b*.

Gajardo, V. H. Fast fire tunnel kiln, P (8) 189*c*.

Galakhov, F. Ya. Microseparation of two-component silicate melts, B (7) 171*a*. Microseparation in two-component silicate systems, B (5) 117*i*.

Galant, E. I. Optical properties and structural elements of silicate glasses containing titanium, B (7) 171*d*. See Ivanov, A. O.

Galanulis, E. See Scholze, H.

Galasso, F. S., Basche, M., and Kuehl, D. Preparation, structure, and properties of continuous silicon carbide filaments, (8) 189*e*.

Galasso, F. S., and Darby, W. Tantalum substitution in the hexagonal tungsten bronzes, (8) 209*g*.

Galasso, F. S., Darby, W. L., Douglas, F. C., and Batt, J. A. Unidirectional solidification of the $BaFe_{12}O_{19}$-$BaFe_2O_4$ eutectic, (7) 156*e*.

Galasso, F. S., and Paton, A. Tungsten borides in boron fibers, (9) 225*f*.

Galdina, N. M. See Zaliznyak, D. V.

Galdina, N. M., Shatova, N. P., Vainshtein, A. L., and Dubova, O. A. Service of refractories for high-temperature melting of glass, (3) 71*h*.

Galdina, N. M., and Yanovskii, Yu. S. Improvement in molds for fused cast refractories, (5) 123*d*. Melting zircon-containing refractories in a three-phase arc furnace, (4) 97*f*.

Galemin, I. M., and Gorokh, A. V. Mechanism of the destruction of carbon linings in the bottom and well of a blast furnace, (9) 224*g*.

Galginaitis, S. V. Semiconductive alloy light source having improved optical transmissivity, P (4) 102*c*.

Galin, L. A., Ryabov, V. A., Fedoseev, D. V., and Cherepanov, G. P. Destruction of high-strength glass, (4) 93*b*.

Galion, Jeffrey, Mfg. Co. See Jeffrey Galion Mfg. Co.

Galkin, Yu. M. See Chukhlantsev, V. G.

Gall, R. W. Method of grinding and introducing a set-control agent into a gypsum slurry, P (8) 174*d*.

Gallagher, B. E. Multizone furnace temperature and atmosphere control, P (8) 189*c*.

Gallagher, P. K., and MacChesney, J. B. Method for preparing stabilized barium titanate and capacitor, P (3) 79*c*.

Gallagher, T. J., and Singer, J., Jr. Process for manufacturing fiber optic devices [shape transducers], P (2) 40*b*.

Gallez, P. Heater panel, P (8) 177*g*.

Galloway, G. L., and Eick, H. A. Preparation of samarium borides and their interaction with boron nitride, molybdenum, and tungsten, (8) 180*g*.

Gallwey, Sir John, & Partners, Ltd. See Sir John Gallwey & Partners, Ltd.

Gelly, H. R. Apparatus and method for manufacturing brick, P (7) 152*i*.

Gal'perin, E. L. See Erman, L. Ya.

Gal'perin, E. L., and Gurvich, A. M. Phase of variable composition in the system Zn-S, (11) 299*h*.

Galy, J. See Hagenmuller, P.

Gamard, H. Process for making objects having the appearance of faience or porcelain, P (11) 284*a*.

Gambino, R. J. Preparation of single-crystal ferrite films, (8) 183*g*. See Cuomo, J. J.

Gambs, C. G. Power plant ash for use in cement, (4) 91*c*.

Gammon, R. W. See Shapiro, S. M.

Ganci, C. J. Method of manufacturing electrical resistors, P (2) 48*a*.

Gancy, A. B. Densification of soda ash by vapor hydration, P (7) 160*i*.

Ganguli, D., and Saha, P. Macroliquation in the system Al_2O_3-SiO_2, (9) 240*j*. Preliminary investigations in the high-silica region of the system BeO-Al_2O_3-SiO_2, (4) 109*j*.

Gani, M. S. See Standage, A. E.

Ganter, K. W. See Hund, F.

Ganther, F. E. See Coburn, O. W.

Gantzel, P. K., Langer, S., Baldwin, N. L., and Kester, F. L. High-temperature modifications of thorium dicarbide, B (5) 139*h*.

Gaodu, A. N. See Kainarskii, I. S.

Gaponov, Ya. G. Automatic charging of wet-process rotary kilns, (5) 132*c*.

Garcia, A. B. Portable apparatus for the calcination of minerals, P (5) 133*c*.

Garcia, F. G. See Gonzalez Garcia, F.

Garcia, J. G. D. R. See Del Rio Garcia, J. G.

Garcia, S. G. See Gonzalez Garcia, S.

Garcia Ramos, G. See Gonzalez Garcia, F.

Garcia Ramos, G., Gonzalez Garcia, F., and Fernandez Veiguela, D. Ceramic clays of Andalucia (IV) tertiary deposits of La Campiña, Cordoba Province, (5) 132*j*.

Garcia Verduch, A. Carbides, borides, silicides, sulfides, and nitrides as refractory materials, B (2) 62*e*. Surface texture of pottery, (5) 125*k*.

Gardener, E. R., Markin, T. L., and Street, R. S. Plutonium-oxygen phase diagram, (8) 205*c*.

Gardner, A. R. Fiber bundles pipe light just where you want it, (10) 252*b*. Transparent plastics open new windows on products, (1) 4*j*.

Gardner, W. L. Fluid tight sealing of glass fiber devices, P (1) 4*j*.

Garey, M. J. See Rice, H. H.

Garfinkel, M., and Eugeler, W. E. High power semiconductor laser devices, P (5) 127*h*.

Garibotti, D. J. Alloy diffused transistor, P (11) 284*g*. See Ullery, L. R., Jr.

Garnache, R. R. See Casey, J. J.

Garnero, A. L. See MacArthur, R. A.

Garno, J. P. See Nanney, C. A.

Garrett, E. E. See Reed, E. L.

Garrett, H. J. See Ruh, R.

Garrett, J. Making a slab plaque, (4) 90*b*.

Garrison, J. W. Process of producing glass in a cupola, P (3) 69*b*.

Garstang, W. W. Filter, P (2) 47*g*.

Garton, G., and Wanklyn, B. M. Growth of complex fluoride single crystals by the flux method, (9) 239*a*. Reinvestigation of the system Na_3AlF_6-Li_3AlF_6, (9) 241*j*.

Garvie, R. C. Study of lattice dilation in finely divided MgO, (8) 208*b*.

Gasemann, N. J. Dependence of coupling factor and polarization behavior on the texture of lead titanate zirconate ceramics, (11) 284*g*.

Gaska, R. A. See Goodenough, R. D.

Gaskey, R. W. See Shaffer, P. D.

Gasparac, R. J. See Balmer, H.

Gasparetto, A. Design of a Torcello glassworks—ancient kilns and melting methods, (11) 273*j*.

Gasparik, M. See Kasperowicz, H.

Gasson, D. B. See Cockayne, B.

Gasson, E. J., and Stewart, D. G. Preparation of an antimony oxide-tin oxide catalyst composition and the product, P (7) 153*f*.

Gates, L. E., Jr., and Babun, C. J. Evaluation of refractory fabrics for flexible heat shields, (3) 71*c*.

Gates, L. E., Jr., and Lent, W. E. Refractory glass fibers, (3) 66*g*.

Gatos, H. C. Structure and electronic configuration of crystalline surfaces, B (8) 212*h*. See Killias, H. R.

Gatti, A., and Untiedt, J. H. Process for producing alumina whiskers, P (10) 260*j*.

Gauglitz, R. See Ackermann, C.

Gauk, W. See Brzozowski, W. S.

Gault, J. M. Field effect transistor with concentric interior electrode, P (3) 78*j*.

Gauss, L. H., Jr. See Bell, A. N.

Gauterin, G. See Pugh, H.

Gavaler, J. R. See Chu, T. L.

Gavryuchenkov, F. G. See Novikov, G. I.

Gayle, J. B. Mechanisms for elbow- and drum-type mixers in mixing of solids, (1) 12*f*.

Gaynes, N. High temperature coatings—they will cost more, (11) 276*b*.

Gazzara, C. P., and Middleton, R. M. X-ray diffraction study of the phase transformation temperature of MnO, B (5) 139*f*.

G.B.D. Soc. Anon. Holding. Glass-drawing apparatus including reheating means for producing flat sheets, P (4) 94*g*.

Gebauer, J., and Bizon, P. Rapid determination of the binding power of cements by the titration method, (4) 91*g*.

Gebel, R. K. H. Method of making an optical fiber phosphor screen, P (3) 68*g*. Modulated light source for electrooptical analysis of spectral lines, P (4) 104*j*.

Gebhardt, E., and Ondracek, G. Preparation of uranium dioxide-molybdenum cermet bodies, (7) 152*b*. Structure of uranium oxide-molybdenum systems, (8) 207*j*.

Gebhardt, E., Ondracek, G., and Thuemmler, F. Properties of uranium oxide-molybdenum cermet bodies, (7) 152*e*.

Gebruder Giulini G.m.b.H. Process for preparing alpha calcium sulfate hemihydrate from synthetic gypsums, P (11) 275*h*.

Gebrueder Pfeiffer Barbarossawerke Akt.-Ges. Sifter of the circulating air type, P (7) 161*d*.

Gedney, J. I. Technique for examining the luminous activity of individual phosphor particles in a functioning electroluminescent lamp, (4) 104*e*.

Geduzin, Ya. E., and Paritskaya, L. N. Diffusion coalescence of pores in crystalline solids with a boundary lattice, (5) 135*f*.

Gee, A. Method of manufacturing semiconductor devices, P (9) 231*i*.

Gee-Pemberton, R., and Walker, B. Bubble structure of ground coat enameled sheet steels, (11) 275*j*. Measurement of enamel by bubble structure, (8) 174*h*.

Gehlen, K. von. Oriented conversion of talc into protoenstatite (γ-$MgSiO_3$) in fired pressings of soapstone, (5) 137*d*.

Gehman, W. G. See Austerman, S. B.

Geiger, B. Pierre Renfer, a Swiss designer, (1) 1*i*.

Geil, F. G. See Thompson, J. H.

Geimer, H., and Overkott, E. Application of nondestructive testing to refractory brick, (2) 40*i*.

Gejo, T. See Muta, A.

Gel'd, P. V. See Baum, B. A.; Dubrovskaya, L. B.; Korshunov, V. A.; Radovskii, I. Z.; Takhai, V. A.

Gel'd, P. V., and Krentsis, R. P. Some thermophysical characteristics of iron silicides, (1) 29*a*.

Gel'd, P. V., and Lyubimov, V. D. Mobility activation energy of Nb and C in metallic niobium and its carbides, (5) 137*i*.

Geller, S. See Espinosa, G. P.; Gonser, U.

Geller, S., Grant, R. W., Cape, J. A., and Espinosa, G. P. Magnetic behavior of the system Mn_2O_3-Fe_2O_3, (8) 202*f*.

Geller, S., and Lind, M. D. Pressure-induced phase of sulfur-selenium, (3) 87*g*.

Gelsing, R. J. H., Stein, H. N., and Stevels, J. M. Vitreous alkali tungstates, (5) 119*e*.

General Aniline & Film Corp. Photoceramic process for producing vitrified photographic images, P (11) 283*j*.

General Dynamics Corp. Carbon coated nuclear fuel and poison particles, P (9) 225*b*. Epitaxially bonded thermoelectric device and method of forming same, P (5) 127*b*. Field effect semiconductor device and method of forming same, P (8) 184*b*. Fuel cell having zirconia-containing electrolyte and ceramic electrodes, P (4) 101*g*. Multipyrocarbon coated nuclear fuel and poison particles and method of preparing same, P (10) 259*j*. Refractory products, P (5) 125*c*. Welding flux, P (11) 276*c*.

General Electric Co. Apparatus for measuring the probability of the presence of optical blemishes, P (8) 176*g*. Apparatus and method of controlling pressure, P (3) 80*c*. Barium potassium ferrite magnetic material exhibiting nonvanishing rotational hysteresis in applied magnetic fields, P (2) 47*g*. Bistable metal-niobium oxide-bismuth thin film devices, P (11) 284*j*. Ceramic article coated with silver containing oxygen and method of making same, P (7) 156*h*. Ceramic bonding, P (1) 3*b*. Coated columbium or tantalum base metal, P (3) 65*b*. Differential output tubular incandescent lamp, P (3) 77*i*. Electric lamp manufacture, P (5) 120*e*. Electrical device with casing seal members comprising a cavity in meeting surface, P (4) 101*b*. Electrical discharge cleaning and coating process, P (9) 233*c*. Epitaxial growth of semiconductor devices, P (8) 184*b*. Field effect semiconductor device with polar polymer covered oxide coating, P (3) 78*i*. Flame spectrophotometer using ionization current detection, P (10) 268*c*. Flash lamp manufacture, P (5) 120*f*. Flexible electroluminescent device and light transmissive electrically conductive electrode material [indium oxide] therefor, P (8) 184*c*. Fluorescent lamp coating, P (7) 156*c*. Fluorescent phosphate glass, P (5) 120*h*. Four layer semiconductor switch with the third layer defining a continuous, uninterrupted internal junction, P (9) 230*j*. Fuel cell with stabilized zirconia electrolyte and nickel-silver alloy anode, P (4) 101*h*. Furnace heat shield, P (2) 52*h*. Glow discharge device having parallel permanent magnetic rod electrodes, P (10) 264*b*. Graphite-catalyst charge assembly for the preparation of diamond, P (8) 173*i*. Graphite lubricating composition of increased load carrying capacity, P (4) 98*j*. Grooved reflector lamp, P (3) 68*a*. Group II metal-thorium phosphate phosphors, P (8) 184*c*. Heterojunction electroluminescent devices, P (10) 264*b*. High power semiconductor laser devices, P (5) 127*h*. High temperature capacitor, P (10) 264*c*. High voltage capacitor assembly, P (9) 231*b*. Humidity-sensitive resistor, P (4) 104*i*. Inorganic-bonded reconstituted mica sheet, P (7) 156*g*. Inorganic molding compositions of the asbestos-orthophosphoric acid type and products, P (9) 225*j*. Lamp bulb assorting apparatus, P (9) 220*b*. Lamp bulb coating apparatus, P (9) 220*c*. Light transmitting electrode including *n*-type semiconductive In_2O_3, P (3) 78*a*. Metallized semiconductor support and mounting structure, P (3) 78*d*. Metal vapor lamp having a heat reflecting coating of calcium pyrophosphate, P (9) 220*e*. Method of forming a carbon body, P (2) 44*j*. Method of forming pyrolytic graphite sheets, P (4) 106*d*. Method of forming a sheet, P (7) 153*i*. Method of growing diamond on a diamond seed crystal, P (4) 103*g*. Method for making thin film glass elements, P (8) 178*e*. Method of manufacturing photoflash lamps [exhaust tip], P (8) 178*h*. Method for producing homogeneous crystals of mixed semiconductive materials, P (10) 264*h*. Method of producing semiconductor devices, P (11) 287*a*. Method for the production of diamond compact abrasives, P (5) 115*h*. Method [vacuum deposition] of forming superconductive niobium films, P (9) 231*d*. Molecular sieves and methods for producing same, P (5) 133*c*. Nonlinear resistance material, P (3) 75*c*. Nuclear fuel, P (3) 72*b*. Oriented graphitic structure, P (2) 44*i*. Pattern diamond growth on diamond crystals, P (5) 128*d*. Photoflash lamp, P (5) 121*d*. Plural wedge-shaped graphite mold with heating electrodes, P (10) 260*c*. Preparation of elongated needle-like diamond having electrically conductive properties, P (7) 145*h*. Process for doping a diamond in a gaseous electrical discharge, P (8) 185*j*. Process for producing alumina whiskers, P (10) 260*j*. Pyrolytic graphite coated casting mold and method of making same, P (2) 45*i*. Quantitative differential thermal analysis apparatus, P (8) 188*e*. Quartz-to-metal seal, P (8) 178*j*. Reflector arc lamp with arc tube support comprising arc tube inlead connectors fastened to the outer end of ferrules sealed in the outer envelope, P (11) 279*c*. Rhenium supported metallic boride cathode emitters, P (7) 157*j*. Sealing a membrane to a target support metal ring, P (3) 69*e*. Semiconductive alloy light source having improved optical transmissivity, P (4) 102*c*. Semiconductor devices with epitaxial contour, P (10) 265*b*. Semiconductor diode with integrated mounting and small area fused impurity junction, P (4) 102*e*. Semiconductor material and method of making the same, P (5) 129*d*. Semiconductor photovoltaic devices, P (3) 79*e*. Semiconductor strain sensitive devices and method of making the same, P (10) 265*c*. Solid state electronic devices, method, and apparatus, P (9) 232*e*. Solion device having hermetically sealed exterior of borosilicate glass, P (4) 102*h*. Surface-adjacent junction electroluminescent device, P (4) 102*i*. Thermocouple pressure gage, P (10) 268*d*. Titanium ceramic composite bodies, P (4) 103*b*. Transistor housing containing packed, earthy, nonmetallic, electrically insulating material, P (1) 12*c*.

General Electric Co., Ltd. Articles of fused silica, P (5) 120*c*. Ceramic materials, P (5) 133*g*. End closures for ceramic tubes, P (2) 47*f*, P (10) 263*h*. Formation of light-diffusing coatings on vitreous silica bodies and devices incorporating them, P (4) 94*f*. Luminescent materials and their manufacture, P (2) 48*a*. Manufacture of colored glass, P (8) 177*j*. Method for forming a tetragonal crystalline oxide coating on germanium, P (11) 286*g*. Methods of and apparatus for forming light-diffusing coatings on the internal surfaces of hollow vessels, P (3) 69*d*. Separation of minerals, P (3) 83*e*. Uranium carbide-tungsten nuclear fuel composition, P (10) 261*b*. Vibratory conveyor screens, P (3) 80*g*.

General Electronics Corp. Method for interchanging curvature of cathode-ray tube faceplate, P (11) 279*c*.

General Instrument Corp. Electrolytic apparatus for treatment of the tips of glass beaded leads, P (1) 10*b*. Piezoelectric ceramic filter, P (4) 102*g*. Variable photosensitive semiconductor device having a graduatingly different operable surface area, P (4) 103*a*.

General Motors Corp. Control of crystal size, P (3) 77*f*. Crystal growth, P (3) 77*h*. High voltage igniter with fluid feed through the [Al_2O_3] insulator core center, P (10) 264*d*. Method and apparatus for hydrostatically compacting metal powders, P (8) 186*h*. Method of forming contacts in semiconductor devices, P (11) 286*f*. Method for making cadmium sulfide field effect transistor, P (9) 231*e*. Method of making contacts on semiconductors, P (11) 286*i*. Method of making magnesium fluoride articles, P (4) 98*e*. Semiconductor crystal growth from a domical projection, P (3) 79*d*. Spark plug having porcelain insulator protected by plasma-jet deposited refractory coating, P (1) 11*j*. Spark plug with improved intensifier spark gap in the center electrode, P (9) 232*e*.

General Precision, Inc. Method of lubricating vitreous fibers, P (4) 94*j*.

General Refractories Co. Lightweight castable refractory composition, P (11) 281*h*. Materials heating and handling apparatus, P (11) 288*g*. Preparation of magnesium oxide from magnesite, P (5) 124*i*. Process of beneficiating magnesite, P (5) 124*i*. Refractory brick of burned magnesia and process of manufacture, P (2) 45*b*. Refractory brick with metal plate bonded by a chloroprene-phenolic adhesive, P (10) 260*f*. Refractory brick wall with a comolded hanger assembly, P (9) 227*c*. Refractory roof and method, P (11) 283*a*. Suspended refractory construction, P (11) 283*c*.

General Refractories, Ltd. Chemically bonded refractory tile and their manufacture, P (9) 225*c*. Refractory bricks and their manufacture, P (1) 8*e*, P (7) 154*e*, P (8) 182*b*, P (11) 283*a*. Refractory silica brick, P (10) 260*i*.

General Steel Wares, Ltd. Gas drier, P (5) 132*e*.

General Telephone & Electronics Laboratories, Inc. Ferroelectric pulse generator, P (10) 263*j*. Method of preparing aluminum arsenide, P (4) 102*c*.

Genkin, Ya. E. See Korsunskii, M. I.

Gens, T. A. Openly porous refractory nuclear fuel microspheres and method of preparation, P (8) 181*i*.

Gentile, A. L. Electric breakdown mechanism in cuprous chloride single crystals, (11) 294*b*.

Gentile, R. J. See Keller, W. D.

Gentry, F. E. Four layer semiconductor switch with the third layer defining a continuous, uninterrupted internal junction, P (9) 230*j*. Semiconductor devices with epitaxial contour, P (10) 265*b*. See Mets, E. J.

Gentsch, H. See Freund, F.

Geo. J. Meyer Mfg. Co. Bottle inspection system, P (3) 67*j*.

Geo. P. Reintjes Co., Inc. Open hearth furnace roof, P (9) 235*a*.

Georg Willy A. G. Conveyors for bricks and the like, P (3) 80*b*.

Georges, R. See Bloch, D.

Georgia Kaolin Co. Method of treating [pumping] clay, P (9) 236*b*. Selective separation of heterogeneous particles, P (4) 107*b*.

Georgia-Pacific Corp. Apparatus for continuous calcination of gypsum, P (5) 116*b*. Continuous calcination of gypsum, P (5) 116*e*.

Gerasimov, A. F., Konev, V. N., and Timofeeva, N. F. Investigation of reaction diffusion in the systems metal-compound gas (VI) system tungsten–carbon–nitrogen, (1) 20*c*.

Gereth, R., and Stephens, C. Transmitted phonon drag measurements in epitaxial silicon, (3) 88*c*.

Gerhardt, W. See Feldmann, K.

Gerhart, P. Automatic filter presses, (9) 232*h*.

Gerken, R. See Schaefer, H.

Gerlach, J. L. Amorphous alkali metal aluminate, P (1) 9*a*.

Gerlach, R. L. See Robins, J. L.

Gerlach, W., Koehl, G., and Moench, W. Process for production of electrically unsymmetrical semiconducting device, P (11) 287*f*.

Gerloff, G. See Schloemer, J.

German, W. L. Some aspects of the effects of base exchange in the properties of clays, (4) 110*b*.

Germer, L. H. Present and proposed uses of low-energy electron diffraction in studying surfaces, B (8) 212*h*.

Gernert, J. F. See Barrall, E. M., II.

Gerow, C. W. Abrasive resinous polymer compositions and their preparation, P (4) 89*f*.

Gerrard, J. E., and Percival, J. Thermocouple for multiple burner combustion control, P (4) 105*a*.

Gerrard, T. A. Environmental studies of Fort Apache member, Supai formation, east-central Arizona, (7) 163*j*.

Gerry, D. J. See Outwater, J. O.

Gershenzon, M. See Ashkin, A.; Trumbore, F. A.

Gershenzon, M., and Mikulyak, R. M. Radiative pair recombination and surface recombination in GaP photoluminescence, (8) 206*a*.

Gerson, R. See Achenbach, G. D.

Gerstenberg, D., and Hall, P. M. Superconducting thin films of niobium, tantalum, tantalum nitride, tantalum carbide, and niobium nitride, (3) 76*j*.

Gesell, W. F. Fluid amplifiers for measurement and control, (4) 93*i*.

Gesellschaft zur Forderung der Forschung an der Eidgenossischen Technischen Hochschule. Method for reprocessing fuel elements with fissionable material in carbide form which are spent in nuclear reactors, P (8) 181*h*.

Gesellschaft fuer Kernforschung m.b.H. Method of reprocessing and/or separating nuclear fuels, P (9) 226*a*.

Gettig, J. H. See Gettig, W. A.

Gettig, W. A., and Gettig, J. H. Method of attaching a metal hypodermic needle to a glass ampoule, P (1) 5*h*.

Getty, R. J., and Armstrong, W. P. Drying air with activated alumina under adiabatic conditions, (4) 103*c*.

Gettys, W. E. See Sturcken, E. F.

Getz, R. W. See Chubb, W.

Geusic, J. E. See Johnson, L. F.

Geyer, N. M. See Srp, O. O.

Geymayer, H. G. Discussion of "Influence of cement paste content on the creep of light-weight aggregate concrete," (11) 275*d*.

Ghersini, G. See Cerrai, E.

Ghosh, B. N. See Gupta, D. M.

Ghosh, R. K., and Srinivasan, N. R. Development of clay pozzolan industry (III) utilization of reactive surkhi and lime-reactive surkhi mix, (10) 269*c*.

Ghosh, R. K., Srinivasan, N. R., Kreshnamachari, R., and Bhatia, M. L. Development of clay pozzolan industry (II) manufacture of reactive surkhi and lime-reactive surkhi mixture, (8) 174*b*.

Giammetti, F. See Folloni, M.

Gianatasio, H. L. Abrasive belt, P (10) 247*f*.

Giardini, A. A., and Tydings, J. E. Synthesis of diamond, P (9) 213*g*.

Gibala, R., and Wert, C. Clustering of interstitials in dilute niobium (columbium)-oxygen-nitrogen solid solutions, (7) 162*h*.

Gibb, T. C., and Greenwood, N. N. Chemical applications of the Moessbauer effect, (1) 17*b*.

Gibbon, C. F., and Kuczynski, G. C. Effect of interfaces on the radiation production of color centers in alkali halides, B (2) 61*d*.

Gibbons, G. See Sze, S. M.

Gibbons (Dudley), Ltd. Protection of refractory materials, P (10) 260*c*.

Gibbs, G. V., and Smith, J. V. Refinement of the crystal structure of synthetic pyrope, (1) 27*j*.

Gibson, C. B., Jr. Phosphor dielectric storage target for cathode ray tube, P (3) 79*i*.

Gibson, I. M. Modified Lovibond tintometer using fiber optics for the measurement of surface color, (1) 14*a*.

Gibson & Sons, Ltd. Production of pottery articles, P (8) 183*a*.
Gieschen, J. A., Parker, R. W., and Habermann, B. L. Automated crusher setting, P (10) 269*i*.
Gieser, R. H. See Erwin, L. R.
Gifford, R. O., and Frugoli, D. M. Silica source in soil solutions, (4) 109*d*.
Gilard, P. See Bast, J. de.
Gilbert, J. T. Program temperature controlling apparatus, P (5) 132*a*.
Gilbert, W., and Hughes, G. Some experiments on the use of basalts in heavy clay products, (8) 179*d*.
Gill, J. B., and Taylor, R. M. System potassium metaphosphate-calcium metaphosphate, (8) 209*d*.
Gill, R. M. Composition including a carbide and a boride and tool made thereof, P (8) 173*h*.
Gill, W., Jr. See Collins, C. C.
Gillam, J. L. See Kalousek, G. L.
Gilles, J. C. Preparation of oxynitrides from refractory oxides, (1) 27*c*. Recent findings on the rare earth oxides, (9) 235*e*.
Gilles, P. W. See Robson, H. E.
Gillis, K. H. See Mathewson, W. F.
Gillooly, G. R. See Rabatin, J. G.
Gilman, W. S. Preparation and characterization of ZrO_2 and HfO_2 microballoons, (7) 152*a*.
Gilson, P. C. J. Manufacture of ceramic products, P (11) 280*b*.
Gimpl, M. L., McMaster, A. D., and Fuschillo, N. Structure of twist grain boundaries in NaCl, B (2) 61*f*.
Gingerich, K. A. See Aronson, S.
Ginsbach, K. H., and Sonntag, A. Method for making a semiconductor device, P (5) 128*b*.
Ginther, L. B. See Swift, H. R.
Ginzburg, D. B., Rapoport, A. Ya., Slivinskii, I. G., Yurkov, L. F., and El'kin, G. B. Investigating the processes of melting high lead glass, (8) 175*d*.
Gipson, M., Jr. Preparation of oriented slides for X-ray analysis of clay minerals, (4) 104*c*. Study of the relations of depth, porosity, and clay mineral orientation in Pennsylvanian shales, (7) 168*c*.
Girling, B. See Inman, D.
Gissane, W. J. M. See Cheetham, C. J.
Gjerstad, S., and Welch, B. J. Oxidation of aluminum by carbon dioxide in the presence of cryolitic electrolyte, (3) 87*f*.
G.K.N. Group Services, Ltd. Settling of particulate matter from liquids, P (2) 50*c*.
Glabbeek, C. H. van. See Sprengers, J.
Glaceries Reunies, Soc. Anon. Fluid quenching apparatus for producing a differentially toughened zone in a toughened glass, P (5) 120*g*.
Glaces de Boussois S. A. Angular jets in conditioning chamber of a glass sheet drawing apparatus, P (8) 176*c*. Apparatus for cutting sheet glass, P (1) 4*c*. Drawing chamber for the continuous manufacture of sheet glass, P (4) 94*c*.
Gladrow, E. M., and Mattox, W. J. Synthetic zeolites, P (10) 270*a*.
Gladrow, E. M., and Thompson, C. E. Fuel cell electrode, P (2) 44*a*.
Gladyshevskii, E. I. Crystal structure of compounds and phase equilibria in ternary systems of two transition metals and silicon, (3) 84*j*. See Borusevich, L. K.; Fedorov, T. F.; Kuz'ma, Yu. B.; Savitskii, E. M.
Gladyshevskii, E. I., Popova, N. M., and Fedorov, T. F. Mutual solubility of the carbides of zirconium, niobium, and hafnium, (2) 55*g*.
Glaister, R. M., Allen, N. A., and Hellicar, N. J. Comparison of methods for preparing fine ferrite powders, B (7) 170*a*.
Glanville, C. R. Electrode system having a potential electrode embedded within a current electrode for measuring the electrical resistivity of a porous rock sample, P (4) 104*i*.
Glaser, H. I. Apparatus for melting and processing heat-softenable mineral materials, P (9) 219*f*, P (10) 254*c*. See Machlan, G. R.
Glaser, W. See Boggum, P.
Glasova, M. P. See Matveev, M. A.
Glass Bulbs, Ltd. Blank forming apparatus for glass ribbon forming machine, P (11) 278*a*.
Glass Machinery, Inc. Apparatus for forming hollow glassware, P (10) 254*i*.
Glasser, L. G., Kanzler, R. J., and Troy, D. J. Method and apparatus for photometric analysis, P (5) 132*a*.
Glatfelter, P. H., Co. White pigment, P (11) 292*e*.
Glaxo Group, Ltd. Method of and apparatus for granulating powdery materials, P (1) 12*i*.
Glenn, G. R. X-ray studies of lime-bentonite reaction products, (7) 169*e*.
Glentworth, J. D. See Barford, J. C.
Glicksman, R. See Minton, R. M.
Glidden Co. Furnaces for fast-firing ceramic ware and process, P (9) 234*j*. Vibratory ball mill, P (2) 50*c*.
Gliemeroth, G. See Scholze, H.
Globe-Union, Inc. Filter, P (2) 47*g*.
Glower, D. D., and Wallace, D. C. Thermal studies of $Ca_xBa_{1-x}TiO_3$, (7) 169*c*.
Glueckauf, E. Coated particle fuels for nuclear reactors, P (7) 153*d*.
Glushko, P. I. See Ivanov, V. E.; Verkhorobin, L. F.
Gluskoter, H. J. Clay minerals in Illinois coals, (8) 192*b*.
Gnaedinger, R. J., Jr. See Flaschen, S. S.
Gnall, R. P. See Pliskin, W. A.
Gobeli, G. W., and Ligenza, J. R. Stabilization of silicon semiconductor surfaces, P (11) 287*h*.
Gobert, G. Detection of moisture in materials, P (3) 81*d*.
Godejahn, G. C., Jr. Semiconductor structure including opposite conductivity segments, P (7) 158*c*.
Goeckel, H. F., and Boicey, C. R. Method of sealing metal to glass, P (9) 221*h*.
Goeddel, W. V. See Bokros, J. C.
Goeddel, W. V., and Luby, C. S. Carbon coated nuclear fuel and poison particles, P (9) 225*b*.
Goeddel, W. V., Luby, C. S., and Chin, J. Multipyrocarbon coated nuclear fuel and poison particles and method of preparing same, P (10) 259*j*.
Goerl, E. See Troemel, G.
Goganov, D. A. See Porai-Koshits, E. A.
Goganov, D. A., and Porai-Koshits, E. A. Chemically heterogeneous structure of certain silicate glasses according to the results obtained by small-angle X-ray scattering, B (7) 171*a*. Investigation of the chemically heterogeneous structure of certain silicate glasses by the small-angle X-ray scattering method, B (5) 141*i*.
Golabi, S. M., Flahaut, J., and Domange, L. Solid solutions formed by the addition of selenides of the rare earths to MSe selenides of the face-centered cubic NaCl type, (1) 28*i*.
Gold Line Co. Magnetically tuned ferrite cavity transistor oscillator, P (11) 286*a*.
Goldberg, G. N. See Rapp, R. A.
Goldberg, M. M., Allegrini, A. P., and Cecil, T. A. Attapulgite clay filter aid product containing combination of fluxes and method for making same, P (1) 15*e*. Clay filter aid and production thereof, P (2) 54*a*.
Goldheim, D. L. See Westwood, A. R. C.
Gol'dshtein, L. Ya. See Okorokov, S. D.
Gol'dshtein, M. E. See Lyubarskii, I. M.
Goldsmith, N. Method of depositing epitaxial layers of gallium arsenide, P (7) 157*d*.
Goldstein, E. E. Apparatus for making rigid mineral fiber panels, P (9) 219*e*.
Goldstein, M. K. See Flanagan, T. B.
Golf, L. C. See Starks, D. F.
Goliber, E. W. Advances in cemented carbide tooling, (3) 63*f*.
Golovanova, T. G. See Belyaev, I. N.
Golovina, E. S., and Khaustovich, G. P. Interaction of carbon with carbon dioxide at high temperatures, (8) 200*i*.
Gol'tseva, V. S. See Shchegrov, L. N.
Golutvin, Yu. M., and Liang, Ching-kuei. Heats of formation, heat contents, and heat capacities of chromium silicides, (3) 86*d*.
Golynko-Vol'fson, S. L. See Okorokov, S. D.
Gomaa, I. See Bishay, A. M.
Gomel'skii, M. S. Structurochemical character of granular heterogeneity in quartz glass, B (9) 245*a*.
Gomes, W. Reduction of silver ions incorporated in alkali halide crystals by hydrogen, (5) 138*b*.
Gomi, S., Hara, N., and Kawajiri, N. Flameless radiant burner, P (10) 268*g*.
Gonser, U., Grant, R. W., Wiedersich, H., and Geller, S. Spin orientation determination by linearly polarized recoil-free γ rays, (8) 207*a*.
Gonsior, T. See Bosch, H.
Gonzalez Garcia, F. See Garcia Ramos, G.
Gonzalez Garcia, F., and Garcia Ramos, G. Ceramic clays of Andalucia (III) tertiary deposits on the right bank of the Guadalquivir River, Seville Province, (5) 132*i*.
Gonzalez Garcia, S., and Dios Cancela, G. Microcalorimetry in laminar silicates (I) energy of hydration of montmorillonite, (4) 108*i*.
Goode, J. H. See Flanary, J. R.
Goodenough, J. B. See Rogers, D. B.
Goodenough, R. D., and Gaska, R. A. Extraction of lithium values from brines containing calcium salts in the presence of ammonia, P (5) 133*i*.
Goodenough, R. D., Gaska, R. A., and Belski, R. C. Method of producing solid solutions of the carnallite type, P (7) 161*a*.
Goodenough, R. D., Jones, G. D., and Anderson, R. E. Recovery of lithium from lithium-bearing ores, P (4) 107*b*.
Goodman, A. M., and O'Neill, J. J., Jr. Photoemission of electrons from metals into silicon dioxide, (2) 55*f*.
Goodman, L. See Chernow, F.
Goodwin, W. D. Apparatus for transforming materials by pyrogenic techniques, P (10) 254*e*.
Gool, W. van. Density, lattice parameters, and defect chemistry of pure nonstoichiometric compounds, (10) 270*h*.
Goonvean China Clay & Stone Co., Ltd. Clay treatment, P (8) 190*d*.
Goorissen, J. Method of producing doped semiconductor material and apparatus therefor, P (9) 231*a*.
Gorbachev, A. A. See Bartenev, G. M.
Gordeev, I. V., and Tret'yakov, Yu. D. Thermodynamics of solid solutions of magnesium ferrite with magnetite, (2) 58*f*.
Gordeev, I. V., Tret'yakov, Yu. D., and Khomyakov, K. G. Thermodynamic properties of solid solutions in the system Fe_3O_4-Mn_3O_4, (4) 112*b*.
Gordienko, A. K. See Tol'skii, A. A.
Gordienko, S. P., and Fesenko, V. V. Use of mass spectrometry for the investigation of refractory compounds, (8) 211*a*.
Gordin, V. L. See Ugai, Ya. A.
Gordon, A. D. See Trubey, P. W.
Gordon, D. W. See Anderson, A. R.
Gordon, R. S., and Kingery, W. D. Thermal decomposition of brucite (I) electron and optical microscope studies, (1) 29*j*; (II) kinetics of decomposition in vacuum, (2) 58*a*.
Gore, E. M., and Keinanen, H. Photoelectric glassware inspecting device, P (2) 39*i*.
Gorokh, A. V. See Galemin, I. M.; Novokhatskii, I. A.
Gorshkova, L. V. See Fedorov, T. F.
Gorski, F. T. See Shannon, R. F.
Goryainov, K. E., Markaryan, M. S., and Aksenov, P. A. Electric welding of refractories, (3) 71*a*.
Goslee, D. E., and Frank, L. Method of producing nuclear fuel elements of stainless steel coated UO_2 particles, P (8) 181*g*.
Goslett, Alfred, Co., Ltd. See Alfred Goslett Co., Ltd.
Gosnell, R. B. Coating process for glass fibers and product, P (4) 93*j*.
Goss, J. W. Dolly for moving boxes of glass, P (5) 120*d*.
Goss, N. P. Continuous casting method with degassed glasslike blanket, P (8) 180*i*.
Gosselin, J. P., Shimony, U., Grodzins, L., and Cooper, A. R. Moessbauer studies on iron in sodium trisilicate glasses, (10) 252*i*.
Goto, E., Iwata, N., and Shinada, H. Methods of sealingly securing lead-in wires to glass tubes, P (5) 121*i*.
Gott, O. Viscosity investigations by beam bending, (10) 254*d*.
Gott, O., and Hillmann, E. Indentation viscometer for small samples, (10) 267*f*.
Gottardi, V. See Locardi, B.
Gottlieb, G. E. Vapor phase transport and epitaxial growth of $GaAs_{1-x}P_x$ using water vapor, (9) 243*b*.
Gottstein, O. See Dubansky, A.
Gould, G. See Piltch, M.
Gould, R. E. See Partington, P. A.
Gould, R. J. See Martin, H. T.
Goulding, F. S. Method and apparatus for determining drift depth of impurities in semiconductors, P (3) 78*c*.
Goulounes, N. Method of baking plaster at low temperatures, P (1) 2*d*. See Chassevent, L. E.
Govorova, R. A. See Alekseeva, O. S.; Bokin, P. Ya.
Gow, J., III. Tunnel diode with tunneling characteristic at reverse bias, P (1) 12*a*.
Gow, W. A. See Kelly, F. J.
Gowen, H. E. T. Controlled deposition and growth of polycrystalline films in a vacuum, P (3) 77*g*.
Grabmaier, J., and Sirtl, E. Method for producing semiconductor devices, P (11) 286*i*.
Grace, M. I., Kedzie, R. W., Kestigian, M., and Smith, A. B. Elastic wave attenuation in lithium niobate, (9) 238*a*.
Grace, R. E. See Edmiston, W. A.
Grace, W. R., & Co. Apparatus for producing sol microspheres, P (11) 288*f*. Aqueous thoria-urania sol, P (9) 225*a*. Cement additives composed of ethanolamine salts, P (10) 249*a*. Hydrous oxide sol of urania and thoria and process, P (10) 259*a*. Method of applying porcelain enamel to metal, P (1) 3*d*. Method of forming a flexible seal between telescopically engageable pipe sections, P (8) 179*f*. Method for making metal oxide microspheres, P (7) 153*a*, P (8) 190*i*. Microspheres containing colloidal carbon, P (10) 259*i*. Preparation of aquasols of crystalline zirconia and/or hafnia, P (2) 45*a*. Preparation of microspheres of urania and other materials, P (10) 260*c*. Preparation of a multilayer copper oxide catalyst for treatment of exhaust gases, P (11) 291*c*. Process for preparing alumina having a narrow pore size distribution, P (9) 226*j*. Process for preparing a desiccant pellet, P (4) 107*c*. Process for preparing a polishing compound and product, P (4) 80*f*. Process for producing high porosity gamma alumina, P (9) 236*h*. Re-expanding compressed exfoliated vermiculite, P (2) 54*d*. Silicon thermistors, P (3) 79*f*. Spodumene accelerated portland cement, P (10) 249*d*. Thorium silicate hydrosols, P (3) 75*a*. Uranium dioxide sol process, P (7) 154*e*. Uranium dioxide-yttrium oxide-zirconium dioxide aquasol process and product, P (10) 261*a*. Uranium dioxide-zirconium dioxide sol preparation, P (7) 154*f*. Uranium trioxide sol process, P (9) 227*i*. Uranium trioxide-zirconium dioxide sol process and product, P (9) 227*j*.
Grach'yan, A. N. See Ponomarev, I. F.
Gradle, B. See Reed, E. L.
Graeber, E. J., and Jelinek, D. A. Technique for obtaining powder patterns from single crystal spheres, (5) 131*g*.
Graf, R. E., and Young, R. W. Method of making ophthalmic lens, P (11) 279*d*.
Graffenberger, H. See Curtis, B. J.
Graham, H. C. See Tallan, N. M.
Graham, H. C., Tallan, N. M., and Russell, R., Jr. Particle size dependence of the electrical conductivity of NaCl, (4) 109*a*.
Graham, H. M., and Phelps, P. L., Jr. Method of temperature cycling ferroelectric ceramics through a temperature range below the Curie point thereof, P (1) 11*h*.
Graham, J., and Wadsley, A. D. Crystal structure of the blue potassium molybdenum bronze $K_{0.2}MoO_3$, (9) 237*f*.
Graham, N. C. See Connolly, T. M.
Graham, P. W. L., and Rindone, G. E. Internal friction peak caused by condensation of water on barium silicate glasses, (7) 148*j*.
Grain, C. F. Phase relations in the ZrO_2-MgO system, (7) 166*j*.
Grams, W. R. Solion device having hermetically sealed exterior of borosilicate glass, P (4) 102*h*. See Lafferty, J. M.
Grand-Clement, A. M. See Bedier, R.
Granitsas, G. A. Method of sealing fiber optic plates, P (5) 121*h*. See Woodcock, R. F.

Granitsas, G. A., and Crandon, H. D. Fiber type energy-conducting structures and method of making same, P (1) 4*i*.
Grankovskii, I. G., and Chernogorenko, V. B. Rheological characteristics of cement pastes and of concentrated suspension models, (4) 91*g*.
Grant, J. F. See Saunders, A. C.
Grant, R. W. See Geller, S.; Gonser, U.
Grant, W. A., and Carter, G. Ion bombardment-induced emission of gas from glass, (7) 148*j*. Thermal desorption of inert gases ionically pumped into glass, (9) 218*i*.
Grant, W. E. Interconnecting circuits with a gallium and indium eutectic, P (11) 285*h*.
Grasenick, F. Device for the thermoelectric measurement of the temperature of rotary specimen carriers, P (2) 52*a*.
Gravette, N. C., Barham, D., and Barrett, L. R. Investigation of the system V_2O_5–SiO_2, (1) 20*d*.
Gray, B. D. Component package, P (7) 156*j*.
Gray, F. L. See Clendinning, W. R.
Gray, J. E. See Bussey, H. E.
Gray, J. H. See Foster, L. H.
Gray, K. R. See Steinberg, J. C.
Gray, N. B., and Henderson, J. Hydrogen reduction of dense hematites, (7) 164*f*.
Gray, P. V., and Brown, D. M. Density of SiO_2-Si interface states, (5) 135*a*.
Gray, R. L. Plant pump, P (4) 100*a*.
Gray, T. J., and Guile, D. Grain boundary effects in relation to the dielectric properties of infrared transmitting materials, B (2) 61*e*.
Gray, T. J., and Zope, J. K. Electron microbeam probe techniques for studying grain boundaries in polycrystalline ceramics, B (2) 61*g*.
Great Lakes Carbon Corp. Apparatus and process for continuously making baked and graphitized carbon bodies, P (2) 43*d*. Substantially isotropic graphitized bodies used in nuclear reactors, P (9) 227*g*.
Greaves, M. J. Spalling of restrained refractory materials due to transient temperatures, (2) 43*d*.
Grebenshchikov, R. G. Energies of crystal lattices of silicates and the heat of formation of silica anion radicals, (8) 196*h*.
Grebenshchikov, R. G., and Pasechnova, R. A. Heats of formation of calcium germanates, (8) 199*a*.
Grebenshchikova, N. I. See Petrovskii, G. T.
Grechanik, L. A. See Fainberg, E. A.; Zertsalova, I. N.
Grechanova, S. B. See Azarov, K. P.
Greco, E. J., and Martinelli, J. A. Compositional dependency of laser-induced damage in glass, (7) 148*d*.
Green, D. Pottery—Materials and Techniques, B (9) 245*h*.
Green, D. H. Petrogenesis of the high-temperature peridotite intrusion in the Lizard area, Cornwall, (1) 24*j*.
Green, E., & Son, Ltd. Dust-separating apparatus, P (4) 103*f*.
Green, J. J. See Maguire, E. A.
Green, W. E. Manufacture of antimony trioxide, P (10) 269*f*.
Greenbank, J. C., and Harper, S. Mechanism of breakaway oxidation in zirconium alloys, (2) 35*d*.
Greenbaum, M. A. See Blauer, J.; Yates, R. E.
Greenbaum, M. A., Arin, M. L., Wong, M., and Farber, M. Thermodynamic and physical properties of beryllium compounds (V) heat of formation and entropy of beryllium(I) chloride(*g*), (8) 210*d*.
Greenbaum, M. A., Ko, Hon Chung, Wong, M., and Farber, M. Vapor pressure and heat and entropy of sublimation of solid magnesium fluoride, (8) 211*c*.
Greenberg, C. B., and Cook, R. L. Interfacial reactions in lead oxide bearing enamel-metal systems, (3) 65*c*.
Greenberg, H. J. See Adler, E. J.
Greenberg, L. S., and Greig, W. J. Semiconductor device fabrication, P (1) 11*e*.
Greene, P. E. See Ewing, R. E.
Greening, N. R. Some causes for variation in required amount of air-entraining agents in portland cement mortars, (10) 248*f*.
Greening, N. R., and Landgren, R. Surface discoloration of concrete flatwork, (1) 2*e*.
Greenland, D. J., Laby, R. H., and Quirk, J. P. Adsorption of amino acids and peptides by montmorillonite and illite (I) cation exchange and proton transfer, (7) 161*f*; (II) physical adsorption, (7) 161*h*.
Greenwood, J. A., and Williamson, J. B. P. Contact of nominally flat surfaces, (11) 293*a*.
Greenwood, N. N. See Gibb, T. C.
Greenwood, R. Unicast ceramic mold process, (2) 43*g*.
Greer, R. T., Staley, W. G., Jr., and Vand, V. Cathodoluminescence device for rapid identification of phase assemblages, (10) 267*c*.
Gregor, L. V. See Burkhardt, P. J.; Hu, S. M.
Gregory, N. W. See Hollahan, J. R.
Greig, W. J. See Greenberg, L. S.
Greiner, J. Magnetic raw materials, P (11) 286*a*.
Greiner, J. H., and Fan, G. J. Longitudinal magneto-optical Kerr effect in EuO and EuS, (8) 201*g*.
Grenis, A. F., and Levitt, A. P. Infrared radiation of titanium boronitride, (1) 20*a*.
Gresens, R. L. Dimensional and compositional control of garnet growth by mineralogical environment, (1) 18*b*.
Gresh, M. See Schwartz, N.
Greskovich, C., and Stubican, V. S. Divalent chromium in magnesium-chromium spinels, (8) 195*b*.
Gress, R. I. See Ivakhin, S. I.
Gridley, P. F. See Stoddard, S. V.
Grieco, M. J. See Miller, K. J.
Griem, P. D., Jr. Method for controlling the temperature of heat-softenable material, P (9) 221*d*.
Griest, E. M. Encapsulated impedance element, P (5) 127*j*.
Griest, E. M., and Theobald, P. R. Method for applying electrical conductors on a smooth vitreous surface and article, P (7) 157*c*.
Grieveson, P. See Turkdogan, E. T.
Grieveson, P., and Turkdogan, E. T. Miscibility gap in sulfate-ferrite melts at 1500°C, (3) 86*j*.
Griffel, M. See Jach, J.
Griffin, J. P. Thermocompression wire attachments to quartz crystals, P (4) 102*j*.
Griffith, R. M. Silica and alumina powders (I) extrusion, (3) 74*c*; (II) coherence and strength of compacts, (3) 74*d*.
Griffiths, D. W. L., and Thomas, W. J. Effect of oxidation on the surface heterogeneity of some graphitized carbons, (2) 41*e*.
Griffiths, L. B., and Mlavsky, A. I. Growth of α-SiC single crystals from chromium solution, (3) 86*c*.
Griffiths, R. Control of the grinding of glazes and vitreous enamels, (11) 283*h*.
Grigas, B. See Mikalkevicius, M.
Grigas, J., Karpus, A., and Meilus, J. Relation of microwave field and Sb_2S_3 single crystals, (5) 138*b*.
Grigor'ev, D. P. Ontogeny of Minerals, B (7) 170*e*.
Grigorovici, R. See Tauc, J.
Grigsby, C. E. Refractory roof and method, P (11) 283*a*.
Grimmeiss, H. G., Kischio, W., and Memming, R. Method of manufacturing semiconductor systems comprising cadmium chalcogenide semiconductors, P (2) 48*b*.
Grimmeiss, H. G., and Memming, R. Method of manufacturing semiconductor devices using cadmium sulfide semiconductors, P (1) 11*f*.
Grinberg, Ya. Kh. See Medvedeva, Z. S.
Grinshtein, Yu. L. See Brekhovskikh, S. M.
Grinstead, R. R. Solvent extraction process for the recovery of Be values, P (9) 236*h*.
Griswold, W. T. Method of calcining and classifying borate, P (7) 160*f*.
Grivna, H. W. See Schuster, G. L.
Grodshtein, A. E., Kriger, E. M., and Lisitsyn, S. M. Manufacture of ferrite powders by thermal decomposition of sulfates, (10) 262*g*.
Grodzins, L. See Gosselin, J. P.
Groh, H. J. See Russell, E. R.
Gromakov, S. D., Kurinnaya, V. N., Latypov, Z. M., and Chvala, M. A. New variant of the zone purification of materials, (8) 203*c*.
Gromakov, S. D., Zoroatskaya, I. V., Latypov, Z. M., Chvala, M. A., Eidel'man, E. A., Badygina, L. I., and Zaripova, L. G. Method of studying phase diagrams of semiconducting systems, (11) 298*f*.
Gromovoi, V. I. Pressed wood components, (3) 74*d*.
Grosborne, P. F. See Bradu, G. M.
Gross, S. B., Uretsky, C. L., and Altebrando, P. T. Variable photosensitive semiconductor device having a graduatingly different operable surface area, P (4) 103*a*.
Grove, A. S. See Deal, B. E.
Grover, J. R., and MacKenzie, M. Production of radioactive fused glass bodies, P (9) 222*b*.
Groyecki, J. See Markuszewicz, M.
Grubbens & Co. A.B. Process and apparatus for disintegrating fibrous material, P (4) 103*i*.
Gruber, B. (editor). Theory of Crystal Defects—Proceedings of the Summer School held in Hrazany in September 1964 (in English), B (4) 114*a*.
Gruber, C. W. See Pritchard, W. L.
Gruber, G. A. See Chu, T. L.
Gruehn, R., and Schaefer, H. Oxidized niobium and tantalum compounds with O/M = 2.33 to 2.50, (11) 299*a*.
Gruender, W. Preparation of Minerals and Ores (Vol. 1) General Preparation, B (11) 305*b*.
Grun Kom.-Ges. Geb. Process and apparatus for the treatment of particulate or granular substances, P (5) 130*c*.
Grundhauser, F. J. See Dyke, W. P.
Gruner, K. See Cuhra, B.
Gruver, R. M. See Kirchner, H. P.
Grylicki, M. Study of weakened fluoberyllate models of Ba_2SiO_4-Mg_2SiO_4 and Ba_2SiO_4-Ca_2SiO_4-Mg_2SiO_4 systems, (1) 29*c*.
Grzymek, J., and Skalny, J. Notes on C_2S polymorphism, (1) 24*a*.
Grzymislawski, S. Apparatus for cutting sheet glass, P (1) 4*c*.
Gubko, I. T., Sizov, I. D., Kostomarov, M. I., and Khitro, E. V. Mixing Dinas bodies in centrifugal runner mill model 115, (5) 123*e*.
Gudovich, N. V., and Ovcharenko, F. D. Formation of organophilic montmorillonite in ion exchange, (7) 163*h*.
Gugel, E. See Hartmann, J.; Kieffer, R.; Schembra, F. W.
Gugel, E., Vogel, H., and Osterried, O. Production of an alkali-resistant stoneware, (3) 74*e*.
Gugeler, A. L. See Bryant, E. E.
Guile, D. See Gray, T. J.
Guillaud, C. See Lecerf, A.
Guillemet, C. See Acloque, P. H.
Guillot, A. See Anthony, A. M.
Guillot, A., and Anthony, A. M. Electrical conductivity of pure zirconia between 1200° and 1750°C, (1) 18*c*.
Guinan, G. H. (Mrs.). Case of the frightened bride (or is it the manufacturer?), (4) 89*j*.
Guiot, J. M. Study of cermets based on SiC (I) study of the Mo-SiC system; (II) study of the reactions between SiC and Mo, (11) 281*e*.
Gulbransen, E. A., and Andrew, K. F. Oxidation of zirconium and zirconium alloys in water vapor atmospheres containing trace amounts of oxygen at 375° and 575°C, (1) 2*h*.
Gulbransen, E. A., Andrew, K. F., and Brassart, F. A. Ablation of graphite in oxygen and air at 1000° to 1400° under flow conditions, (2) 40*i*. Reaction of hydrogen with graphite at 1200° to 1650°C, (9) 241*i*.
Gulbransen, E. A., Andrew, K. F., Brassart, F. A., and Feild, A. L., Jr. Ablation of high purity and nuclear reactor core graphite in oxygen and air, (7) 151*b*.
Gulden, T. D. Direct observation of nonbasal dislocations in sintered alumina, (10) 270*i*. Nature of dislocation loops in neutron irradiated sapphire, (9) 24*d*.
Gul'ev, G. F. See Kudrina, A. P.
Gulevic, O. Influence of glaze thickness on strength of electrical porcelain, B (5) 141*h*.
Gulf Research & Development Co. Aqueous solutions of devitrifiable glasses, methods of using, and products thereof, P (10) 254*f*. Process for producing alumina comprising nordstrandite in major proportion, P (9) 227*a*.
Gul'ko, N. V. See Berezhnoi, A. S.; Tarnopol'skaya, R. A.
Gullberg, R., and Lagneborg, R. X-ray determination of the volume fraction of phases in textured materials, (9) 243*h*.
Gulledge, H. C. See Emslie, R. S.
Gulliver, H. W. See Brown, R. S.
Gulotta, J. A. Manufacture of glass sheets on different fluid supports, P (11) 278*g*.
Gulton Industries, Inc. Ferrite memory cells and matrices, P (8) 184*b*.
Gulyaeva, V. F., and Salmanov, G. D. Use of highly refractory concrete in slot furnaces, (5) 123*j*.
Gumm, B. J., and Miles, C. V. H. Semiconductor barrier layer switch with symmetrical characteristics on either polarity, P (7) 158*a*.
Gunderson, A. S. See Hazdra, J. J.
Gundzik, R. M. See Stern, D. R.
Gunn, E. F., Jr. See Heller, G. L.
Gupta, A., and Lahiri, D. Hydraulicity of blast furnace slag in relation to composition, (2) 34*d*.
Gupta, D. M., Ghosh, B. N., and Talkalkar, T. W. Pouring pit refractories—nozzles, (10) 258*h*.
Gupta, S. K., and Prasad, S. N. Production of mirrors and silvering on glass (I) selection, cleansing, and sensitizing of glass, (5) 119*c*.
Gurevich, M. A. Tensimetry of vanadium carbides, (2) 57*e*. See Meerson, G. A.
Gurkovskii, E. V. See Borgman, V. A.
Gurney, E. L. See Taylor, A. W.
Gurney, J. J., and Erlank, A. J. Direct current arc spectrographic technique for determination of trace amounts of lithium, rubidium, and cesium in silicate rocks, (2) 50*i*.
Gurovich, N. A., and Sokolova, E. I. Oxidation of germanium disulfide, (11) 298*j*. Reaction of germanium dioxide with elemental sulfur and pyrite, (11) 300*b*.
Gurvich, A. M. See Gal'perin, E. L.
Gusarov, A. D., Deshko, Yu. I., and Kuchma, L. Kh. Determination of rheological characteristics of slurries and suspensions, (9) 233*j*.
Gustin, D. S. Apparatus for [electrostatic] coating of glass bulbs, P (9) 219*d*.
Guten, H. R. von. See Baertschi, P.
Gutfeld, R. J. von, and Nethercot, A. H. Thermal relaxation of indium films on insulating substrates between 4° and 300°K, (4) 111*g*.
Gutheil, H. H. See Born, G. E.
Gutierrez, W. A. See Wilson, H. L.
Gutkin, A. M., and Zhukov, N. V. Plastic and viscous properties of clay paste under normal load, (7) 166*g*.
Gutman, E. M. Statistical criterion for the degree of dispersity and allowance for the effect of particle shape on the permeability and pressibility of powders, (4) 110*g*.
Gutsche, H. Apparatus for producing highest-purity silicon for electric semiconductor devices, P (10) 263*b*.
Gutshall, P. L., and Swanson, G. D. Vacuum furnace for high temperature fracture studies, (1) 14*a*.
Gutsov, I. Overall crystallization of sodium phosphate glasses as an example of reconstructive crystallization, B (9) 246*c*. Relation between the structure of a substance in the glassy state and its zero-point entropy, B (7) 171*g*.
Gutt, W., and Osborne, G. J. System $2CaO \cdot SiO_2$-CaF_2, (4) 111*f*.
Guyer, E. M., and Nitsche, J. E. Method and apparatus for manufacturing glass beads, P (8) 177*d*.
Guyot, P., and Frison, E. Quality control in a refractories works by ultrasonic methods—possibilities, methods, and aims, (2) 42*a*.
Guzman, I. Ya., and Morozova, V. S. Foamed silicon carbide insulation and its properties, (4) 96*f*.
Guzman, I. Ya., and Poluboyarinov, D. N. Properties of porous ceramics made of beryllium oxide, (4) 97*e*.
Gwilliam, R. D. Filter presses, P (1) 12*c*.
Gyorgy, E. M. See Dillon, J. F., Jr.; LeCraw, R. C.

Haacke, H. See Hofmann, U.
Haagen-Smit, J. W., and Ramirez-Munoz, J. Multichannel integrating flame photometer, (4) 104*j*.

Haan, E. F. de, Schampers, P. P. M., and Drift, A. van der. Photosensitive device including layers of different conductivity types, P (2) 48*j*.
Haarmann, M. Process for thermal compensation of permanent magnetization systems by the use of a ferrite, P (11) 287*h*.
Haas, I. Transistor with elongated base and collector current paths, P (2) 49*d*.
Haas, P. A. See Clinton, S. D.; Farrell, J. B.
Haas, P. A., and Clinton, S. D. Method for preparing metal oxide microspheres, P (10) 259*h*.
Haas, P. A., Clinton, S. D., and Kleinsteuber, A. T. Preparation of urania and urania-zirconia microspheres by a sol-gel process, (4) 97*b*.
Haase, T. Pfefferkorn apparatus as an absolute instrument, (5) 131*j*.
Haase, T., and Ulbricht, J. Brown glaze for electrical porcelain, (3) 73*g*.
Habermann, B. L. See Gieschen, J. A.
Hach, C. C. Turbidimeter for sensing the turbidity of a continuously flowing sample, P (5) 132*b*.
Hach Chemical Co. Turbidimeter for sensing the turbidity of a continuously flowing sample, P (5) 132*b*.
Hackerman, N., and Estes, N. N. Method of treating electrodes for use in electrochemical devices, P (9) 226*c*.
Hackett, F. L. See Wood, T. K.
Hackley, L. W. Passivated alloy diode, P (3) 79*h*.
Hackney, H., and Jones, P. R. Response surface for dry modulus of rupture and drying shrinkage, (9) 233*j*.
Hacskaylo, M. Thin film diode manufacture, P (11) 288*b*. Vacuum-deposited magnetic thin films of Fe_2O_3-B_2O_3 mixtures, (3) 77*f*.
Haddad, I. N. See Banbury, P. C.
Haddad, I. N., and Banbury, P. C. Energy dependence of anisotropy of defect production in electron irradiated diamond-type crystals (I) experimental measurements on *n*- and *p*-type silicon, (8) 197*a*.
Haden, W. L., Jr. See Sawyer, E. W., Jr.
Haden, W. L., Jr., and Dzierzanowski, F. J. Cracking catalyst and preparation thereof, P (10) 269*j*. Method for making a faujasite-type crystalline zeolite, P (11) 291*j*. Zeolite agglomerates and the preparation thereof, P (3) 83*g*.
Hadjiioannou, T. P. See Vassiliadis, C.
Haetlinger, W. W. Torsional mode ceramic bandpass filter, P (4) 103*a*.
Haegele, W. Construction and possible uses of the automatic titrator Holderbank system, (11) 274*j*.
Haeger Potteries, Inc. Porous ceramic bodies and composite members and methods of making the same, P (2) 46*f*. Prosthetic parts and methods of making, P (8) 183*a*.
Haenichen, J. C. High voltage semiconductor device, P (7) 157*f*. Method for making a semiconductor device, P (7) 157*f*.
Haensel, V. See Hayes, J. C.
Haering, R. R., and Miksic, M. G. Thin film transistor and method of fabrication, P (2) 49*d*.
Haering, R. R., Miksic, M. G., and Pennebaker, W. B. Thin film transistor, P (2) 49*c*.
Haertling, G. H. Properties of hot-pressed ferroelectric alkali niobate ceramics, (7) 156*b*.
Haertling, G. H., and Zimmer, W. J. Analysis of hot-pressing parameters for lead zirconate-lead titanate ceramics containing 2% (at.) bismuth, (1) 9*f*.
Haese, U. New process control equipment for grate coolers, (11) 275*g*.
Hafferkamp, H. C. Method and apparatus for handling hot deformable glassware, P (5) 121*a*.
Hafner, H. C., and Rood, J. L. Some precautions necessary for precision measurements of index of refraction, (9) 234*b*.
Haft, H. H. See Bellott, E. M.
Hagedorn, E. C. Ultraviolet light-absorbing glass, P (3) 69*h*.
Hagel, W. C. Oxygen-ion diffusion in hematite, (1) 24*d*.
Hagenlocher, A. K. See Feuersanger, A. E.
Hagenmuller, P. See Lecerf, A.; Le Flem, G.
Hagenmuller, P., Galy, J., Pouchard, M., and Casalot, A. Recent investigations of vanadium bronzes (I) additive monovalent elements, (7) 167*g*; (II) additive divalent and trivalent elements, (8) 206*a*.
Haggerty, J. S., and Cooper, A. R., Jr. Configurational thermal expansion of three inorganic glasses, B (2) 61*j*.
Hagglund, J. See Musha, T.
Haglington, J B See Lakin, J. R.
Hagy, H E. Design strength of a chemically toughened glass, (5) 118*b*.
Hahn, R. L. See Ricci, E.
Hahn, S. Apparatus for calibrating thermistor thermometers, P (8) 184*a*.
Haider, H. See Barz, G. J.
Haigh, H. E. See Hughes, W.; Twist, W.
Hailstone, R., Sowards, D. M., and Weidman, V. W. Radiant heating devices, P (9) 235*a*.
Hair, M. L. See Chapman, I. D.
Hair, M. L., and Chapman, I. D. Surface composition of porous glass, (1) 4*i*.
Haisty, R. W. See Cronin, G. R.
Hajduk, T. J., and Kowalski, F. Cathode-ray tube manufacturing apparatus, P (11) 278*b*.
Hajela, R. B. See Jain, L. C.
Hakim, R. See Kennedy, T. N.
Hakki, B. W. Amplification oscillation and mixing in a single piece of bulk semiconductor, P (11) 284*h*.
Halcon International, Inc. Process for preparing a silicon carbide supported vanadium-containing oxidation catalyst, P (2) 45*e*.
Halder, N. C., and Wagner, C. N. J. Analysis of the broadening of powder pattern peaks using variance, integral breadth, and Fourier coefficients of the line profile, B (5) 139*f*.
Hall, A. Petrogenetic study of the Rosses Granite complex, Donegal, (7) 166*g*.
Hall, C. R. Effect of weak Bragg reflected beams on the absorption of electrons, (11), (8) 195*j*.
Hall, C. R., Hirsch, P. B., and Booker, G. R. Effect of point defects on absorption of high energy electrons passing through crystals, (8) 195*k*.
Hall, H. T. See Barnett, J. D.
Hall, J. N. See Hodges, J. R.
Hall, L. L. See Morgan, C. S.
Hall, P. M. See Gerstenberg, D.
Hall, R. F., and Stocker, B. J. Cold-cathode glow-discharge tube, P (2) 47*a*.
Hall, R. N. Method for producing homogeneous crystals of mixed semiconductive materials, P (10) 264*h*. Semiconductor strain sensitive devices and method of making the same, P (10) 265*c*.
Hall, R. O. See Hodgson, J.
Hall, T. P. P. See Henderson, B.
Hall, W. F. See Hildenbrand, D. L.
Hallen, R. L., and Valletta, R. M. Method and apparatus for cathode sputtering including suppressing temperature rise adjacent the anode using a localized magnetic field, P (10) 264*g*.
Haller, J. Method of molding an elongated powdered material composite compact, P (7) 158*f*.
Halperin, A. See Mackey, J. H.
Halsey, G. D., Jr. Plane monolayer adsorption with area changes, (1) 26*j*.
Halsted, R. E., Aven, M., and Coghill, H. D. Fluorescent emission spectra in II-VI compounds, (9) 239*g*.
Haltner, A. J., and Luetzel, W. G. Graphite lubricating composition of increased load carrying capacity, P (4) 98*j*.
Halva, C. J. Process for making nuclear fuel materials, P (8) 182*a*.
Ham, J. L. Production of Nb_3Sn diffusion layers, P (1) 11*d*.
Hamamura, A. Cation distribution in $ZnFe_2O_4$ precipitated from aqueous solution, (5) 126*d*.
Hamano, K., Yamada, H., and Ohba, T. Microstructure of stabilized zirconia and some considerations on the partial stabilization of zirconia, (3) 86*i*.
Hamano, Y. Studies on the sintering of alumina (VII) effects of strain energy and temperature gradient on the grain growth of alumina, (7) 168*a*.
Hamano, Y., and Kinoshita, M. Studies on the sintering of alumina (III) effect of pores on the rate of grain growth of sintered alumina, (4) 110*d*; (VI) grain growth, mechanical strength, and light transmission of hot-pressed alumina, (7) 168*i*.
Hamblen, D. P. See Blair, G. E.
Hamid, A. See Safdar, M.
Hamilton, D. R., O'Hara, S., and Seidensticker, R. G. Process for controlling dendritic crystal growth, P (4) 102*h*.
Hamilton, W. C. See Abrahams, S. C.
Hammer, J. See Beyersdorfer, K.
Hammer, W. N. See Mandel, G.
Hammock, L. G. See Saia, F. J.
Hammond, J. P. Vapor phase sintering process, P (3) 73*d*. See Werner, W. J.
Hamner, R. L. See Pilloton, R. L.
Hampton, A. L. See Jakacki, E. J.
Hampton, G. P. See Lasch, C. A., Jr.
Hanak, J. J. See Rosi, F. D.
Handt, P. R. See Hoornstra, C. W.
Handwerk, E. C. See Kaneko, T. M.
Handwerk, J. H. See Boltax, A.
Haneta, Y. Vapor deposition device, P (8) 186*c*.
Hanisch, H., and Biedermann, W. Molecular sieve formed bodies hardened with a binding agent, P (3) 83*f*.
Hanley, H. J. M. Thermal transpiration measurements on a porous ceramic, (11) 290*f*.
Hanna, L. See Trubey, P. W.
Hanna Mining Co. Use of kiln gas for production of magnetic iron oxide, P (2) 54*e*.
Hannavy, A. Microwaves detect flaws in composite materials, (10) 267*g*.
Hansen, K. W. Semiconduction in iron phosphate glasses, (11) 277*j*.
Hansen, K. W., and Shonkwiler, F. P. Furnace construction, P (4) 98*g*.
Hansen, R. C. See Kean, J. S., Sr.
Hanson, C. See Brown, A. H.
Hanson, C. K., Horton, R. M., and Wadsworth, M. E. Method and catalyst for combining hydrogen and oxygen in thorium oxide slurries, P (7) 153*h*.
Hanson, D. C. See Davies, B.
Hanson, M. M., Oberg, P. E., and Tolman, C. H. Substrate-temperature measurement and control, (3) 76*i*.
Hanumanlu, K., and Sastry, B. S. R. Effect of milling and firing conditions on density and oxygen content of microwave magnesium manganese ferrites, (10) 262*g*.
Hanwell, A. E. See Bowden, F. P.
Hanyu, T. Dislocation etch tunnels in quartz crystals, (8) 194*j*.
Haq, K. E. Deposition of germanium films by sputtering, (10) 262*c*.
Hara, K. See Tada, T.
Hara, N. See Gomi, S.
Harada, J., Watanabe, M., Kodera, S., and Honjo, G. Diffuse streak diffraction pattern of electron and X rays due to low frequency optical mode in tetragonal $BaTiO_3$, (9) 238*d*.
Harbison-Carborundum Corp. Wear-resistant refractory lining article, P (3) 73*e*.
Harbison-Walker Refractories Co. Basic oxygen steelmaking vessels, P (4), 98*b*. Basic refractory, P (2) 43*d*. Basic refractory product, P (7) 152*j*. Basic refractory for use in rotary kiln, P (4) 98*c*. Brick for improved service life in certain ferruginous environments, P (8) 180*e*. Coke oven door, P (4) 98*e*. Degree of direct bonding in brick of magnesia and chrome ore, P (9) 225*d*. Fired chrome-magnesite refractories, P (8) 181*b*. Furnace construction, P (4) 98*g*. Glass tank structure with a regenerator chamber, P (9) 235*a*. Heat transfer unit, P (7) 153*e*. High alumina refractories, P (2) 44*e*. Kiln operation, P (9) 235*c*. Manufacture of ceramic objects, P (3) 72*h*, P (5) 126*b*. Material handling, P (4) 98*c*. Metal encased refractory, P (9) 226*c*. Method of fabricating a heat shield structure, P (8) 181*j*. Method of *in situ* fabrication of a monolith refractory lining, P (3) 72*j*. Method of lining a metallurgical furnace and the product, P (10) 259*g*. Method of making partially stabilized zirconia, P (4) 89*k*. Mullite production, P (11) 282*i*. Nozzle construction with thermally expanding refractory insert, P (11) 282*j*. Oxygen converter linings, P (3) 72*b*. Pouring tube for pressure pouring apparatus, P (10) 260*d*. Prefabricated taphole assembly for metallurgical furnaces, P (10) 260*d*. Process for making refractory brick, P (2) 45*d*. Process for manufacturing improved refractory brick, P (1) 8*i*. Production of dead-burned refractory grain in a shaft kiln, P (1) 8*a*. Production of vitreous silica in a rotary kiln, P (8) 182*e*, P (9) 227*i*. Refractory bonding mortar, P (4) 99*c*. Refractory brick units, P (2) 45*c*. Refractory catalyst carrier and method of preparation thereof, P (5) 125*a*. Refractory lining, P (2) 45*c*. Refractory mortar composition, P (2) 45*f*. Refractory support, P (3) 73*b*. Rotary kiln scraper, P (4) 105*k*.
Harbison-Walker Refractories Co. and Koppers Co., Inc. Tundish ladles, P (10) 261*a*.
Harding, W. E., and Schwartz, R. S. Method of selectively coating semiconductor chips, P (1) 11*k*.
Hardison, L. C. Catalytic infrared heater, P (7) 160*f*. What plant engineers face in closer control of air pollution, (11) 288*e*.
Hardy, J. F. See Stoddard, S. V.
Hardy, J. R. Temperature dependence of the infrared absorption due to U centers in alkali halides, (2) 57*d*. See Marlow, P. G.
Hardy, S. See Gabrysh, A. F.
Hardy & Padmore, Ltd. Mechanism for grading and mixing sand, P (3) 83*d*.
Hare, W. A. Refractory shapes, P (4) 99*a*.
Hare, W. A., and Jordan, W. E. Abrasion resistant refractory material, P (2) 43*b*.
Harkness, A. C., and Young, L. Anodic oxide films on indium antimonide, (3) 75*e*. High resistance anodic oxide films on aluminum, (3) 76*a*.
Harkulich, T. M. See Vukasovich, M. S.
Harland, D. G. Radioactive method for measuring variations in density in concrete cores, cubes, and beams, (2) 51*c*; Reply to discussion, (11) 274*g*.
Harley, T. H. Stopper [design] for a ladle or similar receptacle, P (3) 73*b*.
Harman. See Smolik, T. J.
Harman, T. C. See Butler, J. F.
Harms, W. Improved surface coatings can be applied on today's brick, (1) 6*j*.
Harnisch, H. See Feldmann, K.
Harper, F. C., Clarke, B. L., and Brown, G. J. Abrasion resistance measurement, P (1) 14*c*.
Harper, S. See Greenbank, J. C.
Harr, H. L., Jr. Clay roof tiles—too costly? (1) 6*h*.
Harrap, V. See Osborne, J. F.
Harrell, W. C., and Demarest, H. M., Jr. Process for finishing float glass, P (2) 40*a*.
Harrington, G. W. See Papaioannou, P. C.
Harrington, R. V. Aluminosilicate glass, P (7) 149*e*. Humidity sensing element, P (5) 120*d*. Tan ophthalmic glass, P (3) 69*g*.
Harrington, R. V., and Karstetter, B. R. Heat-absorbing glass, P (9) 220*j*.
Harris, A. H., and Watson, A. H. Tiles, P (3) 64*i*.
Harris, D. C., and Brooker, E. J. X-ray spectrographic analysis of minute mineral samples, (2) 51*i*.
Harris, D. M. Graphite heating elements and method of conditioning the heating surfaces thereof, P (10) 259*j*.
Harris, D. P. Probability model of mineral wealth, (4) 106*d*.
Harris, H. M., Kelley, J. E., Sunset, P. H., and Kelly, H. J. Hot rolling of oxide-glass compositions, (11) 277*b*.
Harris, J. E. Method of treating [glass] fibers with dry binder material, P (11) 279*h*.
Harris, J. N., and Poulos, N. E. Fibrous ceramic structures, (1) 12*c*.
Harris, N. H., and Tennery, V. J. Structural and dielectric investigation of the $PbTiO_3$-$BaZrO_3$ system, (9) 230*c*.
Harris, P. H., and Johnson, D. A. Apparatus for alkali metal condensation in cement kilns, P (3) 64*b*.
Harrison, J. D. L. See Russell, L. E.
Harrison, P. L. Oxidation by transport through blocking pores, (9) 241*a*.
Harrop, D. See Cox, J. D.
Harrop, P. J., and Wanklyn, J. N. Dielectric loss spectra of corrosion films on zirconium, (4) 100*c*.

Harruff, R. W. See Trolander, H. W.

Harry W. Dietert Co. Physical properties testing apparatus, P (8) 188*d*. Structure for and method of cooling granular material, P (9) 233*d*. Temperature controlled structure for and method of cooling granular material, P (10) 261*a*.

Harsco Corp. Roll type rock crusher, P (9) 236*g*.

Harshaw Chemical Co. Calcium iodide phosphors, P (5) 127*a*. Scintillation detector comprising a transparent tin-activated calcium iodide scintillator, P (4) 102*b*.

Hart, A. B. See Taylor, D. W.

Hart, A. L. See Benson, C. A.

Hart, E. W. Modern theory of fluid surface tension, B (9) 245*e*.

Hart, J. See Birks, J. B.

Hart, L. D. See Heilich, R. P.

Hartman, C. W. See Daily, A. M.

Hartman, E. C., and Johnson, M. B. Coke oven door, P (4) 98*e*.

Hartman, R. A. Gob chute with fluid flow means, P (11) 278*d*.

Hartman, T. E. Density of thin evaporated aluminum films, (1) 17*d*.

Hartmann, J., Gugel, E., and Wiedenhorn, G. "Memory" of ceramic bodies, (4) 99*j*.

Harwood, D. J. See Oldfield, L. F.

Harwood, M. G., Macdonald, G. L., and Middel, V. J. Wet ball-milling of iron oxide, B (7) 169*j*.

Hasbrouck, R. A. See Bullard, R. L.

Hasegawa, K. See Hayashi, H.

Hasegawa, S. See Yamada, T.

Hashi, T. See Yasuoka, H.

Hashimoto, Y. See Condit, R. H.

Hashizume, K. Production of ion exchangeable substances from montmorillonite clay minerals, P (9) 236*a*.

Hasky, J. J. See Jones, D. P.

Hass, G. See Cox, J. T.; Drummeter, L. F., Jr.

Hass, G., and Ritter, E. Optical film materials and their applications, (9) 229*e*.

Hass, G., and Thun, R. E. (editors). Physics of Thin Films—Advances in Research and Development (Vol. 2), B (11) 305*i*.

Hasselman, D. P. H. Approximate theory of thermal stress resistance of brittle ceramics involving creep, (10) 270*d*. Relation between macroscopic shear moduli and micromechanical shear stress concentrations of multicomponent materials, (7) 167*i*.

Hasselman, D. P. H., and Fulrath, R. M. Micromechanical stress concentrations in two-phase brittle-matrix ceramic composites, (9) 240*i*.

Hastings, J. A. Glass enclosed passivated semiconductor with contact means of alternate layers of chromium, silver, and chromium, P (3) 78*j*.

Hatch, G. B. Phosphate glass composition, P (2) 39*i*.

Hatch, L. P. See Tuthill, E. J.

Hatch, S. E. See Carnall, E., Jr.

Hatcher, O. W. Method of making field effect transistor device, P (11) 286*i*.

Hatfield, C. See Oakes, A. C.

Hatfield, C. B., and Rohrbacker, T. J. Dolomite-insoluble residue relationships in the Ten Mile Creek dolomite (Middle Devonian) near Toledo, Ohio, (4) 107*j*.

Hatschek, R. A. Method for the direct measurement of pressure differences, P (4) 104*j*. Piezoelectric device, particularly a force measuring instrument and the process of manufacturing same, P (1) 11*a*. Piezoelement for force measuring instruments, P (1) 11*b*.

Hattori, M. See Tanaka, M.

Hauck, J. E. Boron nitride—high cost material with a promising future, (9) 223*g*.

Hauff, A., and Scheidig, H. Device for suspending a consumable electrode and supplying a melting current thereto, P (7) 160*f*.

Haul, R. Diffusion in oxides, (5) 135*f*.

Haul, R., and Duembgen, G. Method and apparatus for determining the surface area of finely divided substances by gas adsorption, P (4) 104*j*.

Haun, R. D., Jr., and Ohlmann, R. C. Cathodoluminescent pumped laser having a cathode surrounding the laser, P (8) 184*d*.

Hauptmanova, K., Pantoflicek, J., and Patek, K. Absorption and fluorescence of Nd^{3+} ion in lanthanum-borate glass, (4) 92*i*.

Hausmann, D. A. Impact-actuated spring system for producing vibrations in a rotating form, P (5) 130*g*.

Hausner, H. H. See Bonis, L. J.

Hauth, C. R. See Cope, G. R.; Stock, D. F.

Hauth, W. E., Jr. Spark plug having porcelain insulator protected by plasma-jet deposited refractory coating, P (1) 11*j*.

Havranek, P. H. Basic refractory particularly suited for use in rotary kiln, P (4) 98*c*. Fired chrome-magnesite refractories, P (8) 181*b*.

Havranek, P. H., and Davies, B. Basic refractory product, P (7) 152*j*. Diffusion of open-hearth slags in basic refractories, (7) 151*h*.

Haw, S. G. See Strange, R. R.

Hawes, R. W. M. See Jones, T. G.

Hawkins, E. G. See Napolitano, A.

Hawkins, R. D. Method of making fiber optic frequency responsive device, P (10) 255*h*.

Hay, B. F. Electrical resistor having a core element with high heat dissipating properties, P (3) 78*a*.

Hay, D. A. Production of dispersion hardened materials, P (2) 45*h*.

Hayakawa, S. See Ikushima, H.; Mikoda, M.; Ouchi, H.

Hayakawa, S., and Ikushima, H. Radiation damage on $BaTiO_3$ single crystals, (3) 87*h*.

Hayakawa Denki Kogyo Kabushiki Kaisha. Radiation energy transducing device, P (1) 11*d*.

Hayama, H., and Totikubo, I. Accidental printing effect in magnetic tape composed of cobalt substituted gamma ferric oxide powder, (9) 237*a*.

Hayama, M. Radiant burner, P (5) 132*g*.

Hayami, H. See Kamogawa, T.

Hayashi, H. See Arai, Z.

Hayashi, H., Matsumoto, H., Takagi, H., and Nishiyama, G. Clay and quartzite from Okinawa for ceramic use, (5) 132*j*.

Hayashi, H., Nakayama, N., Hasegawa, K., Mizukusa, S., Mizuno, M., Ogiso, S., and Torii, Y. Phase transition under high pressure (IV) synthesis of $ZnSiO_3$ pyroxene, (1) 26*a*.

Hayashi, H., Nakayama, N., Hasegawa, K., Mizukusa, S., Noguchi, T., Ogiso, S., and Takagi, H. Phase transition under high pressure (V) transition of Zn_2SiO_4, (1) 26*c*.

Hayashi, K. See Kawamura, T.; Tsuji, S.

Hayashi, T., Tabata, K., and Okuda, S. Tar-saturated magnesia brick, (11) 281*f*.

Hayashi, T., and Watanabe, H. Method of producing tunnel diodes by double alloying, P (1) 11*h*.

Hayashi, T., Watanabe, H., and Sotome, Y. Negative resistance semiconductor device utilizing tunnel effect, P (5) 128*c*.

Hayashida, S. See Naruse, Y.

Hayden, R. L. Method and apparatus for traversing strand material, P (3) 68*a*.

Hayer, M., Mandl, M., and Doubek, J. Device for sampling and analysis of metallurgical furnace atmospheres, (5) 131*c*.

Hayes, J. C., McGrath, D., and Haensel, V. Manufacture of high purity alumina sol from relatively low grade aluminum, P (11) 281*j*.

Hayes, W. See Bessent, R. G.; Elliott, R. J.

Hayhurst, A. See Caldwell, M.

Hayhurst, A., and Laming, J. Effect of firing temperature on the properties of chrome-magnesite brick, (4) 96*j*.

Hays, F. R. Method of sealing fiber optic plates, P (5) 121*g*. Radiation absorption heating of a bundle of glass fibers, P (9) 222*c*.

Hays, J. F. See Uhlmann, D. R.

Hays Corp. Paramagnetic oxygen analyzer measuring cell, P (1) 14*e*.

Hayward, A. T. J. Apparatus and method for measuring the compressibiiity of liquids, P (7) 159*g*.

Hazdra, J. J. Coating composition and glassware coated with the same, P (1) 4*g*.

Hazdra, J. J., and Gunderson, A. S. Method of increasing the durability of glassware, P (1) 6*b*.

Hazdra, J. J., and Lontz, H. M. Glass to glass adhesives, P (11) 278*b*.

Hazell, A. C. Anomalous scattering of X rays by centrosymmetric crystals, (1) 16*i*.

Head, E. L. See Holley, C. E., Jr.

Headlee, W. C. See Ziselberger, A. E.

Heald, M. T., and Renton, J. J. Experimental study of sandstone cementation, (8) 197*g*.

Healy, G. W., and Schottmiller, J. C. Chromium oxide-silica system at low oxygen pressures, (3) 83*i*.

Healy, J. H. See Mohanty, G. P.

Hearmon, R. F. S. See Bechmann, R.

Hearne, K. R., and Nixon, S. A. Method for measuring transient arc electrode temperatures, (7) 159*i*.

Heasley, J. H. See Shaw, R. R.

Heavens, O. S. Measurement of optical constants of thin films, B (11) 305*j*.

Hechler, R. W. See Schwiete, H. E.

Hecht, A. Tall shell insulators, (9) 228*d*.

Hecht, H. G. See Wendlandt, W. W.

Heck, R. F., Muehleisen, R. W., and Speigel, K. Method of cataphoretic deposition of luminescent materials, P (8) 185*b*.

Hecklinger, C. F. See Copson, R. L.

Hedden, W. A. See King, B. W., Jr.

Hedges, K. B. Method for improving perlite filter aids with a phosphoric agent, P (11) 282*b*.

Hedley, G. G. Applications of electrocast refractories, (2) 40*j*.

Hedley, W. H., Roehrs, R. J., and Trask, W. T., Jr. Production of uranium dioxide by flame denitration, (4) 97*c*.

Heeley, E. J. Determination of the residual strain in some vitreous enamel coatings, (11) 276*a*.

Heering, P. G. Technical aspects of the use of natural gas in the ceramic industry, (8) 189*a*.

Heerschap, M., and Delavignette, P. Vacancy loops in irradiated and annealed graphite, (8) 211*d*.

Heestand, R. L. See Robinson, W. C.

Heflich, H. G. See Engel, W. T.

Hegedus, A. J. Modern no-dazzle incandescent tungsten filament lamps and their production and use, (1) 4*b*. Thermogravimetric study of manganese(II) nitrate pyrolysis, (2) 58*i*.

Hegyi, I. J. See Tietjen, J. J.

Heidrich, W., and Koerner, K. Sintered product for use in foaming ceramics, P (10) 260*i*.

Heier, K. S. Some crystallochemical relations of nephelines and feldspars on Stjernoy, north Norway, (2) 56*d*.

Heil, O. Art of sealing quartz to metal, P (1) 10*g*. Method of preparing an electron tube including sputtering a suboxide of titanium on dielectric components thereof, P (7) 157*h*.

Heilich, R. P., Rohr, F. J., and Hart, L. D. Pneumatic gunning of refractory concrete, (8) 180*g*.

Heilmann, P. E., and Chesney, J. Piezoelectric ceramic filter, P (4) 102*g*.

Heilmann, T. Manufacture of cement, P (9) 215*h*.

Heimke, G. Effect of water vapor on the reactions of hard-magnetic ferrites, (3) 75*g*.

Heine, M. A., and Sperry, P. R. Distribution of defects in aluminum oxide films near the metal-to-oxide interface, (9) 229*c*.

Heinemann, H., Kraus, J. W., and Spector, M. L. Radioactive materials of low surface area, P (5) 128*i*.

Heinemann, O. Device for the continuous pneumatic feeding of powdered or granular material, P (7) 158*i*.

Heinen, K. G., and Larrabee, G. B. Activation analysis of silicon by convention carrier separations and by computer reduction of gamma spectra, (2) 50*d*.

Heinrich, K. F. J. Electron-probe microanalysis, B (8) 211*j*.

Heinrich Koppers G.m.b.H. Conveyor, P (3) 80*a*. Device for igniting and checking the flame of a [gas] burner, P (9) 234*j*.

Heinze, G., and Podschus, E. Production of silica bonded zeolitic molecular sieve granules, P (4) 107*a*.

Heit, A. H. Surface cleaning method and composition, P (1) 3*d*.

Heitmann, A. C. Nickel chrome alloy, P (8) 178*c*.

Helbing, C. H. Bonded glass fiber product and process, P (11) 278*a*.

Hellbardt, G. See Michelitsch, M.

Heller, G. L., White, J. W., and Gunn, E. F., Jr. Apparatus for producing pigmentary silica, P (2) 53*i*.

Heller, L. See Bodenheimer, W.

Heller, W. Apparatus for determining the shape of colloidal particles using light scattering, P (4) 104*h*.

Hellicar, N. J. Electrolytic capacitor with dielectric film formed on ceramic material, P (10) 263*g*. See Glaister, R. M.

Hellner, E., and Schurmann, K. Stability of metamorphic amphiboles—the tremolite-ferroactinolite series, (10) 272*b*.

Hellwege, K. H. (editor). Landolt-Boernstein (New Series), Numerical Data and Functional Relationships in Science and Technology, B (11) 305*b*.

Helm, J. W., and Davidson, J. M. Effect of massive neutron exposure on the distortion of reactor graphite, (2) 41*e*.

Helmbrecht, W. L., Welker, R. H., and Krieger, A. E. Apparatus for glass inspection and sorting having contour sensing means, P (7) 149*g*.

Helming, B., and Henne, H. Method of and apparatus for grinding moist material, P (3) 80*d*.

Helmuth, R. A., and Turk, D. H. Reversible and irreversible drying shrinkage of hardened portland cement and tricalcium silicate pastes, (10) 248*d*.

Helser, J. L. See Shannon, R. F.

Hemmer, F. J. Thin film circuit vacuum processing facility, P (8) 186*b*.

Hemmer, F. J., and Piedmont, J. R. Vacuum furnace, P (1) 15*a*.

Hemphill, R. B. Ultrasonic attenuation in zinc oxide at room temperature, (8) 211*e*.

Hemstock, G. A., and Bergmann, R. J. Clay slurries and method for making same, P (5) 133*g*. Paper coating clay and method for treating the same, P (4) 106*j*.

Hench, L. L. (editor). Bibliography of Ceramics and Glass, B (8) 211*i*.

Henderson, B. See King, R. D.

Henderson, B., and Hall, T. P. P. Some studies of Cr^{3+} ions and Mn^{4+} ions in magnesium oxide, (7) 167*h*.

Henderson, B., and King, R. D. Dose dependence of F-center production by fast neutrons in magnesium oxide, (1) 18*c*.

Henderson, C. M., and Beaver, E. R., Jr. Two-phase thermoelectric body comprising a silicon-germanium matrix—silicon-carbon matrix—lead-tellurium matrix, P (2) 49*e*.

Henderson, J. See Gray, N. B.

Henderson, J., Jr. See Onn, D. G.

Henderson, L. A. See Dyer, H. N.

Hendricks, R., Jr. See Ballard, A. H.

Hendricks, S. J. Precast fireplace, methods of manufacture and erection, P (4) 98*i*.

Hendrickson, G. R., Shaw, D. W., and Mehal, E. W. Fabrication of a metal base transistor, P (9) 230*i*.

Hendrickson, H. S. Dipole antenna including ferrite sleeves about the medial portions of its radiating elements, P (4) 101*a*.

Henkel & Cie G.m.b.H. Preparation of metal surfaces for enameling, P (8) 174*i*.

Henker, H., and Rummel, T. Method and apparatus for producing semiconductor material, P (7) 157*a*.

Henn, J. J. See Peters, F. A.

Henne, H. See Helming, B.

Henney, J., and Jones, J. W. S. High-temperature phase equilibria in the Th-U-C system in the presence of free carbon, (5) 136*a*. Phase equilibria in the thorium–carbon system, (1) 25*b*.

Hennicke, H. W. Isostatic pressing in ceramics, (9) 232*j*. See Ackermann, C.

Hennicke, H. W., and Leers, K. J. Practical determination of elastic moduli of refractories, (2) 42*h*.

Hennicke, H. W., and Lehmann, H. Wear of glazed surfaces as a function of time, (3) 74*h*.
Hennicke, H. W., and Salge, H. Observations on a firebrick after long service, (9) 224*h*.
Hennicke, H. W., Schwiete, H. E., and Sieckmann, J. Determination of the wear resistance of glazes (II), (3) 73*j*.
Hennig, G. R. See Bollmann, W.
Henrie, T. A. See Kesterke, D. G.
Henry, G. R. See Weaver, E. P.
Henry, K. M. See Chapman, G. C., Jr.
Henry, V. J., Jr. See Howard, J. D.
Hensiek, H. H. Paving brick and its cement base, (3) 70*g*.
Hensler, J. R., and Weidel, R. A. Tungsten oxide-metal metaphosphate glasses, P (1) 6*e*.
Hepler, L. G. See Hu, Teh.
Hepworth Iron Co., Ltd. Clayware piping, P (8) 179*f*.
Heraeus Quarzschmelze G.m.b.H. Infrared heater, P (8) 189*b*.
Heraeus, W. C., G.m.b.H. Device for suspending a consumable electrode and supplying a melting current thereto, P (7) 160*f*. Vacuum electric arc furnace arrangements, P (2) 53*e*. Vacuum electric arc furnaces, P (1) 15*a*.
Herbert, D. B. Applications for silicon carbide refractories, (4) 96*e*.
Herbert, J. W. See Badger, A. E.; O'Connell, T. B.
Herbst, D. L. See Layer, E. H., Jr.
Herbst, H. J., and Lyon, J. E. Refractory compositions and processes, P (8) 182*c*.
Hercules, Inc. Process for the preparation of cadmium yellow pigments, P (11) 291*g*.
Herczog, A. Barium titanate materials, P (11) 284*i*. See Layton, M. M.
Herkart, P. G. See Arlett, R. H.
Herman, F. Atomic structure, B (9) 244*d*.
Herman, H. (editor). Advances in Materials Research (Vol. 1) Experimental Methods of Materials Research, B (8) 211*i*.
Hermann, J. A. Preparation and purification of lithium chloride, P (1) 16*c*.
Heron, G. F. Method of producing cellular material from a dispersion asbestos fiber, P (11) 282*f*.
Herrero, C. A. See Alvarez Herrero, C.
Herrick, C. S., and Day, H. R., Jr. Apparatus for measuring the probability of the presence of optical blemishes, P (8) 176*g*.
Herring, A. P. Redox equilibria in glasses—comments on papers, (5) 119*c*.
Herring, C. Magnetism—A Treatise on Modern Theory and Materials (Vol. IV) Exchange Interactions Among Itinerant Electrons, B (11) 305*i*.
Herrmann, E. R. Molding comminuted nonplastic inorganic material, P (10) 266*e*.
Herrmann, R. See Masson, R.
Herrmann, R. A. See Shen, C. Y.
Herron, R. H., and Smothers, W. J. Technique for microscopic observation of crack propagation, (3) 81*h*.
Herschelmann, W. Development, preparation, and testing of enamels resistant to washing liquids, (9) 216*c*.
Hershinger, L. W. Solid state thin film triode with a graded energy band gap, P (3) 79*f*.
Hertl, W. See Pultz, W. W.
Hertl, W., and Pultz, W. W. Disproportionation and vaporization of solid silicon monoxide, (8) 195*a*.
Herzig, K. H. High voltage insulator filled with semiconductive foam containing gas under superatmospheric pressure, P (9) 231*c*.
Herzog, J. A. See Mehan, R. L.
Herzog, L. F., II. Composition determination by spark source and ion microprobe mass spectrography, (1) 13*e*.
Herzog, R. F. K. See Barrington, A. E.
Heslop, R. B., and Pearson, E. F. Quinolinium and lutidinium molybdates as reagents for the precipitation of phosphate, (8) 187*i*.
Hess, A. R., Sleighter, G. E., and Ernsberger, F. M. Method of strengthening glass by ion exchange and articles therefrom, P (2) 30*c*.
Hess, F. O. Apparatus for forming glass beads, P (3) 67*c*.
Hess, M. S., Viva, O. R., and Armstrong, W. J. Properties of diffused resistors, (5) 126*e*.
Hesse, T. Problems in the use of stainless steels, especially in the enameling industry, (10) 250*d*.
Hessevick, R. E. See Blake, R. L.
Hessinger, P. S., and Weber, T. W. Method of making synthetic mica and ceramoplastic materials, P (11) 286*b*.
Hesson, H. J. See Stroud, R. C.
Heuer, A. H. See Sellers, D. J.
Heuer, A. H., and Roberts, J. P. Thermal etching of single-crystal corundum, (2) 58*f*.
Heuer, R. P. Preparation of magnesium oxide from magnesite, P (5) 124*i*. Process of beneficiating magnesite, P (5) 124*i*. Refractory brick of burned magnesia and manufacture, P (2) 45*b*.
Hewitt, A. W. Process for ornamenting glass articles, P (10) 256*d*.
Hewitt, G. F., and Sharratt, E. W. Effect of back pressure on the counter diffusion of gases in graphite, (7) 151*i*.
Hewson, C. W., and Kingery, W. D. Effect of MgO and $MgTiO_3$ doping on diffusion-controlled creep of polycrystalline aluminum oxide, (5) 135*i*.
Hey, A. W., and Livey, D. T. Calcination of two BeO powders, (5) 134*d*.
Heybey, A. T. See Skogerboe, R. K.
Heyding, R. D., Taylor, J. B., and Bright, N. F. H. Inorganic research in Canada, (11) 303*f*.
Heyman, M. D. Sheet containing mica and glass, P (9) 232*d*.
Heynau, H. A. See Penney, A. W., Jr.
Heytmeijer, H. R., and Lockwood, G. H. Method of doping tungsten oxide, P (2) 48*f*.
Heywang, W. See Spielmann, W.
Heywood, D. See Arridge, R. G. C.
Hiatt, W. R. Solid state electronic devices, method, and apparatus, P (9) 232*e*.
Hiatt, W. R., and Barrett, J. R. Bistable metal-niobium oxide-bismuth thin film devices, P (11) 284*j*.
Hickam, W. M., and Zamaria, J. F. Furnace control by fuel cell, (11) 290*b*.
Hickok, R. L. See Parodi, J. A.
Hicks, J. F. G. Structure of silica glass, (4) 93*b*.
Hicks, J. W., Jr. Method of making fiber bundles, P (3) 68*f*. Method of making light-conducting optical multifiber structures, P (9) 221*h*.
Hicks, M. K. See Fisher, H. E.
Hicks, W. T. Bonding telluride-containing thermoelectric modules, P (4) 100*h*. Semiconducting behavior of substituted tungsten diselenide and its analogues, (7) 167*g*.
Hidalgo, P. J., and Sizmann, R. Inclusion of radioactive krypton in aluminum oxides during thermal surface changes, (2) 55*d*.
Higgins, J. K. Reaction of alumina with cesium vapor, (5) 137*j*.
Higginson, K. Efficient fuel usage in brickmaking, (7) 159*j*.
Highberg, C. W., and Bonnet, R. E. Apparatus for grinding, P (3) 67*c*.
Highfill, C. W., Jr., and Self, T. J., Jr. Grinding [hammer] mill, P (10) 266*a*.
Higuchi, M., Tanaka, K., and Hiwatari, Y. Statistical observation of the relation between the properties of ladle brick and decline in its consumption, (9) 224*i*.
Hildebrand, E. L. See Ziselberger, A. E.
Hildebrand, H. See Stieler, A.
Hildebrandt, E. W. B. Are tunnel kilns advantageous for small and medium-sized brickworks? (3) 81*i*.
Hildenbrand, D. L., and Hall, W. F. Decomposition pressure of boron carbide and the heat of sublimation of boron, (8) 194*g*.
Hildinger, W. M., Boyer, W. H., and Van Dreser, M. L. Refractory, P (2) 45*a*.
Hill, A. E., and Hoffman, G. R. Stress in films of silicon monoxide, (7) 167*j*.
Hill, D. C. See Vergano, P. J.
Hill, J. See Calandrello, N. A.
Hill, O. F. See Townsend, M. G.
Hill, T. E., Jr., and Calhoun, W. A. Processing high-iron Arkansas bauxite ores, (8) 189*f*.
Hillegas, W. J., Jr. See Schnable, G. L.
Hillert, L. Phase diagram (64% SiO_2 + 36% CaO)–CaF_2, (1) 25*f*. Phase diagram (90% SiO_2 + 10% TiO_2)–CaF_2, (8) 204*g*. Phase diagram (95% SiO_2 + 5% Al_2O_3)–CaF_2, (8) 204*g*. Phase diagram TiO_2–CaF_2, (8) 204*g*. Phase diagram (80% TiO_2 + 20% Al_2O_3)–CaF_2, (1) 25*h*. Phase diagram (81% TiO_2 + 19% CaO)–CaF_2, (8) 204*g*.
Hilliard, J. E. Estimating grain size by the intercept method, (3) 80*i*. Specification and measurement of microstructural anisotropy, (4) 110*b*. See Cohen, J. B.
Hillman, T. F. Split mold operating mechanism, P (9) 222*e*.
Hillmann, E. See Gott, O.
Hillner, E. High-temperature oxidation kinetics of zirconium in dry oxygen, (5) 136*j*.
Hills (West Bromwich), Ltd. Glazed structures, P (2) 46*d*.
Hilsum, C. Laser diode with metal contacts plated over the sides of the semiconductor, P (8) 184*j*.
Hilton, A. R., Jr., Jones, C. E., Jr., and Brau, M. J. Ge-P-Te glasses and method of making same, P (11) 278*f*.
Hilton, R. R. B. Refractory and heat insulating materials, P (4) 99*f*.
Hime, W. G. See Crow, R. F.
Himes, R. C. See Miller, J. F.; Reid, F. J.
Hinchliffe, N. W. Aluminosilicate monolithic refractories in iron and steel manufacture, (9) 223*f*. Furnace casing and lining secured by an anchorage assembly, P (11) 281*e*. Furnace with metal link and refractory anchor member, P (5) 124*h*.
Hinckley, D. N. Mineralogical and chemical variations in the kaolin deposits of the coastal plain of Georgia and South Carolina, (1) 23*g*.
Hinder, J. W. Ceramic [art] experiments of Lotte Reimers, (9) 213*i*. German husband and wife potters in Istanbul—Rolf and Ursula Busz, (7) 145*j*.
Hinds, G. W. See Cable, T. H., Jr.
Hiner, H. C. See Martin, J.
Hines, F. F. Thermal measuring probe, P (3) 81*h*.
Hinotani, K., and Sugigami, M. Electrical properties of *p*-type ZnTe showing injection electroluminescence, (11) 294*d*.
Hinzner, F., and Ruehle, M. Electron microscopic observations of the precipitation of niobium oxide from supersaturated solutions, (11) 294*j*.
Hipp, J. C. See Vickery, R. C.
Hippel, A. R. von (editor). Dielectrics and Waves, B (8) 212*b*.
Hiragushi, K. See Ohba, H.
Hirai, A. See Yasuoka, H.
Hirai, M. See Sano, S.
Hirai, T. See Takeda, Y.
Hirakis, E. C. See Bornstein, N. S.
Hirao, E. Results of service tests on fused cast Mg-Cr brick for open-hearth furnace roofs, (11) 281*c*.
Hirao, M. See Takeda, Y.
Hirayama, C. Electroluminescent lamp having a moisture resistant vitreous light-transmitting material which includes 4 to 8% LiF, P (3) 78*e*.
Hirayama, C., and Taylor, H. L. Glass composition and thermoelectric element coated therewith, P (1) 5*d*.
Hirose, H., and Wada, Y. Nonohmic conduction in vacuum-deposited SiO films, (11) 298*g*.
Hirota, E., and Yanase, A. Crystalline anisotropy energy in CrO_2, (5) 134*j*.
Hirsch, N. See Mann, J. E.
Hirsch, P. B. See Hall, C. R.
Hirt, T. J. See Maryanowski, C. W.
Hirth, J. P., and Moazed, K. L. Nucleation processes in deposition onto substrates, B (9) 245*e*.
Hirth, L. J. See Clinton, S. D.
Hispano-Suiza-Lallemant. See Societe Hispano-Suiza Lallement.
Hitachi, Ltd. Method of selective diffusion from impurity source, P (3) 79*f*. Semiconductor composition with negative resistance characteristics at extreme low temperatures, P (7) 158*a*. Ultra-high-temperature burners, P (5) 132*h*.
Hitco. Refractory fibers and methods of making them, P (7) 154*e*.
Hiwatari, Y. See Higuchi, M.
Hiyama, H. See Niwa, S.
Hlavacek, J. New batch houses for household glass, (3) 66*c*.
Ho, C. Y. See Powell, R. W.
Ho, R. K. Method of manufacturing and attaching nonelectrolytic tantalum capacitors, P (3) 79*a*.
Hobart Brothers Co. Arc welding with ac power and cored electrode, P (7) 147*h*.
Hochberg, F. See Berkenblit, M.
Hochberg, F., and Reisman, A. Fabrication technique, P (11) 285*b*.
Hochman, H. T. Semiconductor circuit complex having low isolation capacitance and method of manufacturing same, P (10) 265*b*.
Hochstrasser, G. Detection of VO^{2+} in glass by electron spin resonance, (2) 36*h*.
Hocker, J. P. Method of making an electrically heated immersible [ceramic] warming unit, P (10) 264*j*.
Hockings, E. F. See Richman, D.
Hockings, W. A., Volin, M. E., and Muiar, A. L. Effect of suspending-fluid viscosity on batch mill grinding, (4) 103*f*.
Hodenberg, R. F. von. Lead orthophosphate ($Pb_3(PO_4)_2$), $Pb_3(VO_4)_2$, and $Pb_3(AsO_4)_2$, (5) 136*j*.
Hodges, J. R., and Hall, J. N. Spun glass crimper, P (3) 69*g*.
Hodgson, B. P. See McMillan, P. W.
Hodgson, J., and Hall, R. O. Process for milling particulate solids in liquids, P (10) 266*g*.
Hodkinson, J. R. Literature on aerosols, (8) 189*i*.
Hodl, F., and Bouvier, G. Carbon-impregnated refractive magnesia bodies and method of preparing the same, P (2) 43*f*.
Hoekstra, G. W. See Taebel, W. A.
Hoekstra, H. R. See Marshall, R. H.
Hoenig, C. L., and Searcy, A. W. Vapor pressure, enthalpy, evaporation coefficient, and enthalpy of activation of the Be_3N_2 decomposition reaction, (10) 272*j*.
Hoenig, C. L., Stout, N. D., and Nordine, P. C. Knudsen cell studies of the vaporization of gadolinium and gadolinium dicarbide, (9) 240*f*.
Hoenig, D. J. Facing assembly for lens grinding tools, P (9) 219*i*.
Hoenig, S. A. Low cost 1300°C vacuum furnace, (9) 234*i*.
Hoens, M. F. A. See Kreuter, J. C.
Hoens, M. F. A., and Vuyk, J. Improved properties and experiences with direct-on enameling, (1) 2*h*.
Hoffer, J. M. Improvement of the plagioclase glass fusion method, (10) 252*i*.
Hoffman, D. M. Materials heating and handling apparatus, P (11) 288*g*.
Hoffman, G. R. See Hill, A. E.
Hoffman, L. C. Glass frits and enamels having esterified surfaces and their preparation, P (10) 255*e*.
Hoffman, M. V. Fluorescent phosphate glass, P (5) 120*h*. Group II metal-thorium phosphate phosphors, P (8) 184*e*.
Hoffman Electronics Corp. Epitaxial alloy semiconductor devices and process for making them, P (3) 78*f*. Simulation of solar radiation, P (10) 265*e*.
Hoffmann, A. See Emeis, R.
Hoffmann, J. E., and Mantell, C. L. Mechanisms of the codeposition of aluminas with electrolytic copper, (7) 165*c*.
Hoffmann, R. L. Gas-solid chromatography using column comprising $AgNO_3$-coated alumina, P (4) 98*i*.
Hofmann, U. Clay minerals and the plasticity of clays, (5) 134*e*.
Hofmann, U., and Haacke, H. Determination of the kaolinite and mica content of a clay or kaolin, (5) 135*b*.
Hofmann, U., Theisen, R., and Yetmen, Y. Use of the electron microprobe and X-ray analysis in the elucidation of the chemistry of antique ceramics, (3) 63*j*.

Hofstadt, C. E., Ludwig, P. F., and Fahn, R. High-melting glass fibers and method, P (7) 149*e*.
Hofstadter, R. See O'Dell, E. W.; Swinehart, C. F.
Hogg, W. R. Aperture tube structure for particle study apparatus, P (4) 104*k*. See Coulter, W. H.
Hogue, C. H. Role of additives as modifiers, (1) 12*f*.
Hojun Kogyo Kabushiki Kaisha. Production of ion exchangeable substances from montmorillonite clay minerals, P (9) 236*a*.
Holcomb, J. A. Porcelain enamel coating, P (11) 276*b*.
Hollahan, J. R., and Gregory, N. W. Torsion effusion study of the reaction of graphite with oxides of thorium and zirconium, (8) 210*d*.
Holland, F. W. Mold with vacuum transfer apparatus, P (4) 95*f*.
Holland, K. See Ritchie, A. R.
Hollebone, B. R., Morgan, W. A., and Wiles, D. R. Use of molten pyridinium chloride in the treatment of ores of niobium and other refractory metals, (5) 124*a*.
Hollefriend, N. H. Rotary kiln with preheater, P (3) 82*b*.
Hollenbeck, A. J. Method of orienting filaments in incandescent lamps, P (4) 95*c*.
Holley, C. E., Jr. Calorimetry of combustions and related reactions—inorganic reactions, (8) 192*c*. See Huber, E. J., Jr.
Holley, C. E., Jr., Mulford, R. N. R., Huber, E. J., Jr., Head, E. L., Eilinger, F. H., and Bjorklund, C. W. Thermodynamics and phase relationships for plutonium oxides, (4) 112*d*.
Holliday, J. E. Determination of electron distribution and bonding from soft X-ray emission spectroscopy, B (5) 139*g*.
Hollister, R. G. Electrical resistance elements, etc., P (8) 184*a*.
Holloway, D. G. See Johnson, J. W.
Hollowell, G. T. Heated-gas system with apparatus for removing gas-borne foreign bodies, P (5) 124*i*.
Holm, J. L. Phase equilibria in the system CaF_2-AlF_3, (8) 204*j*. Phase transitions and structure of lithium cryolite, (10) 271*a*.
Holmberg, B. Crystal structure of ScOF, (10) 270*c*. See Gado, P.
Holmberg, B., and Dagerhamn, T. X-ray studies on solid solutions of oxygen in α-zirconium, (3) 88*a*.
Holmes, C. L. Precision resistance element and method of making the same, P (9) 226*g*. See Faber, W. M., Sr.
Holmes, W. C., & Co., Ltd., and United Steel Co., Ltd. Furnace joint, P (9) 234*j*.
Holmquist, S. B. Reply to comment on "Hydrothermal silica transformations," (1) 17*e*. Thermal reactions between sodium sulfite and silica, (8) 176*j*.
Holonyak, N., Jr. See Stillman, G. E.
Holonyak, N., Jr., Nuese, C. J., Sirkis, M. D., and Stillman, G. E. Effect of donor impurities on the direct-indirect transition in $Ga(As_{1-x}P_x)$, (5) 135*g*.
Holowaty, M. O. See Gaffney, L. J.
Holscher, H. H. Hollow and Specialty Glass—Background and Challenge, B (8) 212*b*.
Holschlag, J. B. Apparatus for the production of continuous glass fibers, P (5) 120*a*. See Day, F.; Russell, R. G.
Holt, J. B. See Condit, R. H.
Holt, J. B., and Condit, R. H. Oxygen-18 diffusion in surface defects on MgO as revealed by proton activation, B (2) 61*c*.
Holt, J. P., and Cash, T. P. Magnesia-zircon refractories, P (5) 124*c*.
Holt, J. P., Day, H. P., and Cash, T. P. Formulations for gunning refractories, P (10) 259*i*.
Holtz, F. C., and Parikh, N. M. Tools of the future, (2) 33*j*.
Holtzberg, F., and Methfessel, S. J. Ferromagnetic intermetallic compounds and method of preparation, P (9) 230*j*.
Holzwarth, W. Heat-resistant structural element, etc., P (3) 64*e*.
Homer, H. H. See Bouchard, G. H.
Homma, K. See Matsuo, S.
Honeywell, Inc. Beryllide coating for beryllium, P (4) 92*d*. Colorimeter employing tristimulus values, P (8) 188*a*. Humidity sensing apparatus, P (1) 14*c*. Process for producing dense ceramic of lead zirconate-titanate, P (5) 128*i*. Thermocouple comprising intimately twisted wires, P (8) 188*h*. Tunnel diodes, P (7) 158*b*.
Honig, E. P. See Ketelaar, J. A. A.
Honig, J. M. See Rogers, D. B.
Honjo, G. See Harada, J.
Honjo, G., Shinozaki, S., and Sato, Hiroshi. Direct observation of the epitaxial growth of silver on magnesium oxide, (8) 183*h*.
Hood, J. S., Jr. See Currin, C. G.
Hood, J. T. See Booe, J. M.
Hoogendoorn, H. M., and Merrin, S. Glasses for encapsulating semiconductor devices, P (5) 127*f*.
Hoornstra, C. W., and Handt, P. R. Inhibition of corrosivity of sulfuric acid on carbon steel, P (8) 174*j*.
Hoover, W. See Metrailer, W. J.
Hope, A. J. N. See Davy, J. R.
Hori, A. See Mishima, S.
Horibe, T., and Kuwabara, S. Preliminary study of phase equilibria in the Al_2O_3-Ti_2O_3 system, (1) 27*a*.
Horie, T. See Iwai T
Horiuchi, S., and Yamaguchi, J. Evaluation of surface states at Si-SiO_2 interface from the characteristics of *p*-type MOS diodes, (11) 295*b*.
Horiuchi, S., Yamaguchi, J., and Shibata, K. Evaluation of surface states at oxidized silicon from the characteristics of surface varactor diode, (11) 295*a*.
Horizons, Inc. Controlled particle size $BaTiO_3$, P (3) 77*k*. Foamed ceramic, P (10) 259*h*. Glass bead making apparatus, P (11) 278*g*. Preparation of inorganic oxide monofilaments, P (7) 153*f*. Process for preparing alumina wool, P (11) 282*f*.
Horlock, R. F. See Anderson, P. J.
Horn, A. J. See Weichselbaum, T. E.
Horn, H. C. See Malissa, H.; Obst, K. H.
Horn, H. F., and Aldrian, A. F. Methods and devices for applying coatings by vaporization, P (9) 233*a*. Process for the vapor deposition of material without thermal radiation of the substrate, P (10) 265*a*.
Hornung, G. See Salt, D. J.
Hornung, H. J. See Zook, J. D.
Hornyak, E. J., Jr., See Baak, T.
Horsting, C. W. Germanium-silicon thermoelement having fused tungsten contact, P (11) 285*f*.
Horstmann, G. See Mohn, H.
Horton, A. T. See Deslattes, R. D.
Horton, R. A. Method of removing patterns from investment molds, P (11) 282*g*.
Horton, R. M. See Hanson, C. K.
Horton, T. P., and Capshaw, L. E. Art of filtration, P (2) 49*i*.
Horvath, J. W. See Osborn, O.
Hosaka, S. See Imai, H.
Hosek, J. Properties of cement mortars modified by polymer emulsion, (4) 91*c*.
Hosford, W. F., Jr., Chao, H. C., and Van Vlack, L. H. Shape change produced by compression of NaCl crystals along [011], (9) 242*f*.
Hoshino, M. See Ikeda, Y.
Hosler, W. R. See Frederikse, H. P. R.
Hospel, P. A. M. Planar semiconductor device with improved emitter and base configuration, P (10) 265*e*.
Hossfeld, F. Systematic error of intensity measurements due to continuous recording, (3) 81*g*.
Hough, R. L. Ablative reinforced plastic article and method of making same, P (9) 225*j*. See Prickett, R. L.; Starks, D. F.
Hounslow, A. W., and Moore, J. M., Jr. Chemical petrology of Grenville schists near Fernleigh, Ontario, (8) 192*h*.
Housh, L. M. See Alder, W. R.
Howard, C. J. See Copson, R. L.
Howard, J. D., and Henry, V. J., Jr. Sampling device for semiconsolidated and unconsolidated sediments, (1) 14*d*.
Howard Aiken Industries. Automatic +X-axis detector, marker, sorter, and collector for [quartz] crystal wafer blanks, P (8) 184*a*.
Howell, B. Raul Angulo Coronel, (4) 90*a*.
Howells, W. P. Research and trouble shooting, (4) 112*i*.
Howie, A. See Fujimoto, F.
Howie, R. A. See Deer, W. A.
Howie, R. A., and Smith, J. V. X-ray-emission microanalysis of rock-forming minerals (V) orthopyroxenes, (10) 272*e*.
Howles, D. A. See Wright, J. W. T.
Howmet Corp. Method of making shell molds for casting reactive metals, P (9) 226*h*. Method of preparing an investment mold for use in precision casting, P (4) 98*f*. Method for shaping beryllium and other metals and ceramics, P (5) 124*e*.
Hradecky, Z. Preparation of the glass batch by cement granulating methods, (3) 66*e*.
Hribar, V. F. See Epstein, G.
Hryniszak, W. Ceramic heat-resisting materials, (2) 36*c*.
Hsiao, C. See Darrow, W. L.
Hsu, S. E., Kobes, W., and Fine, M. E. Strengthening of sapphire by precipitates containing titanium, (4) 110*j*.
Hu, S. M., Kerr, D. R., and Gregor, L. V. Evidence of hole injection and trapping in silicon nitride films prepared by reactive sputtering, (10) 262*j*.
Hu, Teh, Ko, Hon Chung, and Hepler, L. G. Calorimetric investigations of molten salts, (8) 192*a*.
Huang, Suei-rong, and Johnson, E. R. Radiation-induced decomposition of some inorganic sulfates, B (9) 244*f*.
Huang, W. H., and Johns, W. D. Simultaneous determination of fluorine and chlorine in silicate rocks by a rapid spectrophotometric method, (8) 188*b*.
Hubbard, W. N. See Rudzitis, E.; Settle, J. L.
Hubble, D. H. See Kappmeyer, K. K.; Lamont, J. A.
Hubble, D. H., and Powers, W. H. Method of making magnesium oxide fibers, P (9) 226*c*.
Hubble, D. H., and Russell, C. K. Refractory composition and method of preparation, P (1) 8*c*.
Huber, E. J., Jr. See Holley, C. E., Jr.
Huber, E. J., Jr., Fitzgibbon, G. C., and Holley, C. E., Jr. Heat of formation of europium sesquioxide, (8) 199*i*.
Huber, J. M., Corp. Clay bleaching under nonoxidizing atmospheres, P (8) 190*c*. Reactive selectively sorptive silica materials and process of producing them, P (9) 236*d*. Reactive silica materials and process, P (9) 236*e*. Stabilized pigment slurries, P (3) 83*e*.
Huckle, W. G., Swigert, G. F., and Wiberley, S. E. Cadmium pigments, (2) 45*j*.
Hudcova, A., and Janku, V. Problems of SnO_2 replacement in opaque glazes for sanitary ware, (10) 261*f*.
Hudock, P. High-mobility PbS and CdS films deposited under ultrahigh vacuum equilibrium conditions, (10) 262*d*.
Hudson, R. M., and Riedy, K. J. Embrittlement-free pickling of ferrous metal, P (7) 147*i*.
Hudson, W. H. Manufacture of cathode ray tubes for color television, P (8) 177*i*.
Huebner, F. New homogeneous vaporizer unit for rapid drying of ceramic batches, (2) 52*h*. Thermal treatment of ceramic bodies and their hot storage, (3) 70*c*.
Huelsenberg, D. Determination of the thermal softening behavior of silica brick, (3) 71*c*.
Huettemann, E. Process for the manufacture of a thermohydraulically bonded high density concrete product, P (4) 91*f*.
Huffaker, E. M. See Adams, M. F.
Huggett, L. G. Radial deformation in rotary kilns, (9) 234*i*.
Huggins, H. W., and Pitt, C. H. Characteristics of silicon carbide produced by thermal decomposition of trimethylchlorosilane, (4) 96*g*.
Hughes, B. P., and Bahramian, B. Laboratory test for determining the angularity of aggregate, (9) 214*g*.
Hughes, B. P., Lowe, I. R. G., and Walker, J. Diffusion of water in concrete at 50° to 95°C, (3) 64*b*.
Hughes, E. W. Electrophoretic deposition for porcelain enamels, (4) 91*i*.
Hughes, F. H. Prepare diamond wheels properly for profits, (11) 273*g*.
Hughes, G. See Gilbert, W.
Hughes, H. Formation of alkali silicates and aluminosilicates and their occurrence in blast furnaces, (5) 122*j*.
Hughes, R. C. See Bronnes, R. L.
Hughes, W. Production of pigment from conditioned and calcined titanium dioxide particles, P (11) 292*a*.
Hughes, W., and Haigh, H. E. Treatment of particulate solids, P (5) 133*h*.
Hughes Aircraft Co. Bonding process, P (4) 100*g*. Cathode ray tube mesh assembly supported between envelope sections, P (2) 47*i*. Controllable ferrite phase shifter having means to cool the ferrite, P (11) 285*b*. Epitaxial method for the production of microcircuit components, P (9) 230*f*. Housed semiconductor device with thermally matched elements, P (10) 264*d*. Method for making an electrical capacitor, P (9) 231*e*. Method of manufacturing semiconductor devices, P (9) 231*i*. Method for the preparation of gallium phosphide, P (5) 128*f*. Method for preparing a gallium arsenide diode, P (5) 128*g*. Method for producing a boron diffused silicon transistor, P (2) 48*c*. Thin film heterojunction device, P (10) 265*i*. Thin film negative resistance device, P (8) 186*c*. Top contact for surface protected semiconductor devices, P (11) 288*c*.
Hughes Tool Co. Method of preparing W_2C containing a fine dispersion of carbon, P (7) 153*c*.
Hughey, V. V. Process for dead-burning dolomite, P (5) 124*j*.
Hughson, R. V. Controlling air pollution, (2) 49*h*.
Huizing, A. See Kwestroo, W.
Hukuo, N., Kozuka, T., Fujishiro, I., and Yoshida, M. Calculation of radiant flux density through the focal zone of a solar furnace—effects of limb darkening of the sun, (5) 134*h*. Measurement of brightness temperature by a photomultiplier, (5) 131*f*.
Hukuo, N., Kozuka, T., Fujishiro, I., Yoshida, M., and Irisawa, T. Measurement of radiant flux density through the focal zone of a solar furnace, (5) 137*c*.
Hulbert, S. F., and Klawitter, J. J. Kinetics and mechanism of the reaction between zinc oxide and barium carbonate, (10) 271*b*.
Hull, D. E. See Bowman, M. G.
Hull, E. H. See Darrow, K. A.
Hull, E. M. Epitaxial growth of homogeneous solid solutions of GaAs-GaP, (7) 163*b*.
Hull, R. W. See Tibol, G. J.
Hullhorst, W. B., and Lockett, P. F. Packaging compressible material, P (9) 221*j*.
Hulliger, F. Superconducting compositions, P (4) 102*h*.
Hultgren, R. R. Interatomic forces and chemical bonding energies, B (9) 244*d*.
Humes, W. W. Pivoted glass sheet bending mold, P (1) 6*c*.
Hummel, F. A. See Brown, J. J.
Humphrey, D. E., Shapiro, L., and Wilder, P. W., Jr. Centrifuge having frustoconical screen with means to improve screen life, P (8) 186*f*.
Hund, F., Koller, H., Raede, D., Quast, H., and Ganter, K. W. Iron oxide pigments containing manganese, P (1) 15*h*.
Hunsberger, J. F., and Tucker, D. J. Method of impregnating lubricant into abrasive wheels, P (9) 213*h*.
Hunt, J. D. See Jackson, K. A.
Hunt, J. D., and Jackson, K. A. Binary eutectic solidification, (7) 162*d*.
Hunter, O., Jr., and Brownell, W. E. Thermal expansion and elastic properties of two-phase ceramic bodies, (2) 58*h*.

Hunter, R. E. Rapid method for determining weight percentages of unsieved heavy minerals, (10) 267*f*.
Hurka, R. J., Jr., See Carothers, J. N.
Hurley, E. B., Smith, E. L., and Kitaj, W. Glass fiber binder, P (9) 220*c*.
Hurley, F. R. See Acker, E. G.; Angstadt, R. L.
Hurley, F. R., Tecotzky, M., and Vanik, M. C. Aqueous thoria-urania sol, P (9) 225*a*.
Hurwitz, C. E. Efficient ultraviolet laser emission in electron-beam-excited ZnS, (10) 271*a*. Efficient visible lasers of CdS_xSe_{1-x} by electron-beam excitation, (8) 196*a*. Electron-beam pumped lasers of CdSe and CdS, (5) 135*h*. High power and efficiency in CdS electron beam pumped lasers, (9) 229*c*.
Hurwitz, M. J., and Aschkenasy, H. Dewatering aqueous suspensions, P (2) 50*b*.
Husa, V., Cihelka, J., Cerny, L., Kriz, J., Ladnar, J., and Luxa, F. Integrated two transistor semiconductor device, P (8) 184*i*.
Husain, S. F. A. See Trew, V. C. G.
Husher, J. D., and Pollock, L. J. Switching transistor structure and method of making the same, P (11) 288*a*.
Husni, S. Y. Superconductive articles, P (11) 287*i*.
Hussain, S. See Narasimhalu, K.
Hussey, R. J., and Smeltzer, W. W. Mechanism of oxidation of zirconium in the temperature range 400° to 850°C, (7) 165*b*. Reaction of zirconium with carbon dioxide and carbon monoxide at 850°C, (11) 300*h*.
Hutcheson, R. L. Crystal growing furnace with an alumina liner, P (2) 52*f*.
Hutchins, G. A. See Perry, F. W.
Hutchison, W. R. See Cartwright, J. K.
Hutchison, W. W. Two stages of decrepitation of micas, (7) 169*f*.
Hutson, C. See Black, H. R.
Huxley, A. S. See Billington, E. W.
Huzimura, R., Ato, Y., and Oishi, M. Radioactive self-luminous compounds (V) trapping center and cross section of excitation, (7) 167*c*.
Hyatt, E. P., Long, S. A., and Rose, R. E. Sintering high purity $BaTiO_3$, (9) 230*a*.
Hyde, J. See Cope, G. R.
Hyde, K. R. See Fletcher, J. M.
Hydrand Corp. Method of reclaiming calcined kaolin from de-inking sludge residue, P (8) 190*d*.
Hylak, P. J. Method for sealing pipe and method for preparing composition useful therein, P (5) 116*f*.
Hynd, W. C. Manufacture of wired glass, P (5) 120*g*.

I/S Kahler & Co. Mineral wool producing system and method, P (5) 121*b*.
I-T-E- Circuit Breaker Co. Ceramic arc plates having minimum density variations, P (2) 47*i*.
Iacobelli, R., and Moretti, S. Thermal diffusivity and conductivity measurements on metals and oxides at high temperatures, (2) 51*i*.
Iannicelli, J. See Maynard, R. N.
Iannucci, A. See Class, W.
Ibraimov, M. I., and Lebedkova, A. A. Prospects for developing refractory raw materials in the Angren deposit, (5) 133*c*.
Ichikawa, M. See Yokobori, T.
Ichikawa, W. Aqueous metal iodide solution for use as an X-ray contrast agent, P (8) 188*a*.
Ichimura, S. See Kajikawa, Y.
Ichinose, N., and Kurihara, K. New ferrimagnetic compound, (7) 166*b*.
Iga, T. See Okuda, H.
Ignatova, L. I., Karpova, L. N., and Zhil'tsova, I. G. Synthesis of minerals of the aluminophosphate group, (8) 208*g*.
Ignatova, T. S., Flyagin, V. G., and Chukreeva, E. I. Increasing the life of ladle brick, (7) 151*c*.
Ignatova, V. A. See Artamonova, N. V.
Iida, S. Electrical properties of nonstoichiometric uranium dioxide, (11) 294*b*. Electrical property of uranium dioxide, (9) 238*h*. See Maeda, K.; Miyamoto, S.; Miyatani, K.; Okada, T.
Iida, S., and Sugita, Y. GaAs whisker crystals containing a germanium core, (5) 136*e*.
IIT Research Institute. Brake lining materials and articles made therefrom, P (7) 153*a*.
Ikeda, T. See Fushimi, S.; Iwasaki, H.
Ikeda, T., and Fushimi, S. Preliminary study on the growth of lead zirconate-titanate crystals, (3) 87*f*.
Ikeda, Y., Hoshino, M., and Kuroki, H. Glass capacitors having a chrome oxide layer on the electrodes, P (1) 10*g*.
Ikeda, Y., Hoshino, M., and Tokumoto, Y. Glass capacitor, (1) 3*j*.
Ikeda, Y., and Murai, J. Ceramic type electroluminescent lamp, (1) 9*h*.
Ikegami, S. See Ueda, I.
Ikegami, S., Ueda, I., Kisaka, S., Mitsuishi, A., and Yoshinaga, H. Far infrared reflectivity of $BaTiO_3$, (3) 85*i*.
Ikushima, H. See Hayakawa, S.
Ikushima, H., and Hayakawa, S. Electron spin resonance of Mn^{3+} in $BaTiO_3$, (8) 196*d*.
Ilikon Corp. Method of heating and forming powdered metals, P (10) 259*g*.
Il'ina, N. I. See Federov, P. I.
Il'ina, N. V., Belyaev, A. K., Zakharenkov, V. K., and Skoblo, L. I. Testing of chamotte concrete with sodium silicate binder in a large-diameter kiln, (9) 215*c*.
Ilschner, B. See Reppich, B.
Il'yasov, I. I., and Bergman, A. G. System comprising the chlorides and bromides of sodium and cadmium, (8) 208*c*.
Il'yasov, I. I., and Dionis'ev, S. D. System Na,Tl, ·Pb‖ I, (11) 301*h*.
Il'yasov, I. I., Dionis'ev, S. D., and Bergman, A. G. Reciprocal system of bromides and iodides of potassium and lead, (7) 167*h*.
Im, H. B. See Wickham, D. G.
Imagawa, H. See Yokota, R.
Imai, A. Free carrier absorption in *n*-type SiC, (8) 198*f*.
Imai, H. See Oomori, K.
Imai, H., Hosaka, S., and Naito, K. Preparation of thorium carbides, (7) 152*b*.
Imaoka, M. Glass formation range (I) borate systems, (2) 36*f*.
Imaoka, M., and Yamazaki, T. Glass formation range (II) silicate systems, (2) 36*g*; (III) germanate systems, (5) 119*a*. Properties and structure of glasses of the B_2O_3-GeO_2 system, (7) 148*c*.
Immergut, E. H. Polymeric materials—synthesis-structure-properties, B (9) 244*e*.
Imperial Chemical Industries, Ltd. Agitation process, P (7) 158*h*. Cementing compositions, P (3) 64*d*. Coating process, P (1) 12*e*. Manufacture of finely divided silica, P (5) 133*b*. Method of chemically strengthening glass, P (8) 177*i*. Process for protecting glass against loss of mechanical strength, P (5) 121*g*. Process for reducing particle size, P (1) 13*b*. Process for strengthening glass, P (8) 178*i*. Silicon compcunds, P (4) 99*b*. Treatment of glass, P (10) 256*b*.
Imre, L. See Gado, P.
Imris, D. See Imris, P.
Imris, P., and Imris, D. Reflection spectra of UO_2 prepared from U_3O_8 calcined under various conditions, (8) 206*b*.
Inagaki, K., and Morikawa, H. Thermal change of corundum particles in Corhart refractories, (7) 152*e*.
Inagaki, K., and Torii, T. Behavior of Fe_2O_3 on heating in refractory bodies of the system kaolin-quartz-talc-Fe_2O_3, (8) 191*d*. Effect of heat treatment on mullite containing Fe_2O_3 as a mixture or solid solution, (8) 195*a*.
Indenbom, V. L. Internal stress in crystals, B (4) 114*b*. Theory of dislocations—present state and future, B (4) 114*b*.
Indenbom, V. L., and Vidro, L. I. Structural and thermoplastic stresses in inorganic glasses, B (7) 171*k*.
Indevco, Ltd. Sinter coating method and apparatus, P (10) 250*g*.
Indugas, Gesellschaft fuer Industrielle Gasverwendung m.b.H. Industrial gas burner, P (2) 53*c*.
Industrie-Companie Kleinewefers Konstruktions- und Handelsgesellschaft. Method of operating a heat exchanger composed of a ceramic recuperator and a metallic recuperator, P (8) 189*c*.
Ing, S. W., Jr., and Davern, W. Glow discharge formation of silicon oxide and the deposition of silicon oxide thin film capacitors by glow discharge techniques, (9) 229*i*.
Ingebrigtsen, K. A., and Tonning, A. Numerical data for acoustic surface waves in α-quartz and cadmium sulfide, (8) 203*h*.
Ingham, H. S., Jr. Flame spraying employing laser heating, P (7) 147*j*.
Ingleby, B. E. Nuclear fuel body containing uranium carbide spheroids coated with silicon carbide, P (1) 8*g*. Process for fabricating a fission product retentive nuclear fuel body, P (3) 72*f*.
Ingles, T. A. Dielectric strength, (11) 284*j*.
Inland Electronic Products Corp. Glass-to-metal seals in electronic devices, P (5) 127*e*.
Inman, D., Regan, I., and Girling, B. Complex ions in molten salts—computer method for the calculation of stability constants from metal-ion concentration data, (8) 192*e*.
Inman, M. C. Application of transmission electron microscopy to studies of relative interfacial energies in solids, B (2) 61*e*.
Innes, W. B. Oxidation catalyst for hydrocarbon combustion exhaust gases, P (2) 44*j*.
Inoue, A. See Shiraki, Y.
Inoue, K. Method of making diamond-faced articles, P (5) 115*i*.
Inoue, M. Tripyramid growth of epitaxial silicon, (9) 242*j*.
Inoue, T. See Watanabe, Y.
Insolio, T. A. Glass cutter, P (1) 5*e*.
Institut fuer Warmetechnik und Automatisierung der Silikathuetteninduatrie. Apparatus for cooling cement clinker or the like, P (1) 2*c*.
Institute of Gas Technology. Method for sealing pipe and method for preparing composition useful therein, P (5) 116*j*.
Instytut Chemii Ogolnej. Methods of homogenizing liquid suspensions of argillaceous raw materials, P (2) 54*e*.
Insulations (Malaya), Ltd. Manufacture of insulating slabs, P (7) 153*g*.
Interlake Steel Corp. Refractory-lined blast furnace tuyere, P (11) 283*e*.
Intermetall Gesellschaft fuer Metallurgie und Elektronik m.b.H. Manufacture of semiconductor assemblies, P (5) 127*i*.
Intermountain Research & Development Corp. Continuous recycle heating process for the production of soda ash and alkali metal phosphates, P (11) 291*e*. Densification of soda ash by vapor hydration, P (7) 160*i*.
International Business Machines Corp. Arc process for forming high melting point compounds, P (9) 230*g*. Coating of aluminum substrates with a magnetic material, P (9) 230*y*. Comminution of glass, P (8) 176*i*. Coupled helical wave structure employing a remanently magnetized ferrite, P (7) 156*b*. Coupled semiconductor injection laser devices, P (5) 127*f*. Cryogenic Hall-effect semimetal electronic element, P (5) 127*f*. Electrical resistance composition and method of using the same to form a resistor, P (11) 285*f*. Fabrication of cermet film resistors to close tolerances, P (7) 156*d*. Fabrication of semiconductor devices, P (1) 10*d*. Fabrication technique, P (11) 285*b*. Ferromagnetic intermetallic compounds and method of preparation, P (9) 230*f*. Glasses for encapsulating semiconductor devices and resultant devices, P (5) 127*f*. High capacitance device, P (1) 10*h*. Intermetallic semiconductor body and method of diffusing an *n*-type impurity thereinto, P (8) 184*i*. Lasers, P (5) 120*f*. Magnetic control of film deposition, P (9) 231*c*. Method and apparatus for cathode sputtering including suppressing temperature rise adjacent the anode using a localized magnetic field, P (10) 264*g*. Method and apparatus for growing [two-component] crystals, P (11) 286*e*. Method of bonding, P (4) 101*b*. Method of covering the surfaces of objects with protective glass jackets and the objects produced thereby, P (4) 101*c*. Method of making a capacitor with a multilayered ferroelectric dielectric, P (5) 128*a*. Method of manufacturing multilayer microcircuitry including electropolishing to smooth film conductors, P (8) 185*i*. Method of modifying electrical characteristic of semiconductor member, P (10) 264*g*. Method of preparing fluorescent rare earth compounds, P (3) 83*f*. Method of pulling monocrystalline silicon carbide, P (1) 8*e*. Method of selectively coating semiconductor chips, P (1) 11*k*. Method for the synthesis of gallium phosphide, P (4) 102*f*. Methods of improving electrical characteristics of semiconductor devices and products so produced, P (5) 128*b*. Methods of producing single crystals on polycrystalline substrates and devices using same, P (10) 265*a*. Microelectronic capacitor material and method of fabrication, P (3) 79*h*. Nondestructive readout magnetic memory, P (11) 287*c*. Photoelectronic semiconductor devices comprising an injection luminescent diode and a light sensitive diode with a common *n* region, P (2) 48*i*. Preparation of gallium arsenide with controlled silicon concentrations, P (9) 231*h*. Preparing group II-VI compound semiconductor devices, P (9) 231*i*. Process for cathodically sputtering a ferromagnetic thin film of a nickel-iron-molybdenum alloy, P (5) 128*f*. Process for cathodically sputtering magnetic thin films, P (5) 128*g*. Process of coating, using a liquid metal substrate holder, P (3) 79*b*. Process for epitaxial growth of semiconductor single crystals, P (4) 102*h*. Process for fabricating reproducible photoconductors, P (10) 265*g*. Semiconductor compound crystals, P (5) 129*a*. Semiconductor devices and their fabrication, P (8) 186*c*. Semimetal *pn* junction devices, P (5) 129*f*. Silicon carbide semiconductor device, P (5) 129*a*. System for measuring kiln conditions using thermocouples in combination with a mathematical model, P (1) 14*f*. Ternary semiconductor compounds and method of preparation, P (5) 129*c*. Thin film transistor, P (2) 49*c*. Thin film transistor and method of fabrication, P (2) 49*d*. Tunnel diode with tunneling characteristic at reverse bias, P (1) 12*a*.
International Combustion (Holdings), Ltd. Pulverized fuel-fired furnaces, P (3) 82*a*.
International Commission on Glass, Sub-Committee AI. Dictionary of Glass-Making; Dizionario di Terminologia Vetraria, B (11) 304*k*; Vocabulario Vitrotecnologico, B (11) 304*i*.
International Diamond Products, Ltd. Apparatus for grinding brick or the like, P (3) 70*f*.
International Minerals & Chemical Corp. Refractory composition and body, P (9) 227*d*. Refractory compositions and method for preparing same, P (8) 182*c*.
International Nickel Co., Inc. Brazing of ceramics and palladium-nickel-titanium brazing alloy therefor, P (1) 10*g*.
International Nickel Co., Ltd. Refractory lined vessels, P (5) 125*b*.
International Pipe & Ceramics Corp. Edge trim element for ceramic wall construction, P (7) 155*c*. Method of treating quartz sands, P (2) 54*d*.
International Product Design & Research Corp. Sheet metal kiln stilt, P (9) 235*c*.
International Rectifier Corp. Compression bonded semiconductor device, P (9) 230*a*. Controlled rectifier having shunted emitter formed by a nickel layer underneath an aluminum layer, P (4) 100*j*. Field effect transistor with concentric interior electrode, P (3) 78*j*.
International Resistance Co. Glass composition and electrical resistance material made therefrom, P (1) 10*g*.
International Standard Electric Corp. Electrolytic capacitor with dielectric film formed on ceramic material, P (10) 263*g*. Method of masking semiconductor and etching beneath mask, P (5) 128*d*. Method of passivating semiconductor devices, P (4) 102*b*. Method of sealing contact reeds in a glass tube, P (2) 39*b*. Process for

passivating planar semiconductor devices, P (7) 157*g*. Semiconductor device having *pn* junction defined by the boundary between two intersecting semiconductor layers, P (11) 287*d*. Solid state image converting display device, P (11) 287*k*. Stackable semiconductor rectifier element having seals under compressive stress, P (3) 79*g*.

International Telephone & Telegraph Corp. Bonded contacts for gold-impregnated semiconductor devices, P (4) 100*g*. Ferromagnetic materials and methods of fabrication, P (3) 78*i*. Printing cathode ray tube using photoconductive layer, P (1) 11*b*. Process for the determination of diffusion profiles in semiconductor bodies, P (5) 128*g*. Tunnel-effect semiconductor system with capacitative gate across edge of *pn* junction, P (7) 158*b*.

Inuishi, Y. See Edagawa, H.; Ishida, A.

Ioffe, A. V., Kuznetsov, V. G., and Palkina, K. K. Thermal conductivity and magnitude of the effectiveness Z of solid solutions of the systems Bi_2Se_3-Sb_2Te_3 and Bi_2Te_3-Sb_2Se_3, (2) 57*i*.

Ion Physics Corp. Semiconductor resistor containing interstitial and substitutional ions formed by an ion implantation method, P (11) 287*f*.

Iowa Mfg. Co. Gas hydraulic spring for crushing apparatus, P (8) 190*e*.

Ippolitova, E. A. See Kovba, L. M.

Irby, B. N. See Dugger, D. L.

Ireland, R. W. Fluorescent lamp bulb spiral groove forming device, P (10) 255*c*.

Irie, T. See Sato, K.

Irisawa, T. See Hukuo, N.

Irvine, W. R. See Armstrong, W. M.

Irwin, W. T., and Drummond, W. W. Process of making fibrous product, P (8) 178*h*.

Irwin, W. T., and Searles, J. H. Fiber glass mat and method of making same, P (11) 278*e*.

Ishibashi, E. Ultra-high-temperature burners, P (5) 132*h*.

Ishida, A., and Inuishi, Y. Current oscillations and high field domains in dark conductive CdS crystals, (3) 75*i*.

Ishido, Y. See Fujii, K.

Ishii, E. See Sano, S.

Ishii, T. See Takeya, G.

Ishijima, I. See Shimizu, Y.

Ishikawa, Y. Superparamagnetism in the $ZnFe_2O_4$-$NiFe_2O_4$ system, (5) 138*h*. See Syono, Y.

Ishikura, O. See Kaga, M.

Ishiwara, S. Service test on graphite containing fireclay brick forming a ladle bottom, (9) 224*g*.

Ishizuka, H. Method for synthetically making diamond, P (10) 247*g*.

Isomet Corp. Fuel cell, P (1) 10*e*. Method of separating hafnium from zirconium, P (1) 15*i*.

Israel Mining Industries—Institute for Research and Development. Sink-float method of classifying wet flocculated solid particles, P (7) 161*d*.

Isupova, E. N., and Keler, E. K. Interactions in the BaO-BeO system, (4) 108*i*. Interactions in the system BaO-BeO-SiO_2, (4) 108*a*.

Ito, J. See Watanabe, M.

Ito, U. Fluxing materials for graphite crucibles, (2) 41*g*. Studies of the manufacture of graphite crucibles (II) composition for graphite crucibles consisting of graphite, silicon carbide, ferrosilicon, borosilicate glass, and fluoride, (7) 152*j*.

Itoh, K. See Miyata, N.

Ivakhin, S. I., Ivakhina, L. A., Leshchenko, N. P., and Gress, R. I. Increasing the effectiveness of coarse grinding of feldspar, (8) 189*g*.

Ivakhina, L. A. See Ivakhin, S. I.

Ivanov, A. O. Investigation of the minimum conductivity effect in germanate glasses, B (9) 245*j*. See Evstrop'ev, K. K.

Ivanov, A. O., Evstrop'ev, K. S., and Dorokhova, M. L. Electrical conductivity of sodium and potassium germanate glasses, B (4) 113*b*.

Ivanov, A. O., and Galant, E. I. Electrical conductivity of alkali silicate and borosilicate glasses containing oxides of gallium and iron, B (4) 113*b*.

Ivanov, I. A. Influence of the gas phase on the firing of magnesite (compositions of fuel combustion products), (4) 97*d*.

Ivanov, V. A. See Danilkin, V. I.

Ivanov, V. E., Nechiporenko, E. P., and Zmii, V. I. Reaction diffusion in the system Mo-Si, (4) 109*b*.

Ivanov, V. E., Nechiporenko, E. P., Zmii, V. I., Glushko, P. I., Aleksandrov, O. M., and Dorokhov, V. I. High temperature oxidation of molybdenum disilicide, (4) 108*d*.

Ivanov, V. I., Pletenetskii, G. E., and Nechiporenko, E. P. Effect of highly refractory oxides on the thermal emf of tungsten, molybdenum, and tantalum in vacuum at 1500°C, (7) 151*i*.

Ivanov, Yu. E. See Mironov, V. E.

Ivanova, L. V. See Kruchinin, Yu. D.

Ivanova, Z. N. See Lande, P. A.

Iverson, H. G., and Singleton, E. L. Reactions of manganese with silica, (8) 206*a*.

Iwai, T., and Horie, T. Effect of heat treatment on WO_3 single crystal (II) green stripes, (3) 85*a*.

Iwaiya, Y. See Atsukawa, M.

Iwasaki, H. System $(1-x)NaNbO_3$-$xKTaO_3$, (4) 111*k*.

Iwasaki, H., and Ikeda, T. Studies on the system $Na(Nb_{1-x}Ta_x)O_3$, (5) 138*c*.

Iwata, N. See Goto, E.

Izmailova, L. E. See Bartenev, G. M.

Izui, K. Fission fragment damage in semiconductors and ionic crystals, (11) 295*i*.

Izumi, H. Bilaterally bistable semiconductor device, P (2) 47*h*.

Jablonsky, S. P. See Kotelnikov, G. R.

Jaccodine, R. J., and Drum, C. M. Extrinsic stacking faults in silicon after heating in wet oxygen, (5) 136*c*.

Jach, J., and Griffel, M. Thermal decomposition of irradiated nickel oxalate, (8) 209*g*.

Jache, A. W. See White, W. E.

Jack, H. R. S., and Wilde, D. Developments in material handling and mixing for the glass industry, (5) 118*c*.

Jackson, C. B. Process for preparing superoxides, P (3) 73*a*. See Burke, O. W., Jr.

Jackson, D. A., Jr., and Leidheiser, H., Jr. Very rapid oxidation of aluminum at room temperature when in contact with mercuric iodide, (3) 77*g*.

Jackson, K. A. See Hunt, J. D.

Jackson, K. A., and Hunt, J. D. Lamellar and rod eutectic growth, (7) 165*b*.

Jackson, K. A., Uhlmann, D. R., and Hunt, J. D. Nature of crystal growth from the melt, (9) 241*c*.

Jackson, R. E., and Culp, J. D. Method of making refractory metal structures with an oxidation resistant coating, P (4) 92*b*.

Jacobs, D. A., and Duke, J. B. Grinding method, P (8) 190*e*.

Jacobs, I. S. See Bloch, D.

Jacobs, L. See Bittner, H. J.

Jacobs, L. J. Plastic refractory compositions, P (2) 44*j*.

Jacobs, P. F. See Nies, N. P.

Jacobs, P. W. M., and Maycock, J. N. Thermoelectric power of ionic crystals (III) heats of transport for potassium chloride, (2) 58*g*.

Jacobsen, A. See Dislich, H.

Jacobson, H. W. Process of forming protective coatings on columbium and tantalum using a fluidized bed, P (5) 117*f*. Protected columbium or tantalum article, P (5) 117*g*.

Jacopini, C. M. Process and apparatus for cooling, solidifying, mixing, and extruding initially liquid or semiliquid materials of low thermal conductivity, P (7) 158*h*.

Jaeger, H. See Kus, R.

Jaenicke, W., Leistikow, S., and Stadler, A. Mechanical stresses during the oxidation of copper and their influence on oxidation kinetics (III), (7) 165*i*.

Jaffe, J. See Clifford, A. F.

Jaffe, M. S., and Fridrich, E. G. Flexible electroluminescent device and light transmissive electrically conductive electrode material [indium oxide] therefor, P (8) 184*c*.

Jaffe, P. M. Processing of electroluminescent phosphors, P (5) 128*j*.

Jaffee, R. I. See Bradley, E. F.

Jahn, W. Investigations of the violet coloration of phosphate glasses containing titania, (10) 252*j*.

Jahoda, J. A. See Erdmann, J. C.

Jain, L. C., Hajela, R. B., and Ahmed, F. U. Brick from murram or red soils of Hyderabad, (8) 179*d*. Efflorescence and salt retention in clay products, (2) 40*e*.

Jain, V. K. See Doss, R.N.

Jakacki, E. J. Plaster composition, P (5) 117*a*.

Jakacki, E. J., and Hampton, A. L. Plaster composition containing polyvinylacetate, P (5) 117*b*.

Jakes, D. See Landspersky, H.

Jakobi, W. Device for igniting and checking the flame of a [gas] burner, P (9) 234*j*.

Jakobljevich, H. Setter bridge between dryer and tunnel kiln, (10) 256*e*.

Jambor, J. Effect of pozzolanic admixtures on cement resistance to sulfate solutions and on the mechanism of the SO_3 bond, (4) 90*j*.

James, D. F. See Saia, F. J.

James, H. L. See Aldrich, L.T.

James, W. J. See Achenbach, G. D.; Straumanis, M. E.

Jameson, W. M. Method for edge sealing safety glass, P (1) 5*i*.

Jamieson, C. F. Graphite thermocouples and method of making, P (5) 132*a*.

Jamieson, R. M. See Clay, D. B.

Jamnik, F. Device for the fabrication of U-shaped profiles of glass in a continuous rolling procedure, P (2) 38*c*.

Jan, R. V. See Seeger, A.

Janku, V. See Hudcova, A.

Janninck, R. F., and Whitmore, D. H. Electrical conductivity and thermoelectric power of niobium dioxide, (8) 196*c*.

Janovec, V. See Dvorak, V.

Jansen, G., Jr. See Kleinpeter, J. H.

Jansson, S. See Soderquist, R.

Jantsch, O. See Bernuth, G. von.

Janus, A. R., and Shirn, G. A. Preparation and properties of reactively sputtered silicon nitride, (9) 229*g*.

Janz, G. J. See Reeves, R. D.

Japan Atomic Energy Research Institute. Process for reprocessing burned uranium fuel using molten bath containing ammonium nitrate, P (9) 227*f*.

Jaray, F. F. Glass spinning crucible, P (1) 5*g*, P (4) 94*h*.

Jarosi, J. J. See Adams, E. A.

Jastrzebski, Z. D. Entrance effects and wall effects in an extrusion rheometer during the flow of concentrated suspension, (11) 289*h*.

Jasutis, V. See Deksnys, A.; Tolutis, V.

Jaupain, M. See Plumat, E.

Javaux, G. Apparatus for the rapid replacement of the bending roll in sheet glass drawing machines, P (7) 149*h*. Method and apparatus for drawing glass strips off of a molten metal bath, P (10) 255*j*. Method of and apparatus for the production of a fire-polished glass strip, P (9) 221*a*. Process and plant for manufacturing flat glass on a molten metal and solid support bed, P (9) 222*a*.

Jaworowski, R. J., Weberling, R. P., and Bracco, D. J. Atomic absorption studies on rare earth and refractory metals, (8) 191*j*.

Jay, E. B. See Aplet, L.

Jeffers, H. J. Segmental [diamond] abrasive wheel, P (3) 63*h*.

Jeffery, J. W. See Chatterji, S.

Jeffrey Galion Mfg. Co. Belt conveyor weighing apparatus, P (10) 266*g*. Continuous muller, P (3) 80*a*. Continuous muller with adjustable mulling wheels and plow means, P (9) 233*b*.

Jeitschko, W. See Toth, L. E.

Jelen, F. C. Alkali metal silicates and method for producing the same, P (2) 46*a*.

Jelinek, D. A. See Graeber, E. J.

Jelinek, J. W. See Lyon, K. C.

Jelinek, J. W., and Lyon, K. C. Model glass furnace evaluates luminous and nonluminous firing, (5) 119*g*.

Jellinek, F. System tantalum-sulfur, (5) 139*c*.

Jellinek, G. See Malissa, H.

Jena, P. K. See Ram, P.

Jenaer Glaswerk Schott & Gen. Photosensitive device using glass of arsenic, sulfur, and halogen, method of using the device, and method of making the glass, P (8) 185*g*. See Carl-Zeiss-Stiftung; VEB Carl Zeiss Jena.

Jenckel, L. H. F. Method for determining the specific surface of nonuniformly shaped substance by measuring the adsorption of noble gases or inert gases at the specimen to be investigated, P (5) 132*b*.

Jendrisak, J. E. Electrostatic deposition of parting materials in method of bending superposed glass sheets, P (10) 255*a*.

Jenike, A. W. Storage and flow of solids, (4) 103*i*.

Jenkins, G. M. Mechanism of tensile fracture in graphite, (7) 151*j*. Thermal expansion of polycrystalline graphite, (8) 210*a*.

Jenkins, J. D., and Reynolds, C. B. Method of encasing brick, P (8) 181*i*.

Jenkins, M. J. See Bond, R. L.

Jenkins, W. H. Method for forming glass wafers, P (3) 68*d*.

Jenkins, W. J., & Co., Ltd. Mixers, P (11) 289*a*.

Jenkinson, J. V. See Uhlir, A., Jr.

Jens, W. H. Reinforced ceramic fuel elements, P (2) 45*g*.

Jensen, P., and Kjekshus, A. Crystal structure of Mo_3As_4, (10) 270*i*. Crystal structure of Mo_3Sb_7, (1) 17*g*.

Jensen, P., Kjekshus, A., and Skansen, T. Crystal structures of Mo_3As_7 and W_3As_7, (8) 194*e*, (10) 270*d*. Systems molybdenum-arsenic, tungsten-arsenic, molybdenum-antimony, tungsten-antimony, niobium-bismuth, tantalum-bismuth, molybdenum-bismuth, and tungsten-bismuth, (2) 57*b*.

Jensen, W. R. See Batchelor, C. S.

Jerphanion, A. de. Use of natural gas in the porcelain industry, (4) 105*f*.

Jeru, H. Furnaces, P (4) 103*g*.

Jeschar, R. See Traustel, S.

Jeschar, R., and Schroeder, U. Liquid gas and light gasoline in the ceramic industry, (3) 81*j*.

Jessop, R. See Raask, E.

Jetzt, J. J. See MacChesney, J. B.

Jewell, R. C. Apertured body for the passage of molten glass, P (7) 149*f*.

Jewell, R. C., and Murphy, N. A. Manufacture of wired glass, P (3) 68*d*, P (5) 120*g*.

Jezek, V. Steatite glazes for single firing at 1350°C, (2) 46*g*.

Jindal, B. K. Effect of fineness of surkhi on the strength and watertightness of masonry, (10) 256*e*. See Parks, G. A.

Jobst, R. 120 years Carl Zeiss Jena—150th birthday anniversary of Carl Zeiss, (5) 119*h*.

Jochems, P. J. W., Werdt, R. de, and Nobel, D. de. Method of manufacturing [doped] semiconductor devices, P (9) 231*h*. Method of manufacturing [double diffused] semiconductor devices, P (10) 264*d*.

Jochmann, F. Two hundred year old blowing mold for optical effect decorative glass, (7) 146*a*.

Johanson, J. R. Method of calculating rate of discharge from hoppers and bins, (4) 106*b*.

Johansson, G. Crystal structure of the potassium aluminate $K_7[Al_2O(OH)_8]$, (1) 17*a*.

John G. Stein & Co., Ltd. Refractory brick, P (10) 260*e*.

John, H. F. See Schmidt, P. F.

John, H. F., and Faust, J. W., Jr. Method of growing crystalline members completely within the solution melt, P (1) 11*c*.

Johns, P. See Macklen, E. D.

Johns, W. D. See Huang, W. H.

Johns-Manville Corp. Apparatus for forming fibrous products, P (10) 254*i*. Apparatus and process for combining glass fibers with synthetic resin fibers, P (1) 4*f*. Apparatus for producing glass fibers, P (2) 38*i*. Art of filtration, P (2) 49*i*. Burner apparatus, P (9) 234*h*. Castable refractory, P (8) 180*f*. Friction composition for high energy service, P (4) 98*f*. Friction material, P (5) 124*g*. Glass fiber binder, P (9) 220*c*. Method and apparatus for forming mineral wool products, P (10) 255*j*. Method and apparatus for traversing strand material, P (3) 68*a*. Method and apparatus for use in manufacturing glass fibers, P (9) 221*c*. Method of treating [glass] fibers with dry binder material, P (11) 279*h*. Recovery of silica, iron oxide, and magnesium carbonate from the treatment of serpentine with ammonium bisulfate, P (11) 292*d*.

Johns-Manville Soc. Anon. Machine for the manufacture of plates from fiber loaded paste, such as asbestos-cement paste, P (9) 233*e*.
Johnson, D. A. See Harris, P. H.
Johnson, D. F. See Rimmer, D. E.
Johnson, E. F., and St. Louis, J. R. Method for alloying an electrode with a semiconductive body, P (9) 231*d*.
Johnson, E. R. See Huang, Suei-rong.
Johnson, G. C. Method for producing crystalline aluminosilicates, P (7) 153*e*.
Johnson, G. H. (compiler and editor). Ceramic-Metal Systems and Enamel Bibliography and Abstracts—1966, B (8) 211*j*.
Johnson, H. B., Miller, G. R., and Cutler, I. B. Dielectric loss in CaF_2 doped with oxygen ions, (11) 293*a*.
Johnson, J. A. Manufacture of ceramic or other articles, P (5) 130*a*.
Johnson, J. M. See Scotti, V. G.
Johnson, J. R. Apparatus for inspecting glassware, P (8) 176*e*.
Johnson, J. W. See Proctor, B. A.
Johnson, J. W., and Holloway, D. G. Shape and size of the fracture zones on glass fracture surfaces, (3) 66*g*.
Johnson, K. N. Ceramic-glass sealing means for encapsulation of electrical devices, P (10) 263*c*.
Johnson, L. F., Geusic, J. E., and Van Uitert, L. G. Efficient, high-power coherent emission from Ho^{3+} ions in yttrium aluminum garnet, assisted by energy transfer, (8) 195*j*.
Johnson, L. W. Rock crusher, P (11) 292*d*. Rock crusher bowl support, P (1) 16*c*.
Johnson, M. B. See Hartman, E. C.
Johnson, M. R. See Stillman, G. E.
Johnson, N. M. Geothermometry from the thermoluminescence of contact-metamorphosed limestone, (11) 296*j*.
Johnson, P. G. See Ray, N. H.
Johnson, P. W. See Peters, F. A.
Johnson, R. C., and Warwick, W. H. Synthesis of aluminum silicate whiskers, P (9) 227*h*.
Johnson, R. E. See Dayal, R. R.
Johnson, R. E., and Wurst, E. C., Jr. Double doping of III-V compound semiconductor material, P (1) 10*a*.
Johnson, R. H. See Cunningham, J. A.
Johnson, R. L. See Buckley, D. H.
Johnson, W. C. Welding flux and method of welding, P (10) 250*g*.
Johnson, W. E. See Carlyle, R. L.
Johnson, W. E., and Rottmann, H. R. Apparatus for measuring the wall thickness of glass containers, P (9) 219*e*.
Johnson, Matthey & Co., Ltd. Electrical resistance elements and the like, P (8) 184*a*. Sparking plug electrodes, P (10) 265*g*.
Johnson Service Co. Electrical humidity sensing element, P (3) 81*d*.
Johnston, R. L. Semiconductor diode and method of making, P (7) 158*b*.
Johnston, T. J. See Richards, N. E.
Johnston, W. D. See Boes, D. J.
Johnston, W. D., and Kessler, F. D. Determination of sulfur in glass by sulfur dioxide evolution at high temperatures, (7) 148*e*.
Johnston, W. J. High voltage igniter with fluid feed through the $[Al_2O_3]$ insulator core center, P (10) 264*d*.
Johnston, W. R., and Cramer, H. A. Precision electrical resistor, P (2) 49*b*.
Jona, F. See Chang, L. L.
Jonas, E. C., and Kuykendall, J. R. Preparation of montmorillonites for random powder diffraction, (1) 14*b*.
Jonas, K. Role of quality and concentration of lattice defects and activators in the catalytic and photochemical behavior of ZnO and TiO_2—mechanism of photochemical reactions, (1) 28*g*.
Jone, P. Y. See Fraser, R. S.
Jones, C. E., Jr. See Hilton, A. R., Jr.; Williams, E. W.
Jones, C. T. Production of aluminous siliceous material filler for asphalt or asphalt containing road surfacing material, P (7) 151*a*.
Jones, D. Color in the realm of the heavy clay industry, (11) 279*j*.
Jones, D. P., and Haaky, J. J. Crucibles, P (4) 98*e*.
Jones, E. D. Results and interpretation of the ^{51}V NMR in V_4O_9, (10) 271*i*.
Jones, E. J. See Kurtz, A. D.
Jones, G. D. See Elliott, R. J.; Goodenough, R. D.
Jones, J. R., Rowlands, D. L. G., and Monk, C. B. Diffusion coefficient of water in water and in some alkaline earth chloride solutions at 25°C, (1) 18*a*.
Jones, J. W. S. See Henney, J.
Jones, P. M. See Claridge, M. A.
Jones, P. R. See Hackney, H.
Jones, R. E. Door operator for a tunnel kiln ceramic plant, P (4) 105*c*.
Jones, R. R. See Whicker, L. R.
Jones, S. P. See Shaw, F.
Jones, T. G., Hawes, R. W. M., and Dyson, J. R. Semiautomatic preparation of ultrathin and large-area petrological sections, (2) 51*g*.
Jones, T. S., Kimura, S., and Muan, A. Phase relations in the system FeO-Fe_2O_3-ZrO_2-SiO_2, (4) 109*g*.
Jones & Laughlin Steel Corp. Frangible ceramic test mold, P (4) 98*f*.
Jonker, G. H. Halogen treatment of barium titanate semiconductors, (9) 229*a*.
Joormann, H. J. M. See Santen, J. G. van.
Jorba, M. P. y. See Perez y Jorba, M.
Jordan, D. E., and Monn, D. E. Rapid determination of magnesium in the presence of calcium and phosphate by titration with CDTA, (5) 131*b*.
Jordan, W. E. See Hare, W. A.
Jorgensen, J. S. See Conroy, J. E., Jr.
Jortner, J. See Rice, S. A.
Joseph, W. See Podschus, E.
Joseph Bancroft & Sons Co. Spun glass crimper, P (3) 69*g*.
Joseph Lucas (Industries), Ltd. Glass compositions, P (4) 94*f*. Manufacture of semiconductor devices, P (9) 231*d*. Process for producing sintered pieces on a metal element, P (2) 49*c*. Spark plugs, P (10) 261*g*.
Joshi, M. L., and Wilhelm, F. Diffusion-induced imperfections in silicon, (9) 238*h*.
Joslin, C. M. D., and Wild, A. P. J. Conversion to oil firing of an open flame tunnel kiln, (1) 14*h*.
Jost, K. H. Structure of the phosphor(III,V) oxides from the mixed crystals (P_4O_6-P_4O_7), (8) 207*i*.
Jourdain, A. Technology of Refractories, B (4) 113*h*.
Jouvet, C. E. New refractory product for lining walls exposed to high temperatures, especially slags and molten metals, P (10) 259*j*.
Joy Mfg. Co. Furnace baffle, P (2) 52*h*.
Joyce, B. A. See Bicknell, R. W.
Joyce, B. D., Formigoni, N. P., Roe, C. C., and Schliesing, F. Technique for obtaining oxide-layer isolation structures, (3) 77*a*.
Juda, W. See O'Connor, T. L.
Judd, G. G. Process for producing high purity alkaline earth compounds, P (11) 275*i*.
Judina, G. V. See Zarkhin, A. M.
Juel, L. H. See Martin, S. W.
Jugovic, Z. T. See Kalousek, G. L.
Juillet, F. See Long, J.
Julien, H. P. See Murata, Y.
Jullien-Davin, J. Device for measuring forces by application of the Hall effect, P (2) 47*b*.
Jung, H. Ceramics with drinking mottos—"black varnish" ware from late Roman potteries on the Rhine and Mosel, (1) 1*h*.
Jungbluth, E. D. X-ray diffraction topographs of imperfections in gallium arsenide by anomalous transmission of X-rays, (11) 303*a*.
Juodis, A. See Pranckevicius, G. A.
Jurenas, V. See Pranckevicius, G. A.
Jurich, R. Glassware orienting device on glazing machine, P (3) 67*j*.
Jurid Werke G.m.b.H. Friction material composition, P (5) 124*h*. Process for the production of shaped metal/ceramic articles, P (2) 45*f*.
Jury, S. H. Mechanically refrigerated ice bath, (9) 233*i*.
Juska, G. See Viscakas, J.
Just, D. Process for the determination of diffusion profiles in semiconductor bodies, P (5) 128*g*.
Juul, N. H. Determination of the thermal diffusivity for polycrystalline graphites as a function of temperature, (2) 54*h*.
Juvinall, J. W., Kock, E., and McCaslin, J. F. Method and apparatus for electrostatic deposition of coating materials, P (4) 92*a*.
Juza, R., and Schulz, K. H. Magnetic and optical investigations on nickel-containing alkali borate glasses, (3) 66*a*.
Jystad, S. Cement mortar for casting of concrete, P (3) 64*d*.

Kabushiki Kaisha Hitachi Seisakusho. Low temperature fusible glass, P (7) 149*g*. Method of making semiconductors and diffusion thereof, P (4) 102*a*. Method of manufacturing semiconductor devices, P (5) 128*e*. Method of manufacturing silicon diodes or silicon transistors by alloying indium with *p*-type silicon to produce a *pn* junction, P (2) 48*c*. Method for producing boron carbide, P (11) 282*e*. Method of producing semiconductor devices, P (4) 102*d*. Method for the production of semiconductor devices, P (11) 287*b*. Method of pulverizing graphite, P (1) 13*a*. Production of boron carbide, P (9) 227*f*. Production of semiconductor elements by the diffusion process, P (7) 157*i*. Variable negative-resistance device, P (8) 186*e*. Zener diode element of low junction capacitance, P (3) 79*i*.
Kabushiki Kaisha Obara Kogaku Garasu Seizosho. Process and apparatus for manufacturing elongated glass products, P (5) 121*f*.
Kachi, S. See Kosuge, K.
Kachi, S., Momiyama, K., and Shimizu, S. Electron diffraction study and a theory of the transformation from γ-Fe_2O_3 to α-Fe_2O_3, (5) 135*i*.
Kachi, S., Takada, T., and Kosuge, K. Electrical conductivity of vanadium oxides, (7) 163*b*.
Kachik, R. H. See Boggs, W. E.
Kacker, K. P. See Ramachandran, V. S.
Kaczer, J. See Fousek, J.
Kadowaki, K. See Tsuji, S.
Kaga, M., and Ishikura, O. Semiconducting properties of hot-pressed titanium dioxide, (3) 76*f*.
Kagel, W. Former peasant potters of "Der Kroening" [Landshut-Vilsbiburg district of Bavaria] and their present-day revival, (1) 1*h*.
Kahle Engineering Co. Machine for cutting glass tubes, P (9) 220*c*.
Kahng, D., and Lepselter, M. P. Barrier diode with metal contact and method of making, P (3) 77*d*.
Kahng, D., Ligenza, J. R., and Wemple, S. H. [Plasma glow] method for making electrode connections to potassium tantalate-niobate, P (9) 231*g*.
Kaibicheva, M. N. Nature of destruction of grains of chrome spinel in the slag zone of electric arc furnaces, (9) 224*g*.
Kaibicheva, M. N., and Pivnik, L. Ya. Destruction of basic refractories in electric furnaces, (4) 96*h*.
Kaibicheva, M. N., and Terekhina, P. Ya. Life of linings of steel melting arc furnaces, (9) 224*f*.
Kainarskii, I. S. New information regarding silica and its application in modern technology, (11) 298*e*.
Kainarskii, I. S., and Gaodu, A. N. Alumina lightweight insulating refractories, (4) 96*e*.
Kainarskii, I. S., and Orlova, I. G. Grogless refractory from nonlean clays and kaolins, (4) 97*a*.
Kainarskii, I. S., Orlova, I. G., and Degtyareva, E. V. Deformation and shrinkage of corundum during sintering, (10) 257*b*.
Kaines, C. J., Preece, K. N., and Saunders, J. Developments in the nondestructive testing of refractories, (2) 41*c*.
Kaiser, H. D. High capacitance device, P (1) 10*h*.
Kaiser, H. D., and Mones, A. H. Method of making a capacitor with a multilayered ferroelectric dielectric, P (5) 128*a*. Microelectronic capacitor material and method of fabrication, P (3) 79*h*.
Kaiser, R. H. See Casey, H. C., Jr.
Kaiser Aluminum & Chemical Corp. Calcareous refractory composition, P (11) 281*h*. Metal encased refractory article, P (8) 181*h*. Method of encasing brick, P (8) 181*i*. Plural tapered refractory blocks and tightly fitting metal case therefor, P (11) 282*c*. Process for the production of refractory hard metal borides, P (9) 227*d*. Refractory, P (1) 8*cd*, P (2) 45*a*, P (7) 154*c*. Refractory composition, P (10) 260*g*. Refractory construction, P (1) 8*e*. Refractory and method of making, P (2) 45*e*, P (9) 227*e*. Refractory products and method, P (10) 260*h*. Refractory shape with embedded channel shape reinforcement, P (2) 45*g*. Refractory with expansion means attached, P (9) 227*e*. Suspended refractory brick, P (1) 8*g*. Suspended refractory units, P (1) 8*h*.
Kaiser Gypsum Co., Inc. Method of grinding and introducing a set-control agent into a gypsum slurry, P (8) 174*d*.
Kajikawa, Y., and Ichimura, S. X-ray fluorescence analysis of electron tube materials, (1) 4*j*.
Kajiyama, K. See Furukawa, Y.
Kaldis, E. Nucleation and growth of single crystals by chemical transport (II) zinc selenide, (1) 24*f*.
Kaldis, E., and Widmer, R. Nucleation and growth of single crystals by chemical transport (I) cadmium-germanium sulfide, (1) 24*f*.
Kale, H. V. Laboratory furnace for high temperatures using butane gas, (10) 268*h*.
Kalinina, A. M. See Filipovich, V. N.
Kalinina, A. M., and Filipovich, V. N. Crystallization characteristics of certain lithium silicate and lithium aluminosilicate glasses, B (9) 246*d*. Sequence of crystallization during heating of lithium aluminosilicate glasses, B (5) 141*i*.
Kalitin, V. I., Luzhnaya, N. P., Yarembash, E. I., and Zinchenko, K. A. Single crystals of the selenides of praseodymium and neodymium, (8) 207*c*.
Kall, H. L. See Mannerberg, A. R.
Kallberg, K. A. Rotary scraping device for nodulizing drums in pelletizing plants, P (8) 190*h*.
Kalliga, G. P. See Poluboyarinov, D. N.
Kallmann, H. E. Ferrite memory cells and matrices, P (8) 184*b*.
Kalnin, I. L., and Rosenstock, J. Vapor deposit on of germanium on molybdenum, (9) 230*e*. Vapor deposition of silicon on graphite and the formation of silicon carbide, (3) 72*b*.
Kalocsai, B. O., and Wrench, R. F. Edge form grinding, P (8) 177*c*.
Kaloni, P. N. Flow of an elasticoviscous fluid in a conical duct, (9) 239*f*.
Kalousek, G. L., Jugovic, Z. T., and Gillam, J. L. New factor in abnormal setting of portland cement, (4) 91*b*.
Kaltner, E., and Nemec, F. Relation of the temperature and the mechanical behavior of chemically bonded magnesite-chrome refractories, (3) 71*e*.
Kalwa, M. See Tokarski, Z.
Kamarov, V. E. See Smirnov, M. V.
Kamath, G. T. See Moorthy, V. K.
Kamemoto, Y., and Yamagishi, S. Process for reprocessing burned uranium fuel using molten bath containing ammonium nitrate, P (9) 227*f*.
Kamenchik, A. E. Strengthening green magnesia bodies and firing them without predrying, (5) 123*f*.
Kamenetskii, Yu. L. See Lur'e, M. A.
Kamentsev, I. E. Role of impurities in the structure of quartz, (8) 206*c*.
Kamerer, J. W. See De Vore, G. C.
Kamiike, O. See Tanaka, M.; Tsubaki, T.
Kamimura, H. See Miyatani, K.
Kamogawa, T., Kotera, H., and Hayami, H. High-repetition pulsed Nd^{3+} glass laser, (11) 284*j*.
Kamstrup-Larsen, H. Rotary kilns, P (2) 53*c*.
Kan, Fu-hsi. Investigation of absorption, luminescence, and stimulated emission of rare-earth ions in glasses, B (9) 245*g*. Variations of the partial properties of oxides in silicate glasses, B (7) 171*c*.
Kana'an, A. S., Besenbruch, G., and Margrave, J. L. Knudsen and Langmuir measurements of the sublimation pressure of CoF_2, (8) 201*j*.
Kanazawa, T. Structure and properties of silicophosphate glasses, (2) 37*e*.
Kandler, J. See Feldmann, K.
Kane, J. C., LaMer, V. K., and Linford, H. B. Effect of solid content on the adsorption and flocculation behavior of silica suspensions, (8) 195*i*. Filtration of amorphous and sized crystalline silica suspensions flocculated by high polymers, (8) 198*a*.

Kaneko, T. M., and Handwerk, E. C. Fluxing agent, P (7) 153*d*.
Kang, K. D., and Metz, E. D. Semiconductor device with passivated junction, P (4) 102*e*.
Kann, J. Preventive medical treatment for silicosis? (2) 60*h*, (9) 244*b*.
Kannewurf, C. R. See Kenny, N.
Kanno, M. See Chiotti, P.
Kanzler, R. J. See Glasser, L. G.
Kao, Y. C. See Chu, T. L.
Kaplan, S. H. Color image reproducer having red phosphor combined with red-pass filter element, P (5) 127*c*.
Kaplow, R. See Strong, S. L.
Kappallo, W. See Michelitsch, M.
Kappmeyer, K. K., Hubble, D. H., and Powers, W. H. Investigation of silicon carbide brick, (1) 7*f*.
Kapralik, I. Phase diagram of the system $2CaO \cdot Fe_2O_3$-MgO, (1) 25*h*.
Kapur, P. C., and Fuerstenau, D. W. Dry strength of pelletized spheres, (2) 54*j*.
Karapetyan, G. O., Kariss, Ya. E., Lunter, S. G., and Feofilov, P. P. Spectroscopic investigations of neodymium-activated glasses, B (9) 245*g*.
Karapetyan, G. O., Reishakhrit, A. L., and Yudin, D. M. Photoconductivity as a method of studying glasses containing selenium and cadmium, B (9) 246*b*.
Karapetyan, G. O., Tsekhomskii, V. A., and Yudin, D. M. Study of semiconducting iron-containing glasses by electron paramagnetic resonance, B (4) 113*g*.
Karapetyan, G. O., and Yudin, D. M. Investigation of the structure of glasses by electron paramagnetic resonances, B (9) 245*h*.
Karaseva, T. P. See Skudnova, E. V.
Karasik, B. R. See Savitskii, E. M.
Karaulov, A. G. See Kukolev, G. V.; Zhikharevich, S. A.
Karelin, N. N. See Andrievskii, A. I.
Kariss, Ya. E. See Karapetyan, G. O.
Karlak, R. F. Metallizing ceramics, (9) 229*d*.
Karlova, L. G. See Polak, A. F.
Karlovitz, B. See Marynowski, C. W.
Karma (New Malden), Ltd. Liquid fuel burners, P (1) 15*a*.
Karpachev, S. V. See Vorob'ev, G. V.
Karpenko, I., Engel, W. H., III, and Dye, R. W. Vibratory ball mill, P (2) 50*c*.
Karpova, L. N. See Ignatova, L. I.
Karpova, N. D. See Lande, P. A.
Karpus, A. See Grigas, J.
Karrena-Feuerungsbau G.m.b.H. Refractory structures, P (7) 154*c*.
Karstetter, B. R. See Beall, G. H.; Duke, D. A.; Harrington, R. V.
Karstetter, B. R., and Voss, R. O. Chemical strengthening of glass-ceramics in the system Li_2O-Al_2O_3-SiO_2, (4) 92*h*.
Kashirina, E. F. See Koz'min, M. I.
Kashiwabara, S. See Okazaki, K.
Kasper, K. H. See Roessle, H.
Kasperowicz, H., and Gasparik, M. Method for interchanging curvature of cathode-ray tube faceplate, P (11) 279*c*.
Kastanek, J. See Sirhal, H.
Kasugai, T., and Nojima, S. Negative resistance semiconductor devices, P (10) 265*c*.
Kates, P. G. See Penton, H. V.
Kato, E. See Naka, S.; Takashima, H.
Kato, K. See Adachi, Y.
Kato, S. See Okuda, H.
Katz, K. Coextruded thermoelectric members, P (2) 47*a*.
Katz, S., and Miller, E. J. Method of making contacts on semiconductors, P (11) 286*i*.
Kauer, E. Optical device having an infrared radiation transmitting and visible radiation reflecting layer of lanthanum hexaboride, P (2) 48*h*.
Kauffman, J. H. Apparatus for feeding and transporting materials, P (4) 103*j*. System for mulling and mixing foundry sand, P (11) 283*d*.
Kaufman, L. Estimation of the entropy of NaCl-type compounds, (3) 85*h*.
Kaufman, L., Clougherty, E. V., and Berkowitz-Mattuck, J. B. Oxidation characteristics of hafnium and zirconium diboride, (10) 258*c*.
Kaufman, S. M. See Basler, W. G.
Kauppila, J. E., and Bockemuehl, R. R. Method for making cadmium sulfide field effect transistor, P (9) 231*c*.
Kawabata, S. See Nakahara, S.
Kawabe, H. See Umeno, M.
Kawada, I. See Sasabuchi, S.
Kawada, N., and Nemoto, A. Calcium silicates in the early stage of hydration, (5) 116*b*.
Kawahara, A., and Takano, Y. Syntheses and X-ray studies of the system PbO-V_2O_5, (5) 138*i*.
Kawai, N., and Nomura, K. Magnesia fiber product and a method for manufacturing the same, P (8) 181*g*.
Kawajiri, N. See Gomi, S.
Kawakubo, T. Crystal distortion and electric and magnetic transition in VO_2, (9) 237*c*.
Kawamura, J. See Tada, T.
Kawamura, T. See Takeuchi, T.; Yasufuku, M.
Kawamura, T., and Hayashi, K. Preparation of silicon carbide single crystals, (3) 87*g*.
Kawasaki Steel Corp. Deep drawing steel sheet and method for producing the same, P (10) 250*c*.
Kawassiades, C. T. See Vassiliadis, C.
Kay, E., and Poenisch, A. P. Magnetic control of film deposition, P (9) 231*c*.
Kaye, B. H. Determining the characteristics of fine powders, (2) 50*i*.
Kaye, B. H., and Treasure, C. R. G. Data handling techniques for particle size analysis, (2) 50*f*.
Kayle, E. L. See Beerbower, A.
Kazakov, V. D. See Sil'vestrovich, S. I.
Kazimir, J. Strength of hemihydrate plaster, (10) 248*h*.
Kean, J. S., Sr., Hansen, R. C., and Metzger, F. L. Package [carton] for glass sheets, P (7) 150*a*.
Kearley, R. A. Preparation of dense chromic oxide, P (1) 16*a*.
Kearney, J. R. See Wosinski, J. F.
Kedzie, R. W. See Grace, M. I.
Keefer, G. E. Glass melting furnace, P (9) 220*e*.
Keeling, P. S. IL/MA—a practical method of assessing pottery clays, (2) 50*d*. Nature of clay, (9) 235*e*.
Keely, W. M. X-ray diffraction technique for rapid surface area determination, (5) 131*j*.
Kegg, R. R. See Doering, W. E.
Kegley, T. M., Jr., and Leslie, B. C. Metallographic preparation of dicarbides of thorium and thorium-uranium, (8) 180*f*.
Kehl, W. L., and Stewart, M. M. Process for producing alumina comprising nordstrandite in major proportion, P (9) 227*a*.
Keihn, F. G., and Keplin, E. J. High-temperature thermal expansion of certain group IV and group V diborides, (3) 86*f*.
Keil, F. Theory of hydraulic hardening, (11) 275*c*.
Keil, K., and Snetsinger, K. G. Niningerite—a new meteoritic sulfide, (4) 108*j*.
Keinanen, H. See Gore, E. M.
Kelco Co. Joint filling composition, P (1) 2*c*.
Keler, E. K. See Isupova, E. N.
Keler, E. K., and Andreeva, A. B. Formation and properties of solid solutions of zirconia with oxides of rare earth elements, (5) 123*a*.
Keler, E. K., Bluvshtein, M. N., et al. New apparatus and method for testing tension in refractories at high temperatures, (7) 151*j*.
Kelleher, C. J. Control of charge for ceramic extrusion, P (8) 186*g*. See Beneke, J. A.
Keller, C. Fluorite phases in the systems protactinium pentoxide-rare earth oxide, (11) 295*i*. Reaction of the dioxides of the elements thorium through americium with niobium and tantalum pentoxides, (8) 206*c*.
Keller, C., Koch, L., and Walter, K. H. Reaction of transuranium oxides with alkali oxides (I) ternary oxides of hexavalent transuranium elements, lithium, and sodium; (II) ternary oxides of pentavalent transuranium elements and of protactinium with lithium and sodium, (8) 206*f*.
Keller, C., and Walter, K. H. Reaction conditions, lattice constants, and chemical properties of some ternary oxides of plutonium, americium, and curium of the type $M(III)X(V)O_4$, (11) 299*f*. Ternary oxides of americium and other rare earths of the type $A(III)_2BO_3$, (11) 302*d*.
Keller, H. N., McLean, D. A., and Vromen, B. H. Method for fabricating printed circuit components, P (3) 78*g*.
Keller, W. Apparatus and method of producing semiconductor rods by pulling from a melt, P (4) 100*f*. Method and apparatus for crucible-free zone melting, P (7) 156*j*. Method of crucible-free zone melting, P (11) 280*e*. Method for determining the electrical resistance of a body of extremely pure semiconductor material for electronic purposes, P (8) 185*c*.
Keller, W., Berger, G., and Schmidt, O. Apparatus for pyrolytic precipitation of semiconductor material from a gaseous compound thereof, P (3) 77*c*.
Keller, W. D., Gentile, R. J., and Reesman, A. L. Allophane and Na-rich alunite from kaolinitic nodules in shale, (8) 191*b*.
Keller Ofenbau G.m.b.H. Process and device for firing a ceramic body in a tunnel kiln, P (2) 53*a*.
Kellett, C. M., King, W. J., and Martin, F. W. Semiconductor resistor containing interstitial and substitutional ions formed by an ion implantation method, P (11) 287*f*.
Kelley, D. T. Method of etching semiconductors, P (3) 78*g*.
Kelley, J. A. Re-expanding compressed exfoliated vermiculite, P (2) 54*d*.
Kelley, J. E. See Harris, H. M.
Kellogg, H. H. See Duby, P.
Kelly, A., and Rowcliffe, D. J. Deformation of polycrystalline transition metal carbides, (7) 162*a*.
Kelly, B. T. See Summers, L.
Kelly, B. T., Martin, W. H., Price, A. M., and Bland, J. T. Mechanism of dimensional changes in the crystals of graphites and carbons under fast neutron irradiation, (8) 202*b*.
Kelly, E. J. Active iron electrode (I) iron dissolution and hydrogen evolution reactions in acidic sulfate solutions, (9) 237*d*.
Kelly, F. J., and Gow, W. A. Production of high-purity niobium oxide from pyrochlore-perovskite concentrate, (1) 15*g*.
Kelly, H. J. See Harris, H. M.
Kelly, P. J., and Laubitz, M. J. Thermoluminescence of alumina, (11) 320*d*.
Kelly, W. T. See Counts, W. E.
Keloglu, Yu. P., and Fedorko, A. S. Diagram of the pseudobinary cross section of ZnSb-CdSb, (11) 293*a*.
Kelsey, R. H. Preparation of inorganic oxide monofilaments, P (7) 153*f*. Process for preparing alumina wool, P (11) 282*f*.
Kelso, J. G. Process for making metal bonded diamond tools employing spherical pellets of metallic powder-coated diamond grits, P (8) 173*g*.
Kemp, G. T. See Estes, N. N.
Kempers, H. See Biegler, H.
Kempf, R. Decolorization of glass, (7) 148*e*.
Kempter, C. P. Isothermal compressibility of uranium monocarbide, (11) 297*e*.
Kempter, C. P., and Krikorian, N. H. Some properties of thorium monocarbide and dicarbide, (5) 138*h*.
Kendall, E. W. Two-stage process for derusting and protecting the surfaces of ferrous materials, P (3) 65*f*.
Kenna, J. L. See Brownell, W. E.
Kennecott Copper Corp. Cone-type crushers with shock pad between frame and adjustment ring, P (11) 291*d*.
Kennedy, J. K. Continuous multistage void differential-density hybrid zone melting apparatus, P (7) 156*a*.
Kennedy, T. N., Hakim, R., and Mackenzie, J. D. Preparation and properties of crystalline and amorphous vanadium pentoxide, (9) 241*f*.
Kennedy Van Saun Mfg. & Eng. Corp. Recovery of radiant heat losses from shells of rotary kilns, P (3) 82*a*.
Kenney, D. M. Method of isolating chips of a wafer of semiconductor material, P (10) 264*i*.
Kennicott, P. R. Determination of nitrogen in silicon by solid source mass spectrometry, (4) 104*e*.
Kenny, N., Kannewurf, C. R., and Whitmore, D. H. Optical absorption coefficients of vanadium pentoxide single crystals, (8) 203*j*.
Keplin, E. J. See Keihn, F. G.
Kerkhof, F. Relation of maximum crack velocity to other material constants of glass, B (2) 61*j*.
Kerkhof, H., and Leinauer, H. Method of producing printed circuit boards, P (10) 264*i*.
Kern County Land Co. Method of calcining and classifying borate, P (7) 160*j*.
Kerns, K. K., and Lentz, E. C. Ceramic coated muffler, P (2) 35*i*.
Kerper, M. J., and Scuderi, T. G. Mechanical properties of chemically strengthened glasses at high temperatures, (1) 4*a*. Relation of fracture stress to the fracture pattern for glass rods of various diameters, (1) 4*d*.
Kerr, D. M. Method of and apparatus for metal cladding refractory brick, P (8) 181*i*.
Kerr, D. R. See Hu, S. M.
Kerr, D. R., and Young, D. R. Methods of improving electrical characteristics of semiconductor devices and products so produced, P (5) 128*b*.
Kerr, G. T. Process for making crystalline zeolites, P (9) 236*f*. Synthetic zeolite, P (8) 190*i*.
Kerr, J. M. Thermal simulation of in-reactor microstructures in ThO_2-UO_2, (10) 259*a*.
Kerr-McGee Corp. Process of producing stoichiometric uranium dioxide, P (4) 99*b*
Kerr-McGee Oil Industries, Inc. Preparation and purification of lithium chloride, P (1) 16*c*.
Kershaw, D. D. Quartz-to-metal seal, P (8) 178*j*.
Kersting, A. Apparatus for producing pure semiconductor material [by vapor deposition], P (11) 284*h*.
Kesler, L. D., and Rankin, J. S. Method of laminating transparent assemblies, P (7) 150*b*.
Kessler, F. D. See Johnston, W. D.
Kessler, S. W., Jr. Ceramic-to-metal seals, P (2) 47*j*.
Kesten, P. N., and Schwartzwalder, K. Spark plug with improved intensifier spark gap in the center electrode, P (9) 232*e*.
Kester, F. L. See Gantzel, P. K.
Kesterke, D. G., Fleck, D. C., and Henrie, T. A. Fused-fluoride electrowinning of thorium-base alloys, (1) 19*b*.
Kestigian, M. Yttrium-iron garnet single-crystal growth by the combined Czochralski-molten salt solvent technique, (4) 100*e*. See Comer, J. J.; Grace, M. I.
Kestigian, M., Curry, R. H., and Leipziger, F. D. Effect of concentration on the fluorescence of samarium in cerium dioxide, (11) 293*g*.
Ketelaar, J. A. A., and Honig, E. P. Ionic mobilities and tracer diffusion coefficients of alkali ions in fused alkali nitrates, (8) 201*a*.
Ketterer, R. J. See Vedder, W.
Kevern, J. Ceramic molding combines simplicity with accuracy, (2) 41*d*. Cooler flame spraying widens choice of plastics, (3) 79*j*. See Parker, M.
Kewanee Oil Co. Thermoluminescent doubly doped LiF phosphor, P (8) 186*b*.
Keys, L. K., and Mulay, L. N. Magnetic studies of the semiconductor to metal transitions in Ti_2O_3 and Ti_2O_3, (10) 271*c*.
Keystone Chemurgic Corp. Hydrated magnesium aluminate and process for preparing same, P (4) 106*c*.
Keyzlar, T., and Richter, F. Manufacture of selenium-cadmium ruby glass for particular requirements, (3) 66*b*.
Kezar, N. P. See Black, H. R.
Khainson, A. M. See Soldatov, G. A.
Khakhlova, N. V. Determination of the degrees of stable diagonals in systems of nine salts of types A and B, (11) 293*j*.
Khan, B. Kh. See Ladokhin, S. V.
Khangil'din, G. N. Low-hygroscopic plasticized casing cement, (10) 248*j*.
Kharchenko, V. K., and Struk, L. I. Effect of temperature on the strength and plasticity of high-melting point materials, (3) 71*j*.
Kharitonov, F. Ya. See Pevzner, R. L.
Khar'yuzov, V. A., and Efimov, A. M. Electrical conductivity of glasses in system As-Ge-Pb-Se, B (4) 113*f*.
Khaustovich, G. P. See Golovina, E. S.
Khazemov, F. F. See Smirnov, M. V.
Kheifets, V. S. See Kuznetsova, G. N.; Vargin, V. V.

Khernburg, M. M. See Ariya, S. M.
Khigerovich, M. I., and Zuikov, G. G. Hydrophobization of cement with fatty acid additives, (10) 248*j*.
Khil'ko, M. M., Moichanova, M. I., et al. Roof brick from finely milled mixtures of magnesite and chromite, (5) 123*b*.
Khitro, E. V. See Gubko, I. T.
Kholodnyi, A. G. See Mchedlov-Petrosyan, O. P.
Khomyakov, A. N. See Buzhinskii, I. M.
Khomyakov, K. G. See Gordeev, I. V.
Khomyakov, M. T. See Kukolev, G. V.
Khorpyakov, O. T. See Lyutaya, M. D.
Khripkova, N. N. See Zhunina, L. A.
Khrushchev, M. S. See Ryabchikov, I. V.
Khrycheva, D. D. See Bresler, R. I.
Khutortsov, G. M., Mikhailov, N. V., and Rebinder, P. A. Optimum structure of concrete and conditions of its formation, (5) 116*h*.
Khvoshchev, S. S. See Zhdanov, S. P.
Khvostenkov, S. I. Constant or variable cross section of rotary kilns, (9) 214*b*. See Budnikov, P. P.
Kibbei, W. H., Jr. See Sheldon, F. R.
Kibby, R. M. See Bullough, V. L.
Kibirev, S. N. See Kogan M. N.
Kiefer, A. See Van Dolah H. J.
Kieffer, R., Gugel, E., Ettmayer, P., and Schmidt, A. Phase stability of silicon carbide, (8) 205*b*.
Kiehl, H. R. See Belentepe, Y. C.
Kienow, S. Lining for installations for the degasification of metals, P (9) 225*j*.
Kienow, S., and Sauthoff, J. Comparative studies of brick from different magnesite sinters, (3) 70*h*.
Kierkegaard, P. See Longo, J. M.; Werner, P. E.
Kierkegaard, P., and Longo, J. M. Crystal structure of vanadium(IV) oxide sulfate, $VOSO_4$, (8) 194*a*.
Kierkegaard, P., and Nyberg, B. Crystal structure of Cu_2SO_5-$CuSO_3$-$2H_2O$, (8) 193*c*.
Kihlborg, L. See Eick, H. A.
Kihlstedt, P. G. Preparation of industrial minerals, (4) 106*c*.
Kikuchi, A. See Sawaguchi, E.; Tamura, H.
Kikuchi, A., and Sawaguchi, E. Electrocaloric effect in $SrTiO_3$, (8) 196*g*.
Kikuchi, C., and Sumitomo, H. Luminescence spectra of alkaline earth halophosphate phosphors, (3) 76*c*.
Kikuchi, T. See Shimada, T.
Kikuchi, T., and Shiozawa, Ken-ichi. Observation of fission fragment tracks in sintered UO_2, (3) 87*d*.
Kile, C., Jr. Method of coating semiconductor with tungsten-containing glass and article, P (10) 264*g*.
Kilian, J. Effect of clinker composition on the hardening of heat-cured concretes, (11) 274*i*.
Killias, H. R., Dermatis, S. N., and Gatos, H. C. Growth and characterization of uranium-doped germanium single crystals, (9) 239*j*.
Killpatrick, J. E., and Sperling, H. G. Colorimeter employing tristimulus values, P (8) 188*a*.
Kilpatrick, W. D. Device for forming negative ions from iodine gas and a lanthanum boride contact ionizer surface, P (11) 285*d*.
Kim, C. D. See Straumanis, M. E.
Kim, P. H., and Namba, S. Study on saturation process by anomalous dispersion of ruby laser, (11) 301*j*.
Kim, Sang-Chul. Glow discharge device having parallel permanent magnetic rod electrodes, P (10) 264*b*.
Kimpe, C. de. See Faille, M. della.
Kimura, E. Silicon rectifier device, P (10) 265*d*.
Kimura, H. See Migitaka, M.; Pastor, R. C.; Takagi, T.
Kimura, S. See Jones, T. S.
Kinawi, A. See Bishay, A.
Kind, S. S., and Summerscales, L. Determination of specific gravity of glass particles by a density gradient method, (2) 36*i*.
King, A. G. Chemical polish and strength of alumina, B (2) 61*h*. Hot pressing apparatus, P (5) 130*e*. Method of hot pressing metals and refractories, P (11) 282*a*.
King, A. G., and Fuchs, E. Polishing porous materials, (7) 159*b*.
King, B. W., Jr., Byrer, T. G., and Hedden, W. A. Al-Si-Mn-Li anode for high temperature galvanic cell, P (4) 92*c*. Method of making an Al-Si-Mn-Li anode for high temperature galvanic cell, P (5) 117*j*.
King, D. F. High alumina refractories, P (2) 44*e*. See Troell, P. T.
King, J. C. Piezoelectric quartz crystal units, P (2) 48*j*.
King, J. C., and Thomas, N. C. Polarization process for ceramics, P (7) 157*e*.
King, L. A., Bissell, C. L., and Duke, F. R. Electric conductivity of fused $LiNO_3$-$NaNO_3$-KNO_3 eutectic, (3) 85*j*.
King, L. A., and Duke, F. R. Direct current measurement of fused salt conductivity (I) molten nitrates, (3) 84*i*.
King, R. D. See Henderson, B.
King, R. D., and Henderson, B. Zero-phonon lines under uniaxial stress in magnesium oxide, (3) 88*b*.
King, W. J. See Kellett, C. M.
Kingery, W. D. See Gordon, R. S.; Hewson, C. W.
Kingery, W. D., and Mickelsen, R. A. Amorphous zinc oxide semiconductor and method of making, P (3) 77*i*.
Kingsley, J. D. See Prener, J. S.
Kinkade, W. A. See McCleary, R. E.
Kinkel'shteyn, L. D. See Nemnonov, S. A.
Kino, A., and Suzuki, M. TiO_2-NiO-Sb_2O_5 compound, (2) 59*a*.
Kino, A., and Takahata, K. Measurement of optical properties of titanium dioxide pigment (I,II), (1) 22*i*.
Kinoshita, M. See Hamano, Y.
Kinsella, J. J. See Schwertz, F. A.
Kinsley, C. W. Apparatus for forming hollow glassware, P (10) 254*i*.
Kinson Pottery, Ltd. Flues, P (9) 223*d*.
Kiouzes-Pezas, D. Process for producing spheroidal alkaline earth metal carbonates, P (5) 133*e*.
Kip, A. F. Conduction electrons in solids, B (9) 244*e*.
Kiparisov, S. S. See Meerson, G. A.
Kirby, R. C. See Peters, F. A.
Kirby, R. K. See Rothrock, B. D.
Kirchner, H. H. See Wiegel, E.
Kirchner, H. P. Composition of matter containing plutonium dioxide and plutonium phosphate, P (11) 281*b*.
Kirchner, H. P., Gruver, R. M., and Walker, R. E Chemically strengthened, leached alumina and spinel, (5) 122*i*.
Kirillin, V. A., Sheindlin, A. E., and Chekhovskoi, V. Ya. Enthalpy and thermal capacity of silicon carbide containing 12% free carbon in the range 1100° to 2850°K, (8) 197*h*.
Kirillin, V. A., Sheindlin, A. E., Chekhovskoi, V. Ya., and Tyukaev, V. I. Enthalpy and specific heat of titanium diboride in the range 273.15° to 2600°K, (8) 197*g*.
Kirillova, I. I. See Buzhinskii, I. M.
Kirkendale, G. A. (editor) Applications of the Computer to Ceramic Operations, B (11) 303*g*. (editor) Drying Claywares, B (8) 212*b*. Operating the dryer, B (8) 212*d*.
Kirkinskii, V. A. See Kuznetsov, L. M.
Kirschner, J. G. See Wiener, R.
Kisaka, S. See Ikegami, S.
Kischio, W. See Grimmeiss, H. G.
Kisfaludy, A., and Tardy, P. Microscopic examination of ferromagnetic phases of alloys, (5) 131*h*.
Kishida, M. Results of test on fused cast Mg-Cr brick used in the backwalls of an open-hearth furnace, (11) 281*d*. Trial manufacture of 8-radial hole center brick and its use, (9) 225*e*.
Kishida, M., and Takahashi, O. Material of brick for charge side lining of LD converter and life of the converter body, (11) 280*i*.
Kishii, T. Change of density of glass by heating (VIII) comparative studies on the glass transition characteristics of organic and inorganic glasses, (7) 148*c*. Quartz crystals in a devitrified soda-lime-magnesia glass, (2) 37*c*. Stresses in seals of molybdenum foil to silica glass, (5) 126*i*. See Ooka, K.
Kishii, T., Asai, T., and Sakurai, J. Sealing characteristics of composite lead-in wires with copper core, (5) 126*g*.
Kishii, T., Omori, T., and Ooka, K. Stress in glass caused by ultraviolet radiation, (5) 119*d*.
Kislova, A. I. See Bogatova, E. I.
Kislyakov, I. P., and Smirnova, I. N. Study of the phase diagram of the system $BaCl_2$-$BaWO_4$, (11) 301*j*.
Kislyi, P. S. See Kocho, V. S.; Panasyuk, A. D.; Samsonov, G. V.
Kislyi, P. S., and Kuzenkova, M. A. Gas-impermeable protective thermocouple sheaths of zirconium boride, (8) 198*g*.
Kislyi, P. S., Panasyuk, A. D., and Samsonov, G. V. Activated sintering of niobium carbide, (3) 83*h*.
Kislyi, P. S., and Samsonov, G. V. Basic principles of the extrusion of pipes and rods from powders of high-melting compounds, (3) 70*h*.
Kiss, I. See Beke, B.
Kiss, K., and Magder, J. Controlled particle size $BaTiO_3$, P (3) 77*g*.
Kita, H. See Masuda, M.
Kita, S., and Watanabe, H. Variable-capacitance point contact diode, P (5) 129*e*.
Kitagawa, M. See Yoshida, T.
Kitaigorodskii, I. I., Pavlushkin, N. M., and Petrov, S. V. Burning sulfur from slag glasses, (5) 118*a*.
Kitaj, W. See Hurley, E. B.
Kitamura, A. Energy transfer from UO_2^{2+} to Er^{3+} in glass, (10) 251*h*.
Kiwak, R. S. Composite article of bonded refractory metal and a ceramic, P (11) 281*a*.
Kizer, J. A. A. See Burke, O. W., Jr.
Kjekshus, A. High temperature X-ray study of the thermal expansion of $IrAs_3$ and $IrSb_3$, (3) 86*g*. See Furuseth, S.; Jensen, P.
Klages, H., and Minx, E. Basis for the construction and use of gas-fired hearths, (10) 268*f*.
Klass, D. L., and Martinek, T. W. Electroviscous fluids (I) rheological properties; (II) electrical properties, (7) 163*g*.
Klassen, V. K. See Luginina, I. G.
Klawitter, J. J. See Hulbert, S. F.
Kleflsch, R. Annealing container or muffles, P (10) 268*i*.
Klein, Adalbert. Rhenish stoneware—current research, (3) 63*i*.
Klein, Alexander. Expansive cements and components thereof, P (5) 116*f*.
Klein, A. L., and Tsikarev, V. G. Determining the melting point of fettling and ramming specimens from hearths of basic open-hearth furnaces, (9) 223*j*.
Klein, C., Jr. Mineralogy and petrology of the metamorphosed Wabush iron formation, southwestern Labrador, (7) 165*f*.
Klein, M. J. See Edington, J. W.
Klein, M. J., and Edington, J. W. Slip in explosively shocked magnesium oxide crystals, (8) 207*d*.
Klein, M. J., and Gager, W. B. Generation of vacancies in MgO by deformation, (4) 108*d*.
Klein, M. J., and Rudman, P. S. X-ray line broadening in explosively shocked magnesium oxide, (10) 272*f*.
Klein, M. V., and Cadwell, R. F. Low temperature system for thermal conductivity measurements, (1) 13*j*.
Klein, N. Temperature detector, P (4) 102*i*.
Kleinhans, R. J. See Weller, E. E.
Kleinknecht, H. P. Semiconductor device fabrication, P (4) 102*d*. Tunnel-effect semiconductor system with capacitative gate across edge of *pn* junction, P (7) 158*b*.
Kleinpeter, J. H., and Jansen, G., Jr. Electrolytic deposition of actinide oxides, P (8) 181*a*.
Kleinsteuber, A. T. See Clinton, S. D.; Haas, P. A.
Klemens, P. G. Thermal conductivity in vitreous systems, B (2) 61*g*.
Kleppa, O. J. See McCarty, F. G.; Meschel, S. V.
Klerer, J. Mechanism of the deposition of silica by pyrolytic decomposition of silanes, (10) 262*i*.
Klerk, J. de. Thin-film piezoelectric transducers used as generators and detectors of microwave phonons, with some attenuation measurements in SiO_2, (3) 77*d*.
Klevtsov, L. P., and Stepanov, G. K. Study of the structure of media consisting of very small particles by capillarimetry, B (1) 30*f*.
Klier, G. See Koziol, K.
Klima, K. G., and Noss, K. Apparatus for producing semiconductor devices, P (3) 77*b*.
Klimenko, M. J. Method for production of catalyst for hydration of olefins to alcohols, P (7) 161*b*.
Klimin, A. V. See Kotelnikov, G. R.
Klimpel, R. R. See Austin, L. G.
Klimpel, R. R., and Austin, L. G. Statistical theory of primary breakage distribution for brittle material, (4) 110*h*.
Kling, H. C., and Koslosky, E. Silicon diode with solder composition attaching ohmic contacts, P (10) 265*d*.
Klingler, E. See Dawihl, W.
Klingler, E. A., Dawihl, W., and Doerre, E. Sintered transparent bodies of aluminum oxide and method of preparing them, P (7) 154*d*.
Klink, J. P. See Martin, W. S.; Smith, R. E.
Kloeckner-Humboldt-Deutz Akt.-Ges. Grinding mill of the swinging type with a plurality of grinder drums, P (7) 160*i*. Vibratory centrifuge for the dewatering of fine granular material, P (5) 130*g*. Vibratory grinding mill of the drum type, P (4) 104*a*.
Klomp, J. T. See Botden, T. P. J.
Klomp, J. T., Botden, T. P. J., and Klop, M. A. F. Process for joining surfaces of refractory material with a MnO-SiO_2-Al_2O_3 system, P (8) 181*j*.
Klop, M. A. F. See Klomp, J. T.
Klossika, W. Semiconductor stabilized mechanically and electrically by a first layer of lacquer and a second layer of boric oxide, P (4) 102*g*.
Klotsman, S. M., Timofeev, A. N., and Trakhtenberg, I. Sh. Investigation of the diffusion properties of the chalcogenides of transition metals (III) self-diffusion of nickel in nickel oxide, (1) 20*j*.
Kiyachin, V. V., Kropanev, S. I., and Zatoplyaev, N. A. Design of hydrocyclones for concentrating kaolins and clays, (3) 79*j*.
Klyucharov, Ya. V., and Eger, V. G. Reaction of magnesiochromite with calcium oxide, (5) 123*i*.
Knapp, O. Calculation of the viscosity of ternary silicate glasses from their composition, (9) 217*h*. Structure of glass fibers, (7) 148*j*.
Knapp, W. J. See Ali, M. A.; Raju, A. P.
Knapsack Akt.-Ges. Process for the manufacture of aqueous clay suspensions, P (9) 233*b*.
Knapsack-Griesheim Akt.-Ges. Method and apparatus for producing polyphosphoric acids, P (2) 54*d*. Process for the manufacture of rounded powdered magnetite particles, P (7) 161*e*.
Knauft, R. W. Evolution of the Ohio Valley refractories industry, (5) 122*i*.
Kneen, G. W. Facing tiles, P (7) 150*i*.
Knight, H. T. See Wiley, J. S.
Knipple, W. R. See Callahan, J. L.
Knop, O. See Brisse, F.
Knopp, A. N., and Stickler, R. Structure and perfection of thermally grown oxide films on silicon, (8) 207*g*.
Knowles, A. R., and Lovicz, V. Heating element, P (8) 184*f*.
Knox, J. J. Method of shrinking glass tubing, P (10) 255*j*.
Knox Laboratories, Inc. Method of shrinking glass tubing, P (10) 255*j*.
Knudsen, P. A. Crushing and grinding plant, P (10) 269*d*.
Knupp, R. C., and Berger, D. F. Effects of iron in ultraviolet absorbing green glass, (2) 36*d*.
Ko, Hon Chung. See Greenbaum, M. A.; Hu, Teh.
Kobayashi, K. See Tomono, M.
Kobayashi, K., and Yokota, R. Dielectric properties of glasses in systems composed of tellurite (TeO_2) and some phosphates, (5) 118*e*.
Kobayashi, T. Aluminum phosphate hydrates, (3) 83*i*. Solid solution of cristobalite and $AlPO_4$ of the cristobalite type, (4) 109*i*. See Miyata, N.
Kobayasi, H. See Akasaki, I.
Kobe Kogyo Corp. Electron tube with inert oxide coating on the envelope, P (10) 263*h*.
Kober, H. See Scharrer, E.
Kobes, W. See Hsu, S. E.; Wolfson, R. G.
Koch, F. B., and Fine, M. E. Magnetic properties of Fe_2O as related to the defect structure, (8) 202*g*.

Koch, L. See Keller, C.

Koch, W. Jaw crushers for crushing minerals or the like, P (1) 15*i*.

Kochetova, A. P. See Dygalo, M. I.

Kocho, V. S., Mitrokhin, A. K., Kislyi, P. S., and Shtopko, V. M. Performance of zirconium boride thermocouple tips in a Bessemer converter, (10) 258*f*.

Kock, E. See Juvinall, J. W.

Kocsis, G. Effect of chemical accelerators on the temperature dependence of the viscosity of silicate glasses, (1) 3*g*. See Locsei, B.

Kocsis, J. Fabrication of a semiconductive device with closely spaced electrodes, P (5) 127*b*.

Kocsis, Z. See Straub, G.

Kodama, H. Crystal distortion of sericite, (5) 134*i*. Transformation of pyrophyllite into an interstratified structure, (5) 139*c*.

Kodera, H. See Migitaka, M.

Kodera, S. See Harada, J.

Kodera, Y. See Sawaguchi, E.

Koehl, G. See Gerlach, W.

Koeneman, M. H. See Stein, J. L.

Koepplin, W. J. See Cable, T. H., Jr.

Koerner, K. See Heidrich, W.

Koester, R. D., and Moak, D. P. Hot hardness of selected borides, oxides, and carbides to 1900°C, (7) 164*f*.

Koffman, D. M., and Mariano, A. N. Single crystal orienter for the Norelco diffractometer, (5) 131*f*.

Kofstad, P., and Espevik, S. Low-pressure oxidation of niobium at 1200° to 1700°C, (9) 240*g*.

Kogan, L. S., and Nikiforov, Yu. V. Production of portland cement with a high content of MgO, (10) 248*d*.

Kogan, M. N., and Kibirev, S. N. Device for grinding a group of lenslike quartz resonators, P (9) 230*b*.

Kogan, S. F. See Yasinskaya, G. A.

Kohls, D. W. Petrology of the Simsboro formation of northeast central Texas, (8) 204*b*.

Kohn, J. A., Eckart, D. W., and Cook, C. F., Jr. Determination of large crystal structures by combined X-ray diffraction and electron microscopy, (9) 238*b*.

Kohn, K. See Miyatani, K.

Kohn, K., and Tasaki, A. Torque measurement on antiferromagnetic yttrium manganese oxide single crystals, (11) 302*d*.

Kohn, R. L., and Pantell, R. H. Second-harmonic enhancement with an internally modulated ruby laser, (3) 76*e*.

Kohra, K. See Yoshimatsu, M.

Koide, S. Electrical properties of $Li_xNi_{1-x}O$ single crystals, (9) 238*e*. Electrical properties of $Ni_{(1-x)}Li_xO$ single crystals, (7) 163*c*.

Koide, S., and Okada, K. Study of highly refractory materials (I) theoretical consideration of temperature distribution in an electric arc furnace, (7) 160*a*.

Koide, S., and Takei, H. Electrical properties of the $Ni_{(1-x)}O$ system, (5) 135*f*.

Koike, M. See Okamoto, E.

Koishi, M. See Meguro, K.

Kojic, L., and Wenzel, M. Medieval glass found in Yugoslavia, (11) 274*a*.

Kokorina, V. F. Some aspects of glass structure in relation to results of investigations of oxygen-free glasses, B (7) 171*f*. See Efimov, A. M.

Kokubo, T. See Tashiro, M.

Kolb, F., Ditterich, K., Obrowski, W., and Schwarz, F. Measuring resistance, P (2) 48*a*.

Kolbin, N. I., Semenov, I. N., and Shutov, Yu. M. Thermal dissociation of osmium trichloride, (8) 209*i*.

Kolchin, I. K. See Erman, L. Ya.

Koichin, O. P., and Berlin, I. K. Manufacture and applications of niobium carbide components, (10) 257*h*.

Koleske, J. V. See Faucher, J. A.

Kolesnik, M. I. See Butenko, V. A.

Kolesova, V. A. Coordination of Al and Ga atoms in the glass network, B (9) 245*f*. Investigation of the crystallization of certain aluminosilicate and gallosilicate glasses, B (5) 141*i*.

Koller, H. See Hund, F.

Kollerup, V. Shot cleaning method for heat exchangers, P (3) 82*b*.

Kolobova, K. M. See Nemnonov, S. A.

Kolomiets, B. T., and Shilo, V. P. Possibility of obtaining oxychalcogenide glasses, B (7) 171*f*.

Koluch, J. S. See Walters, E. L.

Kolykov, G. A. Structure of complex glasses above the liquidus temperature, B (7) 171*e*.

Komarek, K. L. See Landler, P. F. J.; Miller, E.

Komatsu, H. See Lawn, B. R.

Komatsubara, K., and Kurono, H. Semiconductor composition with negative resistance characteristics at extreme low temperatures, P (7) 158*a*. Variable negative-resistance device, P (8) 186*e*.

Komeya, K. See Matsuo, S.

Komissarova, L. N., Van, Gen'-Shi, Spitsyn, V. I., and Simanov, Yu. P. System La_2O_3-HfO_2, (8) 208*g*.

Kondo, H., and Miyahara, S. Magnetic properties of some synthetic olivines, (5) 137*a*.

Kondo, R. Synthesis and crystallography of a group of new compounds having the hauynite structure, (8) 208*f*.

Kondoh, H. Multiple twin domains and domai walls in NiO crystal, (3) 87*b*. New birefringence pattern of antiferromagnetic NiO crystal, (5) 137*j*. Optically biaxial properties in antiferromagnetic NiO, (7) 166*d*. See Takeda, T.; Uchida, E.

Kondoh, H., and Takeda, T. Observation of antiferromagnetic domains in nickel oxide, (8) 203*i*.

Kondrashev, Yu. D., and Omel'chenko, Yu. A. X-ray investigation of certain oxide and sulfide systems, (9) 243*b*.

Kondrat'ev, Yu. N. Certain peculiarities of chemical bonding in lithium aluminosilicates, B (9) 246*d*. Dual role of titanium dioxide in the formation of the structure of transparent crystalline glass materials, B (9) 246*c*.

Kondrat'eva, B. S. See Evstrop'ev, K. K.

Konev, V. N. See Gerasimov, A. F.

Konnerth, K. See Rupprecht, H.

Konno, H. See Kudaka, K.

Kono, H. Analytical treatment of the reaction zone of a cement shaft kiln, with special reference to the effect of CO loss, (5) 116*b*.

Konopicky, K. Tendencies in the development of refractory building materials, (9) 225*a*. See Patzak, I.; Wohlleben, K.

Konopicky, K., and Routschka, G. Investigations on used hot blast stove brick, (10) 257*d*.

Konozenko, I. D., and Neshpor, V. S. Effect of nuclear radiation on the properties of high-melting compounds, (8) 195*f*.

Konrad, H. E. Castable refractory, P (8) 180*f*.

Konta, J., and Borovec, Z. Heavy minerals in raw kaolin from Sedlec (Zettlitz) in Bohemia, (3) 82*h*.

Kooi, E. Formation and composition of surface layers and solubility limits of phosphorus during diffusion in silicon, (7) 163*g*.

Koorneef, J. See Vrolijks, M. H. M.

Kooy, C. Material transport in solid-state reactions, (8) 202*b*. Preparing nickel ferrite single crystals on a monocrystalline substrate, P (10) 265*f*.

Kopineck, H. J., Muszkiewicz, H., and Schlotter, C. Method and apparatus for increasing the entrainment of pulverous material in a carrier gas utilizing pressure shocks, P (8) 186*i*.

Koppers Co., Inc. See Harbison-Walker Refractories Co.

Koppers, Heinrich, G.m.b.H. See Heinrich Koppers G.m.b.H.

Koppius, O. G. Method for impregnating tungsten dispenser cathodes, P (8) 185*e*.

Kopylov, N. I. See Margulis, E. V.

Korda, E. J. See Pruden, L. H.

Kordesch, K. V. Hydrogen anode including aluminum spinel and platinum family coatings and method of making same, P (5) 124*j*.

Koreeda, S. See Matsukura, Y.

Korelova, A. I. See Alekseeva, O. S.; Bokin, P. Ya.

Korenev, Yu. M. See Novoselova, A. V.

Koretzky, H. Coating of aluminum substrates with a magnetic material, P (9) 230*j*.

Korneev, V. I. See Sychev, M. M.

Korob, O., and McCartney, E. R. Electrophoretic mobility of kaolin-water suspensions with additions of a basic aluminum chloride complex, (7) 154*h*.

Koromal'di, E. V. See Zhdanov, S. P.

Korshunov, B. G. See Safonov, V. V.

Korshunov, B. G., and Drobot, D. V. Fusibility diagrams in the systems YCl$_3$-NaCl and YCl$_3$-KCl, (4) 108*b*.

Korshunov, B. G., and Lapkina, E. D. System MoCl$_5$-AlCl$_3$-NaCl, (1) 29*g*.

Korshunov, V. A., and Gel'd, P. V. Nature of defects in the higher manganese silicide lattice, (4) 108*j*.

Korshunov, V. A., Sidorenko, F. A., et al. Phase components of the system MnSi-Si, (3) 87*a*.

Korsunskii, M. I., Genkin, Ya. E., and Verkhoglyadova, T. S. Corrected $L\beta_2$ emission band of niobium and bond forces in the system niobium-nitrogen, (3) 84*f*.

Kortel, A. A. See Voronin, N. I.

Korzekwa, T. M. Electrostatic separator with coated discharge electrode, P (3) 83*c*.

Korzenkova, M. P. See Novoselova, A. V.

Kosaka, M. See Minowa, S.

Koslosky, E. See Kling, H. C.

Kostanyan, K. A., and Erznkyan, E. A. Investigation of the electrical conductivity of glasses in the system K_2O-SiO_2 over a wide temperature range, B (9) 245*j*.

Kostanyan, K. A., Saakyan, K. S., and Avetisyan, E. M. Electrical conductivity of molten glasses, B (4) 113*b*.

Kostomarov, M. I. See Gubko, I. T.

Kostyuk, V. A., Skrebtsov, A. M., and Val'ter, O. I. Study of the conditions for fettling and wear of hearths of tilting open-hearth furnaces, (5) 123*f*.

Kostyukov, N. S. See Budnikov, P. P.

Kostyukov, N. S., Antonova, N. P., and Dmitriev, V. I. Soret effect in electrotechnical porcelain, (11) 301*c*.

Kosuge, K. See Kachi, S.

Kosuge, K., and Kachi, S. Crystallographic and magnetic properties of the V_2O_3-Cr_2O_3 system, (11) 293*g*.

Kosuge, K., Kachi, S., Nagasaki, H., and Minomura, S. Phase transition in V_4O_{25}, (11) 299*f*.

Kosuge, K., Takada, T., and Kachi, S. Phase diagram and magnetism of the V_2O_3-V_2O_5 system, (5) 137*g*.

Kotelnikov, G. R., Trokhachev, I. R., Booshin, A. N., Klimin, A. V., Jablonsky, S. P., Chikhachev, Y. N., Monozon, S. M., Sobolev, V. M., Mkheidze, O. A., and Zigel, V. A. Apparatus for [spray] drying solutions, emulsions, and suspensions and for heat treatment of the dried material, P (3) 80*e*.

Kotera, H. See Kamogawa, T.

Kotik, P. L. See Uteush, Z. V.

Kotovich, V., and Vasilev, V. Isomorphism in the helvite group minerals, (1) 21*a*.

Kotseva, Y. How a Bulgarian ceramic tradition was recognized, (7) 145*j*.

Kotsmid, F., and Dietrich, W. Determination of thermal expansion of glass by a modified Padmos method, (10) 251*j*.

Kotze, I. A., and Kuhlmann-Wilsdorf, D. Theory of the interfacial energy between a crystal and the melt, (10) 272*h*.

Koury, F. See Butler, K. H.

Koury, F., and Waymouth, J. F. High pressure electric discharge device having electrodes with thorium on the exposed surface thereof, P (8) 184*h*.

Kovacev, R. See Lyutskanov, S.

Kovacs, A. J. See Braun, G.

Kovalenko, E. N., and Cutler, I. B. Origin of calcite decomposition nuclei, B (2) 61*h*.

Kovaleva, I. S. See Zorina, E. L.

Koval'skaya, K. V., Manuilova, N. S., and Murzova, L. I. Laboratory study and tests of refractories in an electric furnace, (9) 224*f*.

Kovba, L. M. See Aslanov, L. A.

Kovba, L. M., Ippolitova, E. A., Simanov, Yu. P., and Spitsyn, V. I. Crystal structure of uranates (I) uranates containing tetragonal (UO_3)-O_2 layers, (3) 84*b*.

Kovba, L. M., Trunov, V. K., and Simanov, Yu. P. Double oxides in the system β-Nb_2O_5-WO_3, (11) 293*e*.

Kovenskii, I. I. See Samsonov, G. V.

Kowalchik, M. See Trumbore, F. A.

Kowalik, T. J. See Perron, A. J.

Kowalski, F. See Hajduk, T. J.

Kozachenko, E. L. See Bergman, A. G.

Kozacka, F. J. Electric fuse with separate quartz fillers having different grain sizes, P (3) 77*j*.

Kozacka, F. J., and Salzer, E. High interrupting capacity fuses having casings of inorganic material, P (3) 78*a*.

Kozin, G. N., Krivchenko, Yu. S., Kudrina, A. P., and Vit, E. F. Service conditions and nature of wear of refractories in oxygen converters, (5) 123*b*.

Koziol, K., and Klier, G. Method of screw connecting carbon or graphite electrodes, P (9) 226*a*.

Kozlova, M. A. See Chistoserdov, V. G.

Kozlowski, M. A. See McAleer, W. J.; Rosenberg, R.

Kozlowski, T. R. See Bartholomew, R. F.

Koz'min, M. I., Min'ko, N. I., and Kashirina, E. F. Nature and cause of the formation of open bubbles in a glass ribbon, (8) 175*e*.

Kozuka, T. See Hukuo, N.

Kracek, F. C., Ksanda, C. J., and Cabri, L. J. Phase relations in the silver-tellurium system, (1) 26*c*.

Kraft, G., and Beck, H. Method of producing lithium fluoride, P (9) 236*a*.

Kramer, G. L. See Ognyanova, E. Z.

Kramer, I. R. Effect of surfaces on mechanical behavior of metals, B (9) 245*f*.

Kramer, W. Preheaters for revolving tubular kilns, P (2) 53*e*.

Kraner, H. M. Slides in technical communication, (9) 244*a*.

Krasil'nikova, L. M. See Presnov, V. A.

Krasnov, Yu. N. See Smirnov, M. V.

Krasotkina, N. I. See Voronin, N. I.

Kratochvil, J. Atomic models of crystal defects, B (4) 114*b*.

Kratohvil, J. P., and Dezelic, G. Determination of the size of small particles by light scattering, (3) 84*i*.

Kraus, H. Combined specific gravity meter and contact goniometer, P (9) 234*d*.

Kraus, J. W. See Heinemann, H.

Kraus, K. A. Process for separating inorganic anions with hydrous oxide anion exchangers, P (10) 270*b*.

Krause, E. Technology of Heavy Clayware (Vol. III) Drier Installations, B (5) 142*e*.

Krause, E. F. See Araujo, R. J.

Krause, G. See Zagar, L.

Krause, I., Segreto, A. J., Przirembel, H., and Mach, R. L. Poisson's ratio for viscoelastic materials, (10) 267*a*.

Krauth, A., and Oel, H. J. Effect of the properties of the powders on the sintering behavior of uranium dioxide, (11) 294*d*.

Krautheim, E. H., and Veverka, V. C. Rotary kiln scraper, P (4) 105*h*.

Kravitz, J. H. Using an ultrasonic disruptor as an aid to wet sieving, (1) 15*j*.

Kreglo, J. R., Jr., and Smothers, W. J. Mechanism of creep in MgO brick, (10) 257*j*.

Kreider, K. G., and Cooper, A. R. Dissolution kinetics of quartz spheres in a sodium silicate melt, (11) 276*h*.

Kreidl, N. J. Optical properties of glass (I), (8) 175*g*.

Kreidl, W. H. Binding agent for refractories and its manufacture, P (10) 259*d*. Cellular glass and method of making same, P (9) 219*b*. Process of producing foamed glass and foamed glass and insulating material produced by this process, P (9) 222*a*. Refractory mortars, P (8) 182*d*, P (9) 227*f*.

Kreim, F. Contemporary German ceramic artists and their work—Wilhelm Kagel, (9) 213*j*.

Kreimer, G. S., Alekseeva, N. A., and Vakhovskaya, M. R. Rupture mechanism of powder metal hard alloys, (1) 28*i*.

Kreimer, G. S., Tumanov, V. I., Alekseeva, N. A., Pavlova, Z. I., Baskin, M. I., and Kuznetsova, K. F. Properties of sintered WC-TiC-Co hard alloys containing tantalum carbide, (10) 258*j*.

Krellner, W. G. Electrographitic brush, P (2) 43*j*.

Krempasky, G. T. See Oudenhoven, M. S.

Krentsis, R. P. See Gel'd, P. V.

Kreshnamachari, R. See Ghosh, R. K.

Kressbach, J. E. See Sheldon, F. R.
Krestnikova, E. N. See Petrovskii, G. T.
Kretz, R. Grain-size distribution for certain metamorphic minerals in relation to nucleation and growth, (1) 19*g*. Interpretation of the shape of mineral grains in metamorphic rocks, (1) 20*g*.
Kreuter, J. C., and Hoens, M. F. A. Stress measurements and their significance in enameling, (3) 65*f*.
Kriegel, W. W., and Palmour, H., III (editors). Materials Science Research (Vol. 3) Role of Grain Boundaries and Surfaces in Ceramics—Proceedings of a Conference Held November 1964 at the North Carolina State University, Raleigh, B (2) 60*j*.
Krieger, A. E. See Helmbrecht, W. L.
Krieger, F. See Toussaint, H. N.
Kriek, H. J. S., and Segal, B. B. Effect of the silicate constitution of magnesite brick on the high-temperature strength, (9) 224*b*.
Krier, C. A. See Regan, R. E.
Kriger, E. M. See Grodshtein, A. E.
Krikorian, F., and Sneed, R. J. Deposition of tantalum, tantalum oxide, and tantalum nitride with controlled electrical characteristics, (2) 54*f*.
Krikorian, N. H. See Kempter, C. P.; Wallace, T. C.
Krinov, S. M. Method of mixing glass batch, P (3) 68*i*.
Krischner, H. Electron diffraction studies of Al_2O_3-KI, (2) 55*b*. See Torkar, K.
Krisciunas, V., and Mikalkevicius, M. Elastic properties of trigonal selenium single crystals, (5) 135*c*.
Krishnan, R. Influence of NiO on the yield of yttrium-iron garnet crystals grown from flux, (1) 19*g*.
Krisleit, R. F. See Caprio, M. J.
Krivchenko, Yu. S. See Kozin, G. N.; Kudrina, A. P.
Kriz, J. See Husa, V.
Krizova, J. Effect of alkali content in clinker on cement quality, (9) 214*c*.
Krochmal, J. J. See Mazdiyasni, K. S.
Krockow, D. See Bernuth, G. von.
Kroenke, W. J. Torsional testing techniques applied to fine diameter glass fibers, (2) 38*c*.
Krogh-Moe, J. Structure of glass, (2) 37*d*.
Krogstad, R. S. Neutron dosimeter comprising nickel oxide with lithium as an impurity, P (8) 185*c*.
Krohn, C. Phase diagram barium chloride–potassium chloride, (1) 25*f*.
Krokhina, A. I., Spivak, G. V., and Shakmanov, V. V. Investigation of the structure of glass-ceramics with the aid of etching by ion bombardment, B (9) 246*d*.
Kronenberg, M. L. Production of catalyzed carbon electrode, P (8) 182*c*.
Kroner, E. Dia- and para-elasticity, B (4) 114*b*. Dislocation field theory, B (4) 114*b*.
Kropanev, S. I. See Klyachin, V. V.
Kroupa, F. Dislocation loops, B (4) 114*c*.
Kruchinin, Yu. D., and Ivanova, L. V. Influence of water treatment of molten blast-furnace slags on the linear rate of crystallization of slag minerals, (1) 2*b*.
Kruger, J., and Calvert, J. P. Oxide films formed on copper single crystal surfaces in water (III) effect of light, (7) 166*f*.
Kruger, O. L. See Moser, J. B.
Kruger, O. L., and Moser, J. B. Sintering characteristics and properties of PuS and PuP, (1) 28*g*.
Krulfeld, M. KBr growth by deposition from the vapor, (9) 240*b*.
Krumholz, A. F., Sr. Sealing means for rotary agitator of a grinding and dispersing mill, P (9) 236*g*.
Krumme, J. P., and Straumanis, M. E. Anodic behavior of GaAs single crystals at increased current densities in alkaline and acidic solutions, (10) 261*i*.
Kruschevska, A. See Christova, R.
Kruse, W. E. Pigmentary TiO_2 manufacture, P (2) 54*a*.
Krylov, B. E. See Lobanov, E. M.
Krylov, E. I., and Pinaeva-Strelina, M. M. Orthotantalates of lanthanum, samarium, and europium, (1) 24*b*.
Ksanda, C. J. See Kracek, F. C.
Ku, P. M. Effects of oxide and organic films on sliding friction, B (8) 212*i*.
Kubaschewski, O. Thermochemistry of metal-refractory interactions, (7) 152*f*.
Kubit, T. T. Flush tank toilet, P (11) 283*j*.
Kubo, K., and Motohashi, H. Lattice expansion in LiF crystals by neutron irradiation, (7) 165*d*.
Kubo, T. See Matsuo, S.
Kubo, T., and Manabe, K. Thermal decomposition of cobaltous acetate tetrahydrate, (4) 111*c*.
Kubo, T., Shirasaki, S., and Mitarai, Y. Catalytic action of mineral acids on the transformation of γ-Fe_2O_3 to α-Fe_2O_3, (8) 192*f*.
Kucera, M. See Formanek, J.
Kuchma, L. Kh. See Gusarov, A. D.
Kucza, J. A. See Mandel, G.
Kucza, J. A., and Mandel, G. Method for the synthesis of gallium phosphide, P (4) 102*f*.
Kuczynski, G. C. See Gibbon, C. F.
Kudaka, K., Konno, H., Matoba, T., and Takahashi, S. Crystal surfaces of cubic boron nitride, (11) 293*f*.
Kudashev, G. K. Dielectric loss in lead borate glasses, B (4) 113*f*.
Kudo, N. See Matsuda, O.
Kudrina, A. P. See Kozin, G. N.
Kudrina, A. P., Krivchenko, Yu. S., and Gul'ev, G. F. Effect of physicochemical factors of basic refractories on lining life in oxygen converters, (9) 224*a*.
Kudryashova, N. F. See Smirnova, E. K.
Kudryavtsev, L. A. See Danilkin, V. I.
Kudyakov, V. Ya., and Smirnov, M. V. Zr/Zr^{3+}, Zr/Zr^{4+}, and Zr^{3+}/Zr^{4+} potentials and the equilibrium constants of the $Zr^{+} + Zr^{4+} \rightleftharpoons 2Zr^{3+}$ reaction in molten KCl, B (1) 30*b*.
Kuebler, N. A. See Robin, M. B.
Kueffer, J. See Barz, G. J.
Kuehl, D. See Galasso, F. S.
Kuehne, K. Function of mobile ions in glass, B (9) 246*a*.
Kuehnert, H. Mehlis glasshouse in the Thueringer Wald, (11) 274*b*.
Kuendig, W., Cape, J. A., Lindquist, R. H., and Constabaris, G. Some magnetic properties of Fe_2SiO_4 from 4° to 300°K, (8) 207*h*.
Kuhlman, W. C. Tungsten-osmium thermocouple and element thereof, P (8) 188*i*.
Kuhlmann-Wilsdorf, D. See Kotze, I. A.; Raghavan, K. S.
Kuhn, W. E. Production of ultrafine boron nitride by arc vaporization, (3) 71*d*.
Kuhne, G. See Flemming, H.
Kukhtenko, V. A. See Degtyareva, E. V.
Kukolev, G. V., and Karaulov, A. G. Properties of water suspensions of commercial alumina and rational conditions for slip casting, (5) 123*h*.
Kukolev, G. V., and Nemets, I. I. New method of increasing the spalling resistance of fireclay refractories, (4) 97*i*.
Kukolev, G. V., Nemets, I. I., and Khomyakov, M. T. Method of increasing the life of saggers, (4) 97*g*.
Kul'ba, F. Ya. See Mironov, V. E.
Kulcinski, G. L., and Maynard, C. W. Combined effect of ultrahigh pressure and nuclear irradiation on solid-solid phase transformations, (2) 54*i*.
Kulemzin, K. N. See Nagornyi, A. I.
Kuliczkowski, J. A., and Wentworth, C. Magnetic body, P (10) 264*a*.
Kulig, C. W. See Fuller, R. A.
Kulik, A. I. See Strelets, V. M.
Kulikov, I. S. See Panov, A. S.
Kulkarni, A. K. See Moorthy, V. K.
Kumar, D., Ward, R. G., and Williams, D. J. Infrared absorption of some solid silicates and phosphates with and without fluoride additions, (7) 164*j*.
Kumar, R. Heat transfer in laminar flow of a Bingham material between two parallel plates, (11) 296*d*.
Kumar, S. Studies on a eutectic glass composition in the system MgO-Al_2O_3-SiO_2, (8) 176*b*.
Kumar, S., and Nag, B. B. Electrical properties of alkaline earth aluminosilicate glasses, (10) 251*g*.
Kumar, S., and Nath, P. Absorption spectra of Mn^{2+} ion in glasses, (2) 35*j*. Effects of manganese and iron oxides on some physical and chemical properties of glass, (2) 36*c*.
Kundra, M. C. See Murthy, H. P. S.
Kunig, H. E. See Brody, T. P.
Kunii, D., Sugahara, Y., Sato, Kiyoshi, Saito, M., and Ogawa, M. Method of drying a hydrogel, P (3) 83*c*.
Kunitomi, M., Kunugi, T., and Yamada, K. Synthesis of colored quartz, (4) 111*e*.
Kunnmann, W. See Rogers, D. B.
Kuno, H. Fractionation trends of basalt magmas in lava flows, (1) 18*j*.
Kuntze, R. A. Synthetic plaster set retarder, P (5) 117*b*.
Kunugi, T. See Kunitomi, M.
Kunzler, J. E., and Matthias, B. T. High field superconducting magnet consisting of a niobium-zirconium composition, P (1) 10*i*.
Kuo, Chu-kun, and Yen, Tung-shen. Phase equilibrium and chemical reactions in the system CaF_2-Al_2O_3, (1) 25*g*.
Kuper, A. B., and Nicollian, E. H. Effect of oxide hydration on surface potential of oxidized *p*-type silicon, (10) 262*h*.
Kuprog, E., Leers, K. J., and Rauschenfels, E. pH value of hydrated calcium aluminates and alumina cement, (3) 64*d*.
Kuramochi, A. See Yasufuku, M.
Kurbanovskaya, O. G. See Polak, A. F.
Kureha Kagaku Kogyo Kabushiki Kaisha. See Chiyoda Kako Kensetsu Kabushiki Kaisha.
Kuriakose, A. K., and Margrave, J. L. Kinetics of the reactions of elemental fluorine with zirconium carbide and zirconium diboride at high temperatures, (8) 201*j*. Kinetics of reaction of elemental fluorine (II) fluorination of hafnium carbide and hafnium boride; (III) fluorination of silicon and boron, (8) 201*j*. Oxidation kinetics of zirconium diboride and zirconium carbide at high temperatures, (3) 87*f*.
Kurihara, K. See Ichinose, N.
Kurinnaya, V. N. See Gromakov, S. D.
Kurkjian, C. R., and Treptow, A. W. Preparation of cerium-containing glasses, P (4) 95*b*.
Kurmaev, R. Kh. See Amirova, S. A.
Kuroda, T. See Mikoda, M.
Kuroki, H. See Ikeda, Y.
Kurono, H. See Komatsubara, K.
Kurosawa, T. Theory of hot electrons in semiconductors, (10) 272*h*. See Osafune, H.
Kurtz, A. D., and Jones, E. J. Semiconductor strain gage transducers, P (10) 265*c*.
Kurtz, P. See Ali, M. A.; Raju, A. P.
Kus, R. Journalling structure for rotatable processing drums such as rotary kilns, tube mills, etc., P (7) 160*c*.
Kus, R., and Jaeger, H. Apparatus for the preheating of raw cement material, P (4) 91*d*.
Kushakovskii, V. I. See Budnikov, P. P.
Kushida, A., Utsumi, R., and Ueda, K. Pressure loss in bent rubber hose on pneumatic conveyance, (9) 232*j*.
Kushida, T. Infrared absorption spectra from excited states in ruby, (9) 239*i*.
Kushiro, I., and Yoder, H. S., Jr. Anorthite-forsterite and anorthite-enstatite reactions and their bearing on the basalt-eclogite transformation, (8) 191*f*.
Kutateladze, K. S., Tandilova, K. B., Soseliya, L. D., Dzhadzhanashvili, O. S., and Chrdileli, O. G. Increasing the activity of clinker, (9) 214*c*.
Kutolin, S. A., and Sergeeva, A. E. Thermodynamic study of formation of compounds of the types M_2TiO_3 and M_2ZrO_3 (titanates and zirconates), (11) 302*b*.
Kutsche, D. See Frank, W.
Kuwabara, H. Results of using ladle brick containing 20 to 40% zircon, (9) 224*c*. See Atsukawa, M.
Kuwabara, S. See Horibe, T.
Kuwata, T., Sugahara, Y., and Nakazawa, T. Method and apparatus for preparing silica-alumina type spherical hydrogels, P (10) 259*f*.
Kuykendall, J. R. See Jonas, E. C.
Kuzenkova, M. A. See Kislyi, P. S.
Kuz'ma, Yu. B. See Fedorov, T. F.
Kuz'ma, Yu. B., Fedorov, T. F., and Shvets, E. A. Phase equilibria in the system Zr-W-C, (8) 204*j*.
Kuz'ma, Yu. B., Lakh, V. I., Markiv, V. Ya., Stadnyk, B. I., and Gladyshevskii, E. I. X-ray diffraction study of the system tungsten-rhenium-carbon, (5) 139*d*.
Kuzmick, P. L. Grinding wheel having an antimony or bismuth trioxide bond, P (8) 173*f*.
Kuznetsov, A. Ya., and Tsekhomskii, V. A. Semiconducting silicate glasses, B (4) 113*f*.
Kuznetsov, F. A., and Rezukhina, T. N. High-temperature heat capacity of cerium sesquioxide, (3) 86*f*.
Kuznetsov, G. F. Ways of utilizing the brick industry for industrializing construction, (3) 70*d*.
Kuznetsov, L. M., Kirkinskii, V. A., and Makarov, E. S. Interactions of uranium dioxide and lead monoxide, (8) 200*d*.
Kuznetsov, V. G. See Eliseev, A. A.; Ioffe, A. V.
Kuznetsov, V. G., and Li, Chi-fa. X-ray investigation of the system SnS-PbS, (9) 243*c*.
Kuznetsov, V. G., Tajukin, L. I., Bychkov, V. P., Brodov, V. G., and Ryurikova, J. N. Multiple-shot X-ray thermal vacuum chamber for testing samples over a wide temperature range, P (11) 289*j*.
Kuznetsov, V. G., Tananaev, N. V., and Shpirt, M. Ya. Reaction of germanium dioxide with the oxides of aluminum, iron, silicon, calcium, and magnesium on heating, (11) 300*c*.
Kuznetsov, V. V. See Soldatov, G. A.
Kuznetsova, G. N., Kheifets, V. S., and Shevyakov, A. M. Infrared spectroscopic study of the structure of sodium zirconosilicate glasses, B (9) 245*f*.
Kuznetsova, K. F. See Kreimer, G. S.
Kvapil, J. Orientation of hydrogen etched corundum crystals by optical back reflection, (9) 233*j*.
Kwestroo, W., and Huizing, A. Preparation of ultrapure lead oxide, (8) 205*a*.
Kyri, H. Natural materials for enameling, (9) 216*d*.
Kyrs, M. See Rais, J.
Kyser, D. F., and Millea, M. F. Etching of gallium arsenide with nitric acid, (4) 100*f*.
Kyushu Refractory Co., Ltd. Manufacture of stabilized dolomite refractory brick, P (8) 181*g*.

Laar, B. van. New interpretation of magnetic anisotropy measurement on CoO single crystals, (10) 271*f*.
Laat, C. D. J. C. de. See Bril, A.
Labino, D. Apparatus for producing glass fibers, P (2) 38*i*. See Searight, C. E.
Labounsky, A. Voltage-pressure bonding, P (8) 187*a*.
Laby, R. H. See Greenland, D. J.
Lacey, M. W. Method of and apparatus for breaking out sheets of glass, P (5) 120*i*.
Lachapelle, R. L. Process for polishing crystalline silicon, P (9) 232*a*.
LaChapelle, T. J. See Wilcox, W. R.
Lachenmayr, H. See Floerke, O. W.
Lacklison, D. E. See Lewis, M. F.
Lacroix, R., and Blavat, H. Fusion processes for the manufacture of metals and alloys employed in contact with molten materials, P (10) 255*c*.
Lacy, H. J. Simple tilting still apparatus, (7) 159*c*.
Ladd, L. S. See Carnall, E., Jr.
Ladell, B. J. See Deacon, R. F.
Ladendorf, E. See Ladendorf, K.
Ladendorf, K., Ladendorf, W., Ladendorf, P., Ladendorf, E., and Ladendorf, K. F. Pumping of suspensions, P (1) 13*a*.
Ladendorf, K. F. See Ladendorf, K.
Ladendorf, P. See Ladendorf, K.
Ladendorf, W. See Ladendorf, K.
Ladnar, J. See Husa, V.
Ladokhin, S. V., Khan, B. Kh., and Ul'yanov, V. L. Causes of chemical heterogeneities in melts for rock castings, (5) 122*g*.
Laegreid, N., and Moseson, R. M. Sputtering of metals wherein gas flow is confined to increase the purity of deposition, P (4) 102*h*.
Lafferty, J. M., and Grams, W. R. Rhenium supported metallic boride cathode emitters, P (7) 157*j*.

Lagarias, J. S. Method for pneumatically elutriating solid particles, P (3) 81*f*.
Lagneborg, R. See Gullberg, R.
La Grange, L. D. Process for making gelled spherical particles of oxides, P (10) 269*i*. See Bray, D. T.
La Grange, L. D., and Steele, W. A. Refractory products, P (5) 125*c*.
Lahiri, D. See Gupta, A.
Lahoda, J. Grinding machine for thick-walled glassware, (3) 66*i*.
Lainer, D. I., Bai, A. S., and Tsypin, M. I. Titanium oxidation kinetics and structure of scale, (3) 88*a*.
Laity, R. W., and Miller, M. P. Diaphragm-cell method for constant mass diffusion measurements—interionic diffusion and friction coefficients in molten silver nitrate-sodium nitrate mixtures, (8) 194*c*.
Lajarte, S. D. de. Electrically resistant glass compositions, P (3) 67*b*. Glass compositions, P (5) 120*j*.
Lajarte, S. D. de, and Bourgeaux, M. Method and apparatus for conveying a glass sheet on a molten metal bath, P (9) 220*f*.
Lakatos, T., and Simmingskold, B. Effect of physical structure of Grossalmerode pot clay on corrosion in molten glass, (5) 118*g*. Influence of constituents on the corrosion of pot clays by molten glass, (10) 252*j*.
Lakh, V. I. See Kuz'ma, Yu. B.
Lakin, J. R. See Eason, M. D.
Lakin, J. R., and Haglington, J. B. Chemical durability, (11) 280*i*.
Lakomkin, I. G., and Alekseevskaya, N. V. Use of phosphates as ion exchangers, (1) 29*j*.
Lalak, J. J. See Milch, A.
Lallemant, P. M. J. Friction linings and processes for their production, P (5) 124*f*.
Lam, H. K. H., and Fullam, H. T. Catalytic chlorination of beryllium from the ore, P (5) 124*c*.
Lamb, D. R. See Brander, R. W.
Lamb, D. R., and Rundle, P. C. Nonfilamentary switching action in thermally grown silicon dioxide films, (7) 155*j*.
Lamb, I. E. Monitor for air-borne beryllium, P (3) 80*c*.
Lamb, J., and Richter, J. Anisotropic acoustic attenuation with new measurements for quartz at room temperature, (8) 191*d*.
Lamb, R. D. See Turner, A. B.
Lambe, J., Donald, D. K., Vassell, W. C., and Cole, T. Electroluminescence of rare-earth ions in cadmium fluoride, (5) 135*f*.
Lambe, J. J., Mudar, J., and Nudelman, S. Electroluminescent display device with piezoelectrical scanning and gating means, P (3) 78*d*.
Lambert, A. G. L. M. Pressing of industrial porcelain and the products obtained, P (11) 284*a*.
Lambert, A. N., and Williams, B. B. Low voltage semiconductor reference diode, P (11) 285*j*.
Lambert, M. See Brichard, E.
Lambert Freres & Cie. Method and apparatus for calcining gypsum in two stages, P (7) 147*c*. Method of baking plaster at low temperatures, P (1) 2*d*.
LaMer, V. K. See Kane, J. C.
Laming, J. See Hayhurst, A.
Lamont, J. A., and Hubble, D. H. Investigation of insulating brick in steel plant service, (8) 180*b*.
Lamorte, M. F. Planar *pn* junction light source with reflector means to collimate the emitted light, P (3) 79*i*.
Lampson, M. L. See Callander, A. H.
Landa, L. M. See Brekhovskikh, S. M.
Lande, P. A., and Karpova, N. D. Increasing the life of stopper refractories in large steel casting ladles, (5) 123*c*.
Lande, P. A., Varvarina, A. I., and Ivanova, Z. N. Use of sonic method for controlling the quality of steel casting plugs, (9) 225*h*.
Landgren, R. See Greening, N. R.
Landis & Gyr Akt.-Ges. Photoresistors, P (5) 128*c*.
Landler, P. F. J., and Komarek, K. L. Reduction of wustite within the wustite phase in H_2-H_2O mixtures, (1) 27*i*.
Landon, D. O., and Marcovecchio, J. Remote control system for a spectroscopic wavelength computer, P (1) 14*c*.
Landspersky, H., Sedlakova, L., and Jakes, D. Thermal decomposition of hydrated UO_3, (2) 58*d*.
Lang, G. F., Jr. Bonding of semiconductor devices to substrates, P (8) 184*c*.
Lang, J. E., Proebstle, R. A., and Wisnyi, L. G. Fuel element containing a mechanically compressible mandrel, P (2) 44*b*.
Lang, K. Direct enameling, (3) 65*a*.
Langauer, T. See Schwiete, H. E.
Lange, H. Luminescent europium activated strontium aluminate, P (3) 78*c*.
Langer, S. See Gantzel, P. K.
Langlois, R. E. Method for bonding bodies of multifilament strands, P (8) 177*h*.
Lanker, R. B. Mold and plunger with internal cooling structure, P (2) 39*g*.
Lant, T. P. R., and Teague, E. D. Protective flame sprayed coatings, P (9) 217*c*.
Lanyon, H. P. D. See Dresner, J.
Lapierre, A. G., III. See Tausch, F. W., Jr.
Lapkina, E. D. See Korshunov, B. G.
Laporte, L. F. Carbonate deposition near mean sea level and resultant facies mosaic—Manlius Formation (Lower Devonian) of New York State. (8) 192*d*.
Laporte Titanium, Ltd. Burner reactor apparatus, P (4) 105*i*. Manufacture of oxides, P (4) 103*g*. Manufacture of titanium dioxide, P (2) 54*c*. Process of particulate matter separation, P (11) 291*f*.
Lapp Insulator Co., Inc. Gyratory grinder, P (11) 288*i*.
Laratta, A. See Capriz, G.
Laredo, E. See Belbeoch, B.
Larking, M. A. Application of LPG to the heavy clay industry, (11) 290*b*.
Larrabee, G. B. See Heinen, K. G.; Osborne, J. F.
Larrison, J. E. Housed semiconductor device with thermally matched elements, P (10) 264*d*.
Larsen, W. L. See Marcotte, V. C.
Larson, A. H. See Tidwell, L. G.
Larson, D. A., and Walsh, P. J. Low-pressure electric discharge lamp with internal elongated structure that modifies the diffusion length of the discharge and improves the lamp performance, P (3) 78*b*.
Lasch, C. A., Jr., Hampton, G. P., and Speransky, B. J. Diffusion [resistance] furnace, P (4) 105*c*.
Laseck, F. B., and Ressler, W. J., Jr. Apparatus for tempering bent glass sheets, P (3) 67*k*.
Lassota, J. See Markuszewicz, M.
Last, J. T. Method of making solid-state circuitry, P (8) 185*h*.
Latypov, Z. M. See Gromakov, S. D.
Laubitz, M. J. See Kelly, P. J.
Lauder, W. B., and Copson, R. L. Production of ultrafine ferric oxide by reacting ferric chloride with nitrogen dioxide, P (11) 292*c*.
Laudise, R. A. See Ballman, A. A.
Laudone, J. A. See Cummings, W. P.
Laudy, J. H. A. Dependence on heat-treatment of the thermal conductivity of a crystallizing glass, B (2) 61*h*.
Laur, T. L. Process for making stable silicone rubber interlayers for glass, P (7) 150*b*.
Laurenson, L. See Baker, M.
Laurent, B., and Fezenko, I. Metallic elements adapted to come in contact with melted glass, P (8) 177*a*.
Lavendel, H. W., and Elliot, A. G. Evaluation of silicide coatings on columbium and tantalum and a means for improving their oxidation resistance, (10) 249*g*.
Lavine, M. C. See Banus, M. D.
Lavino, E. J., & Co. Apparatus and method for manufacturing brick, P (7) 152*i*. Metal encased refractory brick and method of making, P (2) 44*j*. Plastic chrome ore, P (4) 98*h*. Universal brick plating machine, P (3) 73*c*.
Lavrinenko, I. A. See Eremenko, V. N.
Law, P. D. Method of and apparatus for production of glass beads by use of a rotating wheel, P (7) 149*j*.
Lawn, B. R., and Komatsu, H. Nature of deformation around pressure cracks on diamond, (8) 203*c*.
Lawrence, W. G. Base exchange and charge development on clays, B (1) 30*b*. (editor) Clay–Water Systems, B (1) 30*a*. Nature of clays, B (8) 2 2*c*. Plastic properties, B (1) 30*b*. Rheological properties of clays, B (1) 30*b*. Structure of water, B (1) 30*b*.
Lay, L. A. See Barry, T. I.
Layden, G. K., and Darby, W. L. Phase equilibria and crystal growth in the system BaO-$YTaO_4$-B_2O_3, (8) 204*h*.
Layer, E. H., Jr., and Herbst, D. L. Electrical component and method of making the same, P (8) 184*j*.
Layman, H. D. See Ropp, R. C.
Layton, M. M., and Herczog, A. Nucleation and crystallization of $NaNbO_3$ from glasses in the Na_2O-Nb_2O_5-SiO_2 system, (8) 175*g*.
Layton, M. M., Randels, R. B., and Stockdale, G. F. Method of producing an electrical capacitor, P (3) 79*d*.
Lazarev, A. N. Flexibility of complex anions and molecules with Si-O-Si and P-O-P bonds, B (5) 142*b*.
Lbov, V. S. See Smirnov, M. V.
Lea, F. M. Action of ammonium salts on concrete, (2) 34*a*.
Leadbetter, A. J. See Barron, T. H. K.
Leadbetter, A. J., and Newsham, D. M. T. Analysis of the vapor pressure of alkali halide crystals, (7) 161*h*.
Leaman, H. E. See Stalego, C. J.
Lean, E. G. H., and Shaw, H. J. Efficient microwave shear-wave generation by mode conversion, (11) 294*j*.
Leander, K. Refractory materials—present and future aspects, (7) 152*h*.
Learn, A. J., Scott-Monck, J. A., and Spriggs, R. S. Barriers at evaporated metal-polycrystalline CdS interfaces, (7) 162*c*.
Leary, J. A., and Nance, R. L. Method of preparing plutonium mononitride, P (1) 8*a*.
Leatham, E. See Campbell, W. W.; Pack, A. H.; Scott, R. K.; Tvergaard, A. M.
Leatham, E., Pack, A. H., Campbell, W. W., Einstein, E., and Miller, E. D., Jr. Mullite production, P (11) 282*i*.
Leavesley, L. A. Heat resistant materials, P (4) 98*j*.
Lebedev, B. A. See Rode, E. Ya.
Lebedeva, K. P., and Baraboshkin, A. N. Effect of the conditions of electrolysis on the structure of zirconium precipitates (I) electrolysis of molten chlorides containing quadrivalent zirconium; (II) effect of fluorine ions on the structure of zirconium precipitates, B (1) 30*e*.
Lebedkova, A. A. See Ibraimov, M. I.
LeBlanc, R. E. See Adamsky, R. F.
Leca (World), Ltd. Process and rotary kiln for the production of a lightweight material from wet plastic clay, P (3) 80*f*.
Lecerf, A., Hagenmuller, P., Villers, G., and Guillaud, C. New ferromagnetic materials and their manufacture, P (7) 157*a*.
Leck, J. H. See Christian, R. G.
Le Claire, A. D. Diffusion and thermal defects in solids, B (5) 140*b*.
LeCraw, R. C., Gyorgy, E. M., and Van Uitert, L. G. Longitudinal radio-frequency resonance in YIG, (10) 271*b*.
Lecrivain, L. Use of sonic tests in a research and testing laboratory, (2) 51*e*.
Ledoux, R. L., and White, J. L. Infrared studies of hydrogen bonding interaction between kaolinite surfaces and intercalated potassium acetate, hydrazine, formamide, and urea, (1) 20*a*.
Lee, D. W. See Doherty, P. E.
Leeds Fireclay Co., Ltd. Heat resistant plug-stoppers, P (8) 181*e*.
Leeds & Northrup Co. Immersion thermocouple assembly, P (3) 81*d*. Thermocouple assembly, P (1) 14*g*.
Leedy, N. J. See Roberson, C. L.
Leers, K. J. See Hennicke, H. W.; Kupzog, E.
Leet, G. M. Glass water still with automatic safety switch, (7) 159*f*.
Lefevre, J. Study of the zirconia-scandium oxide system—a comparison with other systems of the type AO_2-M_2O_3, (2) 56*f*.
Lefevre, M. A. Apparatus for grinding brick or the like, P (3) 70*f*.
Le Flem, G., and Hagenmuller, P. System V_2O_3-ThO_2, (1) 29*h*.
Leflet, H. A., Jr. Method and apparatus for bending and tempering glass sheets, P (1) 5*c*. Sheet supporting apparatus, P (8) 179*a*. See Carson, F. J.
Leflet, H. A., Jr., and Carson, F. J. Method of bending a glass sheet for producing a vehicle window, P (9) 221*c*.
Leflet, H. A., Jr., and Wampler, D. M. Method of bending glass sheets, P (1) 5*h*. Method of producing pattern-cut bent glass sheet, P (1) 6*e*.
Le Gras, J. See Tailleur, A.
Legros, J. Devitrification of titanate glasses subjected to cosmic rays, (9) 217*g*.
Lehmann, H. Up-to-date testing methods for the investigation of refractories, B (5) 141*i*. See Hennicke, H. W.
Lehmann, H., et al. Investigations on changes in the properties of the permanent tar-dolomite lining of a basic converter with increasing time in service, (10) 257*c*.
Lehmann, H., and Lindner, K. H. Effect of fine-grinding on the inversion behavior of quartz and quartz-mineralizer mixtures during firing, (8) 195*h*.
Lehmann, H., and Lorenz, W. Measurement of the pH of feldspar suspensions, (5) 137*b*.
Leibowitz, D., and Sommer, A. Segmented ferrite-sonar transducer with permanent magnet bias, P (4) 102*b*.
Leidheiser, H., Jr. See Jackson, D. A., Jr.
Leimer, H. Automatic manufacture of stoneware pipe, (3) 70*a*, (8) 179*c*.
Leinauer, H. See Kerkhof, H.
Leineweber, G., and Neugebauer, W. Process for making silicon carbide, P (5) 124*j*.
Leipold, M. H. See Nielsen, T. H.
Leipziger, F. D. See Kestigian, M.
Leisenberg, M. Process and device for improving combustion and regulating the height of the flame in an oil furnace, particularly for ceramics, P (10) 268*b*.
Leiser, D. B., and Whittemore, O. J., Jr. System LiI-KI, (2) 57*e*.
Leistiko, O., Jr., and Sah, Chih-Tang. Field-effect transistors, P (10) 264*a*.
Leistikow, S. See Jaenicke, W.
Leitten, C. F., Jr. See Robinson, W. C.
Leitten, C. F., Jr., Potter, R. A., and McDonald, R. E. Method of preparing oxides for neutronic reactor control, P (4) 98*g*.
Leitz, Ernst, G.m.b.H. See Ernst Leitz G.m.b.H.
Lejsek, L. Experience in Czechoslovakia with calcium sulfate obtained as a by-product in chemical processes, (9) 214*j*.
Leko, V. K. Influence of cation field strength on structure and electrical properties of silicate glasses, B (9) 245*i*. See Petrovskii, G. T.
Leko, V. K., and Dorokhova, M. L. Dielectric loss in glasses and certain crystalline glass materials, B (4) 113*f*.
Lele, R. V., and Ray, R. N. Low solubility lead borate glaze (I), (2) 46*e*.
Lemardeley, C. Y. L. See Barrot, P. M. E.
Lemmens, H. J., and Zalm, P. Double layer oxide cathode with reducing agent, P (10) 263*d*.
Lendvay, E. Monocrystals of Mn phthalate, (1) 23*b*. Nucleation in diffusion crystal growing, (1) 24*d*.
Lenfestey, R. de J. Use of low melting point alloys in the shaping of pottery, (9) 228*c*.
Lent, W. E. See Gates, L. E., Jr.
Lenton, K. W., and Badzer, F. G. Manufacture of building bricks with transversely directed perforations or recesses, P (1) 6*i*.
Lentz, A. E., and Monfore, G. E. Thermal conductivities of portland cement paste, aggregate, and concrete down to very low temperatures, (1) 2*a*.
Lentz, E. C. See Kerns, K. K.
Lenzo, P. V., Turner, E. H., Spencer, E. G., and Ballman, A. A. Electrooptic coefficients and elastic-wave propagation in single-domain ferroelectric lithium tantalate, (5) 135*j*.

Leonard, L. B. Glass electrode with metal frame support and method of making thereof, P (11) 278*a*.

Leonhardt, H. R. Synthesis of GaAs by vapor transport reaction, (9) 242*c*.

Leopold, F. Process for the production of very strong briquets, P (10) 260*b*.

Leppanen, K. See Nasanen, R.

Lepselter, M. P. Integrated circuit device and method, P (10) 264*e*. Semiconductor contacts and protective coatings for planar devices, P (2) 49*c*. See Kahng, D.

Lepselter, M. P., and Naymik, D. A. Method of making integrated semiconductor devices, P (5) 128*b*.

Leroux, J. P. Particle classifier, P (9) 236*d*.

LeRoy, J. Enameled product for various uses, P (11) 276*a*.

Leroy, P., and Simon, R. Method of making porous refractory products, P (9) 226*f*.

Lersmacher, B. See Nacken, M.; Scholz, S.

Lescelius, T. J. See Sermon, G. T.

Leschen, J. G. Titanium ceramic composite bodies, P (4) 103*b*.

Leschonski, K. See Rumpf, H.

Leshchenko, N. P. See Ivakhin, S. I.

Lesinski, C. A. Scale removal, ferrous metal passivation, and compositions therefor, P (5) 117*g*.

Leskauskas, B. See Sasnauskas, K.

Leslie, B. C. See Kegley, T. M., Jr.

Lesnik, N. D. Poreless materials of high hardness prepared by impregnation, (10) 258*g*.

Lessor, A. E., Jr. See Dobbin, W. J.

Letter, E. C. Fusion of glass particles with brief high intensity light flashes, P (11) 278*c*. Method of making optical elements from Ba or Mg fluoride containing boron nitride, P (7) 150*c*. Optical shutters, P (3) 69*h*.

Leusden, C. O. P. Design of dies for the manufacture of curved pipes, (3) 70*c*.

Levandowsky, L. See Blin, C.

Levavasseur, G., and Frisby, H. Ultrasonic study of the distribution of cracks and pores in sintered beryllia, (2) 59*i*.

Leve, E. N. See Pirogov, A. A.

Levecque, M. Formation of glass mats, P (9) 220*a*.

Levecque, M., and Brion, H. Fiber glass [sheet] product and method of making it, P (9) 219*i*.

Levecque, M., Mabru, M., and Charpentier, M. Apparatus for producing fibers from thermoplastic material, P (2) 38*h*.

Leveskis, N. G. Polishing process, P (9) 213*f*.

Levin, D. I., and Nikulina, L. N. Behavior of potash and calcium-soda feldspars during heating, (3) 82*d*.

Levin, E. M. Structural interpretation of immiscibility in oxide systems (IV) occurrence, extent, and temperature of the monotectic, (2) 56*a*. System Sc_2O_3-B_2O_3, (2) 57*a*. System Y_2O_3-V_2O_5, (8) 209*f*.

Levine, A. K., and Natansohn, S. Method and apparatus for the heat treatment of synthetic mica, P (10) 269*g*.

Levine, M. W., and Subramanian, M. Cathodoluminescence of ruby, (2) 54*f*.

Levinson, A. A., and Vian, R. W. Hydrothermal synthesis of montmorillonite group minerals from kaolinite, quartz, and various carbonates, (1) 19*d*.

Levinstein, H. See Norton, B.

Levinstein, H. J. See Abrahams, S. C.; Nassau, K.

Levinstein, M. A. See Foldes, S.

Levitskii, V. K. See Soldatov, G. A.

Levitt, A. P. See Grenis, A. F.

Levitt, C. M., and Nabarro, F. R. N. Impact strength of diamond under different rates of strain, (8) 199*h*.

Levitt, R. S., and Weiser, K. Photoelectronic semiconductor devices comprising an injection luminescent diode and a light sensitive diode with a common *n* region, P (2) 48*i*.

Levy, M., and Wong, P. Oxidation of pyrolytic graphite at temperatures of 1400° to 1800°F and at air velocities of 25 to 100 cm/sec, (7) 166*f*.

Levy, P. W. Annealing of the defects and color centers in unirradiated and in reactor irradiated Al_2O_3, (3) 83*h*.

Lewis, A. See Barnet, F. R.

Lewis, A. E. Use of index of refraction liquids for the measurement of the refractive index of thin transparent films on silicon, (3) 81*i*.

Lewis, B. See Oldfield, L. F.

Lewis, C. J., and De Ment, E. R. Process for producing iron oxide pigments, P (11) 291*i*.

Lewis, D. W., and Tierney, P. A. Thermoelectric unit comprising intimate layers of gallium-indium alloy and alumina, P (11) 288*a*.

Lewis, G. L. See Emslie, R. S.

Lewis, G. L., and Sowards, D. M. Process for producing fibrous alkali metal titanates, P (10) 265*i*.

Lewis, J. C., and Floyd, I. J. Reorientation effects in vitreous carbon and pyrolytic graphite, (10) 271*g*.

Lewis, J. G., and Ohlgren, H. A. Method for forming a refractory metal or carbide coating on refractory materials and article, P (5) 117*i*.

Lewis, M. F., and Lacklison, D. E. New mode in axially magnetized YIG rods, (11) 298*c*.

Lewis, M. H. Defects in spinel crystals grown by the Verneuil process, (8) 194*g*. Microstructure of magnesium oxide cleavage surfaces, (1) 23*c*.

Lewis Engineering Co. Thermocouple probe construction, P (2) 52*b*.

Li, C. H. See Liu, T. S.

Li, Che-Yu, and Blakely, J. M. Defects near ionic crystal surfaces, B (9) 245*f*.

Li, Chia-chih, Lo, Chie-yueh, and Cheng, Hu-ming. Investigation of internal friction of photosensitive glass-ceramics in the system Li_2O-K_2O-Al_2O_3-SiO_2, B (9) 246*a*.

Li, Chi-fa. See Kuznetsov, V. G.; Morozov, I. S.

Li, Pei-Ching. Method for making single crystal graphite sheets, P (2) 44*a*.

Liang, Ching-kuei. See Golutvin, Yu. M.

Libbey-Owens-Ford Glass Co. Apparatus for continuous production of glass sheets, P (8) 176*d*. Apparatus for glass inspection and sorting having contour sensing means, P (7) 149*g*. Apparatus for inhibiting upward rising bubbles in a molten metal bath, P (10) 254*j*. Apparatus for press bending glass sheets, P (3) 67*e*, P (10) 254*c*. Apparatus for preventing devitrification of molten glass at the joints of a glass furnace, P (4) 93*g*. Apparatus for producing a laminated assembly, P (5) 120*a*. Apparatus for protecting the withdrawing rollers of a molten metal bath in a glass sheet making operation, P (8) 176*k*. Blending of granular materials, P (3) 80*f*. Cooler compensating heater for temperature control in glass making, P (10) 254*i*. Enclosure means in a glass sheet drawing apparatus, P (9) 219*h*. Glass contacting refractories, P (9) 225*h*. Glass manufacture, P (4) 94*h*. Glass polishing composition comprising a water-soluble zinc salt, P (8) 177*d*. Increasing the melting rate of glass batch, P (9) 220*a*. Insulated edge roller for window glass machine, P (10) 255*g*. Laminated glass, P (2) 38*i*. Liptile mounting, P (3) 68*d*. Means for maintaining sheet width while drawing sheet glass, P (3) 68*d*. Method and apparatus for automatic glass cutting, P (2) 29*b*. Method and apparatus for bending and tempering glass sheets, P (1) 5*c*. Method and apparatus for consolidating batch, P (3) 68*e*. Method and apparatus for forming a film on a glass surface, P (5) 120*j*. Method and apparatus for press bending and tempering glass sheets, P (11) 278*h*. Method and apparatus for producing a continuous glass ribbon, P (11) 278*i*. Method and apparatus for producing window glass sheets, P (10) 255*c*. Method of bending a glass sheet for producing a vehicle window, P (9) 221*c*. Method of bending glass sheets, P (1) 5*h*. Method of coating glass for subsequent soldering, P (3) 68*b*. Method of finishing glass, P (10) 255*h*. Method of producing pattern-cut bent glass sheet, P (1) 6*c*. Method of sealing metal to glass, P (9) 221*h*. Package [carbon] for glass sheets, P (7) 150*a*. Rare earth chlorides in a glass polishing composition, P (8) 178*j*. Seal for and method of packing joints in a glass furnace P (11) 279*d*. Sheet handling apparatus for glass plates, etc., P (9) 222*d*. Sheet supporting apparatus, P (8) 179*a*. Storing glass sheets, P (4) 95*g*.

Libchaber, A. See Nanney, C. A.

Licencia Talamanyokat Ertekesito Vallalat. Calcium aluminate ferrite cements, P (8) 174*b*. Cement additives, P (5) 116*d*.

Licentia Patent-Verwaltungs-G.m.b.H. Method of improving *pn* junctions, P (2) 48*j*. Method for making a semiconductor device, P (5) 128*b*. Process for production of electrically unsymmetrical semiconducting device, P (11) 278*f*. Use of silicon in semiconductor devices, P (5) 129*d*.

Lichter, B. D., and Bredig, M. A. Solid and liquid phase miscibility of calcium metal and calcium fluoride, (11) 301*b*.

Lidiard, A. B., and Perrin, R. Growth of interstitial clusters in graphite under irradiation, (8) 199*a*.

Lieb, N. H., Rosenbluth, H. E., and Turchi, A. J. Combination bladed bur diamond drill, P (7) 145*f*.

Liebau, F. Criterion for the stability of silicate structures, (5) 134*h*.

Lieber, W. Effect of zinc oxide on the setting and hardening of portland cements, (7) 146*d*.

Liebmann, W. K. Orientation of stacking faults and dislocation etch pits in β-SiC, (3) 87*d*.

Liebmann, W. K., and Spielmann, W. K. Method of pulling monocrystalline silicon carbide, P (1) 8*c*.

Liebson, S. H. Method for growing single thin film crystals, P (11) 286*h*.

Ligenza, J. R. See Gobeli, G. W.; Kahng, D.

Light, T. B., and Wagner, C. N. J. X-ray diffraction study of vacuum-evaporated silver films, (2) 59*e*.

Lightbody, A. See Barnet, F. R.

Lignes Telegraphiques et Telephoniques. Ferromagnetic materials and method of fabrication, P (11) 285*d*.

Ligon, E. R. Horizontal auger extrusion of large pipe, (7) 150*i*.

Lileev, I. S. See Dubrovo, S. K.; Permyakova, T. V.

Liley, P. E. See Powell, R. W.

Lilley, T. H. See Covington, A. K.

Limes, R. W., and Ponzani, D. Basic refractory compositions for intermediate temperature zones, P (2) 43*e*.

Limes, R. W., and Russell, R. O. Basic refractory compositions, P (5) 124*c*. Carbon-bearing refractories, P (5) 124*c*.

Limpel, E. J. Method and apparatus for fusing a coating to a metal surface P (2) 35*d*.

Lin, C. C. See Schieber, M. M.

Lin, F. C. M. Preshaped two-phase glass-ceramic body and process for preparing the same, P (2) 39*i*.

Lin, H. C. Diode structure in semiconductor integrated circuit and method of making the same, P (10) 263*d*.

Linares, R. C., Jr. See Ballman, A. A.

Lind, M. D. See Geller, S.

Lindblad, F. W. Grinding wheel, P (3) 63*h*. Method of making a saw, P (3) 63*f*.

Lindmayer, J., and Reynolds, J. H. Charge distribution in thermally grown silicon dioxide, (2) 54*g*.

Lindner, K. H. See Lehmann, H.

Lindquist, O., and Wengelin, F. Crystal structure of a potassium tellurate, (8) 193*c*.

Lindquist, R. H. See Kuendig, W.

Lindsay, J. G. See Bakker, W. T.

Lindsley, D. H. See Buddington, A. F.

Lindstrom, G. A. Process for polishing crystals, P (9) 213*g*.

Lindvall, F. See Musha, T.

Line, L. E., Jr. See Forney, H. B.

Linford, H. B. See Kane, J. C.

Ling, F. F. Deformational and geometrical aspect of surfaces in sliding contact, B (8) 212*i*.

Ling, I. See Adamson, A. W.

Lingl, H. Device for stacking unfired brick on a carrier, P (2) 50*a*.

Lingl, H., Jr. Development of brick manufacturing methods in recent years, (8) 179*f*.

Linhart, O. C. See Van Dolah, H. J.

Link-Belt Co. Slurry mixing apparatus, P (2) 35*b*.

Linton, H. R. See Marshall, W. J.

Lintz, M. Preparation of fluorspar, P (1) 16*b*.

Lipka, A. See Behr, H.

Lipovskii, I. E., and Nashel'skii, A. M. Mechanical strength of fused rock at high temperatures, (5) 123*c*.

Lippman, A., Jr. See Floyd, J. R.

Lippmann, R. J., and Mumford, E. H. Apparatus and method for press molding glass articles, P (3) 67*d*. Reciprocating glass pressing apparatus, P (10) 256*a*.

Lirones, N. G. Method of making shell molds for casting reactive metals, P (9) 226*h*. Method of preparing an investment mold for use in precision casting, P (4) 98*f*. Method for shaping beryllium and other metals and ceramics, P (5) 124*e*.

Lisityn, S. M. See Grodshtein, A. E.

List, H. Method for the direct measurement of pressure differences, P (4) 104*j*. Piezoelectric device, particularly a force measuring instrument and the process of manufacturing same, P (1) 11*a*. Piezoelement, in particular for piezoelectric force measuring instruments, P (1) 11*b*.

Lisy, A. See Matousek, J.

Lithium Corp. of America, Inc. Lithium oxide having active absorption capacity for carbon dioxide and method of preparing same, P (9) 235*j*.

Litovitz, T. A., and Macedo, P. Ultrasonic relaxation, viscosity, and free volume in molten glasses, B (2) 61*h*.

Little, Arthur D., Inc. See Arthur D. Little, Inc.

Litton Precision Products, Inc. Cathode ray tube including faceplate comprising tapered fiber optical elements mounted in an opaque mosaic, P (5) 127*c*. Method for lowering index of refraction of glass surfaces, P (8) 178*a*. Method of making a glass sheet having a plurality of spaced wires therein, P (5) 121*c*.

Litton Systems, Inc. Apparatus for cathode sputtering including a plasma-confining chamber, P (3) 77*j*. Reduction of oxides by ion bombardment P (11) 287*a*.

Litvan, G. G. Phase transitions of adsorbates (I) specific heat and dimensional changes of the porous glass-water system, (3) 87*b*.

Litz, L. M. See Criscione, J. M.

Liu, Chun-yang. See Shiau, Y. G.

Liu, Chun-yang, and Shiau, Y. G. Study on silica alumina with high alumina content prepared by the cogelling method (II) changes in surface property during the preparation process, (1) 15*i*.

Liu, S. G. Infrared and microwave radiations associated with a current-controlled instability in GaAs, (11) 297*g*. See Chang, K. K. N.

Liu, T. S., Stokes, R. J., and Li, C. H. Cold work and the ductile-brittle transition of silver chloride, (3) 84*a*.

Livey, D. T. See Hey, A. W.

Livshits, A. L. See Bannikov, G. K.

Livshits, Yu. S. Production of aluminized mirrors, (3) 66*f*.

Llavona, F. Selection of refractories, (5) 123*b*.

Lloyd, J. E., and Martin, F. S. Coating with beryllia, P (3) 65*c*.

Lloyd, M. H. Preparation of plutonium oxide sol and calcined microspheres, P (7) 153*g*.

Lloyd, R. D. Apparatus and method for discharging receptacles, P (8) 186*j*. Method and apparatus for removing blockage of material in transporting conduits, P (8) 186*i*.

Lloyd, T. W. Metal encased refractory, P (9) 226*c*.

Lo, Chie-yueh. See Li Chia-chih.

Lo, Mei-Kuo. See Gabrysh, A. F.

Lobanov, E. M., Solodovnikov A. O., Krylov, B. E., Nudel'man, B. I., and Rozov, M. N. Study of lining conditions by means of radioactive isotopes, (9) 234*c*.

Locardi, B., Bonetti, G., and Gottardi, V. Effect of boron coordination on the reactivity of glasses with lead oxide, (10) 251*b*.

Loch, L. D. High beta thermistors, P (11) 285*f*.

Locher, F. W. Sulfate resistance of slag cements, (1) 2*d*.

Lockett, J. A. See Astbury, N. F.

Lockett, P. F. See Hullhorst, W. B.

Lockhart, A. W. Composition and process for production of flame colorants, P (11) 278*c*.
Lockheed Aircraft Corp. Ferrimagnetic pressure transducer, P (5) 127*c*.
Lockwood, D. L. See Paulley, D. S.
Lockwood, G. H. See Heytmeijer, H. R.
Lockyer, G. E., and Proudfoot, E. A. Non-destructive determination of mechanical properties of refractory materials, (7) 159*j*.
Locsei, B. Effect of small quantities of aluminum fluoride additives on the strength of refractory materials, (5) 122*d*. Processes during firing of ceramic products (I) increase of Al_2O_3 content of porcelain; (III) processes during the firing of porcelain in the presence of fluorides, (1) 9*b*. Relation between refractoriness under load and alumina content bound as mullite of aluminosilicate refractories, (1) 7*h*.
Locsei, B., Kocsis, G., and Somogyi, A. Increase of production capacity of drawn sheet glass manufacture by changing technological parameters, (1) 3*f*. Investigation of a defect on the surface of safety glass, (1) 3*i*.
Lode, W. See Dettmar, H. K.
Lodholz, J. C. See Tillett, T. J.
Loedige, F. See Loedige, W.
Loedige, W., Loedige, F., and Luecke, J. Mixing apparatus, P (10) 266*d*.
Loeffler, J. Glass melting vats having refractory bricks containing chromium oxide, P (1) 5*f*.
Loeffler, R. F. Thermocouples, resistance temperature detectors, thermistors—which? (9) 234*f*.
Loehrke, H. F., and Van Zee, A. F. Hermetically sealing glass parts including intervening electrical conductor, P (3) 68*b*.
Loew, G. A. Ceramic loaded buncher for linear accelerators, P (11) 285*a*.
Logachev, M. S. See Strelets, V. M.
Logan, R. A. See Cohen, B. G.; Trumbore, F. A.
Logan, R. K. Electroluminescent device including a dielectric substrate having a plurality of closely spaced thin wire conductors passing therethrough, P (3) 78*d*.
Loginov, N. A. See Smirnov, M. V.
Lohrengel, H. Isostatic pressing techniques, (9) 232*i*.
Loiacono, G. M. See Nassau, K.
Loiselle, A. A., Jr. See Rowse, R. A.
Lombos, B. A., and Somogyi, T. R. Multiple slice epitaxial deposition of silicon in resistance heated furnace, (4) 100*i*.
Long, B. Continuous method of making a glass sheet, P (4) 94*b*. Glass-drawing apparatus including reheating means for producing flat sheets, P (4) 94*g*. Method of making a multicellular vitreous sheet on a molten metal bath, P (2) 39*j*.
Long, J., Juillet, F., and Teichner, S. J. Properties of titania (anatase) formed in a flame reactor, (1) 27*g*.
Long, R. K., Mize, J. P., and Windecker, R. T. Method for making a *pnpn* device by diffusing, P (8) 185*g*.
Long, R. S., Ellis, D. A., Cox, K. E., and Magner, J. E. Titanium dioxide pigment and method for preparation thereof, P (10) 270*b*.
Long, S. A. See Hyatt, E. P.
Longenecker, L. S. Veneer furnace wall construction, P (9) 235*c*.
Longin, H. Experience in controlling the wear processes of the refractory linings of basic oxygen LD furnaces, (7) 151*j*.
Longo, F. N. Self-fusing flame spray material, P (5) 117*h*.
Longo, J. M. See Kierkegaard, P.
Longo, J. M., and Kierkegaard, P. Crystal structure of $NbOPO_4$, (1) 17*h*.
Longo, T. A., and Miller, M. Four-layer semiconductor switching device having turn-on and turn-off gain, P (7) 156*c*.
Longwell, J. A. See Borom, M. P.
Lontz, H. M. See Hazdra, J. J.
Lontz, H. M., Taylor, E. C., and Ryder, R. J. Identification of hot-end surface coatings—estimate of thickness using X-ray fluorescence techniques, (2) 36*i*.
Lonza-Werke Elektrochemische Fabriken G.m.b.H. Fired refractory shape and process for its manufacture, P (9) 225*f*.
Loomis, T. C. See Senhouse, L. S., Jr.
Loomis, T. C., and Storks, K. H. X-ray microanalysis in chemistry, (9) 234*b*.
Loopstra, B. O., and Boldrini, P. Neutron diffraction investigation of WO_3, (8) 203*f*.
Loose, G. H. Method and apparatus for coating electrical components, P (7) 156*j*.
Lopenski, S. A. Method and apparatus for coating electric lamp bulbs, P (1) 5*d*.
Lopez, J. M. Expansion vs. fracture in fired ceramics, (4) 89*j*.
Loral Electronics Corp. Yttrium iron garnet preselectors, P (4) 103*b*.
Lord, P. A. See Akmenkalns, I. G.
Lorenz, M. R. Chemical polish for lead telluride, (9) 229*b*.
Lorenz, W. Suspension effect, (5) 138*i*. See Lehmann, H.
Lorenzini, R. E. Crystal growing apparatus, P (11) 285*b*. Crystal growth sampler, P (11) 285*c*.
Lorey, F. D. Reboil phenomena in glass, (1) 4*d*.
Lorinczy, A., Nemeth, T., and Szebeni, P. Microinhomogeneities in Ge single crystals, (1) 23*b*.
Loro, A. Method for making a semiconductor device by diffusing impurities through spaced-apart holes in a nonconducting coating to form an overlapped diffused region by means of transverse diffusion underneath the coating, P (5) 128*c*.
Lotz, H. See Rachor, L.
Loubser, J. H. N. See Van Rynveld, W. P.
Loughridge, F. A. Process for fabricating arc tubes, P (2) 39*j*.
Louisnathan, J. See Moore, P. B.
Loukes, D. G., and Banner, J. G. Method of manufacture of flat glass on molten tin, P (5) 121*e*. Process of manufacturing flat glass on a molten metal bath, P (11) 279*i*.
Loukes, D. G., and Edwards, A. Method of removing impurities in a molten metal bath for glass sheet making, P (10) 255*i*.
Loup, J. P., and Anthony, A. M. Ionization of air in a furnace and measurement of the resistivity of magnesia between 1500° and 1800°C, (1) 20*f*.
Louzos, D. V. See Powers, R. A.
Lovicz, V. See Knowles, A. R.
Lovisetto, L. See Ascoli-Bartoli, U.
Lovoos, J. P. Carlton Ball—master potter, (5) 115*j*.
Low, M. J. D., and Argano, E. S. Sorption of activated hydrogen on Vycor glass, (9) 218*j*.
Lowe, C. L., Jr. See Rollins, F. E.
Lowe, I. R. G. See Hughes, B. P.
Lowe, S. W., Jr. Apparatus for forming and collecting filamentary materials, P (1) 4*c*.
Lowell, C. E. Solid solution of boron in graphite, (4) 109*i*.
Lubalin, I. J. Manufacture of ceramic shapes or bodies, P (7) 158*j*.
Lubatti, E. Apparatus for the production of abrasive carbides, P (4) 104*h*.
Luby, C. S. See Goeddel, W. V.
Lucas, J. W., Newton, G. W., and Sing, K. S. W. Surface properties of precipitated alumina (V) a radiochemical investigation of chloride-ion contamination, (2) 57*a*.
Lucas, Joseph, (Industries), Ltd. See Joseph Lucas (Industries), Ltd.
Luce, B. M. Electroless plating of gold, P (5) 127*j*.
Luce, E. C. Which diamond wheel for space age ceramics? (7) 145*g*.
Ludowici, J. W. Baking ceramic or loose material, P (1) 14*j*.
Ludwig, P. F. See Hofstadt, C. E.
Ludwig, R. Effect of mineralogical and physical properties of the raw meal on burning behavior in the rotary kiln, (7) 146*b*.
Ludwig, W. Dynamics of a crystal lattice with defects, B (4) 114*b*.
Lueck, A. M. Small light sensor package, P (1) 11*i*.
Luecke, J. See Loedige, W.
Luertzing, P. R. Apparatus for the centrifugal molding of articles in split molds, P (3) 67*b*.
Luertzing Corp. Apparatus for the centrifugal molding of articles in split molds, P (3) 67*b*.
Luetzel, W. G. See Haltner, A. J.
Luginina, I. G., Zakharov, V. P., and Klassen, V. K. Origin of clinker dust, (9) 215*c*.
Lukacs, J. See Abrecht, H.
Lukashenko, G. M. See Eremenko, V. N.
Lukashenko, G. M., and Eremenko, V. N. Thermodynamic properties of magnesium silicide, (11) 302*h*.
Lukashenko, G. M., Eremenko, V. N., and Sidorko, V. R. Thermodynamic study of the silver-antimony system, (4) 112*c*.
Lukaszewski, G. M. Differential thermal analysis (IX) heat conduction problem in DTA; (X) influence of the rate of heat transport; (XI) central consideration of thermoanalytical systems, (10) 267*e*.
Luke, C. L. See Trumbore, F. A.
Lukes, R. M. See Abolins, V.
Lukin, E. S., and Poluboyarinov, D. N. Thermomechanical properties of pure oxide ceramics, (7) 152*f*.
Lukin, E. S., and Serova, G. A. Some properties of refractory materials made of calcium oxide, (4) 97*a*.
Luks, D. W. Ceramic products and process of making same, P (3) 74*i*.
Luk'yanova, T. T. See Zhunina, L. A.
Lummus Co. Flare apparatus for combustible gases, P (9) 234*j*.
Lundberg, M. Crystal structure of $LiNb_6O_{15}F$, (8) 193*g*.
Lundberg, M., and Andersson, S. Phase analysis studies in the LiF-Nb_2O_5 system, (8) 204*d*.
Lundstrom, T. New phases in the Zr-P and Zr-As systems, (10) 271*g*.
Lundy, T. S., and Federer, J. I. Method for separating grain-boundary and lattice diffusion effects in polycrystalline materials, (3) 86*i*.
Lunghard, J. Examination of costs in the porcelain industry, (3) 74*b*.
Lunsford, G. Method and apparatus for cathode sputtering using a cylindrical cathode, P (8) 185*a*.
Lunter, S. G. See Karapetyan, G. O.
Lur'e, M. A., Kamenetskii, Yu. L., and Volchenok, M. K. Economics of introducing new techniques in the refractories industry, (9) 223*j*.
Lusher, K. G. Method and apparatus including flexible conductive offset member for decorating articles, P (1) 5*e*. Partially devitrified glass article and method for making the same, P (4) 95*i*.
Luth, W. C. System $KAlSiO_4$-Mg_2SiO_4-$KAlSi_2O_6$, (5) 139*c*.
Luthi, B. Magnetoacoustic birefringence in magnetite and nickel, (5) 137*b*.
Luza, F. See Husa, V.
Luzhnaya, N. P. See Kalitin, V. I.
Luzhnaya, N. P., Slavnova, G. K., Medvedeva, Z. S., and Eliseev, A. A. System In-As-Se, (8) 208*f*.
L'vov, S. N., Nemchenko, V. F., and Samsonov, G. V. Effect of nonmetallic atoms on the electrical properties of high-melting compounds of transition metals, (3) 85*d*.
Lykken, W. H., Freysinger, H. L., and Bercaw, J. W. Reject spouts, P (9) 236*f*.
Lynch, C. T. See Mazdiyasni, K. S.; Mersol, S. A.; Vahldiek, F. W.
Lynch, C. T., Mersol, S. A., and Vahldiek, F. W. Microstructure of single-crystal titanium diboride, (11) 298*i*.
Lynch, H. R. Apparatus for cutting [sheet] glass, P (1) 4*c*.
Lynnworth, L. C. See Carnevale, E. H.
Lyon, J. E. See Herbst, H. J.
Lyon, J. E., Fox, T. U., and Lyons, J. W. Phosphate bonding of magnesia refractories, (1) 7*f*.
Lyon, K. C. See Jelinek, J. W.
Lyon, K. C., and Jelinek, J. W. Glass blowing machine having controlled blow pressure, P (1) 5*b*.
Lyon, W. L. Preparation of a filterable coprecipitate of plutonium and uranium, P (3) 72*d*.
Lyons, J. W. See Lyon, J. E.
Lyons, L. R., and Powell, R. L. Production of substantially anhydrous magnesium chloride, P (11) 292*b*.
Lyons, S. C. Method of treating [pumping] clay, P (9) 236*b*.
Lyons, V. J. See Compton, D. M. J.
Lytle, F. W. X-ray absorption fine structure in crystalline and noncrystalline materials, B (2) 61*e*.
Lyubarskii, I. M., and Gol'dshtein, M. E. Wear-resistant nickel phosphide coatings, (2) 43*i*.
Lyubimov, V. D. See Gel'd, P. V.
Lyutaya, M. D., Samsonov, G. V., and Khorpyakov, O. T. Nitrides of germanium, (11) 298*f*.
Lyutsareva, L. A. See Poluboyarinov, D. N.
Lyutsedrauskii, V. A. See Azarov, K. P.; Budnikov, P. P.
Lyutskanov, S., and Kovacev, R. Properties of low-melting glasses in the ZnO-PbO-B_2O_3-SiO_2 system, (3) 66*f*.

M-O Valve Co., Ltd. Low-pressure gas-filled discharge device having an envelope comprising metal parts at different potentials in operation insulated from one another by ceramic members, P (11) 285*j*.
Maatman, R. W. See Dugger, D. L.
Mabbs, F. E., and Barnard, B. Production of titanium dioxide, P (11) 292*b*.
Mabey, D. H. See Christensen, F. L.
Mabru, M. Apparatus for the production of fibers from organic or inorganic thermoplastic materials, P (2) 38*j*. Process and apparatus for the manufacture of fiber mats, P (4) 95*c*. See Levecque, M.
McAdie, H. G. Production of calcium sulfate hemihydrate, P (7) 147*d*.
McAleer, W. J. See Barkemeyer, H. R.; Rosenberg, R.
McAleer, W. J., Kozlowski, M. A., and Pollak, P. I. Polycrystalline silicon films on foreign substrates, (3) 76*g*.
MacArthur, R. A., and Garnero, A. L. Expanded perlite and method, P (9) 235*g*. Method for the formation of perlite structures, P (9) 223*b*.
Macarthys, Ltd. Indicating devices for heat treatment, P (9) 234*d*.
Macartney Patents, Ltd. Pulverizing apparatus, P (5) 133*f*.
McAuley, W. J., Rhodes, E., and Ubbelohde, A. R. Equivalent volumes of mixtures of molten alkali and alkaline earth nitrates, (8) 197*c*.
MacAvoy, T. C. Liquid and amorphous materials—structure and properties, B (9) 244*e*.
McBride, J. Semiconductor encapsulating and reinforcing materials utilizing boron nitride, P (2) 49*g*.
McCade, C. L. See Dancy, E. A.
McCaldin, J. O., and Widmer, A. E. Method of treating semiconductor device by ionic bombardment, P (9) 231*c*.
McCall, C. I. Thermocouple probe construction, P (2) 52*b*.
McCallum, D. W. See Erwin, L. R.
McCamont, J. W. See Bartlett, R. W.
McCarron, R. L. See Belton, G. R.
McCarthy, W. W. See Walker, H. N.
McCarthy, W. W., and Walker, H. N. Sonolation cuts scrap reprocessing time, (9) 228*a*.
McCarthy & Sons, Ltd. Sand-lime mortars, P (7) 147*e*.
McCartney, E. R. See Korob, O.
McCarty, F. G., and Kleppa, O. J. Thermochemistry of the alkali chloride-lead chloride liquid mixtures, (8) 210*b*.
McCaslin, J. F. See Juvinall, J. W.
MacChesney, J. B. See Gallagher, P. K.
MacChesney, J. B., Jetzt, J. J., Potter, J. F., Williams, H. J., and Sherwood, R. C. Electrical and magnetic properties of the system $SrFeO_3$-$BiFeO_3$, (1) 9*i*.
MacChesney, J. B., Williams, H. J., Sherwood, R. C., and Potter, J. F. Magnetic interactions of the system $SrFe_2O_{4.00-4.50}$, (8) 183*e*.
McCleary, R. E., and Kinkade, W. A. Apparatus for making ultrafine calcium sulfate dihydrate crystals, P (5) 116*c*.
McClelland, R. H. See Wiener, R.
McConnaughey, N. See McVey, C. I.
McConnell, B. L. See Dugger, D. L.
McConnell, D. Hydrogen ion incorporation in crystals, (3) 86*g*.
McConnell, R. K., Jr. See Allen, R. V.

McCord, A. T. Organophilic and hydrophobi particles and method for their preparation, P (10) 260*b*. Process for chlorinating oxides, P (3) 72*f*.
McCormick, G. R. Subsolidus equilibria in the system MgO-GeO_2-MgF_2, (1) 29*f*. See Miller, J. L., Jr.
McCormick, G. R., and Ehlers, E. G. Ternary phases in the system MgO-GeO_2-LiF, (9) 242*g*.
McCormick, W. R., and Smith, E. C. Corrosion resistant chlorinator lining, P (10) 259*f*.
McCown, W. E. See Mambourg, J. E.
McCreight, D. O. See Scott, R. K.
McCreight, L. R. Oriented graphitic structure, P (2) 44*i*.
McCurdy, H. R., and Van Orsdel, J. R. Method of preparing W_2C containing a fine dispersion of carbon, P (7) 153*c*.
McCusker, J. H. Method for fabricating thin film transistors, P (4) 101*f*.
McDade, P. J. See Compton, D. M. J.
McDaniel, C. L., and Schneider, S. J. Phase relations in the systems TiO_2-IrO_2 and SnO_2-IrO_2 in air, (11) 299*d*
Macdonald, A. M. G., and Rivero, A. M. Determination of phosphorus with organic base molybdates, (8) 187*f*.
Macdonald, G. L. See Harwood, M. G.
Macdonald, H. F. See Elliott, R. J.
McDonald, R. E. See Leitten, C. F., Jr.
McDonald, W. J. See Adams, R. J.
MacDonell, H. L. Method for electrophoretic separation of materials in a localized area, P (11) 288*j*.
McDonnell Aircraft. Method of making refractory metal structures with an oxidation resistant coating, P (4) 92*b*.
MacDowell, J. F. Nucleation and crystallization of barium silicate glasses, B (7) 170*j*. See Duke, D. A.
McDowell-Wellman Engineering Co. Iron-containing flux material for steelmaking process, P (7) 153*f*, P (8) 181*f*. Manufacture of expanded shale, P (9) 223*a*. Method of making lightweight aggregate from fly ash, P (9) 223*b*.
Macedo, P. See Litovitz, T. A.
Macedo, P. B., and Napolitano, A. Effects of a distribution of volume relaxation times in the annealing of BSC glass, (10) 251*e*.
Macfarlane, J. C., and Weaver, C. Low frequency dielectric losses in thin films of NaCl and NaBr, (1) 21*g*.
McFarlane, L. See Foster, K. J.
McGee, J. D. Method of coating fluorescent layer of electron discharge tube, P (1) 11*c*.
McGee, S. W. See Sump, C. H.
McGee, T. D. See Martin, D. M.
McGill, W. C. See Rudness, R. G.
McGill, W. H. Method of thermometer bulb fabrication, P (2) 39*e*.
McGlashen, R. See South of Scotland Electricity Board.
McGlasson, J., Jr., and Nelson, J. T. Vapor deposition mask, P (2) 49*f*.
McGonnagle, W. J. Nondestructive testing, B (7) 170*c*.
McGrath, D. See Hayes, J. C.
McGraw-Edison Co. Ceramic mold, P (2) 46*b*. Glass-encased electric fuses, P (5) 127*e*. Mold design for ceramic casting, P (2) 46*e*.
Mach, R. L. See Krause, I.
McHargue, C. J. See Morgan, C. S.
Machlan, G. R., McKinnis, C. L., and Glaser, H. I. Apparatus for producing fine continuous filaments, P (3) 67*f*.
McIlhenny, W. F. See Bornemann, G. A.
McIlvaine, R. L. Apparatus for conditioning granular material using rotating spokes and aerating cleats, P (5) 130*c*. Mixer including mulling wheel with resilient tire means to facilitate wheel rotation, P (9) 233*b*. Mulling machine, P (10) 266*c*.
McIlwain, M. C. See Werner, W. J.
McIntosh, R. O. See Theodorou, D. G.
MacIver, B. A., and Bergstrom, J. W. Method of forming contacts in semiconductor devices, P (11) 286*f*.
McIver, D. J. See Scruby, S. R.
McIver, G. W. See Scott, J. H., Jr.
Mackay, T. L., and Muller, A. N. Plasma-sprayed dielectric coatings for heat sinks in electronic packaging, (10) 263*b*.
McKee, R. L. Abrasive finishing restores museum pieces, (11) 273*h*. That speed thing, (8) 173*f*. What's ahead for abrasive machining? (9) 213*f*.
McKelvey, H. E. Method and apparatus for bending and tempering glass sheets, P (4) 94*d*. See Black, L. V.; Stilley, G. W.
McKelvey, H. E., and Reese, T. J. Bending mold for glass sheets, P (1) 4*f*.
McKelvy, R. W. Three ways to protect graphite against high temperatures, (2) 43*f*.
McKenna, B. D. Refractory composition, P (10) 260*g*.
McKenney, D. J. See Clyne, M. A. A.
Mackenzie, J. D. Method for making thin film glass elements, P (8) 178*e*. New glasses, (2) 36*j*. Semiconduction in oxide glasses—effects of pressure, B (2) 62*c*. See Kennedy, T. N.; Schwartz, M.
MacKenzie, M. See Grover, J. R.
McKewan, W. M. See Olsson, R. G.
Mackey, J. H., Smith, H. L., and Halperin, A. Optical studies in X-irradiated high purity sodium silicate glasses, (8) 175*h*.
Mackey, J. H., Smith, H. L., and Nahum, J. Competitive trapping in sodium disilicate glasses doped with Eu^{3+}, (8) 175*b*.
McKinnis, C. L. See Machlan, G. R.
Mackley, E. D., and Johns, P. Influence of furnace atmosphere on sintered ferrite density, B (7) 170*i*.
Mackles, L. Glare reducing of glass, P (10) 255*d*.
Macks, E. F. Concentric foraminous shaping means for tubes or bars, P (4) 94*a*.
McLaren, J. R. Production of nuclear fuel materials, P (5) 125*c*.
McLaughlin, W. T. See Clancy, J. V.
McLean, D. A. See Keller, H. N.
McLean, D. A., and Roszteczy, F. E. Use of manganese oxide counterelectrodes in thin film capacitors—the TMM capacitor, (5) 126*i*.
McLeran, W. A., Jr. See Eppler, R. A.
McMahon, J. F. Dryer problems, B (8) 212*d*. See Binns, C. F.
McMaster, A. D. See Gimpl, M. L.
McMaster, H. A. Apparatus for bending glass sheets, P (3) 67*b*. Apparatus for positioning glass plates during laminating, P (1) 4*d*. Conveying apparatus, P (2) 38*b*. Press bending apparatus, P (10) 256*b*. Thermally compensated bed for supporting glass sheets, P (1) 6*d*.
McMaster, H. A., and Nitschke, N. C. Gaseous support bed for conveying and heat-treating glass sheets, P (11) 278*e*. Method of and apparatus for heat treating glass sheets on a gas support bed, P (10) 255*a*. Method of and apparatus for manufacturing glass sheets on a gas support bed, P (10) 255*b*. Method and apparatus for uniformly heating sheet material, P (4) 94*g*.
McMaster, H. A., and Van Zee, A. F. Apparatus providing a gaseous support bed and method for treating glass thereon, P (10) 254*d*.
Macmillan, N. H., and Smith, D. A. Slip plane of lithium chloride and bromide, (8) 207*e*.
McMillan, P. W. Glass-Ceramics, B (11) 304*j*. High-strength glass materials, (5) 119*d*.
McMillan, P. W., and Hodgson, B. P. Method of making bonded metal-ceramic elements, P (9) 217*a*. New glass-ceramics for insulator seals, (4) 93*a*.
McMillan, P. W., and Partridge, G. Preparation of ceramics by controlled crystallization of glasses, B (7) 170*a*.
McMillan, P. W., Phillips, S. V., and Partridge, G. Structure and properties of a lithium zinc silicate glass-ceramic, (9) 218*b*.
McMinn, C. J., and Dewey, J. L. Alumina reduction cell and method for making refractory lining therefor, P (9) 225*j*.
McNabb, A., and Duncan, M. E. Firing deformation of ceramic bodies, (7) 163*f*.
McNally, P. H. See O'Connor, T. L.
McNally, R. N. See Alper, A. M.
McNamara, M. J. Chlorite-biotite equilibrium reactions in a carbonate free system, (8) 192*j*.
McPherson, H. W. Jet operated toilet, P (10) 261*d*.
McQuillan, A. D. See Upadhyaya, G. S.
McShane, P. C. Refractory brick with metal plate bonded by a chloroprene-phenolic adhesive, P (10) 260*f*.
McTaggart, G. D., and Norman, E. K. Ceramic refractory, P (2) 43*g*.
McVeigh, G. S. See Englander, R. A.
McVey, C. I., and McConnaughey, N. Pressure bonded ceramic-to-metal gradient seals, P (9) 231*i*.
McWhan, D. B. Linear compression of α-quartz to 150 kbar, (7) 165*d*.
Madden, G. I., and Van Vlack, L. H. Transformation of quartz to tridymite in the presence of binary silicate liquids, (9) 242*i*.
Maddocks, F. S. See Dobbin, W. J.
Madeyski, A., and Smeltzer, W. W. Preparation and structure of zirconia spheres, (10) 271*e*.
Madlem, K. W. Matrix and particle size effects in analyses of light elements, zinc through oxygen, by soft X-ray spectrometry, B (5) 139*g*.
Maeda, K., and Iida, S. Behavior of CdS crystals under laser light excitation, (10) 270*d*.
Maeda, T., and Mizobuchi, Y. Method of manufacturing film resistors, P (10) 264*d*.
Maeder, H. J. Vibratory grinding mill of the drum type, P (4) 104*a*. See Decker, H.
Maejima, R. See Tokutaka, H.
Maekawa, S. See Sakudo, T.
Maerker, R. Critical look at the testing of frits for cast-iron bathtubs, (10) 249*j*. Enameling furnaces, especially muffle and chamber furnaces, (7) 147*f*.
Maerz Ofenbau Akt.-Ges. Wall constructions for furnaces, P (2) 53*e*.
Maevskii, E. R. See Zaliznyak, D. V.
Mafrica, L. Top closure for high temperature electrostatic precipitator, P (3) 80*f*.
Magder, J. Foamed ceramic, P (10) 259*h*. See Kiss, K.
Magee, J. S., and Briggs, W. S. Process for preparing alumina having a narrow pore size distribution, P (9) 226*j*.
Magee, J. S., Jr., Briggs, W. S., and Ciapetta, F. G. Process for producing high porosity gamma alumina, P (9) 236*h*.
Mager, E. L. Electroluminescent lamp with homogeneous phosphor-dielectric layer, P (3) 78*e*.
Magill, P. J., and Young, T. Detection of strain in evaporated films by wavefront reconstruction, (9) 233*j*.
Maglic, G. A. S. See Drazic, D. M.
Magneli, A. See Gado, P.; Werner, P. E.
Magner, J. E. See Long, R. S.
Magnezitipari Muvek. Manufacture of refractory materials consisting of two ceramic materials, P (11) 282*a*.
Magnier, P. Complementary course for ceramic engineers, (9) 244*a*.
Maguire, E. A., and Green, J. J. Magnetic properties of yttrium-gadolinium-iron-aluminum-indium garnets, (5) 126*h*.
Maguire, S. G. See Beneke, J. A.
Magyar Optikai Muvek. Sample holders for thermoanalytic examination, P (5) 132*a*.
Maiden, C. E. Method of sealing glass to metal, P (7) 157*j*.
Maifeld, L. C. Kiln car lubrication system, P (9) 235*c*.
Maines, R. Q. Coaxial termination utilizing boron nitride member to enhance radiation, P (4) 100*i*.
Maissel, L. I. Process of coating, using a liquid metal substrate holder, P (3) 79*b*.
Maissel, L. I., Flur, B. L., and Bertelsen, B. I. Process for cathodically sputtering magnetic thin films, P (5) 128*g*.
Majauskas, J. See Abraitis, R. I.; Pranckevicius, G. A.
Majima, H., and Peters, E. Oxidation rates of sulfide minerals by aqueous oxidation at elevated temperatures, (3) 82*e*.
Majumdar, N. C., and Stevens, T. J. Determination of the apparent specific heat of clay, (7) 159*a*.
Makariunas, K. See Makariuniene, E.
Makariuniene, E., and Makariunas, K. Peculiarities of the gamma-ray spectra of the neutron-activated Te and CdTe crystals and the activation cross sections of Te isotopes, (5) 137*e*.
Makarov, E. S. See Kuznetsov, L. M.
Makarov, V. I. See Zolotov, V. A.
Makarova, T. A. See Sipovskii, D. P.
Maki, T., and Tashiro, M. Studies on thermal shock resistant ceramics of the Li_2O-Al_2O_3-SiO_2 system (III) hot pressing of a mixture of petalite powder and pulverized lithia-containing glass, (2) 37*i*; (IV) slip casting of petalite ceramics, (5) 125*g*.
Makino, K. See Takeya, G.
Makishima, S. See Nagasawa, M.
Maklad, M. S. See Bishay, A. M.
Malagari, F. A., Jr. See Ames, S. L.
Malhotra, V. M. Discussion of "New approach to the determination of the tensile strength of cement paste by centrifugal force," (2) 34*c*.
Malicheff, A. See Brichard, E.
Malinovsky, M. See Matiasovsky, K.
Malissa, H. Possible use of an electron beam microanalyzer to investigate oxide materials, (3) 81*a*.
Malissa, H., Obst, K. H., Jellinek, G., and Horn, H. C. Example of a computer program to calculate the mutual solubilities of MgO and CaO in dolomites, (3) 80*j*.
Mallett, G. R. See Mueller, W. M.
Mallick, S. K., and Sastry, M. K. L. N. Redistribution of moments in prestressed concrete continuous beams, (11) 275*i*.
Mallinson, J. C. See Eagle, D. F.
Mallory, J. D. Decorating chuck, P (9) 219*e*.
Mallory, P. R., & Co., Inc. Electrical capacitor with a boron nitride dielectric, P (1) 10*b*. Glass-bonded mica encapsulated tantalum capacitor, P (4) 101*h*. Plated packaging for electronic components, P (8) 185*h*. Vapor deposition apparatus including tumbler, P (5) 129*e*.
Malloy, F. Process for producing lead titanate powder, P (10) 265*a*.
Malmberg, T. Effect of grading on the properties of olivine sands (for steel molds), (4) 96*j*.
Malofeeva, G. I. See Rudnev, N. A.
Malone, E. W. Thermal measuring apparatus, P (2) 52*b*.
Maloney, T. C. Glow cathode indicator tube having memory, P (8) 184*d*.
Maloney, T. C., and Boyer, J. T. Gaseous cold cathode indicator tube having a segmented electrode and an insulating shield plate, P (1) 10*f*.
Mal'tseva, L. F., and Marmer, E. N. Determination of the electrical properties of graphite at high temperatures, (3) 84*h*.
Malyuchkov, O. T., Okhrimenko, Yu. Ya., and Chertkov, A. A. Proton magnetic resonance method of studying the hydrides of TiV alloys, (4) 109*a*.
Mambourg, J. E. Apparatus for preventing devitrification of molten glass at the joints of a glass furnace, P (4) 93*g*. See Oelke, W. W.
Mambourg, J. E., and McCown, W. E. Apparatus for continuous production of glass sheets, P (8) 176*d*.
Mana, J. Temporary heating of glass tank furnaces by coal gas, (3) 66*j*.
Manabe, K. See Kubo, T.
Manasevit, H. M. See Miller, A.
Manchenko, Z. F. Investigation of the variations of certain properties of glasses in the system SiO_2-Al_2O_3-CaO-B_2O_3-R_2O, B (9) 246*c*.
Mandal, S. S. See Chattopadhyay, D.
Mandal, S. S., and Roy, S. B. Effect of thickness on the power factor of mica, (2) 46*j*.
Mandel, G. See Kucza, J. A.
Mandel, G., Morehead, F. F., Kucza, J. A., and Hammer, W. N. Preparing group II-VI compound semiconductor devices, P (9) 231*i*.
Mandelkorn, J. Method of making a silicon semiconductor device, P (7) 157*g*.
Mandl, M. See Hayer, M.
Mandle, R. M., and Straehle, W. T. Process for preparing a polishing compound and product, P (4) 89*f*.
Mandorf, V., Jr. Preparation of aluminum nitride, P (5) 124*h*.
Mandorf, V., Jr., and Reidl, R. W. Refractory articles, P (3) 73*c*.

Manenc, J. See Vagnard, G.
Mankoff, L. L., and Nakata, R. High voltage capacitor assembly, P (9) 231*b*.
Manley, J. C. Glass-sealed electrical resistor, P (5) 127*e*.
Manley, R. E. Method and apparatus for pneumatically classifying solids, P (2) 50*a*.
Mann, H. See Meyer-Simon, E.
Mann, J. E., Trigger, H., and Hirsch, N. Semiconductor alloying technique, P (3) 79*d*.
Mann, K. H. See Westmore, J. B.
Mannami, M. See Fitzgerald, A. G.
Mannerberg, A. R., Meday, J. J., and Kall, H. L. Particle size analysis of fine abrasive powders by sedimentation techniques, (1) 1*f*.
Mannewitz, F., and Mannewitz, M. Hollow glass building block, P (7) 149*f*.
Mannewitz, M. See Mannewitz, F.
Manning, B. See Bonis, L. J.
Manning, D. C., and Capacho-Delgado, L. Dissociation and ionization effects in atomic absorption spectrochemical analysis, (4) 104*f*.
Manning, F. S. See Spitzer, R. H.
Manring, W. H., and Billings, D. D. Direct observation and photography inside operating glass furnaces, (3) 66*c*.
Mansfield Sanitary, Inc. Toilet with deformable water seal trap, P (5) 126*c*.
Mansikka, K., and Bystrand, F. Theoretical determination of cohesive energy, lattice parameter, and compressibility of LiF crystals, (8) 209*b*.
Mantell, C. L. See Hoffmann, J. E.
Manuilova, N. S. See Koval'skaya, K. V.
Marboe, E. C. See Weyl, W. A.
Marceau, W. E. Glass tempering apparatus with resilient sheet support means, P (11) 278*c*. Method of making a molten foamed glass, P (9) 221*i*.
Marchenko, V. I., and Samsonov, G. V. Thermal properties of the sulfides of certain lanthanides, (2) 58*h*.
Marchlik, T. J. Graphite continuous casting mold, P (5) 124*i*.
Marcotte, V. C., and Larsen, W. L. Phase studies of high-niobium-content Nb-Zr-O alloys, (11) 299*e*.
Marcovecchio, J. See Landon, D. O.
Marcus, J. H. See Ormsby, W. C.
Mare, E. See Dettmar, H. K.
Maretheu, A. Control of the resistance of refractories to attack by carbon monoxide, (7) 151*f*.
Marezio, M. See Remeika, J. P.
Marezio, M., Remeika, J. P., and Dernier, P. D. High pressure synthesis of $YGaO_3$, $GdGaO_3$, and $YbGaO_3$, (8) 199*d*.
Marglass, Ltd. Composite structure containing glass fiber, P (10) 254*i*.
Margotin, P. Solid state lasers, (9) 230*b*.
Margrave, J. L. High temperature thermodynamics and kinetics, B (5) 140*a*. See Kana'an, A. S.; Kuriakose, A. K.
Margulis, E. V., Remizov, Yu. S., and Kopylov, N. I. Solid-phase interactions between oxides and sulfates of zinc, cadmium, and copper, (1) 28*h*.
Maria Sistiaga, J. Refractory metals and cermets, B (2) 62*e*.
Mariano, A. N. See Koffman, D. M.
Marinder, B. O., Dorm, E., and Seleborg, M. Studies on rutile-type phases in mixed transition metal dioxides (II), (5) 138*b*.
Marinkovic, S. Solid solution formation in the U_3O_8-UO_2 transformation, (4) 109*j*.
Marinov, M. R., and Dimitriev, Ya. B. Upper boundaries of glass formation and structure of glasses in the binary systems M_2O-SiO_2, MO-SiO_2, M_2O-GeO_2, and MO-GeO_2, B (7) 171*c*.
Mark, P. See Micheletti, F. B.
Markaryan, M. S. See Goryainov, K. E.
Markevich, E. P. See Dolgina, G. Z.
Markin, T. L. See Gardener, E. R.
Markiv, V. Ya. See Kuz'ma, Yu. B.
Markonrenkov, Yu. A. See Nagornyi, A. I.
Markotan, R. J. See Zawodni, J. T.
Markov, A. I., and Mikhailov, N. V. Contraction and formation of contraction porosity during hydration hardening of cements, (1) 1*j*.
Markova, T. P. Electrical conductivity of thallium sulfoselenide-arsenic glasses in relation to their structurochemical characteristics, B (4) 113*f*.
Markovskii, L. Ya., Sapozhnikov, Yu. P., and Boev, E. I. Selenites of bismuth, (9) 242*c*.
Markuszewicz, M., Groyecki, J., Lassota, J., and Zawada, A. Stability of inclusions and the formation of secondary grains in silicon-iron alloys, (1) 29*d*.
Marley Tile Co., Ltd. Flooring materials, P (9) 228*g*. Pipes, P (9) 223*d*.
Marlow, P. G., Russell, J. P., and Hardy, J. R. Raman scattering in uranium dioxide, (8) 206*c*.
Marlowe, M. O., and Wilder, D. R. Sensitive resonant frequency technique for the study of sintering kinetics, (4) 104*d*. Sintering kinetics study using reduced variables, (11) 300*j*.
Marmer, E. N. See Mal'tseva, L. F.
Maroy, K. Crystal structure of tetramethylthiuram disulfide, (8) 193*j*.
Marschik, D. See Flowers, L. C.
Marshall, A. See Walker, L.
Marshall, C. W. See Dyer, H. N.
Marshall, D. J. See Barrer, R. M.
Marshall, K. See Bennett, H.
Marshall, R. H., and Hoekstra, H. R. Preparation and properties of $TiUO_3$, (8) 205*j*.
Marshall, Thomas, & Co. (Loxley), Ltd. See Thomas Marshall & Co. (Loxley), Ltd.
Marshall, W. J., Linton, H. R., and Cupery, M. E. Nacreous glass flake pigment compositions, P (10) 256*a*.
Martel, R. A. Method of lubricating vitreous fibers, P (4) 94*j*.
Marti, F. B. See Burriel Marti, F.
Martin, D. H. Magnetism in Solids, B (8) 212*c*.
Martin, D. M., Fehr, G. K., and McGee, T. D. Grain boundaries in sodium chloride, B (2) 61*f*.
Martin, F. S. See Lloyd, J. E.
Martin, F. W. Method for etching glass, P (1) 5*i*. See Kellett, C. M.
Martin, H. T., and Gould, R. J. Elastic protective corner and tensioning strips for transportable brick packages, P (10) 256*f*.
Martin, J., and Hiner, H. C. Method of gettering impurities in electrical devices such as incandescent lamps, P (8) 178*a*.
Martin, J. E., and Merrill, J. A. Ceramic transducer assembly, P (7) 156*j*.
Martin, J. H. Ceramic with metal film via binder of copper oxide containing glass, P (3) 77*d*.
Martin, R. E. See Burzynski, A. J.
Martin, S. W., Shea, F. L., Jr., and Juel, L. H. Substantially isotropic graphitized bodies used in nuclear reactors, P (9) 227*g*.
Martin, W. H. See Kelly, B. T.
Martin, W. S., and Klink, J. P. Apparatus for forming and collecting filamentary materials, P (8) 176*e*.
Martin-Marietta Corp. Method of sphering refractory oxides, P (1) 8*f*.
Martinek, T. W. See Klass, D. L.
Martinelli, J. A. See Greco, E. J.
Martinet, J. R. Refractory, P (1) 8*d*. See Neely, J. E.
Martinet, J. R., and Van Dreser, M. L. Refractory, P (7) 154*c*.
Martinez, E. Chrysotile asbestos—relation of the surface and thermal properties to the crystal structure, (3) 82*e*. Concentration of asbestos ore, P (9) 235*j*.
Martyn, L. G., and Tooley, A. B. Crystal structure, P (11) 285*c*.
Marusak, F. J. Method of making high strength glass articles, P (4) 95*b*.
Marx, A. Ball mills, P (3) 80*e*.
Marynowski, C. W., Karlovitz, B., and Hirt, T. J. Electrical augmentation of natural gas flames, (10) 268*f*.
Marzocchi, A. Elastomeric-glass fiber products and process and elements for use in same, P (2) 38*d*. Method of making elastomeric-glass fiber products for use in endless belts, P (4) 95*a*. Neoprene-glass fiber structures and preparation, P (7) 150*g*.
Marzocchi, A., and Rammel, G. E. Method for applying a forming lubricant to glass fibers, P (2) 39*f*.
Maschinenfabrik Backau R. Wolf A. G. Apparatus for conveying and stacking bricks, P (3) 70*e*.
Mashkovich, M. D. Dielectric loss of glasses at the wavelength of 8 mm, B (4) 113*e*.
Maslenkov, S. B., and Zharkova, D. N. Phase composition of the diffusion layer of boronized nickel, (1) 25*c*.
Maslennikova, G. N. See Budnikov, P. P.
Mason, J. E. See Baker, A. A.
Mason, J. H., and Stein, H. A. Polybenzimidazole resin bonded abrasive articles, P (10) 247*g*.
Mason, T. R. See Smith, W. A.
Mason, W. P. Single crystal quartz filter elements, transducers, and delay lines, P (7) 158*d*. Stress sensing semiconductive devices, P (1) 12*a*.
Massachusetts Institute of Technology. Method of making a heterojunction semiconductor device, P (11) 286*j*.
Massaux, H., Van Asbroeck, P., Mestdagh, G., and Pech, P. Fabrication of dense UO_2 by hot-pressing and coextrusion, (10) 257*i*.
Masson, R., Niesel, K., and Herrmann, R. Life of the inorganic world, (7) 151*g*.
Masuda, M., Kita, H., Okada, Y., and Fujita, R. Process for polishing glass, P (7) 150*c*.
Masuoka, T. See Tomura, M.
Masyukov, N. T. See Tol'skii, A. A.
Matay, I. M. Method for determining the factor of anisotropy of resistivity of a graphite body, P (11) 289*i*.
Matheus, R. E. See Slate, F. O.
Mathewson, W. F., Ratterman, E., and Gillis, K. H. Analysis of the coated diamond/bond system, (2) 33*f*.
Mathias, B. B. Inspecting containers for slant bottom condition, P (3) 68*c*.
Mathias, R. G. See Baker, T. C.
Mathieu, A. See Paquot, C.
Matiasovsky, K., Malinovsky, M., and Ordzovensky, S. Electrical conductivity of the melts in the system Na_3AlF_6-Al_2O_3-NaCl, (3) 85*j*.
Matijewic, E., and Milic, I. Precipitation effects of aluminum, lanthanum, iron(III), and thorium phosphates, (3) 87*e*.
Matoba, T. See Kudaka, K.
Matousek, J., and Lisy, A. Adhesion of the gold layer on glass, (10) 250*i*.
Matson, L. K. See Reid, F. J.
Matsuda, O., and Kudo, N. Method of retarding the setting time of cement, P (8) 174*e*.
Matsuda, T. See Yoshida, T.
Matsuev, N. S. See Royak, S. M.
Matsui, D. Variable disk capacitor, P (11) 288*b*.
Matsuki, Y. See Matsuo, S.
Matsukura, Y., Oda, J., and Koreeda, S. Anomalous diffusion of boron into silicon grain boundary, (11) 292*h*.
Matsumae, T. See Shibata, S.
Matsumoto, H. See Hayashi, H.
Matsumoto, H., Yamauchi, S., and Nishiyama, G. Alumina base cermet (VII) effect of addition of CaO-MgO-SiO_2 mixture on sintering of Al_2O_3-Fe-Fe_3O_4, (11) 280*d*.
Matsumoto, Y. See Yasufuku, M.
Matsumura, T. Electrical properties of alumina at high temperatures, (3) 85*b*.
Matsuno, S. See Ando, J.
Matsuo, S., and Homma, K. Sintering in the binary system $MoSi_2$-ZrO_2, (2) 43*b*. Spectral emissivity of molybdenum disilicide, (5) 138*k*.
Matsuo, S., Komeya, K., and Matsuki, Y. Sintering of the system AlN-Al in nitrogen, (7) 152*i*.
Matsuo, S., and Kubo, T. Sintering in the binary system $MoSi_2$-WSi_2, (2) 43*a*.
Matsuo, S., Kubo, T., and Homma, K. Molybdenum disilicide heating elements, (2) 42*a*.
Matsuo, Y. See Miyadai, T.
Matsuoka, H. Refractory for tapping spout of electric arc furnace, (11) 281*a*.
Matsushima, I. Thermal etching patterns on germanium surface under low vacuum, (3) 77*b*.
Matsushita, T., and Suzuki, K. Effect of crucible supporting methods on the growth of single crystals by the Stockbarger method, (2) 49*i*.
Matsushita Electric Industrial Co., Ltd. Barium titanate ceramic composition, P (8) 184*b*. Method of manufacturing film resistors, P (10) 264*d*. Slug-type titanium wet electrolytic capacitors, P (9) 232*d*.
Matsushita Electronics Corp. Silicon rectifier device, P (10) 265*d*.
Matsuura, M. See Yasuoka, H.
Matsuzaki, R. See Saeki, Y.
Matthews, J. R. Method for the production of glass fibers, P (4) 95*d*.
Matthews, J. W. Growth of face-centered-cubic metals on sodium chloride substrates, (1) 19*j*.
Matthews, R. K. Flue liners, P (1) 7*e*.
Matthias, B. T. See Kunzler, J. E.
Mattmueller, R. Manufacture of silica glass, P (10) 255*h*.
Mattocks, G. R. See British Glass Industry Research Association.
Mattocks, G. R., et al. Design aspects of glass tank furnace regenerators, (5) 118*a*.
Mattox, D. M. Apparatus for coating a cathodically biased substrate from plasma of ionized coating material, P (10) 263*b*. Chromizing molybdenum for glass sealing, (1) 3*f*.
Mattox, W. J. See Gladrow, E. M.
Mattson, R. A. See Ehlert, R. C.
Mattson, R. A., and Ehlert, R. C. Application of a soft X-ray spectrometer to study the oxygen and fluorine emission lines from oxides and fluorides, B (5) 139*h*.
Mattuck, J. B. See Davis, R. S.
Matulionis, A. See Viscakas, J.
Matveev, G. M. See Babushkin, V. I.; Mchedlov-Petrosyan, O. P.
Matveev, M. A., and Agarkov, A. S. Effect of thermal history on the kinetics of the solution of alkali silicate glasses, (3) 66*e*.
Matveev, M. A., Mazo, Zh. E., Volkodatov, A. F., and Volchek, L. K. Influence of aluminum oxide on properties of glasses in certain alkali-free systems, B (7) 171*d*.
Matveev, M. A., Mel'nik, M. T., and Glasova, M. P. Synthesis and study of the electrical and other properties of glasses in the system V_2O_5-CdO-P_2O_5, (8) 176*i*.
Matveev, M. A., and Semenov, I. N. Influence of the chemical stability of glass on its microhardness, (3) 66*j*.
Matveev, M. A., Smirnova, K. A., and Ustinova, V. F. Ceramic filters from bodies based on waste from asbestos-enrichment factories, (4) 96*f*.
Matyushenko, N. N. See Verkhorobin, L. F.
Maul Brothers, Inc. Glass delivery system, P (11) 278*i*. Glass forming apparatus with self-accommodating and universal plungers, P (9) 220*d*.
Maurer, K. Semiautomatic production of porcelain combustion boats, (10) 261*h*.
Maurer, R. D. Structure of crystallizing glass, B (7) 171*a*.
Maurice, J. See Cherbuy, J.
Maxwell Chemicals Pty., Ltd. Preparation and method for preventing excessive buildup of solid products of combustion in the outlet flues of boiler, open hearth, and other furnaces, P (2) 53*c*.
May, J. E. Kinetics of epitaxial silicon deposition by a low pressure iodide process, (11) 297*f*.
May, M. Meissen porcelain—1710–1810 in the Bavarian National Museum, Munich, (7) 145*j*.
Mayaud, E. E. See Bishop, A. E.
Maycock, J. N. See Jacobs, P. W. M.
Mayer, A. Low temperature synthesis of compound semiconductors, P (7) 156*h*.
Mayer, E. H., Rahn, H. N., and Oliver, E. M. Low carbon steel alloy for vitreous enameling, P (2) 35*i*.
Mayer, R. P. Process for producing magnesium hydroxide and a noncontaminated effluent solution, P (3) 83*b*.
Mayer, R. P., and Stowe, R. A. Slaking process, P (5) 117*a*.
Mayer, W. N. Reduction of oxides by ion bombardment, P (11) 287*a*.
Maynard, C. W. See Kulcinski, G. L.
Maynard, E., and Ptasienski, M. P. Substantially dry joint compound comprising calcium sulfate, polyvinyl acetate, and starch, P (4) 91*g*.
Maynard, R. N., and Iannicelli, J. Clay bleaching under nonoxidizing atmospheres, P (8) 190*c*.
Maynard, W. J. See Rauner, L. A.
Mayo, R. F. See Wen, C. P.
Mays, H. D. Stacking apparatus, P (5) 126*a*.

Mays, R. K., and Bertorelli, O. L. Reactive selectively sorptive silica materials and process of producing them, P (9) 236*d*. Reactive silica materials and process, P (9) 236*e*.
Mazdiyasni, K. S., Lynch, C. T., and Krochmal, J. J. Method for making high purity fine particle oxides, P (4) 106*e*.
Mazdiyasni, K. S., Lynch, C. T., and Smith, J. S., II. Cubic phase stabilization of translucent yttria-zirconia at very low temperatures, (11) 293*i*.
Mazelsky, R., and Ohlmann, R. C. Chromium fluorescence in the $LaAlO_3$-$LaGaO_3$ system, (11) 292*j*.
Mazieres, C. Differential thermal microanalysis apparatus, P (2) 52*a*.
Mazo, Zh. E. See Matveev, M. A.
Mazur, R. G. Lapping and polishing apparatus, P (1) 14*d*.
Mazurenko, V. D. See Zhunina, L. A.
Mazurin, O. V. Combined study of certain electrical and mechanical properties of glass as a means for revealing its structural peculiarities, B (4) 113*a*. Glass in a direct electric field, B (4) 113*a*. (editor) Structure of Glass (Vol. IV) Electrical Properties and Structure of Glass, B (4) 113*g*. See Brailovskii, V. B.; Petrovskii, G. T.; Zorin, A. P.
Mazurin, O. V., and Brailovskii, V. B. Problem of microheterogeneity of glasses in the light of studies of their electrical properties, B (9) 245*i*.
Mazza, J. S. Nuclear radiation shielding window, P (2) 39*h*.
Mchedlov-Petrosyan, O. P. See Babushkin, V. I.
Mchedlov-Petrosyan, O. P., and Kholodnyi, A. G. Correlations in the structural formation of portland cement stone during hardening, (10) 248*a*.
Mchedlov-Petrosyan, O. P., Matveev, G. M., and Safronov, V. S. Investigation of the energetics of devitrification processes as a method for studying the structure of glasses, B (9) 246*c*.
Mead, C. A. Surface barrier indium arsenide transistor, P (2) 49*b*.
Mead, C. A., Snow, E. H., and Deal, B. E. Barrier lowering and field penetration at metal-dielectric interfaces, (8) 183*c*.
Meade, R. H. Factors influencing the early stages of the compaction of clays and sands—review, (8) 197*i*.
Meaders, J. C., and Carithers, M. D. Boron nitride evaporation source for aluminum, (1) 12*d*.
Meador, S. E. See Stern, K. H.
Meadowcroft, T. R., and Richardson, F. D. Heats of formation of some crystalline and glassy phosphates, (5) 136*i*.
Meadows, F. W. See Dowley, A.
Mecky, K. Pressure lid for filter presses, P (10) 266*g*.
Meday, J. J. See Mannerberg, A. R.
Medvedeva, Z. S. See Luzhnaya, N. P.
Medvedeva, Z. S., and Grinberg, Ya. Kh. Thermodynamics of boron phosphide, (7) 169*d*.
Meeder, G. H. W. Process for producing sodium carbonate from sodium bicarbonate obtained by the ammonia-soda process, P (11) 291*j*.
Meerlender, G. Measurement and numerical investigation of viscosity-temperature relation of glasses (I) range of validity and properties of the Vogel-Tammann-Fulcher equation, (10) 252*c*.
Meerman, W. C. P. M. See Bolk, A.
Meerson, G. A., Kiparisov, S. S., Gurevich, M. A., and Den, Fen-syan. Conditions of preparation and some properties of pseudobinary B_4C-B_4Si hard alloys, (10) 256*j*. Preparation and study of the properties of hard alloys from the pseudobinary section SiC-BC grown from the gaseous phase, (8) 205*j*.
Megalopoulos, A. See Skulikidis, A.
Meggers, B. J., Evans, C., and Estrada, E. Early Formative Period of Coastal Ecuador—The Valdivia and Machalilla Phases, B (4) 113*b*.
Megles, J. E. Method of making high strength nepheline crystalline glass, P (8) 178*b*.
Meguro, K., Koishi, M., and Takada, S. Adsorption of dyes to etch pits on crystal surface of potassium chloride, (9) 233*f*.
Mehal, E. W. See Finch, W. F.; Hendrickson, G. R.
Mehan, R. L., and Berry, J. M. Nonlinear behavior in three-point bending of high-strength high-modulus fibers—correction, (1) 23*j*.
Mehan, R. L., Sutton, W. H., and Herzog, J. A. Review of the methods of measuring the strength of whiskers and their role in reinforcing metal matrices, (1) 2*j*.
Mehta, J. M., Riewald, P. G., and Van Vlack, L. H. System MnSe-MnS, (4) 111*i*.
Mehta, P. K. Expansion characteristics of calcium sulfoaluminate hydrates, (5) 136*b*.
Meieran, E. S. See Blech, I. A.
Meilus, J. See Grigas, J.
Meiresonne, A. C. Sealing glass parts to form cathode ray tube envelopes, P (9) 222*d*.
Meissner, F. H. Deflection measurement accuracy, (5) 130*j*.
Mekler, L. I. See Buketov, E. A.
Melabs. Ferrite circulator having three mutually coupled coils coupled to the ferrite material, P (2) 47*f*.
Melanson, W. A. Adjustable capacitor with moving dielectric, P (2) 47*f*.
Mellar, C. J. See Wiener, R.
Mellors, G. W., and Senderoff, S. Density and surface tension of molten fluorides (II) system NaF-LiF-ZrF_4, (7) 162*b*. Hexavalent fluorides of tantalum and niobium, (11) 296*i*.
Melmed, A. J. Field-emission microscopy, B (8) 211*j*.
Melngailis, I., and Strauss, A. J. Spontaneous and coherent photoluminescence in $Cd_xHg_{1-x}Te$, (5) 138*j*.
Mel'nik, E. P. See Zaliznyak, D. V.
Mel'nik, M. T. See Matveev, M. A.
Mel'nikova, I. G. See Berkman, A. S.
Meloy, T. P. Impact grinding, P (11) 291*h*.
Melpar, Inc. Thin film circuit vacuum processing facility, P (8) 186*b*. Thin film diode manufacture, P (11) 288*b*. Vacuum furnace, P (1) 15*a*.
Memming, R. See Grimmeiss, H. G.
Mendelson, S. Stacking-fault tetrahedra in {001} epitaxial silicon films, (11) 301*g*. Structural defects in epitaxial films—role of surfaces in nucleation, (10) 263*h*.
Mendel'son, V. M. See Polak, A. F.
Mendez-Penalosa, R., and Otero, J. L. Rapid method of measurement of elastic properties of graphite by flexural sonic waves, (2) 42*c*.
Menelly, R. A. Fluorescent electric discharge lamp having the phosphor particles admixed with indium powder particles, P (11) 285*e*. High temperature fluorescent lamp with reflector having mercury amalgamative material on its electrode stems, P (2) 47*j*.
Meneret, J. Isostatic pressing, (5) 129*j*. See Bedier, R.
Menezes, I. de, and Stubican, V. S. Grain-boundary reactions in magnesia-chrome refractories—application of the electron probe (II), (1) 7*e*.
Menna, A. A. See Weinstein, M.
Men'shikov, A. Z. See Nemnonov, S. A.
Mercade, V. Method for beneficiating clay by flotation, P (11) 291*i*. Mineral bleaching process, P (4) 106*g*.
Merck & Co., Inc. Semiconductor process and products, P (5) 129*e*.
Merilainen, P. See Nasanen, R.
Mering, J. See Bouraoui, A.; Oberlin, M.
Meriwether, H. R., Jr. See Zellers, J. T., Jr.
Merkel, H. See Wenzel, F.
Merkl, W. A. Grooved active medium for laser, P (4) 101*h*.
Merlini, A. E. See Young, F. W., Jr.
Merriam, J. C. Glass-coated steel adds edge coat, (5) 117*d*.
Merrill, J. A. See Martin, J. E.
Merrin, S. See Hoogendoorn, H. M.
Merritt, F. R. See Sturge, M. D.
Mersol, S. A. See Lynch, C. T.; Vahldiek, F. W.
Mersol, S. A., Vahldiek, F. W., and Lynch, C. T. Veining substructure in single crystal dimolybdenum carbide, (11) 303*c*.
Merten, U. See Bray, D. T.
Meschel, S. V., and Kleppa, O. J. Thermochemical study of some reciprocal fused-salt systems involving the monovalent liquid nitrates, (8) 210*b*.
Messineo, P. J., and Thomsen, S. M. Luminescent screens utilizing nonluminescent separator layers, P (3) 78*c*.
Messmer, E. Thin layer ground-coat enamels, (7) 147*f*.
Mestdagh, G. See Massaux, H.
Metal Diffusions, Ltd. Refractory material, P (8) 182*d*.
Metallgesellschaft Akt.-Ges. Apparatus for measuring temperatures within rotary kilns, P (10) 268*b*. Method of producing cement or cement-like materials from oil shale, P (4) 91*e*. Method of producing lithium fluoride, P (9) 236*a*. Refractory brick linings of catalytic reactors, P (4) 99*f*.
Metallwerk Friedrichshafen G.m.b.H. Kilns, P (8) 189*b*.
Metaltronics, Inc. Sintered carbides, P (9) 227*f*.
Metco, Inc. Flame spraying employing laser heating, P (7) 147*j*. Plasma flame powder spray gun, P (5) 117*e*. Self-fusing flame spray material, P (5) 117*h*.
Methfessel, S. J. See Holtzberg, F.
Metrailer, W. J. Molded carbon bodies, P (2) 44*f*.
Metrailer, W. J., and Hoover, W. Molded carbon bodies, P (2) 44*e*.
Metro Minerals. Method for improving perlite filter aids with phosphoric agent, P (11) 282*b*.
Mets, E. J., and Gentry, F. E. Method of producing semiconductor devices, P (11) 287*a*.
Metz, E. D. See Kang, K. D.
Metz, P. Process for producing bodies of refractory material, P (10) 260*a*.
Metzgar, F. L. See Kean, J. S., Sr.
Metzger, J. W., Engel, M. J., and Diaconis, N. S. Oxidation and sublimation of graphite in simulated reentry environments, (5) 123*f*.
Mewbourne, C. A. See Oelke, W. W.
Meyer, G., and Michel, A. Radioactive ceramic source of strontium fluorapatite and method of manufacture, P (10) 270*b*.
Meyer, Geo. J., Mfg. Co. See Geo. J. Meyer Mfg. Co.
Meyer, H. Fundamentals and applications of the plasma torch, (5) 132*e*. Nitrogen compounds stable at high temperature in ceramic materials, (5) 133*a*. See Onn, D. G.
Meyer, J. See Denker, S. P.
Meyer, R. A. See Powell, H. W.
Meyer-Simon, E., and Frey, A. Production of mixtures of zirconium oxide and silicic acid, P (4) 99*d*. Recovery of zirconium compounds from alkali metal zirconium silicates, P (1) 16*b*.
Meyer-Simon, E., Mann, H., and Ruecker, A. Manganese and aluminum containing pink pigments for glazes and underglazes, P (10) 261*e*.
Meyst, G. J., and Snethorst, A. C. J. M. Method of manufacturing germanium-containing products substantially free of fluorine from liquids containing fluorine and germanium, P (11) 286*e*.
Mezure, J. Use of natural gas in the French clay products industry, (5) 122*a*.
Michael, H. J. Method of providing high temperature protective coatings, P (4) 92*c*.
Michaels, A. S. Refractory coatings for metal surfaces, P (10) 250*f*.
Michaels, A. S., Baker, W. E., Bixler, H. J., and Vieth, W. R. Permeability and washing characteristics of flocculated kaolinite filter cakes—hydraulic permeability and particle orientation, (5) 133*b*; washing characteristics, (5) 133*d*.
Michaels, M. Patching composition containing polyvinyl and epoxy resins with hydraulic cement, P (10) 249*b*.
Michel, A. See Meyer, G.
Micheletti, F. B., and Mark, P. Effects of chemisorbed oxygen on the electrical properties of chemically sprayed CdS thin films, (10) 262*h*.
Michelitsch, M. Epitaxial growth of GaAs through cracks in SiO_2 masks, (11) 295*f*.
Michelitsch, M., Kappallo, W., and Hellbardt, G. Reactions of gallium arsenide with water vapor and hydrogen chloride gas, (7) 167*g*.
Michl, L., and Spielmann, W. Apparatus for crucible-free zone melting of crystalline semiconductor rods, P (3) 77*a*.
Mickelsen, R. A. See Kingery, W. D.
Microcyclomat Co. Reject spouts, P (9) 236*f*.
Microwave Associates, Inc. Semiconductor point contact devices, P (4) 102*f*.
Middel, V. J. See Harwood, M. G.
Middleton, R. M. See Gazzara, C. P.
Midgley, H. G. Mineralogy of set high-alumina cement, (9) 214*i*. See Fletcher, K. E.
Mid-West Abrasive Co. Solid abrasive article, P (1) 1*f*.
Mierzejewska, S., and Niemyski, T. Vapor growth of boron crystals, (2) 59*a*.
Migitaka, M. Method for the production of semiconductor devices, P (11) 287*b*. See Takagi, T.
Migitaka, M., Kodera, H., Ueda, H., and Kimura, H. Method of selective diffusion from impurity source, P (3) 79*f*.
Migitaka, M., and Tokuyama, T. Method of manufacturing silicon diodes or silicon transistors by alloying indium with p-type silicon to produce a pn junction, P (2) 48*c*. Zener diode element of low junction capacitance, P (3) 79*i*.
Mikalkevicius, M. See Krisciunas, V.
Mikalkevicius, M., and Grigas, B. Trap studies in Sb_2Se_3 single crystals by thermally stimulated current technique, (11) 302*j*.
Mikalkevicius, M., and Paukste, J. Difference in energy gap in Sb_2S_3 determined from the spectral characteristics of photoconductance and absorption, (5) 135*d*.
Mikami, H. M. Plastic chrome ore, P (4) 98*h*. Refractory composition and body, P (9) 227*d*.
Mikhail, R. Sh. Activation and sintering behavior of calcium oxide—effect of copper X-irradiation on the surface area of the oxide produced by thermal decomposition, B (9) 244*f*.
Mikhail, R. Sh., Brunauer, S., and Copeland, L. E. Kinetics of the thermal decomposition of calcium hydroxide, (1) 21*g*.
Mikhailov, N. V. See Doronin, L. K.; Khutortsov, G. M.; Markov, A. I.
Mikoda, M., Kuroda, T., and Hayakawa, S. Effects of crystallization on electrical properties of an R_2O-RO-PbO-SiO_2 glass, (7) 148*f*.
Miksic, M. G. See Haering, R. R.
Mikulyak, R. M. See Gershenzon, M.
Milberg, M. E. See Otto, K.
Milch, A., Lalak, J. J., and Ahlert, R. H. Refractory metal-to-ceramic seal, P (11) 283*e*.
Milde, C. Is the zigzag kiln still modern? (3) 81*j*.
Miles, C. V. H. See Gumm, B. J.
Milette, K. A. See O'Brien, R. F.
Milic, I. See Matijewic, E.
Millea, M. F. See Kyser, D. F.
Miller, A., and Manasevit, H. M. Single crystal silicon epitaxy on foreign substrates, (1) 28*e*.
Miller, A. E., and Dane, A. H. Preparation of a new type nonstoichiometric rare-earth oxide, (8) 205*g*.
Miller, C. A. Ceramic crucible for barium titanate melts, (9) 223*h*.
Miller, C. H. See Burklo, D. C.
Miller, D. G. Automatic clearing mechanism for crushers, P (10) 269*i*.
Miller, E., and Komarek, K. L. Retrograde solubility in semiconducting intermetallic compounds—liquidus curves in the Pb-S, Pb-Se, and Pb-Te systems, (7) 167*c*.
Miller, E. D., Jr. Calcium hexaluminate articles, P (7) 153*b*. Manufacture of ceramic objects, P (3) 72*h*, P (5) 126*b*. Pouring tube for pressure pouring apparatus, P (10) 260*d*. Refractory catalyst carrier and method of preparation, P (5) 125*a*. See Leatham, E.
Miller, E. D., Jr., and Beals, R. S. Refractory lining, P (2) 45*c*.
Miller, E. J. See Katz, S.
Miller, G. R. See Johnson, H. B.
Miller, H. C. Grinding wheel with predeterminately oriented fixed replaceable abrasive segments, P (8) 173*g*.
Miller, H. J. Roll type rock crusher, P (9) 236*g*.
Miller, J. A. See Montague, J. H.
Miller, J. F. See Reid, F. J.
Miller, J. F., Moody, J. W., and Himes, R. C. Preparation of PbTe crystals, (10) 263*b*.
Miller, J. L., Jr., McCormick, G. R., and Ampian, S. G. Phase equilibria in the system GeO_2-Al_2O_3, (7) 166*i*.

Miller, K. J., and Grieco, M. J. Study of HCl-H_2 and $GeCl_4$-H_2 etching of germanium substrate for epitaxial deposition, (7) 168*b*.
Miller, M. Semiconductor switching device and method of manufacture, P (9) 232*c*. See Longo, T. A.
Miller, M. P. See Laity, R. W.
Miller, N. C., and Shirn, G. A. Cosputtered Au-SiO_2 cermet films, (10) 261*j*.
Miller, P. R. See Pearson, A. J.
Miller, R. C., and Savage, A. Temperature dependence of the optical properties of ferroelectric $LiNbO_3$ and $LiTaO_3$, (9) 242*c*.
Miller, R. R. See Walker, B. E.
Miller, W. S. Continuous recycle heating process for the production of soda ash and alkali metal phosphates, P (11) 291*e*.
Millett, A. See Catling, H. W.
Millett, A., and Catling, H. W. Composition and provenance—a challenge, (11) 274*a*.
Millhiser, R. G. Apparatus for handling grit, P (10) 266*e*.
Milligan, W. C. Burner elements, P (7) 153*b*. Catalytically active radiant tile, P (5) 132*c*.
Millman, N. See Shurling, B. E.
Mills, D. S. See Vogel, R. R.
Mills, L. E., and Boolen, R. F. Graphite welding, P (2) 44*e*.
Mills, R. See Spedding, P. L.
Millsaps, F. W., and Browning, J. S. Flotation of mica, P (1) 15*g*.
Milner, G. W. C., Wood, A. J., Weldrick, G., and Phillips, G. Determination of plutonium in refractive materials by electrometric methods after dissolution by fusion with ammonium hydrogen sulfate, (8) 187*h*.
Minaev, E. M. See Aksenov, G. I.
Minami, S., Nakada, K., and Mizushima, W. Slug-type titanium wet electrolytic capacitors, P (9) 232*d*.
Minami, T. See Tanaka, M.
Minamigawa, S. See Shimomura, Y.
Minden, H. T. Preparation and properties of GaAs-InAs mixed crystals, (9) 241*g*.
Miner, R. J., and Timm, W. A. Tumbler beader, P (2) 40*c*.
Mineralimpex Magyar Olaj- es Banyatermek Kulkereskedelmi Vallalat. Basic refractory brick and process of making it, P (10) 259*d*.
Mineral Industries Corp. of America. Flotation method and apparatus, P (5) 133*i*.
Minerals & Chemicals Philipp Corp. Attapulgite clay filter aid product containing combination of fluxes and method for making same, P (1) 15*e*. Clay coated with haloalkyl phosphorus ester and polyester resins containing the same, P (3) 83*b*. Clay filter aid and production thereof, P (2) 54*a*. Clay slurries and method for making same, P (5) 133*g*. Colloidal clay coated with acrylic acid-polyallyl sucrose copolymer, P (7) 160*h*. Cracking catalyst and preparation thereof, P (10) 269*j*. Foundry sand composition, P (1) 7*e*. Grinding method, P (8) 190*c*. Inhibited clay slurry composition, P (2) 54*b*. Kaolin clay coated with neutralized monomeric *N,N*-diallylmelamine and polyester resins containing the same, P (4) 106*c*. Method for beneficiating clay by flotation, P (11) 291*i*. Method for making a faujasite-type crystalline zeolite, P (11) 291*j*. Method of reducing clay viscosity, P (9) 236*b*. Mineral bleaching process, P (4) 106*g*. Paper coating clay and treating method, P (4) 106*f*. Stabilized clay dispersions, P (11) 292*b*.
Minhas, G. S., and Rao, H. V. B. Development of superduty silica brick with indigenous raw materials, (2) 41*b*.
Minjer, C. H. de. Method of coating *p*-type germanium with antimony, lead, or alloys thereof by electrodeposition and product thereof, P (9) 231*d*.
Min'ko, N. I. See Koz'min, M. I.
Minkovich, B. D., Antonov, G. I., et al. Production of dense magnesite-chromite refractories, (7) 152*d*.
Minneman, L. C., Powell, D. E., and Spear, B. W. Reinforced cathode-ray tube and faceplate therefor, P (8) 179*a*.
Minnesota Mining & Mfg. Co. Constrained ceramics, P (7) 155*b*. Mica pigments, P (7) 161*d*. Molybdenum fiber reinforced alumina, P (9) 226*c*. Radiation source, P (10) 260*c*. Sealed beam headlight with glass-beaded light reflecting shield, P (3) 69*d*. Solid state switching device, P (7) 158*d*.
Minomura, S. See Kosuge, K.; Nagasawa, H.
Minowa, S., and Kosaka, M. Corrosion of silicon nitride refractory by molten iron, (11) 280*f*.
Minowa, S., and Yamada, M. Refractories for the protection of thermocouples from molten aluminum and zinc, (9) 224*j*.
Minton, R. M., and Glicksman, R. Semiconductor devices and method of manufacture, P (2) 49*f*.
Minx, E. See Klages, H.
Mirgalovskaya, M. S. See Skudnova, E. V.
Mironov, V. E., Kul'ba, F. Ya., and Ivanov, Yu. E. Complex compounds of zinc with chlorides of the alkali metals, (11) 292*g*.
Mischanski, M. S. Grinding mill, P (11) 291*g*.
Mishima, S., and Hori, A. Studies on pitchstone from Yokota area, Fukushima prefecture—effects of firing conditions on the bulk density of expanded pitchstone, (5) 133*f*.
Miskarli, A. K., and Zemlyanskaya, V. Ya. Effect of alkali tannides on aqueous clay suspensions, (7) 162*d*.
Miskin, S. F. A. See Cooper, C. F.; Deacon, R. F.
Misson, G. W. Apparatus for producing sheet glass, P (4) 93*g*. Method and apparatus for conveying and heating glass on a fluid support bed, P (4) 94*e*. Method of manufacturing flat glass on a bilevel forming surface, P (8) 178*f*.
Missouri-Rogers Corp. Crusher, P (4) 106*j*.
Misu, A. Emissions of ruby, (8) 196*f*.
Mita, M. Ferromagnetic resonance in spherically shaped single crystal $BaFe_{12}O_{19}$, (5) 136*d*.
Mitarai, Y. See Kubo, T.
Mitchell, A. Structure of sodium oxide + boric oxide and sodium fluoride + boric oxide liquids and the electronic spectrum of Co^{2+}, (7) 168*c*.
Mitchell, C. V. Carbon foam, P (5) 124*c*.
Mitchell, D. G. Role of the solvent in flame photometry, (8) 188*a*.
Mitchell, P. H. Bushing assembly for forming glass fibers, P (10) 254*g*.
Mitrokhin, A. K. See Kocho, V. S.
Mitrokhina, N. S. See Tsigler, V. D.
Mitsubishi Denki Kabushiki Kaisha. Method of making solid composition resistors of monolithic structure, P (10) 264*c*. Stripline circulator having means causing electrostatic capacitance between adjacent pairs of terminals to be substantially equal to each other, P (10) 265*h*.
Mitsubishi Shipbuilding & Engineering Co., Ltd. Process for preventing dissolution of alkaline material from cement articles, P (10) 249*c*. Process of recovering valuable components from red mud, P (7) 161*a*.
Mitsui, N. See Shimizu, Y.
Mitsuishi, A. See Ikegami, S.
Mittereder, F. X. See Borst, D.
Mitzmager, A., and Mizrahi, J. Sink-float method of classifying wet flocculated solid particles, P (7) 161*d*.
Miura, Y. Effect of orientation on surface charge density at silicon-silicon dioxide interface, (11) 294*b*.
Miwa, H., and Shiojiri, T. Electron tube with inert oxide coating on the envelope, P (10) 263*h*.
Miyadai, T., Matsuo, Y., and Miyahara, S. Growth of a $CuFe_2O_4$ single crystal and its Laue photographs, (8) 198*j*.
Miyadai, T., Miyahara, S., and Matsuo, Y. Ferrimagnetic resonance in copper ferrite (I) cubic-phase single crystal, (11) 295*c*.
Miyagi, T. See Tamada, K.
Miyahara, S. See Kondo, H.; Miyadai, T.
Miyake, T. See Onuki, M.
Miyamoto, O., Tanaka, Y., and Furukawa, M. Determination of zinc in ferrite by use of anion exchange resin, (5) 135*c*.
Miyamoto, S., Tanaka, N., and Iida, S. Ferromagnetic resonance in single crystals of cobalt-substituted nickel ferrite, (11) 295*g*.
Miyashige, S. See Shimizu, Y.
Miyata, N., Kobayashi, T., and Itoh, K. Ferro magnetic crystalline anisotropy and transition temperature of Ti-substituted magnetite, (7) 163*e*.
Miyatake, K., Furumi, K., and Shikano, H. Basicity of slag contributing to erosion of high-temperature burned basic brick, (11) 280*f*.
Miyatake, K., Semba, K., and Tsuru, H. Trial manufacture of nozzle brick from imported raw materials and results of use test, (9) 225*f*.
Miyatani, K., Kohn, K., Iida, S., and Kamimura, H. Nuclear magnetic resonance of ^{59}Co and ^{27}Al in paramagnetic Co_3O_4 and $CoAl_2O_4$, (9) 241*e*.
Mize, J. P. See Long, R. K.
Mizobuchi, Y. See Maeda, T.
Mizoguchi, T. See Tanaka, M.
Mizrahi, J. See Mitzmager, A.
Mizukusa, S. See Hayashi, H.
Mizuno, M. See Hayashi, H.
Mizusawa Kagaku Kogyo Kabushiki Kaisha. Method and apparatus for preparing silica-alumina type spherical hydrogels, P (10) 259*f*. Method of drying a hydrogel, P (3) 83*e*.
Mizushima, W. See Minami, S.
Mkheidze, O. A. See Kotelnikov, G. R.
Mlavsky, A. I. See Griffiths, L. B.
Mo och Domsjo A. B. Mold or core composition for metal casting purposes, P (2) 44*f*.
Moacanin, J. See Rembaum, A.
Moak, D. P. See Koester, R. D.
Moazed, K. L. See Hirth, J. P.
Moberly, L. E. See Boes, D. J.
Mobil Oil Corp. Method for producing crystalline aluminosilicates, P (7) 153*e*. Method for producing crystalline aluminosilicate zeolitic particles of uniform size, P (8) 190*c*. Process for making crystalline zeolites, P (9) 236*f*. Steam treatment of the matrix in a crystalline aluminosilicate catalyst composite, P (10) 270*a*. Synthesis of mordenite, P (10) 260*j*. Synthetic zeolite, P (8) 190*i*.
Moburg, L. Stoneware lantern with glass inserts, (5) 116*a*.
Mochel, E. L., Nordberg, M. E., and Elmer, T. H. Strengthening of glass surfaces by sulfur trioxide treatment, (1) 4*g*.
Mochel, J. M. Method of producing thin flakes of metal oxide, P (11) 291*j*.
Mochel, V. D. Modified Zn_2SiO_4 compositions, P (10) 265*b*.
Mock, J. A. Lower cost porcelain enamels, (2) 35*d*.
Mockrin, I. See Phillips, B.
Modreski, E. L. See Cole, F.
Moehle, K. Process of producing spark plug insulators by dry pressing, P (11) 284*b*.
Moeken, H. H. P., and Van Neste, W. A. H. Absorptiometric determination of microgram amounts of uranium with rhodamine B, (8) 187*b*.
Moench, W. See Gerlach, W.
Mogon, M. Industrial application of electromagnetic techniques to ceramics, (5) 131*e*.
Mohan, A. See Rao, S. V. K.
Mohanty, G. P., Fiegel, L. J., and Healy, J. H. System niobium pentoxide-tantalum pentoxide, (8) 209*c*.
Mohler, N. Handmade brick, the automated way, (9) 222*h*. See Pixley, G.
Mohn, H., Horstmann, G., and Muller, E. Infrared heater, P (8) 189*b*.
Moiola, R. J. See Wermund, E. G.
Moiseev, G. K., and Stepanov, G. K. Dependence of the surface tension of molten salts on the binding energy between ions, B (1) 30*c*.
Moiseev, V. V. See Zhabrev, V. A.
Mokhosoev, M. V., and Fedorov, P. I. Interactions of sodium ditungstate with the tungstates of iron, magnesium, and copper, (4) 108*j*.
Molbach, A. See Cromer, W. R.
Molchanova, M. I. See Khil'ko, M. M.
Moles, L. Method for producing a boron diffused silicon transistor, P (2) 48*c*.
Moll, S. H. See Schippert, M. A.
Mollet, A. J. T. See Vrenken, L. E.
Mollon, P. See Dupuydenus, C.
Momiyama, K. See Kachi, S.
Mondin, L. Ya. See Shchegrov, L. N.
Mones, A. H. Electrical resistance composition and method of forming a resistor, P (11) 285*f*. See Kaiser, H. D.
Monfore, G. E. Properties of expansive cement made with portland cement, gypsum, and calcium aluminate cement, (11) 275*h*. See Lentz, A. E.
Monforte, F. R. See O'Bryan, H. M., Jr.
Monk, C. B. See Jones, J. R.
Monn, D. E. See Jordan, D. E.
Monolith Portland Cement Co. Hardening a cement mixture, P (5) 116*h*. Means for holding kiln brick within a rotary kiln, P (10) 259*e*.
Monozon, S. M. See Kotelnikov, G. R.
Monsanto Chemicals, Ltd. Asbestos-cement products, P (2) 34*b*. Process for the production of fluid compositions containing silica, P (2) 54*c*. Refractories, P (3) 73*b*.
Monsanto Co. Alumina supported copper oxide-rare earth oxide catalyst compositions, P (2) 43*c*. Apparatus and method for discharging receptacles, P (8) 186*j*. Apparatus and process for preparing semiconductor rods, P (9) 230*f*. Graphite heating elements and method of conditioning the heating surfaces thereof, P (10) 259*j*. Laminated glass having electrically operated instrument indicator means embedded in the interlayer, P (8) 177*i*. Method and apparatus for removing blockage of material in transporting conduits, P (8) 186*i*. Orthorhombic boron arsenides and their preparation, P (11) 282*b*. Production of epitaxial films of semiconductor compound material, P (7) 157*i*. Refractory compositions and processes, P (8) 182*c*. Two-phase thermoelectric body comprising a silicon-germanium matrix—silicon-carbon matrix—lead-tellurium matrix, P (2) 49*e*.
Montague, J. H., and Miller, J. A. Refractory compositions and method for preparing same, P (8) 182*c*.
Montecatini Societa Generale per l'Industria Mineraria e Chimica. Apparatus for the production of abrasive carbides, P (4) 105*h*. Process for recovering iron, titanium, and aluminum from the red slurries obtained in processing bauxite by the Bayer process, P (4) 107*a*. Production of iron sponge and the recovery of titanium and aluminum from red slurries of bauxite, P (4) 107*d*.
Montecatini Societa Generale per l'Industria Mineraria e Chimica and Pirelli S.p.A. Dielectric composition having anticorona properties, P (9) 230*c*.
Montrimas, E. See Viscakas, J.
Moodie, A. F., Warble, C. E., and Williams, L. S. Magnesia precursor and sintering study, (1) 22*a*.
Moody, J. W. See Miller, J. F.
Mooi, J. See Engebretson, G. R.
Mook, G. C. See Adams, E. A.
Mooney, D. P. Article handling and transfer device, P (5) 120*b*.
Mooney, R. W. See Schmid, W. F.
Moore, A. B. See Whitehurst, E. A.
Moore, A. E. Tricalcium aluminate and related phases in portland cement, (2) 34*d*. See Fletcher, K. E.
Moore, D. G. See Clark, H. E.
Moore, D. J. See Prout, E. G.
Moore, D. L. Metallic ceramic composite contacts for semiconductor devices, P (4) 101*a*.
Moore, E. L. See Gagliano, L. J.
Moore, F. See Astbury, N. F.
Moore, F. D. Method of vibratory milling, P (4) 103*h*.
Moore, F. L. Method for separating members of actinide and lanthanide groups, P (1) 15*j*.
Moore, H. See Sneed, R. B.
Moore, J. M., Jr. See Hounslow, A. W.
Moore, P. B., and Louisnathan, J. Fresnoite—unusual titanium coordination, (9) 239*h*.
Moore, R. W., and Bowling, J. E., Jr. Abrasive blasting wheel assembly, P (2) 33*f*.
Moorthy, V. K. See Rao, S. V. K.
Moorthy, V. K., and Bhat, R. Sintering of beryllia (I) influence of origin and thermal treatments on the sintering behavior of beryllia powders, (10) 258*f*.
Moorthy, V. K., Kamath, G. T., and Bahl, J. K. Sintering of beryllia (II) hot-pressing of beryllia powders of different origin and thermal treatment, (10) 258*f*.

Moorthy, V. K., Kulkarni, A. K., and Vyas, B. R. Development and evaluation of pyrolytic graphite coated resistors, (3) 75*e*.
Moorthy V. K., Prasad, G. E., and Kulkarni, A. K. Sintering of thoria powders (IV) development of crystallinity in thoria powders during heating and its influence on their sintering behavior, (4) 109*f*.
Moosbrunner Glasfabriks-Akt.-Ges. Device for the fabrication of U-shaped profiles of glass in a continuous rolling procedure, P (2) 38*c*.
Morain, A. J. L. Mosaic tile assembly, P (10) 261*f*.
Moran, J. P. See Coulter, W. H.
Morana, S. J. Protective coating for beryllium metal, P (4) 92*e*.
Moratis, C. J. See Carlson, W. G.; Tien, T. Y.
Moreau, C. See Blanchard, R.; Blum, P.
Moreau, N., and Seifert, J. A. Method of shaping a continuous glass tube, P (11) 279*f*.
Moreau, R. Ceramic tesserae—the easy way, (4) 89*f*.
Morehead, F. F. See Crowder, B. L.; Mandel, G.
Moren, R. E. Mold or core composition for metal casting purposes, P (2) 44*f*.
Moretti, S. See Iacobelli, R.
Morgan, C. S. See Yust, C. S.
Morgan, C. S., and Hall, L. L. Effect of isostatic pressure on sintering, (8) 195*b*.
Morgan, C. S., McHargue, C. J., and Yust, C. S. Material transport in sintering, B (7) 170*g*.
Morgan, W. A. See Hollebone, B. R.
Morgan, W. A. C. H. Cementitious material, P (1) 2*c*.
Morgan Refractories, Ltd. Refractory product, P (11) 283*a*.
Morganite, Inc. Furnace casing and lining secured by an anchorage assembly, P (11) 281*e*. Furnace with metal link and refractory anchor member, P (5) 124*h*.
Morgunov, N. N. See Budnikov, P. P.
Mori, H. Radiation energy transducing device, P (1) 11*d*.
Mori, S. Phase transformation in barium orthoferrate, $BaFeO_{3-x}$, (1) 26*h*.
Mori, S., and Sasaki, H. Electron-microscopic observation of (Ba,Sr)TiO_3 crystals, (11) 294*j*.
Mori, T. See Tagai, H.
Moriguchi, H. See Akatsuka, Y.
Morikawa, H. See Inagaki, K.
Morikawa, K. Seebeck effect in cadmium sulfide, (9) 242*b*.
Morin, L. H. Traveler having a wear resistant element, P (3) 75*b*.
Morita, A., Abe, Y., and Yamazaki, H. Theory of lattice magnetic susceptibility of semiconductors, (5) 139*c*.
Morita, S. Results of tests on ladle nozzle brick containing zircon, (9) 224*c*.
Morita, Y. See Edagawa, H.
Moriya, S. M. Apparatus for the treatment of liquid materials, P (4) 103*j*.
Moriya, T. See Sakaino, T.
Moriya, Y., Warrington, D. H., and Douglas, R. W. Study of metastable liquid-liquid immiscibility in some binary and ternary alkali silicate glasses, (9) 218*f*.
Morlevat, J. P. See Blum, P. L.
Morley, H. See Dominey, D. A.
Morley, J. G., and Proctor, B. A. Method of producing solid metal materials containing pretensioned silica, P (5) 117*d*.
Morozov, I. S. See Tverskov, V. A.
Morozov, I. S., and Li, Chi-fa. Reciprocal system $SnCl_2 + PbS \rightleftarrows SnS + PbCl_2$, (1) 27*e*.
Morozova, M. P., and Ponomareva, V. N. Continuous transitions in the system Fe_3O_4-Fe_2O_3, (7) 162*i*.
Morozova, V. S. See Guzman, I. Ya.
Morrell, J. C. Dental impression materials, P (3) 74*j*.
Morris, C. Blank forming apparatus for glass ribbon forming machine, P (11) 278*a*.
Morris, D. See Bussey, H. E.
Morris, H. H. See Beamesderfer, J. W.
Morris, M. C. See Swanson, H. E.
Morrison, A. R. See Wong, R.
Morrison, G. H. See Skogerboe, R. K.
Morrison, J. A. See Barron, T. H. K.; Black, H. R.
Morrison, J. A., and Tuzi, Y. Determination of thermal accommodation of translational energy of vapors at a glass surface, (1) 17*f*.
Morrison, J. R. See Bate, G.
Morrissey, J. W. Method of decorating semicrystalline bodies, P (8) 177*j*.
Morsanyi, A. V. Silica brick in the superstructure of glass melting furnaces (I) corrosion of silica brick by the vapor of sodium salts, (5) 123*c*; (II) corrosion of silica brick in the superstructure and crowns of glass melting furnaces, (5) 123*d*.
Morse, L. E. Method for preparation of urania sols, P (2) 44*b*.
Mortland, M. M. Urea complexes with montmorillonite—an infrared absorption study, (4) 112*f*.
Mortlock, A. J. See Rungis, J.
Morton, J. R. Electron spin resonance spectra of radiation-damaged inorganic crystals, B (9) 244*e*.
Mortsell, T. E. Drum type magnetic separator, P (9) 235*f*.
Mosaic Fabrications, Inc. Method of making fiber bundles, P (3) 68*f*.
Mosaic Tile Co. Machine and method for automatically fabricating multiple unit assemblies of individual pieces, P (9) 228*g*. Stacking apparatus, P (5) 126*a*.
Moscker, E. See Borbas, J. J.
Moser, J. B. See Kruger, O. L.
Moser, J. B., and Kruger, O. L. Preparation of plutonium phosphide by direct combination of the elements, (11) 299*e*.
Moser, M. Basic and technical questions on the production of grinding wheels from ceramic bonded corundum grains, (3) 63*f*.
Mosenson, R. M. See Laegreid, N.
Moss, A. A. See Moss, E.
Moss, E., and Moss, A. A. Natural glasses from Macusani, Peru, (10) 269*g*.
Moteki, K. See Nishino, T.
Motohashi, H. See Kubo, K.
Motorola, Inc. Alloy-diffused method for producing semiconductor devices, P (7) 156*e*. Apparatus for fabricating alloyed junction semiconductor assemblies, P (3) 77*a*. Crystal structure, P (11) 285*c*. High voltage semiconductor device, P (7) 157*f*. Method of etching semiconductors, P (3) 78*g*. Method of forming thin oxide films, P (5) 117*j*. Method for making a semiconductor device, P (7) 157*f*. Passivated alloy diode, P (3) 79*k*. Process of forming an inorganic glass coating on semiconductor devices, P (4) 102*i*. Semiconductor device with passivated junction, P (4) 102*e*.
Motson, J. F. Electroluminescent lamp having a transparent nickel, chromium, iron alloy metal electrode, P (10) 263*f*.
Mourier, G. Electron discharge device with external mode suppression means which separate and allow for dissipation of unwanted modes, P (3) 78*f*.
Moutarde, R. C. See Alais, M. E.
Mozelewski, E. J. See Schindler, P. H., Jr.
Mozheiko, V. I. See Dubrovo, S. K.
Mrackova-Metlika, A. Method for the preparation of ceramic semiconductive glazings, P (8) 185*a*.
Mrozinski, S. J. See Valchar, C. E.
Muan, A. See Biggers, J. V.; Dayal, R. R.; Jones, T. S.
Mudar, J. See Lambe, J. J.
Muehleisen, R. W. See Heck, R. F.
Mueller, H. A. See Fischer, P.
Mueller, H. G., and Bade, E. Method of and arrangement for increasing the alkali content in alkali-laden dusts of flue gases, P (8) 174*c*.
Mueller, L. Filter press, P (10) 266*g*.
Mueller, R. F. See Olsen, E.
Mueller, W. Paraelectric ceramic for high voltage capacitors, P (10) 265*d*.
Mueller, W. M., Mallett, G. R., and Fay, M. J. (editors). Advances in X-Ray Analysis (Vols. 8 and 9) Proceedings of the 13th and 14th Annual Conferences on Applications of X-Ray Analysis, August 1964 and 1965, Denver, Colorado, B (5) 139*e*.
Muenchberg, W. See Obst, K. H.
Muir, I. D., Tilley, C. E., and Scoon, J. H. Basalts from the northern part of the Mid-Atlantic Ridge (II) the Atlantis collections near 30° N, (8) 191*c*.
Muir, W. B. Comparison of Harman and cooling couple methods for Z determination, (3) 75*g*.
Muirhead, J. F. See Burtch, F. W.
Mukai, O. See Tanaka, M.
Mukai, T. Mixing apparatus, P (10) 266*d*.
Mukaihata, T. See Roberts, P. S.
Mukerjee, T. See Adams, N.
Mukherjee, S. G., and Samaddar, B. N. Spinel formation from coprecipitated hydroxides of aluminum and magnesium, (4) 110*c*.
Mukherjee, S. K. See Basu, A. N.
Mukherjee, S. P., and Rogers, P. S. Nucleation and crystal growth in silicate glasses containing fluorides, (11) 277*f*.
Mular, A. L. See Hockings, W. A.
Mulaskey, B. F. Method of depositing metals on siliceous supports, P (9) 235*j*.
Mulay, L. N. See Keys, L. K.
Muldagalieva, R. A. See Buketov, E. A.
Mulford, R. N. R. See Holley, C. E., Jr.
Mullard, Ltd. Manufacture of crystals, P (8) 190*g*. Methods of heat-treating semiconductor materials, P (7) 157*a*.
Muller, A. N. See Mackay, T. L.
Muller, C. S. See Forney, H. B.
Muller, E. See Mohn, H.
Muller, O., White, W. B., and Roy, R. Crystal chemistry of some technetium-containing oxides, (8) 192*j*.
Mulligan, R. J., and Wendt, J. J. Liquidless foundry molding process, P (5) 124*b*.
Mumford, E. H. Timing system for I.S.-type glassware forming machine, P (5) 121*k*. See Colchagoff, R. D.; De Shetler, L. C.; Lippmann, R. J.
Mumford, E. H., and Rieck, A. W. Takeout apparatus for glass forming machines, P (5) 121*k*.
Munakata, C. Measurement of the homogeneity of a semiconductor with an electron beam, (11) 298*d*. See Watanabe, H.
Munakata, M. See Namikawa, H.
Munir, Z. A., and Searcy, A. W. Torsion effusion study of the vapor pressure and heat of sublimation of gallium, (7) 169*e*.
Munn, G. E. Process for impregnating glass fiber mat with methyl methacrylate polymer, P (2) 40*b*.
Murai, J. See Ikeda, Y.
Murakami, K. See Sugiura, T.; Tanaka, H.
Murakami, T., Terasaki, Y., and Toyoda, H. Analysis of CdS thin film transistor static characteristics, (4) 100*b*.
Murao, T. See Tsujikawa, I.
Murao, T., and Ebina, A. Faraday effect for localized electrons in insulators, (11) 295*c*.
Murat, M. See Cubaud, J. C.
Murata, Y., Julien, H. P., and Whitney, E. D. Densification and wear resistance of ceramic systems (I) titanium diboride, (8) 179*j*.
Murata, Y., and Sucharski, L. R. Ceramic compositions and process of making same, P (5) 124*e*, P (10) 259*f*.
Murata Mfg. Co., Ltd. Semiconductive capacitor and the method of manufacturing the same, P (4) 102*c*.
Muratov, F. Sh., and Semenenko, K. N. Cubic modification of beryllium oxide, (8) 194*e*.
Murphy, B. T. Methods for forming monolithic semiconductor devices [including epitaxial growth], P (9) 231*e*.
Murphy, E. G. See Brown, M.
Murphy, J. A. See Donovan, D. R.
Murphy, N. A. See Jewell, R. C.
Murphy, N. A., and Baybutt, W. E. Manufacture of lead glasses, P (9) 220*d*.
Murray, H. H. Mining and beneficiation of kaolin, B (1) 30*b*.
Murray, P., and Williams, J. Ceramic and cermet fuels, (3) 70*h*.
Murray Curvex Printing, Ltd. Machines for printing or decorating articles, P (1) 9*c*.
Murthy, B. S., and Naik, S. P. Certain fabrication aspects of *p*-type germanium tunnel diodes, (11) 284*e*.
Murthy, H. P. S., and Chatterjee, B. Comparative studies on a high temperature coke oven coal tar pitch as a binder for carbon refractories and compacts, (2) 41*g*.
Murthy, H. P. S., Kundra, M. C., Sen, P. C., Rao, M. R. K., and Rao, H. V. B. Pilot plant studies on the production of forsterite refractories (I) study of process variables, (2) 42*e*.
Murthy, M. K., and Emery, K. Properties and structure of glasses in the system M_2O-Ga_2O_3-GeO_2(M = Li, Na, K), (9) 218*h*.
Murthy, S. R. N. Dhamrasite—the tin garnet, (11) 290*f*.
Murthy, Y. G. K. Bauxite deposits of Kalahandi district, Orissa, (8) 189*f*.
Murton, C. B. Stopper for a ladle or similar receptacle, P (2) 45*h*.
Murzova, L. I. See Koval'skaya, K. V.
Musha, T., Lindvall, F., and Hagglund, J. Microwave emission from InSb for low electric fields, (5) 137*h*.
Mustacchi, C. Thermal shock rupture of some uranium ceramics, (7) 152*e*.
Muszkiewicz, H. See Kopineck, H. J.
Muta, A., Gejo, T., and Shiozawa, M. Method for producing boron carbide, P (9) 227*f*, P (11) 282*e*.
Muth, S., Jr. Thermocouple reference junction compensators, (9) 234*e*.
Mutter, W. E. Semiconductor devices and their fabrication, P (8) 186*e*.
Mycalex Corp. of America. Method of making synthetic mica and ceramoplastic materials, P (11) 286*b*.
Myers, D. O. Method for treating a material in a solution, P (3) 69*c*.
Myers, M. B. See Felty, E. J.
Myers, R. A., and Powell, C. G. Anomalous polarity-dependent electrooptic effect in cubic ZnS and ZnTe, (10) 270*c*.
Myers, R. L. Sheet steels for porcelain enameling, (9) 216*g*.
Mytych, C. J., and Tietjen, T. A. Method for simultaneous production of a plurality of microcircuit wafers, P (10) 264*j*.
Myuller, R. L. Thermal ionization in glasses and mobility of current carriers in them, B (4) 113*a*. See Borisova, Z. U.
Myuller, R. L., and Pronkin, A. A. Nature of the conductivity of sodium aluminosilicate glasses, B (4) 113*c*.

Nabarro, F. R. N. See Levitt, C. M.
Nabaul, A. R. Easy to clean off overspray quickly, (10) 266*b*.
Nacken, M., Scholz, S., and Leramacher, B. Kinetics of the sintering of tantalum carbide, (5) 136*i*.
Nadachowski, F. Assessment of the phase composition of fireclay refractories based on ternary phase diagrams, (2) 41*a*.
Nadirov, E. G. See Buketov, E. A.
Naeser, G., and Scholz, W. Activation and inhibition of chemical reactions and sintering processes by mechanical working, (5) 133*j*.
Naeser, G., Scholz, W., and Fiedler, A. Mechanical activation and passivation of solids—change of the energy content of NaCl, zinc oxide, and copper powder as a function of milling time, (4) 103*g*.
Nag, B. B. See Kumar, S.
Nagamiya, T. See Uchida, E.
Nagamiya, T., Saito, S., Shimomura, Y., and Uchida, E. Magnetic structure of CoO, (10) 271*c*.
Nagarajan, M. K., Nanis, L., and Bockris, J. O'M. Diffusion of sodium-22 in molten sodium nitrate at constant volume, (8) 194*h*.
Nagasaki, H. See Kosuge, K.
Nagasawa, H., Takeshita, S. K., Tomono, Y., Minomura, S., and Okai, B. ^{51}V nuclear magnetic resonance in V_2O_5, (8) 211*d*.
Nagasawa, M., Shionoya, S., and Makishima, S. Electron effective mass of SnO_2, (11) 294*g*.
Nagase, K., Taki, H., and Nitta, T. Barium titanate ceramic composition, P (8) 184*b*.
Nagornyi, A. I., Bragin, B. A., Markonrenkov, Yu. A., Kulemzin, K. N., and Beloborodova, S. S. Effect of additives on the crystallization of melts of metallurgical slags and rocks, (3) 71*j*.

Nagy, K. Cement raw material improvement by the hydrocyclone, (7) 146*d*.
Nahas, R. S. Flare apparatus for combustible gases, P (9) 234*j*.
Nahum, J. See Mackey, J. H.
Naidich, Yu. V. See Eremenko, V. N.
Naidich, Yu. V., and Eremenko, V. N. Metal-oxygen technology for brazing ceramic materials, (10) 262*j*.
Naik, S. P. See Murthy, B. S.
Naito, K. See Imai, H.
Naka, S., and Kato, E. Effects of iron group oxides on stabilization of ZrO, (3) 85*f*.
Nakada, K. See Minami, S.
Nakagawa, T., and Nomura, S. Phase transition in $Sr(FeTa)_{1/2}O_3$, (9) 241*b*.
Nakahara, N. Method and apparatus for making spherical granules, P (1) 12*j*.
Nakahara, S., and Kawabata, S. Stripline circulator having means causing electrostatic capacitance between adjacent pairs of terminals to be substantially equal to each other, P (10) 265*h*.
Nakai, Y. Electron paramagnetic resonance study of γ-ray irradiated phosphate glasses, (5) 118*i*.
Nakamichi, T. Magnetostrictive behavior of antiferromagnetic CoO single crystal in magnetic field, (9) 240*f*.
Nakamura, Sen-ich. See Arai, Z.
Nakamura, Tetsuro. Semiconductor device, P (2) 49*e*. See Osafune, H.
Nakamura, Tomizo. See Toyama, I.
Nakanuma, S. Radiotracer studies on the incorporation of phosphorus in epitaxially grown silicon, (7) 167*d*.
Nakata, R. See Mankoff, L. L.
Nakayama, F. S., and Rasnick, B. A. Calcium electrode method for measuring dissociation and solubility of calcium sulfate dihydrate, (10) 266*i*.
Nakayama, M. See Oomori, K.
Nakayama, N. See Hayashi, H.
Nakayama, Y. See Yamada, T.
Nakazato, Y. See Yoshida, H.
Nakazawa, T. See Kuwata, T.
Nakazumi, Y. See Uchida, E.
Nalco Chemical Co. Amorphous alkali metal aluminate, P (1) 9*a*.
Naldrett, A. J. Talc-carbonate alteration of some serpentinized ultramafic rocks south of Timmins, Ontario, (7) 168*g*.
Namba, S. See Kim, P. H.
Nameishi, N. Reinforcement of roseki ladle brick by adding Cr_2O_3 to its matrix, (9) 224*b*.
Nameishi, N., Ohmachi, T., and Yamamoto, H. Fired dolomite brick tested in an LD converter, (11) 280*f*.
Namikawa, H., and Munakata, M. Effects of residual water on the transformation temperature and the structure of $BaO-P_2O_5$ glasses, (7) 148*g*.
Nance, R. L. See Leary, J. A.
Nandi, D. N. See Banerjee, J. C.
Nanigian, J., and Nichols, E. J. Fast response right angle thermocouple, P (2) 52*b*.
Nanis, L. See Nagarajan, M. K.; Tricklebank, S. B.
Nanmac Corp. Fast response right angle thermocouple, P (2) 52*b*.
Nanney, C. A., Libchaber, A., and Garno, J. P. Helicon-drift current interaction in a layered semiconductor structure, (11) 296*f*.
Naoe, M. See Yamanaka, S.
Naoumidis, A. See Stoecker, H. J.
Napolitano, A. See Macedo, P. B.
Napolitano, A., and Hawkins, E. G. Standard Reference Materials—viscosity of a standard lead-silica glass, (2) 37*i*.
Napper, D. H. Modern theories of colloid stability, (7) 165*i*.
Naradi, Narodni Podnik. Method of preparing a diamond tool, P (2) 33*i*.
Narasimhalu, K., Taraporewalla, K. J., and Hussain, S. Neyveli fly ash as a partial replacement for cement, (10) 248*b*.
Narayana, P. S. See Warrier, A. V. R.
Naray-Szabo, I. Problem of the structure of glass, B (7) 171*g*.
Naruse, A. Absorption characteristics of phosphate glasses containing ferrous iron as the near infrared absorber, (4) 92*h*.
Naruse, A., and Abe, Y. Striking effect of phosphate glass due to elementary phosphorus, (7) 148*i*.
Naruse, Y., Hayashida, S., and Shiraishi, A. Pulverization of refractory materials by vibrating ball mill, (11) 280*j*.
Nasanen, R., Merilainen, P., and Leppanen, K. Potentiometric determination of the solubility product of lead carbonate, (3) 81*b*.
Nasedkin, V. V., Panesh, V. I., and Rudnitskaya, E. S. Some structural peculiarities of natural water-containing glasses, B (7) 171*e*.
Nash, D. B. See Speed, R. C.
Nashel'skii, A. M. See Lipovskii, I. E.
Nashinkin, A. S. See Buketov, E. A.
Naslund, E., and Carlson, H. F. Tableware sorter, P (9) 228*h*.
Nassau, K., Levinstein, H. J., and Loiacono, G. M. Ferroelectric lithium niobate (I) growth, domain structure, dislocations, and etching, (8) 197*j*; (II) preparation of single domain crystals, (8) 198*b*.
Nasu, S. Visible and ultraviolet absorption spectra of UO_2, (8) 211*e*.
Nasu, S., Shikazono, N., and Takekoshi, H. Moessbauer effect in ^{57}Fe in single crystals of UO_2, (8) 202*g*.
Natansohn, S. See Levine, A. K.
Natarajan, A. S., and Shah, V. K. Red iron oxide pigments, (11) 291*a*.
Nath, P. Cr^{3+}-Cr^{6+} equilibrium in binary alkali borate glasses, (5) 118*h*. Cr^{3+}-Cr^{6+} equilibrium in binary alkali borate melts, (8) 175*f*. Effect of glass composition on redox equilibria and oxygen ion activity in glasses, (2) 36*j*. See Brown, D.; Douglas, R. W.; Kumar, S.
Nath, P., and Douglas, R. W. Cr^{3+}-Cr^{6+} equilibrium in binary alkali silicate glasses—correction, (5) 118*h*.
Nath, P., Paul, A., and Douglas, R. W. Physical and chemical estimation of trivalent and hexavalent chromium in glass—correction, (5) 119*a*.
National Beryllia Corp. Preparation of beryllia whiskers, P (3) 72*c*.
National Cash Register Co. Method for growing single thin film crystals, P (11) 286*h*. Semiconductor circuit complex having low isolation capacitance and method of manufacturing same, P (10) 265*b*.
National Clay Pipe Research Corp. Measurement of consistency, P (7) 159*h*.
National Engineering Co. Apparatus for conditioning granular material using rotating spokes and aerating cleats, P (5) 130*c*. Apparatus for feeding and transporting materials, P (4) 103*j*. Mixer including mulling wheel with resilient tire means to facilitate wheel rotation, P (9) 233*b*. Mulling machine, P (10) 266*e*. Mulling shoe mixer, P (2) 50*a*. System for mulling and mixing foundry sand, P (11) 283*d*.
National Gypsum Co. Dry powder for wallboard joint treatment, P (5) 116*f*. Gypsum product, P (9) 215*g*.
National Lead Co. Preparation of a titania hydrate, P (11) 291*d*. Process for producing lead oxides, P (9) 236*h*. Process for the production of cubic crystalline zirconia, P (10) 270*a*. Production of substantially anhydrous magnesium chloride, P (11) 292*b*.
National Research Corp. Hard superconductor clad with metal coating, P (7) 156*f*. Method of forming intermetallic superconductors, P (4) 101*f*. Niobium stannide superconductor product, P (8) 185*e*. Process for forming niobium-stannide superconductors, P (7) 157*f*. Process for manufacture of coated superconductive ribbons, P (9) 232*a*. Production of Nb_3Sn diffusion layers, P (1) 11*d*. Superconductor comprising a niobium substrate having a coating of niobium stannide and particles of a ferromagnetic material, P (11) 287*j*.
National Research Development Corp. Cathode ray tube with composite multiple glass fiber face, P (9) 219*a*. Laser diode with metal contacts plated over the sides of the semiconductor, P (8) 184*j*. Method of coating fluorescent layer of electron discharge tube, P (1) 11*c*. Method of metallizing bodies of high melting point crystal materials containing aluminum oxide, P (9) 231*a*. Semiconductor materials, P (9) 232*b*. Sensitive weighing apparatus, P (10) 268*b*.
Nauchno-Issledovatelskii Institut Monomerov dlya Sinteticheskogo Kauchuka. Apparatus for [spray] drying solutions, emulsions, and suspensions and for heat treatment of the dried material, P (3) 80*e*.
Nauchno-Issledovatelskii Institut Sinteticheskikh Spirtov i Organicheskikh Produktov. Method for production of catalyst for hydration of olefins to alcohols, P (7) 161*b*.
Naudin, F. See Zarzycki, J.
Naumann, A. W., and Dresher, W. H. Process for dispersing asbestos, P (4) 107*a*.
Nauta, C. J. Mixing devices, P (8) 186*j*.
Nautamix, N. V. Mixing devices, P (8) 186*j*.
Nayak, U. N., and Prasad, S. N. Investigations of new sources of raw materials for the glass industry (I) silica deposits of Assam, Madhya Pradesh, and Orissa, (5) 119*e*.
Naylor, G. New shape for canteen crockery, (7) 146*a*.
Naymik, D. A. See Lepselter, M. P.
Naz, M. A. See Safdar, M.
Nazarov, K. S. Testing magnesite-chromite products in the roofs of open-hearth furnaces, (5) 123*i*.
Neal, F. M. Diffusing lens for spotlights with axially oriented filaments, P (10) 255*a*.
Neal, F. M., and Ryan, J. D. Street light refractor, P (8) 179*b*.
Neave, J. H. See Bicknell, R. W.
Nechiporenko, E. P. See Efimenko, L. N.; Ivanov, V. E.
Needham, J. G., Davies, N. C., and Ranshaw, J. H. Sputtering apparatus including a folded flexible conveyor, P (2) 49*a*.
Neely, J. E. Behavior of high-fired basic brick in sprung arches, (7) 151*d*. Refractory with expansion means attached, P (9) 227*e*.
Neely, J. E., and Martinet, J. R. Refractory, P (1) 8*c*.
Negre, P. J. V. Process for ensuring noncorrosive contacts on heating rods, P (2) 53*b*.
Nehru, A. K., and Suh, N. P. Electrically conductive abrasive bodies, P (7) 145*g*.
Neipert, M. P., and Bon, C. K. Method of lithium recovery, P (5) 133*c*.
Neishi, H. See Yamada, T.
Nekhoroshev, A. V. Siliceous cement, (9) 215*j*.
Nekrasov, K. D. New developments in the study and use of refractory concretes, (4) 97*i*.
Nekrasov, K. D., Fedorov, A. E., and Yastrubinskii, V. I. Determining the moisture content of heat resistant concretes, (5) 131*b*.
Nelson, C. J. See Ban, T. E.
Nelson, E. W., and Wikswo, J. P. Process for the oxidation of $TiCl_4$, P (11) 291*f*.
Nelson, F. W. Corrosion resistant metal members, P (1) 3*c*.
Nelson, H. See Tietjen, J. J.
Nelson, J. A. See Bremser, A. H.
Nelson, J. E. Autogenous grinding mill, P (3) 83*a*.
Nelson, J. T. See McGlasson, J., Jr.
Nelson, P. A., and Chasanov, M. G. Nuclear reactor fuel material and a method of preparing the same, P (2) 44*g*. Uranium mononitride-sodium paste nuclear fuel, P (11) 283*e*.
Nelson, R. A. Radiation pyrometer and temperature standard therefor, P (8) 188*f*.
Nelson, W. F. Optical properties of the rare earths when doped into pure fused silica, B (2) 62*b*.
Nemchenko, V. F. See L'vov, S. N.
Nemec, F. See Kaltner, E.
Nemeth, T. See Lorinczy, A.
Nemets, I. I. See Kukolev, G. V.
Nemilov, S. V. Viscosity and structure of glass, B (7) 171*g*.
Nemirovskii, L. R. See Bernshtein, D. G.
Nemnonov, S. A., Sorokina, M. F., Men'shikov, A. Z., Kolobova, K. M., and Kinkel'shteyn, L. D. Nature of atomic interaction in the intermetallic compounds transition metal-aluminum and transition metal-silicon, (1) 23*e*.
Nemoto, A. See Kawada, N.
Nemoto, K. See Watanabe, H.
Neosid Pemetzrieder G.m.b.H. Method of producing sintered bodies, particularly sintered ferrite bodies, P (8) 185*b*.
Neshpor, V. S. See Konozenko, I. D.; Vil'k, Yu. N.
Neshpor, V. S., and Reznichenko, M. I. Study of the thermal expansion of some silicides, (5) 123*h*.
Nesor, H. See Class, W.
Nesterova, O. P. See Panteleimonov, L. A.
Nethercot, A. H. See Gutfeld, R. J. von.
Neuenschwander, E., Schuett, K., and Scheller, W. Finely dispersed carbides and process for their production, P (11) 281*c*.
Neugebauer, C. A. Structural disorder phenomena in thin metal films, B (11) 305*j*.
Neugebauer, C. A., and Rairden, J. R., III. Method [vacuum deposition] of forming superconductive niobium films, P (9) 231*d*.
Neugebauer, W. See Biegler, H.; Leineweber, G.
Neuimin, A. D. See Bessonov, A. F.; Tkachenko, E. V.
Neuroth, N. See Deeg, E. W.
Nevald, R. See Christensen, A. N.
Neville, A. M. See Rutledge, S. E.
Nevins, M. J., and Weintritt, D. J. Determination of cation exchange capacity by methylene blue adsorption, (7) 159*b*.
Newby, B. J. Separation of uranium from uranium dioxide-zirconium dioxide mixtures, P (11) 283*b*.
Newey, C. W. A., and Davidge, R. W. Dislocations in Lithium Fluoride, B (3) 88*g*.
Newkirk, H. W. See Cline, C. F.
Newman, K. See Anson, M.
Newnham, R. E. Crystal structure of $ZrTiO_4$, (5) 134*j*.
New Nippon Electric Co., Ltd. Glass capacitors having a chrome oxide layer on the electrodes, P (1) 10*g*.
Newport, G. N. See Bloom, M. C.
Newsham, D. M. T. See Leadbetter, A. J.
Newton, G. W. See Lucas, J. W.
Newton, R. C. Kyanite-andalusite equilibrium from 700° to 800°C, (1) 21*c*.
NGK Insulators, Ltd. Manufacture of porcelain objects from blast-furnace slag, P (3) 75*a*.
Nicholas, E. W., and Dildilian, A. T. Glass fabric with particulate material and pile yarns penetrating the same, P (8) 177*d*.
Nicholls, D. See Barton, L.
Nichols, E. J. See Nanigian, J.
Nichols, F. A. Theory of grain growth in porous compacts, (7) 168*j*.
Nicholson, D. See Dollimore, D.
Nickiene, M. See Aleinikov, F. K.
Nicki, J. Method and apparatus for growing monocrystalline layers on monocrystalline substrates of semiconductor material, P (3) 78*f*. Method of precipitating crystalline layers of highly pure brittle materials, P (11) 286*f*.
Nickle, N. L. See Speed, R. C.
Nickus, I., Zvirenas, A., and Truskauskas, I. Cast stone from local [Lithuania] materials, (8) 173*j*.
Nicolas, J. Kaolin of Quessoy (I) deposits, (7) 160*g*.
Nicoll, F. H. Ultraviolet ZnO laser pumped by an electron beam, (8) 183*j*.
Nicollian, E. H. See Kuper, A. B.
Niebuhr, J. Lower oxides of tantalum, (11) 298*a*.
Niel, E. See Schwiete, H. E.
Nielsen, S. Recrystallization of thin films of germanium and silicon, (10) 263*e*. See Filby, J. D.
Nielsen, T. H., and Leipold, M. H. Surface hydroxyl in MgO, (1) 29*f*.
Niemitz, G. Recovery of radiant heat losses from shells of rotary kilns, P (3) 82*a*.
Niemyski, T. See Mierzejewska, S.; Peshev, P.
Nies, N. P., and Jacobs, P. F. Crystalline sodium metaborate tetrahydrate and process for production thereof, P (4) 106*b*.
Niesel, K. See Masson, R.

Nigam, R. C. Direct rapid iodometric determination of magnesium in limestone, dolomite, and magnesite, (7) 159*d*.
Nihon Gaishi Kabushiki Kaisha. Method of manufacturing single crystals of corundum, P (9) 226*f*.
Nihon Genshiryoku Kenkyu Sho. Process for preparing fine spherical particles of thorium dioxide, P (8) 190*e*.
Niimi, Y. See Shibata, S.
Nikandrova, G. A. See Alekseeva, O. S.; Bokin, P. Ya.
Nikiforov, Yu. V. See Kogan, L. S.
Nikolic, P. See Woolley, J. C.
Nikol'skaya, T. A., Vil'k, Yu. N., and Avarbe, R. G. Variation of the molar mixing volumes in the systems zirconium-carbon and niobium-carbon, (10) 272*a*.
Nikol'skii, B. P., and Shul'ts, M. M. Generalized ion-exchange theory of the glass electrode, B (4) 113*g*.
Nikulina, L. N. See Levin, D. I.
Nilsen, W. G. See Comstock, R. L.
Nippon Columbia Co., Ltd. Piezoelectric transducer device, P (2) 49*a*.
Nippon Electric Co., Ltd. Glass sealed ceramic housings for semiconductor devices, P (10) 264*a*. Intermetallic compound semiconductor devices, P (4) 101*j*. Method of glass glazing, P (7) 157*e*. Method of making a conductive connection to a semiconductor device electrode, P (5) 128*a*. Method of manufacture of semiconductor elements, P (3) 78*j*. Method of manufacturing semiconductor devices, P (1) 11*e*. Method of manufacturing solid electrolytic capacitor, P (8) 185*j*. Method of producing tunnel diodes by double alloying, P (1) 11*h*. Negative resistance semiconductor device utilizing tunnel effect, P (5) 128*c*. Semiconductor device, P (2) 49*e*, P (7) 158*b*, P (8) 186*d*. Vapor deposition device, P (8) 186*e*. See Nippon Telegraph & Telephone Public Corp.
Nippon Electric Glass Co., Ltd. Method of preventing scum formation in glass melts and glass-ceramic products, P (2) 39*a*.
Nippon Sheet Glass Co., Ltd. Process for polishing glass, P (7) 150*c*.
Nippon Telegraph & Telephone Public Corp. Bilaterally bistable semiconductor device, P (2) 47*h*.
Nippon Telegraph & Telephone Public Corp. and Nippon Electric Co., Ltd. Variable-capacitance point contact diode, P (5) 129*e*.
Nisel'son, L. A., Pustil'nik, A. I., and Sokolova, T. D. Orthobaric density and critical parameters of the pentachlorides of niobium and tantalum, (8) 204*d*.
Nishi, C. K. See Prokopovich, N. P.
Nishida, M. See Ouchi, H.
Nishida, Y. Paramagnetic relaxation of chromium ion in ruby and potassium alum, (8) 204*h*.
Nishimoto, Y. See Atsukawa, M.
Nishimura, H. See Tomura, M.
Nishimura, J., and Oka, S. Steady flow of a viscous fluid through a tapered tube, (8) 207*c*.
Nishino, T., Moteki, K., and Shikano, H. Thermal decomposition of magnesium chromate, (4) 111*d*.
Nishiyama, G. See Hayashi, H.; Matsumoto, H.
Nishiyama, M. See Sameshima, Y.
Nishizawa, J. See Watanabe, Y.
Nishizawa, Jun-Ichi. See Fujikawa, K.
Nitsche, J. E. Methods for forming materials of high purity by fusion, P (5) 128*a*. See Callander, A. H.; Guyer, E. M.
Nitsche, J. E., and Smith, R. E. Method for reshaping glass articles, P (3) 69*b*.
Nitsche, R. E., and Wilson, R. W. Means for supporting glass tubing during the drawing thereof, P (1) 5*a*.
Nitschke, N. C. See McMaster, H. A.
Nitta, T. See Nagase, K.
Niwa, S., and Hiyama, H. Test on the vitrification of highly siliceous roseki brick, (9) 225*d*.
Nixon, S. A. See Hearne, K. R.
Nixon, V. H. Crusher, P (4) 106*j*.
Nizhenko, V. I. See Eremenko, V. N.
Noack, R. L. Method of making magnetic material with pattern of embedded nonmagnetic material, P (10) 264*j*.
Nobel, D. de. See Jochems, P. J. W.
Noga, Kin-ichi. Field emission studies on kinetics of barium oxide on tungsten, (3) 85*j*.
Noguchi, T. See Hayashi, H.
Nojima, S. See Kasugai, T.
Nolan, R. W. Electrochemical liquid junction structure and method for producing same, P (2) 38*e*.
Noll, W. S. See Eisenhower, W. D., Jr.
Nomura, K. See Kawai, N.
Nomura, S. See Nakagawa, T.
Nomura, S., and Akutsu, C. Oxidation kinetics and oxide film breakaway of zirconium and its alloys at high temperatures, (1) 2*j*.
Nonoyama, M. See Uyeda, R.
Noonan, J. See Esterowitz, L.
Nordberg, M. E. See Elmer, T. H.; Mochel, E. L.
Nordberg Mfg. Co. Automated crusher setting, P (10) 269*i*. [Bowl] adjusting mechanism for gyratory crushers, P (9) 235*j*. Crusher feeding apparatus, P (10) 269*c*. Frame for gyratory crushers, P (5) 133*a*.
Nordby, R. M. Cathode-ray tube, P (5) 127*b*.
Nordbye, O. Choosing the right type of plaster, (11) 283*g*.
Nordine, P. C. See Hoenig, C. L.
Norin, R. Crystal structure of $Nb_{12}O_{29}$ (monoclinic), (10) 270*i*.
Norman, E. K. Ceramic refractory bodies, P (2) 43*h*. See McTaggart, G. D.
Norreys, J. J. Uranium carbide-tungsten nuclear fuel composition, P (10) 261*b*.
Norrish, K. See Taylor, R. M.
North American Aviation, Inc. Bonded metallic and metallized ceramic members and method of making, P (2) 47*h*. Interconnecting circuits with a gallium and indium eutectic, P (11) 285*k*. Method of chemically bonding a metal to a ceramic, P (4) 101*c*. Method of providing high temperature protective coatings, P (4) 92*c*. Method of treating semiconductor device by ionic bombardment, P (9) 231*c*. Semiconductor structure including opposite conductivity segments, P (7) 158*c*.
North American Philips Co., Inc. Apparatus relating to evacuating and filling gas discharge lamps and the like, P (7) 149*h*. Ceramic article with sintered metallic layer and flux, P (7) 156*h*. Cold-cathode glow-discharge tube, P (2) 47*a*. Compound semiconductor device and method of making same by alloying, P (1) 10*j*. Compression ceramic-metal seal, P (5) 127*d*. Current lead-through member, P (1) 4*h*. Double layer oxide cathode with reducing agent, P (10) 263*d*. Green radiation lamp for optical maser, P (8) 184*e*. Incandescent lamp including a fluorine gas atmosphere and a solid fluorinating agent, P (7) 149*f*. Metallizing nonmetals, P (11) 286*d*. Method of coating p-type germanium with antimony, lead, or alloys thereof by electrodeposition and product thereof, P (9) 231*d*. Method of covering a glass wall portion of a cathode-ray tube, P (3) 68*c*. Method of making a casting mold, P (11) 282*c*. Method for making a ferromagnetic memory core, P (3) 78*i*. Method of making memory core, P (4) 101*j*. Method of manufacturing curved gas discharge lamps, P (3) 68*h*. Method of manufacturing [doped] semiconductor devices, P (9) 231*h*. Method of manufacturing [double diffused] semiconductor devices, P (10) 264*d*. Method of manufacturing germanium-containing products substantially free of fluorine from liquids containing fluorine and germanium, P (11) 286*e*. Method of manufacturing glass, P (5) 121*f*. Method of manufacturing glass articles having a high mechanical strength, P (3) 68*h*. Method of manufacturing a magnetic member having a coating of crystalline ferromagnetic material having uniaxial magnetic anisotropy, P (5) 128*f*. Method of manufacturing MnBi magnets, P (8) 185*h*. Method of manufacturing parts of annular magnetic heads, P (10) 264*e*. Method of manufacturing photoconductive layers, P (2) 48*a*. Method of manufacturing a semiconductor device by vapor deposition, P (10) 264*f*. Method of manufacturing semiconductor devices using cadmium sulfide semiconductors, P (1) 11*f*. Method of manufacturing semiconductor systems comprising cadmium chalcogenide semiconductors, P (2) 48*b*. Method of producing doped semiconductor material and apparatus for carrying out the methods, P (9) 231*a*. Method of providing tubular lamps, P (9) 221*k*. Optical device having an infrared radiation transmitting and visible radiation reflecting layer of lanthanum hexaboride, P (2) 48*h*. Passive gas cell frequency standard in the millimeter wave range, P (8) 185*f*. Photosensitive device including layers of different conductivity types, P (2) 48*j*. Planar semiconductor device with improved emitter and base configuration, P (10) 265*c*. Preparing nickel ferrite single crystals on a monocrystalline substrate, P (10) 265*f*. Process for joining surfaces of refractory material with a MnO-SiO_2-Al_2O_3 system, P (8) 181*j*. Refractory metal-to-ceramic seal, P (11) 283*e*. Sintered tantalum carbide bodies, P (8) 182*d*. Solid semiconductor circuit with crossing conductors, P (3) 79*f*.
Northern Brick Co. (Belfast), Ltd. Bricks, P (2) 40*i*.
Northern Electric Co., Ltd. Method for alloying an electrode with a semiconductive body, P (9) 231*d*. Method for making a semiconductor device by diffusing impurities through spaced-apart holes in a nonconducting coating to form an overlapped diffused region by means of transverse diffusion underneath the coating, P (5) 128*c*. Sputtering apparatus including a folded flexible conveyor, P (2) 49*a*.
Northover, W. R. See Pearson, A. D.
Northrop, D. A. Vaporization of lead zirconate-lead titanate materials, (10) 272*a*.
Northrop, D. A., and Clayton, R. N. Oxygen isotope fractionations in systems containing dolomite, (1) 24*f*.
Northrop, D. P. See Emidy, T. J.
Northwest Magnesite Co. Method of preparing magnesia, P (8) 181*e*.
Norton, B., and Levinstein, H. Process for preparing thin film semiconductor thermistor bolometers and articles, P (7) 157*g*.
Norton, C. L., Jr., Bohling, W. C., and Fentzke, A. D. Insulating firebrick, P (7) 153*c*.
Norton, F. J., and Seybolt, A. U. Gas permeation through fused-silica capsules during high temperature heat treatments, (3) 86*b*.
Norton Co. Coated abrasives, P (10) 247*g*, P (11) 273*g*. Firing of grinding wheels and the like in a tunnel furnace, P (9) 213*f*. Fusion process for production of stoichiometric UO_2, P (8) 181*d*. Hot pressing apparatus, P (5) 130*e*. Humidity controlled phenolformaldehyde resin bonded abrasives, P (9) 213*g*. Metal backed abrasives, P (2) 33*k*. Method of hot pressing metals and refractories, P (11) 282*a*. Polymer saturated backing material, P (4) 89*f*. Process for making metal bonded diamond tools employing spherical pellets of metallic powder-coated diamond grits, P (8) 173*g*. Protective flame sprayed coatings, P (9) 217*c*. Pulpstones and method of making, P (1) 1*f*. Rods for flame spraying, P (10) 250*g*. Vertical kiln for continuous grain calcination, P (1) 15*a*.
Norton Grinding Wheel Co., Ltd. See De Havilland Aircraft Co., Ltd.
Noss, K. See Klima, K. G.
Novack, M. A., Jr., and Dionne, G. F. Direct glass-Kovar tubular seals, (1) 3*f*.
Novak, J. See Arend, H.
Novak, R. F., and Zabroski, F. Device for orienting bottles, P (11) 278*d*.
Nova Products, Inc. Conveyor, P (5) 130*d*.
Novikov, G. I. See Polyachenok, O. G.
Novikov, G. I., and Gavryuchenkov, F. G. Saturated vapor pressure of the chlorides of Ca, Sr, and Ba, (7) 167*e*.
Novikov, G. I., Polyachenok, O. G., and Frid, S. A. Fusibility diagram of the systems formed by the di- and trichlorides of samarium and ytterbium with potassium chloride, (7) 163*i*.
Novikova, T. A. See Tumanov, V. I.
Novokhatskii, I. A., Belov, B. F., Gorokh, A. V., and Savinskaya, A. A. Phase diagram of the system ferrous oxide-alumina, (11) 299*b*.
Novoselova, A. V. See Aslanov, L. A.
Novoselova, A. V., Korenev, Yu. M., and Korzenkova, M. P. System KF-BeF_2, (11) 301*g*.
Novotny, J., and Spurny, Z. Effect of ionizing radiation of glasses—kinetics of radiocoloration and phosphorescence of borate glasses, (8) 175*i*.
Nowak, E. A. Screen decorating apparatus, P (7) 150*e*. Screen decorating method, P (2) 40*c*.
Nuckolls, D. E. See Stoddard, S. D.
Nuclear Power Plant Co., Ltd., and A. E. I. John Thompson Nuclear Energy Co., Ltd. Nuclear reactor cores, P (4) 98*h*.
Nuclear Technical Service Corp. Method for forming a refractory metal or carbide coating on refractory materials and article, P (5) 117*i*.
Nudel'man, B. I. See Lobanov, E. M.
Nudelman, S. See Lambe, J. J.
Nuese, C. J. See Holonyak, N., Jr.
Nukem Nuklear-Chemie und- Metallurgie Gesellschaft m.b.H. Fuel material for nuclear reactors and process and apparatus for its manufacture, P (2) 44*c*.
Nussbaum-Christmann, G. Composite abrasive grindstones, P (7) 145*g*.
Nussear, J. G. See Reznick, F. J.
Nutter, G. D., Wike, R. B., and Bollerman, P. V. High precision automatic optical pyrometers, (9) 233*g*.
N. V. Koninklijke Sphinx-Ceramique. Apparatus for suspending plates, saucers, etc., during glaze firing, P (11) 283*h*.
N. V. Philips' Gloeilampenfabrieken. Ceramic objects and their manufacture, P (3) 80*g*. Fuel elements for use in nuclear reactors, P (1) 7*f*. Furnace, P (11) 290*c*. Manufacture of ceramic bodies, P (11) 288*e*. Manufacture of a memory core, P (11) 286*b*. Soft magnetic sintered body and its manufacture, P (10) 265*e*.
N. V. Vereenigde Glasfabrieken (United Glassworks). Method of and apparatus for covering a moil from a glass workpiece, P (8) 177*b*. Method of removing glass articles from a mold, P (8) 178*i*. Methods of molding integrally a glass foot and stem part of a stem type glass, P (1) 6*f*.
Nyberg, B. See Kierkegaard, P.
Nye, W. F. See Cook, C. F., Jr.
Nylander, A. G. See Wood, T. K.
Nyquist, R. A. See Zellers, J. T., Jr.
Nystroem, E. H. B. Production of glass and like mineral fibers, P (4) 95*f*.

Oakes, A. C., Hatfield, C., and Oakes, W. W. Glass cutting apparatus, P (3) 67*g*.
Oakes, W. W. See Oakes, A. C.
Obata, Y. Intensity variation of paramagnetic resonance lines of rare earth ions in garnets, (5) 136*h*.
Obenhaus, V. M. Method of making a mica paper capacitor, P (10) 264*b*.
Oberg, P. E. Masking device, P (10) 264*f*. See Hanson, M. M.
Oberlin, M., and Mering, J. Study of the oxidation kinetics of a graphitic carbon in a liquid environment, (4) 110*j*.
Oberlin, M., Rappeneau, J., and Yvars, M. Kinetics of oxidation of the liquid phase of nonirradiated and irradiated nuclear graphites, (2) 55*c*.
Obermayer, S., Co. Plastic refractory compositions, P (2) 44*j*.
Oberschmidt, L. E. Alsey Refractories makes strong comeback, (9) 223*c*. Broad River leaps ahead with new Blacksburg plant, (9) 222*g*. Carolina Lightweight Aggregate Co., Inc., builds model plant, (1) 6*h*. Clay roof tile captures 95% of home market, (4) 95*j*. Hanley demonstrates new firing system, (4) 105*d*. Higgins presses 8 x 8 x 16 in. block from brick mix, (4) 95*j*. Japan's brick industry studies new methods, (4) 96*b*. Mesalite produces 60% of Japanese lightweight aggregate, (4) 96*b*. Mission Clay Products Corp. sets pace with straight pipe, (4) 96*d*. Modern refractories plant operates two tunnel kilns, (4) 97*i*. New high in automation at

Burns Brick, (9) 223*b*. Pacific Clay Products—California's leading heavy clay products manufacturer, (4) 96*a*. Product diversification costs $6 million at Port Costa, (4) 96*b*. Products made by five processes at Shinagawa, (4) 97*d*. San Valle builds automated roof tile plant, (4) 96*b*. Streamlined production flow featured at new Porter plant, (9) 223*c*. 3000 plus, (5) 123*i*. Time and costs studied on isostatic pressing, (9) 223*d*. Tokoame ships 50% of Japan's clay pipe, (4) 96*c*.

Obrecht, C. D. See Fulton, H. A.

O'Brien, D. L. Constrained ceramics, P (7) 155*b*.

O'Brien, J. L. See Allen, R. V.

O'Brien, R. F., and Milette, K. A. Toilet construction, P (7) 155*f*.

Obrowski, W. See Kolb, F.

O'Bryan, H. M., Jr., Monforte, F. R., and Blair, R. Reply to discussion of "Oxygen content of nickel ferrite at 1300°C," (1) 28*g*.

O'Bryan, H. M., Jr., and Parravano, G. Sintering of single crystal rutile, (11) 300*j*.

Obst, K. H. Mutual solubility of CaO and MgO in calcined dolomite, (8) 202*j*. See Malissa, H.; Troemel, G.

Obst, K. H., Horn, H. C., and Muenchberg, W. Evaluation of magnesite sinters with microscope and electron-beam microanalysis, (8) 197*f*.

Ochiai, T. See Oomori, K.

O'Connell, T. B., Badger, A. E., Herbert, J. W., and Wilson, W. I. Glass contacting refractories, P (9) 225*h*.

O'Connor, J. R. Unusual crystal-field energy levels and efficient laser properties of YVO_4:Nd, (11) 303*b*.

O'Connor, J. R., Schaffer, P. S., and Bradbury, R. A. Laser properties of a vapor-grown ruby, (8) 183*c*.

O'Connor, T. L., Juda, W., McNally, P. H., and Rosenberg, N. W. Preparation of thoria sols by electrodialysis, P (1) 16*a*.

Oda, J. See Matsukura, Y.

O'Dell, E. W. See Swinehart, C. F.

O'Dell, E. W., Dierssen, G. H., and Hofstadter, R. Calcium iodide phosphors, P (5) 127*a*.

O'Dell, T. H. Measurements of the magnetoelectric susceptibility of polycrystalline chromium oxide, (1) 22*b*.

O'Donnell, J. M., Platt, R. O., and Gabor, C. D. Process for making refractory brick, P (2) 45*d*.

Oel, H. J. Determination of the size distribution of particles, crystallites, and pores, (5) 130*j*. Properties of powders and the sintering of pure magnesia and of magnesia with nickel, (5) 137*i*. See Frischat, G. H.; Krauth, A.

Oel, H. J., and Dietzel, A. Basic research on the weathering and leaching of enamels and glasses, (3) 64*j*. Measurement of stress in fired enamels, (10) 249*j*.

Oel, H. J., and Frechette, V. D. Stress distribution in multiphase systems (I) composites with planar interfaces, (11) 301*g*.

Oelke, W. W., Badger, A. E., Mambourg, J. E., and Mewbourne, C. A. Insulated edge roller for window glass machine, P (10) 255*g*.

Oess, F. Cathode ray tube mesh assembly supported between envelope sections, P (2) 47*i*.

Oesterheld, K. A. Apparatus for dressing crude asbestos, P (2) 53*h*. Device for dressing crude asbestos, P (11) 291*e*. Method of opening up fibrous bundles of crude asbestos separated from the source rock, P (8) 190*b*.

Oesterreichisch-Amerikanische Magnesit Akt.-Ges. Process for making unfired brick based on magnesia, P (3) 72*i*. Process for the production of very strong briquets, P (10) 260*b*. Refractory brick unit, P (4) 99*f*, P (5) 125*a*.

Oetting, F. L. Determination of plutonium in plutonium oxide by calorimetry, (8) 187*h*.

Ogawa, Kazuo. See Shiraki, Y.

Ogawa, Keiichi. Transmission electron-microscopic studies on mechanisms for dipole formation in MgO, (8) 210*e*. Transmission electron-microscopic studies on surface effect on dislocation and friction stress in MgO, (2) 59*c*.

Ogawa, M. See Kunii, D.

Ogawa, S., and Waki, S. Specific heat of Co_2TiO_4 and its anomaly associated with magnetic transition, (11) 301*d*.

Ogawa, T. See Ohba, H.

Ogden, H. R. See Bradley, E. F.

Ogilvie, R. E. See Ban, Z.; Schippert, M. A.

Ogiso, S. See Hayashi, H.

Oglebay Norton Co. Bottom ring-wiper strip assembly [for a hot top] and method of making it, P (10) 259*e*. Continuous casting method with degassed glasslike blanket, P (8) 180*i*.

Ognyanova, E. Z., and Kramer, G. L. Phosphogypsum as an effective mineralizer for firing cement, (9) 215*d*.

O'Hara, S. See Hamilton, D. R.

Ohba, H. See Sugita, K.

Ohba, H., Hiragushi, K., and Ogawa, T. Study on slag corrosion of casting pit refractories (I) effect of casting conditions on slag corrosion of siliceous fireclay brick, (9) 224*j*.

Ohba, H., and Sugita, K. Slagging resistance of basic refractories under load, (2) 43*c*. Wettability of refractories by molten steel—determination of wettability by carbon steels under a hot-stage microscope, (2) 43*j*.

Ohba, T. See Hamano, K.

Ohio Brass Co. Ceramic supports, P (3) 74*j*.

Ohio Fire Brick Co. Method and apparatus for metal cladding refractory brick, P (8) 181*i*.

Ohio Lime Co. Process for producing high purity alkaline earth compounds, P (11) 275*i*.

Ohlberg, S. M., and Parsons, J. M. Distribution of sodium ions in soda-lime-silica glass, B (2) 61*f*.

Ohlgren, H. A. See Lewis, J. G.

Ohlmann, R. C. See Haun, R. D., Jr.; Mazelsky, R.

Ohmachi, T. See Nameishi, N.

Ohmart, P. E. Method and apparatus for continuously weighing material on a conveyor comprising a radioactive source and detector, P (1) 12*h*.

Ohmart Corp. Method and apparatus for continuously weighing material on a conveyor comprising a radioactive source and detector, P (1) 12*h*.

Ohta, K. See Azuma, K.

Ohta, K., Tomita, T., and Watanabe, T. X-ray micrographic study of silicon carbide crystals, (11) 303*b*.

Ohtsuka, A. Effect of the coordination preference of cations on the formation and color development of tin spinels, (11) 293*h*. Formation and color development of magnesium-zinc-titanium spinels containing Co^{2+} and Ni^{2+} ions, (11) 295*j*. Formation and color development of titanium-tin spinels containing Co^{2+} and Ni^{2+} ions, (11) 296*a*.

Oikawa, M., and Okabe, T. Low temperature fusible glass, P (7) 149*g*.

Oishi, M. See Huzimura, R.

Oja, W. J. Method and apparatus for de-shotting and separating mineral fiber, P (7) 149*h*.

Oka, S. See Nishimura, J.

Okabe, T. See Oikawa, M.

Okada, J. See Takeuchi, Y.

Okada, K. See Koide, S.

Okada, T., and Akashi, T. Richter-type aftereffect in manganese zinc ferrite, (9) 241*j*.

Okada, T., Sekizawa, H., and Iida, S. Ferromagnetic resonance in garnet $Y_3Fe_{5-x}Co_{x/2}Ge_{x/2}O_{12}$, (7) 163*c*.

Okada, Y. See Masuda, M.

Okai, B. See Nagasawa, H.

Okamoto, E., and Koike, M. Method of manufacturing solid electrolytic capacitor, P (8) 185*j*.

Okamoto, G. See Furuichi, R.

Okamura, T. Method for the treatment of raw glass material containing easily volatilizable ingredients, P (3) 69*c*.

O'Kane, D. F. See Axe, J. D.

Okazaki, K., and Kashiwabara, S. Microstructure and dielectric properties of high permittivity ceramics, (7) 155*i*.

Okazaki, K., Takemoto, H., and Takahashi, K. Sintering of ceramic dielectric materials by hot-pressing, (7) 156*b*.

Okazaki, K., Yoshioka, T., and Takahashi, K. Anomalous expansion in the firing of piezoelectric ceramics containing PbO, (7) 155*h*.

Okhotin, M. V., Vilenskaya, E. I., and Tuzikov, A. I. Methods of measuring the viscosity of glass in a tank furnace, (3) 66*c*.

Okhrimenko, Yu. Ya. See Malyuchkov, O. T.

Okikawa, S. See Somiya, S.

Okorokov, S. D., and Gol'dshtein, L. Ya. Strength of fused portland cements as a function of their composition, (10) 248*h*.

Okorokov, S. D., Golynko-Vol'fson, S. L., Satalkina, M. A., and Dmitrieva, G. G. Specific features of mineral formation in the CaO-Al_2O_3-SiO_2 system in the presence of gypsum and CaF_2, (9) 215*a*.

Okuda, H., Kato, S., and Iga, T. Composition of mullite formed in kaolin minerals containing LiF at temperatures below 900°C, (5) 134*f*. Effects of fluoride used as mineralizer on thermal reaction of kaolin minerals, (5) 135*a*.

Okuda, S. See Faruqi, F. A.; Hayashi, T.

Olaculith Patentverwertungs A.G. Heat-resistant structural element and the like, P (3) 64*e*.

Olby, J. K. Ceramic stains, P (4) 100*a*. Stains for ceramic glazes, P (7) 155*d*.

Olcott, J. S. Glass-ceramic body and method of making it, P (1) 5*b*.

Oldfield, B. W. See Steele, B. R.

Oldfield, L. F., Harwood, D. J., and Lewis, B. Differential thermal analysis and X-ray diffraction study of devitrification process (I) Li_2O-B_2O_3-SiO_2 glasses; (II) Li_2O-Al_2O_3-B_2O_3-SiO_2 solder glasses, (9) 217*h*.

O'Leary, T. G. Fluorescent glass and method of making it, P (9) 219*j*. Method of making a phototropic glass article, P (5) 121*d*.

Oleinikova, V. A. See Smirnov, M. V.

Oles, K. F. See Enlows, H. E.

Olin Mathieson Chemical Corp. Brazing flux and method of brazing with same, P (9) 217*b*.

Oliver, A., Jr. Late Hellenistic glass in the Metropolitan Museum, (11) 274*a*.

Oliver, E. M. See Mayer, E. H.

Oliver, J. F. See Anderson, P. J.

Ollfisch, F., and Reinmold, H. Method and apparatus for severing glass panels, P (5) 121*b*.

Olmstead, J. A. See Scott, J. H., Jr.

Olombel, A., Perebaskine, C., and Raggenbass, A. Sintered pollucite radioactive source and method of production, P (11) 292*a*.

Olphen, H. van. Internal mutual flocculation in clay suspensions, (8) 200*i*.

Olsen, D. A., and Osteraas, A. J. Critical surface tension of glass, (8) 175*g*.

Olsen, E., and Mueller, R. F. Stability of orthopyroxenes with respect to pressure, temperature, and composition, (10) 272*d*.

Olson, N. E. See Benecke, M. W.

Olsson, R. G., and McKewan, W. M. Diffusion of H_2-H_2O through porous iron formed by the reduction of hematite, (9) 238*g*.

Olstowski, F. Acid-wetted expandable phosphorus containing graphite composition and method of preparation, P (10) 259*c*. Process for producing expanded graphite, P (9) 227*c*. See Osborn, O.

O'Meara, E. L., Jr. See Sandmeyer, K. H.

Omel'chenko, Yu. A. See Kondrashev, Yu. D.; Vil'k, Yu. N.

Omori, T. See Kishii, T.

Ondracek, G. See Gebhardt, E.

O'Neil, F. H. Electrical device with casing seal members comprising a cavity in meeting surface, P (4) 101*b*.

O'Neill, E. T. Piezoelectric crystal evaluator, P (3) 81*h*.

O'Neill, J. J., Jr. See Goodman, A. M.

Onn, D. G., Remeika, J. P., Meyer, H., and Henderson, J., Jr. Calorimetric study of several garnets at low temperatures, (8) 192*a*.

Ono, S. See Yamaguchi, G.

Ono, Y. See Yamaguchi, G.

Onoda Cement Co., Ltd. Method for the manufacture of glass, P (10) 255*i*. Method for the preparation of cement, P (4) 91*d*, P (8) 174*e*. Method of retarding the setting time of cement, P (8) 174*c*. Pan-type granulating machine [nodulizer], P (11) 275*g*. Process for regulating the humidity of gas entering an electrical dust collector, P (10) 268*j*.

Onodera, Y. Positive phonon drag effect in the Nernst coefficient of CdS, (9) 241*e*.

Ontario Research Foundation. Electrostatic separator with coated discharge electrode, P (3) 83*c*.

Onuki, M., and Miyake, T. Photoconductivity of CdS in blocking electrodes, (5) 137*h*.

Ooka, K. Corrosion of molybdenum by molten glasses, (5) 118*f*. See Kishii, T.

Ooka, K., and Kishii, T. Stress in glass caused by ultraviolet radiation (II) stress in some borosilicate glasses; (III) stress buildup in various commercial glasses; (IV) effect of gamma and ultraviolet radiation on commercial borosilicate glasses, (7) 148*c*.

Oomori, K., Shimazaki, T., Ochiai, T., Nakayama, M., Aizawa, I., and Imai, H. Properties of unfired roseki ladle brick and its durability, (9) 224*j*.

Opoczky, L. Better utilization of the hydraulic properties of blast-furnace slags by wet grinding, (7) 146*b*. See Beke, B.

Ordzovensky, S. See Matiasovsky, K.

Orem, M. See Adamson, A. W.

Orlov, A. N. Kinetics of dislocations, B (4) 114*c*.

Orlova, G. P., and Rudnitskaya, E. S. Interaction of water with silicate melts under pressure, B (7) 171*e*.

Orlova, I. G. See Kainarskii, I. S.

Orme, G. R. See Fruth, L. S., Jr.

Ormsby, W. C., and Diamond, S. Effect of Ca$(OH)_2$ on the flow properties of montmorillonite-water systems, (2) 45*j*.

Ormsby, W. C., and Marcus, J. H. Flow properties of aqueous suspensions containing kaolins of varying degrees of crystallinity, (5) 136*e*.

Orne, N. Electrical separation of dust, P (2) 50*c*.

Orrok, N. E. Machining with oxide tooling, (2) 33*i*. Percussion welder coats tools with carbides, (2) 33*i*.

Orrville Tile Co. Method for producing and handling elongated tubular items, P (7) 150*j*.

Orth, W. H. Effect of firing rate on physical properties of wall tile, (10) 261*e*. Furnaces for fast-firing ceramic ware and fast-firing process, P (9) 234*j*.

Orton, J. W. See Wertz, J. E.

Osafune, H., and Kurosawa, T. Semiconductor device, P (8) 186*d*.

Osafune, H., and Nakamura, Tetsuro. Method of manufacturing semiconductor devices, P (1) 11*e*.

Osak, B. J. See Otis, C. L.

Osaka Kinzoku Kogyo Co., Ltd. Preparation of uranium dioxide, P (4) 98*j*.

Osakeyhtio, A. A. Process for the manufacture of shaped objects of foamed glass, P (1) 6*c*.

Osborn, E. F. Comment on "Hydrothermal silica transformations," (1) 17*e*.

Osborn, O., Olstowski, F., and Horvath, J. W. Method of hot topping using [acid-treated] vermicular graphite, P (7) 153*j*.

Osborne, D. W. See Flotow, H. E.

Osborne, G. J. See Gutt, W.

Osborne, J. F., Larrabee, G. B., and Harrap, V. Determination of sodium in ultrapure silicon and silicon dioxide films by activation analysis, (10) 267*c*.

Oscar Gossler Glasgespinstfabrik G.m.b.H. Methods of and apparatus for producing fleeces of fibers, e.g., glass fibers, P (7) 150*f*.

Oscar-Paul Corp. Potter's wheel having a variable speed power transmission system, P (3) 64*a*.

Oser, W. Fuel cell, P (1) 10*e*.

Oshcherin, B. N. New formula for calculating the characteristic temperature from the melting point, (3) 87*b*.

Osmer, J. A. See Chase, A. B.

Ostapenko, G. T. Results of a study of the dissociation of gypsum under pressure and their possible significance for petrology, (10) 271*j*. Trivariant equilibria and plotting diagrams of the chemical potentials for them, (8) 210*h*.

Ostberg, J. E. Method for controlling the reaction in an arc furnace, P (9) 235*a*.

Ostberg, W. Device for removing clinker from [rotary kiln] thermocouple probe, P (9) 215*g*.

Osteraas, A. J. See Olsen, D. A.

Osterberg, H. See Snitzer, E.

Osterholtz, C. E., Werner, J. E., and Baab, K. A. Stability of refractories during vacuum deoxidation of steel, (1) 7*j*.
Osterried, O. See Gugel, E.
Ostertag, W. See Collins, C. V.
Ostertag, W., and Collins, C. V. Electrical resistivity of cubic rare earth, th...um, and uranium tungsten bronzes, (9) 229*g*.
Ostrander, G. W., and Pendleton, W. W. Porous-refractory encapsulant for coils and coil encapsulated therewith, P (5) 124*g*.
Ostrikov, M. S. See Dibrov, G. D.
Ostrikov, M. S., Dibrov, G. D., and Danilova, E. P. Capillary contraction forces in tricalcium aluminate and tetracalcium aluminoferrite, (4) 90*e*.
Ostrovskaya, T. V. See Pechkovskii, V. V.
O'Sullivan, G. A. Resistance thermometer system, P (4) 105*a*.
Ota, M. Frost-resisting properties of Japanese roofing tile, (2) 40*g*.
Otero, J. L. See Mendez-Penalosa, R.
Otis, C. L., and Osak, B. J. Process for preparing sheet metal surfaces with dry lubricant coatings, P (4) 92*e*.
Otrhalek, J. V. Process for agglomerating anhydrous sodium metasilicate fines, P (11) 291*e*.
Otsuka, N. See Shiraki, Y.
Otterbein, H. Flame-photometric determination of Na_2O and K_2O in cements and cement raw materials, (5) 116*e*.
Ottley, D. J. Pierre Gy's sampling slide rule, (3) 82*h*.
Otto, Dr. C., & Comp. G.m.b.H. Manufacture of refractory products, P (2) 44*h*. Production of refractories, P (2) 45*h*.
Otto, E. M. Equilibrium pressures of oxygen over MnO_2-Mn_2O_3 at various temperatures, (11) 295*h*.
Otto, K., and Milberg, M. E. Ionic conduction and structure in cesium and thallium silicate glasses, (11) 277*d*.
Ouchi, H., Nishida, M., and Hayakawa, S. Piezoelectric properties of $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics modified with certain additives, (1) 10*c*.
Oudemans, G. J. See Stuijts, A. L.
Oudenhoven, M. S., and Krempasky, G. T. Photoelastic study of an internally stressed circular opening in a biaxial stress field, (1) 26*g*.
Oulton, T. D. Synthetic swelling lithium aluminum silicate hydrate product, P (5) 126*b*.
Outboard Marine Corp. Traction drive for ceramic regenerators, P (4) 99*c*.
Outwater, J. O., and Gerry, D. J. Effects of high uniaxial compressive stress on glass, (8) 175*b*.
Ovcharenko, F. D. See Gudovich, N. V.
Overkott, E. See Geimer, H.
Ovitron Corp. Coaxial termination utilizing boron nitride member to enhance radiation, P (4) 100*i*.
Ovsyannikov, I. O., Vainshtein, E. E., and Samsonov, G. V. LIII X-ray absorption spectra of lanthanum and cerium in certain compounds with nonmetals, (4) 108*c*.
Owen, A. E. See Schmidt, P. F.
Owen, C. J. Method of making a thin-film [passive] electronic component, P (11) 286*c*.
Owen, J. See Eichler, B.
Owen, V. J., and Clews, F. H. Methods of measuring the thermal conductivity of bricks at room temperature, (2) 50*f*.
Owens, I. E. Proper fluids mean better quartz grind, (7) 145*f*.
Owens-Corning Fiberglas Corp. Apparatus [belt] for coating continuously produced filaments, P (10) 254*h*. Apparatus for collecting filamentary materials, P (5) 119*h*. Apparatus for forming and collecting filamentary materials, P (1) 4*c*, P (8) 176*e*. Apparatus for forming and collecting filaments, P (3) 67*b*, P (10) 254*h*. Apparatus for making composite fibers P (10) 254*b*. Apparatus for melting and processing heat-softenable mineral materials, P (9) 219*f*. Apparatus and methods for producing panels of mineral fibers, P (11) 277*i*. Apparatus for processing filament-forming mineral materials, P (9) 219*j*. Apparatus for processing heat-softenable mineral material, P (10) 254*c*. Apparatus for producing fibers from heat-softenable material, P (2) 38*g*. Apparatus for producing fine continuous filaments, P (3) 67*f*. Apparatus for the production of continuous glass fibers, P (5) 120*a*. Compatible fibrous glass reinforcements of superior bonding and wetting characteristics, P (7) 149*j*. Elastomeric-glass fiber products and process and elements for use in same, P (2) 38*d*. Epoxide additive for amylaceous forming size compositions, P (4) 94*d*. Feeder for production of fibers of heat-softenable materials, P (5) 120*e*. Fibrous acoustical panel with impregnant in rear body portion, P (10) 255*b*. Fibrous glass [decorative] binder, P (10) 255*b*. Glass distribution means for a rotary fiber-forming apparatus, P (11) 278*j*. Glass mat fibers bonded together by a polyester composition, P (11) 278*c*. High temperature insulation for electrical conductors, P (8) 177*g*. High temperature resistant acoustical board, P (2) 44*f*. Method and apparatus for flowing streams of heat-softened material from a supply, P (7) 149*i*. Method and apparatus for indication and control of fiber-forming operations, P (4) 94*f*. Method and apparatus for producing foliated or flake glass, P (9) 220*j*. Method and apparatus for producing strand package, P (2) 39*e*. Method and apparatus for producing a wound textile package having uniform tension, P (1) 5*g*. Method and apparatus for treating and packaging strands of filaments, P (1) 5*g*. Method for applying a forming lubricant to glass fibers, P (2) 39*f*. Method for bonding bodies of multifilament strands, P (8) 177*h*. Method for controlling the temperature of heat-softenable material, P (9) 221*d*. Method for indicating material stream characteristics by calorimetry, P (9) 221*g*. Method of making a bonded mat of surface treated glass fibers, P (2) 39*g*. Method of making elastomeric-glass fiber products for use in endless belts, P (4) 95*a*. Method of making hollow glass fibers, P (2) 39*h*. Method of producing strong foamed glass bodies and structure produced thereby, P (9) 221*f*. Neoprene-glass fiber structures and method for preparation, P (7) 150*g*. Nickel chrome alloy, P (8) 178*c*. Packaging compressible material, P (9) 221*j*. Phenolic resole-bone glue-urea-diluent extender binder composition for bonded mat, P (9) 221*j*. Process of producing flexible glass flake electrical insulation, P (4) 95*e*. Process for producing integrated body of multifilament strands, P (4) 95*d*. Producing high temperature calcium silicates, P (8) 190*g*. Production of polarizing elements, P (3) 69*c*. Reinforced composites and method for producing the same, P (3) 64*g*. Reinforced mat construction and method of forming same, P (1) 6*d*. Slurry pouring means and method, P (4) 103*j*. Temperature control system for high temperature melters or the like, P (2) 40*a*. Transfer pallet construction, P (1) 9*d*. Treated glass fibers and methods for treating glass fibers to improve the bonding relation with epoxy resins, P (11) 279*g*.
Owens-Illinois, Inc. Apparatus for blending molten glass, P (9) 219*c*. Apparatus for inspecting glassware, P (8) 176*e*. Apparatus for measuring the resistivity of molten glass, P (11) 277*h*. Apparatus for measuring the wall thickness of glass containers, P (9) 219*e*. Apparatus and method for press molding glass articles, P (3) 67*d*. Apparatus for sealing hollow glass parts, P (3) 67*g*. Article grouping device, P (2) 38*j*. Article handling and transfer device, P (5) 120*b*. Bottle inspector including a rotating photocell for scanning, P (9) 219*j*. Bottle metering mechanism, P (1) 4*g*. Bottle sorting machine and method, P (1) 4*g*. Cathode-ray and other vacuumized tubes resistant to fracture and capable of controlled evacuation, P (10) 254*k*. Cathode-ray tubes, P (10) 254*k*. Colored glasses and process of manufacture, P (9) 219*c*. Conductive mold rack for electrocleaning mold parts, P (4) 94*b*. Cylinder mounting on I.S. type glassware forming machine, P (8) 177*b*. Decorating chuck, P (9) 219*e*. Detection of chips in syringe cartridges, P (9) 219*f*. Electrical printing using stencil and moving slot powder metering means, P (5) 120*e*. Feeder tube support and drive for glass furnace, P (10) 255*a*. Forehearth construction, P (3) 67*d*. Gaging wall thickness of glass tubing, P (5) 120*i*. Glass aerosol bottles and method for making same, P (2) 38*f*. Glass forming apparatus, P (11) 278*a*. Glass furnace bottom wall construction, P (5) 120*b*. Glass melting furnace, P (9) 220*e*. Glass shaping plunger with a mercury mass condenser cooling means, P (2) 38*h*. Glass tube gaging and cutting apparatus, P (8) 177*e*. Glassware handling apparatus, P (9) 220*k*. Gob chute with fluid flow means, P (11) 278*d*. Hermetically sealing glass parts including intervening electrical conductor, P (3) 68*b*. Inspecting containers for slant bottom condition, P (3) 68*c*. Inspecting glass containers with lasers, P (5) 120*e*. Inspecting glass containers for line-over-finish defects, P (5) 120*e*. Inspecting glass containers having rounded top finishes, P (9) 220*b*. Inspecting hypodermic syringe cartridges and the like, P (5) 120*e*. Luminescent glass articles and method for forming same, P (4) 94*a*. Means for controlling electric currents in a glass furnace, P (9) 220*c*. Method and apparatus for handling hot deformable glassware, P (5) 121*a*. Method and apparatus including flexible conductive offset member for decorating articles, P (1) 5*e*. Method and apparatus for manufacturing pipettes, P (7) 149*j*. Method of and apparatus for producing nonthermal currents in a body of molten glass, P (3) 68*j*. Method of an article formed by sealing alumina ceramic to a metal with a sealant glass, P (10) 255*e*. Method for controlling the rate of devitrification, P (4) 94*i*. Method of feeding mixed colorants to glass in the forehearth, P (10) 255*g*. Method for improving the durability of glassware, P (11) 279*b*. Method for increasing scratch resistance of a glass surface with a pyrolyzing treatment and a coating of an olefin polymer, P (9) 221*e*. Method of shearing charges of molten glass, P (2) 39*c*. Mold and plunger with internal cooling structure, P (2) 39*g*. Molded semivitreous article and method of making same, P (8) 178*b*. Molten glass feeder tube centering and drive, P (10) 256*a*. Neck mold and plunger unit for glass forming apparatus, P (5) 121*c*. Partially devitrified glass article and method for making the same, P (4) 95*i*. Perovskites, P (7) 157*b*. Preparation of silica gel, P (9) 236*e*. Process and apparatus for electrostatically printing on hot substrate, P (3) 69*a*. Reciprocating glass pressing apparatus, P (10) 256*a*. Reinforced cathode-ray tube and faceplate therefor, P (8) 179*a*. Screen decorating apparatus, P (7) 150*e*. Screen decorating method, P (2) 40*c*. Sealing glass parts to form cathode ray tube envelopes, P (9) 222*d*. Solder glass compositions and method of sealing therewith, P (3) 69*f*. Takeout apparatus for glass forming machines, P (5) 121*h*. Timing system for I.S.-type glassware forming machine, P (5) 121*h*. Transparent glass container and method of making same, P (4) 95*h*. Transparent reinforced glass pipe, P (8) 179*b*. Tumbler beader, P (2) 40*c*. Ultraviolet light-absorbing glass, P (3) 69*h*.
Owens-Illinois Glass Co. Method and apparatus for electroforming split glassware molds, P (2) 39*d*. Mold and plunger for pressing flanged glass articles, P (4) 95*f*. Pipe coupling for joining pipe sections of varying size, P (4) 95*b*. Treatment of glass surfaces with polymers of alkali metal vinyl siliconates, P (1) 6*e*.
Oxley, C. E. See Emblem, H. G.
Oxley, G. H., and Cail, D. Method for diverting flow currents in a glass drawing pot, P (10) 255*f*.
Oxley, J. H. See Powell, C. F.
Oxley, J. H., Browning, M. F., Veigel, N. D., and Blocher, J. M., Jr. Microminiaturized fuel elements by vapor-deposition techniques, (4) 100*h*.
Oxydes Francais. Methods of treating nonmagnetic iron ores, P (2) 54*a*. Process for obtaining artificial magnetic oxides from dense liquors, P (2) 49*c*.
Oxymet A. G. Method and device for the production of finely dispersed substances, P (3) 80*e*.
Oya, I. See Tanaka, M.
Oya, T., and Takeuchi, M. Pan-type granulating machine [nodulizer], P (11) 275*g*.
Ozaki, S., and Tatematsu, R. Action of surfactants on pulverized ceramic materials, (5) 133*j*.
Ozark-Mahoning Co. Stannous hexafluorozirconate, P (11) 292*c*.
Ozeryanaya, I. N. See Strekalovskii, V. N.; Volodin, V. P.

Pabst, K. Wear processes of basic refractory brick in the roofs of open-hearth furnaces, (4) 98*a*.
Pace, H. Method of filling electric incandescent lamps, discharge tubes, etc., with gas and of sealing them, P (7) 150*a*.
Pacific Vegetable Oil Corp. Method for making burned clay building products, P (7) 150*i*.
Pack, A. H. See Campbell, W. W.; Leatham, E.; Tvergaard, A. M.
Pack, A. H., Campbell, W. W., and Leatham, E. Production of dead-burned refractory grain in a shaft kiln, P (1) 8*a*.
Packard, R. Q. Moisture stress in unfired ceramic clay bodies, (7) 166*a*.
Packard-Bell Electronics Corp. Electrical capacitor formed from thin films, P (2) 47*c*. Electrical capacitor and methods of forming, P (2) 47*d*.
Paderno, V. N. See Samsonov, G. V.
Paderno, Yu. B. See Samsonov, G. V.; Vainshtein, E. E.
Padfield, R. C. Development of bonded basic roofs for open-hearth furnaces, (7) 151*f*. See Borbas, J. J.
Padfield, R. C., Beechan, C. R., and Thwaite, R. D. Linear change in basic brick under cycled temperatures, (7) 151*h*.
Padoa, L. Defects of red body tile in relation to pressing, (5) 125*f*.
Pagano, M. See Aveline, M.
Paine, B. Porcelain enamel cracks housing market in New York City, (9) 216*f*.
Painter, G. See Born, G. E.
Pajasova, L. See Tauc, J.
Pakalns, P., and Flynn, W. W. Spectrophotometric determination of traces of silicon by an extraction method, (10) 267*i*.
Pakhmura, N. G. See Shishkin, K. N.
Pakhomov, L. G. See Fialkov, A. S.
Palaniappan, R. C. See Aravamudan, V.
Palermo, J. J., Bonazoli, R. P., Scoledge, R. F., and Audesse, E. G. Electric lamp with tubular body and light transmitting closure having overlapping flange seal, P (9) 219*g*.
Palframan, J. F., and Walker, E. A. Techniques in gas chromatography (I) choice of solid supports, (5) 131*g*.
Pal'guev, S. F. See Vorob'ev, G. V.
Palkin, A. P. See Chikanov, N. D.; Palyura, I. P.
Palkina, K. K. See Ioffe, A. V.
Pall, A. Silicate examination by infrared spectroscopy, (11) 289*f*.
Pallen, M. S., and Pogiud, G. T. Method of sintering aluminum nitride refractories, P (2) 44*c*.
Pallinger, J. Method and apparatus for separating suspended particles from gases, P (11) 288*i*.
Palmer, A. L., and Anderson, H. G. Lamp bulb coating apparatus, P (9) 220*c*.
Palmer, R. C., Poirier, V. D., and Blase, E. F. Method of making thermoluminescent manganese-activated calcium fluoride, P (2) 48*j*.
Palmour, H., III. See Choi, D. M.; Davis, M. P.; Kriegel, W. W.
Palmquist, P. V., and Tung, C. F. Sealed beam headlight with glass-beaded light reflecting shield, P (3) 69*d*.
Palyi, L. Pulverizer, P (9) 236*d*.
Palyura, I. P., and Palkin, A. P. System $AlCl_3$-TlCl, (11) 301*e*.

Pampuch, R., and Blaszczak, K. Infrared vibrational spectra of kaolin group minerals, (1) 20*d*.
Pan, Lin-Sen. See Gabrysh, A. F.
Panarin, A. P. See Vydrina, Zh. A.
Panasyuk, A. D. See Kislyi, P. S.; Samsonov, G. V.
Panasyuk, A. D., and Kislyi, P. S. Some features of the sintering of niobium carbide, (10) 258*j*.
Panasyuk, V. I. "Vacuum bubbles" in glass spheres, (8) 176*b*.
Panesh, V. I. See Nasedkin, V. V.
Pangborn Corp. Abrasive blasting wheel assembly, P (2) 33*f*. Metal cleaning, P (9) 217*e*.
Panina, N. S. See Butt, Yu. M.
Pankova, N. A. Typical compositions of bubbles in commercial glasses, (8) 176*a*.
Pankove, J. I. See Tietjen, J. J.
Panov, A. S., Kulikov, I. S., and Taylev, L. M. Effect of calcium sulfides on the surface tension and density of CaO-MgO-SiO_2 melts, (4) 90*i*.
Panteleimonov, L. A., and Nesterova, O. P. Study of melts of the system NiSb-Ni_3Sn_2, (4) 110*h*.
Pantell, R. H. See Kohn, R. L.
Panti, B. N. See Chatterjee, N. B.
Pantoflicek, J. See Hauptmanova, K.
Pao, Yoh-Han. See Robin, M. B.
Paoli, A. de. Continuous sliding bat passage kilns and their use in the ceramic industry, (5) 132*d*.
Paon, O. See Poggi, L. A.
Papa, P. See Alper, A. M.
Papaioannou, P. C., and Harrington, G. W. Specific conductance and density measurements in fused alkali metal nitrate systems (I) solvent systems and binary solutions; (II) conductometric titrations, (8) 207*j*.
Papen, E. L. J. Isostatic pressing, (9) 232*j*.
Paquot, C., Perron, R., and Mathieu, A. Apparatus for recording and regulating temperature during differential thermal analysis, P (8) 188*j*.
Parametrics, Inc. Ultrasonic measurement apparatus, P (8) 188*j*.
Paretzkin, B. See Deslattes, R. D.
Parfenov, A. I. See Shul'ts, M. M.
Parfenov, V. A. See Aleinikov, F. K.
Parikh, N. M. See Holtz, F. C.
Pariseau, W. G. Post-yield mechanics of rock and soil, (8) 205*f*.
Parisot, G. Process for production of hydrofluoric acid from sulfuric acid, fluorspar, and anhydrite, P (4) 107*c*.
Paritskaya, L. N. See Geduzin, Ya. E.
Park, C. D. See Bray, D. T.
Park, R. E., and Sias, C. B. Glass laminate having an unsaturated polyester resin containing silane adhesive interlayer, P (10) 255*f*.
Parke, S. Kramers-Kronig relations and their application to the dielectric properties of glasses, B (2) 61*i*.
Parker, E. R. See Zackay, V. F.
Parker, F., Ltd. Screens, P (1) 13*a*.
Parker, M., and Kever, J. Parts are investment-cast in quantity at less cost, (11) 283*h*.
Parker, R. W. See Gieschen, J. A.
Parker, S. G., Wilson, O. W., and Barbee, B. H. Indium antimonide of high perfection, (9) 239*h*.
Parkerson, C. R. See Wieder, H. H.
Parks, G. A., Jindal, B. K., and Anderson, J. H. Temperature and humidity in electrical separation of oxide minerals, (4) 106*h*.
Parks, V. J. See Durelli, A. J.
Parks, W. J. Vibrating screening apparatus with wedge ring support, P (7) 158*j*.
Parnham, H. Recent advances in steelworks refractories, (7) 152*f*.
Parodi, J. A., Hickok, R. L., Segelken, W. G., and Cooper, J. R. Electronic paramagnetic resonance study of the thermal decomposition of dibasic calcium orthophosphate, (11) 295*b*.
Parot, M. See Cornaz, P.
Parravano, G. See O'Bryan, H. M., Jr.
Parrish, W. Improved slits for X-ray powder diffractometers, (1) 13*h*.
Parslow, G. R. See Barratt, M. S.
Parsons, A. H. See Plaskett, T. S.
Parsons, D. S. Reduction of tungsten oxides by hydrogen, (1) 27*g*.
Parsons, J. M. See Ohlberg, S. M.
Parsons, M. F. Downdraft vertical kiln system, P (2) 52*f*.
Parsons, W. F. See Carnall, E., Jr.
Parthasarathi, M. N., and Agrawal, B. C. Lead in ceramics, (2) 53*j*.
Partington, P. A., and Gould, R. E. Case history of high intensity clay dispersion, B (1) 30*c*.
Partiot, M. Deep combustion radiant elements [design], P (3) 72*g*.
Partridge, G. See McMillan, P. W.
Pascard, R. See Anselin, F.
Paschal, F. Setting brick mechanically—a reality, (1) 6*h*.
Pasechnova, R. A. See Grebenshchikov, R. G.
Pashinkin, A. S. See Buketov, E. A.
Pashley, D. W., and Stowell, M. J. Nucleation and growth of thin films as observed in the electron microscope, (1) 24*f*.
Pask, J. A. (editor). Atomistic Approach to the Nature and Properties of Materials, B (9) 244*c*. See Benecke, M. W.; Borom, M. P.; Copley, S. M.
Pasquale, A. See Pasquale, C.
Pasquale, C., and Pasquale, A. Apparatus for preparing a water asbestos-cement slurry in the desired proportions and delivering the slurry to the utilizing apparatus, P (3) 64*c*.
Passmore, E. M., Duff, R. H., and Vasilos, T. Creep of dense polycrystalline magnesium oxide, (1) 17*f*.
Pasternak, R. A. See Endow, N.
Pastor, A. C. See Pastor, R. C.
Pastor, A. C., Pastor, R. C., and Soffer, B. H. Steady state studies in the conventional verneuil process—the gas-liquid and the liquid-solid interfaces, (8) 207*c*.
Pastor, R. C. See Pastor, A. C.
Pastor, R. C., Kimura, H., and Arita, K. Partition in the growth of solid solution crystals, (8) 204*j*.
Pastor, R. C., and Pastor, A. C. Crystal growth above 2200°C by the verneuil method, (8) 193*b*.
Pastor, R. C., and Tenorio, A. M. Partition of ions in ammonium alum, (8) 204*a*.
Paszyc-Stepkowska, E. Applicability of physicochemical theories to soil mechanics, (1) 16*j*.
Patchen, D. G. Developing suitable X-ray radiography techniques for thin rock slabs, (8) 187*i*.
Patek, K. See Hauptmanova, K.
Patel, C. K. N. See Boyd, G. D.
Patent-Treuhand-Gesellschaft fuer elektrische Gluehlampen m.b.H. Furnace for the manufacture of fused quartz, P (8) 189*c*. Luminescent europium activated strontium aluminate, P (3) 78*c*. Method of producing electric incandescent lamps and lamps produced, P (2) 39*a*. Sintered electrode, P (1) 11*i*.
Paton, A. See Galasso, F. S.
Patschorke, W. O. Glass delivery system, P (11) 278*i*.
Patterson, R. J. Process [gaseous] for preparing boron nitride coatings, P (9) 226*h*.
Patterson, S. H. Bauxite reserves and potential aluminum resources of the world, (8) 189*f*.
Patterson, W. E. See White, C. L.
Patterson-Kelley Co., Inc. Materials feeding and blending, P (11) 288*f*.
Patzak, I., and Konopicky, K. Direct determination of the glass content of aluminosilicates, (3) 71*k*. Studies on tridymite, (5) 138*d*.
Paukste, J. See Deksnys, A.; Mikalkevicius, M.
Paul, A. See Brown, D.; Douglas, R. W.; Nath, P.
Paul, R. A., and Forchheimer, O. L. Refractory material, P (7) 154*a*.
Paulavichius, R. B. See Aleinikov, F. K.
Paulik, F., Paulik, J., and Erdey, L. Sample holders for thermoanalytic examination, P (5) 132*a*.
Paulik, J. See Paulik, F.
Paulitsch, P. Texture effects in ceramics, B (5) 141*j*.
Paulley, D. S., and Lockwood, D. L. Method for manufacturing ceramic substrates for electrical circuits, P (9) 231*f*.
Paulus, M. Properties of grain boundaries in spinel ferrites, B (2) 61*c*.
Pavlov, V. N. See Efimenko, L. N.
Pavlova, G. A. Changes in the electrical properties of glasses in the system MgO-Al_2O_3-SiO_2 during crystallization, B (4) 113*e*.
Pavlova, Z. I. See Kreimer, G. S.; Tumanov, V. I.
Pavlovskii, V. K. See Evstrop'ev, K. K.
Pavlushkin, N. M. See Kitaigorodskii, I. I.
Pavol, M., Jr. See Sawyer, E. W., Jr.
Pawel, R. E., and Campbell, J. J. Electron microscope observations of the crystallization of anodically formed tantalum and niobium oxide films, (7) 163*f*.
Payne, D. A., and Anderson, H. U. Inhibition of grain growth in barium titanate, (10) 262*f*.
Payne, G. See Eason, M. D.
Payrissat, M. See Beucherie, P.
Peacock, J. See Evans, A. W.
Pearson, A. D. Hall effect-Seebeck effect sign anomaly in semiconducting glasses, (3) 66*j*.
Pearson, A. D., Fisher, J. R., and Northover, W. R. Preparation of optical quality glass in small batches, (5) 119*a*.
Pearson, A. D., and Peterson, G. E. Direct observation of sink-terminated concentration quenching of Gd^{3+} fluorescence in calibo-1 glass, (8) 175*h*.
Pearson, A. J., and Duffee, H. W. Reinforced composites and method for producing, P (3) 64*g*.
Pearson, A. J., and Miller, P. R. Reinforced mat construction and method of forming same, P (1) 6*d*.
Pearson, E. F. See Heslop, R. B.
Pearson, G. L. See Allen, J. W.
Peart, L. T. See Strief, M. J.
Peart, R. F., Weiser, K., Woodall, J., and Fern, R. Some effects of Zn diffusion on Mn-doped GaAs, (9) 242*i*.
Peat, A. J. See Westbrook, J. H.
Pech, P. See Massaux, H.
Pechiney-Compagnie de Produits Chimiques et Electrometallurgiques. Method for manufacture of low permeability carbonaceous products, P (1) 7*j*. See Produits Chimiques. . .
Pechini, M. P. Method of preparing lead and alkaline earth titanates and niobates and coating method using the same to form a capacitor, P (10) 264*h*.
Pechkovskii, V. V. See Amirova, S. A.
Pechkovskii, V. V., and Vorob'ev, N. I. Thermochemical transformations of the chlorides of iron, (4) 111*j*.
Pechkovskii, V. V., Vorob'ev, N. I., and Ostrovskaya, T. V. Thermodynamic transformations of the chlorides of nickel and cobalt, (8) 210*j*.
Pechmann, W. Process and apparatus for the continuous polishing of bottles, ampoules, etc., P (3) 69*j*.
Peckham, G. Phonon dispersion relation for magnesium oxide, (7) 166*a*.
Pedersen, B. F. Crystal structure of $AlNbO_4$, (5) 134*j*. Crystal structure of rubidium oxalate monohydrate, $Rb_2C_2O_4 \cdot H_2O$, (8) 193*e*.
Peiffer, H. R. Strength and creep behavior of silver-alumina alloys above the melting point of silver, (4) 110*i*.
Peirce, J. W. Planning for a computer in the ceramics plant, (1) 12*f*.
Pellissier, G. E. See Boggs, W. E.
Pelm Research & Development Corp. Apparatus for cooling metallic and nonmetallic particles, P (5) 132*g*.
Pels Leusden, C. O. See Leusden, C. O. P.
Pemsler, J. P. Kinetics and mechanism of oxide film growth on zirconium, (5) 136*i*. Studies on the oxygen gradients in oxidizing metals (II) hafnium, (7) 168*i*; (III) kinetics of the oxidation of zirconium at high temperatures, (11) 301*h*.
Penberthy, H. L. Glass furnace, P (3) 67*h*. Gob temperature control, P (9) 220*j*. Method of charging and melting a glass batch, P (9) 221*d*. Ultraviolet absorbing green glass, P (10) 256*b*.
Penberthy, L. Discussion of "Economics of container glass melting," (9) 218*b*. Electric melting of glass—1966, (5) 118*i*.
Pence, E. A. See Corwin, R. E.
Pendas, S. de A. See Aza Pendas, S. de.
Pendleton, W. W. See Ostrander, G. W.; Saums, H. L.
Pennebaker, W. B. See Haering, R. R.
Penney, A. W., Jr., and Heynau, H. A. PTM single-pulse selection from a mode-locked Nd^{3+}-glass laser using a bleachable dye, (9) 241*h*.
Pennitalia, S.p.A. Packaging device for flat glass, P (5) 121*d*.
Pennsalt Chemicals Corp. Centrifuge having frustoconical screen with means to improve screen life, P (8) 186*f*. Polymorph of calcium disilicide and its method of preparation, P (8) 190*d*. Tablet press, P (11) 289*b*.
Pentecost, J. L. Dielectric and electronic measurements at high temperatures, B (5) 140*a*.
Penton, H. V., and Kates, P. G. Reflex reflecting article for use as a sign, P (1) 3*c*.
Peplinski, D. M. Purifying device for magnesium production retort, P (7) 154*a*.
Percival, J. See Gerrard, J. E.
Perdue, R. D. See Cohn, M. I.
Perebaskine, C. See Olombel, A.
Pereira, E. See Calvelo, A.
Perel'man, F. M. Phase Diagrams of Multicomponent Systems—Geometric Methods, B (5) 140*h*.
Perera, V. See Berg, P. W.
Peret, J. L. Grinding wheels and stones of oxide bonded $B_{13}P_2$ and method of producing same, P (2) 33*g*.
Peretti, E. A. See Ryan, E. J.
Perez y Jorba, M. See Delamarre, C.; Tolloca, G.
Pergola, G. C. D. See Pritchard, C.
Perino, E. Device for sectioning ceramic tile, facing plates, etc., P (5) 130*c*.
Perio, P. See Belbeoch, B.
Perkins Pipe Linings, Inc. Rate of flow indicator for mortar, P (8) 174*f*.
Perks, A. J., and Simmons, J. H. W. Radiation-induced creep in graphite, (2) 55*g*.
Perkuhn, U. See Vescia, M.
Perli, S. B., and Edel'man, I. E. Cooling of clinker in recuperators of rotary kilns, (9) 214*b*.
Perloff, A. See Robbins, C.
Permaglass, Inc. Apparatus for bending glass sheets, P (3) 67*b*. Apparatus providing a gaseous support bed and method for treating glass thereon, P (10) 254*d*. Conveying apparatus, P (2) 38*b*. Gaseous support bed for conveying and heat-treating glass sheets, P (11) 278*c*. Glass bending furnace with burner blast guide tubes, P (11) 278*h*. Method of and apparatus for heat treating glass sheets on a gas support bed, P (10) 255*a*. Method of and apparatus for manufacturing glass sheets on a gas support bed, P (10) 255*b*. Method and apparatus for uniformly heating sheet material, P (4) 94*g*. Method for edge sealing safety glass, P (1) 5*i*. Press bending apparatus, P (10) 256*b*. Thermally compensated bed for supporting glass sheets, P (1) 6*d*.
Permyakova, T. V., and Lileev, I. S. Production of the silicates of lanthanum, (8) 205*c*.
Perraudin, R., Perrin, C., and Seris, G. Process of manufacturing a silicocalcareous body of high porosity, P (11) 284*a*.
Perri, J. A., and Ruggles, R. L., Jr. Method of covering the surfaces of objects with protective glass jackets and the objects, P (4) 101*c*.
Perrin, C. See Perraudin, R.
Perrin, R. See Lidiard, A. B.
Perron, A. J., and Kowalik, T. J. Sheet metal kiln stilt, P (9) 235*c*.
Perron, R. See Paquot, C.
Perrotta, A. J., and Savage, R. O. Beta eucryptite crystalline solutions involving P^{5+}, (3) 83*h*.
Perry, F. W., Hutchins, G. A., and Cross, L. E. Compositional inhomogeneity of (Ba,Pb)TiO_3 crystals, (10) 270*g*.
Perry, G. S. Review of recent literature on the dielectric properties and sintering of alumina, (9) 229*i*.
Perry, J. T. See Gager, R. M.
Perry, W. M. Burner apparatus, P (9) 234*h*.
Persson, R. Processes and products in the flat glass industry, (5) 119*b*.

Peshekhonova, N. V. See Shul'ts, M. M.
Peshev, P., and Niemyski, T. Preparation of crystalline titanium diboride by a gas-phase reaction, (11) 299*b*.
Peter Spence & Sons, Ltd. Amorphous alumina, P (2) 53*g*.
Peters, E. See Majima, H.
Peters, F. A., Johnson, P. W., Henn, J. J., and Kirby, R. C. Methods for producing alumina from clay—an evaluation of a lime-soda sinter process, (10) 269*f*.
Peters, F. G. Dielectric properties of silicon dioxide and lead tellurium oxide glass films formed by reactive sputtering, (1) 9*g*.
Peters & Russell, Inc. Jet operated toilet, P (10) 261*d*.
Petersen, D. T., and Rexer, J. Composition of ThH_2 and the diffusion of hydrogen in ThH_2, (3) 84*d*.
Peterson, A. Studies on the hydrolysis of metal ions—the uranyl ion, UO_2^{2+}, in Na_2SO_4 medium, (4) 1.0*c*.
Peterson, C. D. Help reduce brick shipment damage, (9) 222*h*.
Peterson, C. H. Suction-type grinding mill, P (8) 190*i*.
Peterson, D. R. Method of forming thin oxide films, P (5) 117*j*.
Peterson, G. E. See Pearson, A. D.
Peterson, M. N. A. Ultrasonic sieving, P (5) 130*f*.
Peterson, O. Investigation of portland cement clinker with the microprobe, (5) 116*g*.
Petley, B. W. See Bussey, H. E.
Petrov, S. V. See Kitaigorodskii, I. I.
Petrova, V. A. See Vasil'kova, I. V.
Petrova, V. Z. Structure and properties of silicate glasses in relation to their crystallization, B (9) 246*e*.
Petrovskii, G. T. Structural peculiarities of fluoroberyllate glasses, B (7) 171*g*. See Evstrop'ev, K. K.
Petrovskii, G. T., Krestnikova, E. N., Grebenshchikova, N. I., and Proskuryakov, M. V. Structural interpretation of the possibility of formation of transparent crystalline glass materials in various systems, B (9) 246*c*.
Petrovskii, G. T., Leko, V. K., and Mazurin, O. V. Electrical conductivity of certain fluoride glasses, B (4) 113*c*.
Pettit, D. G. See Rupprecht, H.
Pettit, F. S. Thermodynamic and electrical investigations on molten antimony sulfide, (8) 210*d*.
Pettit, G. D. See Weller, P. F.
Petzenhauser, I. See Borchert, W.
Pevzner, R. L., and Kharitonov, F. Ya. Resistance of ceramics to water and steam at high temperatures, (3) 74*a*.
Peyser, W. P. Method of making semiconductor devices utilizing vacuum welding, P (5) 128*d*.
Peyssou, J. Special ceramics and their use in electronics and electricity, (9) 230*b*.
Pfau, J. H. See Corson, B. L.
Pfaudler Permutit, Inc. Surface cleaning method and composition, P (1) 3*d*.
Pfeiffer, E. See Frederikse, H. P. R.
Pfizer, Chas., & Co., Inc. See Chas. Pfizer & Co., Inc.
Pflaum, R. T. See Wehking, M. W.
Phaal, C., and Zuidema, G. Transmission electron microscopy of synthetic diamond, (8) 210*f*.
Phair, E. See Bruce, C. F.
Phariseau, P. Electronic structure of disordered materials, (11) 295*c*.
Phelps, G. W. Particle-size analysis—sedimentation methods, (4) 104*c*.
Phelps, G. W., and Dennis, J. S. Casting and plant control of the casting process, B (1) 30*c*.
Phelps, P. L., Jr. See Graham, H. M.
Philadelphia Quartz Co. Formation of solid bodies, P (9) 225*g*. Method of making shell molds, P (3) 72*a*. Nonreflective glass coatings, P (4) 95*g*. Production of refractory objects, P (8) 182*d*. Refractory binder comprising organic silicates, P (10) 260*d*.
Philbrook, W. O. See Spitzer, R. H.
Philco Corp. Glass enclosed passivated semiconductor with contact means of alternate layers of chromium, silver, and chromium, P (3) 78*j*. Method of making a miniature lens, P (2) 39*h*. Semiconductor encapsulating and reinforcing materials utilizing boron nitride. P (2) 49*g*. Solid state thin film triode with a graded energy band gap, P (3) 79*f*.
Philco-Ford Corp. Method of coating semiconductor with tungsten-containing glass and article, P (10) 264*g*. Method of producing gallium phosphide in crystalline form, P (5) 128*h*.
Philippot, J. See Blanchard, R.
Philipps, T. E., and White, J. S. Compatible fibrous glass reinforcements of superior bonding and wetting characteristics, P (7) 149*j*.
Philips Electrical Industries, Ltd. Arrangement for clamping refractory heating elements, P (7) 152*i*. Glass envelopes, P (4) 94*g*. Light diffusing coatings on quartz, P (4) 94*j*. Luminescent materials, P (2) 48*a*. Manufacture of ceramic bodies suitable for piezoelectric uses, P (1) 11*b*. Method of manufacturing semiconductor bodies, P (1) 11*d*. Methods of alloying electrodes to semiconductor bodies, P (2) 48*e*, P (7) 157*j*. Methods and devices for the manufacture of a bar by segregation from a melt, P (2) 50*a*. Methods of manufacturing glass objects, P (2) 39*g*. Methods of manufacturing monocrystalline bodies of semiconductor material, P (4) 102*g*. Methods of manufacturing semiconductor devices, P (1) 11*j*. Methods of manufacturing thallium telluride semiconductor materials, bodies, and devices, P (2) 48*e*. Methods of producing monocrystals, P (2) 48*f*. Methods for reinforcing glass objects, P (7) 150*f*. Methods of strengthening glass objects, P (7) 150*f*. Methods of treating solid material, P (2) 48*f*. Weighing apparatus provided with a magnet system, P (2) 50*c*.
Philips Electronic & Associated Industries, Ltd. Glass cathode ray tubes, P (3) 67*g*. Manufacture of ceramic bodies suitable for piezoelectric uses, P (10) 264*e*. Manufacturing aluminum oxide films, P (10) 264*e*. Manufacturing ceramic articles by sintering, P (5) 130*b*. Methods and devices for sealing together glass parts, P (8) 178*a*. Methods of forming objects of materials having different thermal expansion coefficients, P (10) 250*e*. Methods of joining a metal conductor to a semiconductor body, P (9) 231*e*. Methods of manufacturing aluminum phosphide crystals, P (3) 79*f*. Methods of manufacturing glass bulbs, P (10) 255*j*. Methods of manufacturing objects of quartz glass, P (9) 221*i*. Methods of manufacturing semiconductor devices, P (9) 231*e*. Methods of manufacturing sintered ferrite bodies, P (9) 231*f*. Methods of producing ceramic materials, P (5) 130*c*. Methods of producing monocrystals, P (10) 266*c*. Methods of providing contacts on semiconductor ceramic bodies of *n*-type oxidic material, P (3) 79*g*. Methods of strengthening a glass cathode-ray display tube, P (5) 121*a*. Methods of strengthening glass objects, P (4) 95*e*. Methods of strengthening hollow glass objects, P (3) 69*f*. Methods of treating bodies of semiconductor material, P (8) 185*c*. Nonimplosive glass vacuum vessels, P (7) 150*a*. Photosensitive cells, P (5) 128*e*. Strengthened glass articles, P (10) 256*b*. Treating quartz crystals for optical uses, P (9) 222*e*.
Phillips, B. Materials for use above 3000°F, (10) 257*i*. See Chang, L. L. Y.; Williams, J. A.
Phillips, B., Warshaw, C. M., and Mockrin, I. Equilibria in $KAlF_4$-containing systems, (1) 18*e*.
Phillips, E. D. Stressed plastic valve for laboratory glassware, P (5) 121*g*. Stressed [Teflon] valve, P (9) 222*e*.
Phillips, G. See Milner, G. W. C.
Phillips, R. M. See Blau, R.
Phillips, S. V. See McMillan, P. W.
Phillips, V. A. Electron microscopy, B (8) 211*j*.
Phillips, W. L. Some observations on the high-temperature oxidation of lanthanum, (7) 167*g*.
Phillips Petroleum Co. Process and apparatus for heating particulate solids in a rotary kiln, P (11) 290*g*.
Philpott, M. R. Exciton-photon coupling in molecular crystals, (1) 18*h*.
Phoenix, R. C. Rheological properties of clay slips, B (1) 30*b*.
Physical Sciences Corp. Ceramic material, P (5) 120*c*. High temperature electrical insulating material, P (1) 10*j*.
Physics International Co. Core element [graphite] for a breeder nuclear reactor, P (9) 225*d*.
Pialoux, A., and Dode, M. High temperature X-ray study in a controlled atmosphere of the system uranium–oxygen, (1) 19*c*.
Pickard, W. F. Electric force effects in dielectric liquids, B (11) 305*f*.
Pickering, S. T. Method and apparatus for the pressure molding of articles, P (1) 5*f*.
Picus, G. S. See Braunstein, A. I.
Pieczonka, W. A. See Castrucci, P. P.
Piedmont, J. R. See Hemmer, F. J.
Piel, T. F. See Fraser, G. L.
Piepany, R. A. See Tavernelli, J. F.
Pierce, G. R. See Seward, T. P., III.
Pierini, G., Francesconi, A., and Schmets, J. Process for the reprocessing of irradiated compact fuels by fluorination, P (11) 282*i*.
Pierson, R. M. Semiconductor crystal growth from a domical projection, P (3) 79*d*.
Pieterse, J. J., and Schmidt, E. R. Relation between compressive strength and modulus of rupture of fired clay products, (2) 40*f*.
Pietsch, T. Method of manufacturing kiln treated articles, P (7) 150*d*.
Pilkington, D. F. Apparatus for the continuous production of flat glass with dual feeding means, P (11) 277*g*.
Pilkington Brothers, Ltd. Apparatus for annealing glass, P (3) 67*a*. Apparatus for the continuous production of flat glass with dual feeding means, P (11) 277*g*. Apparatus for molding glass articles, P (5) 119*i*. Apparatus for vertically drawing glass in sheet form from a body of molten glass, P (1) 4*f*. Manufacture of flat glass, P (3) 68*d*. Manufacture of glass, P (2) 39*a*. Manufacture of lead glasses, P (9) 220*d*. Manufacture of wired glass, P (3) 68*d*, P (5) 120*g*. Method of and apparatus for the manufacture of flat glass on a molten metal bath, P (8) 177*c*. Method and apparatus for the pressure molding of articles, P (1) 5*f*. Method and apparatus for purifying the molten bath of a glass sheet forming operation, P (11) 278*j*. Method and apparatus for reinforcing glass, P (8) 177*g*. Method for diverting flow currents in a glass drawing pot, P (10) 255*f*. Method of manufacture of flat glass on molten tin, P (5) 121*e*. Method of manufacture of flat glass with reducing atmosphere, P (11) 279*d*. Method of manufacturing flat glass of different thicknesses, P (5) 121*d*. Method of removing impurities in a molten metal bath for glass sheet making, P (10) 255*i*. Methods and apparatus for producing toughened glass, P (3) 69*e*. Methods for mixing finely divided materials, P (5) 121*a*. Mold with vacuum transfer apparatus, P (4) 95*f*. Process of manufacturing flat glass on a molten metal bath, P (11) 279*i*. Television tube assemblies, methods of forming such assemblies, and implosion guards therefor, P (7) 150*f*.
Pilloton, R. L., and Hamner, R. L. Preparation of actinide metal carbide microspheres, P (4) 98*i*.
Pilsetnieks, D. Apparatus for use in handling ferrite cores, P (3) 77*c*.
Pilstrom, G. Crystal structure of Ni_5Si_2 with some notes on Ni_3Si_2, (3) 84*b*.
Piltch, M., and Gould, G. High temperature alumina discharge tube for pulsed metal vapor lasers, (1) 9*j*.
Pinaev, G. F. Metric properties of barycentric phase diagrams, (11) 298*g*. Transformation of the index of barycentricity of phase diagrams of multicomponent systems, (11) 302*h*.
Pinaeva-Strelina, M. M. See Krylov, E. I.
Pinchin, F. J. See Bond, R. L.
Pines, B. Ya. Recent Soviet work on the dielectric properties and sintering of alumina, (9) 229*i*.
Pinkham, R. M., and Tribble, R. M. Heat sealing glass to the surface of a body, P (2) 38*h*.
Pinter, H. J. Composite titanium boride bars, P (11) 281*a*.
Pirelli, S.p.A. See Montecatini Societa Generale per l'Industria Mineraria e Chimica.
Piriou, B. Study of light rays from magnesia and corundum—effect of temperature, (2) 56*d*.
Pirkle, R. O. See Besore, C. D.
Pirogov, A. A., Leve, E. N., et al. Testing carbon blocks in the iron gutter of a blast furnace, (7) 152*d*.
Pirogov, A. A., Rakina, V. P., and Volkov, N. V. Unfired dolomite refractories with high hydration resistance, (5) 123*j*.
Pirogov, Y. A., Brown, R. M., and Friedberg, A. L. Electrical properties of Al_2O_3-nickel metal multilayer flame-sprayed coatings, (1) 2*h*.
Pirooz, P. P. See Ware, R. K.
Pirotskii, V. Z. See Royak, S. M.
Pisarevskii, A. M. See Belyustin, A. A.
Pischtiak, G. Surface roughness of ceramics, (9) 228*c*.
Pisters, H. Chromium in cement and chromate eczema, (5) 116*c*.
Pitak, N. V. See Strelets, V. M.
Pitha, J. J. Nonlinear resistance material, P (3) 75*c*.
Pither, L. F. Molded semivitreous article and method of making same, P (8) 178*b*.
Pitirimov, B. Z. See Vasil'kova, I. V.
Pitro, V. See Schill, F.
Pitt, C. H. See Huggins, H. W.
Pittman, G. E. See Biard, J. R.
Pittsburgh Corning Corp. Continuous method of making a glass sheet, P (4) 94*b*. Method of making a multicellular vitreous sheet on a molten metal bath, P (2) 39*j*.
Pittsburgh Plate Glass Co. Annealing of glass, P (4) 93*f*. Apparatus for maintaining optimum speed of cutting shears when glass gob sizes are varied, P (10) 254*a*. Apparatus for positioning glass plates during laminating, P (1) 4*d*. Apparatus for producing glass fibers, P (2) 38*i*. Apparatus for producing sheet glass, P (4) 93*g*. Apparatus for tempering bent glass sheets, P (3) 67*h*. Assemblies of glass sheets, P (4) 93*h*. Bending mold for glass sheets, P (1) 4*f*. Bonded glass fiber product and process of preparing same, P (11) 278*a*. Bronze-smoke ophthalmic glass composition, P (4) 93*j*. Bronze-smoke segment glass, P (3) 67*j*. Bushing assembly for forming glass fibers, P (10) 254*g*. Dispersion process, P (11) 288*h*. Fiber glass mat, P (11) 278*c*. Glass cutting apparatus, P (3) 67*g*. Glass drawing kiln L-block, P (5) 120*j*. Glass laminate having an unsaturated polyester resin containing silane adhesive interlayer, P (10) 255*f*. Glass sheet bending mold, P (9) 220*g*. Glass sheet bending mold with pivoted end sections, P (2) 38*h*. Glass sheet tempering apparatus, P (3) 67*j*. Manufacture of glass, P (2) 38*j*. Manufacture of glass sheets on a plurality of different fluid supports, P (11) 278*g*. Manufacture of multiple glazing units, P (1) 5*j*. Method of annealing sheets of glass on a decreasing temperature gas support, P (10) 255*i*. Method of and apparatus for bending glass sheets, P (5) 120*h*. Method and apparatus for bending and tempering glass sheets, P (4) 94*d*. Method and apparatus for bending and tempering glass sheets vertically supported with fluid pressure, P (11) 278*h*. Method and apparatus for conveying and heating glass on a fluid support bed, P (4) 94*e*. Method of and apparatus for feeding a substantially untwisted multifilament strand, P (3) 68*f*. Method and apparatus for generating currents in molten glass, P (5) 120*j*. Method and apparatus for improving homogeneity of viscous liquids, P (10) 255*a*. Method and apparatus for press bending glass sheets, P (3) 68*i*, P (8) 177*f*. Method of and apparatus for shaping glass sheets with opposed pressing members, P (10) 255*d*. Method and apparatus for tempering glass sheets on a gas support bed, P (3) 68*a*. Method of bending and annealing glass sheets, P (8) 177*g*. Method of forming glass fibers, P (2) 39*g*. Method of heating glass sheets, P (3) 68*d*. Method of laminating transparent assemblies, P (7) 150*b*. Method of manufacturing flat glass on a bilevel forming surface, P (8) 178*f*. Method of mixing glass batch, P (3) 68*i*. Method of press bending vertically supported glass sheets, P (4) 95*d*

Method for producing fibers, P (2) 39*b*. Method for producing nonglare, low specular reflecting films on glass articles, P (9) 221*e*. Method for the production of glass fibers, P (4) 95*d*. Method of strengthening glass by ion exchange and articles therefrom, P (2) 39*c*. Method of supporting a thermoplastic sheet with gas, P (11) 279*g*. Method for treating a material in a solution, P (3) 69*c*. Neutral brown heat absorbing glass composition, P (4) 95*f*. Nuclear radiation shielding window, P (2) 39*h*. Phototropic glass and method, P (1) 6*b*. Pivoted glass sheet bending mold, P (1) 6*c*. Preparation of dense chromic oxide, P (1) 16*a*. Press bending mold with heat reflective surface, P (9) 222*c*. Process of annealing glass sheets, P (7) 150*b*. Process for finishing float glass, P (2) 40*a*. Process of making fibrous product, P (8) 178*h*. Process for removing float glass carryover on steel rolls, P (11) 279*b*. Traction rolls and material handling apparatus employing such rolls, P (8) 179*c*. Transverse heat absorption from a drawn glass sheet subsequent to roll forming, P (2) 69*h*.

Pivnik, L. Ya. See Kaibicheva, M. N.

Piwkowski, T. R. See Wolsky, S. P.

Piwonka, T. S., and Flemings, M. C. Pore formation in solidification, (7) 166*h*.

Pixley, G., and Mohler, N. Profit concept in brick plant design, (1) 6*j*.

Pixley, G. W. Apparatus for cooling metallic and nonmetallic particles, P (5) 132*g*.

Pizzarello, F. A. Method for the preparation of gallium phosphide, P (5) 128*f*. Method for preparing a gallium arsenide diode, P (5) 128*g*.

Place, D. E. Temperature sensing probe with means for maintaining the tubular element in engagement with a ceramic rod member, P (7) 159*i*.

Plaskett, T. S., and Parsons, A. H. Detection of striae in GaAs by chemical etching, (11) 284*i*.

Platt, R. O. See O'Donnell, J. M.

Plaul, T. Development, measurement, and interpretation of electrical potential gradients in drying clays, (2) 53*g*. Technology of Heavy Clayware (Vol. I) Raw Materials, Preparation, and Forming, B (5) 142*c*; (Vol. VI) Production and Testing, B (5) 142*g*.

Pleasants, J. Conveyor, P (5) 130*d*.

Plessey Co., Ltd. High temperature flame spraying of ceramic material, P (7) 147*j*. Magnetic cores for information storage and methods of making them, P (5) 127*i*. Method of producing high density silicon nitride, P (3) 72*b*. Production of ceramic materials, P (1) 13*c*. Reinforced refractory bodies, P (1) 8*g*. Sealing of high-purity alumina to metal, P (3) 79*d*.

Pletenetskii, G. E. See Ivanov, V. I.

Pliskin, W. A. Comminution of glass, P (8) 176*i*.

Pliskin, W. A., and Gnall, R. P. Evidence for oxidation growth at the oxide-silicon interface from controlled etch studies, (3) 85*h*.

Plowman, J. Mortar mixes and load-bearing brickwork, (9) 223*b*.

Plumat, E. Apparatus and process for refining glass and for continuously manufacturing sheet glass, P (9) 219*h*. Formation of pseudovitreous and pseudocrystalline systems (I, II), (11) 276*h*. Process and apparatus for the manufacture of flat glass on a molten metal bath, P (5) 121*e*, P (8) 178*g*. Process and arrangement for heating glass sheets with a view to subsequent thermal treatment, P (9) 222*d*. Protective salt bath for a glass ribbon, P (4) 95*f*. See Brichard, E.

Plumat, E., and Jaupain, M. Gray glass composition, P (4) 94*i*.

Plumbo, R., and Wasser, R. E. Method of making an integrated circuit package, P (7) 157*e*.

Plummer, W. A. See Fontana, E. H.

Plyushchev, V. E. See Samuseva, R. G.

Plyushchev, V. E., and Samuseva, R. G. Double systems of the bromides of cesium and the bromides of lithium, potassium, and rubidium, (11) 293*f*.

Pobst, D. F., Jr., and Rowlett, B. J. Process for forming aggregates of powdered materials, P (5) 130*d*.

Poch, W. Anion chain-length distribution in high pressure modifications of Na phosphate glasses in dependence on the pressing temperature, (10) 250*j*.

Pocza, J. F. See Barna, A.

Podesva, S. See Rais, J.

Podolsky, L. Thermoelectric elements of oriented graphite containing spaced bands of metal atoms, P (10) 265*h*.

Podschus, E. Process for the production of finely dispersed calcium silicate fillers, P (8) 190*f*. See Heinze, G.

Podschus, E., and Joseph, W. Calcined pigments from kaolin, P (7) 160*j*.

Podushko, E. V. See Alekseev, A. G.

Poellet, A. L., and Barczak, V. J. Ceramic sealing structure, P (3) 77*e*.

Poenisch, A. P. See Kay, E.

Poeschmann, H. See Effenberg, A.

Poggi, L. A., Facincani, E., and Paon, O., Installation for drying and firing brick, P (5) 132*f*.

Poglud, G. T. See Pallen, M. S.

Pogson, E. H. See Fitzgerald, A. G.

Pohl, E. Nondestructive testing in building practice, (2) 50*h*.

Pohl, H. A. See Rembaum, A.

Point, M. A. R. Electrostatic coating process and apparatus, P (9) 233*c*.

Poirier, V. D. See Palmer, R. C.

Polak, A. F., Karlova, L. G., and Kurbanovskaya, O. G. Formation of seeds of new phase in the hardening of monomineral binders, (10) 248*g*.

Polak, A. F., and Mendel'son, V. M. Mechanism of dissolution of binders, (7) 165*j*.

Polaroid Corp. Incandescent lamp with TaC filament and cyanide-radical producing and halogen atmosphere, P (1) 11*a*.

Polezhaev, Yu. Y. Effect of nonequilibrium evaporation and dissociation of vapors on the mass transport parameters of heatproof glassy materials, (8) 195*e*.

Polin, F. See Amato, I.

Polinsky, M. A. Semiconductive device fabrication, P (11) 287*c*.

Polishchuk, P. A. Electrical conductivity of oxyfluoride melts of potassium, zirconium, and boron, (8) 196*e*. Oxide-fluoride systems of potassium, zirconium, and boron, (8) 204*f*.

Polito, W. J. See Rozgonyi, G. A.

Pollak, P. I. See Barkemeyer, H. R.; McAleer, W. J.; Rosenberg, R.

Pollitz, H. C. Gas hydraulic spring for crushing apparatus, P (8) 190*c*.

Pollock, L. J. See Husher, J. D.

Polska Akademia Nauk Instytut Badan Jadrowych. Method of and apparatus for grinding hard materials, P (2) 54*d*.

Poluboyarinov, D. N. See Duderov, I. G.; Guzman, I. Ya.; Lukin, E. S.; Vlasov, A. S.

Poluboyarinov, D. N., Kalliga, G. P., and Lyutsareva, L. A. Stabilization and sintering of zirconia of high purity, (5) 123*e*.

Polucci, A. J. Digital ultrasonic delay line, P (4) 101*a*.

Polukhin, V. N. Specific and molecular refractivity of silicate and borosilicate glasses containing oxides of the rare elements, B (7) 171*h*.

Polyachenok, O. G. See Novikov, G. I.

Polyachenok, O. G., and Novikov, G. I. System $ScCl_3$–Sc, (1) 20*h*. Systems $SmCl_3$–Sm and YCl_3–Y, (1) 29*i*.

Polycarbide Corp. High temperature resistant member and process for forming, P (2) 44*g*.

Polysius G.b.m.H. Device for the continuous pneumatic feeding of powdered or granular material, P (7) 158*i*. Kilning of cement, P (7) 147*e*. Method of and apparatus for grinding moist material, P (3) 80*d*. Method and apparatus for increasing the entrainment of pulverous material in a carrier gas utilizing pressure shocks, P (8) 186*i*. Method of and apparatus for recovering substances with a high alkali percentage from the flue gases of cement kilns, P (2) 35*b*. Method of and arrangement for increasing the alkali content in alkali-laden dusts of flue gases, P (8) 174*c*. Method of recovering the content of alkali metal compounds from alkali-rich dust obtained when producing cement clinker and apparatus therefor, P (9) 215*i*. Method of removing the alkalis from the flue gas emanating from a cement kiln and cement kilning plant therefor, P (9) 215*i*. Rotary shaft coolers and crushers, P (3) 83*e*.

Ponomarev, I. F. Spherulites with periodic glass crystallization, B (9) 246*e*.

Ponomarev, I. F., Grach'yan, A. N., and Gaidzhurov, P. P. Effect of different gas atmosphere during firing on the clinker properties of white cement, (10) 248*c*.

Ponomarev, I. F., Grach'yan, A. N., and Zubekhin, A. P. Effect of mineralizers on the clinker-formation process, (9) 214*g*.

Ponomareva, V. N. See Morozova, M. P.

Ponzani, D. See Limes, R. W.

Poole, J. P., Snyder, H. C., and Ryder, R. J. Corrosion retarding fluorine treatment of glass surfaces, P (8) 176*j*.

Poole, K. R. Characterization of powders to indicate mixing properties, B (7) 169*j*.

Pootmans, J. D. Pigment grinding mill, P (10) 266*f*.

Popova, N. M. See Gladyshevskii, E. I.

Popovics, S. Use of the fineness modulus for the grading evaluation of aggregates for concrete, (9) 215*d*.

Popper, P., and Astbury, N. F. Electrode-dielectric interactions at high temperature, (2) 47*a*.

Porai-Koshits, E. A. Crystal-chemical aspects of the structure of inorganic glasses, B (7) 171*e*. Some Results of the Symposium on Catalyzed Crystallization of Glass, B (9) 246*b*. Structure of glass and initial stages in the formation of glass-ceramics, B (5) 141*g*. (editor) Structure of Glass (Vol. VI) Properties, Structure, and Physical-Chemical Effects, B (7) 171*a*; (Vol. VII) Methods of Studying the Structure of Glass, B (9) 245*j*. See Andreev, N. S.; Aver'yanov, V. I.; Goganov, D. A.; Rudenko, V. S.; Toropov, N. A.

Porai-Koshits, E. A., Goganov, D. A., and Aver'yanov, V. I. Study of the supermolecular structure of silicate glasses by direct methods, B (2) 61*g*.

Porter, C. A., and Schreiner, W. A. Method and apparatus for manufacturing pipettes, P (7) 149*j*.

Porter, E. H. Method of making isolated epitaxial field-effect device, P (3) 78*j*.

Porteus, C. See Broderick, R. L.

Portland-Zementwerke Heidelberg Akt.-Ges. Processes for the burning of materials in industrial processes, P (5) 117*b*.

Porto, S. P. S. See Ballman, A. A.

Poschenrieder, W. P. See Barrington, A. E.

Posey, B., Jr., and Varnado, T. E., Jr. Process for removing iron from phosphoric acid, P (7) 148*a*.

Posner, A. M. See Edwards, D. G.

Potemkin, P. S., Shumilin, A. A., et al. Firing Dankovsk dolomites in a rotary kiln, (9) 224*d*.

Potemkin, P. S., Shumilin, A. A., Shalkov, K. A., and Yakovlev, A. I. Combined grinding and drying of refractory clays in a shaft mill, (5) 122*j*.

Potocnik, K., and Simon, G. Heating chamber walls, particularly the backwalls of furnaces, such as Siemens-Martin furnaces, P (8) 189*a*.

Potter, C. C. Direct current plasma—a new spheroidizing process, (9) 234*g*.

Potter, J. F. See MacChesney, J. B.

Potter, P. E. Volatility of plutonium carbides, (8) 211*h*.

Potter, R. A. See Leitten, C. F., Jr.

Potters Brothers, Inc. Method and apparatus for forming glass beads, P (1) 5*d*.

Potuzak, V., and Chour, Z. Obtaining feldspars from granitic rocks, (10) 269*h*.

Pouchard, M. See Hagenmuller, P.

Poulos, N. E. See Harris, J. N.

Poulsen, R. G. See Westwood, W. D.

Powder Melting Corp. Means for preventing flashback in powder melting torches, P (1) 3*d*.

Powell, C. F., Oxley, J. H., and Blocher, J. M., Jr. (editors). Vapor Deposition, B (2) 62*f*.

Powell, C. G. See Myers, R. A.

Powell, D. E. See Minneman, L. C.

Powell, D. E., and Spear, B. W. Cathode-ray and other vacuumized tubes resistant to fracture and capable of controlled evacuation, P (10) 254*h*.

Powell, H. W., Meyer, R. A., and Bourdeau, R. G. Control of radiation effects in a graphite reactor structure, (3) 70*h*.

Powell, R. L. See Lyons, L. R.

Powell, R. W., Ho, C. Y., and Liley, P. E. Thermal conductivity of selected materials, B (8) 212*h*.

Powers, M. C. Fluid-release mechanisms in compacting marine mudrocks and their importance in oil exploration, (11) 290*j*.

Powers, R. A., Louzos, D. V., and Darland, W. G., Jr. Inert electrodes for electrochemical devices, P (7) 147*j*.

Powers, W. H. Ceramic coated muffler with drainage openings, P (7) 147*k*. See Dodge, N. B.; Hubble, D. H.; Kappmeyer, K. K.

Pozubenkov, A. F., and Florinskaya, V. A. Relation between the structure and properties of sodium silicate glasses, B (9) 245*e*.

Prabhakaram, P. Consideration of surface area and crystallinity of kaolinite as factors in its base exchange capacity, (11) 292*j*.

Prager, H. J. See Chang, K. K. N.

Pranckevicius, G. A., Jurenas, V., Dauknys, V., Juodis, A., and Majauskas, J. Thermal resistance of refractory materials (I) apparatus for the investigation of thermal resistance at high temperatures, (2) 43*e*.

Prasad, G. E. See Moorthy, V. K.

Prasad, J. See Bishui, B. M.

Prasad, S. N. See Gupta, S. K.; Nayak, U. N.; Ram, A.

Prasad, T. V. See Sahota, N. S.

Pratt, P. L., Roy, C., and Evans, A. G. Role of grain boundaries in the plastic deformation of calcium fluoride, B (2) 61*e*.

Precht, W. Thermoelectric converter composition, P (3) 79*h*.

Precision Metalsmiths, Inc. Method of removing patterns from investment molds, P (11) 282*g*.

Preece, K. N. See Kaines, C. J.

Prekast Fireplace Mfg. Co. Precast fireplace, methods of manufacture and erection, P (4) 98*i*.

Prener, J. S., and Kingsley, J. D. Semiconductor material and method of making, P (5) 129*d*.

Prenton Brick & Tile Co., Ltd. Drop arches for kilns, P (1) 14*i*.

Prenton Brick & Tile Co., Ltd., and Sharples, A. G. Roof construction for kilns, P (5) 132*h*.

Prerovske Strojirny Narodni Podnik. Installation for sampling homogeneous raw materials, P (5) 130*g*. Process for preheating fragments or granular materials and apparatus therefor, P (7) 158*i*.

Presnov, V. A., and Krasil'nikova, L. M. Thermal analysis of silicate glasses in the system Na_2O-SiO_2, B (7) 171*c*.

Pres-on Abrasives, Inc. Abrasive belt, P (10) 247*f*.

Presser, H. See Falkenthal, A.

Preston, B. W. Optical method for the inspection of a transparent object for defects including comparing light energy at two stations, P (9) 221*i*.

Preston, J. A. Refractory mold, P (5) 125*b*.

Preuss, L. E., Toothacker, W. S., and Bugenis, C. K. Demonstration of X-ray diffraction by LiF using the Mn $K\alpha$ X rays resulting from ^{55}Fe decay, (9) 237*j*.

Preziosi, L. M., and Zecca, J. J. Method of manufacturing double-ended electric lamps, P (4) 95*c*.

Pribil, R., and Vesely, V. Determination of iron, aluminum, magnesium, calcium, titanium, and manganese in iron ores and slags, (5) 130*h*. Determination of magnesium (and calcium) in calcareous materials and silicates, (5) 130*i*.

Price, A. M. See Kelly, B. T.

Price, F. P. Nucleation and condensation in polymer systems, B (9) 245*f*.

Price, M. S. T. See Bentolila, J.

Price, P. B., and Walker, R. M. Molecular sieves and methods for producing same, P (5) 133*c*.

Price, R. J. See Bokros, J. C.

Prickett, R. L. Ultra-high temperature single-crystal texture camera diffractometer, B (5) 139*h*.

Prickett, R. L., and Hough, R. L. Generation of a two-dimensional silicon carbide lattice, B (5) 139*f*.

Prijn, C. Method of providing tubular lamps, P (9) 221*h*.
Prikhodchenko, N. A. See Budnikov, P. P.
Prins, J. A. Structure of noncrystalline solids, B (2) 61*e*. (editor) Physics of Non-Crystalline Solids—Proceedings of an International Conference Held under the Auspices of the International Union of Pure and Applied Physics, Delft, July, 1964, B (2) 61*i*.
Prins, K., and Dunfee, H. Centrifugal type separator, P (2) 53*j*.
Prior, W. L. Inorganic plastic cements and the preparation thereof, P (8) 174*b*.
Prislan, G. Angular jets in conditioning chamber of a glass sheet drawing apparatus, P (8) 176*c*. Drawing chamber for the continuous manufacture of sheet glass, P (4) 94*c*.
Prismo Safety Corp. Colored reflective coating composition, P (2) 38*b*. Marking materials, P (2) 39*a*. Reflectorized marking material and method of making same, P (1) 6*c*. Reflectorizing glass spheres and method of making them, P (3) 69*c*.
Pritchard, C., and Pergola, G. C. D. Contacting of *pn* junctions, P (4) 100*i*.
Pritchard, W. C. Method of stabilizing plutonium dioxide, P (10) 259*i*.
Pritchard, W. L., Schumann, C. E., and Gruber, C. W. Selection of adhesive-coated materials for particulate sampling, (11) 289*e*.
Prival, K. B. Method for making electrical components, P (9) 231*f*.
Probst, R. Torsional studies of refractory materials, (3) 71*i*.
Procter, J. P., Cole, H., and Yale, B. Manufacture of glass, P (2) 39*a*.
Proctor, B. A. See Morley, J. G.
Proctor, B. A., Whitney, I., and Johnson, J. W. Strength of fused silica, (9) 218*a*.
Produits Chimiques Pechiney-Saint-Gobain. Preparation of powdered ferrites, P (11) 287*c*. See Pechiney.
Proebstle, R. A. See Lang, J. E.
Prokin, A. I., and Dylgerov, V. D. Domain structure of magnesium-manganese ferrite single crystals, (1) 18*c*.
Prokopovich, N. P., and Nishi, C. K. Methodology of mechanical analysis of subaqueous sediments, (8) 187*d*.
Pronkin, A. A. See Myuller, R. L.
Proskuryakov, M. V. See Petrovskii, G. T.
Protti, A. M. See Amato, I.
Proudfoot, E. A. See Lockyer, G. E.
Prout, E. G., and Moore, D. J. Thermal decomposition of gamma-irradiated barium azide, B (9) 244*d*. Thermal decomposition of irradiated mercuric oxalate, B (9) 244*c*.
Prout, W. E. See Russell, E. R.
Provance, J. D., and Wood, D. C. Molybdenum phosphate glasses containing Ag_2O or K_2O, (11) 277*d*.
Pruden, L. H., Korda, E. J., and Williams, J. P. Characterization of surface topography with the scanning electron microscope, (9) 233*j*.
Pryor, R. C. Process and apparatus for heating particulate solids in a rotary kiln, P (11) 290*g*.
Przirembel, H. See Krause, I.
Przybylek, A. See Tokarski, Z.
Przybylski, B. See Werner, H.
Ptacek, J. Winning of refractory raw materials, (2) 53*g*.
Ptasienski, M. P. See Maynard, E.
Pucher, S. Volumetric determination of potassium in cement analysis with polarization current titration, (1) 2*b*.
Pugh, E. N. See Westwood, A. R. C.
Pugh, H., and Gauterin, G. Thermocouples, P (8) 188*h*.
Pugh, S. F. Fracture of brittle materials, (7) 163*h*.
Pulliam, G. R. Chemical vapor growth of single-crystal magnetic oxide films, (8) 183*d*.
Pullman, Inc. Clay calcining process, P (8) 190*d*. Radioactive materials of low surface area, P (5) 128*j*. Roller hearth tunnel kilns, P (10) 268*j*.
Pultz, W. W. Manufacture of silica-sheathed silicon carbide fibers and the product thereof, P (10) 259*d*. Oxidation of submicroscopic fibrous silicon carbide, (9) 241*a*. See Hertl, W.
Pultz, W. W., and Hertl, W. Oxidation kinetics of particulate silicon monoxide, (5) 137*e*.
Pundsack, F. L. Recovery of silica, iron oxide, and magnesium carbonate from the treatment of serpentine with ammonium bisulfate, P (11) 292*d*.
Pustil'nik, A. I. See Nisel'son, L. A.
Putsch, H., & Comp. Glass pressing machine, P (11) 278*c*. Motion transmitting means for glass feeder plunger, P (8) 178*c*.
P'yachev, V. A. Strength of ash-portland cement as a function of mineralogical composition of clinker, (9) 215*b*.
P'yachev, V. A., and P'yacheva, G. E. Behavior of alkali as a function of firing conditions and charge composition, (10) 247*j*.
P'yacheva, G. E. See P'yachev, V. A.

Quaas, J. F. Flux-coated carbide welding rod, P (10) 250*c*. Method for producing carbide containing materials, P (5) 115*f*.
Quaas, J. F., and Broderick, J. P. Alloy powder for flame spraying, P (11) 276*d*.
Quaker Oats Co. Method for cold molding pitch bonded shaped carbon bodies, P (3) 72*j*.
Quang, B. T. See Res, M.
Quartz & Silice S. A. Ferroelectric ceramic composition and its applications, P (11) 285*c*.
Quast, H. See Hund, F.
Quate, C. F. See Caddes, D. E.
Quebec, Ministere des Richesses Naturelles. Production of zeolites and lithium salts, P (7) 161*c*.
Quentin, R. J., and Boone, F. H. X-rays measure glass minor ingredients, (1) 4*a*.
Quershi, M., and Varshney, K. G. Selective determination of iron by potassium cyanide-potassium ferrocyanide reagent, (10) 267*g*.
Queyroux, F. Systems formed by lime with the oxides of type C rare-earth elements, (2) 57*a*.
Quigley Co., Inc. Furnace repair gun, P (10) 250*j*.
Quinn, C. M., and Roberts, M. W. Photoelectric investigation of the nickel + oxygen system, (7) 166*a*.
Quinn, P. D., Waitkins, G. R., and Depew, H. A. Production of silica lamellas, P (9) 236*c*.
Quinn, R. G. Friction material, P(5) 124*g*.
Quinn, T. J. Calculation of emissivity of cylindrical cavities giving near blackbody radiation, (11) 289*d*.
Quirk, J. P. See Edwards, D. G.; Greenland, D. J.

Raask, E., and Jessop, R. Miscibility gap in the potassium sulfate-potassium silicate system at 1300°C, (7) 165*h*.
Rabatin, J. G., and Gillooly, G. R. Vapor transport reactions related to halophosphate phosphor formation, (10) 263*a*.
Rabinowicz, E. Effect of surface energy on lubrication, B (8) 212*i*.
Racal Electronics, Ltd. Crystal ovens, P (2) 52*f*.
Rachor, A. Process and apparatus for mixing and distributing bulk products or different materials, P (11) 289*b*.
Rachor, L., and Lotz, H. Fuel material for nuclear reactors and process and apparatus for its manufacture, P (2) 44*c*.
Radczewski, O. E., and Schaedel, J. Ultramicrotome sections of kaolin—the metakaolinite problem, (5) 139*a*.
Radiation, Ltd. Gaseous fuel burners, P (3) 82*c*.
Radio Corp. of America. Art of making color-phosphor mosaic screens, P (1) 10*f*. Ceramic-to-metal seals, P (2) 47*j*. Color cathode ray tube with radiation-emitting index stripes, P (1) 10*j*. Field effect solid state device having a partially insulated electrode, P (5) 127*d*. Germanium-silicon thermoelement having fused tungsten contact, P (11) 285*f*. Group III-V compound transistor, P (9) 230*j*. Heater for electron tubes, P (9) 231*a*. Insulated gate field-effect semiconductor device, P (5) 127*h*. Low temperature synthesis of compound semiconductors, P (7) 156*h*. Luminescent screens utilizing nonluminescent separator layers, P (3) 78*c*. Magnetic body, P (10) 264*a*. Method of depositing epitaxial layers of gallium arsenide, P (7) 157*d*. Method of etching to dice a semiconductor slice, P (2) 48*f*. Method of fabricating a semiconductor device, P (2) 48*g*. Method of fabricating a semiconductor by masking, P (4) 101*e*. Method of isolating chips of a wafer of semiconductor material, P (10) 264*i*. Method of making a composite insulator semiconductor wafer, P (3) 78*i*, P (4) 101*h*. Method of making luminescent screens, P (2) 48*j*. Method of making magnetic material with pattern of embedded nonmagnetic material, P (10) 264*j*. Method of making phosphor screens, P (8) 185*g*. Method of manufacturing semiconductor devices, P (10) 264*f*. Method and materials for metallizing ceramics, P (3) 79*b*. Method of metallizing luminescent screens, P (8) 185*j*. Photoconductive device incorporating stabilizing layers on the face of the selenium layer, P (7) 157*d*. Planar *pn* junction light source with reflector means to collimate the emitted light, P (3) 79*i*. Process for preparing lanthanum, yttrium, or lutetium phosphate phosphors, P (9) 232*b*. Reciprocal latched ferrite phase shifter, P (11) 287*a*. Semiconductive device fabrication, P (11) 287*c*. Semiconductor device fabrication, P (1) 11*e*, P (4) 102*d*. Semiconductor devices having modifier-containing surface oxide [silicon oxide] layers, P (11) 287*d*. Semiconductor devices with layer of silicon monoxide and germanium mixture and methods of fabricating them, P (9) 232*b*. Semiconductor devices and method of manufacture thereof, P (2) 49*f*. Stabilizing coatings for semiconductor devices, P (10) 265*g*. Superconducting materials and method of making them, P (3) 79*g*. Superconductive articles, P (11) 287*i*. Tellurium thin film field effect solid state electrical devices, P (3) 79*k*. Thermoelectric device having silicon-germanium alloy thermoelement, P (1) 12*a*.
Radjy, F. See Richards, C. W.
Radley, S. A. Gaseous fuel burners, P (3) 82*c*.
Rado, G. T., and Suhl, H. (editors). Magnetism—A Treatise on Modern Theory and Materials (Vol. IIA) Statistical Models, Magnetic Symmetry, Hyperfine Interactions, and Metals; (Vol. IIB) Interactions and Metals, B (8) 212*c*.
Radovskii, I. Z., Shubina, T. S., Gel'd, P. V., and Sidorenko, F. A. Magnetic susceptibility of chromium silicides, (8) 202*h*.
Radus, R. J. See Carlson, W. G.
Raede, D. See Hund, F.
Raggenbass, A. See Olombel, A.
Raghavan, K. S., and Kuhlmann-Wilsdorf, D. Effect of specimen shape on the selection of the primary slip plane, (11) 294*i*.
Raghavan, R. See Aravamudan, V.
Rahman, H. U., and Runciman, W. A. Crystal field calculation in uranium dioxide, (8) 193*a*.
Rahn, H. N. See Mayer, E. H.
Rai, M. Separation and identification of clay minerals in argillaceous and siliceous limestones, (8) 189*h*.
Raichenko, O. I. Investigation of interdiffusion in a two-component mixture of powders of different degrees of dispersion, (3) 86*j*.
Rairden, J. R., III. See Neugebauer, C. A.
Rais, J., Podesva, S., and Kyrs, M. Extraction of cesium with nitrobenzene in the presence of phosphomolybdic acid, (1) 13*e*.
Raithel, K. Method for heat-treating of monocrystalline semiconductor bodies, P (8) 185*d*.
Raju, A. P., Kurtz, P., Jr., and Knapp, W. J. Strength of biaxially prestressed ceramic plates after nonuniform heating, (1) 29*g*.
Rakina, V. P. See Pirogov, A. A.
Ram, A., and Prasad, S. N. Principles underlying the production of copper ruby glass, (8) 175*j*.
Ram, G. L., and Salamon, R. G. Process for purifying colloidal particles for subsequent structural analysis with an electron microscope, P (8) 188*e*.
Ram, P., Gadiyar, H. S., and Jena, P. K. Kinetics of uranium dioxide sintering between 950° and 1500°C in dry hydrogen atmosphere, (11) 297*h*.
Ramachandran, V. S. See Feldman, R. F.
Ramachandran, V. S., and Kacker, K. P. Thermal decomposition of dye-clay mineral complexes, (2) 58*b*.
Ramachandran, V. S., Sereda, P. J., and Feldman, R. F. Discussion of "Volume expansion of hardened cement paste due to the presence of dead-burned CaO." (11) 274*h*.
Ramakrishna, T. V., Robinson, J. W., and West, P. W. Determination of calcium and magnesium by atomic absorption spectroscopy, (1) 13*g*.
Ramalho, R. S., and Bui, V. T. Improved design method for countercurrent exchangers, (5) 132*f*.
Ramamurthy, S. G. See Subramanian, T. V. A.
Ramberg, E. G., and Epstein, D. W. Art of making color-phosphor mosaic screens, P (1) 10*f*.
Ramirez-Munoz, J. See Haagen-Smit, J. W.
Rammel, G. E. See Marzocchi, A.
Ramos, G. G. See Garcia Ramos, G.
Ramous, E. Determination of rare earths in glass by X-ray fluorescence, (10) 251*h*.
Ramseier, R. O. Zone-melting apparatus for growing ice monocrystals, (8) 188*i*.
Ramsey, T. H., Jr., and Rice, S. B., Jr. Dielectrics with conductive portions and method of making same, P (4) 100*f*.
Ranby, B. See Yoshida, H.
Ranby, P. W., and Smith, D. W. Electroluminescent lamp with boric acid or boric oxide used in conjunction with the zinc sulfide layer, P (2) 47*e*.
Randels, R. B. See Layton, M. M.
Raney, A. K. Computers and their application in glass manufacturing (I) glass process automation concepts; (II) digital process control computer in glass manufacturing, (8) 175*e*.
Rankin, J. S. See Keslar, L. D.
Ransburg Electro-Coating Corp. Electrostatic spray coating apparatus, P (3) 65*c*.
Ranshaw, J. H. See Needham, J. G.
Ransley, C. E. Method for manufacturing solid current conducting elements, P (8) 181*c*.
Rao, B. V. J. Glass composition and electrical resistance material made therefrom, P (1) 10*g*. Infrared spectra of GeO_2-P_2O_{16}-V_2O_5 glasses and their relation to structure and electronic conduction, (1) 3*h*.
Rao, G. V. Apatite-magnetite-vermiculite deposits near Sitarampur, Visakhapatram district, Andhra Pradesh, (8) 189*e*.
Rao, H. V. B. See Minhas, G. S.; Murthy, H. P. S.; Sahota, N. S.; Sen, P. C.
Rao, M. K., and Roonwal, G. S. Mineral separation from rocks with the Frantz isodynamic magnetic separation, (8) 189*i*.
Rao, M. R. K. See Murthy, H. P. S.; Sen, P. C.
Rao, N. S. G. Drying of ceramic ware, (4) 105*c*.
Rao, R. S. Dielectric constants of cupric phosphate and manganese sulfate, (9) 238*c*.
Rao, S. V. K. Investigation of ThO_2-UO_2 as a nuclear fuel, (7) 151*g*.
Rao, S. V. K., Mohan, A., Anandan, N. S., and Moorthy, V. K. Factors influencing the sinterability of uranium dioxide, (2) 41*f*.
Rao, Y. D. P. See Aravamudan, V.
Rao, Y. P. Improved kilns for lime manufacture, (10) 268*h*.
Rapoport, A. Ya. See Ginzburg, D. B.
Rapp, J. E., and Babcock, C. L. Rapid method for approximating viscosity-temperature data in the range 10^{12} to 10^{14} poises, (9) 233*j*.
Rapp, R. A., and Colson, H. D. Kinetics of simultaneous internal oxidation and external scale formation for binary alloys, (9) 240*c*.
Rapp, R. A., and Goldberg, G. N. Oxidation of Cb–Zr and Cb–Zr–Re alloys in oxygen at 1000°C, (9) 241*h*.
Rappeneau, J. See Oberlin, M.
Rapson, B., and Southam, F. W. Refractory gas seal, P (7) 154*f*.
Raraty, L. E. Effects of changes in strength of texture on the physical properties of fiber-textured materials, (9) 216*d*.
Rasch, R. Importance of elastic modulus, compressive strength, and expansion of refractory materials for furnace and kiln construction, (8) 179*j*.
Rasmussen, S. E. See Christensen, A. N.

Rasnick, B. A. See Nakayama, F. S.

Rassilstein, A. G. Method of roughening the surface of a coated body, P (1) 13*a*.

Rastorguev, L. N. See Bol'shakov, K. A.

Rasul, C. G. See Cable, M.

Ratcliffe, E. H. Thermal conductivities of plastics with glass, asbestos, and cellulosic fiber reinforcement, (9) 218*h*.

Rath, E. W. High power fuse with ceramic casing, P (4) 101*i*.

Rathbone, R. R. Communicating Technical Information—A Guide to Current Uses and Abuses in Scientific and Engineering Writing, B (9) 244*i*.

Rathenau, G. W. See Schinkel, C. J.

Rathgeber, R. F., and Fowler, H. Iron cordierite in the core structure of a bloated building brick, (4) 96*a*.

Rathmann, D. W. Magnetic perturbation scanning—a new nondestructive testing method, (7) 159*h*.

Ratobyl'skaya, V. A. See Tarasov, V. V.

Ratterman, E. See Mathewson, W. F.

Raue, E. J. Manufacturing process for electronic capacitors, P (5) 127*j*.

Rauland Corp. Cathode-ray tube manufacturing apparatus, P (11) 278*b*.

Rauner, L. A., and Maynard, W. J. Hydrophobic silica as a grinding aid, P (10) 266*a*.

Rauschenbach, H. S. See Bickler, D. B.

Rauschenfels, E. See Kupzog, E.

Ray, N. H. Method of chemically strengthening glass, P (8) 177*i*.

Ray, N. H., and Johnson, P. G. Effect of alkali silicate solutions on the strength of glass, (11) 276*i*.

Ray, N. H., Stacey, M. H., Thomas, R. E., and Webster, S. J. Reactions between glass and molten borofluoride-nitrate solutions, (11) 277*i*.

Ray, N. H., Stacey, M. H., and Webster, S. J. Increasing the strength of glass by treatment in molten salts, (9) 218*c*.

Ray, R. N. See Lele, R. V.

Raybestos-Manhattan, Inc. Composite flame spraying wire, P (10) 250*b*.

Raymond, J. J. See Comstock, R. L.

Rayonier, Inc. Process for producing portland cement compositions, P (10) 249*c*.

RCM. See Revisione Construzione Macchine.

RDF Corp. Thermal measuring probe, P (3) 81*h*.

Rea, R. F. Continuous heat treat furnace with a conveyor, P (10) 268*j*.

Read, H. H. Orthonorite containing spinel xenoliths with late diaspore at Mill of Boddam, Insch, Aberdeenshire (Scotland), (3) 87*d*.

Read, T. B. CW pumping of YAG:Nd^{3+} by water-cooled krypton arcs, (10) 270*e*.

Readey, D. W. Nonstoichiometry of cadmium sulfide thin films, (1) 23*j*. See Atlas, L. M.

Reaney, W. A. Production of burnt lime with a rotary kiln and a rotary hearth, P (4) 91*f*.

Reber, R. L. Duo resist process, P (8) 184*i*.

Rebinder, P. A. See Doronin, L. K.; Khutortsov, G. M.

Reburn, W. T., and Foster, H. R., Jr. Separately crystallizing boric acid and alkali sulfate from aqueous solution by evaporation at different temperatures, P (11) 292*e*.

Recknagel, Firma H. See Firma Hermann Recknagel.

Reddy, J. M. See Abrahams, S. C.

Redland Tiles, Ltd. Tiles, P (3) 64*i*.

Redline, H. S. See Stoyell, L. A.

Redman, M. J., and Chen, J. H. Zinc tellurite glasses, (11) 277*g*.

Reed, A. K., and Repsher, R. W. Method for phosphor coating a fluorescent tube of irregular section, P (5) 128*f*.

Reed, E. L., Gradle, B., and Garrett, E. E. Bonded metallic and metallized ceramic members and method of making, P (2) 47*h*.

Reed, L. Method and material for metallizing ceramics, P (3) 79*a*. Method for reducing electron multipactor on a dielectric window surface, P (10) 264*i*.

Reed, T. B. Arc techniques for materials research, (9) 233*g*.

Rees, L. V. C., and Williams, C. J. Neutron irradiation of Linde molecular sieve 13X, (1) 23*f*.

Rees, V. C. Apparatus and process for combining glass fibers with synthetic resin fibers, P (1) 4*f*.

Reese, T. J. See McKelvey, H. E.

Reese, W. Low-temperature excess heat capacity in glassy polymers, (4) 108*c*.

Reesman, A. L. See Keller, W. D.

Reeve, K. D. Control of microstructure in single phase oxide ceramics, (4) 103*c*.

Reeves, P. C. See Stamos, C.

Reeves, R. D., and Janz, G. J. Viscosity measurements on fused salts (I) theoretical principles of the oscillating hollow cylinder method; (II) alkali and alkaline earth chlorides, (7) 169*d*.

Regan, I. See Inman, D.

Regan, R. E., Baginski, W. A., and Krier, C. A. Oxidation studies of complex silicides for protective coatings, (7) 147*i*.

Regents of the University of California. Ultrasonic sieving, P (5) 130*f*.

Rehm, K. Testing the chemical behavior of silicate glasses, (10) 253*f*.

Reichard, H. F. Nuclear reactor fuel production, P (2) 44*h*.

Reid, A. F. Calcium ytterbate, $CaYb_2O_4$, an orthorhombic calcium ferrite isomorph, (10) 270*f*.

Reid, F. J. Semiconductor light emitters, (9) 229*j*.

Reid, F. J., Matson, L. K., Miller, J. F., and Himes, R. C. Electric properties of selected rare earth compounds and alloys, (3) 85*c*.

Reid, L. J., Jr. Synthesis of mordenite, P (10) 260*j*.

Reidl, R. W. See Mandorf, V., Jr.

Reimbert, A. Means for discharging pulverulent or granular materials from silos, P (11) 288*g*.

Reinmold, H. See Ollfisch, F.

Reintjes, G. G. See Byfield, D. R.

Reintjes, Geo. P., Co., Inc. See Geo. P. Reintjes Co., Inc.

Reishakhrit, A. L. See Karapetyan, G. O.

Reisman, A. Process for epitaxial growth of semiconductor single crystals, P (4) 102*h*. See Berkenblit, M.; Hochberg, F.

Reisman, A., and Berkenblit, M. Substrate orientation effects and germanium epitaxy in an open tube HI transport system, (9) 242*b*.

Reisman, A., Berkenblit, M., and Alyanakyan, S. A. Transpiration studies of the Ge-I_2-inert gas system, (9) 242*j*.

Reiss, F. Emissivity and electrical resistivity of flame-sprayed Al_2O_3 and ZrO_2 coatings at higher temperatures, (3) 65*c*.

Reisstad, T. X-ray fluorescence method for the determination of iron in mineral, (11) 289*g*.

Reitmayer, F. Surface-scratch stress in ground glass, (10) 253*d*.

Rembaum, A., Moacanin, J., and Pohl, H. A. Polymeric semiconductors, B (11) 305*f*.

Remeika, J. P. Devices utilizing lithium metagallate, P (2) 47*c*. Process for the growth of ordered lithium ferrite, P (5) 128*h*. See Comstock, R. L.; Dillon, J. F., Jr.; Marezio, M.; Onn, D. G.; Sturge, M. D.; Wood, D. L.

Remeika, J. P., Dodd, D. M., and DiDomenico, M., Jr. Dichroism in bismuth-doped single-crystal barium titanate, (7) 162*b*.

Remeika, J. P., and Marezio, M. Growth of α-Ga_2O_3 single crystals at 44 kbars, (5) 136*g*.

Remenyi, K. Grindability of limestone and rock-salt mixture in a Hardgrove mill, (5) 129*h*.

Remirez, R. Fly-ash debut in brick manufacturing, (8) 179*f*.

Remizov, Yu. S. See Margulis, E. V.

Remmey, G. B. Preheater for furnaces, P (1) 15*b*.

Renault, P. Double dilatometric analysis of clays, kaolins, and ceramic bodies for a better knowledge of their nature and their physicochemical changes during firing—practical applications, (11) 289*f*. Research on eutectics and vitreous compounds of the type $CaO \cdot xAl_2O_3 \cdot ySiO_2$ for various ceramic applications, (5) 125*j*.

Renkey, A. L. See Troell, P. T.

Renner, J. See Steeb, S.

Renner, T. See Arndt, H. H.

Renton, J. J. See Heald, M. T.

Reppich, B., Blum, W., and Ilschner, B. Apparatus for measuring the high temperature deformation of ceramic materials, (8) 187*d*.

Repsher, R. W. See Reed, A. K.

Republic Steel Corp. Basic refractory compositions, P (5) 124*c*. Basic refractory compositions for intermediate temperature zones, P (2) 43*e*. Carbon-bearing refractories, P (5) 124*c*.

Res, M. Control of changes in the physical properties of high-lead glasses, (5) 118*f*.

Res, M., and Quang, B. T. Evaluation of strains in hollow glassware, (10) 252*a*.

Res, M., and Tutunarova, I. Use of apparatus for flow point determination, (2) 51*d*.

Research Corp. Electroluminescent display device with piezoelectrical scanning and gating means, P (3) 78*d*.

Reshchikova, A. A. See Eliseev, A. A.

Reshetnikov, N. A. Complex formation in the crystallization of melts of salts, (11) 292*g*.

Resnick, R., and Seigle, L. Diffusion of carbon in tantalum monocarbide, (9) 238*e*.

Ressler, W. J., Jr. See Laseck, F. B.

Retali, R. Improvements in rotary kilns and analogous chemical reactors, P (7) 160*c*.

Rettenmaier, J. Tamping arrangement for supplying a material to crushing rollers, P (11) 292*d*.

Rettenmaier, J., & Soehne. Tamping arrangement for supplying a material to crushing rollers, P (11) 292*d*.

Retzer, T. C. High-current seal for electric discharge lamp, P (1) 10*i*.

Reuter, H. L. See Thomas, L. D.

Reuter, H. L., and Thomas, L. D. Rare earth chlorides in a glass polishing composition, P (8) 178*j*.

Revesz, A. G., Zaininger, K. H., and Evans, R. J. Deviations from parabolic growth in the thermal oxidation of silicon, (5) 135*c*.

Revisione Construzione Macchine. Apparatus for preparing a water asbestos-cement slurry in the desired proportions and delivering the slurry to the utilizing apparatus, P (3) 64*c*.

Revolinsky, E. See Bergstrom, B. H.

Rexer, J. See Petersen, D. T.

Reynders, A. Apparatus relating to evacuating and filling gas discharge lamps and the like, P (7) 149*h*.

Reynik, R. J. See Foster, J. P.

Reynolds, C. B. See Jenkins, J. D.

Reynolds, C. B., Eklund, W. M., and Burklo, D. C. Metal encased refractory article, P (8) 181*h*.

Reynolds, J. B. See Stowe, R. A.

Reynolds, J. H. Semiconductor-metal-semiconductor light detector, (10) 263*g*. See Lindmayer, J.

Reynolds Metals Co. Alumina reduction cell and method for making refractory lining therefor, P (9) 225*j*. Electrically conductive cermet compositions, P (9) 225*e*. Manufacture of shaped carbon bodies, P (9) 226*b*. Method of manufacturing shaped carbon bodies, P (2) 44*b*.

Reznichenko, M. I. See Neshpor, V. S.

Reznick, F. J., and Nussear, J. G. Attaching leads to semiconductors, P (7) 156*f*.

Rezukhina, T. N. See Kuznetsov, F. A.

Rheinische Kalksteinwerke G.m.b.H. Method of producing cement clinker from raw powder containing quicklime, P (7) 147*b*.

Rheinische Werkzeug- und Maschinenfabrik G.m.b.H. Screen with spring supported vibratory drive, P (10) 266*h*.

Rheinstahl Industrie-Planung G.m.b.H. Preheating and thermal treatment of powdered products, such as lime, raw cement, minerals, etc., P (2) 35*b*.

RHEWUM. See Rheinische Werkzeug- und Maschinenfabrik G.m.b.H.

Rhodes, E. See McAuley, W. J.

Rhodes, E. G. Electrical capacitor manufacture, P (7) 149*b*.

Rhodes, W. H. See Sellers, D. J.

Rhodin, T. N. See Robins, J. L.

Rhone, W. C., and Roudabush, H. L. Refractory brick wall with a comolded hanger assembly, P (9) 227*c*.

Rhys, D. W., and Berry, R. D. Brazing of ceramics and palladium-nickel-titanium brazing alloy therefor, P (1) 10*g*.

Ribbe, P. H. See Smith, J. V.

Ribbe, P. H., and Smith, J. V. X-ray emission microanalysis of rock-forming minerals (IV) plagioclase feldspars, (2) 60*a*.

Ricci, E., and Hahn, R. L. Sensitivities for activation analysis of 15 light elements with 18-Mev helium-3 particles, (9) 242*e*.

Rice, D. A. See Fuerstenau, M. C.

Rice, H. H., and Garey, M. J. Method of making magnesium fluoride articles, P (4) 98*c*.

Rice, R. W. Internal surfaces of MgO, B (2) 61*g*.

Rice, S. A., and Jortner, J. Theory of ionic and electronic mobility in liquids, B (11) 305*g*.

Rice, S. B., Jr. See Ramsey, T. H., Jr.

Rich, T. A. Flame spectrophotometer using ionization current detection, P (10) 268*c*.

Richards, C. W., and Radjy, F. New application of internal friction to concrete research, (7) 146*i*.

Richards, E. E. See Blin-Stoyle, A. E.; Catling, H. W.

Richards, J. L. See Sirgo, V. H.

Richards, M. W. See Aiken, H. H.

Richards, N. E., Berry, J. S., Jr., and Johnston, T. J. Electrically conductive cermet compositions, P (9) 225*c*.

Richards, R. Ceramic industry in Spain, (7) 169*g*.

Richards, S. R. See Bockris, J. O'M.

Richards Structural Steel Co., Ltd. Mulling machine, P (1) 13*b*.

Richardson, D. V. Compensated tapped thermocouple system, P (5) 132*a*.

Richardson, F. D. See Meadowcroft, T. R.

Richardson, G. W., and Wright, J. E. Cooking apparatus with cooking vessel centering and holding means, P (8) 176*j*.

Richardson, H. M. Slags and refractories, (4) 97*g*.

Richardson, R. E. Assemblies of glass sheets, P (4) 93*h*. Press bending mold with heat reflective surface, P (9) 222*c*.

Richartz, W. Formation of alumina hydrate phases during the setting of cement, (7) 146*e*.

Richman, D., and Hockings, E. F. Heats of fusion of InSb, InAs, GaAs, and InP, (11) 296*f*.

Richman, D., and Tietjen, J. J. Rapid vapor phase growth of high-resistivity GaP for electro-optic modulators, (10) 263*c*.

Richmond, A. See Waxter, W. E.

Richter, C. Clay preparation in the fine ceramic industry, (9) 228*c*.

Richter, F. See Keyzlar, T.

Richter, J. See Lamb, J.

Richter, K. Increasing the quality of ceramic bodies, (7) 158*e*.

Rickles, R. N. Effect of heat on inorganic cements, (10) 248*d*.

Ride, C. Propane burners used in ceramic kilns and their principal applications, (5) 132*g*.

Rider, J. G. See Foxon, C. T. B.

Riebling, E. F. Volume relations in $Na_2O \cdot B_2O_3$ and $Na_2O \cdot SiO_2 \cdot B_2O_3$ melts at 1300°C, (2) 38*e*.

Rieck, A. W. See Mumford, E. H.

Riedy, K. J. See Hudson, R. M.

Riegger, H. Raku (I) history and appreciation; (II); (III) raku pottery of America, (5) 115*j*.

Rieke, J. K. See Clock, G. E.

Ries, H. B. Problems in the comminution of materials of medium hardness (I, II), (10) 266*c*.

Rieth, H. F. Electrical capacitor formed from thin films, P (2) 47*c*. Electrical capacitor and methods of forming the capacitor, P (2) 47*c*.

Riewald, P. G. See Mehta, J. M.

Rigby, G. R. Production of direct bonded basic brick, P (4) 99*c*. Spalling-resistant refractory brick, P (4) 99*b*.

Riley, B. Determination of melting points at temperatures above 2000°C, (7) 159*b*.

Riley, H. L. Production of electrically conducting carbon, P (7) 153*i*.

Riley, J. D. See Roberson, C. L.

Riley, J. E. Method and capacitor comprising [Mn] oxide electrolyte derived from permanganic acid, P (8) 185*b*.

Riley, J. E., and Williams, B. B. Dielectric devices, P (8) 184*g*.

Riley, J. P. See Chan, K. M.

Riley, M. B. See Whitney, J. M.
Riley, O. J. Potter's wheel having a variable speed power transmission system, P (3) 64*a*.
Riley, R. R. See Barns, G. L.
Rimbach, H. W. Coating composition, P (8) 184*e*. Copper activated strontium phosphate phosphors, P (9) 230*b*.
Rimmer, D. E., and Johnson, D. F. Study of the origin of the trigonal crystal field in ruby (I) analysis of experiment data, (4) 110*i*.
Rindone, G. E. Process for increasing the index of refraction of glass and an article made thereby, P (9) 222*f*. See Graham, P. W. L.; Stewart, D. R.
Rinehimer, W. A. See Dohman, F. J.
Ringbom, A. See Skrifvars, B.
Riseman, J. H., Ross, J. W., and Wall, R. A. Glass electrode and method of making the same, P (2) 38*g*.
Riseman, J. H., and Wall, R. A. Glass electrode apparatus and process for making same, P (5) 120*a*.
Rispal, C. Improvements in processes for radioactive labeling, P (2) 44*h*.
Ristic, M. M. See Zivanovic, B.
Ritchie, A. R., and Holland, K. Indicating devices for heat treatment, P (9) 234*d*.
Ritter, E. Deposition of oxide films by reactive evaporation, (2) 46*j*. See Hass, G.
Ritter, G. F., Jr. Method and apparatus for press bending and tempering glass sheets, P (11) 278*h*. Method and apparatus for producing a continuous glass ribbon, P (11) 278*i*. See Carson, F. J.
Ritter, J. See Barz, G. J.
Ritter, J. E., Jr., and Burton, M. S. Adherence and wettability of nickel, nickel-titanium alloys, and nickel-chromium alloys on sapphire, (10) 249*g*.
Ritter Pfaudler Corp. High temperature coatings for columbium alloys, P (11) 276*b*.
Rittler, H. L. See Beall, G. H.
Ritz, J. W. High temperature ceramic-metal seal, P (2) 47*i*.
Rivero, A. M. See Macdonald, A. M. G.
Robbins, C., Perloff, A., and Block, S. Crystal structure of BaGe [Ge_2O_5] and its relation to benitoite, (3) 84*h*.
Robbins, M. See Arlett, R. H.
Roberson, C. L. See Stalego, C. J.
Roberson, C. L., Leedy, N. J., and Riley, J. D. Feeder for production of fibers of heat-softenable materials, P (5) 120*e*.
Robert Body, Ltd. Sampling of free-flowing granular materials, P (9) 234*f*.
Roberts, A. L., Street, G. B., and White, D. Mechanism of phenol adsorption by organo-clay derivatives, (1) 22*f*.
Roberts, D. A. See Sliker, T. R.
Roberts, F. Method of making graphite articles, P (7) 153*j*. See Fletcher, J. M.
Roberts, G. J. Report on the symposium on gases in glass, (5) 119*d*.
Roberts, J. P. Microscopic examination of technical silicates, B (5) 141*g*. See Heuer, A. H.
Roberts, M. W. See Quinn, C. M.
Roberts, P. S., and Mukaihata, T. Dielectric constant measurements by reflectometer, (1) 13*j*.
Roberts, R. W., Jr. Ferrite circulator having three mutually coupled coils coupled to the ferrite material, P (2) 47*f*.
Roberts & Schaefer Co., Division of Thompson-Starrett Co., Inc. Method and apparatus for removing moisture from material by sonic or ultrasonic energy in combination with centrifugal energy, P (9) 233*e*.
Robertshaw Controls Co. Temperature sensor, P (2) 52*a*.
Robertson, J. A. See Berg, K. M.
Robertson, R. H. S. See Wilson, A.
Robertson, W. M., and Chang, R. Kinetics of grain-boundary groove growth on alumina surfaces, B (2) 61*c*.
Robidoux, R. A. [Glass] encapsulated thermostatic switch with shunt, P (1) 10*c*.
Robin, M. B., Kuebler, N. A., and Pao, Yoh-Han. Micaceous biotite as efficient Brewster angle polarizer for vacuum ultraviolet, (1) 10*a*.
Robins, J. L., Rhodin, T. N., and Gerlach, R. L. Dislocation structures in cleaved magnesium oxide, (2) 54*i*.
Robinson, A. S. Manufacture of flat glass, P (3) 68*d*. Method of and apparatus for the manufacture of flat glass on a molten metal bath, P (8) 177*c*. Method of manufacturing flat glass of different thicknesses, P (5) 121*d*.
Robinson, J. H. See Rohl, C. W.
Robinson, J. W. See Ramakrishna, T. V.
Robinson, L. B. Thermal properties, B (9) 244*e*.
Robinson, P. Electrical resistor and the like, P (3) 78*a*.
Robinson, P. M., and Bever, M. B. Thermodynamic properties of the tellurides of cadmium, indium, tin, and lead, (3) 77*c*.
Robinson, W. C. See Chiotti, P.
Robinson, W. C., and Chiotti, P. Reaction of uranium carbide in a KCl–LiCl/zinc system, (11) 300*f*.
Robinson, W. C., Heestand, R. L., and Leitten, C. F., Jr. One-step method of converting uranium hexafluoride to uranium compounds, P (10) 260*a*.
Robitschek, P. Glass mat fibers bonded together by a polyester composition, P (11) 278*c*.
Robredo, J. Thermal treatment of glass to improve its properties, (5) 119*e*.
Robson, H. E. Synthetic crystalline aluminoborosilicate zeolites and preparation thereof, P (9) 235*i*.
Robson, H. E., and Gilles, P. W. High temperature vaporization properties of boron carbide and the heat of sublimation of boron, (8) 199*g*.
Rockni, M. See Volterra, V.
Rodbell, D., and DeVries, R. C. Decomposition of CrO_2 in air, (10) 270*e*.
Rode, E. Ya., and Lebedev, B. A. Sulfides of tungsten, (11) 30*b*.
Rodgers, H. G. See Belentepe, Y. C.
Rodriguez, R. Refractory material and method for making the same, P (3) 73*a*.
Roe, C. C. See Joyce, B. D.
Roe, D. W. New glass compositions possessing electronic conductivities, (11) 277*d*.
Roeder, G. A., and Smeltzer, W. W. Dissociation pressures of iron-nickel oxides, (7) 162*c*.
Roeder, M. See Wirth, H.
Roehrs, R. J. See Hedley, W. H.
Roes, J. B. Epitaxially bonded thermoelectric device and method of forming same, P (5) 127*b*.
Roess, D. Single-mode operation of a room temperature CW ruby laser, (5) 138*d*.
Roess, D., and Zeidler, G. Quasicontinuous ruby giant pulse laser using a saturable absorber as a *Q* switch, (1) 10*d*.
Roessle, H., Kasper, K. H., and Rumler, H. Stackable semiconductor rectifier element having seals under compressive stress, P (3) 79*g*.
Roetter, R. P. Method of coating glass for subsequent soldering, P (3) 68*b*.
Rogers, D., and Skapski, A. C. Crystal structure of β-Sb_2O_4—a new polymorph, (8) 193*d*.
Rogers, D. B., Ferretti, A., and Kunnmann, W. Single crystal growth and electrical transport properties of intermediates in the spinel system $Co_{1+\delta}V_{2-\delta}O_4$, (8) 206*j*.
Rogers, D. B., Honig, J. M., and Goodenough, J. B. Electrical properties and band structure of doped $LaInO_3$, (9) 229*e*.
Rogers, L. A. Phosphoreacent opal glasses, P (4) 95*a*.
Rogers, P. S. See Mukherjee, S. P.
Rohl, C. W., and Robinson, J. H. Fiber-reinforced carbon and graphite, (1) 7*d*.
Rohm & Haas Co. Dewatering aqueous suspensions, P (2) 50*b*.
Rohr, F. J. See Heilich, R. P.
Rohr Corp. Two-stage process for derusting and protecting the surfaces of ferrous materials, P (3) 65*f*.
Rohrbacker, T. J. See Hatfield, C. B.
Rokhvarger, E. L. See Berenshtein, P. I.
Rolin, M., and Thanh, P. H. Phase diagrams of mixtures that are nonreactive with molybdenum (I) liquidus of the sodium aluminate–alumina system; (II) system calcium aluminate–alumina; (III) system alumina-lanthanum oxide, (1) 25*i*.
Rolland Glass Co. Apparatus for cutting [sheet] glass, P (1) 4*c*.
Rollins, F. E., and Lowe, C. L., Jr. Apparatus for collecting filamentary materials, P (5) 119*h*.
Rolls-Royce, Ltd. Aerofoil blade for use in a hot fluid stream, P (8) 174*i*. Glass coated glass fibers, P (1) 5*c*. Method of producing solid metal materials containing pretensioned silica, P (5) 117*d*.
Rolseth, H. C. See Arnold, C. S.
Ronson Corp. Process for producing cerium molybdate, tungstate, and vanadate, P (5) 133*d*.
Rood, J. L. See Hafner, H. C.
Rooney, L. F. Gypsum deposits in northern Indiana, (4) 105*j*.
Roonwal, G. S. See Rao, M. K.
Rooymans, C. J. M. New compound in the Na_2O-Fe_2O_3 system, (3) 87*b*.
Ropp, R. C. Cadmium halophosphate phosphors, (4) 100*c*. Luminescence of europium in the ternary system La_2O_3-Gd_2O_3-Y_2O_3, (9) 240*b*. Orthophosphate phosphor compositions, P (1) 11*j*.
Ropp, R. C., and Layman, H. D. Copper activated strontium metaphosphate phosphors, P (8) 184*f*.
Ropska, H. See Tokarski, Z.
Rosa, I. Magnesia cements with uniform volume change and their hydration, (10) 248*a*.
Rose, A., and Rose, E. (editors). Condensed Chemical Dictionary, B (11) 303*j*.
Rose, E. See Rose, A.
Rose, R. E. See Hyatt, E. P.
Rosemount Engineering Co., Ltd. Resistance thermometer and method of making the same, P (10) 268*a*.
Rosen, S., and Sprang, P. G. Ternary carbide phases formed by scandium-group elements with aluminum and carbon, B (5) 139*i*.
Rosenberg, N. W. See O'Connor, T. L.
Rosenberg, R., Kozlowski, M. A., McAleer, W. J., and Pollak, P. I. Strain patterns in Ga-$As_{(1-x)}P_{(x)}$ alloy overgrowths, (11) 301*g*.
Rosenberger, F. Production of very pure alkali halogenide single crystals by zone melting, (8) 205*e*. Vacuum distillation and crystal growth of alkali halogenides, (7) 169*b*.
Rosenblatt, G. M. See Brewer, L.
Rosenbluth, H. E. See Lieb, N. H.
Rosenfield, A. R. See Wilcox, B. A.
Rosenheinrich, R. Method for production of semiconductor devices, P (2) 48*c*.
Rosenqvist, T. See Rossemyr, L.
Rosenstock, J. See Kalnin, I. L.
Rosenthal-Porzellan Akt.-Ges. Dense ceramic porcelain-type body with high thermal shock resistance and high mechanical strength and its manufacture, P (11) 283*i*.
Roshore, E. C. Field exposure tests of reinforced concrete beams, (8) 174*d*.
Rosi, F. D., and Hanak, J. J. Superconducting materials and method of making them, P (3) 79*g*.
Roske, E. Ceramic piezoelectric transducers for ultrasonic delay lines, (9) 229*a*.
Roskova, G. P. See Totesh, A. S.
Ross, B. Epitaxial alloy semiconductor devices and process for making them, P (3) 78*f*.
Ross, I. M. See Clark, J. E.
Ross, J. F. Ceramic bonding, P (1) 3*b*.
Ross, J. W. Calcium-selective electrode with liquid ion exchanger, (9) 233*i*. See Riseman, J. H.
Ross, S. Physical adsorption by homogeneous and heterogeneous solid surfaces, B (8) 212*i*.
Rossemyr, L., and Rosenqvist, T. Thermodynamic properties of manganese silicides and of manganous chloride, (4) 112*a*.
Rossetti, M. See Spriggs, R. M.
Rossi, C. E. See Campbell, W. W.
Rossi, J. A. See Stillman, G. E.
Rossin, R., Bersan, J., and Urbain, G. Study of the viscosity of liquid slags belonging to the ternary system SiO_2–Al_2O_3–CaO, (2) 56*d*.
Rossini, F. D. Excursion in chemical thermodynamics, from the past into the future, (7) 169*g*.
Rostron, P. Russian porcelain under the czars, (3) 63*j*.
Roswell, A. E., and Cave, E. F. Method of manufacturing semiconductor devices, P (10) 264*f*.
Rosztoczy, F. E. See McLean, D. A.
Rota Patent A. G. Method and apparatus for the manufacture of glass containers, such as ampoules, injection bottles, etc., P (2) 39*e*.
Rotaru, M. See Teoreanu, I.
Rotger, H. Production, research, and theoretical interpretation of opacification in a fluosilicate glass, B (2) 62*a*.
Roth, R. S., and Waring, J. L. Phase equilibria as related to crystal structure in the system niobium pentoxide-tungsten trioxide, (2) 55*b*.
Roth, R. W. See Stalego, C. J.
Roth, W. L. Barium potassium ferrite magnetic material exhibiting nonvanishing rotational hysteresis in applied magnetic fields, P (2) 47*g*.
Rothberg, H. M., and Foster, F. J. Rubber latex, graphite, and cement, P (4) 91*f*.
Rothenberg, P. Enameling steep-sided bowls, (4) 89*j*.
Rothman, S. J., Barr, L. W., Rowe, A. H., and Selwood, P. G. Diffusion and conductivity in the NaCl–$ZnCl_2$ system, (8) 194*f*.
Rothrock, B. D., and Kirby, R. K. Apparatus for measuring thermal expansion at elevated temperature, (10) 266*j*.
Rothwell, W. S. Analysis of time-dependent creep phenomena in single-crystal MgO, (1) 16*f*.
Rottmann, H. R. Bottle inspector including a rotating photocell for scanning, P (9) 219*j*. Detection of chips in syringe cartridges, P (9) 219*f*. Gaging wall thickness of glass tubing, P (5) 120*i*. Inspecting glass containers for line-over-finish defects, P (5) 120*e*. See Johnson, W. E.
Roubal, A. J. Cooler for rotary kiln, P (1) 14*i*.
Roudabush, H. L. See Rhone, W. C.
Rough, R. Apparatus for blending molten glass, P (9) 219*c*.
Round Hill Associates, Inc. Apparatus for calibrating thermistor thermometers, P (8) 184*a*.
Routschka, G. See Konopicky, K.
Rowcliffe, D. J. See Kelly, A.
Rowden, E. Firing in the heavy clay and refractories industries 1950–64 (II), (11) 279*j*.
Rowe, A. H. See Rothman, S. J.
Rowe, G. E. Apparatus for moving glass containers onto a moving conveyor, P (8) 176*h*. Mold holder for glassware forming machine, P (1) 6*f*.
Rowe, S. Nuclear weighing, (5) 129*j*.
Rowell, M. H. Extraction of fused salts of europium and neodymium using a molten borate ion-exchanger, P (11) 291*f*.
Rowland, B. W. See Engel, E. G.
Rowlands, D. L. G. See Jones, J. R.
Rowlett, B. J. See Pobst, D. F., Jr.
Rowse, R. A., and Loiselle, A. A., Jr. Humidity controlled phenol-formaldehyde resin bonded abrasives, P (9) 213*g*.
Roy, C. See Cox, B.; Pratt, P. L.
Roy, D. M. See Faile, S. P.
Roy, H. Effect of surface area on the viscosity of dilute suspension of H-clays, (4) 107*f*.
Roy, P. Mechanical responses in a piezoelectric plate transducer, (11) 284*e*.
Roy, R. Application of the isothermal flux evaporation method, (8) 187*e*. See Barry, T. L.; Muller, O.; Sarjeant, P. T.; Short, J. M.; White, E. W.
Roy, R., and White, W. B. Recent data on high temperature-high pressure phase transformations, B (5) 140*b*.
Roy, S. B. See Chattopadhyay, D.; Mandal, S. S.
Roy, S. K., and Coble, R. L. Solubility of hydrogen in porous polycrystalline aluminum oxide, (9) 242*h*.
Royak, S. M., Pirotskii, V. Z., and Matsuev, N. S. Intensification of fine grinding of clinker by surfactants, (9) 214*f*.

Royan, J. See Calandrello, N. A.
Royce, B. S. H. Low-temperature annealing processes in alkali halides, B (9) 244*e*.
Royce, D. V., Jr. See Floyd, J. R.
Royer, J. J. Piezoelectric quartz elements, P (10) 265*e*.
Royka, S. F., and Sheldon, G. J. Illuminator, P (1) 5*h*.
Rozenblyum, M. Ya. See Brailovskii, V. B.
Rozgonyi, G. A. See Foster, N. F.
Rozgonyi, G. A., and Polito, W. J. Preparation of ZnO thin films by sputtering of the compound in oxygen and argon, (3) 76*i*.
Rozov, M. N. See Lobanov, E. M.
Rubenstein, M. Preparation of homogeneous and reproducible solid solutions of GaP–GaAs, (11) 299*c*.
Rubin, J. A. Method of chemically bonding a metal to a ceramic, P (4) 101*c*.
Rubin, J. J., and Van Uitert, L. G. Growth of sapphire and ruby by the Czochralski technique, (8) 199*c*.
Rubinstein, C. B. See Berger, S. B.
Rubisch, O. See Fitzer, E.
Ruble, T. A. Method and apparatus for calcining inorganic hydrates, P (10) 268*g*.
Ruby, S. L. See Shirane, G.
Rucha, U. See Sandmann, H.
Ruck, G. E. See Ellis, W. L.
Rud, B. M. See Samsonov, G. V.
Rudd, D. W. See Ballman, A. A.
Rudenko, V. S., and Porai-Koshits, E. A. X-ray diffraction method for determination of the 'degree of crystallinity' of glass-ceramics with the composition of spodumene, B (5) 142*a*.
Rudham, R. See Cochrane, H.
Rudman, P. S. See Klein, M. J.
Rudman, R. Low-temperature X-ray diffraction powder techniques, (5) 131*e*.
Rudman, V. M. Automatic bubbling equipment, (3) 65*i*.
Rudness, R. G., and McGill, W. C. Arc process and apparatus for growing crystals, P (8) 180*e*.
Rudnev, N. A., and Malofeeva, G. I. Study of coprecipitation in the system In^{3+}, $H^{+}S^{2-}$, ReO_4^-, (1) 29*i*.
Rudnitskaya, E. S. See Nasedkin, V. V.; Orlova, G. P.
Rudolph, R. R., Strutz, C., Jr., and Strutz, F. C. Workpiece supporting and registering apparatus for bottle decorating apparatus, P (7) 150*f*.
Rudy, E., and Brukl, C. E. Lower temperature modifications of Nb_2C and V_2C, (7) 165*f*.
Rudy, E., and Windisch, S. Evidence for zeta Fe_2N-type sublattice order W_2C at intermediate temperatures. (7) 163*c*.
Rudzitis, E., Feder, H. M., and Hubbard, W. N. Fluorine bomb calorimetry (VII) heat of formation of cadmium difluoride, (8) 198*b*; (IX) enthalpy of formation of magnesium difluoride, (8) 198*b*.
Rudzitis, E., Terry, R., Feder, H. M., and Hubbard, W. N. Fluorine bomb calorimetry (VIII) enthalpy of formation of zinc difluoride, (8) 198*b*.
Rueb, F. Dryers for ceramic bodies, (9) 234*h*.
Ruecker, A. See Meyer-Simon, E.
Ruedl, E., and Staroste, E. Behavior of vacancies in quenched Al–Al_2O_3 alloys, (8) 191*c*.
Ruegge, F. (editor). Structural Clay Products Yearbook 1966, B (1) 31*i*; 1967, B (8) 212*g*.
Kuehle, M. See Hinzner, F.
Ruehlemann, H. E. Connector with glass substrate, P (2) 47*b*.
Ruehrwein, R. A. Production of epitaxial films of semiconductor compound material, P (7) 157*i*.
Rueter, H., Cherdron, E., and Faessle, F. Process for preparing alpha calcium sulfate hemihydrate from synthetic gypsums, P (11) 275*h*.
Rueter, H. L. See Reuter, H. L.
Ruf, E. Process for producing cerium molybdate, tungstate, and vanadate, P (5) 133*d*.
Ruggles, R. L., Jr. See Perri, J. A.
Ruh, E. See Wallace, R. W.
Ruh, R., and Garrett, H. J. Nonstoichiometry of ZrO_2 and its relation to tetragonal-cubic inversion in ZrO_2, (7) 166*c*.
Ruhl, R. C. Cooling rates in splat cooling, (10) 261*i*.
Ruiz, C. True-strain extensometer, (5) 131*i*.
Rulon, R. M. Electroluminescent lamp with a barium titanate layer, P (2) 47*d*.
Rumler, H. See Roessle, H.
Rummel, T. Method of producing monocrystalline layers of silicon on monocrystalline substrates, P (9) 231*a*. Process for pyrolytically precipitating elemental semiconductor substance, P (11) 287*g*. See Henker, H.
Rumpf, H., and Leschonski, K. Process and apparatus for pneumatically separating solid particles, P (7) 158*h*.
Rumyantsev, P. F. See Toropov, N. A.
Runciman, W. A. See Rahman, H. U.
Rundle, P. C. See Brander, R. W.; Lamb, D. R.
Rundqvist, S. Crystal structure of Re_2P, (3) 84*b*.
Runge, W. See Singer, E.
Rungis, J., and Mortlock, A. J. Diffusion of calcium in magnesium oxide, (8) 194*d*.
Rupprecht, H., Woodall, J. M., Konnerth, K., and Pettit, D. G. Efficient electroluminescence from GaAs diodes at 300°K., (9) 229*d*.
Rupprecht, J. Halogen doped Bi_2Te_3-Bi_2Se_3-As_2Se_3 thermoelectric composition, P (7) 156*f*.
Ruprecht, B. C. Bulk density of granular refractories determined by arrested absorption, (8) 179*j*.
Rushmer, I. Group project in ceramics, (5) 115*j*.
Rushton, E. See Bussey, H. E.
Ruskin, F. Process and apparatus for concentrating and separating a component of a fluid mixture, P (1) 13*b*.
Rusoff, S. Method of manufacturing basic refractories, P (7) 153*b*.
Russell, C. K. See Hubble, D. H.
Russell, E. R., Prout, W. E., Groh, H. J., and Watt, G. W. Thorium oxide or thorium-uranium oxide with magnesium oxide, P (7) 154*d*.
Russell, G. See Bussey, H. E.
Russell, J. D. Infrared study of the reactions of ammonia with montmorillonite and seponite, (7) 164*a*. Method of transporting material and device therefor, P (7) 158*g*.
Russell, J. L., and Becker, M. Process for preparing a silicon carbide supported vanadium-containing oxidation catalyst, P (2) 45*e*.
Russell, J. P. See Marlow, P. C.
Russell, K. C. Nucleation in homogeneous vapors, B (9) 245*e*.
Russell, L. E., and Harrison, J. D. L. Process for producing high density uranium carbide-plutonium carbide pellets, P (11) 282*g*.
Russell, P., Jr. Protective coating composition, P (2) 35*f*.
Russell, R., Jr. See Graham, H. C.
Russell, R. G., and Holschlag, J. B. Method and apparatus for producing a wound textile package having uniform tension, P (1) 5*g*.
Russell, R. O. See Limes, R. W.
Russell, V. A. See Blank, J. M.
Rutes, V. S., and Zubarev, A. I. Steel casting and intermediate ladles for continuous steel casting plant, (5) 123*f*.
Rutledge, S. E., and Neville, A. M. Influence of cement paste content on the creep of lightweight aggregate concrete, (11) 275*d*; Reply to discussion, (11) 275*d*.
Rutz, R. F. Silicon carbide semiconductor device, P (5) 129*a*.
Ruzicka, J. See Sherer, A. I.
Ryabchikov, I. V., Khrushchev, M. S., and Shchedrovitskii, Ya. S. Kinetics of the reaction of liquid silicon with silica, (1) 21*e*.
Ryabov, V. A. See Galin, L. A.
Ryabov, V. A., and Fedoseev, D. V. Statistical theory of strength of glass, (1) 4*f*.
Ryadchenko, A. G. See Shchegrov, L. N.
Ryan, E. J., and Peretti, E. A. Quasi-binary system InTe-InBi, (8) 205*j*.
Ryan, J. D. See Neal, F. M.
Ryan, J. R. See Searight, C. E.
Ryan, J. R., and Cunningham, J. L. Laser microprobe helps identify inclusions, (3) 80*i*.
Rybal'chenko, M. K. Some aspects of the thermal cycling resistance of sintered materials, (10) 258*h*.
Ryder, R. J. See Lontz, H. M.; Poole, J. P.
Ryder, R. W. Pulverizing apparatus, P (5) 133*f*.
Ryurikova, J. N. See Kuznetsov, V. G.
Ryzhik, O. A. See Smirnov, M. V.
Ryzhkova, T. P. See Vil'k, Yu. N.

Saada, G. Stacking faults in crystals, B (4) 114*b*.
Saakyan, K. S. See Kostanyan, K. A.
Saalfeld, H. Mechanism of exsolution in alumina-rich nickel-aluminum spinels, (5) 137*d*.
Saba, W. G. See Furukawa, G. T.
Sabacek, T. Replacement of plaster for the manufacture of molds used in forming household ceramics, (2) 46*f*.
Sabaeva, E. I. See Buzhinskii, I. M.
Sabane, C. D., Sinha, A. P. B., and Biswas, A. B. Electrical properties of coppe. manganite, (9) 238*d*.
Saburi, O. Semiconductive capacitor and the method of manufacturing the same, P (4) 102*c*.
Sachse, W., and Witt, R. K. New method of holding crystal specimens during sectioning, (11) 289*j*.
Sack, W., and Scheidler, H. Effect of the nucleating agents TiO_2 and ZrO_2 on the separating crystal phases during the production of glass-ceramics, (10) 251*d*.
Sackett, A. J., & Sons Co. Apparatus for classifying materials, P (5) 133*g*.
Sackett, W. J., Jr. Apparatus for classifying materials, P (5) 133*g*.
Sadler, A. G. See Westwood, W. D.
Sadler, H. E. Detailed study of microfacies in the Mid-Visean (S_2-D_1) limestones near Hartington, Derbyshire, England, (8) 194*j*.
Sadofsky, J. See Aranson, S.
Saeki, Y., and Matsuzaki, R. Thermal transformation of tantalum pentoxide, (4) 111*h*.
Saelzle, E. Method of polishing crystal glass and lead crystal glass articles, P (3) 68*j*.
Safdar, M., Hamid, A., and Naz, M. A. Study of a high alumina clay from Musakhel, (5) 123*g*.
Safonov, V. V., Korshunov, B. G., Shevtsova, Z. N., and Bakum, S. I. Reaction of tantalum trichloride with the chlorides of the alkali metals in melts, (11) 300*d*.
Safrankova, M. See Fousek, J.
Safronov, V. S. See Mchedlov-Petrosyan, O. P.
Sagen, G., and Christensen, K. E. H. Mineral wool producing system and method, P (5) 121*b*.
Sager, J. R. Inspecting hypodermic syringe cartridges and the like, P (5) 120*e*.
Sah, Chih-Tang. See Bittmann, C. A.; Collins, D. R.; Deal, B. E.; Leistiko, O., Jr.
Saha, P. See Bandyopadhyay, T.; Ganguli, D.
Sahota, N. S., Prasad, T. V., and Rao, H. V. B. Refractory clays from Jammu and Kashmir, (2) 42*g*.
Saia, F. J., James D. F., and Hammock, L. G. Top contact for surface protected semiconductor devices, P (11) 288*c*.
St. John, D. F. Process and apparatus for electrostatically printing on hot substrate, P (3) 69*a*.
St. Louis, J. R. See Johnson, E. F.
St. Pierre, G. R. See Adelsberg, L. M.
St. Pierre, P. D. S. Nuclear fuel, P (3) 72*b*.
Saito, H. See Takusagawa, N.
Saito, H., and Takusagawa, N. Synthesis of fibrous potassium titanate by flux evaporation method, (1) 29*g*.
Saito, M. See Kunii, D.
Saito, N. See Terada, S.
Saito, Shinroku. See Somiya, S.
Saito, Shozo. X-ray diffraction micrography of the twin structure of antiferromagnetic nickel oxide, (3) 88*a*. See Nagamiya, T.; Shimomura, Y.
Saji, T. Electrical conductivity of dehydrated phosphoric acids, (4) 107*i*. Viscosity of dehydrated phosphoric acids, (4) 112*c*.
Sakaino, T. Color development in silver containing glasses (II) process of coloration by heat treatment at constant temperature, (4) 92*i*.
Sakaino, T., and Moriya, T. Color developing process of copper ruby glass, (4) 92*h*. Coloration of vanadium-containing glass, (4) 92*j*.
Sakaki, T. See Sasabuchi, S.
Sakalauskaite, D. See Deksnys, A.
Sakka, S. See Tashiro, M.
Sakka, S., and Tashiro, M. Dielectric loss of polycrystalline material produced from glass of the system Li_2O-MgO-Al_2O_3-SiO_2, (4) 93*g*.
Sakudo, T., and Unoki, H. Electron spin resonance of Fe^{3+} in $BaTiO_3$ in the rhombohedral and cubic phases, (8) 196*c*.
Sakudo, T., Unoki, H., and Maekawa, S. Electron paramagnetic resonance in $BaTiO_3$ near the Curie temperature, (7) 163*f*.
Sakurai, J. See Kishii, T.
Sala Maskinfabriks Aktiebolag. Drum type magnetic separator, P (9) 235*f*. Rotary scraping device for nodulizing drums in pelletizing plants, P (8) 190*h*.
Salamon, R. G. See Ram, G. L.
Salge, H. See Hennicke, H. W.
Salier, N. See Saulx, C. K. de la.
Salmanov, G. D. See Gulyaeva, V. F.; Shakhlin, V. I.
Salt, D. J., and Hornung, G. Synthesis and X-ray study of hafnium silicate, (11) 301*d*.
Salter, L. S. See Barron, T. H. K.
Saltzman, M. See Billmeyer, F. W., Jr.
Salzer, E. See Kozacka, F. J.
Samaddar, B. N. See Mukherjee, S. G.
SAMES. See Societe Anonyme de Machines Electrostatiques.
Sameshima, Y., and Nishiyama, M. Stress analysis in hermetic compression seals, (1) 4*h*. Stress distribution in hermetic compression seals, (7) 156*c*.
Sampsell, J. W. Transducer array for underwater transponder, P (1) 12*c*.
Samsonov, G. V. Crystal-chemical properties of sulfides of the rare-earth metals and actinides, (3) 84*h*. Problem of the classification of carbides, (2) 42*i*. See Kislyi, P. S.; L'vov, S. N.; Lyutaya, M. D.; Marchenko, V. I.; Ovsyannikov, I. O.; Stadnyk, B. I.
Samsonov, G. V., and Epik, A. P. Parameters of the reaction diffusion of boron and carbon in refractory transition metals, (1) 24*i*.
Samsonov, G. V., Fomenko, V. S., Paderno, V. N., and Rud, B. M. Thermoemission characteristics of alloys of isomorphous carbides, (8) 210*b*.
Samsonov, G. V., Kislyi, P. S., and Vlasov, K. R. Pressing protective thermocouple sheaths, (7) 152*c*.
Samsonov, G. V., and Kovenskii, I. I. State of carbon in the carbides of transition metals, (4) 110*e*.
Samsonov, G. V., Paderno, Yu. B., and Panasyuk, A. D. Physical and electrical properties of transition metal carbides of fixed composition and homogeneity domain of groups IV and V to 2500°C, (3) 87*d*.
Samuseva, R. G. See Plyushchev, V. E.
Samuseva, R. G., and Plyushchev, V. E. Systems KI-RbI, KI-CsI, and RbI-CsI, (11) 302*c*. Systems NaBr-RbBr and NaI-RbI, (11) 302*c*.
Samuseva, R. G., Zharkova, R. M., and Plyushchev, V. E. System Na_2MoO_4-$CsMoO_4$, (11) 301*g*.
Sanchez, M. G. See Fitch, F. T.
Sanchez, M. G., and Barrett, W. T. Silicon thermistors, P (3) 79*f*.
Sanchez, M. G., and Triggiani, L. V. Preparation of a multilayer copper oxide catalyst for treatment of exhaust gases, P (11) 291*c*.
Sanchez Conde, C. Calcium and magnesium compounds as refractory materials, B (2) 62*d*.
Sandelien, J. F. System for measuring kiln conditions using thermocouples in combination with a mathematical model, P (1) 14*f*.
Sanders Associates, Inc. Method of making semiconductor devices utilizing vacuum welding, P (5) 128*d*.
Sandholtz, W. A. Bench scale isostatic pressing, (7) 158*e*.
Sandmann, H., and Dotzer, R. Process using an oxygen free electrolyte for doping and contacting semiconductor bodies, P (9) 232*f*.
Sandmann, H., and Rucha, U. Process and apparatus for pyrolytic production of pure semiconductor material, preferably silicon, P (2) 49*b*.
Sandmeyer, K. H., and O'Meara, E. L., Jr. Wear-resistant refractory lining article, P (3) 73*e*.

Sando, W. J. Madison limestone (Mississippian), Wind River, Washakie, and Owl Creek Mountains, Wyoming, (8) 201*j*.
Sandven, O. A. See Bonis, L. J.
Sandvikens Jernverks Aktiebolag. Hot top, P (4) 98*a*. Hot top composition for casting molds, P (4) 98*b*.
Sanford, R. A. Humidity-sensitive resistor, P (4) 104*i*.
Sanker, P. E. See Town, J. W.
Sanlaville, J. See Bellay, M. G. du.
Sanno, A. P. de, & Son, Inc. Method of impregnating lubricant into abrasive wheels, P (9) 213*h*.
Sano, S., Sugiura, M., Ishii, E., and Hirai, M. Forsterite porcelain as a high frequency insulator (VI) relation between the microstructure and the metallizing properties of forsterite porcelain; (VII) effect of kaolin on the properties of forsterite porcelain, (2) 46*d*.
Santamaria, F. S. See Soria Santamaria, F.
Santelli, T. R. Treatment of glass surfaces with polymers of alkali metal vinyl siliconates, P (1) 6*e*.
Santen, J. G. van, Esveit, H., and Joormann, H. J. M. Method of manufacturing photoconductive layers, P (2) 48*a*.
Sanvordenker, V. C. Optical and microstructural variations with electric field in barium-strontium titanate ceramics, (7) 156*a*.
Sapozhnikov, R. A. See Buketov, E. A.
Sapozhnikov, Yu. P. See Markovskii, L. Ya.
Sapunov, P. See Stamboliev, H. T.
Sarabia, A. Refractory linings in the cement industry, B (2) 62*e*.
Sarco Canada, Ltd. Burner control system, P (9) 234*i*.
Sarjeant, P. T., and Roy, R. New glassy and polymorphic oxide phases using rapid quenching techniques, (11) 298*c*.
Sarkisov, R. B. Vermiculite-ceramic products, (8) 180*c*.
Sarver, J. F. Compound formation and phase-equilibrium relations in the systems CoO-P_2O_5 and NiO-P_2O_5, (1) 17*e*. Diffuse reflectance characteristics of monoclinic ZrO_2 as a function of purity, (10) 249*g*. See Winkler, E. R.
Sasabuchi, S., Sakaki, T., and Kawada, I. Method of and apparatus for automatically cutting a glass ribbon, P (2) 39*b*.
Sasada, T. See Eisenberg, A.
Sasaki, H. Growth process of $BaTiO_3$ butterfly crystals, (9) 239*d*. Net pattern in mixed crystals of barium-strontium titanate, (8) 203*e*. See Mori, S.
Sasaki, H., and Watanabe, A. New growing method for VO_2 single crystals, (8) 203*j*.
Sasaki, S. Automatic moisture content determination and control apparatus, P (1) 14*c*.
Sasnauskas, K., and Leskauskas, B. Effect of electric current on the properties of porous silicate and on the synthesis of calcium hydrosilicates at 20°, 40°, and 60°C, (8) 174*c*.
Sastry, B. S. R. See Hanumanlu, K.
Sastry, M. K. L. N. See Mallick, S. K.
Sata, T. Fusion point measurement of pure oxides with a small amount of sample material, (7) 159*e*. Studies on the sintered body of the system UO_2-ThO_2 (III) phase relations in the system UO_2-ThO_2-O, (9) 242*a*. See Anthony, A. M.
Satalkina, M. A. See Okorokov, S. D.
Satava, V. Relation between structure and strength of set plaster suspensions, (9) 215*f*. Studies of relations between structure and strength of hardened suspensions of plaster, (10) 248*j*.
Sato, Heizaburo. Apparatus for manufacture of ceramic condenser elements, P (7) 156*f*.
Sato, Hiroshi. See Honjo, G.
Sato, Hisanao. Effects of phonon distribution on hot electrons in semiconductors, (5) 135*b*. Phonon-drag thermoelectric effect in piezoelectric semiconductors, (10) 271*b*. See Sugihara, K.
Sato, Katsuo. See Tsuji, S.
Sato, Katsuo, and Irie, T. Method of making a conductive connection to a semiconductor device electrode, P (5) 128*a*.
Sato, Kenzo. Infrared lattice vibration spectra of crystalline quartz, (11) 297*g*.
Sato, Kiyoshi. See Kunii, D.
Sato, N. See Furuichi, R.
Sato, T. Thermal transformation of alumina trihydrate, hydrargillite, (2) 58*j*.
Sauerwein, K. Principles and use of the GAMMAMAT type γ-radiography apparatus for material testing, (2) 51*a*.
Saulnier, T. A. Method of metallizing luminescent screens, P (8) 185*j*.
Saulx, C. K. de la, and Salier, N. Chimney for cooling hot gases, P (4) 105*c*.
Sauma, H. L., and Pendleton, W. W. Pyrolyzable enamel from Mn and Co chelates, glass, and siloxane resin, P (3) 65*f*.
Saunders, A. C., and Grant, J. F. Refractory body and method of making same, P (3) 73*c*, P (10) 260*c*.
Saunders, J. See Kaines, C. J.
Sauthoff, J. See Kienow, S.
Savage, A. See Miller, R. C.
Savage, R. O. See Perrotta, A. J.; Shapiro, J. R.
Savage, R. O., and Tauber, A. Growth of complex single-crystal hexagonal ferrites, (11) 296*a*.
Savage, W. E., III. Method of finishing glass, P (10) 255*h*.
Savateev, A. I. See Sil'vestrovich, S. I.
Savinskaya, A. A. See Novokhatskii, I. A.
Savitskii, E. M., Baron, V. V., Efimov, Yu. V., Karasik, B. R., Vylegzhanina, T. V., and Gladyshevskii, E. I. System V_3Si-V_3Ge, (11) 301*j*.
Sawaguchi, E. See Kikuchi, A.; Tamura, H.
Sawaguchi, E., Kikuchi, A., and Kodera, Y. Microscopic examination of $SrTiO_3$ at low temperatures, (5) 137*g*.
Sawamoto, K. Cyclotron resonance in CdS, (7) 162*a*.
Sawchuk, L. G. See Stookey, S. D.
Sawchuk, L. G., and Stookey, S. D. Glass article and method of making it, P (3) 67*f*.
Sawyer, C. B. Method for growth of pegmatitic quartz crystals in a controlled axial direction, P (3) 78*h*.
Sawyer, E. W., Jr. Foundry sand composition, P (1) 7*e*.
Sawyer, E. W., Jr., and Haden, W. L., Jr. Stabilized clay dispersions, P (11) 292*b*.
Sawyer, E. W., Jr., and Pavol, M., Jr. Inhibited clay slurry composition, P (2) 54*b*.
Sawyer Research Products, Inc. Method for growth of pegmatitic quartz crystals in a controlled axial direction, P (3) 78*h*.
Say, P. A. Method of forming a flexible seal between telescopically engageable pipe sections, P (8) 179*f*.
Saylor, D. E., and Schneider, G. P. Refractory gunning of basic oxygen furnaces, (2) 42*h*.
Scardefield, J. E. See Weller, P. F.
Scarpa, T. J. High-frequency ultrasonic [piezoelectric] generators, P (9) 231*b*.
Schachter, H. Apparatus for shredding molten mineral materials into fibers, P (11) 277*j*.
Schaedel, J. See Arndt, H. H.; Radczewski, O. E.
Schaefer, H. See Gruehn, R.
Schaefer, H., Schibilla, E., Gerken, R., and Scholz, H. Chemistry of niobium and tantalum (XXXII) reaction of tantalum with quartz, 14Ta + $5SiO_2$ = $5Ta_2Si$ + $2Ta_2O_5$, (1) 17*d*.
Schaefer, H., and Zylka, L. Chemistry of niobium and tantalum (XLVI) NbO_2I and TaO_2I, (2) 54*h*.
Schaefer, K. Automatic brick setters, (10) 256*d*. From hand setting to automatic setting, (10) 256*f*.
Schaeffler, L. See Aronson, H.
Schaevitz-Bytrex, Inc. Semiconductor strain gage transducers, P (10) 265*c*.
Schafer, C. B. See Badger, A. E.
Schaffer, P. S. See O'Connor, J. R.
Schairer, J. F. See Bailey, D. K.; Boyd, F. R.
Schampers, P. P. M. See Haan, E. F. de.
Scharrer, E., and Kober, H. Graphite suspensions, (3) 86*b*.
Schauer, S. Sifter of the circulating air type, P (7) 161*d*.
Scheible, H. G. Heater for electron tubes, P (9) 231*a*.
Scheidig, H. See Hauff, A.
Scheidler, H. See Sack, W.
Scheller, W. See Neuenschwander, E.
Schembra, F. W., Gugel, E., and Schuettig, R. Clays from the Muggenbach/Tambach deposit (Oberfranken), (3) 82*f*.
Schemmell, M. See Schwiete, H. E.
Schenck, R. T. E. Hydrated magnesium aluminate and process for preparing same, P (4) 106*c*.
Schering Akt.-Ges. Synthetic resin concretes for use as constructional building material and methods of making the same, P (7) 147*e*.
Schermerhorn, L. J. G. Terminology of mixed coarse-fine sediments, (4) 111*b*.
Schibilla, E. See Schaefer, H.
Schick, G. E. Composite titanium boride bars, P (11) 281*a*.
Schieber, M. Composition diagrams for crystal growth from molten oxides, (8) 192*f*. Crystal growth of α-Fe_2O_3 and $GaFeO_3$ by the flux method and segregation studies of Fe^{3+} in $Ga_{2-x}Fe_xO_3$ crystals, (4) 107*h*.
Schieber, M., Frankel, R. B., Blum, N. A., and Foner, S. High-magnetic-field studies of orthorhombic and rhombohedral $Al_{2-x}Fe_xO_3$ compounds, (8) 199*c*.
Schieber, M. M., Lin, C. C., and Van Vleck, J. H. Magnetic behavior of thulium garnets in a cubic field, (9) 240*c*.
Schieck, F. L. (editor). Thermodynamics of Certain Refractory Compounds (Vol. I) Sections I–VI, Discussion of Theoretical Studies; (Vol. II) Sections VII–IX, Thermodynamic Tables, Bibliography, and Property File, B (5) 142*h*.
Schiele, E. Requirements of lime and development tendencies in the technique of lime burning, (5) 116*j*.
Schieltz, J. D., and Wilder, D. R. Anomalous sintering behavior of Y_2O_3, (9) 237*f*.
Schiff, D. Broad band circular polarizer utilizing a plate of pyrolytic boron nitride, P (7) 156*g*. See Basche, M.
Schill, F., and Pitro, V. Leachable borosilicate glasses, (3) 66*j*.
Schilling, W. A. See Siekanowicz, W. W.
Schindler, P. H., Jr., and Mozelewski, E. J. Mold for ceramic casting, P (1) 9*c*.
Schink, N. Jogging device in apparatus for treating semiconductor wafers in gas, P (4) 101*a*. Method for surface treatment of semiconductor elements, P (4) 102*e*.
Schinkel, C. J., and Rathenau, G. W. Magnetic interactions in borate glasses containing manganese ions, B (2) 61*h*.
Schippert, M. A., Moll, S. H., and Ogilvie, R. E. Analytical applications of a combined electron microscope/electron microanalyzer, (10) 266*i*.
Schjeldahl, G. T., Co. Sputtering of metals wherein gas flow is confined to increase the purity of deposition, P (4) 102*h*.
Schlegel, W. New methods of manufacturing ceramic tile, (9) 228*h*.
Schlehman, G. J. See Atlas, L. M.
Schlemmer, P. S. See Bullard, R. L.
Schlesinger, J. H. Siliceous dental filling, P (10) 261*g*.
Schliesing, F. See Joyce, B. D.
Schloemer, J., and Gerloff, G. Friction material composition, P (5) 124*h*.
Schlosser & Co. G.m.b.H. Apparatus for manufacturing crystalline mineral compounds, P (2) 53*i*.
Schlotter, C. See Kopineck, H. J.
Schmahl, N. G., and Stemmler, B. Equilibria of the Mn_3O_4-Mn_2O_4-O_2 systems, (9) 239*c*.
Schmalz, R. F. Kinetics and diagenesis of carbonate sediments, (8) 201*f*.
Schmalzried, H. See Sockel, H. G.; Taylor, R. W.
Schmets, J. See Pierini, G.
Schmid, O. Expansion behavior of ceramic bodies after different high prefirings, (10) 257*h*.
Schmid, W. F., and Mooney, R. W. Copper-activated thorium phosphate phosphors, (3) 75*i*.
Schmidhammer, G. I. Basic properties influence selection of electronic ceramics, (9) 228*j*.
Schmidt, A. See Kieffer, R.
Schmidt, E. Firing of barium titanate ceramics on bats of various materials, (2) 47*b*.
Schmidt, E. R. See Pieterse, J. J.
Schmidt, J. J. See Faile, S. P.
Schmidt, O. See Keller, W.
Schmidt, P. F., and John, H. F. Simultaneous double diffusion process, P (5) 129*b*.
Schmidt, P. F., and Owen, A. E. Anodic oxide films for device fabrication in silicon (I) controlled incorporation of phosphorus into anodic oxide films on silicon, (3) 75*e*.
Schmidt, P. F., and Stickler, R. Silicon phosphide precipitates in diffused silicon, (7) 167*g*.
Schmidt, R. P. Method of making a laminated glass assembly, P (1) 6*d*.
Schmidt, T. Industrial gas burner, P (2) 53*c*.
Schmidt, W. Apparatus for grinding and polishing the edges of glass panes, mirrors, or the like, P (8) 176*e*.
Schmidtlein, J. A. Gaseous discharge lamp with internally cooled electrodes, P (7) 149*d*.
Schmitz, A. Solid semiconductor circuit with crossing conductors, P (3) 79*f*.
Schmitz, A. N. Method of coating a metal surface with a ferrite composition, P (2) 48*c*.
Schnabel, H. W. Flexible coated abrasive product, P (10) 247*f*.
Schnable, G. L., Hillegas, W. J., Jr., and Thornton, C. G. Preferential silicon epitaxy with oxide masking, (3) 76*g*.
Schneegans, M. Determination of the nature and the chemical composition of the defects of homogeneity of glasses by physical methods of analysis, (11) 276*f*.
Schneider, G. P. See Saylor, D. E.
Schneider, H. Method of producing a casting mold, P (9) 226*i*. Process for production of lost models in precision casting operations, P (8) 182*b*.
Schneider, J. F. Noble metal thermocouple having base metal compensating leads, P (9) 234*f*.
Schneider, M., and Boehm, H. P. Experiments of hydrolysis of siloxane bonds at silicon dioxide surfaces, (3) 85*i*.
Schneider, P. Fundamental study of the applicability of carbides to the construction of high-power tubes, (11) 280*h*.
Schneider, S. See Strief, M. J.
Schneider, S. J. See McDaniel, C. L.
Schnitzer, W. A. Bromophenol blue for distinguishing limestone from dolomite, (5) 130*j*.
Schoenlaub, R. A., Stone, D. A., and Blankenship, C. L. Oscillating plate calciner, (4) 105*f*.
Scholz, H. See Schaefer, H.
Scholz, S. See Nacken, M.
Scholz, S., and Lorsmacher, B. Sintered tantalum carbide bodies, P (8) 182*d*.
Scholz, W. See Naeser, G.
Scholze, H. Bubbles in glazes, (8) 128*g*. Gases and water in glass (I–III) (8) 175*c*. See Straub, F.
Scholze, H., and Galanulis, E. Dissolution of lime and dolomite particles in primary melts, (3) 66*c*.
Scholze, H., and Gliemeroth, G. Vapor measurements of $Na_2SiO_3 \cdot nH_2O$ glasses, (10) 254*a*.
Schooley, J. F. See Frederikse, H. P. R.
Schoonover, R. M. See Bowman, H. A.
Schottmiller, J. C. See Healy, G. W.
Schouwenburg, J. C. van, and Wey, A. D. van der. Unusual effect of iron in the flame-photometric determination of calcium, (2) 51*b*.
Schraeder, C. R. See Fisher, H. E.
Schramm, J. A. Method of fabricating a semiconductor device, P (2) 48*g*.
Schreiber, C. L. Display device [phototropic glass], P (9) 219*f*.
Schreiner, M. P. Isolated base four-layer semiconductor system, P (1) 11*a*.
Schreiner, W. A. See Porter, C. A.
Schreiner, W. C. See Walen, N., Jr.
Schreurs, J. W. H., and Tucker, R. F. Experimental and theoretical investigation of radiation effects in glasses, B (2) 62*b*.
Schrewelius, N. G. Heat-resistant and oxidation-proof materials, P (4) 98*j*, P (9) 225*i*. Insulating refractory brick and the production thereof, P (8) 181*e*.
Schroder, D. K. See Collins, D. R.
Schroeder, H. Coating of large glass surfaces to change the transmission of radiation, (10) 251*b*. See Shuster, E.

Schroeder, J. Incandescent lamp including a fluorine gas atmosphere and a solid fluorinating agent, P (7) 149*f*.
Schroeder, U. See Jeschar, R.
Schroll, F. Flotation process for the purification of silicon carbide, P (8) 181*c*.
Schroth, P., and Baker, B. H. Evaluation of open-hearth roof brick, (8) 179*i*.
Schuechtermann & Kremer-Baum A. G. fuer Aufbereitung. Jaw crushers, P (3) 83*d*. Screening machine, P (2) 50*c*.
Schuele, W. J. Shaped fine particle ferrites and method for their preparation, P (1) 11*g*.
Schueller, K. H. Study of porcelain texture with the optical and electron microscopes, (3) 74*e*.
Schuett, K. See Neuenschwander, E.
Schuettig, R. See Schembra, F. W.
Schuller, W. H. W. Apparatus for manufacturing slivers or yarns from glass filaments or the like, P (10) 254*b*. Continuous glass filaments, P (4) 94*b*. Continuous production of filaments, P (7) 149*a*. Manufacture of glass and like, material fibers, P (9) 220*d*. Product consisting of a body of fibers made of glass or like material fibers, P (4) 95*f*.
Schulman, J. H. Method of manufacture of miniature radiation dosimeters, P (11) 286*d*.
Schulte, K. Refractoriness under load of zones in used silica crown brick, (10) 258*d*.
Schulten, G. Passive gas cell frequency standard in the millimeter wave range, P (8) 185*f*.
Schulz, H. Viscosity of glasses, (9) 219*a*.
Schulz, K. H. See Juza, R.
Schulz, M. See Billick, I. H.
Schulz, W. P. Apparatus for coating substrates by cathode sputtering, P (3) 77*j*. Method for lowering index of refraction of glass surfaces, P (8) 178*a*.
Schumacher, H. Two-terminal pair network damping by ohmic resistors, (9) 230*d*.
Schumann, C. E. See Pritchard, W. L.
Schuppner, H. R., Jr. Joint filling composition, P (1) 2*c*.
Schurmann, K. See Hellner, E.
Schuster, E., and Schroeder, H. Degree of polarization of the fluorescence of borosilicate glasses containing uranium, (10) 251*d*.
Schuster, G. L., and Grivna, H. W. Abrasive sleeve for rotary abrading machines, P (11) 273*f*.
Schwabe, W. E., and Ciotti, J. A. Pyrometer, P (4) 105*a*.
Schwaerzler, G. Ceramic art of Ernst Loesche—exhibition in Munich, (9) 213*i*. International ceramic competition in Florence, 1966, (9) 213*j*.
Schwartz, A., Tauber, A., and Shapiro, J. R. Growth of γ-MnS crystals in sodium silicate gels, (9) 239*a*.
Schwartz, C. M. See Sclar, C. B.
Schwartz, H. S. See Schwartz, R. T.
Schwartz, M., and Mackenzie, J. D. Ionic conductivity in calcium silicate glasses, (1) 4*a*.
Schwartz, N., and Berry, R. W. Thin film components and circuits, B (11) 305*a*.
Schwartz, N., and Gresh, M. Effect of ambients and contact area on the asymmetric conduction of anodic tantalum oxide films, (9) 229*c*.
Schwartz, R. S. See Harding, W. E.
Schwartz, R. T., and Schwartz, H. S. Characteristics of boron fibers and boron-fiber-reinforced plastic composites, (5) 122*g*.
Schwartzwalder, K. See Kesten, P. N.
Schwarz, F. See Kolb, F.
Schweikert, W. H. Pyrolytic graphite coated casting mold and method of making same, P (2) 45*i*.
Schweppe, J. V. Method for producing fibers, P (2) 39*b*.
Schwerdtfeger, K. Rate of silica reduction in reducing gases at 1500°C, (7) 167*e*.
Schwerdtner, G. See Stoerr, M.
Schwertz, F. A., and Kinsella, J. J. Method for forming a thin film resistor, P (2) 48*i*.
Schwiete, H. E. Determination of thermal shock resistance by nondestructive test methods, (2) 41*a*. See Hennicke, H. W.
Schwiete, H. E., and Boehme, H. J. Errors in the measurement of the thermal conductivity of refractories due to poor temperature distribution in the specimen, (5) 122*g*.
Schwiete, H. E., and Hechler, R. W. Solid state reactions of silicate systems, B (5) 141*g*.
Schwiete, H. E., and Niel, E. Formation of new compounds at the beginning of hydration of clinker and cement, (1) 2*a*.
Schwiete, H. E., Schemmell, M., and Langauer, T. Adsorption measurements on glasses of different compositions, (10) 250*j*.
Schwindt, W. See Vescia, M.
Sclar, C. B., Carrison, L. C., and Schwartz, C. M. High-pressure metallic indium telluride—preparation and crystal structure, (3) 86*d*.
Scoledge, R. F. See Palermo, J. J.
Scoon, J. H. See Muir, I. D.
Scott, D. R. See Bordeaux, J.
Scott, G. W. Development of direct firing, (8) 174*h*.
Scott, J. A. Brazing flux and method of brazing with same, P (9) 217*b*.
Scott, J. H., Jr., and McIver, G. W. Method of fabricating a semiconductor by masking, P (4) 101*e*.
Scott, J. H., Jr., and Olmstead, J. A. Semiconductor devices having modifier-containing surface oxide [silicon oxide] layer, P (11) 287*d*.
Scott, J. J., and Turnbull, N. C. Fusion process for production of stoichiometric UO_2, P (8) 181*d*.
Scott, R. K., Leatham, E., and Einstein, E. Production of vitreous silica in a rotary kiln, P (9) 227*i*.
Scott, R. K., McCreight, D. O., Einstein, E., and Thompson, C. L. Production of vitreous silica in a rotary kiln, P (8) 182*e*.
Scott, W. J. Method of producing semiconductor devices by employing vitreous material, P (5) 128*i*.
Scott Aviation Corp. Process for preparing superoxides, P (3) 73*a*.
Scotti, V. G., Johnson, J. M., and Cunningham, R. T. Electron microprobe analysis of highly radioactive samples, B (5) 139*g*.
Scott-Monck, J. A. See Learn, A. J.
Scroger, M. G. See Chang, L. L. Y.
Scruby, S. R., and McIver, D. J. Handling of pulverulent materials, P (7) 158*i*.
Scruggs, D. M. Ductile molybdenum composition containing a spinel dispersion, P (8) 181*a*. Ductile tungsten composition containing a spinel dispersed uniformly throughout, P (8) 181*a*.
Scuderi, T. G. See Kerper, M. J.
Searcy, A. W. Underdeveloped areas in high temperature chemistry, B (5) 140*a*. See Anthrop, D. F.; Hoenig, C. L.; Munir, Z. A.
Searight, C. E., Alexander, E. M., and Ryan, J. R. High titanate glass beads, P (3) 68*b*. Method for manufacturing glass beads, P (9) 221*c*.
Searight, C. E., Alexander, E. M., Ryan, J. R., and Labino, D. Colorless high index glass compositions, P (3) 67*a*. Yellow glass bead compositions, P (3) 69*i*.
Searight, W. H. Apparatus for making glass beads, P (2) 38*c*.
Searles, J. H. See Irwin, W. T.
Sears, G. W., Jr. See Alexander, G. B.
Sears, J. H., and Benton, K. R. Apparatus [belt] for coating continuously produced filaments, P (10) 254*h*.
Secrist, D. R. Compound formation in the systems lithium-carbon and lithium-boron, (11) 292*i*.
Sedlak, B. See Blau, R.
Sedlakova, L. See Landspersky, H.
Sedmal, U. Ya. See Eiduk, Yu. Ya.
Seeger, A. Point defects in metals, B (4) 114*b*.
Seeger, A., and Jan, R. V. Radiation damage production, B (4) 114*c*.
Segal, B. B. See Kriek, H. J. S.
Segelken, W., G. See Parodi, J. A.
Segnit, E. R. Microstructure of ceramic materials (II) heavy clay products, (7) 150*j*; (III) forms of silica, (8) 180*f*; (IV) whiteware, (9) 228*e*. Mineralogy of salt glazes containing boron, zinc, and manganese, (4) 96*c*. Mineralogy of salt glazes on iron-rich clay bodies, (7) 154*j*.
Segreto, A. J. See Krause, I.
Seidensticker, R. G. See Hamilton, D. R.
Seider, R. See Warshaw, S. I.
Seifert, J. A. See Moreau, N.
Seigle, L. See Resnick, R.
Seip, H. M. Failure of the first Born approximation in electron diffraction (I) UF_6, (8) 197*i*.
Seiser, H. Heat efficiency data for the firing of porcelain in tunnel kilns with different fuels, (3) 74*b*.
Seiter, H. Ceramic resistor contacted barrier-free with noble metal, P (8) 184*d*.
Seitz, H. German pipe system—flexible layout, (1) 6*i*.
Seitzinger, V. F. Unfired-ceramic flame-resistant insulation and method of making the same, P (4) 99*d*. See Smock, A. W.
Seitz-Werke G.m.b.H. Pressure lid for filter presses, P (10) 266*g*.
Seiyama, T. See Yoshida, T.
Seki, H., and Araki, H. Thermodynamical study of the growth rate of epitaxial silicon from SiI_4, (11) 302*c*.
Sekizawa, H. See Okada, T.
Selas Corp. of America. Apparatus for forming glass beads, P (3) 67*c*. Glass tempering apparatus with resilient sheet support means, P (11) 278*c*. Industrial burner, P (8) 189*a*. Method of making a molten foamed glass, P (9) 221*i*.
Seleborg, M. See Marinder, B. O.
Self, T. J., Jr. See Highfill, C. W., Jr.
Self Organizing Systems, Inc. Electrical [solion] device with closely spaced electrodes and method for making same, P (3) 78*b*.
Selis, S. M. Kinetic study of bismuth electrodes in molten lithium chloride-potassium chloride, (8) 201*f*.
Selka, F. See Fitzer, E.
Sellers, D. J., Heuer, A. H., Rhodes, W. H., and Vasilos, T. Alumina crystal growth by solid-state techniques, (5) 134*b*.
Seltzer, M. S. Point defects in binary compounds, (9) 241*d*.
Selwood, P. G. See Rothman, S. J.
Semavina, K. P. See Bron, V. A.
Semba, K. See Miyatake, K.
Semchenko, I. A., and Stovba, N. I. Action of some electrolytes on the strength of granules in the charge, (10) 247*i*.
Semenenko, K. N. See Muratov, F. Sh.
Semenov, I. N. See Kolbin, N. I.; Matveev, M. A.
Semicon Associates, Inc. Method for impregnating tungsten dispenser cathodes, P (8) 185*c*.
Semi-Elements, Inc. Laser materials, P (11) 285*i*. Transparent magnetic glass compositions, P (8) 179*a*.
Semkina, N. V. See Bron, V. A.
Sen, P. C. Some empirical methods of evaluating the suitability of raw dolomite for use in steel melting furnaces, (8) 180*b*. See Murthy, H. P. S.
Sen, P. C., Rao, M. R. K., Dutta, A., and Rao, H. V. B. Occurrence and refractory properties of Rajasthan magnesite, (8) 189*j*.
Sen, S. See Bhushan, B.
Send, A., and Engel, K. Properties, type of construction, and life of the refractory linings of blast furnaces, (7) 152*d*.
Senderoff, S. See Mellors, G. W.
Seney, J. S. Encapsulated electrical component, P (7) 156*c*.
Senhouse, L. S., Jr., DePaolis, M. V., Jr., and Loomis, T. C. Calcium concentration vs. net ionized donor concentration in single-crystal $KTaO_3$, (5) 134*f*.
Sennett, C. T. See Elliott, R. J.
Senno, H. See Tawara, Y.
Serafin, F. G. See Dodson, V. H., Jr.
Sereda, P. J. See Ramachandran, V. S.
Sergeeva, A. E. See Kutolin, S. A.
Seria, G. See Perraudin, R.
Sermon, G. T., and Lescelius, T. J. Abrasive tools and methods of making such tools, P (7) 145*h*.
Serova, G. A. See Lukin, E. S.
Serpinsky, V. V. See Bering, B. P.
Sersale, R., and Aiello, R. Nature of hydration products present in pastes of portland, blast furnace slag, and pozzolan cements immersed for five years in potable water, (2) 34*f*.
Service (Engineers), Ltd. Method of and apparatus for drying pottery, P (11) 290*c*.
Sesana, L. Resins in the construction of molds for ceramics, (10) 261*g*.
Sestak, B. Glide and work-hardening in bcc metals, B (4) 114*c*.
Sethi, B. K. Ways and means to increase the mechanical strength of cylindrical porcelain insulators and bushings, (2) 46*h*.
Settle, J. L., Feder, H. M., and Hubbard, W. N. Fluorine bomb calorimetry (VI) enthalpy of formation of uranium hexafluoride, (8) 198*a*.
Seufert, L. E. Process for preparing hollow refractory particles, P (4) 99*a*.
Seufert, L. E., and Talsma, H. Process for forming a refractory coating on aluminum, P (7) 148*a*.
Seversky, A. P. de. Integrated mechanical filter and [wet] electrostatic precipitator system for broad spectrum purification, P (8) 186*g*. Integrated pollution control system, P (8) 186*h*.
Seward, R. P., and Field, P. E. Solubility of thallous bromide and silver chloride in molten nitrate solvents, (8) 207*g*.
Seward, T. P., III, Uhlmann, D. R., Turnbull, D., and Pierce, G. R. Transmission electron microscopy of thin glass samples, (2) 38*d*.
Seybolt, A. U. Activity of gallium in NiGa and associated gallium-gallium oxide equilibria, (3) 83*i*. See Norton, F. J.; Westbrook, J. H.
Seymour, S. L. Method of and apparatus for shaping glass sheets with opposed pressing members, P (10) 255*d*.
Shabalina, O. K., and Chufarov, G. I. Mechanism and kinetics of wustite disintegration (III), (3) 86*g*.
Shabanov, O. M. See Smirnov, M. V.
Shafer, M. W. See Ahn, K. Y.
Shafer, W. C. Method and apparatus for indication and control of fiber-forming operations, P (4) 94*f*.
Shaffer, P. C., and Stratton, K. E. Frit dispensing device, P (11) 285*c*.
Shaffer, P. D. See Stevens, S.
Shaffer, P. D., and Gaskey, R. W. Method of bending and annealing glass sheets, P (8) 177*g*.
Shafrin, E. G., and Zisman, W. A. Effect of adsorbed water on the spreading of organic liquids on soda-lime glass, (10) 251*b*.
Shah, V. K. See Natarajan, A. S.
Shakhlin, V. I., Shunin, T. G., et al. Experience with the use of heat resistant concretes in parts of open-hearth furnaces, (7) 151*b*.
Shakhlin, V. I., Tarasov, A. F., and Salmanov, G. D. Testing blocks of heat resistant concrete in soaking pit walls, (9) 225*c*.
Shakhmagon, N. V. See Budnikov, P. P.
Shakmanov, V. V. See Krokhina, A. I.
Shalek, P. D. See Baskin, Y.
Shaler, R. G. See Dohman, E. J.
Shalimo, Z. N. Microheterogeneous structure of glasses in the system SiO_2-Al_2O_3-CaO-Na_2O, B (7) 171*b*.
Shalkov, K. A. See Potemkin, P. S.
Shannon, R. D. Topotaxy in decomposition of CrO_2, (2) 59*c*.
Shannon, R. F. Fibrous acoustical panel with impregnant in rear body portion, P (10) 255*b*. Method of producing strong foamed glass bodies and structure produced thereby, P (9) 221*f*. Slurry pouring means and method, P (4) 103*j*. Transfer pallet construction, P (1) 9*d*.
Shannon, R. F., Gorski, F. T., and Zellar, W. V. Apparatus and methods for producing panels of mineral fibers, P (11) 277*i*.
Shannon, R. F., and Helser, J. L. High temperature resistant acoustical board, P (2) 44*f*.
Shapiro, J. R. See Schwartz, A.
Shapiro, J. R., Tauber, A., and Savage, R. O. Microprobe and magnetic characterization of some single crystal hexagonal ferrites, (9) 240*i*.
Shapiro, L. See Humphrey, D. E.
Shapiro, S. M., Gammon, R. W., and Cummins, H. Z. Brillouin scattering spectra of crystalline quartz, fused quartz, and glass, (9) 217*g*.

Shapochkin, V. A. Experimental apparatus for investigating the physicomechanical and heat resistance properties of refractories, (4) 96*g*.
Shaposhnikov, A. P., and Zolotov, I. N. Pipes made from fused rock, (5) 123*g*.
Sharai, V. N. See Zhunina, L. A.
Sharma, S. D. See Deo, P. G.
Sharma, S. K. See Srivastava, A. C.
Sharma, V. Productivity and the [Indian] glass industry, (8) 176*b*.
Sharonov, Yu. A., and Vol'kenshtein, M. V. Calorimetric investigation of softening and annealing of polymer glasses, B (7) 171*g*.
Sharpataya, G. A. See Sokolov, V. A.
Sharpe, C. Methods and economics for the mine and stockpile, (9) 235*e*. Smooth material flow keeps up with increased production at Chattahoochee Brick, (9) 223*c*.
Sharples, A. G. See Prenton Brick & Tile Co., Ltd.
Sharratt, E. W. See Hewitt, G. F.
Shatova, N. P. See Galdina, N. M.
Shatterproof Glass Corp. Electrostatic deposition of parting materials in method of bending superposed glass sheets, P (10) 255*a*.
Shaw, D. W. See Hendrickson, G. R.
Shaw, F., and Jones, S. P. Effect of sodium sulfate and furnace atmosphere on fining a container-type glass, (1) 3*i*.
Shaw, H. J. See Lean, E. G. H.
Shaw, R. K. See Cleland, R. L.
Shaw, R. R., and Heasley, J. H. Superparamagnetic behavior of $MnFe_2O_4$ and α-Fe_2O_3 precipitated from silicate melts, (7) 156*d*.
Shaw, S. E. See Wilkinson, J. F. G.
Shchedrovitskii, Ya. S. See Ryabchikov, I. V.
Shcheglov, S. I., and Zaikina, V. D. Effect of industrial factors on the compaction of forsterite shapes, (7) 151*j*.
Shchegrov, L. N., Mondin, L. Ya., Gol'tseva, V. S., Ryadchenko, A. G., and Skrobotun, V. N. Reactivity of magnesium oxide of different pseudostructures, (11) 300*i*.
Shchekotikhina, N. M. See Zaliznyak, D. V.
Shcherbak, T. I. See Azarov, K. P.
Shcherbina, V. V. See Urusov, V. S.
Shea, P. L., Jr. See Martin, S. W.
Sheindlin, A. E. See Kirillin, V. A.
Shelby, J. E. See Steinkamp, W. E.
Sheldon, F. R., Kibbel, W. H., Jr., and Kressbach, J. E. Clay bleaching, P (3) 83*b*.
Sheldon, G. J. Apparatus for producing optical fiber, P (2) 38*i*. Fiber glass orifice, P (3) 67*c*. Method of confining and surfacing end portions of optical fiber bundles for maximum light transmission, P (4) 94*h*. See Royka, S. F.
Shelimova, L. E., and Abrikosov, N. K. System Sn-Te in the region of the compound SnTe, (11) 301*h*.
Shelkovnikov, B. A. Russian glass in the second half of the nineteenth century, (11) 274*e*.
Shell International Research Maatschappij N. V. Stripping oil for structures and objects made from mixtures containing mortar, clay, and brick, P (11) 280*c*.
Shelyubskii, V. I. Investigation of crystallization of titanium-containing glasses with the aid of specimens of variable composition, B (9) 246*d*. Study of crystallization of vitreous systems by using variable-composition samples, (8) 176*c*. Study of microcrystallization of photosensitive glasses by the method of variable-composition samples, (8) 176*g*. See Vaisfel'd, N. M.
Shen, C. Y., and Herrmann, R. A. Hydration of sodium tripolyphosphate by water vapor, (2) 46*c*.
Shenango Ceramics, Inc. Recuperator tubes, P (7) 154*a*.
Shepard, A. O. Ceramics for the Archaeologist, B (4) 112*j*.
Shepherd, C. F. Suction-type grinding mill, P (8) 190*i*.
Shepherd, R. See Anderson, J. T.
Shequen, W. G. See Abelmann, R. A.
Sherby, O. D. Mechanical strength and deformation, B (9) 244*f*.
Sherer, A. I., and Ruzicka, J. Etching composition and method of etching, P (4) 94*c*.
Sherr, A. E. Water resistant plasters, P (10) 249*d*.
Sherrill, F. A. See Young, F. W., Jr.
Sherwood, R. C. See MacChesney, J. B.
Shestopalov, N. F. Automatic return for tunnel kiln cars, (5) 132*c*.
Shevelevich, R. S. Investigations of the structure of glass fibers by microwave spectroscopy, B (9) 245*h*.
Shevtsova, Z. N. See Safonov, V. V.
Shevyakov, A. M. See Kuznetsova, G. N.
Shewchun, J., and Wei, L. Y. Germanium-silicon alloy heterojunctions, (4) 100*g*.
Shewmon, P. G. Surface self-diffusion at high temperatures, B (9) 245*f*.
Shiau, Y. G. See Chu, Chih-wei; Liu, Chun-yang.
Shiau, Y. G., Liu, Chun-yang, and Chin, Hsue-wen. Investigations of the dual function of electronic-acidic catalyst (IV) isomerization reactivity and surface property of the catalyst platinum on silica alumina, (1) 15*f*.
Shibata, A. See Yoshimatsu, M.
Shibata, K. See Horiuchi, S.
Shibata, S., Niimi, Y., and Matsumae, T. Spectrophotometric determination of nickel with 1-(2-pyridylazo)-2-naphthol (PAN) and simultaneous determination of nickel and manganese, (5) 138*i*.
Shields, T. W. Carbonaceous ramming paste, P (5) 124*d*.
Shiffer, S. O. Automated tile handling system, P (8) 182*j*.
Shikano, H. See Miyatake, K.; Nishino, T.
Shikazono, N. See Nasu, S.
Shilo, V. P. See Kolomiets, B. T.
Shimada, K. See Sugita, K.
Shimada, T., and Kikuchi, T. Neutron irradiation effects of electrical properties in vitreous carbon, (10) 271*f*.
Shimazaki, T. See Oomori, K.
Shimizu, S. See Kachi, S.
Shimizu, Tadao. Ruby laser with external mirrors of large spacing, (11) 300*f*.
Shimizu, Tsuneo. Determination of trace quantities of scandium in silicate rocks by a combined ion exchange-spectrophotometric method, (5) 131*a*.
Shimizu, Y., and Funaki, K. Properties of trihydrates obtained by aging alumina gel in aqueous solutions, (1) 27*i*.
Shimizu, Y., Ishijima, I., and Funaki, K. Supplementary note on the mechanism of conversion of alumina gel to crystalline alumina hydrate, (2) 56*j*.
Shimizu, Y., Mitsui, N., and Funaki, K. Study on rehydration of amorphous alumina, (1) 29*j*.
Shimizu, Y., Miyashige, S., and Funaki, K. Study on the aging of alumina gel, (2) 56*a*.
Shimoda, S. Mineralogical studies on garnierite and aquacreptite, (9) 241*a*. X-ray study of the crystal structure of aquacreptite, (9) 243*c*.
Shimohira, T. See Tagai, H.
Shimohira, T., and Tagai, H. Orientation of crystals of lead antimonate and titanate on the surface of aluminum porcelain enamel, (5) 117*f*.
Shimomura, Y. See Nagamiya, T.
Shimomura, Y., Saito, S., and Minamigawa, S. Preliminary electron microscope observations on NiO bombarded by ions or electrons, (4) 109*h*.
Shimony, U. See Gosselin, J. P.
Shinada, H. See Goto, E.
Shinada, M., and Sugano, S. Optical absorption edge in layer-type semiconductors, (10) 271*g*.
Shinko, J. S. See Cranch, G. E.
Shinoda, G. See Umeno, M.
Shinozaki, S. See Honjo, G.
Shiojiri, T. See Miwa, H.
Shionoya, S. See Nagasawa, M.
Shioura, Y. See Yoshida, T.
Shiozawa, Ken-ichi. See Kikuchi, T.
Shiozawa, M. See Muta, A.
Shipley, L. H. Tin coating of copper surfaces by replacement plating, P (5) 129*d*.
Shipley Co., Inc. Tin coating of copper surfaces by replacement plating, P (5) 129*d*.
Shira, W. S. Screen tensioning device, P (5) 130*c*.
Shiraishi, A. See Naruse, Y.
Shiraki, Y. Studies on clay-water systems (III-5) cracking of clay during steady heating in a water-saturated atmosphere; (III-6) imbibitional swelling properties of the clay-water system, (7) 168*f*. Studies on roseki (II) relation between specific surface area and ceramic properties of the nonsericite roseki (pyrophyllite) used for wall tile bodies, (7) 160*i*. Studies on slip casting (VIII) effect of specific base-exchange cations on the casting properties of pottery bodies; (IX) effect of coagulants on the casting properties of alkaline casting slips, (7) 155*c*.
Shiraki, Y., and Inoue, A. Studies on roseki (I) comparison of thermal properties between compact and wet ball-milled roseki (pyrophyllite), (7) 160*h*.
Shiraki, Y., and Otsuka, N. Properties of Fukui pottery stone, (5) 125*j*.
Shiraki, Y., Otsuka, N., and Ogawa, Kazuo. Orientation of clay particles (II) studies on the texture of green bodies of suspension insulators, (5) 125*i*.
Shiraki, Y., Otsuka, N., and Urushido, H. Effect of particle size distribution on the properties of Nishiyama pottery stone, (5) 125*g*.
Shirane, G., Cox, D. E., Takei, W. J., and Ruby, S. L. Study of the magnetic properties of the $FeTiO_3$-α-Fe_2O_3 system by neutron diffraction and the Moessbauer effect, (4) 110*g*.
Shirasaki, S. See Kubo, T.
Shirn, G. A. See Janus, A. R.; Miller, N. C.; Smyth, D. M.
Shishkin, K. N., and Pakhmura, N. G. Study of the classification of ground chamotte in an air stream, (9) 224*i*.
Shmaevskii, V. E. Physical properties of a solid solution in $ZnCdSb_2$, (11) 299*i*.
Shmidt, Yu. A. See Dubrovo, S. K.
Shoda, S. See Yasui, E.
Shonkwiler, F. P. See Hansen, K. W.
Shono, Y. See Yoshida, T.
Shorr, N. Traction rolls and material handling apparatus employing such rolls, P (8) 179*c*.
Short, J. M., and Roy, R. Diffusion in defect crystalline solutions in the systems CaF_2-YF_3 and NaF-LiF-MgF_2, (8) 194*h*.
Shortes, S. R. Electrical interconnections, P (9) 230*d*.
Shpirt, M. Ya. See Kuznetsov, V. G.
Shriver, T., & Co., Inc. Plate self-shifter for filter presses, P (5) 130*c*.
Shtopko, V. M. See Kocho, V. S.
Shubina, T. S. See Radovskii, I. Z.
Shulishova, O. I. Approximate method for the calculation of crystal lattice energies, (5) 134*c*.
Shull, C. G. Neutron diffraction, B (8) 211*j*.
Shull, J. D., Jr. Gypsum product, P (9) 215*g*.
Shul'ts, M. M. Potentialities of the electrode method for studying glass structures, B (9) 246*b*. See Nikol-skii, B. P.
Shul'ts, M. M., Peshekhonova, N. V., Parfenov, A. I., Belyustin, A. A., and Bobrov, V. S. Electrode properties and chemical nature of glass, B (4) 113*h*.
Shumilin, A. A. See Potemkin, P. S.
Shunin, T. G. See Shakhlin, V. I.
Shurling, B. E., and Millman, N. Stabilized pigment slurries, P (3) 83*c*.
Shurtz, R. F. Mathematics of mine sampling, (4) 106*b*.
Shurygin, P. M., and Boronenkov, B. N. Kinetics of reaction of magnesia, silica, and alumina with melts of the ternary system CaO-SiO_2-Al_2O_3, (8) 201*i*.
Shutov, Yu. M. See Kolbin, N. I.
Shveikin, G. P. See Dubrovskaya, L. B.
Shvets, E. A. See Kuz'ma, Yu. B.
Shyam, M. See Allen, J. W.
Sias, C. B. See Park, R. E.
Siddiqi, A. J. See Trew, V. C. G.
Sidorenko, F. A. See Korshunov, V. A.; Radovskii, I. Z.
Sidorko, V. R. See Lukashenko, G. M.
Sidorov, T. A. Molecular interpretation of the boric oxide anomaly, B (9) 245*f*.
Sieckmann, J. See Hennicke, H. W.
Siegelman, A. See Coulter, W. H.
Siegmund, W. P. Method of making fiber optical image transfer device, P (1) 6*b*.
Siekanowicz, W. W., Schilling, W. A., and Bardash, I. Reciprocal latched ferrite phase shifter, P (11) 287*a*.
Siemens & Halske Akt.-Ges. Apparatus for crucible-free zone melting of crystalline rods, particularly of semiconductor rods, P (3) 77*a*. Apparatus for producing semiconductor devices, P(3) 77*b*. Apparatus for vapor deposition of silicon, P (11) 284*h*. Ceramic resistor contacted barrier-free with noble metal, P (8) 184*d*. Epitaxial method of producing semiconductor members using a support having varyingly doped surface areas, P (3) 78*g*. Ferromagnetic manganese-zinc ferrite of high permeability and its preparation, P (11) 285*c*. Metallizing the surfaces of a ceramic body, P (2) 48*c*. Method and apparatus for growing monocrystalline layers on monocrystalline substrates of semiconductor material, P (3) 78*f*. Method and apparatus for producing semiconductor material, P (7) 157*b*. Method and apparatus for vapor deposition of patterns on a carrier surface, P (3) 78*f*. Method of precipitating crystalline layers of highly pure brittle materials, P (11) 286*f*. Method of producing monocrystalline layers of silicon on monocrystalline substrates, P (9) 231*a*. Method of producing monocrystalline silicon of high purity, P (9) 231*b*. Method of producing pure semiconductor material by chemical transport reaction using H_2S/H_2 system, P (3) 79*e*. Method for producing semiconductor devices, P (11) 286*i*. Method for producing a semiconductor with pn junction, P (3) 79*e*. Method of producing semiconductors by diffusion, P (7) 157*i*. Method for the production of semiconductor dendrites, P (5) 128*j*. Methods and apparatus for forming semiconductor materials, P (7) 157*a*. Preparation of crystalline semiconductors, P (3) 79*a*. Preparation of monocrystalline semiconductor materials, P (9) 231*k*. Preparation of sintered ferromagnetic ferrite bodies, etc., P (10) 265*f*. Pressure sensitive semiconductor device, P (8) 185*i*. Process and apparatus for producing elongated, particularly tape-shaped, semiconductor bodies from a semiconductor melt, P (3) 79*a*. Process for the metallization of the surfaces of ceramic bodies, P (3) 75*c*. Process for producing ferrite cores having rectangular hysteresis loops and long switching constants, P (5) 128*j*. Process for producing a metal coating on a ceramic body, P (10) 250*f*. Process for producing tape-shaped semiconductor bodies, P (3) 79*c*. Process for the production of doped semiconductor materials, P (9) 232*e*. Process of pyrolytically growing epitaxial semiconductor layers upon heated semiconductor substrates, P (11) 287*f*. Process for pyrolytically precipitating elemental semiconductor substance, P (11) 287*g*. Semiconductor product and method for making same, P (9) 232*b*. Treatment of semiconductor components, P (8) 186*d*. Zone melting of silicon rods, P (10) 266*h*.
Siemens-Planiawerke Akt.-Ges. fuer Kohlefabrikate. Carbon bodies, P (9) 225*b*. Contact layer for a silicon-containing material, P (5) 127*e*. Method for producing a contact layer on a silicon-containing material, P (1) 8*b*.
Siemens-Schuckertwerke Akt.-Ges. Apparatus and method of producing semiconductor rods by pulling from a melt, P (4) 100*f*. Apparatus for producing highest-purity silicon for electric semiconductor devices, P (10) 263*b*. Apparatus for producing pure semiconductor material [by vapor deposition], P (11) 284*h*. Apparatus for production of fine-crystalline boron phosphide, P (1) 7*b*. Apparatus for pyrolytic precipitation of semiconductor material from a gaseous compound thereof, P (3) 77*c*. Controllable semiconductor devices with a negative current-voltage characteristic and method of their manufacture, P (9) 230*a*. Doped semiconductor process and

products produced thereby, P (8) 184*h*. Electrically insulating compositions, P (2) 47*d*. Electronic semiconductor device, P (1) 10*b*. Electronic semiconductor device of the four-layer junction type, P (1) 10*c*. Encapsuled [monocrystalline] semiconductor device with lapped surface connector, P (1) 10*c*. Encapsuled semiconductor with alloy-bonded carrier plates and pressure maintained connectors, P (1) 10*d*. Galvanomagnetic semiconductor device, P (8) 184*c*. Halogen doped Bi_2Te_3-Bi_2Se_3-As_2Se_3 thermoelectric composition, P (7) 156*f*. Jogging device in apparatus for treating semiconductor wafers in gas, P (4) 101*a*. Method and apparatus for crucible-free zone melting, P (7) 156*j*. Method of crucible-free zone melting, P (11) 280*e*. Method for determining the electrical resistance of a body of extremely pure semiconductor material for electronic purposes, P (8) 185*c*. Method for heat-treating of monocrystalline semiconductor bodies, P (8) 185*d*. Method of producing crystalline boron phosphide, P (11) 286*g*. Method of producing crystalline semiconductor material on a dendritic substrate, P (11) 286*h*. Method for production of semiconductor devices, P (2) 48*c*. Method for surface treatment of semiconductor elements, P (4) 102*e*. Methods of preparing semiconducting substances, P (10) 265*a*. Multilayer junction semiconductor devices such as controlled rectifiers and transistors containing electropositive protective coating, P (8) 185*d*. Process and apparatus for pyrolytic production of pure semiconductor material, preferably silicon, P (2) 49*b*. Process of open-type diffusion in semiconductor by gaseous phase, P (8) 186*a*. Process for the production of crystalline semiconductor material, P (7) 157*h*. Process for the production of an oxide coating on a substantially monocrystalline body of semiconductor material, P (9) 232*f*. Process for the production of a *p*-doped zone in a body of semiconductor material, P (8) 186*b*. Process for the production of sintered semiconducting thermoelectric materials, P (7) 157*h*. Process for the production of thin semiconducting layers from semiconducting compounds, P (3) 79*c*. Process for use in the production of a semiconductor device, P (1) 11*d*, P (8) 186*c*. Process using an oxygen free electrolyte for doping and contacting semiconductor bodies, P (9) 232*f*. Semiconductor device with pressure maintained nonbonded connectors, P (1) 11*f*. Semiconductor devices with terminal contacts and method of their production, P (3) 79*e*. Semiconductor *pn* junction devices and method for their manufacture, P (4) 102*f*. Thermocouples, P (2) 53*d*.

Siempelkamp, E. Heatable presses, P (1) 12*g*.

Sievers, A. J. See Aring, K.

Sigariov, A. M. See Bannikov, G. K.

Sigler, J. E. Epitaxial method for the production of microcircuit components, P (9) 230*f*.

Signode Corp. Elastic protective corner and tensioning strips for transportable brick packages, P (10) 256*f*.

Sigvaldason, O. T. Influence of testing machine characteristics on the cube and cylinder strength of concrete, (11) 275*d*.

Silcoa Products, Inc. Patching composition containing polyvinyl and epoxy resins with hydraulic cement, P (10) 249*b*.

Silika- und Schamotte-Fabriken, Martin & Pagenstecher Akt.-Ges. Process for the manufacture of refractory bricks and materials, P (5) 125*a*.

Silver, T. J. Method of and apparatus for compacting ferrite particles, P (1) 11*b*.

Silverio, A. See Atkins, A. G.

Silverman, M. S. Polymorph of calcium disilicide and its method of preparation, P (8) 190*d*.

Silvernail, W. L. Process for producing rare earth containing glass polishing agents, P (7) 150*d*.

Silvestri, V. J., and Fang, F. Incorporation of zinc in vapor grown gallium arsenide, (4) 100*b*.

Sil'vestrovich, S. I., Kazakov, V. D., and Savateev, A. I. Mechanism of two-stage strengthening of glass, (10) 252*d*.

SIMAB. See Societe Industrielle des Materiaux Blancs.

Simanov, Yu. P. See Aslanov, L. A.; Komissarova, L. N.; Kovba, L. M.

Simautics, Inc. Device for orienting bottles, P (11) 278*d*.

Simeoni, P. Continuous kiln for brick, etc., P (10) 268*f*.

Simison, A. L. Method and apparatus for treating and packaging strands of filaments, P (1) 5*g*.

Simko, F. A., Jr. See Bergna, H. E.

Simmingskold, B. See Lakatos, T.

Simmler, W. Organic siloxanes and silicon groups as bonding agents between glass and plastic materials, (9) 216*e*.

Simmons, C. E. Continuous muller with adjustable mulling wheels and plow means, P (9) 233*b*.

Simmons, J. G. See Frank, R. I.

Simmons, J. H. W. See Perks, A. J.

Simon, G. See Potocnik, K.

Simon, R. See Leroy, P.

Simon, R. A. See Adler, M. D. W.

Simons, L. See Black, H. R.

Simplicity Engineering Co. [Centrifugal] crusher mechanism, P (10) 269*j*. Crusher apparatus, P (4) 106*a*.

Simplimatic Engineering Co. Apparatus for transporting cylindrical articles, P (1) 12*j*.

Sims, H. A. See Dohmen, H. G.

Sinclair, A. G. Method and apparatus for forming mineral wool products, P (10) 255*j*.

Sinclair Research, Inc. Hydrocarbon conversion process and catalytic contact material therefor, P (8) 190*f*. Method for the manufacture of catalytically active clay, P (11) 282*d*.

Sinden, A. D. Apparatus for handling bulk materials, P (1) 12*i*.

Sing, K. S. W. See Lucas, J. W.

Singer, E., and Runge, W. Quasi-industrial studies on plastic raw materials, (8) 186*g*.

Singer, J., Jr. See Gallagher, T. J.

Singh, G. See Uppal, H. L.

Singh, S. Orthopyroxene-bearing rocks of charnokitic affinities in the South Savanna-Kanuku complex of British Guiana, (7) 166*e*.

Singleton, E. L. See Iverson, H. G.

Sinha, A. P. B. See Sabane, C. D.

Sinha, B. C. See Bhattacharya, S. K.

Sintsova, I. T. See Avgustinik, A. I.

Sipovskii, D. P., Makarova, T. A., and Fedoseev, A. D. Study of the crystallization conditions of fibrous amphibole in hydrothermal synthesis, (10) 272*g*.

Sirazhiddinov, N. A. See Toropov, N. A.

Sircar, A. See Doss, R. N

Sirdeshmukh, D. B. See Babu, V. H.

Sirera, S. B. Machine for the manufacture of asbestos cement pieces, P (5) 116*i*.

Sirgo, V. H., and Richards, J. L. Method of producing gallium phosphide in crystalline form, P (5) 128*h*.

Sirhal, H., and Kastanek, J. Changes in the physical-mechanical properties of the ceramic body during the firing process as a basis for determining the optimum firing rate, (4) 105*c*.

Sir John Gallwey & Partners, Ltd. Detection of moisture in materials, P (3) 81*d*.

Sirkis, M. D. See Holonyak, N., Jr.; Stillman, G. E.

Sironi, G. See Colombo, U. P.

Sirrine, R. Growth of $(Ga_xIn_{1-x})As$ single crystals by vapor phase reaction, (3) 86*c*.

Sirtl, E. Epitaxial method of producing semiconductor members using a support having varyingly doped surface areas, P (3) 78*g*. Method of producing monocrystalline silicon of high purity, P (9) 231*b*. Method of producing pure semiconductor material by chemical transport reaction using H_2S/H_2 system, P (3) 79*e*. Process of pyrolytically growing epitaxial semiconductor layers upon heated semiconductor substrates, P (11) 287*f*. See Dersin, H.; Grabmaier, J.

Siryak, A. I. See Belyavskaya, L. M.

Sistiaga, J. M. See Maria Sistiaga, J.

Sizmann, R. See Hidalgo, P. J.

Sizov, I. D. See Gubko, I. T.

Skalny, J. See Grzymek, J.

Skansen, T. See Jensen, P.

Skapski, A. C. See Rogers, D.

Skelliett, A. M. Field effect transistor with a junction parallel to the (111) plane of the crystal, P (4) 101*f*.

Skinner, D. D. See Thompson, J. H.

Skinner, H. A. Key heat of formation data, (8) 201*f*.

Sklar, M. See Deal, B. E.

Sklyarenko, L. I. See Eremenko, V. N.

Skoblo, L. I. See Il'ina, N. V.

Skogerboe, R. K., Heybey, A. T., and Morrison, G. H. Oxyhydrogen flame excitation of refractory elements, (2) 50*i*.

Skorobogatova, I. V. See Ermolaeva, E. V.

Skowron, H. M. Workpiece handling apparatus, P (11) 279*h*.

Skrebtsov, A. M. See Kostyuk, V. A.

Skrifvars, B., and Ringbom, A. Stepwise photometric titrations, (1) 14*e*.

Skrivan, J. F. See Di Stefano, V. N.

Skrobotun, V. N. See Shchegrov, L. N.

Skudnova, E. V., Karaseva, T. P., and Mirgalovskaya, M. S. System In-Sb-Zn, (4) 111*g*.

Skulikidis, A., Megalopoulos, A., and Barafakas, Ch. Mechanism of sorption of molecular colloids on solids (IV) sorption of Congo red on alumina, (3) 86*h*.

Skurcenski, A. See Sterry, J. P.

Skytronics, Inc. Moisture proof connector for spark plugs, P (10) 265*c*.

Slagle, O. D. Deformation mechanisms in polycrystalline graphite, (11) 293*i*.

Slate, F. O., and Matheus, R. E. Volume changes on setting and curing of cement paste and concrete from 0 to 7 days, (3) 64*h*.

Slavnova, G. K. Polymorphism of In_2Se_3, (1) 27*a*. See Luzhnaya, N. P.

Slavnova, G. K., and Eliseev, A. A. X-ray investigation of melts of indium-selenium, (2) 60*e*.

Sleight, A. W. Crystal structure of $Nb_{16}W_{18}O_{94}$, a member of a $(MO)_xMO_3$ family of compounds, (10) 270*j*.

Sleighter G. E. Method of heating glass sheets, P (3) 68*d*. See Chisholm, R. S.; Fredley, J. C.; Hess, A. R.

Sliker, T. R., and Roberts, D. A. Thin-film CdS-quartz composite resonator, (11) 284*e*.

Slip Pruf Service Corp. Process for slip-proofing glazed ceramic surfaces, P (8) 183*b*.

Slivinskii, I. G. See Ginzburg, D. B.

Sloan, H. B. Tantalum carbide incandescent lamp and manufacture thereof, P (2) 49*b*.

Smakota, N. F. See Belyaev, G. I.

Smallbone, A. H. See Abelmann, R. A.

Smallen, H. See Epstein, G.

Smalley, A. K. See Ervin, G., Jr.

Smeltzer, W. W. See Hussey, R. J.; Madeyski, A.; Roeder, G. A.

Smidth, F. L., & Co. Apparatus for the heat treatment of finely divided materials, P (7) 160*d*. Crushing and grinding plant, P (10) 269*d*. Defibering of asbestos and like materials, P (1) 12*e*. Grinding cement clinker, P (3) 64*e*. Manufacture of cement, P (9) 215*h*. Methods of and plants for burning cement, P (8) 174*f*.

Smiley, W. D. Tungsten carbide compositions, method, and cutting tool, P (4) 89*g*.

Smiley, W. D., and Wilder, A. G. Process of infiltrating diamond particles with metallic binders, P (3) 63*f*.

Smirnov, M. V. See Kudyakov, V. Ya.; Usov, P. M.; Volodin, V. P.

Smirnov, M. V., Krasnov, Yu. N., Khazemov, F. F., and Kamarov, V. E. Instability constants of fluoride complexes of lanthanum in molten LiCl-KCl mixtures, B (1) 30*c*.

Smirnov, M. V., and Loginov, N. A. Thermodynamics of some reactions of titanium chloride in a molten NaCl-KCl mixture, B (1) 30*b*.

Smirnov, M. V., and Ryzhik, O. A. Equilibrium between molybdenum and molybdenum ions in molten lithium chloride, B (1) 30*b*.

Smirnov, M. V., Tsiovkina, L. A., and Oleinikova, V. A. Processes occurring on platinum and nickel cathodes during electrolysis of molten carbonates, B (1) 30*d*.

Smirnov, M. V., Usov, P. M., Lbov, V. S., and Shabanov, O. M. Electrical conductivity and transport numbers in the $LaCl_3$ + La system, B (1) 30*c*.

Smirnova, E. K., Vasil'kova, I. V., and Kudryashova, N. F. Enthalpy of formation of the chloroniobates and chlorotantalates of rubidium and cesium, (7) 163*i*.

Smirnova, E. V. Infrared and ultraviolet spectra of certain glasses and crystalline silicates in the system PbO-SiO_2, B (9) 245*f*.

Smirnova, I. N. See Kislyakov, I. P.

Smirnova, K. A. See Matveev, M. A.

Smit, J. Magnetism, B (9) 244*e*.

Smith, A. B. See Fessler, T. E.; Grace, M. I.

Smith, A. L. Process for preparing lanthanum, yttrium, or lutetium phosphate phosphors, P (9) 232*b*.

Smith, A. O., Corp. Corrosion resistant metal members, P (1) 3*c*. Method and apparatus for fusing a coating to a metal surface, P (2) 35*d*.

Smith, A. W. See Criscione, J. M.

Smith, D. A. See Macmillan, N. H.

Smith, D. F. Plaster of Paris bandage, P (8) 174*f*. Plaster of Paris product [bandage] and process improvements, P (2) 35*b*.

Smith, D. K. Nonexistence of yttrium zirconate, (1) 23*j*

Smith, D. W. See Ranby, P. W.

Smith, E. Interaction between two coplanar dislocation-type cracks, (1) 20*f*.

Smith, E. C. See McCormick, W. R.

Smith, E. L. See Hurley, E. B.

Smith, F. G. Computation and plotting of liquidus isotherms in multicomponent silicate systems, (7) 162*i*.

Smith, F. H. Illuminating apparatus for a microscope system using polarized light, P (1) 14*d*.

Smith, G. I. See Eugster, H. P.

Smith, G. V. See Bicknell, R. W.

Smith, H. L. See Mackey, J. H.

Smith, J. A. Compacting press with selective ejection, P (11) 288*h*.

Smith, J. G. Method for making metal oxide microspheres, P (7) 153*a*. Uranium dioxide sol process, P (7) 154*e*. Uranium dioxide-zirconium dioxide sol preparation, P (7) 154*f*. See Fitch, F. T.; Flack, H. P.

Smith, J. G., and Fitch, F. T. Uranium trioxide-zirconium dioxide sol process and product, P (9) 227*j*.

Smith, J. G., and Flack, H. P. Method for making metal oxide microspheres, P (8) 190*i*.

Smith, J. M. See Adams, N.

Smith, J. P. See Taylor, A. W.

Smith, J. S., II. See Mazdiyasni, K. S.

Smith, J. V. X-ray emission microanalysis of rock-forming minerals (II) olivines, (2) 59*g*; (VI) clinopyroxenes near the diopside-hedenbergite join, (10) 272*f*. See Gibbs, G. V.; Howie, R. A.; Ribbe, P. H.

Smith, J. V., and Ribbe, P. H. X-ray emission microanalysis of rock-forming minerals (III) alkali feldspars, (2) 59*i*.

Smith, L. W., Estes, J. F., Cowles, R. J., and Bruchmann, H. Prosthetic parts and methods of making, P (8) 183*a*.

Smith, M. C. Longitudinal tensile behavior of H4LM graphite in nitrogen to 2750°C, (8) 201*h*.

Smith, M. W. See Ward, T. D.

Smith, N. O. Chemical Thermodynamics—A Problems Approach, B (11) 303*j*. See Callanan, Sister J. E.

Smith, R. E. Apparatus for forming and collecting filaments, P (10) 254*h*. See Nitsche, J. E.

Smith, R. E., and Klink, J. P. Apparatus for forming and collecting filaments, P (3) 67*b*.

Smith, R. G. See Freeman, I. L.

Smith, R. M., and Wells, L. J. Glass aerosol bottles and method for making, P (2) 38*f*.

Smith, R. P. Solubility of niobium carbide in gamma iron, (5) 138*e*.

Smith, R. W. Activation of beryl and feldspars by fluoride in cationic collector systems, (4) 105*j*.

Smith, R. W., and Fuller, M. Alpha hematite—stable remanence and memory, (9) 237*e*.

Smith, T. Diffusion coefficients and anion vacancy concentrations for the zirconium-zirconium dioxide system, (11) 293*b*. Mechanism of the oxidation of zirconium in oxygen and liquid sodium, (9) 240*g*. Mechanism of the reduction of adsorbed oxygen on zirconium dioxide with hydrogen, (5) 137*f*. Zirconium dioxide-oxygen reactions (I) molecular oxygen adsorption with electron transfer; (II) chemisorption of atomic oxygen, (7) 169*f*.
Smith, T. P. Packaged electronic device, P (8) 185*e*.
Smith, W. A., and Mason, T. R. Heated glass cathodes in electrostatic beam separators, (1) 13*f*.
Smith, W. J. Electrical humidity sensing element, P (3) 81*d*.
Smith, W. L. See Spencer, W. J.
Smock, A. W., and Seitzinger, V. F. Radiant heat reflective coatings and method for application, P (2) 35*f*.
Smock, G. E., and Fulk, W. F. Process for producing integrated body of multifilament strands, P (4) 95*d*.
Smoke, E. J. See Arlett, R. H.
Smolik, T. J., Harman, and Fuerstenau, D. W. Surface characteristics and flotation behavior of aluminosilicates, (4) 106*g*.
Smoot, T. W. Method of making partially stabilized zirconia, P (4) 89*h*. See Troell, P. T.
Smoot, T. W., and Cook, M. D. Method of *in situ* fabrication of a monolith refractory lining, P (3) 72*j*.
Smothers, W. J. See Herron, R. H.; Kreglo, J. R., Jr.; Ulmer, G. C.
Smothers, W. J., and Chiang, Y. Handbook of Differential Thermal Analysis, B (1) 30*g*.
Smucker, C. A., and Stalego, J. P. Phenolic resole-bone glue-urea-diluent extender binder composition for bonded mat, P (9) 221*j*.
Smutny, Z. See Brezny, B.
Smyrnos, G. J. Crystal oven heating and control system, P (4) 100*j*.
Smyth, D. M., and Shirn, G. A. Capacitor with dielectric film having phosphorus-containing component therein, P (5) 127*b*.
Smyth, D. M., Shirn, G. A., and Tripp, T. B. Heat-treatment of anodic oxide films on tantalum(III) conductivity profile, (4) 100*g*.
Snape, E., and Beeley, P. R. Refractory-melt reactions in vacuum induction melting of nickel-base alloys, (8) 180*i*.
Sneed, R. B., and Moore, H. Sulfides speed flint glass fining, (9) 218*h*.
Sneed, R. J. See Krikorian, F.
Snellman, R., and Cunningham, J. L. Brick for improved service life in certain ferruginous environments, P (8) 180*e*.
Snethorst, A. C. J. M. See Meyst, G. J.
Snetsinger, K. G. See Keil, K.
Snitchler, L. C. Lenses for focusing infrared utilizing elements of silicon and of zinc sulfide, P (5) 120*f*.
Snitzer, E., and Osterberg, H. Optical resonant cavities, P (5) 121*c*.
Snow, E. H. See Deal, B. E.; Mead, C. A.
Snow, H. A. Cable-type stone cutting saw, P (4) 89*f*.
Snow, J. D. See Berstickler, A. C.
Snow Diamond Products, Inc. Cable-type stone cutting saw, P (4) 89*f*.
Snyder, F. H. Ceramic product and process. P (2) 46*c*.
Snyder, H. C. See Poole, J. P.
Sobolev, V. M. See Kotelnikov, G. R.
Societa per Azioni Ing. Filippo & Carlo Tassara. Process for repairing refractory structures, particularly the interior surfaces of industrial furnaces, and the materials used, P (11) 282*h*.
Societe Alsacienne de Constructions Mecaniques. Method for making thermocouples, P (1) 11*d*.
Societe Anonyme Babbittless. Gyratory crushers, P (5) 133*b*.
Societe Anonyme Glaverbel. Apparatus for manufacturing glass ribbon on a molten metal bath, P (8) 176*f*. Apparatus for and process of annealing glass as it is being drawn upwardly, P (3) 67*e*. Apparatus and process for refining glass and for continuously manufacturing sheet glass, P (9) 219*h*. Apparatus for the rapid replacement of the bending roll in sheet glass drawing machines, P (7) 149*h*. Furnaces for working materials such as glass, P (9) 220*b*. Glass manufacture, P (8) 177*d*. Gray glass composition, P (4) 94*i*. Heater panel, P (8) 177*g*. Manufacture of flat glass, P (8) 177*a*. Manufacture of glass ribbon, P (8) 177*a*, P (10) 255*h*. Manufacture of sheet glass, P (4) 94*c*. Method and apparatus for drawing glass strips off of a molten metal bath, P (10) 255*j*. Method of and apparatus for the production of a fire-polished glass strip, P (9) 221*a*. Method and apparatus for the recovery of heat from glass furnaces, P (8) 177*f*. Method of and device for the protection of barriers in glass furnaces, P (10) 255*f*. Method and plant for drawing a glass strip, P (8) 178*h*. Method and tank furnace for glassmaking, P (8) 178*i*. Process and apparatus for heating molten materials, P (2) 39*j*. Process and apparatus for the manufacture of flat glass on a molten metal bath, P (5) 121*e*. Process and arrangement for the continuous manufacture of sheet glass, P (8) 178*f*. Process and arrangement for the continuous manufacture of sheet glass on a molten metal bath, P (8) 178*g*. Process and arrangement for heating glass sheets with a view to subsequent thermal treatment, P (9) 222*d*. Process and arrangement for the protection of glass during the thermal treatment thereof, P (3) 69*a*. Process and device for casting articles of refractory material, P (10) 260*c*. Process and plant for manufacturing flat glass on a molten metal and solid support bed, P (9) 222*a*. Protective salt bath for a glass ribbon, P (4) 95*f*.
Societe Anonyme de Machines Electrostatiques. Electrostatic coating process and apparatus, P (9) 233*c*. Electrostatic powder application, P (9) 233*d*. Electrostatic spraying [gun] apparatus, P (8) 174*j*. Spray-coating apparatus, P (1) 13*b*.
Societe d'Electro-Chimie, d'Electro-Metallurgie et des Acieries Electriques d'Ugine. Process for making an anhydrous alumina product consisting principally of alpha alumina from alumina hydrate, P (11) 282*d*. Process for production of hydrofluoric acid from sulfuric acid, fluorspar, and anhydrite, P (4) 107*c*. Process for the production of molybdenum dioxide, P (11) 292*a*.
Societe Fives Lille-Cail. Improvements in rotary kilns and analogous chemical reactors, P (7) 160*c*.
Societe Francaise de Ceramique, Service Technique et Industriel. Possibilities of using the Rheomat 15 coaxial cylinder viscometer in the ceramic industry, (7) 159*b*.
Societe Francaise de l'Electro-Resistance. Electrical resistance coatings and their manufacture, P (11) 285*e*.
Societe Francaise de Produits Hypo-Metallurgiques, Societe la Magnesienne, Societe des Produits Industrielles et Magnesiens du Roussilon, and Blondel, R. C. M. F. Refractory linings for metal furnaces and their application, P (3) 73*e*.
Societe Grenobloise d'Etudes et d'Applications Hydrauliques. Process and apparatus for the sorting of two or more materials, P (4) 103*i*.
Societe Hispano-Suiza Lallemant. Friction linings and their production, P (5) 124*f*. Friction linings especially for aircraft brakes, P (10) 250*d*.
Societe Industrielle des Materiaux Blancs. Microporous chalk mortar composition, P (9) 215*j*.
Societe Industrielle des Silicones. Mold release agent, P (1) 13*a*.
Societe des Lieges des Hamendas et de la Petite Kabylie. Mosaic tile assembly, P (10) 261*f*.
Societe la Magnesienne. See Societe Francaise de Produits Hypo-Metallurgiques.
Societe Nationale d'Etude et de Construction de Moteurs d'Aviation. Process for ensuring noncorrosive contacts on heating rods, P (2) 53*b*.
Societe Nouvelle des Etablissements Emile Muller. Rotary kiln for firing chamotte, P (11) 290*h*.
Societe de Produits Chimiques d'Auby. Process for treating plaster and the products, P (7) 147*c*.
Societe des Produits Industrielles et Magnesiens du Roussilon. See Societe Francaise de Produits Hypo-Metallurgiques.
Societe du Verre Textile. Manufacture of structural clay products, P (5) 122*c*.
Societe des Verreries Industrielles Reunies du Loing. Apparatus for melting glass, P (2) 38*f*. Cathode ray tube envelope, P (7) 149*j*. Manufacture of glass, P (11) 278*f*.
Society of Glass Technology, Chemical Analysis Committee. Determination of sodium oxide in soda-lime-silica glasses by flame photometry, (10) 251*i*.
Society of Glass Technology, Chemical Durability Committee. Comparison of two methods for testing the resistance of grains of glass to attack by water, (5) 118*c*.
Sockel, H. G., and Schmalzried, H. Role of phase boundaries during reaction between single crystals of various oxides, B (2) 61*c*.
Soderquist, R., and Jansson, S. X-ray and electron microscope study of precipitates formed by the hydrolysis of iron(III) in 0.5*M* NaCl ionic medium, (10) 272*d*.
Soffer, B. H. See Pastor, A. C.
Soga, N., and Anderson, O. L. High-temperature elasticity and expansivity of forsterite and steatite, (7) 164*c*.
Sokolov, I. N. See Butenko, V. A.
Sokolov, V. A., and Sharpataya, G. A. Small-size calorimeter for determining specific heat at low temperatures—specific heat of potassium chloride, (9) 234*a*.
Sokolova, E. I. See Gurovich, N. A.
Sokolova, T. D. See Nisel'son, L. A.
Solar, Z. Arch insulation of glass melting furnaces, (10) 256*h*.
Soldatov, G. A., Levitskii, V. K., Khainson, A. M., Kuznetsov, V. V., and Spektor, M. P. Drying mettlach (floor) tile in radiation driers, (3) 73*i*.
Solinov, F. G. See Fondymakin, B. I.
Solitron Devices, Inc. Semiconductor device, P (9) 232*a*.
Solodovnikov, A. O. See Lobanov, E. M.
Solomon, A. L. See Feuersanger, A. E.
Solov'ev, I. F. See Solov'eva, M. E.
Solov'eva, M. E., and Solov'ev, I. F. Operating tunnel kilns with natural gas, (8) 189*a*.
Solumeta. Preparation of metal or silicon oxides, P (3) 72*e*.
Solvay & Cie. Manufacture of dense sodium carbonate, P (3) 83*d*.
Somayaji, K. N. See Subramanian, T. V. A.
Somiya, S. Bursting phenomena of chromium-bearing refractories (I, II), (7) 151*d*.
Somiya, S., Okikawa, S., and Saito, Shinroku. Thermal expansion and electrical resistance of sintered bodies in the system ZrO_2-CeO_2, (8) 209*j*.
Sommer, A. See Leibowitz, D.
Sommer, C. Plaster mortars, P (11) 275*g*.
Somogyi, A. See Locsei, B.
Somogyi, T. R. See Lombos, B. A.
Sonntag, A. See Ginsbach, K. H.
Sonoco Products Co. Forming tube for glass fibers, P (9) 220*b*.
Sony Corp. Cathode ray tube having metallic layer of nonuniform thickness, P (11) 284*j*. Method of making a cathode ray tube, P (10) 264*i*.
Sooy, W. R. See Aplet, L. J.
Sorbie, T. B. Inspecting glass containers having rounded top finishes, P (9) 220*b*.
Soref, R. A. See Carleton, H. R
Soria Santamaria, F. Physicochemical reactions of the system refractory-clinker in cement kilns, B (2) 62*e*.
Sorkin, E. S. Thermal expansion and structure of crystallizing glass, B (9) 246*e*.
Sormberger, R. L. See Cusano, D. A.
Sorokin, P. P. Lasers, P (5) 120*f*.
Sorokina, M. F. See Nemnonov, S. A.
Soseliya, L. D. See Kutateladze, K. S.
Sostman, H. E. Resistance thermometers, (1) 14*c*.
Sotome, Y. See Hayashi, T.
Soubier, L. D., and Swain, A. B., Jr. Method of and apparatus for producing nonthermal currents in a body of molten glass, P (3) 68*j*.
Soubrier, J. L. See Carbonisation Entreprise et Ceramique.
Soule Steel Co. Process and apparatus for manufacturing mosaics, P (4) 100*a*.
South African Council for Scientific and Industrial Research. Piezoelectric transducers, P (1) 11*a*.
Southam, F. W. See Rapson, B.
Southgate, P. D. Internal friction due to chromium and iron in magnesium oxide, (8) 200*g*.
South of Scotland Electricity Board and McGlashen, R. Method of and apparatus for enameling baths and other hollow articles, P (3) 65*c*.
Southwest Enterprises, Inc. Process for producing iron oxide pigments, P (11) 291*i*.
Southwestern Portland Cement Co. Method of grinding and cooling cement, P (11) 275*e*.
Sowards, D. M. See Hailstone, R.; Lewis, G. L.
Sowman, H. G. Molybdenum fiber reinforced alumina, P (9) 226*e*.
Soyck, W. Ceramic insulators for railroad traffic systems, (9) 228*b*.
Space Age Materials Corp. Continuous method of manufacturing ablative and refractory materials, P (3) 72*f*.
Sparks, D. J. See Franklin, A. D.
Sparrow, L. R. See Comado, S. J.
Sparrow, L. R., and Braiman, J. Glass-bonded mica encapsulated tantalum capacitor, P (4) 101*k*.
Spear, B. W. Cathode-ray tubes, P (10) 254*h*. See Minneman, L. C.; Powell, D. E.
Spears, D. M. Resonant and antiresonant vibratory members attached to a crystal, P (8) 186*c*.
Spector, M. L. See Heinemann, H.
Spedding, P. L., and Mills, R. Trace-ion diffusion in molten alkali carbonates. (11) 302*g*.
Speed, R. C., Nash, D. B., and Nickle, N. L. Lunar X-ray diffraction experiment, B (5) 139*j*.
Speerschneider, C. J. Beryllide coating for beryllium, P (4) 92*d*.
Speidel, D. H. Evaluation of quantitative electron microprobe analyses of multiphase microcrystalline refractory materials, B (5) 139*g*. Phase equilibria in the system MgO-FeO-Fe_2O_3—1300°C isothermal section and extrapolations to other temperatures, (7) 166*j*.
Speigel, K. See Heck, R. F.
Speiser, R. See Adelsberg, L. M.
Spektor, M. P. See Soldatov, G. A.
Speliotis, D. E. See Bate, G.
Spellman, J. E. Diamond reinforced coatings and method of preparing same, P (4) 89*g*.
Spembly, Ltd. Electric furnaces, P (4) 105*d*.
Spence, G. M. Hardening a cement mixture, P (5) 116*h*.
Spence, Peter, & Sons, Ltd. See Peter Spence & Sons, Ltd.
Spencer, C. D. Process for cavity wetting, P (11) 289*b*.
Spencer, E. G. See Lenzo, P. V.
Spencer, W. J., and Smith, W. L. Defects in natural quartz, (1) 17*b*.
Spenke, E., and Welker, H. Method of producing crystalline semiconductor material on a dendritic substrate, P (11) 286*h*.
Speranskaya, E. I., and Arshakuni, A. A. System bismuth oxide-germanium dioxide, (7) 168*e*.
Speransky, B. J. See Lasch, C. A., Jr.
Sperling, H. G. See Killpatrick, J. E.
Speros, D. M., and Woodhouse, R. L. Quantitative differential thermal analysis apparatus, P (8) 188*e*.
Sperry, P. R. See Heine, M. A.
Sperry Rand Corp. Masking device, P (10) 264*f*. Method of making fiber optic frequency responsive device, P (10) 255*h*.
Spex Industries, Inc. Remote control system for a spectroscopic wavelength computer, P (1) 14*e*.
Spicer, W. E. Effect of electromagnetic radiation, B (9) 244*e*.
Spiegler, J. Enclosed electronic device, P (11) 285*i*.
Spielmann, W. See Michl, L.
Spielmann, W., and Heywang, W. Process for producing tape-shaped semiconductor bodies, P (3) 79*c*.

Spielmann, W., Ziegler, G., and Heywang, W. Process and apparatus for producing elongated, particularly tape-shaped, semiconductor bodies from a melt, P (3) 79*a*.
Spielmann, W. K. See Liebmann, W. K.
Spiess, Dr., G.m.b.H. See Dr. Spiess G.m.b.H.
Spiess, H. G. Semidry preparation and hot steam forming with fast drying, (8) 179*g*.
Spiteri, Y. Automatic hydrocarbon feeding device for continuous furnace and movable fire chambers, P (10) 268*j*.
Spitsyn, V. I. See Komissarova, L. N.; Kovba, L. M.
Spitzer, R. H., Manning, F. S., and Philbrook, W. O. Generalized model for the gaseous, topochemical reduction of porous hematite spheres, (9) 239*i*.
Spivak, G. V. See Krokhina, A. I.
Spohn, E. Processes for the burning of materials, P (5) 117*b*.
Spoor, W. J., and Burggraaf, A. J. Strengthening of glass by ion exchange (III) mathematical description of the stress relaxation after ion exchange in alkali aluminosilicate glasses, (2) 37*b*.
Sporkenbach, G. A. Tunnel-kiln construction critically reviewed, (3) 82*a*.
Sprague, J. W. See Dyer, H. N.
Sprague Electric Co. Capacitor process, P (1) 10*i*. Capacitor with dielectric film having phosphorus-containing component therein, P (5) 127*b*. Ceramic with metal film via binder of copper oxide containing glass, P (3) 77*d*. Electric circuit elements, P (9) 230*d*. Electrical resistor and the like, P (3) 78*a*. Electrolytic capacitor comprising glass-to-metal and resilient pressure seal combination, P (9) 230*f*. Method of making a mica paper capacitor, P (10) 264*b*. Method of making semiconductive devices by means of a carrier gas with impurities, P (11) 286*j*. Method of preparing lead and alkaline earth titanates and niobates and coating method using the same to form a capacitor, P (10) 264*h*. Process of coating a silicon semiconductor with indium using an ion beam, P (3) 79*a*. Semiconductor method and device, P (11) 287*e*.
Sprang, P. G. See Rosen, S.
Spremulli, P. F. See Bell, A. N.
Sprengers, J., Stauttener, C. F., and Glabbeek, C. H. van. Method of covering a glass wall portion of a cathode-ray tube, P (3) 68*c*.
Spriggs, R. M. See Vasilos, T.
Spriggs, R. M., Brissette, L. A., Rossetti, M., and Vasilos, T. Method of monitoring pressure sintering procedures, P (1) 11*g*.
Spriggs, R. M., Vasilos, T., and Brissette, L. A. Grain size effects in polycrystalline ceramics, B (2) 61*g*.
Spriggs, R. S. See Learn, A. J.
Springer, R. H., and Anderson, D. E. Barium vapor activation of oxide cathodes, (3) 75*g*.
Sprokel, G. J., and Fairfield, J. M. Diffusion of gold into silicon crystals, (9) 238*f*.
Sprout, Waldron & Co., Inc. Apparatus for mixing particulate materials, P (11) 288*f*. Attrition mill apparatus, P (1) 15*e*, P (4) 106*i*. Mixer, P (8) 186*f*.
Sprung, S. Chemical and mineralogical composition of cement kiln dust, (7) 146*c*.
Spurny, Z. See Novotny, J.
Spyridelis, J., Delavignette, P., and Amelinckx, S. Direct observation of the superlattices of Ta_2O_5 and Nb_2O_5 in the electron microscope, (9) 238*i*.
Srinivasan, N. R. Development of clay pozzolan industry (I) survey of pozzolanic clays of India, (8) 174*a*. See Ghosh, R. K.
Srivastava, A. C., and Sharma, S. K. Heat transfer due to the flow between two infinite plates (one rotating and the other fixed) under a transverse magnetic field, (8) 199*f*.
Srivastava, S. N. P. Limestone in Hazaribagh district, Bihar, (8) 189*h*.
Srp, O. O., and Geyer, N. M. Protective coating requirements and recent developments, B (5) 140*c*.
Stacey, M. H. See Ray, N. H.
Stachiw, J. D. Dome-shaped glass housing for deep submergence undersea lights, (10) 251*a*.
Stackpole Carbon Co. Electrographitic brush, P (2) 43*j*.
Stadelmaier, H. H., and Derbyshire, S. W. Variation of dielectric constant and spontaneous strain with density in polycrystalline barium titanate, B (2) 61*d*.
Stadler, A. See Jaenicke, W.
Stadnyk, B. I. See Kuz'ma, Yu. B.
Stadnyk, B. I., and Samsonov, G. V. Thermocouples for measuring high temperatures, (4) 104*f*.
Staerk, K. Piezoelectric ceramics, (9) 229*f*.
Staerker, A. Process for making corrosion-resistant products, P (3) 72*h*.
Stagg, M. G. See Turnbull, J. A.
Stahl, D. See Taylor, K. M.
Stahl- und Walzwerke Rasselstein/Andernach Akt.-Ges. Process and apparatus for casting a liquid film from plastic dispersions, solutions, or emulsions, especially on metal sheets or strips, P (5) 117*e*.
Stalego, C. J. Apparatus for producing fibers from heat-softenable material, P (2) 38*g*. Method and apparatus for flowing streams of heat-softened material from a supply, P (7) 149*i*. See Day, F.
Stalego, C. J., Leaman, H. E., Roberson, C. L., and Roth, R. W. Method of making hollow glass fibers, P (2) 39*h*.
Stalego, J. P. Fibrous glass [decorative] binder, P (10) 255*b*. See Smucker, C. A.
Staley, W. G., Jr. See Greer, R. T.
Stal'gorova, O. V. See Voronov, F. F.
Stalnecker, S. G., Jr. Electroless copper plating on ceramic material, P (4) 101*d*.
Stamboliev, H. T., Stojanov, R., and Sapunov, P. Metasomatic albite-granitoid in the Ograzden mountains (Jugoslavia)—an important ceramic raw material, (3) 82*j*.
Stamenkovic, H. Determining absorption and moisture in aggregate and moisture in a fresh concrete mass, (11) 274*j*.
Stamicarbon, N. V. Device for wet screening a mixture of fine solid particles suspended in a liquid, P (2) 50*a*.
Stamos, C., Reeves, P. C., and Wender, J. D., Jr. Method and apparatus for removing moisture from material by sonic or ultrasonic energy in combination with centrifugal energy, P (9) 233*e*.
Standage, A. E., and Gani, M. S. Reaction between vitreous silica and molten aluminum, (3) 65*c*.
Standard Oil Co. Attrition resistant solid catalysts, P (11) 28*h*. Fibrous reinforcing materials having improved surface characteristics, P (1) 4*j*. Glass lined vessels, P (1) 5*e*. Lightweight structural units and method for producing, P (1) 5*i*. Mold apparatus for forming glass lined vessels, P (3) 69*f*.
Standard Telephones & Cables, Ltd. Bonding of metals to ceramic materials, P (2) 35*i*. Ceramic-metal seals, P (10) 263*d*. Method of etching and contacting semiconductor elements, P (8) 185*c*. Production of ferrimagnetic ceramic materials, P (4) 102*i*. Semiconductor devices, P (5) 129*c*.
Stanesa, E. See Black, H. R.
Stanke, W. Conveyor, P (3) 80*a*.
Stanton, J. H. See Dugger, D. L.
Star Dental Mfg. Co., Inc. Combination bladed bur diamond drill, P (7) 145*f*.
Staring, B. J. Burner control system, P (9) 234*i*.
Starks, D. F., Hough, R. L., and Golf, L. C. Surface finishes for boron filaments, (1) 2*j*.
Staroste, E. See Ruedl, E.
Statham, K. E. Semiconductor devices and methods of making same, P (5) 129*c*.
Statni vyzkumny ustav silnoproude elektrotechniky. Integrated two transistor semiconductor device, P (8) 184*i*.
Stauffer, R. A. See Allen, L. R.
Stauffer Chemical Co. Catalytic chlorination of beryllium from the ore, P (5) 124*e*.
Stauttener, C. F. See Sprengers, J.
Stautz, K. See Buntenbach, F.
Steatit-Magnesia Akt.-Ges. Burners for gaseous fuel, P (3) 82*b*. Paraelectric ceramic for high voltage capacitors, P (10) 265*d*. Process for firing ferrites of manganese and zinc to the equilibrium state, P (10) 265*h*.
Steatite & Porcelain Products, Ltd. Insulators, P (2) 46*c*.
Stebbins Engineering & Mfg. Co. Building block and its use in a wall, P (1) 6*i*.
Stecco S. A. de Technique Chimique. Grinding methods and apparatus, P (2) 50*a*.
Stedham, M. E. C. Control of the moisture content in clay, P (7) 160*i*.
Steeb, S., and Renner, J. Investigation of the structure of the tantalum suboxides TaO_y-(Ta_2O_5) by electron diffraction, (11) 297*d*.
Steele, B. R., Ware, J. O., and Oldfield, B. W. Permeability measurements as a means of characterizing powder compacts, B (7) 169*j*.
Steele, F. N., and Douglas, R. W. Observations on the absorption of iron in silicate and borate glasses—correction, (5) 119*h*.
Steele, W. A. See La Grange, L. D.
Steerup, J. Photoluminescent composition consisting essentially of boric acid and fluorescein, P (3) 79*i*.
Steetley Refractory Brick Co., Ltd. Refractory bricks, P (10) 260*f*. Refractory furnace linings, P (10) 260*h*. Silica brick, P (10) 260*i*. Tar-bonded dolomite refractories, P (10) 261*a*.
Stefanov, G. Production of sanitary ware and facing ceramics in Bulgaria, (11) 283*i*.
Stefanov, S. Silicon carbide saggers for the porcelain industry, (9) 224*g*.
Steigelman, H. A. See Carl, D. G.
Steil, W. W. Welded terminal resistor, P (10) 265*i*.
Steimer, A. Industrial ceramic kiln heated by a combustible liquid, P (5) 132*e*.
Stein, H. A. See Mason, J. H.
Stein, H. N. See Gelsing, R. J. H.
Stein, H. N., and Stevels, J. M. Influence of silica on the hydration of $3CaO \cdot SiO_2$, (1) 19*i*.
Stein, John G., & Co., Ltd. See John G. Stein & Co., Ltd.
Stein, J. L. Lightweight castable refractory composition, P (11) 281*h*.
Stein, J. L., and Koeneman, M. H. Suspended refractory construction, P (11) 283*c*.
Stein, R. See Vand, V.
Steinberg, J. C., and Gray, K. R. Process for producing portland cement compositions, P (10) 249*c*.
Steinberg, M. A. Atomistic viewpoint in materials applications, B (9) 244*f*.
Steiner, C. See Diller, R. E.
Steinkamp, W. E., Shelby, J. E., and Day, D. E. Internal friction of mixed-alkali silicate glasses, (7) 148*i*.
Steinmaier, W. See Bloem, J.
Steinrisser, F. Bakeout procedure for small glass ultrahigh-vacuum systems, (9) 217*f*.
Steinwerke Feuerfest Karl Albert G.m.b.H. Method of manufacturing lightweight refractory bricks, P (3) 72*j*, P (9) 226*h*. Process for making refractory cements with high clay content and the products obtained, P (11) 282*e*.
Stemmler, B. See Schmahl, N. G.
Stenborg, W. D. See Brown, G. N.
Stepanov, G. K. See Arkhipov, G. G.; Klevtsov, L. P.; Moiseev, G. K.
Stepanov, G. K., and Trunov, A. M. Electroreduction of oxygen in molten carbonates, B (1) 30*e*.
Stepanova, A. A. See Zhuravlev, N. N.
Stephanoff, N. N. Method and apparatus for drying wet pulverulent material in a gaseous path, P (11) 288*h*. Method and means for pulverizing and drying solids, P (8) 190*b*.
Stephens, C. See Gereth, R.
Stephens, J. D., and Tuddenham, W. M. Infrared studies of quartz-kaolin-microcline reactions, (9) 224*e*.
Stephens-Adamson Mfg. Co. Apparatus for handling bulk materials, P (1) 12*i*.
Stephenson, N. C. Crystal structure of a sodium molybdenum bronze, (9) 237*h*.
Sterbutzel, G. A. Surface temperature measuring device, P (9) 234*f*.
Sterling, H. F., and Drake, C. F. Method of masking semiconductor and etching beneath mask, P (5) 128*d*.
Sterman, S. Binding aid for gold trim on glass, P (3) 67*i*.
Stern, D. R., and Gundzik, R. M. Process for treating a gaseous mixture containing titanium dioxide, P (7) 161*b*.
Stern, K. H. Conductance of glass immersed in molten salts, (9) 217*j*.
Stern, K. H., and Meador, S. E. Electrode potentials in fused systems (X) measurement of cation concentration in molten salts using glass membrane electrodes, (3) 66*h*.
Stern, K. H., and Stiff, J. A. Electrode potentials in fused systems (VII) effect of ion size on membrane potentials, (7) 163*e*.
Stern, K. H., and Weise, E. L. High temperature properties and decomposition of inorganic salts (I) sulfates, (5) 136*d*
Sternberg, J. C. Fragmentation apparatus for characterization of sample compositions, P (9) 234*d*.
Sternheim, G. See Bertozzi, G.
Sterry, J. P., and Skurcenski, A. Refractory fibers and methods of making them, P (7) 154*e*.
Stetser, D. A., and DeMaria, A. J. Optical spectra of ultrashort optical pulses generated by modelocked glass: Nd lasers, (10) 271*g*.
Stettinius, K. E. Gyratory grinder, P (11) 288*i*.
Stevels, J. M. Recent trends in glass research, B (2) 62*a*. See Gelsing, R. J. H.; Stein, H. N.
Stevens, S., and Shaffer, P. D. Method and apparatus for bending glass sheets, P (5) 120*h*.
Stevens, T. J. See Majumdar, N. C.
Stevenson, C. K. Glass bending furnace with burner blast guide tubes, P (11) 278*h*.
Stevenson, D. A. See Zupp, R. R.
Stevenson, J. A. Control of glass melting furnaces—temperature measurement with platinum thermocouples, (1) 13*g*. See Brown, J. F. W.
Stewart, D. G. See Gasson, E. J.
Stewart, D. R., Rindone, G. E., and Dachille, F. Heats of solution, density, and refractive index changes in sodium borate glasses subjected to high pressure, (10) 252*h*.
Stewart, M. M. See Kehl, W. L.
Stewart, R. F. See Argue, G. R.
Stewart, R. W., and Cutler, I. B. Effect of temperature and oxygen partial pressure on the oxidation of titanium carbide, (5) 135*a*.
Stichting Reactor Centrum Nederland. Method for directly preparing granular uraniferous material having definite particle size, P (10) 259*f*. Preparation of practically spherical granular uranium-containing material, P (4) 98*j*.
Stickler, R. See Booker, G. R.; Knopp, A. N.; Schmidt, P. F.
Stickney, T. M. See Anderson, A. R.
Stickney, W. A. See Town, J. W.
Stiegler, R. W., Jr. See Bergman, H. P.
Stieler, A., and Hildebrand, H. Electrical and magnetic enrichment of ceramic raw materials, (5) 132*i*.
Stiff, J. A. See Stern, K. H.
Stiles, A. B. Catalyst aggregates of crystallites, P (8) 180*g*.
Stiles, V. E. Hydrogen zeolite Y having improved hydrothermal stability, P (3) 83*c*.
Stilley, G. W., and McKelvey, H. E. Method of heating glass sheets, P (3) 68*d*.
Stillman, G. E. See Holonyak, N., Jr.
Stillman, G. E., Sirkis, M. D., Rossi, J. A., Johnson, M. R., and Holonyak, N., Jr. Volume excitation of an ultrathin single-mode CdSe laser, (9) 243*e*.
Stirland, D. J. Investigation of matched cleavage faces of sodium chloride crystals, (1) 20*b*.
Stirland, D. J., and Campbell, D. S. Use of matching cleavage faces of sodium chloride in the study of thin-film growth, (8) 211*b*.
Stirling, H. T. Reclamation of material, P (9) 233*d*. See Ferer, H. D.
Stirling Sintering Co. Reclamation of material, P (9) 233*d*.
Stiteler, E. C. Ladle valve arrangement with stationary plug and slidable nozzle, P (7) 153*g*.
Stobbs, J. J. Cracking and carbon pickup in the oxide formed on uranium in carbon dioxide at 650°C, (11) 293*c*.

Stoch, L. Corrosion of refractories by molten silicate glass as the solid dissolution process, (1) 7*a*. Effect of mineralogical composition on some technological properties of kaolinitic clays, (1) 15*c*.
Stochl, V. See Dubansky, A.
Stock, D. F., and Hauth, C. R. Development of prescription furnace linings, (10) 257*f*.
Stockdale, G. F. See Layton, M. M.
Stockdale Engineering, Ltd. Rotary drum filters, P (1) 13*a*.
Stocker, B. J. See Hall, R. F.
Stoddard, S. D., and Nuckolls, D. E. Tungsten slip casting method, P (9) 227*i*.
Stoddard, S. V., Hardy, J. F., and Gridley, P. F. Tar-bonded refractories containing pine tar, P (11) 283*d*.
Stoecker, H. J., and Naoumidis, A. Hexagonal uranium nitride, (8) 199*b*.
Stoerr, M. See Baburek, J.
Stoerr, M., and Schwerdtner, G. Mineralogical and technological studies of kaolin from Kemmlitz in Saxony, (2) 53*j*.
Stojanov, R. See Stamboliev, H. T.
Stokes, R. J. See Day, R. B.; Liu, T. S.
Stolnitz, D. See Flatley, D. W.
Stone, D. A. See Schoenlaub, R. A.
Stone, E. O. Hermetically encased electroluminescent display device, P (8) 184*f*.
Stone, P. L. See Wallace, T. C.
Stone, R. L., and Burress, G. T. Thermocouple for DTA, P (4) 105*b*.
Stong, G. E. Method of producing composite semicrystalline articles, P (9) 221*d*.
Stookey, K. W. Refractory heat exchangers, P (8) 189*d*.
Stookey, S. D. Method of making synthetic mica bodies, P (9) 221*a*. See Sawchuk, L. G.
Stookey, S. D., and Sawchuk, L. G. Transparent devitrified strengthened glass article and method of making it, P (2) 40*b*.
Stoops, R. F. Liquid phase extrusion for forming refractory materials, P (8) 181*f*.
Stora Kopparbergs Bergslags A. B. Means for protecting internally lined exhaust openings of rotary furnaces, P (4) 105*f*.
Storey, C. Testing for service, (11) 281*g*.
Storks, K. H. See Loomis, T. C.
Storm, J. Properties of spray dried bodies for dry pressing, (5) 129*h*.
Stout, N. D. See Hoenig, C. L.
Stovba, N. I. See Semchenko, I. A.
Stover, E. R. Method of forming a carbon body, P (2) 44*j*.
Stowe, R. A. See Mayer, R. P.
Stowe, R. A., and Reynolds, J. B. Process for production of magnesium hydroxide and calcium chloride, P (4) 107*e*.
Stowell, M. J. See Pashley, D. W.
Stoyell, L. A., and Redline, H. S. Refractories, P (9) 227*a*.
Stradtmann, J. See Troemel, G.
Straehle, W. T. See Mandle, R. M.
Strange, R. R., and Haw, S. G. Frangible ceramic test mold, P (4) 98*f*.
Strasser, A. See Taylor, K. M.
Strasser, R. von. Box of Schackert porcelain, (11) 273*i*.
Stratton, K. E. See Shaffer, P. C.
Straub, F., and Scholze, H. Effect of saturated steam on the strength of stoneware, (3) 73*j*.
Straub, G., and Kocsis, Z. Effect of radioactive irradiation on semiconductors (I) effect of neutron irradiation on *n*-germanium, (1) 18*g*.
Straumanis, M. E. See Krumme, J. P.
Straumanis, M. E., and Kim, C. D. Growth of As_2O_3 on GaAs, (7) 155*j*. Solid solubility in the system GaSb-GaAs, (9) 242*h*.
Straumanis, M. E., Welch, G. E., and James, W. J. Disintegration of iron and steel while dissolving in acids, (4) 91*i*.
Strausberg, S. Conversion of U_3O_8 to UC, P (8) 180*j*.
Strauss, A. J. See Melngailis, I.
Strauss, K. Ancient stoneware from Muskau (Oberlausitz, East Germany), (1) 1*h*. Exhibition of old Austrian folk majolica in Castle Gobelsburg near Krems, (1) 1*i*.
Street, G. B. See Roberts, A. L.
Street, R. S. See Gardener, E. R.
Strekalovskii, V. N. See Bessonov, A. F.; Tkachenko, E. V.
Strekalovskii, V. N., Beketov, A. R., and Vlasov, V. G. Density and structure of uranium oxides with compositions between UO_3 and U_3O_8, B (1) 30*f*.
Strekalovskii, V. N., Bessonov, A. F., Ust'yantsev, V. M., and Burov, G. V. Study of ceramic material by high-temperature X-ray analysis, B (1) 30*f*.
Strekalovskii, V. N., Burov, G. V., and Ozeryanaya, I. N. X-ray investigation of the products of corrosion of some alloys in molten carbonates, B (1) 30*f*.
Strelets, V. M., Pitak, N. V., Kulik, A. I., and Logachev, M. S. Life of zircon nozzles for continuous steel casting, (4) 97*f*.
Strelov, K. K., and Bessonov, A. F. Classification of pores in refractories, (9) 223*f*.
Strel'tsina, M. V. See Totesh, A. S.
Strickland, G. See Tuthill, E. J.
Strickland-Constable, R. F. See Claxton, K. T.
Strief, M. J., Peart, L. T., and Schneider, S. Cermet resistance elements and terminal and tap connections therefor, P (9) 230*j*.
Stringer, R. K. Accuracy of volume measurement by mercury displacement, (4) 104*b*.
Stringfellow, A. E. Ceramic arc plates having minimum density variations, P (2) 47*i*.
Strobel, K. Development of a fully automated transport installation for tunnel kiln cars, (3) 81*j*.
Strobel, O. Geological surveys around Tirschenreuth—kaolin deposits, (3) 82*g*.
Stroehlein & Co. Method and apparatus for determining the surface area of finely divided substances by gas adsorption, P (4) 104*j*.
Stroiwas, E. See Clock, G. E.
Strong, H. M. Apparatus and method of controlling pressure, P (3) 80*c*. Thermocouple pressure gage, P (10) 268*d*.
Strong, H. M., and Tuft, R. E. Pattern diamond growth on diamond crystals, P (5) 128*d*.
Strong, S. L., and Kaplow, R. Elimination of incoherent X-rays with diffracted beam monochromators, (1) 13*j*.
Stroud, C. E. Manufacture of multiple glazing units, P (1) 5*j*.
Stroud, D. E. See Fletcher, E.
Stroud, R. C., and Hesson, H. J. Thermocouple assembly, P (1) 14*g*.
Struk, L. I. See Kharchenko, V. K.
Strutz, C., Jr. See Rudolph, R. R.
Strutz, Carl, & Co., Inc. See Carl Strutz & Co., Inc.
Strutz, F. C. See Rudolph, R. R.
Stuart, R. E. See Alexander, G. B.
Stuart, W. I., and Whateley, T. L. Adsorption of water and carbon dioxide on beryllium oxide, (7) 161*j*.
Stubican, V. S. See Barry, T. L.; Greskovich, C.; Menezes, I. de.
Stubican, V. S., and Viechnicki, D. Grain boundary precipitation in oxide systems, (1) 19*e*.
Stucki, F. F. Ferrimagnetic pressure transducer, P (5) 127*c*.
Stueber, C. Use of ultrasonic impulse method for the nondestructive testing of high tension insulators, (8) 182*j*.
Stuijts, A. L., and Oudemans, G. J. Ceramic forming methods, B (7) 170*c*.
Sturcken, E. F., Gettys, W. E., and Bohn, E. M. Substructure measurements by statistical fluctuations in X-ray diffraction intensity, B (5) 139*e*
Sturge, M. D., Merritt, F. R., and Remeika, J. P. Spin resonance of Co^{2+} in YGaG, (8) 207*b*.
Sturhahn, H. Thermal shock resistance of wall tile, (3) 74*g*.
Stutske, W. A. Feeder tube support and drive for glass furnace, P (10) 255*a*. See Davey, D. G.
Stutske, W. A., and Toepfer, W. J. Method of shearing charges of molten glass, P (2) 39*c*.
Stutzman, G. R. Hermetically sealed thin film module, P (8) 184*g*.
Subramanian, D. R. Urgent problems facing the refractories industry, (11) 281*g*.
Subramanian, M. See Levine, M. W.
Subramanian, T. V. A., Upadhyayula, L. C., Ramamurthy, S. G., and Somayaji, K. N. Behavior of electronic components toward nuclear radiation, (11) 284*c*.
Sucharski, L. R. See Murata, Y.
Suchil'nikov, S. I. See Baum, B. A.
Suchkov, V. D. See Budrin, D. V.
Suchow, L. Ternary semiconductor compounds and method of preparation, P (5) 129*c*.
Suddarth, J. M. See Coburn, O. W.
Suddick, L. Circuit element totally encapsulated in glass, P (9) 230*j*.
Suemune, Y. Thermal conductivity of $BaTiO_3$ and $SrTiO_3$ from 4.5° to 300°K, (9) 242*g*.
Sueoka, O. Plasma oscillation of electrons in LiF, (8) 205*c*.
Sugahara, Y. See Kunii, D.; Kuwata, T.
Sugano, S. See Shinada, M.
Sugano, S., and Tanabe, Y. Covalency in ionic crystals—$KNiF_3$, (10) 270*h*.
Sugigami, M. See Hinotani, K.
Sugihara, K., and Sato, H. Electrical conductivity of graphite, (5) 135*c*.
Sugita, K. See Ohba, H.
Sugita, K., and Ohba, H. Study on the technological properties of magnesia refractories (I) sintering of magnesia brick and effect of various factors on contraction rates, (7) 152*b*.
Sugita, K., Shimada, K., and Ohba, H. Study on the technological properties of magnesia refractories (II) effect of load on the refractoriness under load of magnesia brick and the change in its microstructure under load, (7) 152*c*.
Sugita, Y. See Iida, S.
Sugiura, M. See Sano, S.
Sugiura, T., Murakami, K., and Tanaka, H. Radiation shielding materials (I) boron litharge glycerine cement, (2) 34*h*; (III) fundamental studies of boron-litharge cement, (7) 146*j*.
Sugiura, T., Murakami, K., Tanaka, H., and Akimoto, H. Radiation shielding materials (II) radiation shielding properties of glasses in the system Li_2O-PbO-B_2O_3, (2) 37*f*.
Suh, N. P. See Nehru, A. K.
Suhl, H. See Rado, G. T.
Suk, K. See Arend, H. T.
Sukegawa, T. See Fujikawa, K.
Sullivan, D. J. See Ackerman, C. B.
Sullivan, J. V. See Walsh, A.
Sullivan, K. M. Australian development of a new moving bar stoker, (2) 52*d*.
Sullivan, M. V. Process for electropolishing both sides of a semiconductor simultaneously, P (3) 79*b*.
Sullivan, P. W. See Wong, R.
Sulzer Brothers, Ltd. Method of producing a casting mold, P (9) 226*i*. Process for production of lost models in precision casting operations, P (8) 182*b*.
Sumitomo, H. See Kikuchi, C.
Summergrad, R. N. Method of preparing aluminum arsenide, P (4) 102*c*.
Summers, L., Walker, D. C. B., and Kelly, B. T. Effect of fast neutron irradiation on the C_{33} elastic modulus of highly oriented pyrolytic graphite, (8) 195*g*.
Summerscales, L. See Kind, S. S.
Sump, C. H., and McGee, S. W. Brake lining materials and articles made therefrom, P (7) 153*a*.
Sump, K. R. See Brite, D. W.
Sundaram, M. See Aravamudan, V.
Sundquist, L. A. See Barr, H. N.
Sunset, P. H. See Harris, H. M.
Super-Cut, Inc. Grinding wheel with predeterminately oriented fixed replaceable abrasive segments, P (8) 173*g*.
Surplice, N. A. Measurement of the concentration and mobility of negative ions of oxygen in an oxide-coated cathode and of the variation of the capacitance of the cathode with temperature, (3) 86*f*.
Sutton, C. R. See Bradbury, E. J.
Sutton, R. W. Method of reclaiming calcined kaolin from de-inking sludge residue, P (8) 190*d*.
Sutton, W. H. See Mehan, R. L.
Sutton, W. H., and Feingold, E. Role of interfacially active metals in the apparent adherence of nickel to sapphire, B (2) 61*i*.
Suwa, Y. See Adachi, Y.
Suzuki, A., and Wahlbeck, P. G. Gaseous products from vaporization of titanium selenides, (3) 75*i*.
Suzuki, H. See Yasui, E.
Suzuki, K. Runner brick (II) firing temperature of runner brick and its characteristics, (9) 224*f*. See Matsushita, T.
Suzuki, M. See Kino, A.
Svec, J. J. Alumina scores in computer assemblies, (1) 9*f*. Harford launches structural calcium silicate brick production, (4) 95*j*. Moland-Drysdale builds modern addition, (9) 223*a*. Tropicana doubles glass container production, (4) 93*c*.
Svenska Flaktfabriken A.B. Apparatus for the supply and atomizing of a liquid in a gaseous medium, P (4) 103*j*. Method and means for ensuring uniform flow of material through driers operating on the fluidized bed principle, P (2) 53*d*.
Swain, A. B., Jr. See Soubier, L. D.
Swallow, D. Magnetic ceramics, (9) 229*d*.
Swanson, G. D. See Gutshall, P. L.
Swanson, H. E., Morris, M. C., and Evans, E. H. Standard X-ray diffraction powder patterns, (3) 81*f*.
Swanson, J. L. Plutonyl species in molten chloride salt solutions, (8) 205*c*.
Sweet, R. C. See Bronnes, R. L.
Sweet, R. L. Clinker control in cement industry, (11) 274*i*.
Sweo, B. J. See Bersticker, A. C.
Swift, H. R., and Ginther, L. B. Glass manufacture, P (4) 94*h*.
Swigert, G. F. See Huckle, W. G.
Swinehart, C. F. Thermoluminescent doubly doped LiF phosphor, P (8) 186*b*.
Swinehart, C. F., Hofstadter, R., and O'Dell, E. W. Scintillation detector comprising a transparent tin-activated calcium iodide scintillator, P (4) 102*b*.
Swisher, J. H., and Turkdogan, E. T. Solubility, permeability, and diffusivity of oxygen in solid iron, (10) 250*g*.
Swistun, G. K. Electrolytic apparatus for treatment of the tips of glass beaded leads, P (1) 10*b*.
Switzer, J. L. Nonvisible penetrant methods of flaw detection and apparatus therefor, P (11) 289*j*.
Switzer Brothers, Inc. Nonvisible penetrant methods of flaw detection and apparatus therefor, P (11) 289*j*.
Sychev, M. M., and Korneev, V. I. Additives to improve qualities of cement, (9) 214*a*.
Sylvania Electric Products, Inc. Apparatus for [electrostatic] coating of glass bulbs, P (9) 219*d*. Copper activated strontium metaphosphate phosphors, P (8) 184*f*. Double-ended tube, P (5) 127*g*. Electric lamp coating comprising agglomerates of silica coated with a pigment, P (8) 184*i*. Electric lamp with tubular body and light transmitting closure having overlapping flange seal, P (9) 219*g*. Electroluminescent lamp with a barium titanate layer, P (2) 47*d*. Electroluminescent lamp with homogeneous phosphor-dielectric layer, P (3) 78*e*. Ferrite stripline circulator having closed magnetic loop path and centrally located conductive foil overlying radially extending center conductors, P (10) 263*j*. Fluorescent electric discharge lamp having the phosphor particles admixed with indium powder particles, P (11) 285*e*. Four-layer semiconductor switching device having turn-on and turn-off gain, P (7) 156*e*. Frit dispensing device, P (11) 285*e*. [Glass] encapsulated thermostatic switch with shunt, P (1) 10*c*. Hermetically encased electroluminescent display device, P (8) 184*f*. High pressure discharge device having a fill including iodine, mercury, and at least one rare earth metal, P (10) 264*c*. High pressure electric discharge device having electrodes with thorium on the exposed surface thereof, P (8) 184*h*. High temperature fluorescent lamp with reflector having mercury amalgamative material on its electrode stems, P (2) 47*f*. Method and apparatus for infiltrating porous bodies, P (7) 157*a*. Orthophosphate phosphor compositions, P (1) 11*j*. Phos-

phor coated articles, P (10) 265*e*. Plant growth lamp, P (2) 49*a*. Process for fabricating arc tubes, P (2) 39*j*. Semiconductor switching device and method of manufacture, P (9) 232*c*. Tantalum carbide incandescent lamp and manufacture thereof, P (2) 49*b*. Thermostatic switch, P (1) 12*b*.

Synfibrit G.m.b.H. Sintered products for use in foaming ceramics, P (10) 260*i*.

Syono, Y., and Ishikawa, Y. Magnetocrystalline anisotropy and magnetostriction of xFe_2TiO_4·$(1-x)Fe_3O_4 (x > 0.5)$, (7) 165*f*,*g*, (8) 202*i*.

Syritskaya, Z. M., and Yakubik, V. V. Coordination numbers of cations in glass and the structure of phosphate glasses, B (7) 171*d*.

Systems Engineering & Mfg. Co., Inc. Handling of pulverulent materials, P (7) 158*i*.

Sze, S. M., and Gibbons, G. Avalanche breakdown voltages of abrupt and linearly graded *pn* junctions in Ge, Si, GaAs, and GaP, (9) 228*i*.

Szebeni, P. See Lorinczy, A.

Szegvari, A. Method of and apparatus for grinding dry or wet materials, P (9) 233*c*.

Szekely, J. Effect of bulk flow on unsteady state diffusion with a variable diffusion coefficient, (7) 162*e*.

Szekely, T. New results in the chemistry of boron and silicon, (1) 23*i*.

Szepesi, Z. P. J. Solid state display device for amplifying or converting input radiation including a field emissive layer, P (11) 287*g*.

Tabakovic, B. See Andreasen, A. H. M.

Tabata, K. See Hayashi, T.

Tabendale, A. J. Method for the production of semiconductor lithium-ion drift [germanium] diodes, P (10) 264*i*.

Tabor, D. See Atkins, A. G.

Tacken, J. Process for making granulated ceramic, porous, or analogous materials, P (2) 35*a*.

Tacken, P. J. M. See Baas, G.

Tada, T., Kawamura, J., and Hara, K. Results of comparative service test on various types of basic brick in an electric arc steelmaking furnace, (11) 281*a*.

Tadsen, V. S., and Derge, G. J. Process for reducing deterioration in equipment handling molten materials, P (2) 45*f*.

Taebel, W. A., and Hoekstra, G. W. Preparation of beryllia whiskers, P (3) 72*c*.

Taft, E. A., Jr. See Dash, W. C.

Tagai, H. See Shimohira, T.; Zisner, T.

Tagai, H., and Shimohira, T. Low melting porcelain enamel of the system $PbO-TiO_2$, (5) 117*e*.

Tagai, H., Zisner, T., Mori, T., and Yasuda, E. Preferred orientation in hot-pressed magnesia, (11) 299*a*.

Tailleur, A., and Le Gras, J. Machine for severing glass, P (4) 94*c*.

Tait, H. Glass with checkered spiral-trail decoration—a group made in the southern Netherlands in the 16th and 17th centuries, (11) 273*i*.

Taiyo Yuden Kabushiki Kaisha. Apparatus for manufacture of ceramic condenser elements, P (7) 156*f*.

Tajukin, L. I. See Kuznetsov, V. G.

Takada, K. See Toyo Kinzoku Kagaku Kabushiki Kaisha.

Takada, S. See Meguro, K.

Takada, T. See Kachi, S.; Kosuge, K.

Takagi, H. See Hayashi, H.

Takagi, K. See Tashiro, M.

Takagi, T. See Tomono, M.

Takagi, T., Migitaka, M., Ueda, H., and Kimura, H. Method of producing semiconductor devices, P (4) 102*d*.

Takahashi, K. See Okazaki, K.

Takahashi, O. See Kishida, M.

Takahashi, S. See Kudaka, K.

Takahashi, T. See Watanabe, H.

Takahata, K. See Kino, A.

Takano, Y. See Kawahara, A.

Takashima, H., and Kato, E. Texture of zinc opaque glazes, (11) 283*i*.

Takatsu, M. Radial velocity distribution of the particle flow in a shaft kiln (I), (7) 146*j*.

Takeda, T. See Kondoh, H.; Tamura, K.; Uchida, E.

Takeda, T., and Kondoh, H. Thermal pits of NiO crystals, (4) 111*g*.

Takeda, T., and Watanabe, A. Two sets of ESR of Gd^{3+} in $BaTiO_3$ ceramic semiconductor, (8) 211*a*.

Takeda, Y., Hirai, T., and Hirao, M. Phase diagram for the pseudobinary system germanium and gallium arsenide, (9) 241*b*.

Takehara, T. See Adachi, Y.

Takei, H. See Koide, S.

Takei, T. See Yoshida, T.

Takei, W. J. See Shirane, G.

Takeishi, Y. Ejection of electrons from barium oxide by noble gas ions, (3) 85*g*.

Takekoshi, H. See Nasu, S.

Takematsu, M. Viscous flow in a two-dimensional cavity, (9) 243*d*.

Takemoto, H. See Okazaki, K.

Takeshita, S. K. See Nagasawa, H.

Takeuchi, M. See Oya, T.

Takeuchi, T. See Watanabe, M.

Takeuchi, T., and Kawamura, T. Spectrophotometric determination of trace amounts of vanadium in titanium oxide, (3) 81*e*.

Takeuchi, Y. Weight loss and dimensional change of carbon during baking, (3) 72*c*.

Takeuchi, Y., and Okada, J. Effect of binder pitch on physical properties of graphitized carbons, (4) 107*f*.

Takeuchi, Y., Tanaka, T., and Yamada, J. Dimensional change of carbon during graphitization, (3) 71*g*.

Takeya, G., Makino, K., and Ishii, T. DTA apparatus, P (8) 188*b*.

Taki, H. See Nagase, K.

Takimoto, S. See Tanaka, M.

Takusagawa, N. See Saito, H.

Takusagawa, N., and Saito, H. Studies on crystallization of fluor-richterite composition glasses (I) phase separation in a model glass, (7) 149*a*.

Talkalkar, T. W. See Gupta, D. M.

Tallada, E. Moving hearth furnace, P (11) 290*f*.

Tallan, N. M. See Graham, H. C., Wimmer, J. M.

Tallan, N. M., Graham, H. C., and Wimmer, J. M. Interfacial polarization effects associated with surfaces and interfaces, B (2) 61*d*.

Tallan, N. M., Tripp, W. C., and Vest, R. W. Electrical properties and defect structure of HfO_2, (7) 163*b*.

Tallman, R. L. See Chu, T. L.

Talsma, H. See Seufert, L. E.

Tamada, K., and Miyagi, T. Viscous flow past a tangential flat plate, (9) 243*d*.

Tamas, F. (editor). Proceedings of the Eighth Conference on the Silicate Industry, Budapest, June 1965, B (5) 141*f*.

Tamura, H., Sawaguchi, E., and Kikuchi, A. Ferroelectric hysteresis character of $YMnO_3$, (11) 295*c*.

Tamura, K., and Takeda, T. Preparation of chromium disilicide and some of its properties, (4) 97*a*.

Tamura, M. Method of making a cathode ray tube, P (10) 264*i*.

Tanabe, Y. See Sugano, S.

Tanaka, H. See Sugiura, T.

Tanaka, H., Murakami, K., and Yoshida, T. Effect of sodium sulfite on the hydration of tricalcium aluminate and tricalcium silicate, (4) 90*e*.

Tanaka, K. See Higuchi, M.

Tanaka, M. Thermodynamic approach to the structure of silicate glasses (II) ionic structure of metasilicate glasses, (2) 38*a*. See Tsubaki, T.

Tanaka, M., and Minami, T. Infrared absorption spectra of arsenic-sulfur glasses prepared by evaporation under normal pressure, (5) 119*d*.

Tanaka, M., Minami, T., and Hattori, M. Thermal expansion and related properties of arsenic-sulfur glasses, (11) 277*d*.

Tanaka, M., Mizoguchi, T., and Aiyama, Y. Moessbauer effect in $Mn_xFe_{3-x}O_4$, (7) 165*j*. Moessbauer study of ^{57}Fe in distorting spinels, (7) 166*a*.

Tanaka, M., Mukai, O., and Kamiike, O. Direct formation of arsenic-sulfur glasses in sheet form by distillation under normal pressure, (7) 148*e*.

Tanaka, M., Takimoto, S., and Kamiike, O. Direct deposition of arsenic-sulfur glasses in film form by evaporation under normal pressure, (5) 118*f*.

Tanaka, M., Taninami, S., and Oya, I. Fundamental studies on Hiraki kaolin (I) geology, deposits, and mineral composition, (3) 86*a*.

Tanaka, N. See Miyamoto, S.

Tanaka, T. See Takeuchi, Y.

Tanaka, Y. See Miyamoto, O.

Tananaev, N. V. See Kuznetsov, V. G.

Tandilova, K. B. See Kutateladze, K. S.

Tanenbaum, J. M. Consumable nozzle for electroslag welding, P (9) 225*c*.

Taninami, S. See Tanaka, M.

Tanner, L. E. Diffraction contrast from elastic shear strains due to coherent phases, (8) 194*d*.

Tannhauser, D. S. See Fisher, B.

Tanokami, S. See Abe, T.

Tappin, G. See Tattersall, H. G.

Taraporewalla, K. J. See Narasimhalu, K.

Tarasov, A. F. See Shakhlin, V. I.

Tarasov, V. V. Polymer models and properties of boric anhydride and borate glasses, B (7) 171*f*.

Tarasov, V. V., Bartenev, G. M., Eremeeva, A. S., and Ratobyl'skaya, V. A. Polymeric character of glassy arsenic trisulfide, B (7) 171*f*.

Tarasova, T. E. See Tseitlin, L. A.

Tardy, P. See Kisfaludy, A.

Tare, V. B. See Anderson, J. R.

Tarkan, S. E. See Ellis, J. L.

Tarnopol'skaya, R. A., and Gul'ko, N. V. Structure of the SrO-ZrO_2 system, (7) 168*d*. Subsolidus structure and fusibility diagram of the SrO Al_2O_3-ZrO_2 system, (7) 168*d*.

Tartakoff, A. See Bouchard, G. H.

Tarte, P. Determination of cation coordination in glasses by infrared spectroscopy, B (2) 62*a*.

Tarukawa, T. Apparatus for automatically mixing several kinds of stock materials, P (5) 130*c*.

Tasaki, A. See Kohn, K.

Tashiro, M. Chemical compositions of glass-ceramics (I); (II) some physical properties of glass-ceramics and their relation to microstructure, (2) 36*e*. See Maki, T.; Sakka, S.

Tashiro, M., Sakka, S., and Kokubo, T. Magnetic materials obtained from silicate melts in the system Fe_2O_3-MnO-alkali oxide-Al_2O_3-SiO_2, (3) 86*e*.

Tashiro, M., Sakka, S., and Yamamoto, T. Change in refractive indices of glasses under high pressure, (2) 36*d*. Chemical durability of polycrystalline materials produced from glasses, (2) 36*f*. Crystallization of lithia-silica glasses at high pressure, (5) 118*i*.

Tashiro, M., and Takagi, K. Method of preventing scum formation in glass melts and glass-ceramic products, P (2) 39*a*.

Tatem, W. A. Electric circuit elements, P (9) 230*d*.

Tatematsu, R. See Ozaki, S.

Tatsak, J. E. Apparatus for maintaining optimum speed of cutting shears when glass gob sizes are varied, P (10) 254*a*.

Tattersall, G. H., and Baker, W. T. Discussion of "Radioactive method for measuring variations in density in concrete cores, cubes, and beams," (11) 274*g*.

Tattersall, H. G., and Tappin, G. Work of fracture and its measurement in metals, ceramics, etc., (10) 272*b*.

Tauber, A. See Savage, R. O.; Schwartz, A.; Shapiro, J. R.

Tauber, E., and Crook, D. N. Use of amblygonite in earthenware bodies, (7) 155*g*.

Tauc, J., Abraham, A., Pajasova, L., Grigorovici, R., and Vancu, A. Optical properties of noncrystalline semiconductors, B (2) 62*b*.

Tausch, F. W., Jr., and Lapierre, A. G., III. Novel crystal growth phenomenon—single crystal GaAs overgrowth onto silicon dioxide, (11) 298*i*.

Tavernelli, J. F., and Piepsny, R. A. Furnace heat shield, P (2) 52*h*.

Tawara, Y., and Senno, H. Barkhausen noise induced by an external stress in a ferrite head in a video tape recorder, (11) 284*d*.

Taylor, A. M. See Flanigen, E. M.

Taylor, A. W., Frazier, A. W., and Gurney, E. L. Solubility products of magnesium-ammonium and magnesium-potassium phosphates, (5) 138*f*.

Taylor, A. W., Frazier, A. W., Gurney, E. L., and Smith, J. P. Solubility products of di- and trimagnesium phosphates and the dissociation of magnesium phosphate solutions, (5) 138*f*.

Taylor, C. R. Method of manufacture of flat glass with reducing atmosphere, P (11) 279*d*.

Taylor, D. W., and Hart, A. B. Ceramic Painting Step by Step, B (3) 88*e*.

Taylor, E. C. See Lontz, H. M.

Taylor, E. H. Influence of radiation on reactivity and catalytic activity of solids, (8) 200*d*.

Taylor, H. F. W. Chemistry of cements, (4) 90*g*.

Taylor, H. L. See Hirayama, C.

Taylor, J. B. See Heyding, R. D.

Taylor, J. R. A. Method of treating opal glass surfaces, P (2) 39*e*.

Taylor, K. M. Production of refractory bodies, P (5) 125*d*.

Taylor, K. M., Andersen, J. C., Strasser, A., Stahl, D., and Forbes, R. L. Monoxide-type compounds of uranium and plutonium (I) oxycarbides, (7) 166*b*.

Taylor, R. M. See Gill, J. B.

Taylor, R. M., and Norrish, K. Measurement of orientation distribution and its application to quantitative X-ray diffraction analysis, (4) 108*f*.

Taylor, R. W., and Schmalzried, H. Free energy of formation of some titanates, silicates, and magnesium aluminate from measurements made with galvanic cells involving solid electrolytes, (8) 198*f*.

Tcheichvili, L. Structure model and its application to the chemistry of the silicates, (4) 110*f*.

Teague, E. D. See Lant, T. P. R.

Teague, J. M., Jr., and Wiens, B. E. Method for improving the durability of glassware, P (11) 279*b*.

Teatum, E. T. Crucible reactor and method, P (10) 259*g*.

Tech-Met Corp. Method of preparing magnetic memory device, P (8) 185*a*.

Technical Industries, Inc. Controlled deposition and growth of polycrystalline films in a vacuum, P (3) 77*g*.

Technion Research & Development Foundation, Ltd. Temperature detector, P (4) 102*i*.

Tecnopatent S. A. Casing with pulsating internal wall for mills, mixers, and similar equipment, P (4) 106*j*.

Tecotzky, M. See Hurley, F. R.

Tefft, W. E. Elastic constants of synthetic single crystal corundum, (2) 54*j*.

Teichner, S. J. See Long, J.

Tektronix, Inc. Combined direct viewing storage target and fluorescent screen display structure, P (11) 285*a*. Phosphor dielectric storage target for cathode ray tube, P (3) 79*i*. Thin porous storage phosphor layer, P (3) 79*i*.

Teledyne, Inc. Method of making field effect transistor device, P (11) 286*i*.

Teleflex, Inc. Composite metal-ceramic article and method for making same, P (4) 92*f*.

Telefunken Akt.-Ges. Apparatus for and method of determining the values of electrical parameters of a semiconductor crystal, P (2) 47*g*.

Telefunken A.G. Patentabteilung. Method of forming a transistor by diffusing recombination centers and device produced thereby, P (8) 185*d*.

Telefunken Patentverwertungs-G.m.b.H. Cathode ray tubes, P (11) 284*j*. Ceramic dielectric, P (10) 263*c*. Semiconductor stabilized mechanically and electrically by a first layer of lacquer and a second layer of boric oxide, P (4) 102*g*.

Telegraph Condenser Co., Ltd. Ceramic bodies and articles made therefrom, P (7) 156*j*. Ceramic dielectric materials, P (8) 184*d*.

Temkin, I. V. Obtaining highly dispersed carbon-graphitic materials, (10) 257*j*.

Tennery, V. J. See Harris, N. H.

Tenorio, A. M. See Pastor, R. C.

Tenpas, E. J., and White, R. A. Magnetic separator for mixtures of magnetic and nonmagnetic material, P (3) 80*c*.

Tensmeyer, L. G. See Fritsche, E. T.

Teoreanu, I., and Rotaru, M. Calcium chloride activation of blast furnace slags of the system MgO-CaO-Al_2O_3-SiO_2, (4) 90*c*.

Terada, S., and Saito, N. Measurement of structure of grinding wheels, (11) 273*f*.

Terao, N. Structures of niobium nitrides, (4) 110*a*.
Terasaki, Y. See Murakami, T.
Terekhina, P. Ya. See Kaibicheva, M. N.
Terent'eva, N. V. See Belyavskaya, L. M.
Terry, R. See Rudzitis, E.
Tesla, Narodni Podnik. Method of production of aqueous silver suspensions applied for only one heating operation, P (5) 126*c*.
Tetelman, A. S. Fracture behavior, B (9) 244*f*.
Teter, A. R. Isostatic pressing points to improved quality, (9) 232*h*.
Tetra, A. B. Method of bonding ceramic and metal materials by flame spraying, P (9) 217*e*.
Teuchert, K. Disadvantages of the Seger formula and its replacement by molar concentrations, (10) 261*e*.
Teumac, F. N. Recovery and separation of cesium and rubidium fluorides using alcohols, P (5) 133*f*.
Texaco Experiment, Inc. Method of making thermoelectric initiators of semiconductor material, P (7) 157*h*.
Texas Instruments, Inc. Ceramic-glass sealing means for encapsulation of electrical devices, P (10) 263*c*. Dielectric devices, P (8) 184*g*. Dielectrics with conductive portions and method of making same, P (4) 100*j*. Double doping of III-V compound semiconductor material, P (1) 10*a*. Electrical interconnections, P (9) 230*d*. Fabrication of a metal base transistor, P (9) 230*i*. Ge-P-Te glasses and method of making same, P (11) 278*f*. Isolated base four-layer semiconductor system, P (1) 11*a*. Low capacitance planar diode, P (8) 185*a*. Low-voltage semiconductor reference diode, P (11) 285*j*. Metallic contacts for semiconductor devices, P (11) 286*c*. Method and capacitor comprising [Mn] oxide electrolyte derived from permanganic acid, P (8) 185*b*. Method of junction passivation and product, P (4) 101*g*. Method for making a *pnpn* device by diffusing, P (8) 185*g*. Method of making semiconductor devices, P (10) 264*c*. Method of making semiconductor by selective impurity diffusion, P (11) 286*j*. Method of making symmetrical switching diode, P (4) 102*a*. Method of producing a field-effect transistor, P (8) 185*b*. Process for applying a protective coat of silicon carbide to refractory metals, P (8) 174*j*. Process [gaseous] for preparing boron nitride coatings, P (9) 226*h*. Semiconductor contact alloy, P (8) 186*c*, P (9) 232*a*. Semiconductor devices and methods of making same, P (5) 129*c*. Semiconductor radiant diode, P (3) 79*e*. Small light sensor package, P (1) 11*i*. Thermionic energy converter [SiC-C], P (9) 232*f*.
Texas Vitrified Pipe Co. Trickling filter media, P (10) 256*g*.
Thakur, R. L., and Thiagarajan, S. Studies on the catalyzed crystallization of glasses—DTA method, (2) 37*f*.
Thanh, P. H. See Rolin, M.
Thedford, R. H. Apparatus for trimming ceramics, P (10) 266*f*.
Thehin, R. Tile, slabs, and panels of cement or ceramic containing special optical areas, P (2) 40*a*.
Theisen, R. See Hofmann, U.
Theobald, P. R. See Griest, E. M.
Theodore, J. G., and Bielawski, C. A. Vacuum fired beryllia ware, P (4) 99*e*.
Theodorou, D. G., McIntosh, R. O., Conklin, T. H., and Earl, K. C. Analysis of gases liberated during the tip-off of some commercially available glasses, (2) 36*a*.
Thermal Engineering Corp. Radiant burner utilizing flame quenching phenomena, P (1) 15*c*.
Thermal Syndicate, Ltd. Attachment of inserts and fixing devices to pieces of vitreous silica, glass, etc., P (7) 149*i*.
Therm-O-Disc, Inc. Temperature sensing probe with means for maintaining the tubular element in engagement with a ceramic rod member, P (7) 159*i*.
Thery, J., and Briancon, D. Structure and properties of sodium aluminates, (1) 29*g*.
Thiagarajan, S. See Thakur, R. L.
Thiele, H. See Barz, G. J.
Thielepape, W. See Weiss, A.
Thiemann, H. Contemporary German ceramic artists and their work—Monika Maetzel, (9) 213*j*. Jan Bontjes van Beek—life devoted to ceramics, (9) 213*j*.
Thiokol Chemical Corp. Abrasive articles and method of making abrasive articles, P (2) 33*j*. Refractory material and method for making the same, P (3) 73*a*.
Tholome, R. See Felici, N. J.
Thomann, H. Relation of lead vaporization and the concentration of lead deficiencies in lead zirconate-titanate ceramics, (3) 76*b*.
Thomas, A. Gyroscopic crusher [portable] of shallow height, P (11) 291*g*.
Thomas, C., and Braunstein, J. Association of silver(I) and chloride in molten cesium nitrate and in molten mixtures of potassium nitrate with cesium nitrate or lithium nitrate, (8) 191*j*.
Thomas, D. G. See Trumbore, F. A.
Thomas, D. L. Method and apparatus for press bending glass sheets, P (3) 68*i*.
Thomas, D. W. Feldspathic materials lower firing temperatures, (1) 6*i*. Improved fusion test method aids critical evaluations, (5) 131*d*. Strength improvement of vitreous china bodies, (3) 74*e*.
Thomas, J. E., Jr., and Young, D. R. Method of modifying electrical characteristic of semiconductor member, P (10) 264*g*.
Thomas, L. D. See Reuter, H. L.
Thomas, L. D., and Reuter, H. L. Glass polishing composition comprising a water-soluble zinc salt, P (8) 177*d*.
Thomas, N. C. See King, J. C.
Thomas, R. A. Device for orienting transparent crystals by use of optic (*c*) axis, (1) 13*h*.
Thomas, R. D. See Champlin, J. B. F.
Thomas, R. E. See Ray, N. H.
Thomas, W. J. See Griffiths, D. W. L.
Thomas Marshall & Co. (Loxley), Ltd. Refractory nozzle for the teeming of molten metal, P (4) 99*a*.
Thompson, C. D. See Ban, T. E.
Thompson, C. E. See Gladrow, E. M.
Thompson, C. L. See Scott, R. K.
Thompson, G. L. Rare earth oxide and vanadate phosphors, P (9) 232*g*.
Thompson, J. H., Skinner, D. D., Whittaker, R. H., and Geil, F. G. Temperature sensor, P (8) 188*f*.
Thompson, J. R. Organic bonded abrasive article, P (2) 33*i*.
Thompson, K. C. See Dagnall, R. M.
Thompson, R. D. Color cathode ray tube with radiation-emitting index stripes, P (1) 10*j*.
Thompson Processing Co., Inc. Facing assembly for lens grinding tools and the like, P (9) 219*i*.
Thomsen, S. M. See Messineo, P. J.
Thorn, R. J. See Ackermann, R. J.
Thorn Electrical Industries, Ltd. Electroluminescent lamp with boric acid or boric oxide used in conjunction with the zinc sulfide layer, P (2) 47*c*. Electroluminescent materials, P (2) 47*c*.
Thornton, C. G. See Beyer, D. S.; Schnable, G. L.
Thorpe, M. L. Plasma flame powder spray gun, P (5) 117*e*.
Threadgill, W. D. Calcium chloride-calcium oxide fused salt electrolytic system—solubilities, metal contents, and freezing points, (11) 292*i*.
Thrush, B. A. See Clyne, M. A. A.
Thuemmler, F. See Gebhardt, E.
Thun, R. E. See Bullard, R. L.; Hass, G.
Thurber, W. R. See Frederikse, H. P. R.
Thwaite, R. D. See Padfield, R. C.
T. I. (Group Services), Ltd. Growth of whiskers, P (9) 225*h*. Manufacture of silicon nitride articles, P (7) 153*h*. Production of refractory carbide fibers, P (9) 227*h*. Production of silicon nitride whiskers, P (9) 227*h*. Reinforced refractory materials, P (1) 8*g*.
Tibol, G. J., and Hull, R. W. Plasma anodized aluminum oxide films, (4) 100*b*.
Tickner, A. W. See Westmore, J. B.
Tidwell, L. G., and Larson, A. H. Influence of selected sulfides on the decomposition rate of zinc sulfate at 600°C, (8) 200*e*.
Tiede, R. L. Apparatus for making composite fibers, P (10) 254*b*. High temperature insulation for electrical conductors, P (8) 177*g*.
Tien, T. Y. See Bratton, R. J.
Tien, T. Y., and Moratis, C. J. Dielectric properties of strontium titanate solid solutions containing niobia, (9) 229*c*.
Tierney, P. A. See Lewis, D. W.
Tietjen, J. J. See Richman, D.
Tietjen, J. J., Pankove, J. I., Hegyi, I. J., and Nelson, H. Vapor-phase growth of $GaAs_{1-x}P_x$ room-temperature injection lasers, (10) 263*i*.
Tietjen, T. A. See Mytych, C. J.
Tighe, N. J. See Barber, D. J.
Tikhomirov, G. P. See Alekseev, A. G.
Tile Council of America, Inc. Flexible ceramic tile unit, P (8) 183*a*. Thixotropic nonflowing adhesive bonding and jointing compositions and methods of bonding ceramic tiles to substrates using them, P (7) 155*e*.
Tillett, T. J., and Lodholz, J. C. Slurry mixing apparatus, P (2) 35*b*.
Tilley, C. E. See Muir, I. D.
Timashev, V. V. See Butt, Yu. M.
Timesavers Sanders, Inc. Abrasive sleeve for rotary abrading machines, P (11) 273*f*.
Timm, W. A. See Miner, R. J.
Timmer, W. F., and Curry, N. A. Metal backed abrasives, P (2) 33*h*. Polymer saturated backing material, P (4) 89*f*.
Timmermans, A., and Tol, T. Green radiation lamp for optical maser, P (8) 184*e*.
Timofeev, A. N. See Klotsman, S. M.
Timofeeva, N. F. See Gerasimov, A. F.
Tippins, H. T. Absorption edge spectrum of scandium oxide, (8) 190*f*.
Tisinai, G. F. Glass lined vessels, P (1) 5*e*. Mold apparatus for forming glass lined vessels, P (3) 69*f*.
Titangesellschaft m.b.H. Production of titanium dioxide, P (9) 236*d*.
Titanium Metals Corp. of America. Corrosion resistant chlorinator lining, P (10) 259*f*.
Tizon Chemical Corp. Process for polishing crystalline silicon, P (9) 232*a*.
Tkachenko, E. V. See Zhukovskii, V. M.
Tkachenko, E. V., Neuimin, A. D., Vlasov, V. G., and Strekalovskii, V. N. Temperature dependence of the electrical conductivity of the higher uranium oxides, (4) 111*a*.
Tkachenko, E. V., and Vlasov, V. G. Phase transformations in the carbon black reduction processes of uranium oxides, (1) 26*h*.
Toa Gosei Kagaku Kogyo Kabushiki Kaisha. Process for the production of crystalline calcium carbonate of vaterite type, P (9) 236*i*.
Tobin, J. M. See Adelsberg, L. M.; Brizes, W. F.
Tobin, R. E. See Campbell, R. H.
Toenshoff, D. A. See Zysk, E. D.
Toenshoff, D. A., and Zysk, E. D. "Birdcage" resistance thermometer, (9) 233*h*.
Toepell, H. D. F. Apparatus for measuring temperatures within rotary kilns, P (10) 268*b*.
Toepfer, W. J. See Stutske, W. A.
Togawa, S. Experimental study on X-ray scattering factors of magnesium oxide, (9) 239*e*.
Tokai Denkyoku Seizo Kabushiki Kaisha. Method for the preparation of flexible carbon fiber, P (2) 44*b*.
Tokarski, Z., Kalwa, M., Przybylek, A., Ropska, H., and Wolfke, S. Raw materials for brick manufacture, (1) 15*i*.
Toko Kabushiki Kaisha. Variable disk capacitor, P (11) 288*b*.
Tokumoto, Y. See Ikeda, Y.
Tokutaka, H., and Maejima, R. Magnetic anisotropy in single-crystal Permalloy thin films epitaxially grown on LiF (110) surface, (9) 240*b*.
Tokuyama, T. See Migitaka, M.
Tokuyama, T., and Uehara, K. Method of manufacturing semiconductor devices, P (5) 128*c*.
Tokyo Jiahaku Kabushiki Kaisha. Methods of manufacturing magnetically anisotropic permanent magnets having crystalline structures, P (3) 79*g*.
Tokyo Shibaura Electric Co., Ltd. Cathode ray tube having a screen conforming to the peripheral surface of a cylinder, P (4) 100*h*. Methods of sealingly securing lead-in wires to glass tubes, P (5) 121*i*.
Tol, T. See Timmermans, A.
Tolloca, G., and Perez y Jorba, M. Refractory compounds having structures derived from the perovskite structure in the systems zirconia-alkaline-earth oxides, (1) 28*d*.
Tolmacheva, Z. I. See Eremenko, V. N.
Tolman, C. H. See Hanson, M. M.
Tol'skii, A. A., Masyukov, N. T., and Gordienko, A. K. Use of chamotte-graphite lances in the bottoms of Bessemer converters, (9) 225*g*.
Tolutis, V. See Deksnys, A.
Tolutis, V., and Jasutis, V. Sublimation of thin polycrystalline CdTe films in vacuo, (11) 301*a*.
Tomita, T. X-ray study of dislocations in SiC crystals, (10) 272*h*. See Azuma, K.; Ohta, K.
Tomizuka, C. T. Some experimental aspects of diffusion in metals, B (8) 211*i*.
Tomizuka, I. See Torikai, N.
Tomlinson, J. W. See Angell, C. A.
Tomochika, T. Absorption bands in evaporated BaO films, (3) 83*h*.
Tomono, M., Ueda, H., Takagi, T., and Kobayashi, K. Method of making semiconductors and diffusion thereof, P (4) 102*a*.
Tomono, Y. See Nagasawa, H.
Tompkins, P. C. Influence of structure on solid-state reactions, (8) 200*f*.
Tomura, M., Masuoka, T., and Nishimura, H. Decay times of luminescence of KI/Tl single crystals, (8) 194*f*.
Tonning, A. See Ingebrigtsen, K. A.
Tooley, A. B. See Martyn, L. G.
Toothacker, W. S. See Preuss, L. E.
Topas, B., and Weinstein, H. Controlled rectifier having shunted emitter formed by a nickel layer underneath an aluminum layer, P (4) 100*j*.
Torgesen, J. L. See Deslattes, R. D.
Torii, T. See Inagaki, K.
Torii, Y. See Hayashi, H.
Torikai, N., and Tomizuka, I. Relation between the graphitization of carbon and its reactivity in the formation of calcium carbide, (1) 28*f*.
Torkar, K., and Krischner, H. Aluminum oxides, (5) 134*b*.
Torok, A. See Engel, E. G.
Torok, J. J. Glass shaping plunger with a mercury mass condenser cooling means, P (2) 38*h*.
Toronto Grinding & Milling Machinery, Ltd. Pulverizer, P (9) 236*d*.
Toropov, N. A. See Bondar, I. A.; Degen, M. G.
Toropov, N. A., and Barzakovskii, V. P. High-temperature Chemistry of Silicates and Other Oxide Systems, B (3) 88*e*.
Toropov, N. A., and Bryantsev, B. A. Physicochemical properties and crystallization of melts in the system magnesium oxide-ferrous oxide-silica, B (5) 142*b*.
Toropov, N. A., and Dobrovol'skii, K. A. Effect of sodium and potassium salts on the formation of clinker minerals, (10) 248*f*. Volatilization of sodium and potassium oxides during the burning of clinker and their distribution in the minerals, (10) 249*c*.
Toropov, N. A., and Fedorov, N. F. Solid solutions in the system calcium orthosilicate-neodymium orthosilicate, (4) 109*j*.
Toropov, N. A., and Porai-Koshits, E. A. (editors). Structure of Glass (Vol. V) Structural Transformations in Glass at High Temperatures, B (5) 141*b*.
Toropov, N. A., and Rumyantsev, P. F. Kinetics of physicochemical processes of cement clinker formation, (9) 214*g*.
Toropov, N. A., and Sirazhiddinov, N. A. Glass formation and crystallization in the system magnesium oxide-alumina-silica, B (5) 142*a*. Phase transformations of cordierite, B (5) 142*b*. System $MgAl_2O_4$-$LaAlO_3$, (8) 209*b*.
Toropov, N. A., and Udalov, Yu. P. Dislocations and their effect on the properties of refractory oxides, (11) 293*d*.
Totesh, A. S., Aver'yanov, V. I., Strel'taina, M. V., and Roskova, G. P. Change of the chemical durability of glass as the result of crystallization, B (5) 142*a*.
Toth, L. E., Jeitschko, W., and Yen, C. M. Superconducting behavior of several complex carbides and nitrides, (2) 56*h*.

Totikubo, I. See Hayama, H.
Tottle, C. R. Science of Engineering Materials, B (1) 31*b*.
Tournoux, M. Action of some oxygenated compounds of potassium on zirconia, (1) 16*d*.
Toussaint, C. J. See Conti, R.
Toussaint, H. N., and Krieger, F. Pressure sensitive semiconductor device, P (8) 185*j*.
Touvay, R. Method of and apparatus for forming flat glass on a liquid bath, P (9) 220*h*. Rotatable current baffle in glass flow furnace, P (9) 222*c*.
Touzalin, R. E. See Armour, F. K.
Town, J. W., Stickney, W. A., Engel, G. T., and Sanker, P. E. Recrystallization of chrome spinel, (11) 300*a*.
Townley, C. W. See Chubb, W.
Townsend, M. G. Cobaltous ion in alumina, (8) 192*c*.
Townsend, M. G., and Hill, O. F. Tetravalent cobalt ion in α-Al_2O_3, (7) 168*i*.
Toy, M. S., and Cannon, W. A. Electrochemical cells with halogen fluoride electrolytes, (7) 163*c*.
Toyama, I., and Nakamura, Tomizo. Decomposition of xenotime by sulfuric acid process, (3) 82*g*.
Toyo Kinzoku Kagaku Kabushiki Kaisha and Takada, K. Process for the production of alkali metal pertitanates and perzirconates, P (1) 11*c*.
Toyoda, H. See Murakami, T.
Tracor, Inc. Thermocouple for DTA, P (4) 105*b*.
Tragert, W. E. Ceramic article coated with silver containing oxygen and method of making same, P (7) 156*h*. Fuel cell with stabilized zirconia electrolyte and nickel-silver alloy anode, P (4) 101*h*.
Trakhtenberg, I. Sh. See Klotsman, S. M.
Tramposch, R. F. Heteroepitaxial films of germanium on sapphire, (11) 296*g*.
Transitron Electronic Corp. Means and method of sealing glass encapsulated diodes, P (7) 156*h*.
Trap, H. J. L. Electric properties of some aluminoborate glasses, B (2) 62*c*. Method of manufacturing glass, P (5) 121*f*.
Trapp, R. L. Traction drive for ceramic regenerators, P (4) 99*c*.
Trask, W. T., Jr. See Hedley, W. H.
Traustel, S., Jeschar, R., and Ulrich, W. Mechanism of the decarbonation of limestone, (5) 116*h*.
Treasure, C. R. G. See Kaye, B. H.
Tredco, Ltd. Ceramic product and process, P (2) 46*c*.
Trehan, J. C. See Verma, M. R.
Tremere, D. A. Surface gradient protected high breakdown junctions, P (11) 287*j*.
Trent, R. M. See Abrams, L. V.
Treptow, A. W. See Kurkjian, C. R.
Tresvyatskii, S. G. See Budnikov, P. P.
Trethewey, W. C. Temperature control system for high temperature melters or the like, P (2) 40*a*.
Tret'yachenko, G. N. Similarity theory applied to the thermal shock resistance of brittle cermets, (8) 206*j*.
Tret'yakov, V. I. See Baskin, M. L.
Tret'yakov, Yu. D. See Gordeev, I. V.
Treuting, R. G., Wagner, R. S., and Ellis, W. C. Application of the Weissenberg goniometer to the determination of the orientation and morphology of microcrystals, (7) 161*j*.
Trew, V. C. G., Husain, S. F. A., and Siddiqi, A. J. Additivity relations in polar diamagnetic salts (II) some salts of Mg and Zn and alkali sulfates, (1) 16*c*.
Triaxon, Inc. Photoluminescent composition consisting essentially of boric acid and fluorescein, P (3) 79*i*.
Tribble, C. J. Tie assembly for faced masonry wall structures, P (7) 151*a*.
Tribble, R. M. See Pinkham, R. M.
Tricklebank, S. B., Nanis, L., and Bockris, J. O'M. Diffusion in the system molten sodium iodide-potassium chloride, (8) 194*i*.
Trigger, H. See Mann, J. E.
Triggiani, L. V. See Sanchez, M. G.
Trinklein, R. L., and Bell, R. Experience with premixed materials, (1) 8*j*.
Triplex Safety Glass Co., Ltd. Method of and apparatus for breaking out sheets of glass, P (5) 120*i*.
Tripp, T. B. See Smyth, D. M.
Tripp, W. C. See Tallan, N. M.
Troell, P. T. Refractory bonding mortar, P (4) 99*e*.
Troell, P. T., Smoot, T. W., Renkey, A. L., and King, D. F. Method of fabricating a heat shield structure, P (8) 181*j*.
Troell, P. T., and Winchester, G. L. Plastic refractory, P (5) 124*f*.
Troemel, G., Obst, K. H., Goerl, E., and Stradtmann, J. System iron (II) oxide-calcium oxide-magnesium oxide as a basis for the determination of the slagging of dolomite, (3) 64*e*.
Trofimova, L. D. See Buketov, E. A.
Trokhachev, I. R. See Kotelnikov, G. R.
Trolander, H. W., and Harruff, R. W. Extended range [dual] thermistor temperature sensing, P (8) 188*c*.
Trout, H. E., Jr. Refractory metals protection, (7) 147*j*.
Trouve, J. See Accary, A.
Trow, S. A. See Emblem, H. G.
Troy, D. J. See Glasser, L. G.
Troy, E. C. Mulling shoe mixer, P (2) 50*a*.
Trubey, P. W., Hanna, L., Gordon, A. D., and Turney, A. C. Magnesium hydroxide and method of preparation, P (9) 226*a*.
Trudeau, U. P. See Dierksheide, D. H.
Trumbore, F. A., Gershenzon, M., and Thomas, D. G. Luminescence due to the isoelectronic substitution of bismuth for phosphorus in gallium phosphide, (8) 201*i*.
Trumbore, F. A., Kowalchik, M., White, H. G., Logan, R. A., and Luke, C. L. Solid solubility and amphoteric behavior of tin in solution grown gallium phosphide, (4) 109*h*.
Trunov, A. M. See Stepanov, G. K.
Trunov, V. K. See Kovba, L. M.
Truskauskas, I. See Nickus, I.
TRW, Inc. Dielectric isolation for monolithic circuit, P (8) 184*h*.
TRW Semiconductors, Inc. Component package, P (7) 156*j*. Method for assembly of semiconductor devices, P (2) 48*d*. Method of forming diode with high resistance substrate, P (5) 127*j*. Method of sealing glass to metal, P (7) 157*j*. Semiconductor alloying technique, P (3) 79*d*.
Tsai, C. S. Elastic wave and infrared light interactions with a moving high-field domain in a piezoelectric semiconductor, (11) 294*a*.
Tsai, T. C. See Borisova, Z. U.
Tscherter, F. Two years of piped gas in North Bavaria, (9) 234*j*.
Tseitlin, L. A., and Tarasova, T. E. Gunning mixes with phosphate bonds, (4) 97*b*.
Tsekhomskii, V. A. See Karapetyan, G. O.; Kuznetsov, A. Ya.
Tsibin, I. P. Firing Dinas for glass furnaces, (4) 96*h*.
Tsigler, V. D., Vinokur, S. V., and Mitrokhina, N. S. Service of forsterite lightweights in the lining of kiln cars, (9) 224*f*.
Tsikarev, V. G. See Klein, A. L.
Tsinzerling, E. V., and Vol'skaya, O. B. Phenomenon of endotaxy in quartz, (10) 271*a*.
Tsiovkina, L. A. See Smirnov, M. V.
Tsirlin, M. S. See Bol'shakov, K. A.
Tskhai, V. A., and Gel'd, P. V. Concentration ranges of homogeneity of the carbides of transition metals of groups IV and V with NaCl structure, (3) 84*d*. Effect of screening on some phase and structural properties of cubic carbides, (11) 294*g*. Screening of the metal-metal bonds in equiatomic oxides and carbides of transition metals with NaCl structure, (3) 87*j*.
Tsubaki, T., Tanaka, M., and Kamiike, O. Studies on vermiculite from Japan (III) fired properties of vermiculite-clay insulating materials, (7) 152*a*.
Tsuji, S., Hayashi, K., Kadowaki, K., and Sato, Katsuo. Method of glass glazing, P (7) 157*e*.
Tsujikawa, I., and Murao, T. Possibility of optical cooling of ruby, (5) 137*i*.
Tsukiyama, K. See Uchikawa, H.
Tsumura, S. Hydration mechanisms of clinker minerals in paste form, (5) 116*c*.
Tsunoda, Y. Method for the preparation of flexible carbon fiber, P (2) 44*b*.
Tsuru, H. See Miyatake, K.
Tsuzuku, T. Mechanical damping in carbon and graphite at low temperature, (2) 55*f*.
Tsylev, L. M. See Panov, A. S.
Tsypin, M. I. See Lainer, D. I.
Tucker, D. J. See Hunsberger, J. F.
Tucker, E. S., III. See Wehking, M. W.
Tucker, R. F. See Schreurs, J. W. H.
Tucker, T. N. Integrated circuit using oxide insulated terminal pads on a SiC substrate, P (5) 127*i*.
Tuddenham, W. M. See Stephens, J. D.
Tuft, R. E. See Strong, H. M.
Tumanov, V. I. See Baskin, M. L.; Kreimer, G. S.
Tumanov, V. I., Funke, V. F., Pavlova, Z. I., Novikova, T. A., and Bystrova, K. A. Influence of composition and structure on the maximum stress of alloys of the systems WC-Co and TiC-WC-Co in compression, (1) 19*e*.
Tung, C. F. See Palmquist, P. V.
Tung, S. K. Effect of substrate orientation on epitaxial growth, (11) 294*i*.
Tung-Sol Electric, Inc. Field effect transistor with a junction parallel to the (111) plane of the crystal, P (4) 101*f*.
Turba, E. Behavior of powders compacted in a die, B (7) 170*c*.
Turbett, F. L. Process of producing stoichiometric uranium dioxide, P (4) 99*b*.
Turchi, A. J. See Lieb, N. H.
Turk, D. H. See Helmuth, R. A.
Turkat, M. Continuous method of manufacturing ablative and refractory materials, P (3) 72*f*.
Turkdogan, E. T. See Grieveson, P.; Swisher, J. H.
Turkdogan, E. T., and Grieveson, P. Transfer of sulfur or oxygen from a low to a high chemical potential through an ionic membrane, (3) 88*c*.
Turkevich, J. Ultrafine particles in the gas phase, B (9) 245*f*.
Turnbull, D. Thermodynamics and kinetics of formation of the glass state and initial devitrification, B (2) 61*f*. See Seward, T. P., III; Uhlmann, D. R.
Turnbull, J. A., and Stagg, M. G. Isothermal annealing studies on vacancy and interstitial loops in single crystal graphite, (8) 201*a*.
Turnbull, N. C. See Scott, J. J.
Turner, A. B., and Lamb, R. D. $PbxTe_{1-2}Cr$ thermoelectric material and thermoelectric device, P (9) 231*f*.
Turner, A. H. Water cooled electrode head for electric furnace electrodes or the like, P (10) 269*b*.
Turner, C. W. Status of fly-ash brick, (9) 223*c*.
Turner, E. H. See Lenzo, P. V.
Turner, G. C. Phosphor fiber faceplate for cathode-ray tubes, P (7) 157*c*.
Turner, P. P., and Brassfield, H. C. Inhibition of grain growth in sintered beryllium oxide bodies, P (1) 7*h*.
Turner Brothers Asbestos Co., Ltd. Method of producing cellular material from a dispersion asbestos fiber, P (11) 282*f*.
Turney, A. C. See Trubey, P. W.
Turney, J. E. Storing glass sheets, P (4) 95*g*.
Tuthill, E. J., Weth, G. G., Emma, L. C., Strickland, G., and Hatch, L. P. Phosphate glass process for disposal of high level radioactive wastes, (10) 253*a*.
Tuttle, M. A. Critical path method, B (11) 303*h*. Simplex method for maximizing properties and minimizing costs, B (11) 303*h*.
Tuttle, M. A., and Funk, J. Water removal from clay, B (8) 212*c*.
Tutunarova, I. See Res, M.
Tuzi, Y. See Morrison, J. A.
Tuzikov, A. I. See Okhotin, M. V.
Tvergaard, A. M., Pack, A. H., Campbell, W. W., and Leatham, E. Kiln operation, P (9) 235*c*.
Tverskov, V. A., and Morozov, I. S. System $ZrCl_4$-$MgCl_2$-KCl, (11) 302*a*.
Tweddle, S. D. New fibrous glass industry for India, (7) 148*c*.
Tweedy, J. G. Fuel oil—the ceramic industry, (2) 52*g*.
Twells, R. G. Method for producing nonglare, low specular reflecting films on glass articles, P (9) 221*e*.
Twist, W., and Haigh, H. E. Apparatus for pulverizing, P (8) 190*b*.
Tydings, J. E. See Giardini, A. A.
Tyler, W. S., Inc. Vibrating screening apparatus with wedge ring support, P (7) 158*j*.
Tyson, W. R. Theoretical strength of perfect crystals, (8) 209*e*.
Tyukaev, V. I. See Kirillin, V. A.
Tyurin, Yu. M. See Aksenova, E. B.

Ubbelohde, A. R. See McAuley, W. J.
Uchida, E. See Nagamiya, T.
Uchida, E., Fukuoka, N., Kondoh, H., Takeda, T., Nakazumi, Y., and Nagamiya, T. Magnetic anisotropy measurements of CoO single crystal, (8) 202*c*.
Uchikawa, H., and Tsukiyama, K. Indexing of the powder X-ray diffraction patterns and the precise determination of the crystal structure of Ba_2SiO_4, (11) 297*f*.
Udalov, Yu. P. See Toropov, N. A.
Udovenko, N. G. See Bartenev, G. M.
Uebel, H. See Arndt, H. H.
Ueda, H. See Migitaka, M.; Takagi, T.; Tomono, M.
Ueda, I. See Ikegami, S.
Ueda, I., and Ikegami, S. Oxidation phenomena in semiconducting $BaTiO_3$, (9) 241*i*.
Ueda, K. See Kushida, A.
Ueda, R. See Yamanaka, M.
Uehara, K. See Tokuyama, T.
Ugai, Ya. A., Gordin, V. L., and Anokhin, V. Z. Production and some properties of Be_3Sb_2, (4) 109*j*.
Ugorets, M. Z. See Buketov, E. A.
Uhlir, A., Jr., and Jenkinson, J. V. Semiconductor point contact devices, P (4) 102*f*.
Uhlmann, D. R. See Jackson, K. A.; Seward, T. P., III; Vergano, P. J.
Uhlmann, D. R., Hays, J. F., and Turnbull, D. Effect of high pressure on crystallization kinetics with special reference to fused silica, (2) 36*b*.
Ukrainskii, Yu. M. See Aslanov, L. A.
Ukshe, E. A., and Bukun, N. G. Study of the salt systems $CaCl_2$-NaCl and $CaCl_2$-KCl by the capacitance method, (11) 301*j*.
Ulbricht, J. See Haase, T.
Ullery, L. R., Jr., and Garibotti, D. J. Method of fabricating thin film capacitors, P (10) 264*h*.
Ullrich, H. Method for producing a semiconductor with pn junction, P (3) 79*e*.
Ulmer, G. C., and Smothers, W. J. Application of mercury porosimetry to refractory materials, (8) 179*h*.
Ulrich, W. See Traustel, S.
Ul'yanov, V. L. See Ladokhin, S. V.
Umanskii, Ya. S. See Bol'shakov, K. A.
Umeno, M., Kawabe, H., and Shinoda, G. Lattice defect research by the Kossel technique and deformation analysis, B (5) 139*j*.
Underwood, E. E. Microstructures and properties, B (9) 244*f*.
Unglert, M. C. See Fraser, H. D.
Unilever, Ltd. Silicate materials, P (8) 190*i*.
Union Carbide Corp. Arc process and apparatus for growing crystals, P (8) 180*e*. Basic refractory bricks, P (4) 98*c*. Binding aid for gold trim on glass, P (3) 67*i*. Broad band circular polarizer utilizing a plate of pyrolytic boron nitride, P (7) 156*g*. Carbon foam, P (5) 124*c*. Carbonaceous ramming paste, P (5) 124*d*. Chemical admixture for hydraulic cementitious mixtures, P (2) 34*j*. Crystal growing furnace with an alumina liner, P (2) 52*f*. Electrochemical linear detector and porous electrode therefor, P (3) 78*c*. Electrodes for electrochemical logarithmic detector units, P (4) 101*c*. Flux-melt method for growing single crystals having the structure of beryl, P (11) 281*c*. Hydrogen anode including aluminum spinel and platinum family coatings and method of making same, P (5) 124*j*. Inert electrodes for electrochemical devices, P (7) 147*j*. Jaw crusher, P (9) 235*i*. Metal ceramic compositions, P (3) 72*i*. Method for con-

tinuous graphitization of carbonaceous thread, P (8) 190*h*. Method for determining the factor of anisotropy of resistivity of a graphite body, P (11) 289*i*. Method of purifying titanium diboride, P (8) 181*g*. Method of treating electrodes for use in electrochemical devices, P (9) 226*c*. Nuclear reactor fuel production, P (2) 44*h*. Preparation of aluminum nitride, P (5) 124*h*. Process for dispersing asbestos, P (4) 107*a*. Process for melting and refining glass batch, P (11) 279*a*. Process for polishing crystals, P (9) 213*g*. Process of preparing boron carbide from boron halide and a hydrocarbon, P (10) 260*i*. Production of catalyzed carbon electrode, P (8) 182*c*. Pyrometer, P (4) 105*a*. Radioactive spheroids coated with pyrolytic graphite, P (5) 125*c*. Refractories, P (9) 227*a*. Refractory articles, P (3) 73*c*. Submerged arc flux composition and method of making the same, P (8) 174*j*. Submerged-arc welding composition, P (9) 217*e*. Thermal mechanical mineral piercing, P (9) 236*i*.

Union Oil Co. of California. Crystalline titanosilicate zeolites, P (10) 269*c*. Crystalline zirconosilicate zeolites, P (10) 269*e*. High-silica molecular sieve zeolites, P (11) 291*k*. Hydrogen zeolite Y having improved hydrothermal stability, P (3) 83*c*. Methods for the manufacture of group IVB metallosilicate zeolites, P (10) 269*i*. Process for preparing a crystalline zeolite, P (4) 107*b*.

United Aircraft Corp. Alloy diffused transistor, P (11) 284*g*. Bonding of semiconductor devices to substrates, P (8) 184*c*. Coatings for columbium base alloys, P (3) 65*c*. Compensated tapped thermocouple system, P (5) 132*a*. Method of and apparatus for compacting ferrite particles, P (1) 11*b*. Method of fabricating thin film capacitors, P (10) 264*h*.

United Coke & Chemicals Co., Ltd. Production of electrically conducting carbon, P (7) 153*i*.

United Glass, Ltd. Mixing apparatus, P (1) 6*f*.

United Glassworks. See N. V. Vereenigde Glasfabrieken.

United Kingdom Atomic Energy Authority. Apparatus for fluidizing beds of particulate solids, P (3) 72*d*. Bonding of metal cladding to a cermet body, P (3) 72*e*. Coated particle fuels for nuclear reactors, P (7) 153*d*. Coating with beryllia, P (3) 65*c*. Manufacture of cermet bodies, P (11) 281*i*. Manufacture of cermet nuclear fuels and fuel elements, P (3) 72*i*. Manufacture of refractory compounds, P (10) 259*c*. Manufacture of sintered uranium dioxide bodies, P (5) 124*c*. Manufacture of uranium dioxide, P (3) 72*i*. Method of extruding carbon articles, P (9) 226*c*. Method of forming graphite articles, P (4) 98*d*. Method of making graphite articles, P (7) 153*j*. Method of testing graphite, P (2) 44*d*. Methods of extrusion, P (9) 233*a*. Nuclear fuel body containing uranium carbide spheroids coated with silicon carbide, P (1) 8*g*. Nuclear fuel components, P (7) 153*e*. Nuclear reactor fuel elements, P (1) 8*h*. Process and apparatus for the reaction of solids with liquids, P (2) 45*b*. Process for fabricating a fission product retentive nuclear fuel body, P (3) 72*f*. Process for producing high density uranium carbide-plutonium carbide pellets, P (11) 282*g*. Production of fuel for nuclear reactors, P (9) 227*g*. Production of nuclear fuel materials, P (5) 125*c*. Production of radioactive fused glass bodies, P (9) 222*b*. Refractory metal compounds, P (4) 99*g*. Testing for lead-210, P (7) 159*i*. Thermocouples, P (8) 188*h*.

United States of America, Administrator of the National Aeronautics and Space Administration. Apparatus for positioning and loading a test specimen, P (9) 234*c*. Metallic film diffusion for boundary lubrication, P (8) 181*h*. Method of forming thin window [lithium] drifted silicon charged particle detector, P (7) 157*d*. Method of making a silicon semiconductor device, P (7) 157*g*. Unfired-ceramic flame-resistant insulation and method of making the same, P (4) 99*d*.

United States of America, Secretary of Agriculture. Gas-solid chromatography using column comprising $AgNO_3$-coated alumina, P (4) 98*i*.

United States of America, Secretary of the Air Force. Ablative reinforced plastic article and method of making same, P (9) 225*j*. Al-Si-Mn-Li anode for high temperature galvanic cell, P (4) 92*c*. Continuous multistage void differential-density hybrid zone melting apparatus, P (7) 156*a*. Graphite thermocouples and method of making, P (5) 132*a*. Method for making high purity fine particle oxides, P (4) 106*e*. Method of making an optical fiber phosphor screen, P (3) 68*g*. Modulated light source for electrooptical analysis of spectral lines, P (4) 104*j*. Radiation pyrometer and temperature standard therefor, P (8) 188*f*.

United States of America, Secretary of the Army. Gaseous discharge lamp with internally cooled electrodes, P (7) 149*d*. Grooved active medium for laser, P (4) 101*h*. Method of coating a metal surface with a ferrite composition, P (2) 48*e*. Method of firing ceramics, P (2) 48*g*. Methods for controlling the thermal expansion properties of ceramics, P (7) 155*d*. Microwave power limiter utilizing a planar ferrite sphere [Mn-ZnV], P (8) 185*c*. Piezoelectric wide bandpass filter with elliptical shape, P (8) 185*h*. Process for producing lead titanate powder, P (10) 265*a*. Pyrolytic graphite coating process, P (8) 182*a*. Radiant heat reflective coatings and method for application, P (2) 35*f*. Single crystal barium titanate, P (1) 11*h*. Synthesis of diamond, P (9) 213*g*. Variable delay line, P (2) 49*f*.

United States of America, Secretary of the Interior. Flotation of mica, P (1) 15*g*, P (10) 269*e*. Process for decomposing manganese sulfate to form manganous oxide and sulfur dioxide, P (4) 106*j*. Synthesis of aluminum silicate whiskers, P (9) 227*h*. Top closure for high temperature electrostatic precipitator, P (3) 80*f*.

United States of America, Secretary of the Navy. Apparatus for determining the shape of colloidal particles using light scattering, P (4) 104*h*. Fabrication of magnetoresistive semiconductor film devices, P (11) 285*a*. Hermetically sealed thin film module, P (8) 184*g*. Method for fabricating thin film transistors, P (4) 101*f*. Method of forming a glass reinforced filament plastic tape, P (5) 121*c*. Method for making single crystal graphite sheets, P (2) 44*a*. Piezoelectric crystal evaluator, P (3) 81*h*. Preparation of hydrates of $2CaO \cdot 3B_2O_3$, P (11) 291*a*. Preparation of thin film indium antimonide from bulk indium antimonide, P (11) 287*d*. Prestressed spherical electroacoustic transducer, P (8) 185*j*. Process for the preparation of the strontium isomorph of colemanite, P (10) 269*i*. Process for preparing the strontium isomorph of colemanite, P (11) 291*k*. Process for producing semiconductor-film Hall devices on oxide-metal substrate, P (9) 232*d*. Radome ness for a missile, and method of making same, P (11) 282*j*. Segmented ferrite sonar transducer with permanent magnet bias, P (4) 102*b*. Strip transmission line ferrite filter-limiter having a ferrite sphere positioned beneath overlapping conductors, P (2) 49*a*. Thermoelectric unit comprising intimate layers of gallium-indium alloy and alumina, P (11) 288*a*. Transducer array for underwater transponder, P (1) 12*c*.

United States of America, U.S. Atomic Energy Commission. Amorphous zinc oxide semiconductor and method of making, P (3) 77*i*. Apparatus for coating a cathodically biased substrate from plasma of ionized coating material, P (10) 263*b*. Apparatus for coating substrates by cathode sputtering, P (3) 77*j*. Ceramic loaded buncher for linear accelerators, P (11) 285*a*. Cermet materials and process of making, P (1) 7*b*. Coated nuclear reactor fuel particle of UO_2 and method of making the same, P (3) 72*e*. Conversion of U_3O_8 to UC, P (8) 180*j*. Crucible reactor and method, P (10) 259*g*. Efficient beta-ray emission source for irradiation applications, P (9) 230*c*. Electrolytic deposition of actinide oxides, P (8) 181*a*. Fuel element containing a mechanically compressible mandrel, P (2) 44*b*. Graphite welding, P (2) 44*e*. High temperature isostatic pressing, P (1) 12*g*. Hollow spherical UO_2 nuclear fuel particles, P (3) 72*g*. Inhibition of grain growth in sintered beryllium oxide bodies, P (1) 7*k*. Liquid phase extrusion for forming refractory materials, P (8) 181*f*. Method and apparatus for determining drift depth of impurities in semiconductors, P (3) 78*e*. Method and catalyst for combining hydrogen and oxygen in thorium oxide slurries, P (7) 153*k*. Method of determining the particle size distribution of a powder, P (10) 268*d*. Method for [platinum] bonding beryllium oxide to graphite, P (4) 98*e*. Method for preparation of urania sols, P (2) 44*b*. Method for preparing actinide oxide fuel particles and article thereof, P (4) 98*f*. Method for preparing metal oxide microspheres, P (10) 259*h*. Method of preparing oxides for neutronic reactor control, P (4) 98*g*. Method of preparing plutonium mononitride, P (1) 8*a*. Method of producing nuclear fuel elements of stainless steel coated UO_2 particles, P (8) 181*g*. Method for separating members of actinide and lanthanide groups, P (1) 15*j*. Method of separating UF_6 from bromine fluorides, P (9) 226*b*. Method of stabilizing plutonium dioxide, P (10) 259*i*. Method of temperature cycling ferroelectric ceramics through a temperature range below the Curie point thereof, P (1) 11*k*. Microscope in combination with a microspark probe including an unshielded electrode of small tip radius, P (8) 188*c*. Nuclear reactor fuel material and a method of preparing the same, P (2) 44*g*. One-step method of converting uranium hexafluoride to uranium compounds, P (10) 260*a*. Openly porous refractory nuclear fuel microspheres and method of preparation, P (8) 181*i*. Preparation of actinide metal carbide microspheres, P (4) 98*i*. Preparation of a filterable coprecipitate of plutonium and uranium, P (3) 72*d*. Preparation of plutonium oxide sol and calcined microspheres, P (7) 153*g*. Preparation of uranium aluminides UAl_3 and $UAl_{4.5}$, P (2) 45*a*. Pressure bonded ceramic-to-metal gradient seals, P (9) 231*i*. Process for chlorinating oxides, P (3) 72*f*. Process for making gelled spherical particles of oxides, P (10) 269*i*. Process for preparing oxide gel microspheres from sols, P (3) 83*a*. Process for the reprocessing of irradiated compact fuels by fluorination, P (11) 282*i*. Process for separating strontium values from rare earth metal values, P (2) 54*d*. Pyrohydrolysis of carbide-type nuclear fuels, P (1) 8*b*. Pyrolytic carbon coated particles for nuclear applications, P (4) 99*e*. Separation of uranium from uranium dioxide-zirconium dioxide mixtures, P (11) 283*b*. Surface-barrier diode for detecting high energy particles and method for preparing same, P (8) 186*a*. Synthetic swelling lithium aluminum silicate hydrate product, P (5) 126*b*. Thermoelectric converter composition, P (3) 79*h*. Thorium oxide or thorium-uranium oxide with magnesium oxide, P (7) 154*d*. Tungsten-osmium thermocouple and element thereof, P (8) 188*i*. Tungsten slip casting method, P (9) 227*i*. Uranium mononitride-sodium paste nuclear fuel, P (11) 283*e*. Vapor phase sintering process, P (3) 73*d*. Zeolite agglomerates and the preparation thereof, P (3) 83*g*.

United States Borax & Chemical Corp. Ceramic composition, P (5) 122*b*. Crystalline sodium metaborate tetrahydrate and process for production thereof, P (4) 106*b*.

United States Gypsum Co. Apparatus for making ultrafine calcium sulfate dihydrate crystals, P (5) 116*c*. Plaster composition, P (5) 117*a*. Plaster composition containing polyvinyl acetate, P (5) 117*b*. Process of producing glass in a cupola, P (3) 69*b*. Substantially dry joint compound comprising calcium sulfate, polyvinyl acetate, and starch, P (4) 91*g*.

United States Rubber Co. Rubber latex, graphite, and cement, P (4) 91*f*.

United States Steel Corp. Centrifugal spraying equipment, P (1) 12*d*. Coated chimney, P (1) 7*d*. Embrittlement-free pickling of ferrous metal, P (7) 147*i*. Method of making magnesium oxide fibers, P (9) 226*e*. Refractory composition and method of preparation, P (1) 8*e*.

United States Stoneware, Inc. Ball mill or the like, P (4) 103*d*. Method of vibratory milling, P (4) 103*h*.

United Steel Co., Ltd. See Holmes, W. C., & Co., Ltd.

Universal Grinding Wheel Co., Ltd. Flexible abrasive products, P (3) 63*h*.

Universal Moulded Fiber Glass Corp. Method and apparatus for making continuous lengths of threaded fiber reinforced resin articles, P (2) 39*d*. Method and apparatus for making elongated articles of fiber reinforced resin material, P (5) 121*a*.

Universal Oil Products Co. Catalytic infrared heater, P (7) 160*f*. Manufacture of high purity alumina sol from relatively low grade aluminum, P (11) 281*j*.

Universal-Rundle Corp. Mold for ceramic casting, P (1) 9*c*.

Univis, Inc. Method of making molds for multifocal ophthalmic lenses, P (4) 95*c*.

Uno, R. Structure and temperature factors of CoO, (7) 168*e*. Structure and temperature factors of NiO, (7) 168*f*. X-ray study on electron distributions in some monoxides of transition elements, (9) 243*f*.

Unoki, H. See Sakudo, T.

Untiedt, J. H. See Gatti, A.

Upadhyaya, G. S., and McQuillan, A. D. Crystal structure of saturated mixed hydrides of titanium and niobium, (3) 84*b*.

Upadhyayula, L. C. See Subramanian, T. V. A.

Uppal, H. L., and Singh, G. Pozzolan surkhi from burned clay brick, (2) 40*k*.

Upton, L. O., and Chwalek, E. J. Lens holder, P (11) 278*d*.

Urani, A. Glass-encased electric fuses, P (5) 127*e*.

Urbain, G. See Rossin, R.

Uretsky, C. L. See Gross, S. B.

Urmetz, W. W., and Carpenter, J. C. Bottom ring-wiper strip assembly [for a hot top] and method of making it, P (10) 259*e*.

Urnes, S. Remarks on the validity of the Nernst-Einstein equation in alkali silicate glass systems, (11) 277*j*.

Urrestarazu, H. Refractory industry in France, (4) 97*f*.

Urushida, K., and Anazawa, S. Glass sealed ceramic housings for semiconductor devices, P (10) 264*b*.

Urushido, H. See Shiraki, Y.

Urusov, V. S., and Shcherbina, V. V. Energy characteristics and some geochemical features of titanates, (11) 295*e*.

Usher, G. W. Sink units, P (2) 46*g*.

Usov, P. M. See Smirnov, M. V.

Usov, P. M., and Smirnov, M. V. Cathodic polarization during electrolysis of lanthanum trichloride, B (1) 30*d*.

Ustinova, V. F. See Matveev, M. A.

Ust'yantsev, V. M. See Bessonov, A. F.; Strekalovskii, V. N.

Uteush, Z. V., Kotik, P. L., et al. Automation of grinding process in ball mills, (8) 186*f*.

Utsumi, R. See Kushida, A.

Uyeda, R., and Nonoyama, M. Electron microscope study on the extinction and absorption of 100 kv electrons in magnesium oxide single crystals, (11) 294*k*.

Uzberg, A. I. See Vydrina, Zh. A.

Vach, J. Electrical melting of glass (II) types of furnaces, (3) 66*g*.

Vagnard, G., and Manenc, J. Study of the deformation at high temperatures of iron and copper oxides, (2) 56*b*.

Vahldiek, F. W. See Lynch, C. T.; Mersol, S. A.

Vahldiek, F. W., Mersol, S. A., and Lynch, C. T. Microhardness anisotropy, slip, and twinning in Mo_2C single crystals, (8) 202*d*.

Vahrenkamp, G. J., and Coppersmith, F. M. Process for producing lead oxides, P (9) 236*h*.

Vainshtein, A. L. See Galdina, N. M.

Vainshtein, E. E. See Ovsyannikov, I. O.
Vainshtein, E. E., Blokhin, S. M., and Paderno, Yu. B. X-ray L-absorption spectra of lanthanum in tetra- and hexaborides with imperfect lattices, (4) 112*e*.
Vaisfel'd, N. M., and Shelyubskii, V. I. Possibilities of electron microscopy for investigating the structure of glass, B (7) 171*a*.
Vakhovskaya, M. R. See Kreimer, G. S.
Vakhrushev, B. M. Use of waste sulfite liquor as slurry diluent and cement plasticizer, (9) 215*f*.
Valchar, C. E. See Barch, H. W.
Valchar, C. E., and Mrozinski, S. J. Method of and apparatus for shaping glass sheets with opposed pressing members, P (10) 255*d*.
Valente, M. Masonry tile, P (3) 70*f*.
Vallance, T. G. Mafic rock alteration and isochemical development of some cordierite-anthophyllite rocks, (8) 202*b*.
Vallebona, A. Packaging device for flat glass, P (5) 121*d*.
Valletta, R. M. See Hallen, R. L.
Valley Dolomite Corp. Formulations for gunning refractories, P (10) 259*i*. Magnesia-zircon refractories, P (5) 124*c*.
Val'ter, O. I. See Kostyuk, V. A.
Van, Gen'-Shi. See Komissarova, L. N.
Van Asbroeck, P. Influence of fabrication parameters on the quality of plutonium fuel elements, (7) 151*c*. See Massaux, H.
Van Avery, P. 4000 degrees plus transparency, (9) 224*c*.
Vancu, A. See Tauc, J.
Vand, V. See Greer, R. T.
Vand, V., Vedam, K., and Stein, R. Laser as a light source for ultramicroscopy and light scattering by imperfections in crystals—investigation of imperfections in LiF, MgO, and ruby, (1) 21*e*.
Van Der Beck, R. R., Jr. Ceramic product and its preparation, P (1) 9*b*.
Vanderpool, C. D. See Chiola, V.
Vandervoort, R. R. See Barmore, W. L.; Cline, C. F.
Vandervoort, R. R., and Barmore, W. L. Dislocation etch pits in single-crystal and polycrystalline beryllium oxide, (4) 107*i*.
Van Dolah, H. J., Linhart, O. C., and Kiefer, A. Method for manufacturing porcelain enamel frit, P (1) 3*a*.
Van Dreser, M. L. Developments with high-purity periclase, (3) 71*e*. See Alder, W. R.; Hildinger, W. M.; Martinet, J. R.
Van Dreser, M. L., and Anderson, W. G. Calcareous refractory composition, P (11) 281*h*.
Van Hise, C. W. Method of soldering semiconductor disks, P (2) 48*d*.
Van Hook, H. J. Apparatus for high pressure high temperature studies of oxide materials, (2) 50*e*. Oxygen stoichiometry in the compound $BaFeO_{3-x}$, (8) 204*h*.
Vanik, M. C. See Fitch, F. T.; Hurley, F. R.
Vannerberg, N. G. Crystal structure of calcium carbide III, (3) 84*j*.
Van Neste, W. A. H. See Moeken, H. H. P.
Van Orsdel, J. R. See McCurdy, H. R.
Van Riper, C., and Willis, D. B. Reducing costs in carbide grinding, (1) 1*f*.
Van Rynveld, W. P., and Loubser, J. H. N. Electron spin resonance in electron-irradiated *n*-type silicon carbide, (3) 85*f*.
Van Tilburg, R. W. See Cole, F.
Van Tuyl, H. H. Process for separating strontium values from rare earth metal values, P (2) 54*d*.
Van Uitert, L. G. See Ballman, A. A.; Johnson, L. F.; LeCraw, R. C.; Rubin, J. J.
Van Vlack, L. H. See Hosford, W. F., Jr.; Madden, G. I.; Mehta, J. M.
Van Vleck, J. H. Crystal field parameters of rare-earth garnets, (9) 237*e*. See Schieber, M. M.
Van Zee, A. F. See Loehrke, H. F.; McMaster, H. A.
Vargin, V. V., and Kheifets, V. S. Crystallization processes in zirconia glasses and enamels, (3) 65*j*.
Varian Associates. Art of sealing quartz to metal, P (1) 10*g*. Gaseous microwave switching tube apparatus, said tube including closely packed solid ceramic alumina spheres, P (10) 264*a*. Grain-oriented dispenser thermionic emitter for electron discharge device, P (3) 78*j*. Grain-oriented thermionic emitter for electron discharge devices, P (2) 47*h*. Method and material for metallizing ceramics, P (3) 79*a*. Method of preparing an electron tube including sputtering a suboxide of titanium on dielectric components thereof, P (7) 157*h*. Method for reducing electron multipactor on a dielectric window surface, P (10) 264*i*.
Varnado, T. E., Jr. See Posey, B., Jr.
Varshney, K. G. See Quershi, M.
Varvarina, A. I. See Lande, P. A.
Vasilev, V. See Kotovich, V.
Vasil'eva, K. F. See Dygalo, M. I.
Vasil'kova, I. V. See Smirnova, E. K.
Vasil'kova, I. V., Efimov, A. I., and Pitirimov, B. Z. Complex formation in systems MCl-$CrCl_3$ (M = alkali metals), (9) 237*j*.
Vasil'kova, I. V., Zaitseva, N. D., and Petrova, V. A. Systems RbCl-WCl_5, RbCl-WCl_6, CsCl-WCl_5, and CsCl-WCl_6, (1) 29*i*.
Vasilos, T. See Passmore, E. M.; Sellers, D. J.; Spriggs, R. M.
Vasilos, T., and Spriggs, R. M. Hot-pressing of ceramics, B (7) 170*i*.
Vassell, M. O. See Conwell, E. M.
Vassell, W. C. See Lambe, J.
Vassiliadis, C., Kawassiades, C. T., Hadjiioannou, T. P., and Colovos, G. Automatic derivative spectrophotometric titration of iron and/or aluminum with EDTA, (1) 13*d*.
Vatterodt, K. See Weiss, W.
Vaughan, H. H. See Bunge, F. H.
Vaugoyeau, H. See Blum, P.
Vause, A. S., and Wright, J. W. T. Electric incandescent lamps, P (2) 38*d*.
Vavra, R. Possibilities of accelerating the dissolving process of sodium silicate, (10) 266*c*.
Veatch, F. See Alford, H. E.
VEB Carl Zeiss Jena. Methods and instruments for analyzing ternary mixtures by means of a two-beam interferometer, P (5) 132*c*. See Jenaer Glaswerk Schott & Co.
VEB Farbenfabrik Wolfen. Method of making molecular sieves, P (3) 83*f*.
VEB Glasfaserwerk Steinach. Machine for making short fibers particularly from glass, P (8) 177*i*.
VEB Keramische Werke Hermadorf. Process for making oxide material of high refractoriness and good thermal shock resistance, P (10) 260*g*.
Vecher, A. A. Thermodynamic properties of oxide systems (I) calculation from experimental data of the thermodynamic properties of solid solutions of ferrites, (11) 302*i*.
Vedam, K. See Vand, V.
Vedder, W., and Ketterer, R. J. Inorganic-bonded reconstituted mica sheet, P (7) 156*g*.
Veigel, N. D. See Oxley, J. H.
Veiguela, D. F. See Fernandez Veiguela, D.
Veitscher Magnesitwerke Akt.-Ges. Basic or neutral refractory brick containing carbon and process for the production thereof, P (9) 225*b*. Carbon-impregnated refractive magnesia bodies and method of preparing the same, P (2) 43*f*. Ceramic recuperators, P (10) 268*j*. Ceramic and tar bonded brick furnace lining, P (11) 281*j*. Composite refractory blocks, P (1) 7*e*. Refractory flue brick for ceramic recuperators and the recuperators, P (11) 283*d*.
Velikanova, T. Ya. See Eremenko, V. N.
Ven, A. J. C. van der. See Botden, T. P. J.
Veran, Costamagna & Cie. Insulating brick, P (8) 181*e*.
Verch, G. O. Multiple compartment grinding mills, P (4) 106*i*.
Verdieck, R. G., and Beumel, O. F., Jr. Preparation of lithium aluminum hydride, P (11) 291*b*.
Verduch, A. G. See Garcia Verduch, A.
Vereinigte Glanzstoff-Fabriken Akt.-Ges. Continuous drying of granular materials, P (1) 14*h*.
Vereinigte Oesterreichische Eisenund Stahlwerke A. G. Crucibles or converters, P (3) 72*g*.
Vereinigung Volkseigener Betriebe Glas Dresden. Glass primarily for the production of glass fibers, P (5) 120*c*. Molds for the production of blocks of silicate material, P (2) 39*g*.
Veres, F. Luminescent glass articles and method for forming same, P (4) 94*a*.
Vereshchagina, V. I., Zakharchenko, M. A., and Belogorskaya, N. V. Cross sections of the quaternary reciprocal system of the fluorides and chlorides of lithium, sodium, and barium, (11) 293*e*.
Vergano, P. J., Hill, D. C., and Uhlmann, D. R. Thermal expansion of feldspar glasses, (2) 38*a*.
Verhaegen, G. See Colin, R.; Drowart, J.
Verhaegen, G., Colin, R., Exsteen, G., and Drowart, J. Mass-spectrometric determination of the stability of gaseous molybdites, tungstites, molybdates, and tungstates of magnesium, calcium, strontium, and tin, (1) 22*e*.
Verkhoglyadova, T. S. See Korsunskii, M. I.
Verkhorobin, L. F., Glushko, P. I., Dorokhov, V. I., and Matyushenko, N. N. Interaction of molybdenum disilicide with beryllium, (3) 86*h*.
Verly, M. J. G. Machine for the manufacture of plates from fiber loaded paste, such as asbestos-cement paste, P (9) 233*e*.
Verma, M. R., and Trehan, J. C. Analytical studies on basic magnesium carbonate and asbestos lagging composition, (11) 290*j*.
Verma, M. R., Trehen, J. C., and Dabas, M. S. Analysis of asbestos-cement products, (11) 274*g*.
Verma, S. P. India's cement and ceramic industries, (7) 169*g*.
Vermilyea, D. A. Ta_2O_5 films formed with non-steady potentials, (4) 111*i*.
Vernikovskii, V. E. Characteristics of filling devices for presses in the refractories industry, (5) 122*i*.
Vernon, R. H. See Wilkinson, J. F. G.
Verson Mfg. Co. Control of charge for ceramic extrusion, P (8) 186*g*. Unloader for green ceramic ware, P (2) 46*g*.
Vertsner, V. N. See Alekseev, A. G.
Vescia, M., Schwindt, W., Dietrich, W., Perkuhn, U., Faulhaber, G., Wolf, H., and Wilhelm, H. Dyed and printed glass fibers and a process for dyeing and printing glass fibers, P (8) 177*c*.
Vesely, V. See Pribil, R.
Vest, R. W. See Tallan, N. M.
Vesuvius Crucible Co. Stopper for a ladle or similar receptacle, P (2) 45*h*, P (3) 73*b*.
Veverka, V. C. See Krautheim, E. H.
Vevoda, E. Process and apparatus for manufacturing mosaics, P (4) 100*a*.
Vian, R. W. See Levinson, A. A.
Vibrasonics, Inc. Piezoelectric ceramic transformer, P (4) 102*g*.
Vickers Armstrongs (Engineers), Ltd. Apparatus for heating powdered material such as raw cement material, P (4) 91*d*.
Vickery, R. C. Laser materials, P (11) 285*i*. See Wright, A. J.
Vickery, R. C., and Fisher, J. V. Transparent magnetic glass compositions, P (8) 179*a*.
Vickery, R. C., and Hipp, J. C. Molybdenum dioxide single crystals, (1) 23*a*.
Vidro, L. I. See Indenbom, V. L.
Vie, G. Clays from the Comminges for use in ceramics, (7) 150*g*.
Viechnicki, D. See Stubican, V. S.
Vieli, O. A. Cellular glass and method of making same, P (9) 219*b*.
Vieth, W. R. See Michaels, A. S.
Vigileva, E. S. See Eliseev, A. A.
Viktorova, Yu. N. See Brekhovskikh, S. M.
Vilaltella, J. L. Improvements in apparatus for the construction of furnace arches, P (2) 53*b*.
Vilenskaya, E. I. See Okhotin, M. V.
Vil'k, Yu. N. See Avarbe, R. G.; Nikol'skaya, T. A.
Vil'k, Yu. N., Avarbe, R. G., Neshpor, V. S., Ryzhkova, T. P., and Omel'chenko, Yu. A. Interaction of niobium carbide with tungsten, (8) 200*b*.
Villa, A. Effect of pressing with friction and hydraulic presses on glazing, (5) 125*h*.
Villers, G. See Lecerf, A.
Vincent, G. L. Quality ferrites from crude iron ore, (4) 100*c*.
Vincent, J. S. See Fessler, T. E.
Vincenzini, P. Glass ceramics (III) crystallization catalysts and types of glass used in the production of glass ceramics, (10) 252*c*.
Vinokur, S. V. See Tsigler, V. D.
Vintaikin, E. Z. Free energy of formation of chromium carbide, (3) 85*j*.
Viscakas, J., Gaidelis, V., and Montrimas, E. Capacity of selenium and zinc oxide electrophotographic layers, (5) 134*i*. Effect of intercrystalline barriers on kinetics of photoconductivity, (11) 294*a*.
Viscakas, J., Matulionis, A., and Juska, G. Characteristics of the photocurrent normal to an illuminated surface of vitreous selenium, (5) 134*a*.
Visser, J. Hot-cathode magnetron ionization gage with photocurrent suppressor, (9) 233*h*.
Vit, E. F. See Kozin, G. N.
Vitta Corp. Ceramic-metallizing tape, P (3) 77*e*.
Viudes, P. de la, C. See Cierva Viudes, P. de la.
Viva, O. R. See Hess, M. S.
Vlasov, A. S., and Poluboyarinov, D. N. Exothermic reactions in the production of chromium-alumina cermets, (4) 96*g*.
Vlasov, K. R. See Samsonov, G. V.
Vlasov, V. G. See Strekalovskii, V. N.; Tkachenko, E. V.; Zhukovskii, V. M.
Vogel, F. L., Jr. Method of making semiconductive devices by means of a carrier gas with impurities, P (11) 286*j*.
Vogel, H. See Gugel, E.
Vogel, M. J., and Brookman, J. W. Method of preparing fluorescent rare earth compounds, P (3) 83*f*.
Vogel, R. R., and Mills, D. S. Method and apparatus for hydrostatically compacting metal powders, P (8) 186*h*.
Vogel, R. S. Microscope in combination with a microspark probe including an unshielded electrode of small tip radius, P (8) 188*c*.
Vogel, W. Microheterogeneous structure of glass, B (7) 171*a*.
Vogelpohl, R. L. Mold and plunger for pressing flanged glass articles, P (4) 95*f*.
Vogg, H. H. Method of reprocessing and/or separating nuclear fuels, P (9) 226*a*.
Voigt, J. Face brick—semidry pressed? (3) 70*d*.
Voith, J. M., G.m.b.H. Apparatus for dewatering suspensions, P (2) 49*i*.
Volchek, K. See Matveev, M. A.
Volchenok, M. K. See Lur'e, M. A.
Voldan, J. Controlled crystallization of fused rocks, (10) 256*j*. Crystallization rate of main phases separated from the basalt melt, (3) 84*c*.
Volin, M. E. See Hockings, W. A.
Volk, H. F. See Criscione, J. M.
Vol'kenshtein, M. V. See Sharonov, Yu. A.
Volkodatov, A. F. See Matveev, M. A.
Volkov, N. V. See Pirogov, A. A.
Volodin, V. P., Ozeryanaya, I. N., and Smirnov, M. V. Corrosion of zirconium in molten chlorides of alkali metals, B (1) 30*e*.
Volostnykh, G. T. Temperature of the main endothermal effect of kaolinite, (8) 209*j*.
Vol'skaya, O. B. See Tsinzerling, E. V.
Vol'skaya, S. Z. See Aslanova, M. S.
Volterra, V., Bronstein, J., and Rockni, M. EPR measurements of some orthorhombic sites of Ce^{3+} and Nd^{3+} in $CaWO_4$, (8) 197*b*.
Voltmer, F. W. See White, R. M.
Von Bichowsky, F. Process for the preparation of a titanate containing two alkali metals, P (8) 186*a*.
Vondracek, C. H. See Westervelt, D. C.
Von Freyhold, H. Formation of solid bodies, P (9) 225*g*.
Vorob'ev, G. V., Pal'guev, S. F., and Karpachev, S. V. Viscosity of molten carbonates of alkali metals (I) Na_2CO_3-K_2CO_3, Li_2CO_3-Na_2CO_3, and Li_2CO_3-K_2CO_3 systems, B (1) 30*c*.
Vorob'ev, N. I. See Pechkovskii, V. V.
Voronin, N. I. See Bresker, R. I.
Voronin, N. I., Kortel, A. A., and Bresker, R. I. Improving silicon carbide elements by metal impregnation, (1) 7*e*.
Voronin, N. I., and Krasotkina, N. I. Phase composition of silicon carbide refractories bonded with silicon nitride, (4) 97*j*.
Voronin, N. I., Krasotkina, N. I., et al. Refractories and ramming bodies for high output burners in steam boilers, (5) 123*j*.
Voronkova, Z. P. See Dertev, N. K.

Voronov, F. F., and Stal'gorova, O. V. Effect of hydrostatic pressure on the elastic properties of powder metal cutting alloys, (4) 96*e*.
Vos, G. See Conti, R.
Voss, R. Abrasive coated backing of sheathed synthetic fiber yarns, P (8) 173*g*.
Voss, R. O. See Karstetter, B. R.
Vossen, J. C. A. Process of manufacturing a pigment from titanium dioxide and zinc oxide, P (11) 291*e*.
Vratny, F. Tantalum oxide films prepared by oxygen plasma anodization and reactive sputtering, (7) 156*d*.
Vrenken, L. E., and Mollet, A. J. T. Method of manufacturing curved gas discharge lamps, P (3) 68*k*.
Vries, E. R. de. Colored reflective coating composition, P (2) 38*b*. Marking materials, P (2) 39*a*.
Vrolijks, M. H. M., and Koorneef, J. Method of manufacturing parts of annular magnetic heads, P (10) 264*e*.
Vromen, B. H. See Keller, H. N.
Vrugt, J. W. ter. See Wanmaker, W. L.
Vsesoyuznyi Nauchno-Issledovatel'skii Institut Burovoi Tekhniki. Device for grading loose-material granules by weight, P (4) 103*e*.
Vsesoyuznyi Nauchno-Issledovatel'skii Institut Stroitelnovo i Dorozhnovo Mashinostroenie. Jaw crusher, P (2) 54*c*.
Vukasovich, M. S., and Harkulich, T. M. Glass bead making apparatus, P (11) 278*g*.
Vuyk, J. See Hoens, M. F. A.
Vyas, B. R. See Moorthy, V. K.
Vydrina, Zh. A., Panarin, A. P., and Uzberg, A. I. Testing periclase-spinel brick in open-hearth roofs, (5) 123*i*.
Vylegzhanina, T. V. See Savitskii, E. M.
Vysotskii, D. A. See Butt, Yu. M.
Vytasil V. Problem of the flow characteristics of enamel slips, (7) 147*i*.

Waage, K. M. See Denson, N. M.
Waagner-Biro Akt.-Ges. Method and apparatus for separating suspended particles from gases, P (11) 288*i*.
Wachtman, J. B., Jr. Mechanical properties of ceramics—an introductory survey, (9) 244*a*.
Wacker, H. A. Surface-passivated alloy semiconductor devices and method for producing them, P (11) 287*j*.
Wacker-Chemie G.m.b.H. Method of absorbing or dispensing and reacting gases in liquids, P (7) 158*e*. Method for controlled doping of crystalline substances, P (8) 185*b*. Preparations of silicone water repellents for masonry materials, P (7) 151*a*. Process for the manufacture of electrical insulating compositions, P (5) 128*i*. Process for the manufacture of very pure silicon carbide, P (8) 190*e*. Process for the production and insulation of apparatus made of glass ceramic or synthetic resins, P (7) 150*e*.
Wada, M. See Watanabe, H.
Wada, Y. See Hirose, H.
Wadham, H. Method of and apparatus for mixing, grinding, dispersing, or dissolving materials comprising solid particles in a liquid, P (10) 266*b*.
Wadsley, A. D. See Andersson, S.; Graham, J.
Wadsten, T. Crystal structure of SiAs, (8) 193*i*.
Wadsworth, M. E. See Hanson, C. K.
Wagner, A. E. Apparatus for expanding heat-expandable ores, P (7) 160*c*.
Wagner, A. E., and Adkins, J. S. Furnace structure for expanding heat-expandable ores, P (7) 160*a*.
Wagner, C. N. J. See Halder, N. C.; Light, T. B.
Wagner, J. B., Jr. See Fueki, K.
Wagner, P. Versatile high temperature furnace, (1) 14*i*.
Wagner, P. R. Method for rapid removal of metallic Ga from GaP crystals, (7) 155*h*. See Crowder, B. L.
Wagner, R. S. See Treuting, R. G.
Wagner Electric Corp. Process of manufacture of incandescent lamp, P (11) 279*h*. Silicon diode with solder composition attaching ohmic contacts, P (10) 265*d*.
Wahl, E. A. Vibratory conveyor-mixer apparatus, P (4) 103*j*.
Wahl, E. F. Dispersion process, P (11) 288*h*.
Wahlbeck, P. G. See Suzuki, A.
Wahman, L. A. See Fries, R. J.
Wainer, E. Fiber reinforced metals containing bond promoting components, P (2) 44*a*. See Burnham, K. D.
Wait, E. See Wheeler, V. J.
Waitkins, G. R. See Quinn, P. D.
Wakabayashi, T. Discussion on the compressibility of powder masses, (3) 84*j*.
Wakatsuki, M. Simple method of selecting the materials for compressible gasket, (11) 300*h*.
Waki, S. See Ogawa, S.
Waldeck, W. F. Method of preparing calcite and the product thereof, P (8) 190*c*.
Walen, N., Jr., and Schreiner, W. C. Clay calcining process, P (8) 190*d*.
Wales, R. D. Production of oxidic films on germanium, P (7) 148*a*.
Walford, L. K., and Cargill, G. S., III. Use of X-ray topography for the observation and characterization of gross imperfections in sapphire single crystals, (10) 272*i*.
Walker, A. J. Electric furnaces, P (4) 105*d*.
Walker, B. See Gee-Pemberton, R.
Walker, B. E., Ewing, C. T., and Miller, R. R. Instability of noble metal thermocouples in vacuo, (2) 50*f*.
Walker, D. C. B. See Summers, L.
Walker, E. A. See Palframan, J. F.
Walker, G. A. See Eubank, W. R.
Walker, G. F. Suspensions of silicate layer minerals and products made therefrom, P (9) 236*h*.
Walker, H. N. See McCarthy, W. W.
Walker, H. N., and McCarthy, W. W. Ultrasonic dispersion of clay bodies, (3) 80*b*.
Walker, J. See Hughes, B. P.
Walker, L., and Marshall, A. Improvements in processes and apparatus for treating clay and analogous refractory materials, P (11) 288*j*.
Walker, R. E. See Kirchner, H. P.
Walker, R. F. High temperature measurements and standards, 1000° to 3000°, B (5) 140*a*. Temperature measurement in high temperature chemistry—1000° to 3000°C, (7) 159*d*.
Walker, R. M. See Price, P. B.
Walker, W. W., and Demer, L. J. Effect of loading duration on indentation hardness, (3) 85*b*.
Walker Mfg. Co. Ceramic coated muffler, P (2) 35*i*. Ceramic coated muffler with drainage openings, P (7) 147*h*.
Wall, G. C. See Flanary, J. R.
Wall, R. A. See Riseman, J. H.
Wallace, D. C. See Glower, D. D.
Wallace, R. W., and Rub, E. Electrical resistivity of refractories, (8) 179*i*.
Wallace, T. C., Krikorian, N. H., and Stone, P. L. High carbon portion of the uranium-gadolinium-carbon system, (7) 164*e*.
Wallenberg, V. H. Urinals, P (3) 75*c*.
Wallert, I. Pectoral of the eighteenth dynasty, (11) 274*c*.
Walley, C. N. Experiments on the firing of pipes, (9) 222*i*.
Wallis, G. See Wolsky, S. P.
Wallis, H. F. Why so slow off the mark with packaged bricks? (11) 280*a*.
Wallmann, J. C. Structural transformation of curium sesquioxide, (8) 207*d*.
Wallwork, C. M. G. Method and apparatus for making cored [sand] casting molds, P (9) 226*c*.
Walsh, A., and Sullivan, J. V. High intensity atomic spectral lamps, P (5) 127*g*.
Walsh, P. J. See Larson, D. A.
Walsh, W. See Black, H. R.
Walt, J. P. Refractory brick units, P (2) 45*c*.
Walter, A. J. See Cohen, D.
Walter, K. H. See Keller, C.
Walters, E. L. Apparatus for protecting the withdrawing rollers of a molten metal bath in a glass sheet making operation, P (8) 176*h*.
Walters, E. L., and Koluch, J. S. Sheet handling apparatus for glass plates, etc., P (9) 222*d*.
Walther, F. H. Basic refractory, P (2) 43*d*. See Bonar, K. M.
Walther, F. H., and Brinkerhoff, G. E. Basic refractories for the glass tank, (10) 256*i*.
Walz, R. N. Radiation source, P (10) 260*c*.
Wampler, D. M. See Leflet, H. A., Jr.
Wang, T. P. Temperature sensors, (9) 234*d*.
Wanie, W. Engobes and slips, (9) 228*d*. Glazing and engobing in the brick and stoneware industry, (3) 70*c*. Reduction glazes, (3) 74*j*. Zinc oxide as a mill addition in glazes, (3) 74*i*.
Wanklyn, B. M. See Garton, G.
Wanklyn, J. N. Properties of oxide films on zirconium alloys and their relevance to corrosion and hydrogen uptake, (2) 35*g*. See Harrop, P. J.
Wanless, L. Particle size determination of milled zircons, (2) 51*a*.
Wanmaker, W. L. See Bril, A.
Wanmaker, W. L., Bril, A., and Vrugt, J. W. ter. Sensitization of Tb^{3+} luminescence by Sn^{2+} and Cu^{+} in alkaline earth phosphates, (3) 76*h*.
Warble, C. E. See Moodie, A. F.
Ward, C. R. Annealing of glass, P (4) 93*f*. Glass drawing kiln L-block, P (5) 120*j*. Manufacture of glass, P (2) 38*j*.
Ward, R. G. See Kumar, D.
Ward, T. D., and Smith, M. W. Trickling filter media, P (10) 256*g*.
Ward Leonard Electric Co. Method of manufacturing electrical resistors, P (2) 48*a*.
Wardale, D. J. S. See Bally, A. O.
Ware, J. O. See Steele, B. R.
Ware, R. K., and Pirooz, P. P. Gas adsorption on freshly broken glass surfaces—a source of error in analysis of bubbles in glass, (11) 276*i*.
Waring, J. L. See Roth, R. S.
Waring, W., and Benjamini, E. A. Luminescence during the anodic oxidation of silicon, (7) 165*f*.
Warmer, R. J. See Cope, L. H.
Warner, J. See Woolley, J. C.
Warner, L. L. See Waugh, J. A.
Warren, R. E. Cooler compensating heater for temperature control in glass making, P (10) 254*i*.
Warrier, A. V. R., and Narayana, P. S. Infrared spectrum of ferroelectric lithium hydraxinium sulfate, (8) 183*j*.
Warrington, D. H. See Moriya, Y.
Warshaw, C. M. See Phillips, B.
Warshaw, S. I., and Seider, R. Comparison of strength of triaxial porcelains containing alumina and silica, (8) 182*h*.
Warthen, W. P. Method for indicating material stream characteristics by calorimetry, P (9) 221*g*.
Warwick, W. H. See Johnson, R. C.
Washburn, J. Crystal imperfections, B (9) 244*e*.
Washburn, M. E. Silicon oxynitride refractories, (8) 180*b*.
Wasser, R. E. See Plumbo, R.
Wassermann, F. See Winstel, G.
Watanabe, A. See Sasaki, H.; Takeda, T.
Watanabe, H. See Hayashi, T.; Kita, S.
Watanabe, H., and Munakata, C. Measurement of resistance by means of electron beam (I), (11) 284*d*.
Watanabe, H., and Nemoto, K. Intermetallic compound semiconductor devices, P (4) 101*j*.
Watanabe, H., Wada, M., and Takahashi, T. Activation energy for oxygen desorption from zinc oxide surfaces, (11) 292*g*.
Watanabe, M. See Harada, J.
Watanabe, M., Takeuchi, T., and Ito, J. Identification of trace $VO_{2.17}$ in V_2O_5 and influence of coexistence of Fe, Co, or Ni in preparing $VO_{2.17}$ from V_2O_5 by heating in vacuum, (4) 108*g*.
Watanabe, T. Electrostatic coating apparatus, P (3) 80*b*. See Ohta, K.
Watanabe, Y., and Inoue, T. Cathode ray tube having metallic layer of nonuniform thickness, P (11) 284*j*.
Watanabe, Y., and Nishizawa J. Inductive semiconductors, P (1) 11*a*.
Watson, A. D. See Davis, T. D.
Watson, A. H. See Harris, A. H.
Watson, G. G. Techniques for measuring surface temperature (V, VI), (8) 188*h*.
Watson, G. M. See Bruin, H. J. de
Watson, W. C. Tile sheet-backing apparatus, P (3) 75*a*.
Watt, G. W. See Russell, E. R.
Waugh, J. A., and Warner, L. L. Process of producing flexible glass flake electrical insulation, P (4) 95*e*
Waxter, W. E., and Richmond, A. Method of applying porcelain enamel to metal, P (1) 3*d*.
Waye, B. E. Introduction to Technical Ceramics, B (11) 304*h*.
Waymouth, J. F. See Butler, K. H.; Koury, F.
Weaver, C. See Macfarlane, J. C.
Weaver, C. W. Kinking in MgO single crystals under high confining pressure, (11) 297*i*.
Weaver, E. P. Process for manufacturing improved refractory brick, P (1) 8*i*.
Weaver, E. P., and Henry, G. R. Method of lining a metallurgical furnace and the product thereof, P (10) 259*g*.
Weaver, M. M. History of Tile Drainage (in America Prior to 1900), B (8) 212*b*.
Webb, J. E. Method for fiberizing ceramic materials, P (11) 279*a*. Simple method of making photovoltaic junctions, P (11) 287*f*.
Webb, W. W. See Burns, S. J.
Weber, G. K. Method for making filamentous mats, P (7) 150*b*.
Weber, H. H. Light scattering and particle size distribution of spherical particles (II) experimental, (3) 86*d*.
Weber, O. Filter presses, P (3) 80*c*.
Weber, T. W. See Hessinger, P. S.
Weberling, R. P. See Jaworowski, R. J.
Webster, A. H., Weston, T. B., and Bright, N. F. H. Effect of PbO deficiency on the piezoelectric properties of lead zirconate-titanate ceramics, (10) 262*h*.
Webster, G. A. Widely applicable dislocation model of creep, (9) 243*f*.
Webster, R. See Caldwell, M.
Webster, S. J. See Ray, N. H.
Wedag Westfalia Dinnendahl Groppel Akt.-Ges. Apparatus for the preheating of raw cement material, P (4) 91*d*.
Wefers, K. System ferric oxide-water (I,II), (8) 208*d*.
Wehking, M. W., Pflaum, R. T., and Tucker, E. S., III. Spectrophotometric determination of iron in strong alkalis, (2) 51*i*.
Wehner, A. Dehydration belt, P (2) 49*j*.
Wehren, P. See Decker, H.
Wei, L. Y. See Shewchun, J.
Weichselbaum, T. E., and Horn, A. J. Means for measuring the specific gravity of liquids and solutions, P (10) 268*d*.
Weidel, R. A. Fluophosphate glasses, P (1) 5*a*. Metaphosphate glass, P (9) 220*f*. Optical glass, P (1) 6*a*. See Blair, G. E.; Hensler, J. R.
Weidman, V. W. See Hailstone, R.
Weil, N. A. Parametric effects governing the mechanics of ceramic materials, B (5) 140*b*.
Weiland, W. Architectural ceramics in Russia, (3) 63*i*.
Weimer, G. Mill additions for enamels, (7) 147*h*.
Weimer, P. K. Field effect solid state device having a partially insulated electrode, P (5) 127*d*. Insulated-gate thin-film transistor, B (11) 305*j*. Tellurium thin film field effect solid state electrical devices, P (3) 79*k*.
Weiner, M. Solar pumped laser, P (4) 102*g*.
Weinreich, G. F. See Chanowitz, H.
Weinstein, H. See Topas, B.
Weinstein, M. See Bates, H. E.
Weinstein, M., Bell, R. O., and Menna, A. A. Preparation and properties of GaAs-GaP, GaAs-Ge, and GaP-Ge heterojunctions, (3) 76*i*.
Weintritt, D. J. See Nevins, M. J.
Weisbecker, H. L. See Adams, R. J.
Weisberg, H. Method of etching to dice a semiconductor slice, P (2) 48*f*.
Weise, E. L. See Stern, K. H.
Weisenborn, H. E. Apparatus for reducing particle concentration in volume of liquid containing same, P (7) 158*k*.
Weiser, K. See Levitt, R. S.; Peart, R. F.
Weiser, K., and Blum, S. E. Method and apparatus for growing [two-component] crystals, P (11) 286*c*.
Weismantel, G. Prolific glassmakers seek new role in the chemical process industry, (11) 277*h*.
Weiss, A., and Thielepape, W. Method of treating clay and clay produced thereby, P (7) 161*c*.
Weiss, G. H. See Billick, I. H.
Weiss, H. Galvanomagnetic semiconductor device, P (8) 184*c*.
Weiss, M. E. See Feinstein, L.

Weiss, W., and Vatterodt, K. Furnace for the manufacture of fused quartz, P (8) 189*c*.
Weissbach, H. Building material compositions for the manufacture of water-repellent products, P (8) 174*a*.
Weissman, I. Grain-oriented dispenser thermionic emitter for electron discharge device, P (3) 78*j*. Grain-oriented thermionic emitter for electron discharge devices, P (2) 47*k*.
Weisz, P. B. Steam treatment of the matrix in a crystalline aluminosilicate catalyst composite, P (10) 270*a*.
Weitzman, L. H. Etching bismuth telluride, P (11) 285*j*.
Welch, B. J. See Gjerstad, S.
Welch, G. E. See Straumanis, M. E.
Welchenberger Christallsandwerke G.m.b.H. Method for improving the durability of refractory furnace linings or the like, P (8) 181*b*.
Weldrick, G. See Milner, G. W. C.
Welker, H. See Spenke, E.
Welker, R. H. See Helmbrecht, W. L.
Weller, E. E., and Kleinhans, R. J. Thixotropic nonflowing adhesive bonding and jointing compositions and methods of bonding ceramic tiles to substrates using them, P (7) 155*c*.
Weller, P. F., Axe, J. D., and Pettit, G. D. Chemical and optical studies of samarium doped CaF_2 type single crystals, (9) 237*k*.
Weller, P. F., and Scardefield, J. E. Doping of alkaline earth halide single crystals, (3) 85*a*.
Wells, L. J. Transparent glass container and method of making same, P (4) 95*h*. See Smith, R. M.
Wemple, S. H. See Kahng, D.
Wen, C. P., and Mayo, R. F. Acoustic attenuation of a single-domain lithium niobate crystal at microwave frequencies, (9) 237*b*.
Wende, P. T. See Belasco, M.
Wendell, C. B. See Carpenter, C. L.
Wender, J. D., Jr. See Stamos, C.
Wendlandt, W. W., and Hecht, H. G. Reflectance Spectroscopy, B (1) 31*a*.
Wendt, J. J. See Mulligan, R. J.
Wengelin, F. See Lindquist, O.
Wentorf, R. H., Jr. Method of growing diamond on a diamond seed crystal, P (4) 103*g*. See Darrow, K. A.
Wentworth, C. See Kuliczkowski, J. A.
Wenzel, F. Apparatus for production of fine-crystalline boron phosphide, P (1) 7*b*.
Wenzel, F., and Merkel, H. Method of producing crystalline boron phosphide, P (11) 286*g*.
Wenzel, M. See Kojic, L.
Werdt, R. de. See Jochems, P. J. W.
Wermund, E. G., and Moiola, R. J. Opal, zeolites, and clays in an Eocene neritic bar sand, (1) 24*j*.
Werner, H., Ziegler, H. W., and Przybylski, B. Process for the manufacture of aqueous clay suspensions, P (9) 233*b*.
Werner, J. E. See Osterholtz, C. E.
Werner, P. E., Kierkegaard, P., and Magneli, A. Thermal expansion of the wolfram bronzes of potassium, rubidium, and cesium, (4) 111*f*.
Werner, W. J., McIlwain, M. C., and Hammond, J. P. Preparation of uranium aluminides UAl_3 and $UAl_{4.5}$, P (2) 45*a*.
Wert, C. See Gibala, R.
Wertz, J. E., Orton, J. W., and Auzins, P. Electron spin resonance studies of radiation effects in inorganic solids, (3) 85*g*.
Wesch, L. Manufacture o an infrared reflective pigment, P (8) 190*g*.
Wesolowski, W. E. Capacitor process, P (1) 10*i*.
West, H. W. H. Moisture movement of bricks and brickwork, (9) 222*j*.
West, P. Graphite tape shapes up as newest exotic material, (10) 257*a*.
West, P. W. See Ramakrishna, T. V.
West, R. Clay dispersion, B (1) 30*b*. Drying clayware, B (8) 212*c*. Engineering statistics, B (11) 303*h*. Plastic behavior of some clays, B (1) 30*b*. Whitewares control test, B (1) 30*c*.
West, R. G., and Blankenship, A. C. Magnetic properties of dense lithium ferrites, (8) 183*g*.
West, S. F. See Alexander, G. B.
West, T. S. See Dagnall, R. M.
Westbrook, J. H. See Wood, D. L.
Westbrook, J. H., Seybolt, A. U., and Peat, A. J. Thermal probe for segregation detection, (3) 81*h*.
Westcott, R. G. See Behnke, G. W.
Western Counties Brick Co., Ltd. Control of the moisture content in clay, P (7) 160*i*.
Western Electric Co., Inc. Apparatus for processing materials in a controlled atmosphere, P (3) 77*b*. Heat sealing glass to the surface of a body, P (2) 38*h*. Method and apparatus for assembling wires in a plurality of apertured parts, P (1) 5*b*. Method and apparatus for cathode sputtering using a cylindrical cathode, P (8) 185*a*.
Westervelt, D. C., and Vondracek, C. H. Insulated conductors and method of making the same, P (9) 217*b*.
Westfalia Dinnendahl Groppel Akt.-Ges. Cone or gyrating crushers of the suspended spindle type, P (3) 83*c*. Journalling structure for rotatable processing drums such as rotary kilns, tube mills, P (7) 160*c*.
Westgaard, H. See Charschan, S. S.
Westinghouse Brake & Signal Co., Ltd. Semiconductor barrier layer switch with symmetrical characteristics on either polarity, P (7) 158*a*.
Westinghouse Electric Corp. Cathodoluminescent pumped laser having a cathode surrounding the laser, P (8) 184*d*. Coating composition, P (8) 184*e*. Coextruded thermoelectric members, P (2) 47*a*. Contacting of p-n junctions, P (4) 100*i*. Copper activated strontium phosphate phosphors, P (9) 230*b*. Diode structure in semiconductor integrated circuit and method of making the same, P (10) 263*d*. Electrically conductive solid lubricant members and process and apparatus employing them, P (4) 101*b*, P (5) 127*i*. Electroluminescent lamp having a moisture resistant vitreous light-transmitting material which includes 4 to 8% LiF, P (3) 78*e*. Electroluminescent lamp structure having the phosphor particles dispersed in a modified cyanoethylated polyvinyl alcohol resin, P (7) 156*b*. Etching bismuth telluride, P (11) 285*j*. Ferrite magnets, P (4) 101*f*. Filament mount and heat shield structure for electric incandescent lamp, P (2) 47*g*. Fluorescent lamp bulb spiral groove forming device, P (10) 255*c*. Glass composition and thermoelectric element coated therewith, P (1) 5*d*. High-current seal for electric discharge lamp, P (1) 10*i*. High-output fluorescent lamp with improved phosphor-coated glass structure that defines a recombination surface and enhances lumen maintenance, P (11) 285*g*. Insulated conductors and method of making the same, P (9) 217*b*. Lapping and polishing apparatus, P (1) 14*d*. Latching ferrite phase shifter having a predetermined phase shift when switched from one major remanent state to the other, P (8) 184*j*. Low-pressure electric discharge lamp with internal elongated structure that modifies the diffusion length of the discharge and improves the lamp performance, P (3) 78*b*. Magnetic ceramic material, P (3) 78*c*. Manufacturing process for electronic capacitors, P (5) 127*j*. Mercury vapor lamp seasoning and sealing method, P (3) 68*e*. Metallic ceramic composition contacts for semiconductor devices, P (4) 101*a*. Method and apparatus for coating electric lamp bulbs, P (1) 5*d*. Method of doping tungsten oxide, P (2) 48*f*. Method of gettering impurities in electrical devices such as incandescent lamps, P (8) 178*a*. Method of growing crystalline members completely within the solution melt, P (1) 11*c*. Method for making an electroluminescent device, P (8) 185*f*. Method of manufacturing double-ended electric lamps, P (4) 95*c*. Method of orienting filaments in incandescent lamps, P (4) 95*c*. Method for phosphor coating a fluorescent tube of irregular section, P (5) 128*f*. Method of reshaping fabricated infrared-generating devices such as electric lamps, P (7) 150*e*. Method of tipping-off exhaust tubing, P (8) 178*j*. Methods for forming monolithic semiconductor devices [including epitaxial growth], P (9) 231*e*. $Pb_xTe_{1-x}Cr$ thermoelectric material and thermoelectric device, P (9) 231*f*. Preshaped two-phase glass-ceramic body and process for preparing the same, P (2) 39*i*. Press sealing apparatus, P (3) 69*j*. Process for controlling dendritic crystal growth, P (4) 102*h*. Processing of electroluminescent phosphors, P (5) 128*j*. Quartz tube coating, P (11) 287*j*. Silica films, P (2) 49*g*. Simultaneous double diffusion process, P (5) 129*b*. Sintered electrical contact members, P (8) 186*e*. Solid state display device for amplifying or converting input radiation including a field emissive layer, P (11) 287*g*. Switching transistor structure and method of making the same, P (11) 288*a*. Temperature sensor, P (8) 188*f*. Thoriated tungsten filament or wire and method of making same, P (1) 12*b*. Two-phase ferrite magnet composition and method for preparing same, P (11) 288*d*.
Westman, S. Phase transition in VO_2, (4) 109*h*.
Westmore, J. B., Mann, K. H., and Tickner, A. W. Mass spectrometric study of the nonstoichiometric vaporization of cadmium arsenide, (8) 202*a*.
Weston, B. M. Foundry composition and method of making same, P (8) 181*d*.
Weston, D. Method and apparatus for the magnetic separation of particulate materials, P (3) 83*c*.
Weston, T. B. See Webster, A. H.
Westrum, E. F., Jr. Progress in the calorimetry and thermodynamics of phase and ordering reactions, (8) 205*g*.
Westwood, A. R. C., Goldheim, D. L., and Pugh, E. N. Complex-ion embrittlement of silver chloride, B (2) 61*i*. Double-layer mechanism for the complex-ion embrittlement of silver chloride, (10) 270*j*.
Westwood, W. D., Eastwood, H. K., Poulsen, R. G., and Sadler, A. G. Single-crystal ferrite films prepared by cathodic sputtering, (4) 100*c*.
Weth, G. G. See Tuthill, E. J.
Wetzel, R. H. See Berry, K. L.
Wey, A. D. van der. See Schouwenburg, J. C. van.
Weyerhaeuser Co. Gypsum castings and method of producing the same, P (5) 116*g*.
Weyl, W. A., and Marboe, E. C. Constitution of Glasses—A Dynamic Interpretation (Vol. II, Part 2) Constitution and Properties of Some Representative Glasses, B (11) 303*h*.
Whalen, T. J. See Basler, W. G.
Whateley, T. L. See Stuart, W. I.
Wheat, T. A. See Carruthers, T. G.
Wheeler, R. W., and Davidson, C. R., Jr. Method and apparatus for bending and tempering glass sheets vertically supported with fluid pressure, P (11) 278*h*. Method of supporting a thermoplastic sheet with gas, P (11) 279*g*.
Wheeler, V. J. See Dell, R. M.
Wheeler, V. J., Dell, R. M., and Wait, E. Uranium trioxide and the UO_3 hydrates, (8) 211*f*.
Wheildon, W. M. Hot-pressing—new technology for improved materials, (9) 232*i*. Rods for flame spraying, P (10) 250*g*.
Whelan, M. J. Annealing of dislocation loops by climb, (8) 191*f*.
Wheldon, R. J. See Baker, B. O.
Whetten, N. R. Secondary electron emission of vacuum-cleaved solids, (1) 28*a*.
Whicker, L. R., and Jones, R. R. Latching ferrite phase shifter having a predetermined phase shift when switched from one major remanent state to the other, P (8) 184*j*.
Whiffen, D. H. See Cook, R. J.
White, C. L., and Patterson, W. E. Conductance during anodic oxidation of tantalum and niobium films, (4) 100*d*.
White, D. See Roberts, A. L.
White, E. A. D. Bibliography on crystal growing—annotated references 1960 to 1965, (9) 232*i*.
White, E. W., and Roy, R. Use of X-ray emission spectroscopy in the characterization of thin films of aluminum oxides and hydroxides, (9) 243*b*.
White, H. G. See Trumbore, F. A.
White, J. Current refractories research and its applications, (11) 280*e*. Sintering—an assessment, B (7) 170*f*. See El-Shahat, R. M.; Gadalla, A. M. M.
White, J. H. Reference Book of Chemistry, (4) 113*f*.
White, J. L. See Diamond, S.; Ledoux, R. L.
White, J. S. See Philipps, T. E.
White, J. U. Optical apparatus for measuring the reflective and emissive characteristics of a sample [spectrometer], P (1) 14*e*.
White, J. W. See Heller, G. L.
White, R. A. See Tenpas, E. J.
White, R. B. Changing Appearance of Buildings, B (11) 303*i*.
White, R. M., and Voltmer, F. W. Direct piezoelectric coupling to surface elastic waves, (3) 75*f*. Ultrasonic surface-wave amplification in cadmium sulfide, (5) 139*b*.
White, W. B. Application of infrared spectroscopy to order-disorder problems in simple ionic solids, (9) 237*f*. See Berkes, J. S.; Muller, O.; Roy, R.
White, W. E., and Jache, A. W. Stannous hexafluorozirconate, P (11) 292*c*.
Whitehurst, E. A., and Moore, A. B. Evaluation of several expanded aggregates for use in skid-resistant pavement surfaces, (4) 90*g*.
Whiteley, P. G. Some problems associated with supplying refractories for pneumatic steel-making vessels, (11) 281*e*.
Whiteside, E. L. Quality control in the plaster mold shop, (1) 9*e*.
Whiteside, J. H. Process for slip-proofing glazed ceramic surfaces, P (8) 183*b*.
Whitman, W. G. See Bowman, M. G.
Whitmore, D. H. See Janninck, R. F.; Kenny, N.
Whitney, E. D. Electrical resistivity and diffusionless phase transformations of zirconia at high temperatures and ultra-high pressures, (9) 238*j*. Kinetics and mechanism of the transition of metastable tetragonal to monoclinic zirconia, (7) 164*g*. See Murata, Y.
Whitney, I. See Proctor, B. A.
Whitney, J. B. Method of bonding sheets of metal, P (9) 217*a*.
Whitney, J. M., and Riley, M. B. Elastic properties of fiber reinforced composite materials, (1) 2*f*.
Whittaker, R. H. See Thompson, J. H.
Whittaker Corp. Coating process for glass fibers and product, P (4) 93*j*.
Whittemore, O. J., Jr. See Leiser, D. B.
Whittingham, M. S. See Dickens, P. G.
Whitworth, R. W. Atomic mechanisms for the transport of charge by dislocations in NaCl type crystals, (8) 191*a*. Production of electrostatic potential differences in sodium chloride crystals by plastic compression and bending, (8) 205*b*.
Wiberley, S. E. See Huckle, W. G.
Wicken, O. M. Refractory mortar composition, P (2) 45*f*.
Wickert, H. Simple methods for investigating cords and knots in glass, (7) 148*e*.
Wickham, D. G. Study of the solid solutions of $Li_{1+x}V_3O_{8+\lambda}$ and preparation of $LiVO_3$ and Li_3VO_4, (8) 208*c*.
Wickham, D. G., and Im, H. B. Fluxes for sintering lithium ferrites, P (4) 101*f*.
Widmann, H. Effect of atmosphere on the sintering of ferrites, titanates, and oxide ceramics (I), (7) 151*h*.
Widmer, A. E. See McCaldin, J. O.
Widmer, R. See Kaldis, E.
Wiedenhorn, G. See Hartmann, J.
Wieder, H. H. See Clawson, A. R.
Wieder, H. H., and Clawson, A. R. Process for producing semiconductor-film Hall devices on oxide-metal substrate, P (9) 232*d*.
Wieder, H. H., Clawson, A. R., and Parkerson, C. R. Preparation of hydrates of $2CaO \cdot 3B_2O_3$, P (11) 291*a*. Process for the preparation of the strontium isomorph of colemanite, P (10) 269*i*, P (11) 291*h*.
Wiederhorn, S. M. Fracture surface energy of soda-lime glass, B (2) 61*h*. Influence of water vapor on crack propagation in soda-lime glass, (9) 218*d*.
Wiedersich, H. See Gonser, U.
Wiedmann, T. Characteristic tension curves of porcelain and steatite glazes (I, II), (10) 261*c*.
Wiegel, E., and Kirchner, H. H. Infrared spectroscopic investigation of thermal dehydration of gypsum, (8) 200*g*.

Wiener, R., Mellar, C. J., Kirschner, J. G., and McClelland, R. H. Vapor deposition apparatus including tumbler, P (5) 129*e*.
Wienert, F. O. Grinding of material in grinding mills, P (9) 233*d*.
Wiens, B. E. See Teague, J. M., Jr.
Wigginton, R. J. See Claridge, M. A.
Wigton, H. F. H. Epitaxially growing layers of semiconductor through openings in oxide mask, P (4) 101*e*.
Wike, R. B. See Nutter, G. D.
Wikswo, J. P. See Nelson, E. W.
Wilcox, B. A., and Rosenfield, A. R. Serrated yielding and negative strain-rate sensitivity, (11) 300*b*.
Wilcox, W. R. See Chase, A. B.
Wilcox, W. R., LaChapelle, T. J., and Forbes, D. H. Gold in silicon—effect on resistivity and diffusion in heavily doped layers, (7) 163*j*.
Wilcox Electric Co., Inc. Ferrite tuned coaxial cavity [resonator] apparatus, P (2) 47*f*.
Wild, A. P. J. See Joslin, C. M. D.
Wilde, D. Methods for mixing finely divided materials, P (5) 121*a*. See Jack, H. R. S.
Wilder, A. G. See Smiley, W. D.
Wilder, D. R. See Carrell, M. A.; Marlowe, M. O.; Schieltz, J. D.; Wirkus, C. D.
Wilder, P. W., Jr. See Humphrey, D. E.
Wiles, D. R. See Hollebone, B. R.
Wiley, J. S., and Knight, H. T. Electrical resistivity of pyrolytic β-MnO_2, (3) 85*d*.
Wilford, P. B. Radome nose for a missile and method of making same, P (11) 282*j*.
Wilhelm, F. See Joshi, M. L.
Wilhelm, H. See Vescia, M.
Wilhoit, R. C. Recent developments in calorimetry (I) introductory survey of calorimetry, (11) 289*d*.
Wilkes, J. G. See Bradshaw, S. E.
Wilkinson, C. D. W. See Caddes, D. E.
Wilkinson, J. F. G., Vernon, R. H., and Shaw, S. E. Petrology of an adamellite-porphyrite from the New England bathylith (New South Wales), (1) 25*b*.
Wilkinson, W. L. Production of fuel for nuclear reactors, P (9) 227*g*.
Wilks, R. S. See Woollaston, H. J.
Will, P. Magnetically tuned ferrite cavity transistor oscillator, P (11) 286*a*.
Willcox, O. B. See Emslie, R. S.
Willems, H. W. V. Primary phase of clear sheet glass, (2) 37*c*.
Willenbrock, H. C., Jr. Oxygen converter linings, P (3) 72*b*.
Williams, B. B. See Lambert, A. N.; Riley, J. E.
Williams, C. J. See Rees, L. V. C.
Williams, D. J. See Kumar, D.
Williams, D. R. Silicate grout, P (3) 64*g*.
Williams, E. W., Cox, R. H., Dobrott, R. D., and Jones, C. E., Jr. Determination of the composition and homogeneity of epitaxial Ga(As,P) alloys by X-ray diffraction and optical reflectivity, (3) 80*k*.
Williams, F. V. Effect of orientation on the electrical properties of epitaxial gallium arsenide, (3) 85*d*. Orthorhombic boron arsenides and their preparation, P (11) 282*b*.
Williams, H. A., and Drum, E. W. Electrostatic spray coating apparatus, P (3) 65*e*.
Williams, H. J. See MacChesney, J. B.
Williams, J. Characteristics and preparation of ceramic powders, B (7) 169*i*. See Murray, P.
Williams, J. A., and Phillips, B. Small-angle X-ray scattering by metastable liquid immiscibility in glass, B (5) 139*k*.
Williams, J. M. See Birchenall, C. E.
Williams, J. P. See Finlayson, K. M.; Pruden, L. H.
Williams, J. R. Epitaxial transistor and method of manufacture, P (9) 230*k*. Industrial burner, P (8) 189*a*.
Williams, L. S. See Moodie, A. F.
Williams, R. M. Roller grinding mill and control therefor, P (11) 292*e*.
Williams, R. O. Determination of the stored energy of deformation of metals and alloys, B (8) 211*i*.
Williams, R. P. See Cunningham, J. A.
Williams Patent Crusher & Pulverizer Co., Inc. Roller grinding mill and control therefor, P (11) 292*e*.
Williamson, G. K., and Cornell, R. M. Behavior of fission product gases in uranium dioxide, (7) 151*c*.
Williamson, J. B. P. See Greenwood, J. A.
Williamson, W. O. Causes and consequences of clay particle orientation in ceramic fabrication processes, B (1) 30*c*. See Faruqi, F. A.
Wills, D. B. See Van Riper, C.
Willy, Georg, A. G. See Georg Willy A. G.
Wilshire, H. G. Prospect alkaline diabase-picrite intrusion, New South Wales, Australia, (8) 205*i*.
Wilson, A., and Robertson, R. H. S. Composition for production of ceramics, P (10) 261*c*.
Wilson, C. B., Dixon, W. S., and Dreckman, H. Paramagnetic oxygen analyzer measuring cell, P (1) 14*e*.
Wilson, H. L., and Gutierrez, W. A. Cadmium selenide thin film field effect transistors, (9) 228*i*.
Wilson, J. Reflector arc lamp with arc tube support comprising arc tube inlead connectors fastened to the outer end of ferrules sealed in the outer envelope, P (11) 279*c*.
Wilson, J. J. Stable silicone rubber interlayers for glass, P (7) 150*f*.
Wilson, O. W. See Parker, S. G.
Wilson, R. C., Jr. Method for producing crystalline aluminosilicate zeolitic particles of uniform size, P (8) 190*c*.
Wilson, R. C. L. Silica diagenesis in Upper Jurassic limestones of southern England, (8) 206*k*.
Wilson, R. W. See Nitsche, R. E.
Wilson, W. E., and Zimmerman, H. A. Method of tipping-off exhaust tubing, P (8) 178*j*.
Wilson, W. I. See O'Connell, T. B.
Wimmer, J. M. See Tallan, N. M.
Wimmer, J. M., Bidwell, L. R., and Tallan, N. M. Electrical properties and defect structure of a $(0.13YO_{1.5}$-$0.87ThO_2)$ electrolyte, (5) 135*f*.
Winchester, G. L. See Troell, P. T.
Windecker, R. T. See Long, R. K.
Windisch, S. See Rudy, E.
Winkler, E. R., Sarver, J. F., and Cutler, I B. Solid solution of titanium dioxide in aluminum oxide, (1) 28*i*.
Winn, D. H. Method and apparatus for use in manufacturing glass fibers, P (9) 221*c*.
Winstel, G., and Wassermann, F. Method of producing semiconductors by diffusion, P (7) 157*i*.
Winter, E. Firing glass enamels on aluminum, (11) 273*k*.
Winter-Klein, A. Structure and physical properties of glass, B (7) 171*f*.
Wirkus, C. D., Berard, M. F., and Wilder, D. R. Self-diffusion of oxygen in Y_2O_3 and Er_2O_3, (3) 88*a*.
Wirsching, F. Phases of the system $CaSO_4$-$CaSO_4$·$2H_2O$, (5) 116*i*.
Wirth, H., Roeder, M., and Dietz, W. Producing and regulating translatory movement in the manufacture of semiconductor bodies, P (11) 287*i*.
Wirth, H. A. See Behnke, G. W.
Wise, D. C., and Ehrenreich, L. C. Refractory bodies and compositions and methods of making the same, P (9) 227*b*.
Wisman, E. C. Method of producing a field-effect transistor, P (8) 185*b*.
Wisnyi, L. G. See Lang, J. E.
Wissinger, S. E., Jr. Reflectorized marking material and method of making same, P (1) 6*c*. Reflectorizing glass spheres and method of making them, P (3) 69*c*.
Witko, P. P., Jr. See Brownell, W. E.
Witt, C. H. See Barnhart, C. L.
Witt, R. K. See Sachse, W.
Wittmann, F. Effect of shrinkage stress on the creep of hardened cement paste, (5) 116*d*.
Wittry, D. B. Cathodoluminescence and impurity variations in Te-doped GaAs, (7) 162*g*.
Wohlleben, K., and Konecpicky, K. Nondestructive testing of model brick by the sonic and X-ray methods, (3) 80*j*.
Wolf, F. See Fuertig, H.
Wolf, F., Fuertig, H., Bluehmke, P., and Borchhardt, D. Method of making molecular sieves, P (3) 83*f*.
Wolf, H. Tool for cutting brick and other construction materials, P (5) 130*e*. See Vescia, M.
Wolfgang, L. G. Printing cathode ray tube using photoconductive layer, P (1) 11*b*.
Wolfke, S. See Tokarski, Z.
Wolfson, R. G., and Kobes, W. Growth of NaCl-KCl mixed crystals from the melt, (9) 239*b*.
Wollast, R. New method for determining the enthalpy and entropy of dehydration of kaolinite, (11) 298*d*.
Wolley, J. Pressing of articles from powdered material, P (7) 158*g*.
Wolsky, S. P., Piwkowski, T. R., and Wallis, G. Low-pressure sputtered germanium films, (1) 21*i*.
Wolverine Porcelain Enameling Co. Porcelain enamel coating, P (11) 276*b*.
Wong, M. See Greenbaum, M. A.
Wong, P. See Levy, M.
Wong, R., and Morrison, A. R. Method of making a bonded mat of surface treated glass fibers, P (2) 39*g*.
Wong, R., and Sullivan, P. W. Epoxide additive for amylaceous forming size compositions, P (4) 94*d*.
Wood, A. J. See Milner, G. W. C.
Wood, D. C. See Provance, J. D.
Wood, D. L. See Ferguson, J.
Wood, D. L., and Remeika, J. P. Effect of impurities on the optical properties of yttrium iron garnet, (8) 195*a*.
Wood, D. L., and Westbrook, J. H. Tensile behavior of the intermetallic compound AgMg, (4) 111*b*.
Wood, J. H. J. Apparatus for the grinding and/or dispersing of pigments in a liquid medium, P (10) 266*c*.
Wood, T. E., Nylander, A. G., and Hackett, F. L. Method and apparatus for forming glass beads, P (1) 5*d*.
Wood Conversion Co. Method and apparatus for de-shotting and separating mineral fiber, P (7) 149*k*.
Woodall, J. See Peart, R. F.
Woodall, J. M. Preparation of gallium arsenide with controlled silicon concentrations, P (9) 231*h*. See Rupprecht, H.
Woodbury, H. H. Surface-adjacent junction electroluminescent device, P (4) 102*i*.
Woodcock, R. F., and Granitsas, G. A. Infrared image transmitting fiber devices, P (4) 94*j*.
Woodhouse, R. L. See Speros, D. M.
Woodring, G. D. Method of etching aluminum, P (1) 3*a*.
Woodruff, M. D. Cyclonic separator, P (10) 266*g*.
Woollaston, H. J., and Wilks, R. S. Contribution of helium bubbles to the expansion of neutron-irradiated BeO, (8) 192*g*
Woolley, J. C. Thermal expansion of GaSb at high temperatures, (11) 302*f*.
Woolley, J. C., and Blazey, K. W. Some properties of GaSb-Ga_2Se_3 and GaSb-Ga_2Te_3 alloys, (4) 110*b*.
Woolley, J. C., and Nikolic, P. Some properties of GeTe-PbTe alloys, (9) 230*b*.
Woolley, J. C., and Warner, J. Preparation of InAs InSb alloys, (7) 166*i*.
Worn, D. K. See Bradbury, E. J.
Worrall, H. Enameling with liquid flux, (4) 89*j*.
Worrall, W. E. See Boardman, G.
Wosinski, J. F. Identification and control of solid inclusions in glass, (2) 36*h*.
Wosinski, J. F., and Kearney, J. R. Methods of determining probable sources of gaseous inclusions in glass, (1) 4*a*.
Wrench, R. F. Cutting tool, P (10) 254*j*. See Kalocsai, B. O.
Wright, A. J., and Vickery, R. C. Electrical terminations for cermet resistance elements, P (9) 230*e*.
Wright, J. E. See Richardson, G. W.
Wright, J. W. R. Manufacture of synthetic aggregates, P (3) 70*f*.
Wright, J. W. T. See Vause, A. S.
Wright, J. W. T., Coaton, J. R., and Howles, D. A. Electric incandescent lamps, P (2) 38*d*.
Wright, M. S. Pivoted glass sheet bending mold, P (1) 6*c*.
Wuhrer, J. See Ellsiepen, E.
Wurm, J. G. See Beucherie, P.
Wurst, E. C., Jr. See Abercrombie, W. M.; Johnson, R. E.
Wyandotte Chemicals Corp. Fluxing agent, P (7) 153*d*. Process for agglomerating anhydrous sodium metasilicate fines, P (11) 291*e*.
Wyckoff, R. W. G. Crystal Structures (Vol. 5), B (11) 304*f*.
Wyllie, P. J. Melting relations in the system CaO-MgO-CO_2-H_2O, with petrological applications, (1) 22*h*. Phase equilibria in system CaO-CO_2-H_2O and related systems, with implications for crystal growth of calcite and apatite, (2) 55*e*.

Xerox Corp. Method for forming a thin film resistor, P (2) 48*i*. Method for simultaneous production of a plurality of microcircuit wafers, P (10) 264*j*.

Yafaev, N. R. Application of the electron paramagnetic resonance of transition-metal ions to the study of the structure of glass, B (9) 245*h*.
Yaguchi, K. Magnetic properties of GdSi$_8$, (11) 284*d*.
Yakhkind, A. K. Shape of the density and refractive-index curves for binary glasses and possibilities for their structural interpretation, B (7) 171*g*. Tellurite glasses, (1) 4*i*. See Evstrop'ev, K. S.
Yakovlev, A. I. See Potemkin, P. S.
Yakovleva, H. G. See Borovik, E. S.
Yakubik, V. V. See Syritskaya, Z. M.
Yale, B. See Procter, J. P.
Yam, V. M. Choice of capacity of pump equipment on a hydraulic press for refractory materials, (5) 122*i*.
Yamada, H. See Hamano, K.; Yasui, E.
Yamada, J. See Takeuchi, Y.
Yamada, K. See Kunitomi, M.
Yamada, M. See Minowa, S.
Yamada, T. Antiferromagnetic domain walls in nickel oxide, (5) 134*c*.
Yamada, T., Hasegawa, S., Nakayama, Y., and Neishi, H. Cathode ray tube having a screen conforming to the peripheral surface of a cylinder, P (4) 100*k*.
Yamagishi, S. See Kamemoto, Y.
Yamaguchi, G., and Ono, Y. Microscopic studies of alite in portland cement clinker, (1) 2*c*.
Yamaguchi, G., Yanagida, H., and Ono, S. Effects of impurity ions on hydrothermal synthesis of corundum (1) crystal habit of hydrothermal corundum, (3) 85*c*.
Yamaguchi, J. See Horiuchi, S.
Yamaka, E. Paramagnetic resonance of Gd^{3+} in TiO_2 crystal, (7) 166*g*.
Yamamoto, H. See Nameishi, N.
Yamamoto, T. See Tashiro, M.
Yamanaka, M., and Ueda, R. Porosity and coercive force in evaporated Permalloy thin films, (11) 284*e*.
Yamanaka, S., and Naoe, M. Vacuum deposition of ferrite films by arc discharge, (11) 284*f*.
Yamashita, J. Electronic structure of TiO and NiO, (7) 163*g*.
Yamauchi, S. See Matsumoto, H.
Yamazaki, H. See Morita, A.
Yamazaki, T. See Imaoka, M.
Yanagida, H. See Yamaguchi, G.
Yanase, A. See Hirota, E.
Yando, S. Ferroelectric pulse generator, P (10) 263*j*.
Yankwich, P. E., and Zavitsanos, P. D. Carbon isotope effect in the pyrolytic decomposition of manganous oxalate, (8) 192*c*; of zinc oxalate, (8) 192*c*. Pyrolysis of zinc oxalate—kinetics and stoichiometry, (8) 205*j*.
Yanovskii, Yu. S. See Galdina, N. M.
Yarembash, E. I. See Eliseev, A. A.; Kalitin, V. I.
Yariv, S. See Bodenheimer, W.
Yaroshenko Yu. G. See Budrin, D. V.
Yasinskaya, G. A., and Kogan, S. F. Refractories for producing zinc white, (9) 224*j*.
Yastrebova, L. S. See Zhdanov, S. P.
Yastrubinskii, V. I. See Nekrasov, K. D.
Yasuda, E See Tagai, H.

Yasufuku, M., Kawamura, T., Matsumoto, Y., and Kuramochi, A. Method of manufacture of silicon [mesa] transistor, P (11) 286*e*.
Yasui, E., Shoda, S., Suzuki, H., and Yamada, H. Process for the production of crystalline calcium carbonate of vaterite type, P (9) 236*i*.
Yasuoka, H., Abe, H., Hirai, A., and Hashi, T. Nuclear magnetic resonance of ^{53}Cr in ferromagnetic CrO_2, (5) 137*j*.
Yasuoka, H., Abe, H., Matsuura, M., and Hirai, A. Spin echoes on ^{55}Mn in manganese ferrite, (7) 167*i*.
Yates, B. Thermodynamic calculation of the Debye-Waller factors of potassium bromide and magnesium oxide, (8) 210*b*.
Yates, J. See Gabrysh, A. F.
Yates, P. C. See Alexander, G. B.
Yates, R. E., Greenbaum, M. A., and Farber, M. Thermodynamic and physical properties of beryllium compounds (VI) heat of formation of beryllium nitride, (8) 210*e*.
Yavorsky, P. J. Gastight refractory article and method of making same, P (2) 44*d*.
Yavorsky, P. M. Efficient beta-ray emission source for irradiation applications, P (9) 230*c*.
Yawata Iron & Steel Co., Ltd. Coarse crystal magnesia refractory material, P (9) 225*c*. Dustable refractory material, P (10) 259*h*.
Yee, J. H. See Condas, G. A.
Yee, S. S. Light emission from semiconducting CdS in the current oscillatory mode at 77°K, (8) 201*c*.
Yeh, Tsu-Hsing, and De Fries, R. M. Intermetallic semiconductor body and method of diffusing an *n*-type impurity thereinto, P (8) 184*i*.
Yellow Springs Instrument Co., Inc. Extended range [dual] thermistor temperature sensing, P (8) 188*c*.
Yen, C. M. See Toth, L. E.
Yen, Tung-shen. See Kuo, Chu-kun.
Yetmen, Y. See Hofmann, U.
Yoder, H. S., Jr. See Fawcett, J. J.; Kushiro, I.
Yoffe, A. D. See Fitzgerald, A. G.
Yokobori, T., and Ichikawa, M. Elastic solid with an infinite row of collinear cracks and the fracture criterion, (7) 162*j*.
Yokota, A. Method of manufacture of semiconductor elements, P (3) 78*j*.
Yokota, R. See Kobayashi, K.
Yokota, R., and Imagawa, H. ESR studies of radiophotoluminescent centers in silver-activated phosphate glass, (11) 276*g*.
York, W. H. Mineral concentrator, P (1) 16*a*.
Yoshida, H., and Nakazato, Y. Deep drawing steel sheet and method for producing the same, P (10) 250*c*.
Yoshida, H., and Ranby, B. Electron spin resonance spectra of hydrogen-bonded HO radicals, (8) 196*e*.
Yoshida, M. See Hukuo, N.
Yoshida, N., and Fukunaga, J. Mineralogical studies on glass stones, (5) 119*f*.
Yoshida, T. See Tanaka, H.
Yoshida, T., Seiyama, T., Shono, Y., and Kitagawa, M. Optical absorptions of neutron-irradiated ZnS, (8) 204*c*.
Yoshida, T., Shioura, Y., Matsuda, T., and Takei, T. Studies on glass-ceramics of the system $CaO \cdot Al_2O_3 \cdot 2SiO_2$-$2MgO \cdot 2Al_2O_3 \cdot 5SiO_2$-$CaO \cdot TiO_2 \cdot SiO_2$—effect of the addition of B_2O_3 on the improvement of bending strength, (7) 149*b*.
Yoshikawa, S. See Bockris, J. O'M.
Yoshimatsu, M., Shibata, A., and Kohra, K. Modification of the scanning X-ray topographic camera (Lang's method), B (5) 139*j*.
Yoshinaga, H. See Ikegami, S.
Yoshioka, H. Double nuclear resonance and nuclear spin relaxation in ruby, (9) 238*j*.
Yoshioka, T. See Okazaki, K.
Young, A. W. TiC usage will grow, (1) 7*j*.
Young, D. A. Crystalline titanosilicate zeolites, P (10) 269*e*. Crystalline zirconosilicate zeolites, P (10) 269*e*. High-silica molecular sieve zeolites, P (11) 291*h*. Methods for the manufacture of group IVB metallosilicate zeolites, P (10) 269*i*. See Dominey, D. A.
Young, D. R. See Kerr, D. R.; Thomas, J. E., Jr.
Young, F. W., Jr., Baldwin, T. O., Merlini, A. E., and Sherrill, F. A. Camera for Borrmann stereo X-ray topographs, B (5) 139*j*.
Young, H. S. Tetragonal silicon and germanium disulfides and their preparation, P (9) 232*f*.
Young, J. E. Reaction of water vapor with fired ceramic products, B (1) 30*c*.
Young, L. Kinetics of recombination of Frenkel defects in anodic oxide films on tantalum, (7) 164*i*. See Harkness, A. C.
Young, R. W. See Graf, R. E.
Young, T. See Magill, P. J.
Young, V. G. Electrical resistance furnace, P (3) 82*c*.
Young, W. D. Differential output tubular incandescent lamp, P (3) 77*i*.
Young, W. J. Gunning of monolithic refractories, (9) 224*c*.
Yuasa, Y. Rotational flow phenomena of powdered system, (11) 300*d*.
Yudin, D. M. See Karapetyan, G. O.
Yupko, V. L. See Andreeva, T. V.
Yurchak, I. Ya. Effect of apatite and chalk additions on the sintering of porcelain, (9) 228*c*.
Yurkov, L. F. See Ginzburg, D. B.
Yuskevich, Yu. G. See Andrievskii, A. I.
Yust, C. S. See Morgan, C. S.
Yust, C. S., and Morgan, C. S. Formation of dislocation clusters during sintering of calcium fluoride, (8) 198*c*.
Yvars, M. See Oberlin, M.

Zabroski, F. See Novak, R. F.
Zackay, V. F., and Parker, E. R. Origin and nature of microstructures, B (9) 244*e*.
Zadumin, V. I. See Borisov, A. F.
Zadumin, V. I., and Borisov, A. F. Use of an electromotive force method for studying processes of glass crystallization, B (4) 113*c*.
Zagainov, G. G. See D'yachkov, P. N.
Zagar, L. Significance and measurement of the specific surface of ceramic materials, (5) 129*i*.
Zagar, L., and Bernhardt, W. Bonding of various metals with nonmetals as a basis for producing cermets, (5) 122*e*.
Zagar, L., and Krause, G. Determination of the specific surface of glass powders and its relation to statistical parameters obtained from particle size analyses, (4) 93*b*.
Zaichenko, F. E. New techniques in the technology of (clay) mining, (5) 132*j*.
Zaikina, V. D. See Shcheglov, S. I.
Zaininger, K. H. Electron bombardment of MOS capacitors, (7) 163*e*. See Revesz, A. G.
Zaitsev, L. M., and Bochkarev, G. S. Formation of oxy-bridges in compounds of zirconium, (11) 296*d*.
Zaitseva, N. D. Synthesis and determination of the heat of formation of the compounds $KWCl_6$ and K_2WCl_7, (2) 57*c*. See Vasil'kova, I. V.
Zakharchenko, M. A. See Vereshchagina, V. I.
Zakharchenko, M. A., Belogorskaya, N. V., and Aslanov, S. M. Cross sections of the quaternary reciprocal system of the fluorides and chlorides of lithium, potassium, and calcium, (4) 107*f*.
Zakharenkov, V. K. See Il'ina, N. V.
Zakharov, V. P. See Luginina, I. G.
Zaliznyak, D. V., Galdina, N. M., Maevskii, E. R., Mel'nik, E. P., Firer, M. Ya., and Shchekotikhina, N. M. Study of the service of various refractories in a tank furnace at the Gomel'sk Glass Factory, (4) 97*f*.
Zalm, P. See Lemmens, H. J.
Zamaria, J. F. See Hickam, W. M.
Zaporozhskii, A. I. See Botvinkin, O. K.
Zappia, A. T. Glass feeder scoop gear index mechanism, P (10) 255*e*.
Zaretzky, Z. Basic principles for refractories selection, (4) 96*f*.
Zaripova, L. G. See Gromakov, S. D.
Zarkhin, A. M., and Judina, G. V. Device for grading loose-material granules by weight, P (4) 103*e*.
Zarzycki, J. Coordination numbers in vitreous and crystalline systems, B (2) 62*a*.
Zarzycki, J., and Naudin, F. Magnetooptical study of molten salts at high temperatures, (1) 22*c*.
Zasolotskaya, M. V. See Alekseev, A. G.
Zatoplyaev, N. A. See Klyachin, V. V.
Zavesky, V. Mathematical correlations for the quality control of refractories, B (5) 141*j*.
Zavitsanos, P. D. See Yankwich, P. E.
Zavody V. I. Lenina Plzen, Narodni Podnik. Method of and apparatus for analyzing combustion products, P (3) 81*f*. Method of and device for regulating the relative amount of burning components for gas burners, P (10) 268*h*.
Zawada, A. See Markuszewicz, M.
Zawodni, J. T., and Markotan, R. J. Reinforced grinding wheel and reinforcing structure therefor, P (8) 173*h*.
Zecca, J. J. See Preziosi, L. M.
Zeidler, G. See Roess, D.
Zeitlin, A. High pressure methods and apparatus, P (10) 266*a*.
Zelenev, Yu. V. See Bartenev, G. M.
Zelentsov, V. V. See Brekhovskikh, S. M.
Zelentsova, S. A. See Brekhovskikh, S. M.
Zellar, W. V. See Shannon, R. F.
Zellers, J. T., Jr. Lip-tile mounting, P (3) 68*d*. Method and apparatus for automatic glass cutting, P (2) 39*b*. Seal for and method of packing joints in a glass furnace, P (11) 279*d*.
Zellers, J. T., Jr., Nyquist, R. A., and Meriwether, H. R., Jr. Method and apparatus for producing window glass sheets, P (10) 255*c*.
Zementanlagenbau Dessau VEB. Process for the calcination of raw silicate material, P (2) 35*a*.
Zemlyanskaya, V. Ya. See Miskarli, A. K.
Zen, E-an. Solubility measurements in the system $CaSO_4$-NaCl-H-O at 35°, 50°, and 70°C and 1 atm pressure, (2) 56*b*.
Zenger, D. H. See Baird, A. K.
Zenith Radio Corp. Cathode-ray tube, P (5) 127*b*. Color image reproducer having red phosphor combined with red-pass filter element, P (5) 127*c*. Process for fabricating miniature capacitors, P (1) 11*c*.
Zenker, M. Motion transmitting means for glass feeder plunger, P (8) 178*c*.
Zerbes, G. Process for firing ferrites of manganese and zinc to the equilibrium state, P (10) 265*h*.
Zertsalova, I. N. Influence of chemical composition on electrical resistance of iron-containing glasses, B (4) 113*g*.
Zertsalova, I. N., Fainberg, E. A., and Grechanik, L. A. Variations of activation energy and volume conductivity of solid glasses in relation to the conduction mechanism, B (4) 113*b*.
Zhabrev, V. A., and Moiseev, V. V. Self-diffusion of sodium ions in aluminosilicate glasses, B (9) 245*j*.
Zharkova, D. N. See Maslenkov, S. B.
Zharkova, R. M. See Samuseva, R. G.

Zhdanov, S. P., Yastrebova, L. S., Koromal'di, E. V., and Khvoshchev, S. S. Structure of the silicon-oxygen network in alkali silicate glasses as indicated by the results of studies of their leaching products, B (7) 171*b*.
Zhikharevich, S. A., Karaulov, A. G., et al. Replacing steel circular-flange inserts with graphitic articles, (9) 224*c*.
Zhil'tsova, I. G. See Ignatova, L. I.
Zhukhovitskii, S. Yu. New characteristics of complete rheological curves of thixotropic structural-linked clay suspensions, (1) 8*j*. Reasons for nonuniformity in the characteristic plastic-viscous flow of aqueous clay suspensions and methods of attaining invariance of these characteristics, (1) 27*j*.
Zhukov, N. V. See Gutkin, A. M.
Zhukovskaya, O. V. See Alekseev, A. G.
Zhukovskii, V. M., Tkachenko, E. V., and Vlasov, V. G. Phase transformations in the reduction of U_3O_8, (1) 26*i*.
Zhunina, L. A., Sharai, V. N., Mazurenko, V. D., Khripkova, N. N., and Luk'yanova, T. T. Certain structural characteristics of crystallization products of glasses in the system CaO-MgO-SiO_2 + (R_2O, R_2O_3), B (9) 246*d*.
Zhuravlev, N. N., and Stepanova, A. A. X-ray determination of the thermal expansion coefficient of ScB_2, (2) 59*d*.
Zhuravleva, M. G. See Brainina, D. Z.
Ziebold, T. O. Precision and sensitivity in electron microprobe analysis, (10) 267*d*.
Ziegler, G. See Spielmann, W.
Ziegler, H. W. See Werner, H.
Ziehr, G., and Drosdziok, H. Preparation of metal surfaces for enameling, P (8) 174*i*.
Zifferer, L. R. Vortex grinding mill, P (4) 107*d*.
Zigel, V. A. See Kotelnikov, G. R.
Zil'berg, E. S. See Balyuk, S. T.
Zimmer, F. Composite structures made by bonding ceramics, cermets, alloys, heavy alloys, and metals of different thermal expansion coefficient, P (2) 43*i*.
Zimmer, W. J. See Haertling, G. H.
Zimmerman, H. A. See Wilson, W. E.
Zimmler, A. Surface temperature measurement and control, (7) 160*c*.
Zinchenko, K. A. See Kalitin, V. I.
Zinkweiss-Forschungsgesellschaft. Production of a zinc oxide pigment, P (8) 190*h*.
Zirconium Corp. of America. Gastight refractory article and method of making same, P (2) 44*d*.
Zirngiebl, E. Process for the production of barium carbonate from barium sulfate, P (5) 133*c*.
Zinelberger, A. E., Eliason, S. H., Hildebrand, E. L., Eliason, S. H., Jr., and Headlee, W. C. Ball mill for forming liquid suspensions of finely divided solid material, P (4) 103*c*.
Zisman, W. A. See Shafrin, E. G.
Zisner, T. Reactive hot-pressing of magnesium hydroxide, (11) 300*h*. See Tagai, H.
Zisner, T., and Tagai, H. Comment on "Functional relation between creep rate and porosity for polycrystalline ceramics," (10) 270*f*. Optical accentuation of fine pores in ceramic bodies, (10) 267*a*.
Zivanovic, B., and Ristic, M. M. Influence of frequency and acceleration on density during the vibrational compaction of ceramic oxides, (7) 151*e*.
Zmii, V. I. See Ivanov, V. E.
Zobel, C. R. See Berger, J. E.
Zollman, J. A., and Berg, M. Method and materials for metallizing ceramics, P (3) 79*b*.
Zolotov, I. N. See Shaposhnikov, A. P.
Zolotov, V. A., and Makarov, V. I. Mechanism of formation of crystals of gypsum α-hemihydrate, (7) 165*a*.
Zoltai, T. See Blake, R. L.
Zook, J. D. and Hornung, H. J. Tunnel diodes, P (7) 158*b*.
Zope, J. K. See Gray, T. J.
Zorin, A. P., and Mazurin, O. V. Measurement of resistance-temperature relations of glasses in the high-resistance region, B (4) 113*d*.
Zorina, E. L., and Kovaleva, I. S. Infrared absorption of the glasslike As_2S_3, (8) 200*f*.
Zoroatskaya, I. V. See Gromakov, S. D.
Zubarev, A. I. See Rutes, V. S.
Zubekhin, A. P. See Ponomarev, I. F.
Zucca, T. See Carraro, G.
Zucker, R. S. Growth of single-crystal cuprous oxide from the melt and luminescence of cuprous oxide, (11) 296*c*.
Zuest, H. E. See Baertschi, P.
Zuidema, G. See Phaal, C.
Zuikov, G. G. See Khigerovich, M. I.
Zuleeg, R. Thin film heterojunction device, P (10) 265*i*.
Zupan, J. See Chao, P. J.
Zupp, R. R., and Stevenson, D. A. Influence of vanadium on the activity of carbon in the Fe-C-V system at 1000°C—correlation of the influence of substitutional solutes on the activity coefficient of carbon in iron-base systems, (7) 164*h*.
Zussman, J. See Deer, W. A.
Zvirenas, A. See Nickus, I.
Zwell, L. See Duggin, M. J.
Zwicker, J. D. Comparison of particle size analysis methods, (4) 104*c*.
Zylka, L. See Schaefer, H.
Zysk, E. D. Noble metal thermocouple having base metal compensating leads, P (10) 268*a*. Thermocouple having tungsten-rhenium alloy leg wires, P (4) 105*a*. See Toenshoff, D. A.
Zysk, E. D., and Toenshoff, D. A. Calibration of refractory metal thermocouples, (10) 266*j*.

SUBJECT INDEX TO CERAMIC ABSTRACTS FOR 1967

The reference number in parentheses refers to the monthly issue of *Ceramic Abstracts;* the number following is the page number. The letter B or P preceding the reference number indicates an abstract of (B) a book, bulletin, or separate publication or (P) a patent. The italic letter following the page number indicates position on the page. For more complete indexing of papers published in the *Journal of The American Ceramic Society* and the *American Ceramic Society Bulletin*, see indexes to the *Journal* and the *Bulletin*.

Ablation, ablative materials, continuous method of making, P (3) 72*f*.
of graphite in oxygen and air at 1000° to 1400°C under flow conditions, (2) 40*i*.
of high purity and nuclear reactor graphite in oxygen and air, (7) 151*b*.
material reinforced plastic with zirconia foil, P (9) 225*j*.
Abrading apparatus. See *Grinding apparatus.*
Abrasion, effect on specific surface area of metals and glass, (3) 66*e*.
resistance measurement, P (1) 14*c*.
resistant refractory material, P (2) 43*b*.
test for refractories, (10) 256*h*.
Abrasives. See also *Aluminum oxide; Carbides; Diamonds; Grinding apparatus; Polishing apparatus; Silicon, carbide.*
articles, and method of making, P (2) 33*j*.
organic bonded, P (2) 33*i*.
polybenzimidazole resin bonded, P (10) 247*g*.
resin bonded, containing olivine, P (10) 247*h*.
solid, P (1) 1*f*.
barrel finishing, 27 different jobs, (7) 145*f*; (8) 186*i*.
belt, P (10) 247*g*.
blasting wheel assembly, P (2) 33*f*.
for cements, P (4) 91*c*.
coated, P (10) 247*g*; P (11) 273*g*.
polymer saturated backing material for, P (4) 89*f*.
coated backing of sheathed synthetic fiber yarns, P (8) 173*g*.
compositions, resinous, and preparation, P (4) 89*f*.
cutting disks, P (1) 1*f*.
cutting tool, wear-resistant hot-pressed, composed of titanium carbide and boride and metal binder, P (8) 173*h*.
diamond reinforced coatings, and method of preparing, P (4) 89*g*.
disk unit, P (5) 115*g*.
elements, P (7) 145*h*.
finishing, for restoring museum pieces, (11) 273*h*.
flexible, products, P (3) 63*h*.
free-, machining, (8) 173*f*.
grit, apparatus for handling, P (10) 266*e*.
machining, future, (9) 213*f*.
metal backed, P (2) 33*h*.
phenol-formaldehyde resin bonded, humidity controlled, P (9) 213*g*.
powders, particle size analysis by sedimentation, (1) 1*f*.
product, P (5) 115*g*.
flexible coated, P (10) 247*f*.
pulpstone, making, P (1) 1*f*.
segments, for saws, P (4) 89*h*.
sleeve for rotary abrading machines, P (11) 273*f*.
substance, process of making, P (2) 33*j*.
surfaces, method of producing, and product, P (5) 115*g*.
tools, and method of making, P (7) 145*h*.
wheels. See *Grinding apparatus.*
Absorption, arrested, for determination of bulk density of granular refractories, (8) 179*j*.
atomic, for analysis of portland cement, (10) 247*j*.
studies on rare earth and refractory metals, (8) 191*j*.
bands, of CeO, rotational analysis, (7) 167*e*.
in evaporated BaO films, (3) 83*h*.
gamma-induced, associated with Tl^+, Pb^{3+}, or Bi^{3+} in potassium borate glasses, (11) 276*i*.
edge, optical, in layer-type semiconductors, (10) 271*g*.
edge spectrum, of scandium oxide, (8) 190*j*.
of electrons, effect of weak Bragg reflected beams, (8) 185*j*.
free carrier, in *n*-type SiC, (8) 198*f*.
gamma-radiation, measurement, for density determination of refractories, (9) 223*g*.
gamma-ray, for slip-casting kinetics of alumina, B (7) 170*e*.
gas, of ion-exchanged type A molecular sieves, (9) 235*f*.
of gases in glasses, (10) 250*j*.
of high energy electrons passing through crystals, effect of point defects, (8) 195*h*.
infrared, for estimation of kaolinite in clays, (8) 187*d*.
for examining coordination of aluminum ions in tricalcium aluminate, (3) 64*b*.
far-, of single crystal UO_2, (8) 209*f*.
of glasslike As_2S_3, (8) 200*f*.
of solid silicates and phosphates with and without fluoride additions, (7) 164*i*.
Absorption infrared, (*continued*)
study of urea complexes with montmorillonite, (4) 112*f*.
temperature dependence, due to U centers in alkali halides, (2) 57*d*.
inner crystalline, of water and organic substances of tetracalcium aluminate hydrate, (8) 174*e*.
NMR, of cesium and thallium silicate glasses, (11) 277*d*.
optical, coefficients of vanadium pentoxide single crystals, (8) 203*j*.
of neutron-irradiated ZnS, (8) 204*c*.
radiation induced, in lead borate glasses in relation to structure changes, (2) 37*d*.
optical, of thermally oxidized Si oxide film, (5) 137*a*.
spectra. See *Spectra.*
visible and near-infrared, of uranium in sodium silicate glass, (7) 149*d*.
Acids. See also specific types.
mineral, catalytic action, on transformation of γ-Fe_2O_3 to α-Fe_2O_3, (8) 192*f*.
phosphomolybdic, extraction of cesium with nitrobenzene in presence of, (1) 13*e*.
silicic, reactions with o-diphenol polymers in water, (3) 87*i*.
Acoustics. See also *Insulation, acoustical; Sound.*
anisotropic, attenuation with new measurements for quartz at room temperature, (8) 191*d*.
attenuation, of single-domain lithium niobate crystal at microwave frequencies, (9) 237*b*.
shear-wave generation, by mode conversion in YAG, (11) 294*j*.
surface waves in α-quartz and cadmium sulfide, numerical data, (8) 203*h*.
Actinide, metal carbide microspheres, preparation, P (4) 98*i*.
oxide fuel particles, method of preparing, and article, P (4) 98*f*.
oxides, electrolytic deposition, P (8) 181*a*.
separating method, P (1) 15*j*.
Adherence. See *Enamels.*
Adhesives, glass to glass, P (11) 278*b*.
Adsorption, of ammonia on fluorine-containing porous glass, (1) 16*g*.
of certain dyes on clays, (1) 16*i*.
of dyes to etch pits on potassium chloride crystal surface, (9) 233*f*.
effects on diffusion in porous silica glass, (8) 175*j*.
of elements from HNO_3-HF and H_2SO_4-HF solutions by cation and anion exchange, (8) 191*a*.
gas, on freshly broken glass surfaces, source of error in analysis of bubbles in glass, (11) 276*i*.
methylene blue, for determination of cation exchange capacity, (7) 159*b*.
montmorillonite and illite, of amino acids and peptides: I, cation exchange and proton transfer; II, physical, (7) 161*f,k*.
phenol, mechanism, by organoclay derivatives, (1) 22*f*.
physical, on heterogeneous surfaces, (1) 26*g*.
montmorillonite and illite, of amino acids and peptides, (7) 161*k*.
plane monolayer, with area changes, (1) 26*j*.
of radioactive phosphate on two ternary borate glasses, (10) 253*e*.
on silica glass, from nonelectrolyte solutions, (8) 175*b*.
of silica suspensions, effect of solid content, (8) 195*i*.
vapor, theory of volume filling, (2) 57*g*.
of water and carbon dioxide on beryllium oxide, (7) 161*j*.
Aerofoil blade, for use in hot fluid stream, P (8) 174*i*.
Aerogels. See *Colloids; Silicon dioxide.*
Aerosols. See *Colloids.*
Afterglow. See *Luminescence.*
Agglomeration, of anhydrous sodium metasilicate fines, P (11) 291*d*.
Aircraft ceramics. See *Cermets; Spacecraft; Turbines.*
Aggregates, absorption and moisture determination in, (11) 274*j*.
angularity, laboratory test for determining, (9) 214*g*.
catalyst, of crystallites, P (8) 180*g*.
for concrete, use of fineness modulus for grading evaluation, (9) 215*d*.
expanded, apparatus for, P (7) 160*c*.
evaluation for use in skid-resistant pavement surfaces, (4) 90*g*.
lightweight, P (11) 280*a*.
expanded shale, P (9) 223*a*.
Japanese, (4) 96*b*.
method of making from fly ash, P (9) 223*b*.
Aggregates (*continued*)
process for forming, of powdered materials, P (5) 130*d*.
silicate, solutions, effect on glass strength, (11) 276*i*.
synthetic, manufacture, P (3) 70*f*.
Aging, behavior dependence of sintered alumina on surfactants, (2) 42*i*.
Air, ablation of graphite in, at 1000° to 1400°C under flow conditions, (2) 40*i*.
pollution, closer controls, problems for plant engineers, (11) 288*e*.
control, (2) 49*h*.
control measures in McIntyre assay dept., (4) 112*h*.
Alkaline earths. See also specific types.
alkaline diabase-picrite intrusion, prospect, New South Wales, Australia, (8) 205*i*.
bromates, crystalline, radiolytic decomposition, B (9) 244*c*.
chlorides, viscosity measurements, (7) 169*d*.
nitrates, and molten alkali mixtures, equivalent volumes, (8) 197*c*.
oxide modules, partially ionic model for, (3) 87*j*.
titanates and niobates, method of preparing and coating to form capacitor, P (10) 264*h*.
Alkalis. See also specific types.
behavior, as function of firing conditions and cement charge composition, (10) 247*j*.
chloride-lead chloride liquid mixtures, thermochemistry, (8) 210*b*.
chlorides, viscosity measurements, (7) 169*d*.
content, in clinker, effect on cement quality, (9) 214*e*.
method and arrangement for increasing in alkali-laden dusts of flue gases, P (8) 174*c*.
halide crystals, vapor pressure analysis, (7) 161*k*.
halides, anharmonic interactions: II, (1) 16*f*.
halides, low-temperature annealing processes, B (9) 244*e*.
halogenide single crystals, very pure, production by zone melting, (8) 205*e*.
halogenides, vacuum distillation and crystal growth, (7) 169*b*.
metal compounds, method and apparatus for recovering from alkali-rich dust when producing cement clinker, P (9) 215*i*.
metal nitrate systems, fused, specific conductance and density measurements: I, solvent systems and binary solutions; II, conductometric titrations, (8) 207*j*.
metal titanates, fibrous, process for producing, P (10) 265*i*.
method and cement kilning plant for removing from flue gas emanating from cement kiln, P (9) 215*i*.
molten, and alkaline earth nitrates mixtures, equivalent volumes, (8) 197*c*.
systems. See *Systems.*
tannides, effect on aqueous clay suspensions, (7) 162*d*.
Allophane, from kaolinitic nodules in shale, (8) 191*b*.
Alloys, alloying material to semiconductor bodies, P (2) 48*e*.
B_4C-B_4Si hard, pseudobinary, conditions of preparation and properties, (10) 256*j*.
binary, kinetics of simultaneous internal oxidation and external scale formation for, (9) 240*e*.
for contact with molten materials, P (10) 255*c*.
ferrous base, coating for protection of, at elevated temperatures, P (4) 92*f*.
GeTe-PbTe, properties, (9) 230*b*.
hard, from pseudobinary section SiC-BC grown from gaseous phase, preparation and study of properties, (8) 205*j*.
of isomorphous carbides, thermoemission characteristics, (8) 210*b*.
of PbTe-SnTe solidification under influence of ultrasonic agitation, (10) 263*h*.
low melting point, use in shaping pottery, (9) 228*d*.
Mo-Si, reaction diffusion, (4) 109*b*.
nickel-base, vacuum induction melting, refractory-melt reactions in, (8) 180*i*.
nickel chrome, with high resistance to attack by molten glass, P (8) 178*c*.
Permalloy, thin film, growth on LiF, (9) 240*b*.
powder metal cutting, effect of hydrostatic pressure on elastic properties of, (4) 96*e*.
powder metal hard, rupture mechanism, (1) 28*i*.
in system Mo-Re-C, X-ray study, (2) 60*f*.
WC-TiC-Co hard, sintered, containing tantalum carbide, properties, (10) 258*j*.

Alumina. See *Aluminum, oxide.*
Aluminates. See also *Alkaline earth.*
alkali metal, amorphous, P (1) 9*a*.
tricalcium, and related phases in portland cement, (2) 34*d*.
Aluminosilicates, crystalline, method for producing, P (7) 153*d*.
crystalline, zeolitic particles of uniform size, method for producing, P (8) 190*c*.
determination of glass content in, (3) 71*h*.
surface characteristics and flotation behavior, (4) 106*g*.
Aluminum, Al-Al_2O_3 alloys, quenched, behavior of vacancies, (8) 191*e*.
$Al_{2-x}Fe_xO_3$ compounds, orthorhombic and rhombohedral, high-magnetic-field studies, (8) 199*c*.
$AlNbO_4$, crystal structure, (5) 134*j*.
arsenide, method of preparing, P (4) 102*c*.
chloride, systems. See *Systems.*
determination in iron ores and slags, (5) 130*h*.
etching, P (1) 3*a*.
evaporation, from boron nitride source, (1) 12*d*.
fluoride, additives, effect on strength of refractory materials, (5) 122*d*.
fluoride, systems. See *Systems.*
high resistance anodic oxide films on, (3) 76*a*.
hydroxide, coprecipitated, spinel formation from, (4) 110*c*.
single crystals, hydrogen liberation during dehydration of, (8) 201*a*.
ions, coordination in tricalcium aluminate, (3) 64*b*.
molten, and vitreous silica, reaction between, (3) 65*c*.
nitride, mixtures, preparation and examination, (7) 152*b*.
physical properties, (8) 207*i*.
preparation, P (5) 124*h*.
refractories, method of sintering, P (2) 44*c*.
thin crystals, measurements of spontaneous bending attributed to surface stresses, (1) 22*d*.
oxidation, by carbon dioxide in presence of cryolitic electrolyte, (3) 87*f*.
from contact with mercuric iodide, (3) 77*g*.
oxide. See also *Boehmite; Corundum; Refractories.* (5) 134*b*.
activated, for drying air under adiabatic conditions, (4) 103*e*.
activated recrystallization sintering of, factors determining, (5) 136*d*.
α-, at low water vapor pressures, (8) 208*j*.
α-, pressure deformed single crystal, gamma-ray induced defect bleaching, (1) 19*c*.
α-, spheres, gamma-irradiated, mechanical and optical properties when subjected to 30-k-bars pressure, (2) 56*f*.
α- and γ- heats of immersion, (7) 164*a*.
amorphous, P (2) 53*h*.
amorphous, rehydration, (1) 29*j*.
aqueous suspensions, and process for production, P (8) 190*c*.
bodies, sintered, corrosion resistance to inorganic acids, (8) 180*i*.
bodies, sintered, determination of elastic limit at room temperature, under local compression, (2) 41*i*.
body, with sintered metallic layer and flux, P (7) 156*h*.
cement, pH value, (3) 64*d*.
ceramic body, metallizing, P (3) 79*a,b*.
chemically strengthened, leached, (5) 122*i*.
Cr_2O_3 solid solution hardening of, (2) 54*f*.
from clay, method for producing in lime-soda sinter process, (10) 269*f*.
cobaltous ion in, (8) 192*e*.
codeposition mechanisms, with electrolytic copper, (7) 165*c*.
commercial, water suspensions properties, and rational conditions for slip casting, (5) 123*h*.
comprising nordstrandite in major proportion, process for producing, P (9) 227*a*.
in computer assemblies, (1) 9*f*.
crystal growth by solid-state techniques, (5) 134*b*.
determination in chrome ore, (3) 70*j*.
dielectric properties and sintering, recent Soviet work, (9) 229*i*.
dielectric properties and sintering, review, (9) 229*i*.
diffusion of Cr_2O_3 and NiO into, (2) 47*a*.
discharge tube, high temperature, for pulsed metal vapor lasers, (1) 9*j*.
electrical properties, at high temperature, (3) 85*b*.
extractability from anorthosite, correlation with reaction products in lime-soda sinter process, (10) 269*d*.
I, extrusion: II, coherence and strength of compacts, (3) 74*c,d*.
-Fe-Fe_2O_3, sintering, effect of CaO-MgO-SiO_2 mixture, (11) 280*d*.
films, distribution of defects near metal-to-oxide interface, (9) 229*c*.
films, manufacturing, P (10) 264*e*.
films, plasma anodized, (4) 100*b*.
fused, Saurashtra bauxite for production of, (11) 291*b*.
fusion point measurement, (7) 159*e*.
gels. See *Colloids.*
high, Kagaku Togyo widens scope with, (4) 99*i*.
high porosity gamma, process for producing, P (9) 236*h*.
highly dispersed, process for purification, P (9) 236*j*.
hot hardness to 1900°C, (7) 164*f*.
Aluminum, oxide (*continued*)
hydrate phases, formation during setting of cement, (7) 146*e*.
improves properties of whiteware bodies, (9) 228*a*.
inclusion of radioactive krypton in, during thermal surface changes, (2) 55*d*.
increased content in porcelain during firing of ceramic products, (1) 9*b*.
kinetics of reaction with melts of ternary system CaO-SiO_2-Al_2O_3, (8) 201*i*.
liner, in crystal growing furnace, P (2) 52*f*.
molybdenum fiber reinforced, P (9) 226*e*.
with narrow pore size distribution, process for preparing, P (9) 226*j*.
particles, method for preparing, P (8) 181*d*.
polycrystalline, diffusion-controlled creep, effect of MgO and $MgTiO_3$ doping, (5) 135*i*.
polycrystalline ceramic, thin silicon film growth on, (4) 100*d*.
porous, solubility of hydrogen in, (9) 242*k*.
-KI, electron diffraction studies, (2) 55*b*.
precipitated, surface properties: V, radiochemical investigation of chloride-ion contamination, (2) 57*a*.
product, of α-alumina from alumina hydrate, process for making, P (11) 282*d*.
reaction with cesium vapor, (5) 137*j*.
reactor irradiated and unirradiated, annealing of defects and color centers in, (3) 83*h*.
silver-, alloys, strength and creep behavior above melting point of silver, (4) 110*i*.
$AgNO_3$-coated, in column for gas-solid chromatography, P (4) 98*i*.
single crystal, corrosion resistance to inorganic acids, (8) 180*i*.
sintered, and dependence of its aging behavior on surfactants, (2) 42*i*.
sintered, effect of pores on rate of grain growth, (4) 110*d*.
sintered, nonbasal dislocations, direct observation, (10) 270*i*.
sintered transparent bodies, and method of making, P (7) 154*c*.
sintering: VI, grain growth, mechanical strength, and light transmission of hot-pressed alumina; VII, effects of strain energy and temperature gradient on grain growth of alumina, (7) 168*i, a*.
solid body, high purity, methods for forming by fusion, P (5) 128*a*.
solid solution of titanium dioxide in, (1) 28*i*.
sorption of Congo red molecular colloids, (3) 86*h*.
substrate, electroless copper plating on, P (4) 101*d*.
supported copper oxide-rare earth oxide catalyst compositions, P (2) 43*c*.
systems. See *Systems.*
thermoluminescence, (11) 302*d*.
tools, ceramic cutting, present and future, (2) 33*h*.
trihydrates properties obtained by aging alumina gel in aqueous solutions, (1) 27*i*.
tunnel junctions, voltage dependence of barrier heights, (5) 139*c*.
wetting by chromium-nickel melts, (10) 259*b*.
wool, process for preparing, P (11) 282*f*.
oxides and hydroxides thin films, use of X-ray emission spectroscopy in characterization, (9) 243*b*.
phosphate, differential thermal analysis and X-ray investigation, (5) 135*e*.
of cristobalite type, solid solution with cristobalite, (4) 109*i*.
phosphates, precipitation effects, (3) 87*e*.
phosphide crystals, methods of making, P (3) 79*f*.
porcelain enamel surface, orientation of lead antimonate and titanate crystals, (5) 117*f*.
recovery of, from red slurries of bauxite, P (4) 107*d*.
recovery process, from red slurries obtained in processing bauxite by Bayer process, P (4) 107*a*.
redistribution, in thermally oxidized Si surface, (5) 134*a*.
resources, potential, of world, (8) 189*f*.
silica fiber reinforced, (3) 65*e*.
silicate whiskers, synthesis, P (9) 227*h*.
systems. See *Systems.*
thermal oxide films, discontinuous, growth kinetics, (3) 86*d*.
trifluoride, anhydrous crystalline, measured relative enthalpy from 273° to 1173°K and derived thermodynamic properties from 273° to 1600°K, (11) 298*b*.
Alunite, from kaolinitic nodules in shale, (8) 191*b*.
Americium, oxides, ternary, (11) 302*d*.
oxides, ternary, of type $M(III)X(V)O_4$, reaction conditions, lattice constants, and chemical properties, (11) 299*j*.
Ammonia, adsorption on fluorine-containing porous glass, (1) 16*g*.
reactions, with montmorillonite and saponite, infrared study, (7) 164*a*.
Ammonium, alum, partition of ions, (8) 204*a*.
salts, action on concrete, (2) 34*a*.
sulfate, chromatographic separation of metals by elution with, (4) 104*c*.
Amphiboles, fibrous, crystallization conditions in hydrothermal synthesis, (10) 272*g*.
metamorphic, stability, the tremolite-ferroactinolite series, (10) 272*b*.
Analysis. See also *Chromatography; Colorimetry; Electron diffraction; Microscopy; Particles; Photometry; Quality control; Screens and sieves; Spectrography; Spectrometry; Spectrophotometry; Spectroscopy; Testing; Thermal analysis; Thermodynamics; Thermogravimetry; Titration; X rays.*
Analysis (*continued*)
absorptiometric determination of microgram amounts of uranium with rhodamine, B (8) 187*b*.
activation, for determination of sodium in ultrapure silicon and silicon dioxide films, (10) 267*c*.
of 15 light elements from 18-Mev helium-3 particles, sensitivities for, (9) 242*e*.
of silicon by convention carrier separations and by computer reduction of gamma spectra, (2) 50*d*.
of asbestos-cement products, (11) 274*g*.
chemical, of potassium in cement with polarization current titration, (1) 2*b*.
complexometric, of Al, Ca, and Mg in cements and clays, (4) 90*h*.
electron microprobe, precision and sensitivity in, (10) 267*d*.
electrooptic, of spectral lines, modulated light source for, P (4) 104*j*.
Fourier, of electron micrographs—laser as light source for optical diffractometers, (1) 13*j*.
gas. See *Gases.*
of hot-pressing parameters for lead zirconate-lead titanate ceramics with 2%(at.) bismuth, (1) 9*f*.
iodometric, for determination of Mg in limestone, dolomite and magnesite, (7) 159*d*.
mechanical, of subaqueous sediments, methodology, (8) 187*d*.
micro-, electron-beam, for evaluation of magnesite sinters, (8) 197*f*.
X-ray, in chemistry, (9) 234*b*.
X-ray-emission, of rock-forming minerals: V, orthopyroxenes; VI, Clinopyroxenes near diopside-hedenbergite join, (10) 272*e*.
quantitative, of binary mixture UO_2-U_3O_8, by X-ray diffraction, (8) 179*i*.
rapid, for Cr_2O_3 in chromite ores and in refractories, (7) 159*c*.
rapid modal, of coarse-grained rocks, device for, (8) 187*c*.
sedimentation dispersion, problems, (10) 267*e*.
spectrochemical, atomic absorption, dissociation and ionization effects, (4) 104*f*.
statistical criterion for degree of dispersity and allowance for particle shape effect on permeability and pressibility of powders, (4) 110*g*.
statistical theory of primary breakage distribution for brittle material, (4) 110*h*.
Analyzers. See also *Gases.*
micro-, electron, combined with electron microscope, analytical applications, (10) 266*i*.
particle studying device pulse, P (3) 81*h*.
Anatase, high-temperature formation, (10) 271*a*.
Anions, chain-length distribution in high pressure modifications of Na phosphate glasses in dependence on pressing temperature, (10) 250*j*.
exchange, for adsorption of elements from HNO_3-HF and H_2SO_4-HF solutions, (8) 191*a*.
inorganic, process for separating with hydrous oxide anion exchangers, P (10) 270*b*.
oxy-, -yielding ingredient aluminum, gallium, or germanium, in luminescent compositions, P (2) 47*j*.
Anisotropy, crystalline, energy, in CrO_2, (5) 134*j*.
factor, of resistivity of graphite body, method for determining, P (11) 289*i*.
ferromagnetic crystalline, of Ti-substituted magnetite, (7) 163*e*.
frictional, in diamond, magnesium oxide, and lithium fluoride crystal surfaces, (11) 296*g*.
magnetic, of magnetoplumbite, $BaFe_{12}O_{19}$, (9) 240*a*.
measurements of CoO single crystal, (8) 202*c*.
measurement on CoO single crystals, new interpretation, (10) 271*f*.
in single-crystal Permalloy thin films epitaxially grown on LiF (110) surface, (9) 240*b*.
magnetocrystalline, of $xFe_2TiO_4 \cdot (1-x)Fe_3O_4$, (7) 165*f*.
of $xFe_2TiO_4 \cdot (1-x)Fe_3O_4 (x > 0.5)$, (8) 202*i*.
microstructural, specification and measurement, (4) 110*b*.
Annealing, of BSC glass, effects of distribution of volume relaxation times, (10) 251*e*.
of defects and color centers in unirradiated and in reactor irradiated Al_2O_3, (3) 83*h*.
of dislocation loops by climb, (8) 191*f*.
of glass. See *Glass.*
isothermal, studies on vacancy and interstitial loops in single crystal graphite, (8) 201*a*.
low-temperature, processes in alkali halides, B (9) 244*e*.
Anodes. See also *Electrodes.*
Al-Si-Mn-Li, for high temperature galvanic cell, P (4) 92*c*; P (5) 117*j*.
anodization, oxygen plasma, preparation of tantalum oxide films, (7) 156*d*.
hydrogen, including aluminum spinel and platinum family coatings, and method of making, P (5) 124*j*.
nickel-silver alloy, in fuel cell, P (4) 101*h*.
Anorthite, -forsterite and -enstatite, reactions and effect on basalt-eclogite transformation, (8) 191*f*.
Antiferromagnetism. See *Ferromagnetism.*
Antimony, β-Sb_2O_4, crystal structure, a new polymorph, (8) 193*d*.
Sb_2S_3, energy gap, difference determined from spectral characteristics of photoconductance and absorption, (5) 135*d*.
Sb_2S_3 single crystals, relation with microwave field, (5) 138*b*.
Sb_2Se_3 single crystals, trap studies by thermally stimulated current technique, (11) 302*j*.
in glass, (2) 36*c*.

Antimony (*continued*)
sulfide, molten, thermodynamic and electrical investigations, (8) 210*d*.
systems. See *Systems*.
trioxide, manufacture, P (10) 269*f*.
Apatite, additions, effect on sintering of porcelain, (9) 228*c*.
crystal growth, implications, (2) 55*e*.
-magnetite-vermiculite deposits near Sitarampur, Visakhapatram district, Andhra Pradesh, (8) 189*e*.
Apparatus. See *Instruments; Machinery and equipment; Testing;* and specific types.
Aragonite, conversion processes to calcite with examples from the Cretaceous of Texas, (7) 166*i*.
Archeology, ancient glass from cemeteries of Samothrace, (11) 273*i*.
ceramics for, B (4) 112*j*.
early formative period of coastal Ecuador, the Valdivia and Machalilla phases, B (4) 113*b*.
glass slab, 8.8 tons, from ancient Galilee, (11) 273*j*.
medieval glass found in Yugoslavia, (11) 274*a*.
microprobe and X-ray, in chemistry of antique ceramics, (3) 63*j*.
Mycenaean and Minoan pottery, spectrographic analysis, (11) 274*f*.
primitive glass furnace in Cairo, (11) 274*d*.
Architecture, architectural ceramics in Russia, (3) 63*i*.
Argon, in glasses, solubilities at pressures to 10 kbars, (1) 4*d*.
Arsenic, As_2O_3, growth on GaAs, (7) 155*j*.
As_2S_3, glasslike, infrared absorption, (8) 200*f*.
Arsenides, orthorhombic boron, and preparation, P (11) 282*b*.
Art and artware. See also *Archeology; Decoration; Design; Majolica; Pottery; Tile*.
bowls, enameling steep-sided, (4) 89*j*.
ceramic, relation between technology and, (4) 90*a*.
ceramics with drinking mottos-"black varnish" ware from late Roman potteries on Rhine and Mosel, (1) 1*k*.
"Der Kroening" peasant potters and present-day revival, (1) 1*h*.
enamel ashtrays for outdoors: I, II, combining enameled metal and casting stone, (4) 89*j*.
enameled belts, (5) 115*j*.
exhibition of Austrian folk majolica in Castle Gobelsburg, (1) 1*i*.
glass, ancient, from cemeteries of Samothrace, (11) 273*i*.
with checkered spiral-trail decoration from southern Netherlands in 16th and 17th centuries, (11) 273*i*.
Hellenistic, in Metropolitan Museum, (11) 274*a*.
at Hoya Glass Works, (4) 93*a*.
individual designs, by Sarpaneva, (7) 146*b*.
Mehlis plant in Thueringer Wald, (11) 274*b*.
methods of molding integrally a foot and stem part, P (1) 6*f*.
optical effect decorative, blowing mold for, (7) 146*a*.
recent acquisitions by collections, (11) 274*d*.
recent publications, (11) 273*j*.
Russian in second half of 19th century, (11) 274*e*.
Torcello ancient kilns and melting methods, (11) 273*j*.
group project in ceramics, (5) 115*j*.
international ceramic competition in Florence, 1966, (9) 213*j*.
international ceramics exhibition, Vicenze, (9) 213*i*.
jewelry, from enamel lumps, (4) 90*b*.
Meissen porcelain, in Bavarian National Museum, (7) 145*j*.
museum pieces, restoration by abrasive finishing, (11) 273*k*.
pectoral, of eighteenth dynasty, inlaid with color glass and semiprecious stones, (11) 274*c*.
porcelain, Russian, under the czars, (3) 63*j*.
Schackert, snuffbox, (11) 273*i*.
Tschirnhaus inventor, not Boettger, (3) 63*j*.
Raku: I, history and appreciation, (5) 115*j*; III, pottery of America, (5) 116*a*.
Rhenish pottery, exhibition in Frechen, (9) 213*j*.
slab plaque, making, (4) 90*b*.
stoneware, ancient from Muskau, (1) 1*h*.
stoneware lantern with glass inserts, (5) 116*a*.
tiled stoves, modern style, (7) 145*j*.
Artists, Ball, F. Carlton, (5) 115*j*.
Boettger, (3) 63*j*.
Bontjes van Beek, Jan, (9) 213*i*.
Busz, Rolf and Ursula, potters in Istanbul, (7) 145*j*.
Coronel, Raul Angulo, (4) 90*a*.
Gigov, Peter, potter maintaining Bulgarian tradition, (7) 145*j*.
Kagel, Wilhelm, (9) 213*j*.
Lakofsky, Charles, (5) 115*j*.
Loesche, Ernst, ceramic art exhibition in Munich, (9) 213*i*.
Maetzel, Monika, (9) 213*j*.
Quillmann, Konrad, (3) 63*i*.
Reimers, Lotte, ceramic art experiments, (9) 213*i*.
Renfer, Pierre, Swiss designer, (1) 1*i*.
Sarpaneva, Timo Tapani, Finnish, with individual designs in glass, (7) 146*b*.
Tschirnhaus, (3) 63*j*.
Asbestos, cement pieces, machine for making, P (5) 116*i*.
-cement products, P (2) 34*k*.
analysis, (11) 274*g*.

Asbestos (*continued*)
crude, apparatus to dress, P (2) 53*k*.
fibers, device for dressing, P (11) 291*e*.
fibrous bundles, separated from source rock, method of opening up, P (8) 190*b*.
defibering, P (1) 12*e*.
dispersing, process, P (4) 107*a*.
fiber, dispersion, for cellular thermal or acoustic insulation, P (11) 282*f*.
lagging composition, analytical studies, (11) 290*i*.
ore, concentration, P (9) 235*j*.
waste for porous ceramics, (4) 96*f*.
Ash, fly, brick, status, (9) 223*c*.
in brick manufacturing, (8) 179*f*.
in cement, (4) 91*c*.
for making lightweight aggregate, P (9) 223*b*.
Neyveli, as partial replacement for cement, (10) 248*b*.
of power stations, deterioration of aluminosilicate refractories, (3) 70*i*.
Atmospheres, effect on sintering of ferrites, titanates and oxide ceramics, (7) 151*k*.
furnace, effect on fining a container-type glass, (1) 3*i*.
influence on sintered ferrite density, B (7) 170*i*.
improvements in control of reducing, (4) 105*e*.
multizone, control, P (8) 189*c*.
gas, effect during firing on clinker properties of white cement, (10) 248*c*.
wet, effect on spontaneous bubble formation in silicate melts at high temperatures, (11) 277*c*.
Atoms, atomic layers, elementary, diameter in strained carbon between 1000° and 2000°C, (2) 54*i*.
atomistic approach to nature and properties of materials, B (9) 244*c*.
nonmetallic, effect on electrical properties of high-melting compounds of transition metals, (3) 85*d*.
Attrition. See *Crushing; Grinding*.
Augers. See *Extrusion*.
Automation, of Maytag Co., (5) 117*d*.

Ball mills. See *Mills*.
Barium, aluminosilicates, synthetic, hydrothermal chemistry, (8) 199*k*.
azide, gamma-irradiated, thermal decomposition, B (9) 244*d*.
$BaFeO_{3-x}$, oxygen stoichiometry, (8) 204*k*.
$BaFe_{12}O_{19}$-$BaFe_2O_4$ eutectic, unidirectional solidification, (7) 156*e*.
$BaFe_{12}O_{19}$, spherically shaped single crystal, ferromagnetic resonance, (5) 136*d*.
$BaGe[Ge_2O_5]$, crystal structure, and relation to benitoite, (3) 84*k*.
(Ba,Pb)TiO_3 crystals, homogeneity, (10) 270*g*.
(Ba,Sr)TiO_3, electron microscopic observations, (11) 294*j*.
Ba_2SiO_4, crystal structure, precise determination, (11) 297*f*.
BaU_2O_7, crystal structure, (8) 193*c*.
carbonate, anhydrous, heats and free energies of formation, (1) 19*a*.
kinetics and reaction with ZnO, (10) 271*b*.
process for production from barium sulfate, P (5) 133*c*.
reactivity in combating scumming in structural clay products, (10) 256*f*.
chloride, saturated vapor pressure, (7) 167*e*.
chloride, systems. See *Systems*.
fluoride, containing boron nitride, method of making optical elements from, P (7) 150*c*.
high pressure X-ray diffraction studies on, (3) 86*f*.
metaborate, protective coating composition, P (2) 35*f*.
oxide, ejection of electrons by noble gas ions, (3) 85*g*.
field emission studies on kinetics of, on tungsten, (3) 85*j*.
films, evaporated, absorption bands in, (3) 83*h*.
systems. See *Systems*.
silicate, systems. See *Systems*.
-strontium titanate, mixed crystals, net pattern, (8) 203*e*.
-strontium titanate ceramics, optical and microstructural variations with electric field, (7) 156*a*.
systems. See *Systems*.
titanate. See also *Dielectrics*.
angular energy dependence of 180° domain wall in, (11) 292*h*.
bismuth-doped single-crystal, dichroism, (7) 162*b*.
butterfly crystals, growth process, (9) 239*d*.
ceramic composition, P (8) 184*b*.
ceramic semiconductor, two sets of ESR of Gd^{3+} in, (8) 211*a*.
ceramics, firing, on bats of various materials, (2) 47*b*.
controlled particle size, P (3) 77*h*.
dielectrics, P (9) 230*g*.
diffuse streak diffraction pattern, (9) 238*d*.
effect of domains on movement of c domain walls, (8) 195*f*.
electron paramagnetic resonance in, near Curie temperature, (7) 163*g*.
electron spin resonance of Fe^{3+} in, (8) 196*c*.
electron spin resonance from Mn^{2+} in, (8) 196*c*.
equilibrium domain structure, (11) 295*g*.
far infrared reflectivity, (3) 85*i*.
halogen treatment of semiconductors, (9) 229*a*.
high purity, sintering, (9) 230*a*.
inhibition of grain growth, (10) 262*f*.
layer on electroluminescent lamp, P (2) 47*d*.

Barium, titanate (*continued*)
materials, P (11) 284*i*.
melts, ceramic crucible for, (9) 223*h*.
oxygen deficient, defect structure, (10) 270*g*.
reduction, chemical processes during, (2) 54*h*.
semiconducting, oxidation phenomena, (9) 241*i*.
single crystal, P (1) 11*h*.
single crystals, radiation damage, (3) 87*h*.
stabilized, P (3) 79*c*.
systems. See *Systems*.
tetragonal, anomalous dispersion and Evans's X-ray study, (7) 166*c*.
thermal conductivity, (9) 242*g*.
thin films, preparation and properties, (4) 100*b*.
vapor activation of oxide cathodes, (3) 75*g*.
Basalt, -eclogite transformation, effect of anorthite-forsterite and anorthite-enstatite reactions, (8) 191*f*.
magmas in lava flows, fractionation trends, (1) 18*j*.
melt, crystallization rate of main phases separated from, (3) 84*c*.
from northern part of Mid-Atlantic Ridge: II, the Atlantis collections near 30° N, (8) 191*c*.
use in heavy clay products, (8) 179*c*.
Batch, batching, new homogeneous vaporizer unit for rapid drying, (2) 52*h*.
weigh system, (5) 129*g*.
Bauxite, clay-, mullite refractories from, (2) 42*b*.
deposits, of Anniston, Fort Payne and Ashville areas, northeast Alabama, (8) 189*e*.
of Kalahandi district, Orissa, (8) 189*f*.
in northeastern Alabama, (8) 189*i*.
ores, high-iron Arkansas, processing, (8) 189*f*.
quartz-, mixes, mullite refractories from, (2) 42*b*.
red slurries, obtained by Bayer process, recovering iron, titanium, and aluminum from, P (4) 107*a*.
recovery of titanium and aluminum from, P (4) 107*d*.
reserves of world, (8) 189*f*.
Saurashtra, use in production of fused alumina, (11) 291*b*.
Base exchange. See *Cations; Ions*.
Bearings, carbon and carbon-graphite, with anti-friction surface, P (4) 98*d*.
Bending. See *Deformation*.
Beneficiation. See also *Classification; Classifiers; Crushing; Grinding; Filters; Flotation; Screens and sieves; Separation; Separators*.
chemical, of beryllite, P (4) 106*d*.
of Indian ilmenite, (11) 290*j*.
dry, of gypsum, (4) 105*j*.
Bentonites, from Bhadres and Hathiki-Dhani, Barmer district, X-ray investigation, (8) 189*j*.
chamotte-, bodies as filters for purifying Ni solutions, (3) 65*c*.
lime-, reaction products, X-ray studies, (7) 169*e*.
Beryl, activation by fluoride in cationic collector systems, (4) 105*j*.
Beryllia. See *Beryllium, oxide*.
Beryllium, air-borne, monitor for, (3) 80*c*.
beryllide coating for, P (4) 92*d*.
beryllite, chemical beneficiation method, P (4) 106*d*.
Be_2Sb_2, production and properties, (4) 109*j*.
Be_3N_2, decomposition reaction, (10) 272*j*.
BeS molecule, electronic spectrum, (1) 18*d*.
bodies, sintered, inhibition of grain growth, P (1) 7*h*.
catalytic chlorination, from ore, P (5) 124*e*.
compounds, thermodynamic and physical properties: V, heat of formation and entropy of beryllium(I) chloride(*g*); heat of formation of beryllium nitride, (8) 210*d*.
interaction with molybdenum disilicide, (3) 86*h*.
metal, protective coating for, P (4) 92*e*.
method of shaping, P (5) 124*e*.
nitride (Be_3N_2), decomposition reaction, vapor pressure, enthalpy, evaporation coefficient and enthalpy of activation, (10) 272*j*.
oxide, adsorption of CO_2 and H_2O, (7) 161*j*.
·Al_2O_3 and BeO·$3Al_2O_3$, relative enthalpy from 273° to 1173°K and thermodynamic properties from 273° to 2150°K, (11) 300*b*, *c*.
·$3Al_2O_3$, heat capacity and thermodynamic properties from 15° to 390°K, (8) 199*h*.
coating with, P (3) 65*c*.
cubic modification, (8) 194*e*.
diffusion and creep, (8) 194*f*.
inversion twin, prototype in, (11) 297*j*.
ionic conductivity, (2) 55*e*.
neutron-irradiated, contribution of helium bubbles to expansion, (8) 192*g*.
polycrystalline, cation self-diffusion and electrical conductivity, (5) 134*j*.
polycrystalline, creep-electrical conductivity correlations, (5) 134*h*.
polycrystalline, dislocation etch pits in, (4) 107*i*.
polycrystalline, high-temperature creep and dislocation etch pits, (7) 164*e*.
porous ceramics, properties of, (4) 97*e*.
powders, calcination, (5) 134*d*.
sinterable, preparation through decomposition of beryllium hydroxide, (1) 27*e*.
sintered, gaseous flow through, (4) 96*j*.
sintered, ultrasonic study of cracks and pores distribution in, (2) 59*h*.
sintering: I, influence of origin and thermal treatments on sintering behavior of beryllia powders; II, hot-pressing of beryllia powders of different origin and thermal treatment, (10) 258*f*,*g*.

Beryllium, oxide (*continued*)
systems. See *Systems.*
ware, vacuum fired, P (4) 99*e.*
self-diffusion in polycrystalline beryllium oxide, (9) 242*e.*
systems. See *Systems.*
Binders, caustic burned magnesite properties, in hardened magnesium oxychloride cement, (11) 275*g.*
composition, phenolic resole-bone glue-urea-diluent extender, for bonded mat, P (9) 221*j.*
for refractories, P (8) 182*d.*
dissolution mechanism, (7) 165*i*
glass fiber, P (9) 220*c.*
glucose and calcium compound, for mold or core composition in metal casting, P (2) 44*f.*
high temperature coke oven coal tar pitch, in carbon refractories and compacts manufacture, (2) 41*g.*
metallic, process of infiltrating diamond particles with, (3) 63*f.*
monomineral, formation of new phase seeds in hardening of, (10) 248*g.*
organic ceramic for body, P (2) 46*e.*
pitch, effect on physical properties of graphitized carbons, (4) 107*f.*
refractory, and molds made therefrom, P (7) 154*c.*
Biotite. See *Mica.*
Birefringence. See *Refraction.*
Bismuth, $BiFeO_3$, single-phase polycrystalline, preparation, (9) 241*g.*
germanium oxide $Bi_{12}GeO_{20}$, piezoelectric, growth and properties, (9) 239*e.*
oxide, systems. See *Systems.*
selenites, (9) 242*c.*
systems. See *Systems.*
telluride, etching, P (11) 285*j.*
telluride, systems. See *Systems.*
Bleaching, mineral, process, P (4) 106*g.*
Blending. See *Mixing.*
Blending apparatus. See *Mixers.*
Bloating, of clay and bloated products, (3) 70*c.*
Bodies, ceramic. See also *Dielectrics.*
and articles made therefrom, P (7) 156*j.*
lime-silica, for storing gas, P (11) 284*a.*
manufacture, suitable for piezoelectric uses, P (1) 11*b.*
manufacturing process for rods or tubes, P (11) 288*e.*
"memory" of, (4) 99*j.*
porcelain-type, dense, with high thermal shock resistance and high mechanical strength and manufacture, P (11) 283*i.*
porous, and composite members, and method of making, P (2) 46*f.*
semivitreous, of powdered glass and Li mineral, P (8) 178*b.*
Bonding. See also *Seals and sealing.*
beryllium oxide to graphite, P (4) 98*e.*
bodies of multifilament strands, P (8) 177*h.*
ceramic coatings with metals, (3) 65*a.*
ceramic and metal materials by flame spraying, P (9) 217*e.*
ceramic part to metallic part, P (5) 127*a.*
contacts, for gold-impregnated semiconductor rods, P (4) 100*g.*
direct, degree in brick of magnesia and chrome ore, P (9) 225*d.*
glass, P (1) 3*b.*
to glass, adhesives for, P (11) 278*b.*
and plastic materials, organic siloxanes and silicon groups as agents, (9) 216*e.*
hydrogen, infrared studies of, interaction between kaolinite surfaces and intercalated potassium acetate, hydrazine, formamide and urea, (1) 20*a.*
in lead monoxide, yellow form, (8) 191*h.*
in Pb_3O_4, (8) 191*g.*
materials of different thermal expansion coefficient, for making assemblies, P (5) 128*c.*
metal cladding to cermet body, P (3) 71*e.*
metal to ceramic, chemically, P (4) 101*c.*
metals to ceramic materials, P (2) 35*i.*
metals with nonmetals, for producing cermets, (5) 122*e.*
metal sheets, P (9) 217*a.*
method, P (4) 101*b.*
phosphate, of magnesia refractories, (1) 7*f.*
of zirconia, (4) 97*a.*
process, P (4) 100*g.*
in red PbO, (8) 191*h.*
semiconductor devices to substrates, P (8) 184*c.*
sintered refractory carbide body to metalliferous surface, P (1) 7*i.*
telluride-containing thermoelectric modules, P (4) 100*h.*
thixotropic nonflowing adhesive, compositions, and methods of using for bonding ceramic tiles to substrates, P (7) 155*e.*
voltage-pressure, P (8) 187*a.*
Bonds, direct, between chrome spinel and periclase, mechanism of formation, (8) 180*c.*
metal-metal, screening in equiatomic oxides and carbides of transition metals with NaCl structure, (3) 87*j.*
polyvinyl chloride resin glass, with secondary aminoalkyl silane primer, P (8) 178*e.*
promoting components in fiber reinforced metals, P (2) 44*a.*
SO_2, effect of pozzolanic admixtures, (4) 90*j.*
Borates, calcining and classifying, P (7) 160*j.*
Boric acid, and alkali sulfate, separately crystallizing from aqueous solution by evaporation at different temperatures, P (11) 292*e.*
for electroluminescent lamp, used with zinc sulfide layer, P (2) 47*e.*
in photoluminescent composition, P (3) 79*i.*
Boric oxide, for electroluminescent lamp, with zinc sulfide layer, P (2) 47*e.*
Boric oxide (*continued*)
fused, viscosity, (10) 254*c.*
liquids, effect of fluoride and oxide ions on structure, with electronic spectrum of Co^{2+} as tracer, (7) 168*c.*
Borides, refractory hard metal, process for production, P (9) 227*d.*
TiB_2, W_2B_5, ZrB_2, HfB_2, hot hardness, to 1900°C, (7) 164*f.*
Boron, anomalous diffusion, into silicon grain boundary, (11) 292*h.*
arsenides, orthorhombic, and preparation, P (11) 282*b.*
B_2O_3, molten, viscosity, (1) 4*j.*
carbide-B_4Si hard alloys, pseudobinary, conditions and properties, (10) 256*j.*
decomposition pressure, (8) 194*g.*
high temperature vaporization properties, (8) 199*g.*
method for producing, P (11) 282*f.*
mortar, use in preparation of analysis samples, (8) 187*g.*
process of preparing from boron halide and hydrocarbon, P (10) 260*i.*
production, P (9) 227*f.*
chemistry, new results, (1) 23*i.*
coordination, effect on reactivity of glasses with lead oxide, (10) 251*b.*
crystals, vapor growth, (2) 59*a.*
fibers, and -fiber-reinforced plastic composites, (5) 122*g.*
tungsten borides in, (9) 225*f.*
filaments, surface finishes, (1) 2*j.*
fluoride, heat and entropy of formation, (8) 199*i.*
fluorination, kinetics of reactions, (8) 201*j.*
heat of sublimation, (8) 194*g;* 199*g.*
litharge glycerine cement as radiation shielding material, (2) 34*h.*
monoxide, and diborane, high-temperature routes to, (8) 199*f.*
nitride, coatings, process for preparing, P (9) 226*h.*
cubic, crystal surfaces, (11) 293*f.*
evaporation source for aluminum, (1) 12*d.*
fibers, (10) 256*j.*
high cost materials with promising future, (9) 223*f.*
member, used in coaxial termination to enhance radiation, P (4) 100*i.*
precipitation from ferrous melts, (10) 258*i.*
purification, continuous process, P (8) 180*j.*
pyrolitic, (4) 97*j.*
pyrolytic, method of forming laminates, P (7) 153*i.*
for semiconductor encapsulating and reinforcing materials, P (2) 49*g.*
ultrafine, production by arc vaporization, (3) 71*d.*
parameters of reaction diffusion in refractory transition metals, (1) 24*i.*
phosphide, crystalline, method of producing, P (11) 286*g.*
fine-crystalline, apparatus for production, P (1) 7*b.*
thermodynamics, (7) 169*d.*
solid solution in graphite, (4) 109*i.*
systems. See *Systems.*
trioxide, heat capacity, change during glass transformation, (8) 175*b.*
Brazing. See *Soldering.*
Brick. See also *Masonry; Refractories; Structural materials.* P (2) 40*i.*
bloated building, iron cordierite in core structure, (4) 96*a.*
and brickwork, moisture movement, (9) 222*j.*
building, manufacture, P (10) 256*g.*
manufacture with transversely directed perforations or recesses, P (1) 6*i.*
burned clay, for pozzolan surkhi, (2) 40*h.*
clays, Hungarian, mineralogical composition and ceramic characteristics, (3) 70*g.*
compounding with feldspathic waste, (1) 6*i.*
direct-bonded, developments, (2) 41*d.*
drying and firing, installation for, P (5) 132*f.*
durability, testing· VIII, frost dilatometry, (5) 121*j.*
face, semidry pressed, (3) 70*d.*
fly-ash, status, (9) 223*c.*
from fly-ash, (8) 179*f.*
handmade, the automated way, (9) 222*h.*
machines, review of U.S., (11) 279*j.*
manganese colored, mortar staining from, (1) 6*h.*
manufacturing methods, development, (8) 179*f.*
mix, for 8 x 8 x 16 in. block at Higgins, (4) 95*j.*
model, nondestructive testing by sonic and X-ray methods, (3) 80*j.*
from murram or red soils of Hyderabad, (8) 179*d.*
packaged, for lower cost, (9) 222*h.*
new system for handling by strapping with steel bands, (11) 280*a.*
packages, transportable, elastic protective corner and tensioning strips for, P (10) 256*f.*
paving, with cement base, (3) 70*g.*
raw materials, (1) 15*i.*
rapid drying and firing, (2) 52*e.*
semidry preparation and hot steam forming with fast drying, (8) 179*g.*
shapes, special, manufacture, (9) 222*h.*
shipping damage, help reduce, (9) 222*h.*
structural calcium silicate, production at Harford, (4) 95*j.*
surface coatings, improved, (1) 6*j.*
thermal conductivity, methods of measuring at room temperature, (2) 50*f.*
wall panel, and method of making, P (10) 256*e.*
work, load-bearing, (9) 223*b.*
Brick industry. See also *Structural clay products industry.*
Burns Brick, new high in automation, (9) 223*b.*
Chattahoochee Brick, smooth material flow keeps up with increased production at, (9) 223*b.*
glazing and engobing, (3) 70*c.*
Japan, studies new methods, (4) 98*b.*
Porter plant, streamlined production flow, (9) 223*c.*
profit concept in plant design, (1) 6*j.*
utilizing for industrializing construction, (3) 70*d.*
Brickmaking apparatus and equipment. See also *Dryers; Kilns; Materials handling; Presses.*
and process, P (2) 40*g.*
setting mechanically—a reality, (1) 6*h.*
setters, automatic, (1) 256*d.*
for transferring fresh clay moldings from cutter to support, P (11) 280*c.*
Bromides, slip plane, (8) 207*e.*
Bromine, fluorides, method of separating UF_6 from, P (9) 226*b.*
Bronze, alkali metal tungsten, catalytic activities, (1) 27*f.*
blue potassium molybdenum, $K_{0.23}MoO_3$, crystal structure, (9) 237*f.*
cubic rare earth tungsten, single-crystal preparation, (1) 28*c.*
rare earth, thorium, and uranium tungsten, electrical resistivity, (9) 229*g.*
sodium molybdenum, crystal structure, (9) 237*h.*
Brucite, thermal decomposition: I, electron and optical microscope studies, (1) 29*j;* II, kinetics in vacuum, (2) 58*a.*
Bubbles, air, effect of introducing, on rheology of aqueous kaolin suspensions, (7) 154*i.*
compositions, in commercial glasses, (8) 176*a.*
in glazes, (8) 182*g.*
open, in glass ribbon, nature and cause of formation, (8) 175*e.*
structure, of ground coat enameled sheet steels, (11) 275*j.*
for measurement of enamel, (8) 174*h.*
"vacuum," in glass spheres, (8) 176*b.*
Building materials. See also *Aggregates; Brick; Enamels; Insulation, thermal; Structural clay products; Structural materials.*
blocks, manufacture, P (5) 122*b.*
and use in wall, P (1) 6*i.*
ceramic panels and components, P (2) 46*c.*
compositions for manufacture of water-repellent products, P (8) 174*a.*
control of changes in appearance caused by climate, exposure and time, B (11) 303*i.*
fibrous ceramic, (1) 12*e.*
nondestructive testing, (2) 50*h.*
panel, fibrous acoustical, with impregnant in rear body portion, P (10) 255*b.*
hydraulic cement, with low density core and fiber reinforced high density surface layers, P (2) 34*j.*
slabs, bricks and blocks, P (4) 96*c.*
structural elements having a ceramic tile facing, P (1) 6*j.*
testing, principles and use of GAMMAMAT type γ-radiography apparatus, (2) 51*a.*
Bulbs. See *Glass.*
Burners. See also *Flames.*
apparatus, P (9) 234*h.*
control system, P (9) 234*i.*
deep combustion radiant elements, P (3) 72*g.*
element, infrared radiant heating, P (7) 153*b.*
flameless radiant, P (10) 268*g.*
fuel vaporizing, arrangements, P (2) 52*h.*
furnace, supplying secondary air to, P (11) 290*h.*
gas, device for igniting and checking flame of, P (9) 234*j.*
gas, method and device for regulating relative amount of burning components for, P (10) 268*h.*
gas-fired radiant, P (4) 105*e.*
for gaseous fuel, P (3) 82*b,c.*
high output, in steam boilers, refractories and ramming bodies for, (5) 123*j.*
industrial, P (8) 189*a.*
industrial gas, P(1) 14*j;* P (2) 53*c.*
liquid fuel, P (1) 15*a.*
propane, used in ceramic kilns, and principal applications, (5) 132*g.*
radiant, P (5) 132*g.*
utilizing flame quenching phenomena, P (1) 15*c.*
radiant tubes for, P (1) 15*c.*
ultra-high-temperature, P (5) 132*h.*
vaporizing, for liquid fuels, P (1) 15*a.*
Burning. See also *Calcination; Combustion; Firing; Lime.*
of powdered fuels, in industrial processes, P (5) 117*b.*
Burnishing. See *Polishing.*

Cadmium, arsenide, nonstoichiometric vaporization, mass spectrometric study, (8) 202*a.*
CdS_xSe_{1-x} lasers, efficient visible, by electron-beam excitation, (8) 196*a.*
-diffused GaAs, correlation of electrical measurements with chemical analysis, (3) 84*g.*
difluoride, heat of formation, (8) 198*b.*
fluoride, rare-earth ions, electroluminescence, (5) 135*f.*
-germanium sulfide, nucleation and growth of single crystals by chemical transport, (1) 24*f.*
halophosphate phosphors, (4) 100*c.*
oxide, systems. See *Systems.*
oxides and sulfates, solid-phase interactions, (1) 28*h.*
pigments, (2) 45*j.*

Cadmium (*continued*)
selenide, crystals, behavior under laser light excitation, (10) 270*d*.
laser, ultrathin single-mode, volume excitation, (9) 243*e*.
thin film transistors, (9) 228*i*.
selenide and sulfide, electron-beam pumped lasers, (5) 135*h*.
sulfide, crystals, dark conductive, current oscillations and high field domains in, (3) 75*i*.
cyclotron resonance, (7) 162*a*.
electron beam pumped lasers, high power and efficiency, (9) 229*c*.
evaporated metal-polycrystalline interfaces, barriers, (7) 162*c*.
films, high-mobility, deposited under ultrahigh vacuum equilibrium conditions, (10) 262*d*.
green-edge emission at 4.2° and 77°K, evidence of distant-pair recombination process, (9) 239*c*.
influence on decomposition rate of zinc sulfate at 600°C, (8) 200*e*.
insulating, contact barriers on, (1) 9*h*.
Nernst coefficient, positive phonon drag effect in, (9) 241*e*.
numerical data for acoustic surface waves in, (8) 203*h*.
photoconductivity, in blocking electrodes, (5) 137*h*.
p-type, high-resistivity, (9) 239*g*.
Seebeck effect, (9) 242*b*.
semiconducting, in current oscillatory mode at 77°K, light emission from, (8) 201*c*.
thin films, chemically sprayed, effects of chemisorbed oxygen on electrical properties, (10) 262*h*.
thin films, nonstoichiometry, (1) 23*j*.
ultrasonic surface-wave amplification, (5) 139*b*.
systems. See *Systems*.
telluride, crystals, neutron-activated, peculiarities of gamma-ray spectra, (5) 137*e*.
films, thin polycrystalline, sublimation in vacuo, (11) 301*a*.
-metal, thin (In, Cu, Au) films, physical properties, (5) 126*i*.
thermodynamic properties of, (3) 77*b*.
Calcia. See *Calcium, oxide*.
Calcination. See also *Firing*.
of cement. See *Cement, burning*.
continuous, of gypsum, P (5) 116*b,e*.
continuous grain, vertical kiln for, P (1) 15*a*.
of $MgCO_3$, in sintering study, (1) 22*a*.
of raw silicate material, P (2) 35*a*.
of two BeO powders, (5) 134*d*.
of minerals, portable apparatus, P (5) 133*c*.
Calciner, oscillating plate, (4) 105*f*.
Calcining, borate, P (7) 160*j*.
facility, for flint clay, (4) 105*j*.
of gypsum, in two stages, apparatus and method, P (7) 147*e*.
inorganic hydrates, method and apparatus, P (10) 268*g*.
method and limekiln for, P (2) 34*k*.
rate meter, for rotary kiln control, P (7) 160*e*.
Calcite, crystal growth, implications, (2) 55*c*.
method of preparing, and product, P (8) 190*c*.
Calcium, aluminates, hydrated, pH value, (3) 64*d*.
aluminates, single crystalline, (11) 300*i*.
aluminum, silicate, systems. See *Systems*.
CaF_2 single crystals, doped with oxygen ions, dielectric loss, (11) 293*a*.
CaF_2 type single crystals, samarium doped, chemical and optical studies, (9) 237*h*.
$Ca(OH)_2$ effect on flow properties of montmorillonite-water systems, (2) 45*j*.
$2CaO \cdot 3B_2O_3$ hydrates, preparation, P (11) 291*a*.
$3CaO \cdot Al_2O_3$, hydration character, influence of $CaSO_4 \cdot 2H_2O$, (11) 275*a*.
$3CaO \cdot SiO_2$ hydration, influence of silica, (1) 19*i*.
$CaSO_4 \cdot 2H_2O$, influence on hydration character of $3CaO \cdot Al_2O_3$, (11) 275*a*.
$CaYb_2O_4$, decomposition kinetics, (8) 194*f*.
carbide, relation between the graphitization of carbon and its reactivity in formation, (1) 28*f*.
carbide III, crystal structure, (3) 84*j*.
carbonate, crystalline, of vaterite type, process for production, P (9) 236*i*.
finely dispersed, process for production, P (9) 236*i*.
finely dispersed, production of, P (2) 54*c*.
process for modifying, P (9) 236*g*.
production from alkaline earth carbonates and oxides containing impurities, P (11) 275*i*.
chloride, in activation of blast furnace slags, (4) 90*c*.
-calcium oxide fused salt electrolytic system, solubilities, metal contents and freezing points, (11) 292*i*.
discoloration from, in concrete flatwork, (1) 2*e*.
process for production, P (4) 107*e*.
saturated vapor pressure, (7) 167*e*.
chloride, systems. See *Systems*.
concentration vs. net ionized donor concentration in single-crystal $KTaO_3$, (5) 134*f*.
determination by atomic absorption spectroscopy, (1) 13*g*.
determination in calcareous materials and silicates, (5) 130*i*.
determination in iron ores and slags, (5) 130*h*.
diffusion, in magnesium oxide, (8) 194*d*.
disilicide, polymorph, and method of preparation, P (8) 190*d*.
flame-photometric determination of, effect of iron, (2) 51*b*
fluoride, with divalent thulium double resonance from, (8) 196*c*.

Calcium, fluoride (*continued*)
formation of dislocation clusters during sintering, (8) 198*c*.
solid and liquid phase miscibility, (11) 301*b*.
systems. See *Systems*.
germanates, heats of formation, (8) 199*a*.
hexaluminate articles, P (7) 153*b*.
hydrosilicates, effect of electric current on synthesis at 20°, 40° and 60°C, (8) 174*c*.
hydroxide, thermal decomposition kinetics, (1) 21*g*.
iodide scintillator, transparent tin-activated, for scintillation detector, P (4) 102*b*.
metal, solid and liquid phase miscibility, (11) 301*b*.
molybdites, tungstites, molybdates, and tungstates, mass-spectrometric determination of stability, (1) 22*e*.
orthophosphate, dibasic, electronic paramagnetic resonance study of thermal decomposition of, (11) 295*b*.
orthosilicate, systems. See *Systems*.
orthovanadate, (3) 87*c*.
orthovanadate $Ca_3(VO_4)_2$, new laser host crystal, (9) 228*j*.
oxide. See also *Lime*.
activation and sintering behavior, effect of copper X-irradiation on surface area produced by thermal decomposition, B (9) 244*f*.
$\cdot x Al_2O_3 \cdot y SiO_2$, for various ceramic applications, research on eutectics and vitreous compounds of, (5) 125*j*.
causes volume expansion of hardened cement paste, discussion, (11) 274*h*.
dead-burned, causes volume expansion of hardened cement paste, (2) 34*f*.
and MgO, mutual solubility in calcined dolomite, (8) 202*j*.
-MgO-SiO_2 mixture, effect on sintering of Al_2O_3-Fe-Fe_2O_3, (11) 280*d*.
purified, process for manufacture, P (9) 236*f*.
reaction with magnesiochromite, (5) 123*i*.
tri-, oxide, systems. See *Systems*.
Yb_2O_3 crystalline solutions, defect characterization in and precipitation from, (3) 84*g*.
silicate, fillers, finely dispersed, process for production, P (8) 190*f*.
fillers, production, P (5) 133*e*.
high temperature, producing, P (8) 190*g*.
in early stage of hydration, (5) 116*b*.
polymorphism, (1) 24*a*.
sulfate dihydrate, crystals, ultrafine, apparatus for making, P (5) 116*c*.
dissociation and solubility, calcium electrode method for measuring, (10) 266*i*.
sulfate hemihydrate, alpha, process for preparing from synthetic gypsums, P (11) 275*h*.
production, P (7) 147*d*.
sulfides, effect on surface tension and density of CaO-MgO-SiO_2 melts, (4) 90*i*.
sulfoaluminate hydrates, expansion characteristics, (5) 136*b*.
systems. See *Systems*.
tetra-, aluminoferrite, capillary contraction forces, (4) 90*c*.
tri-, aluminate, capillary contraction forces, (4) 90*c*.
aluminate, coordination of aluminum ions in, (3) 64*b*.
aluminate, effect of sodium sulfite on hydration of, (4) 90*e*.
aluminate and related phases in portland cement, (2) 34*d*.
silicate, effect of sodium sulfite on hydration of, (4) 90*e*.
silicate pastes, hardened, reversible and irreversible drying shrinkage, (10) 248*c*.
ytterbate, $CaYb_2O_4$, orthorhombic calcium ferrite isomorph, (10) 270*f*.
Calorimeter, conduction, studies of portland cement heat of hydration, (7) 146*g*.
small-size, for determining specific heat of potassium chloride at low temperatures, (9) 234*a*.
Calorimetry, of combustions and related reactions —inorganic reactions, (8) 192*c*.
determination of plutonium in plutonium oxide, (8) 187*g*.
fluorine bomb: VI, enthalpy of formation of uranium hexafluoride; VII, heat of formation of cadmium difluoride; VIII, enthalpy of formation of zinc difluoride; IX, enthalpy of formation of magnesium difluoride, (8) 198*a*.
for indicating material stream characteristics of glass, P (9) 221*f*.
investigations of molten salts, (8) 192*a*.
low temperature, thermal contact with powdered samples for, (1) 14*g*.
micro-, in laminar silicates: I, hydration energy of montmorillonite, (4) 108*i*.
of phase and ordering reactions, progress, (8) 205*g*.
recent developments: I, introductory survey, (11) 289*d*.
of several garnets at low temperatures, (8) 192*a*.
Capacitors, adjustable, with moving dielectric, P (2) 47*f*.
ceramic, P (10) 263*c*.
elements, apparatus for manufacture, P (7) 156*f*.
with dielectric film having phosphorus-containing component, P (5) 127*b*.
electrical, and methods of forming, P (2) 47*d*.
method of making, P (3) 79*d*; P (4) 101*h*; P (9) 231*e*.
with boron nitride dielectric, P (1) 10*b*.
formed from thin films, P (2) 47*c*.
manufacture, P (7) 149*b*.
electrolytic, comprising glass-to-metal and resilient pressure seal combination, P (9) 230*f*.

Capacitors, electrolytic (*continued*)
with dielectric film formed on ceramic material, P (10) 263*g*.
electronic, manufacturing processes, P (5) 127*j*.
formed by coating lead and alkaline earth titanates and niobates, P (10) 264*h*.
glass, (1) 3*j*.
having a chrome oxide layer on the electrodes, P (1) 10*g*.
high temperature, P (10) 264*c*.
high voltage, assembly, P (9) 231*b*.
paraelectric ceramic for, P (10) 265*d*.
with MnO electrolyte derived from permanganic acid, and method, P (8) 185*b*.
method of making, with multilayered ferroelectric dielectric, P (5) 128*a*
mica paper, method of making, P (10) 264*b*.
microelectronic material, and method of fabrication, P (3) 79*h*.
miniature, process for fabricating, P (1) 11*c*.
nonelectrolytic tantalum, method of making and attaching, P (3) 79*a*.
process, P (1) 10*i*.
semiconductive, and method of making, P (4) 102*c*.
silicon oxide thin film, deposition by glow discharge techniques, (9) 229*i*.
slug-type titanium wet electrolytic, P (9) 232*d*.
solid electrolytic, method of manufacturing, P (8) 185*j*.
from stabilized barium titanate, P (3) 79*c*.
tantalum, glass-bonded mica encapsulated, P (4) 101*h*.
thin film, method of fabricating, P (10) 264*h*.
use of manganese oxide counter-electrodes, (5) 126*i*.
variable disk, P (11) 288*b*.
Carbides. See also specific types.
abrasive, apparatus for production, P (4) 105*h*.
cemented, advances in tooling, (3) 63*f*.
tools, applications for, (2) 33*g*.
classification problem, (2) 42*i*.
coating on tools, (2) 33*i*.
complex, superconducting behavior, (2) 56*h*.
-containing materials, method for producing, P (5) 115*f*.
dies, steel bonded, with machinability, (2) 33*g*.
finely dispersed, and process for production, P (11) 281*c*.
of fissionable and fertile materials, process for making, P (2) 45*b*.
grinding, cost reduction, (1) 1*g*.
$(Fe,Mn)_3C$ and $(Fe,Mn)_4C$, structural studies, (7) 168*a*.
isomorphous, thermoemission characteristics of alloys of, (8) 210*b*.
metal, of fixed composition and homogeneity domain of groups IV and V to 2500°C, physical and electrical properties of, (3) 87*d*.
mono-, from transition metals of subgroups IV to VI, thermodynamic stability, (8) 210*h*.
niobium and zirconium, variation of molar mining volumes, (10) 272*a*.
NbC, TiC, TaC_{1-x}, HfC_{1+x}, $(Ta_{0.8}Hf_{0.2})C_{1+x}$, W_2C, and $(W_{0.8}Cr_{0.14}Re_{0.16}Ta_{0.07})_2C$, hot hardness, to 1900°C, (7) 164*f*.
nuclear fuel, fissile and/or fertile, furnace for manufacture of, P (4) 98*h*.
process for preparation, P (10) 260*h*.
oxy-, from uranium and plutonium monoxide-type compounds, (7) 166*b*.
phase and structural properties, effect of screening, (11) 294*g*.
sintered, P (9) 227*f*.
tools of future, (2) 33*j*.
of transition metals, of groups IV and V with NaCl structure, concentration ranges of homogeneity, (3) 84*d*.
with NaCl structure, screening of metal-metal bonds in, (3) 87*j*.
WC-Co and TiC-WC-Co, composition and structure influence on maximum stress of alloys, (1) 19*e*.
Carbon. See also *Graphite*.
activity, in Fe-C-V, influence of vanadium at 1000°C, (7) 164*h*.
articles, method of extruding, P (9) 226*c*.
blocks, testing in iron gutter of blast furnace, (7) 152*d*.
bodies, baked and graphitized, apparatus and process for continuously making, P (2) 43*d*.
method for cold molding pitch bonded shaped P (3) 72*j*.
method of forming, P (2) 44*j*.
molded, P (2) 44*e*.
shaped, method of making, P (2) 44*b*.
bond state, in carbides of transition metals, (4) 110*e*.
carbonaceous bodies, process for densification, P (9) 226*g*.
carbonaceous thread, method for continuous graphitization, P (8) 190*h*.
crystals, mechanism of dimensional changes under fast neutron irradiation, (8) 202*b*.
diffusion, in tantalum monocarbide, (9) 238*c*.
dimensional change, during graphitization, (3) 71*g*.
dioxide, adsorption on beryllium oxide, (7) 161*j*.
in glasses, solubilities at pressures to 10 kbars, (1) 4*d*.
interaction with carbon at high temperatures, (8) 200*i*.
oxidation of aluminum, in presence of cryolitic electrolyte, (3) 87*f*.
electrically conducting, production, P (7) 153*i*.
fiber, flexible, method for making, P (2) 44*b*.
fiber-reinforced, (1) 7*d*.
ofam, P (5) 124*c*.

Carbon (*continued*)
-graphite as bearings, P (4) 98*d*.
graphitic, study of oxidation kinetics in liquid environment, (4) 110*f*.
graphitic structure, oriented, P (2) 44*i*.
graphitization, relation between, and its reactivity in formation of calcium carbide, (1) 28*f*.
graphitized, effect of binder pitch on physical properties, (4) 107*f*.
effect of oxidation on surface heterogeneity, (2) 41*e*.
-impregnated refractive magnesia bodies and method of making, P (2) 43*f*.
interaction with carbon dioxide at high temperatures, (8) 200*i*.
isotope effect in pyrolytic decomposition of manganous and zinc oxalate, (8) 192*c,d*.
layer, depositing, equipment and process for, P (5) 124*f*.
mechanical damping in, at low temperature, (2) 55*f*.
mobility activation energy, in metallic niobium and its carbides, (5) 137*i*.
monoxide, resistance of refractories to, (7) 151*f*.
parameters of reaction diffusion in refractory transition metals, (1) 24*i*.
pickup, in oxide formed on uranium in carbon dioxide at 650°C, (11) 293*c*.
pyrolytic, coated particles, for nuclear applications, P (4) 99*e*.
reactions, with carbon dioxide activated by low voltage electrons, (2) 55*i*.
strained, diameter of elementary atomic layers in, between 1000° and 2000°C, (2) 54*i*.
weight loss and dimensional change during baking, (3) 72*c*.
vitreous, neutron irradiation effects of electrical properties in, (10) 271*f*.
and pyrolytic graphite, reorientation effects, (10) 271*g*.
-zirconium reaction, kinetics above 2000°C, (7) 164*j*.

Carbonaceous materials, low permeability, method for manufacture, P (1) 7*j*.

Carbonates, alkali, molten, trace-ion diffusion, (11) 302*g*.
alkaline earth metal, spheroidal, process for producing, P (5) 133*e*.
deposition in Manlius formation of New York, (8) 192*e*.
negative replication for electron microscopy study of, (10) 267*h*.
sediments, experimental compaction effects, (7) 163*d*.
kinetics and diagenesis, (8) 201*f*.

Carbonation, de-, of limestone, mechanism, (5) 116*h*.

Casting. See also *Molding; Molds; Refractories; Slip casting.*
continuous, for making bars of uranium compound, particularly uranium carbide, P (11) 282*c*.
method with degassed glasslike blanket, P (8) 180*i*.
and plant control, B (1) 30*c*.
precision, method of preparing investment mold for, P (4) 98*f*.
process for production of lost models in, P (8) 182*b*.
pressure, of refractory ceramics, (1) 7*g*.
tungsten slip, method, P (9) 227*h*.

Castings, gypsum, and method of producing, P (5) 116*g*.
rock, causes of chemical heterogeneities in melts for, (5) 122*g*.
industry, development, (5) 122*j*.

Cast iron. See *Enameling metals; Iron.*

Cathodoluminescence. See *Luminescence.*

Catalysts, antimony oxide-tin oxide, composition, preparation and product thereof, P (7) 153*f*.
attrition resistant solid, P (11) 281*h*.
cracking, and preparation, P (10) 260*j*.
crystallization, used in production of glass ceramics, (10) 252*c*.
electronic-acidic, investigations of dual function: III, reactivity and poisoning of nickel sulfide on silica alumina; IV, isomerization reactivity and surface property of catalyst platinum on silica alumina, (1) 15*f*.
multilayer copper oxide, for treatment of exhaust gases, preparation, P (11) 291*c*.
oxidation, for hydrocarbon combustion exhaust gases, P (2) 44*j*.
production, for hydration of olefins to alcohols, P (7) 161*b*.
silicon carbide supported vanadium-containing oxidation, process for making, P (2) 45*e*.

Cathodes, double layer oxide, with reducing agent, P (10) 263*d*.
heated glass, in electrostatic beam separators, (1) 13*f*.
oxide, barium vapor activation, (3) 75*g*.
oxide-coated, measurement of concentration and mobility of negative oxygen ions in, and variation of capacitance with temperature, (3) 86*f*.
photo-, analysis of gases liberated during tip-off of commercially available glasses, (2) 36*a*.
sputtering, method and apparatus using cylindrical cathode, P (8) 185*a*.
sputtering apparatus, including plasma-confining chamber, P (3) 77*j*.
tungsten dispenser, impregnating, P (8) 185*e*.

Cathode-ray tubes. See *Tubes.*

Cations, concentration measurement in molten salts using glass membrane electrodes, (3) 66*h*.
distribution, in $CuMn_2O_4$, (9) 237*g*.
in $ZnFe_2O_4$ precipitated from aqueous solution, (5) 126*d*.

Cations (*continued*)
exchange, for adsorption of elements from HNO_3-HF and H_2SO_4-HF solutions, (8) 191*a*.
in montmorillonite and illite adsorption of amino acids and peptides, (7) 161*f*.
in zeolites, (8) 206*f*.
exchange capacity, determination by methylene blue adsorption, (7) 159*b*.
of kaolinite, surface area and crystallinity as factors in, (11) 292*j*.
self-diffusion, in polycrystalline beryllium oxide, (5) 134*j*.
trace element, interaction with montmorillonite clay: III, fixation and release of cations from respective clay salts, (9) 239*j*.
interaction with montmorillonite clay, dissociation of Co^{2+}, Ni^{2+}, and Mn^{2+} from respective clays at different degrees of supersaturation, (9) 240*a*.

Cells, alumina reduction, and method for making refractory lining for, P (9) 225*j*.
electrochemical, with halogen fluoride electrolytes, (7) 163*c*.
fuel, for furnace control, (11) 290*b*.
galvanic, high temperature, method of making Al-Si-Mn-Li anode for, P (4) 92*c*; P (5) 117*j*.
paramagnetic oxygen analyzer measuring, P (1) 14*e*.
Peltier, for cooling semiconductor component with *pn* junction, P (1) 11*e*.
photosensitive, P (5) 128*e*.

Cements. See also *Concrete; Plasters; Refractories.* P (4) 91*c*.
additive, of fly ash, (10) 248*b*.
additives, P (5) 116*d*.
composed of ethanolamine salts, P (10) 249*a*.
to improve qualities, (9) 214*a*.
of metallurgical slags, (9) 214*a*.
alumina, pH value, (3) 64*d*.
aluminous, "ciment fondu," manufacture, (11) 274*i*.
analysis, of Na_2O and K_2O by flame photometry, (5) 116*e*.
volumetric determination of potassium, (1) 2*b*.
asbestos-, products, (2) 34*h*.
products, analysis, (11) 274*g*.
ash-portland, strength as function of mineralogical composition of clinker, (9) 215*b*.
automatic titrator Holderbank system for $CaCO_3$ control, (11) 274*j*.
base, for paving brick, (3) 70*g*.
binding power, rapid determination by titration method, (4) 91*g*.
boron-litharge, as radiation shielding material, (7) 146*j*.
boron litharge glycerine, as radiation shielding material, (2) 34*h*.
burning, P (7) 147*e*.
effect on mineralogical and physical properties, (7) 146*b*.
methods and plants, P (8) 174*f*.
volatilization of Na_2O and K_2O during, (10) 249*c*.
calcium aluminate ferrite, P (8) 174*b*.
cast stone from Lithuania materials, (8) 173*j*.
cementing compositions, P (3) 64*d*.
chemistry, (4) 90*g*.
clinker, activity, increasing, (9) 214*e*.
apparatus for cooling, P (1) 2*c*.
behavior of alkalis in, (10) 247*j*.
burning, use of oxygen, (11) 275*c*.
composition, effect on hardening of heat-cured concretes, (11) 274*i*.
control by gamma radiation, (11) 274*i*.
cooling in recuperators of rotary kilns, (9) 214*b*.
device for removing from thermocouple probe, P (9) 215*g*.
dust, origin, (9) 215*c*.
fine grinding, intensification by surfactants, (9) 214*f*.
formation, kinetics of physicochemical processes, (9) 214*g*.
formation in highly siliceous charges, (9) 214*a*.
-formation process, effect of mineralizers, (9) 214*g*.
grinding, P (3) 64*e*.
hydration, formation of new compounds, (1) 2*a*.
limestone for formation, (10) 248*g*.
liquid phase, effect of Na_2SiF_6 on viscosity, (9) 214*j*.
method and apparatus for recovering content of alkali metal compounds from alkali-rich dust in production of, P (9) 215*i*.
method of producing from raw powder quicklime, P (7) 147*b*.
minerals, effect of sodium and potassium salts on formation, (10) 248*f*.
minerals, hydration, (5) 116*e*.
structural changes in fine grinding, (11) 275*b*.
clinkers and clinker mixtures, results of measuring grindability, (9) 215*i*.
complexometric determination of Fe, Al, Ca, and Mg in, (4) 90*h*.
composition, electrically conductive, of rubber latex, graphite, and cement, P (4) 91*g*.
for joint filling, P (1) 2*c*.
construction properties, improvement, (9) 214*d*.
dissolution, process for preventing, P (10) 249*c*.
expansive, and components, P (5) 116*f*.
made with portland cement, gypsum, and calcium aluminate cement, properties, (11) 275*h*.
firing, phosphogypsum as effective mineralizer, (9) 215*d*.
glossary of terms, (3) 64*c*.
grinding and cooling method, P (11) 275*e*.
hardening, theory, (11) 275*c*.

Cements (*continued*)
high-alumina, set, mineralogy, (9) 214*i*.
hydration, formation of new compounds, (1) 2*a*.
hydration hardening of, contraction and porosity formation, (1) 1*f*.
hydraulic, P (9) 215*h*.
cementitious mixtures, chemical admixture, P (2) 34*j*.
panel with low density core and fiber reinforced high density surface layers, P (2) 34*j*.
hydrophobization with fatty acid additives, (10) 248*j*.
inorganic plastic, and process for preparation, P (8) 174*b*.
kilns. See *Kilns.*
kinetics of hardening, study by electrochemical method, (4) 91*a*.
low-hydroscopic plasticized, for well casing, (10) 248*j*.
magnesia, with uniform volume change, and hydration, (10) 248*a*.
viscosity, method of increasing, P (11) 275*f*.
magnesium oxychloride, hardened, caustic burned magnesite properties as binder in, (11) 275*g*.
manufacture, P (9) 215*h*.
material, P (1) 2*c*.
materials, photometric titration of CaO, MgO, and Fe_2O_3 in, (9) 215*e*.
method for preparation, P (4) 91*e*.
method of producing from oil shale, P (4) 91*e*.
mills. See *Mills.*
mixture, hardening, P (5) 116*h*; 116*i*.
mortars. See *Mortars.*
nominal and actual content of hydraulically active materials in, (9) 215*b*.
paste, hardened, effect of shrinkage stress on creep, (5) 116*d*.
hardened, volume expansion due to dead-burned CaO, (2) 34*f*; discussion, (11) 274*h*.
influence on creep of lightweight aggregate concrete, discussion and reply, (11) 275*d*.
rheological characteristics, (4) 91*g*.
rheological studies, (2) 34*i*.
setting time, determining with copper-lead electrode, (9) 214*c*.
tensile strength, determination by centrifugal force, discussion, (2) 34*c*.
volume changes on setting and curing from 0 to 7 days, (3) 64*h*.
patching composition containing polyvinyl and epoxy resins with hydraulic cement, P (10) 249*b*.
phosphate, effect of heat, (10) 248*d*.
plasticizer, use of waste sulfite liquor, (9) 215*f*.
portland, analysis by atomic absorption, (10) 247*j*.
charges, firing at high temperatures (up to 2273°K), (9) 214*c*.
compositions, process for producing, P (10) 249*c*.
correlations in structural formation during hardening, (10) 248*a*.
fused, strength as function of composition, (10) 248*h*.
heat of hydration, (7) 146*g*.
new factor in abnormal setting, (4) 91*b*.
plaster content, (4) 91*b*.
production with high content of MgO, (10) 248*d*.
setting and hardening, effect of ZnO, (7) 146*d*.
spodumene accelerated, P (10) 249*d*.
tricalcium aluminate and related phases, (2) 34*d*.
portland clinker, hydration of, and its component minerals in presence of small amounts of alkali sulfates, (4) 90*b*.
investigation with microprobe, (5) 116*g*.
microscopic studies of alite, (1) 2*c*.
portland paste, aggregate, concrete, thermal conductivities of, down to very low temperatures, (1) 2*a*.
CPAC, thermal evolution at 25° to 1000°C—differential thermal and dilatometric analyses, (2) 34*a*.
hardened, reversible and irreversible drying shrinkage, (10) 248*e*.
nature of hydration products after 5 years immersion in potable water, (2) 34*f*.
power plant ash in, (4) 91*c*.
pozzolan pastes, nature of hydration products after 5 years immersion in potable water, (2) 34*f*.
pozzolan surkhi from burned clay brick, (2) 40*h*.
preparation, method, P (8) 174*e*.
production, in rotary kiln, P (5) 116*d*.
quality, effect of alkali content in clinker, (9) 214*e*.
raw, powdered, preheating and thermal treatment, P (2) 35*b*.
raw materials. See *Raw materials.*
refractory, containing iron scale, (4) 97*c*.
refractory composition, P (2) 33*i*.
resistance to sulfate solutions, effect of pozzolanic admixtures, (4) 90*j*.
setting, formation of alumina hydrate phases during, (7) 146*e*.
setting time, method of retarding, P (8) 174*e*.
silicate grout, P (3) 64*g*.
siliceous, (9) 215*j*.
slag, sulfate resistance of, (1) 2*d*.
slurry mixing apparatus, P (2) 35*b*.
slurry pouring means and method, P (4) 103*j*.
strength, of granular charge, action of electrolytes on, (10) 247*i*.
strontium, (7) 147*c*.

Cements (*continued*)
sulfate, obtained as by-product in chemical processes, experience in Czechoslovakia, (9) 214*j*.
tile, slabs and panels, containing special optical areas, P (2) 40*a*.
water asbestos-, slurry, apparatus for preparing and delivering to utilizing apparatus, P (3) 64*c*.
white, clinker properties, effect of different gas atmosphere during firing, (10) 248*c*.
Cement industry, in India, (7) 169*g*.
in India, historical survey, (10) 248*j*.
Ceramic engineering. See *Engineering*.
Ceramic industry, Australian, (11) 303*e*.
basic science importance to, (11) 292*i*.
Centralab invests in facilities for future, (1) 9*g*.
fuel oils in, (2) 52*g*.
in India, (7) 169*g*.
in Israel, (11) 303*e*.
Japanese manufacturer exports half of production, (4) 99*i*.
in Spain, (7) 169*g*.
traditional, and basic science, (2) 60*h*.
in western Africa, (9) 244*a*.
Ceramic materials. See also *Bodies, ceramic; Raw materials;* and specific types. P (5) 133*g*.
bonding metals to, P (2) 35*i*.
handbook, for ceramic processing, (5) 132*j*.
method of producing, P (5) 130*c*.
nitrogen compounds stable at high temperatures in, (5) 133*a*.
plastic, process for producing thin sheets, P (5) 130*e*.
production, P (1) 13*c*.
raw, electrical and magnetic enrichment, (5) 132*i*.
Ceramic-metal systems. See also *Enamels*.
enamel bibliography and abstracts–1966, B (8) 211*j*.
hydrogen behavior in, understanding for improvement of vitreous coatings, (4) 91*j*.
Ceramics, antique, use of electron microprobe and X-ray analysis in elucidation of chemistry of, (3) 63*j*.
articles, manufacture, P (5) 130*a*.
"black varnish" ware from late Roman potteries, (1) 1*h*.
brittle, thermal stress resistance, theory involving creep, (10) 270*d*.
composition, containing lightweight aggregate, P (5) 122*b*.
compositions, P (9) 228*g*.
composites, composition and uses, (4) 112*g*.
exhibition in Jahrhunderthalle, Frankfurt, 1966–Konrad Quillmann, (3) 63*i*.
fabrication, new processes, (3) 80*a*.
fired, expansion vs. fracture, (4) 89*j*.
and glass, bibliography, B (8) 211*i*.
manufacture, P (7) 158*c*.
with metal film via binder of copper oxide containing glass, P (3) 77*d*.
metallization of, and ceramic assembly fabricated by process, P (2) 48*c*.
in microcircuit design, add flexibility, (5) 126*g*.
nonfissionable, nuclear applications, B (5) 140*c*.
modern, review, (9) 244*a*.
objects and manufacture, P (3) 80*g*.
product, of clay and spodumene, and preparation, P (1) 9*b*.
for mending discontinuities, and process, P (2) 46*d*.
resistance to water and steam at high temperatures, (3) 74*a*.
technical, introduction, B (11) 304*h*.
titanate, (1) 10*c*.
Cerium, Ce^{3+}, orthorhombic sites in $CaWO_4$, EPR measurements, (8) 197*b*.
CeO, absorption bands, rotational analysis, (7) 167*c*.
CeO_2-ZrO_2, thermal expansion and electrical resistance of sintered bodies, (8) 209*j*.
dioxide, single-crystal growth from lithium ditungstate solvent, (4) 109*c*.
L_{III} X-ray absorption spectra, in compounds with nonmetals, (4) 108*c*.
molybdate, tungstate, and vanadate, process for producing, P (5) 133*d*.
monocarbides, standard free energy of formation, (4) 110*d*.
Cermets, alumina base: VII, effect of addition of CaO-MgO-SiO_2 mixture on sintering of Al_2O_3-Fe-Fe_2O_3, (11) 280*d*.
article, and method of making, P (4) 92*g*.
based on SiC study: I, Mo-SiC system; II reactions between SiC and Mo, (11) 281*e*.
bearings, porous, problem of calibrating, (3) 71*c*.
brittle, thermal shock resistance, similarity theory applied to, (8) 206*j*.
chromium-alumina, exothermic reactions in production, (4) 96*g*.
composition, P (3) 72*i*.
compositions, with metal grains of dispersed refractory metal oxide particles, process of making, P (7) 153*i*
electrically conductive, compositions, P (9) 225*c*.
elements, bonded, method of making, P (9) 217*a*.
hot working, P (11) 281*g*.
materials, determination of physicomechanical and technological properties on a single annular specimen, (10) 257*d*.
method of determining deformations, (2) 50*g*.
and process of making, P (1) 7*b*.
nuclear fuel body, manufacture, P (11) 281*i*.
preparation, P (8) 181*i*.
producing, bonding various metals with nonmetals as basis for, (5) 122*e*.
Cermets (*continued*)
resistance composition and resistor, P (9) 230*g*.
resistance element, and material, P (9) 230*h*.
electrical terminations, (9) 230*e*.
and terminal and tap connections for, P (9) 230*j*.
shaped, process for making, P (2) 45*f*.
uranium dioxide-stainless steel, physical properties, (7) 151*j*.
uranium oxide-molybdenum, bodies, preparation, (7) 152*b*.
bodies, properties, (7) 152*e*.
and uranium oxide-tungsten, dependence on microstructure of high temperature properties, (2) 41*h*.
Cesium, chloroniobates and chlorotantalates, enthalpy of formation, (7) 163*i*.
determination of trace amounts of, in silicate rocks, by direct current arc spectrographic technique, (2) 50*i*.
extraction, with nitrobenzene in presence of phosphomolybdic acid, (1) 13*e*.
fluorides, recovery and separation using alcohols, P (5) 133*f*.
sesquioxide, high-temperature heat capacity of, (3) 86*f*.
systems. See *Systems*.
vapor, reaction of alumina with, (5) 137*j*.
wolfram bronzes, thermal expansion, (4) 111*f*.
Chalcogenides, of transition metals, diffusion properties investigation: III, self-diffusion of nickel in nickel oxide, (1) 20*j*.
Chalk, additions, effect on sintering of porcelain, (9) 228*c*.
Chamotte. See *Refractories*.
Chemical properties, crystal-, of sulfides of rare-earth metals and actinides, (3) 84*h*.
Chemical reactions, activation and inhibition by mechanical working, (5) 133*j*.
Chemistry. See also *Analysis; Electrochemistry; Geochemistry; Thermodynamics*.
of boron and silicon, new results, (1) 23*i*.
of cements, (4) 90*g*.
chemical, behavior of silicate glasses, testing, (10) 253*f*.
composition, of cement kiln dust, (7) 146*e*.
compositions of glass-ceramics, (2) 36*e*.
dictionary, condensed, B (11) 303*j*.
durability of polycrystalline materials produced from glasses, (2) 36*f*.
variations in kaolin deposits of Georgia and S. Carolina coastal plain, (1) 23*g*.
crystal, of technetium-containing oxides, (8) 192*j*.
high temperature, 1000° to 3000°C, measurement, (7) 159*d*.
of silicates and other oxide systems, B (3) 88*e*.
hydrothermal, of silicates: XII, synthetic strontium aluminosilicates; XIII, synthetic barium aluminosilicates, (8) 199*g*.
reference book, B (4) 113*f*.
of silicates, structure model and application to, (4) 110*j*.
China clay. See *Kaolin*.
China, vitreous, bodies, strength improvement, (3) 74*e*.
vitrified, polishing by vibration, (9) 228*f*.
Chinaware. See also *Art and artware; Dinnerware; Porcelain*.
manufacturer diversifies, (4) 99*h*.
Chlorides, of indium, potassium, copper(I), silver and thallium(I), interaction, (8) 200*j*.
-ion contamination, radiochemical investigation, in surface properties of precipitated alumina, (2) 57*a*.
ions, repulsion by negatively charged clay surfaces: I, univalent cation Fithian illites; II, univalent cation montmorillonites; III, di- and trivalent cation clays, (7) 167*j*, *a*, *b*.
molten pyridinium, use in treatment of ores of niobium and other refractory metals, (5) 124*a*.
rare earth, in glass polishing composition, P (8) 178*i*.
salt solutions, molten, plutonyl species in, (8) 205*e*.
and silver, association in molten cesium nitrate and in molten mixtures of potassium nitrate with cesium nitrate or lithium nitrate, (8) 191*j*.
single crystals, cuprous, electric breakdown mechanism, (11) 294*b*.
Chlorination, catalytic, of beryllium from ore, P (5) 124*c*.
Chlorine, and fluorine, in silicate rocks, simultaneous determination by rapid spectrophotometry, (8) 188*b*.
Chlorite, -biotite equilibrium reactions in carbonate free system, (8) 192*j*.
Chromaticity. See *Color*.
Chromatographs, gas, for analyzing single bubbles in glass, (11) 276*j*.
Chromatography, gas, techniques: I, choice of solid supports, (5) 131*g*.
gas-solid, using column comprising $AgNO_3$-coated alumina, P (4) 98*i*.
to separate Mg, Ca, Sr by elution with ammonium sulfate, (4) 104*c*.
Chromia. See *Chromium, oxide*.
Chrome. See *Chromium; Refractories*.
Chrome-magnesite brick. See *Refractories*.
Chromium, carbide, free energy of formation, (3) 85*j*.
in cement and chromate eczema, (5) 116*c*.
-chrome-bearing materials, analysis: II, determination of silica and lime, (5) 130*h*.
chromic oxide, dense, preparation, P (1) 16*a*.
Cr^{3+} ions, in magnesium oxide, (7) 167*h*.
Cr^{3+}-Cr^{4+} equilibrium, in binary alkali borate glasses, (5) 118*h*.
Chromium, Cr^{3+}-Cr^{4+} equilibrium (*continued*)
in binary alkali borate melts, (8) 175*f*.
in binary alkali silicate glasses, correction, (5) 118*h*.
Cr-Fe diffusion coating ferrous metal substrate, P (3) 65*d*.
dioxide, decomposition in air, (10) 270*e*.
crystalline anisotropy energy, (5) 134*j*.
epitaxial growth, (8) 197*i*.
ferromagnetic, nuclear magnetic resonance of ^{53}Cr, (5) 137*j*.
ferromagnetic, preparation, P (1) 15*f*.
topotaxy in decomposition, (2) 59*c*.
disilicide, preparation and properties, (4) 97*a*.
divalent, in magnesium-chromium spinels, (8) 195*b*.
doping, for preparation of semi-insulating gallium arsenide, (3) 76*i*.
ion, paramagnetic relaxation in ruby and potassium alum, (8) 204*h*.
oxide, from ferrophos, P (5) 133*g*.
polycrystalline, magnetoelectric susceptibility measurements, (1) 22*b*.
rapid method for determining in chromite ores, chrome-magnesite bodies and refractories, (7) 159*c*.
radioactive, diffusion into alumina, (2) 47*a*.
silicides, heats of formation, heat contents and heat capacities, (3) 86*d*.
magnetic susceptibility, (8) 202*h*.
molten, electrical conductivity, (3) 85*a*.
solution, for growth of α-SiC crystals, (3) 86*c*.
spinel, recrystallization, (11) 300*a*.
systems. See *Systems*.
trivalent and hexavalent, in glass, physical and chemical estimation, correction, (5) 119*a*.
Chrysotile, asbestos, relation of surface and thermal properties to crystal structure, (3) 82*e*.
morphology and texture, effect of dehydroxylation, (11) 293*i*.
Circuits, air-oxide isolated integrated, (7) 155*h*.
boards, printed, method of producing, P (10) 264*i*.
components, printed, method for fabricating, P (3) 78*g*.
element totally encapsulated in glass, P (9) 230*j*.
interconnecting, with gallium and indium eutectic, P (11) 285*h*.
integrated, package, method of making, P (7) 157*e*.
using oxide insulated terminal pads on SiC substrate, P (5) 127*i*.
micro-, design, glass and ceramics add flexibility, (5) 126*g*.
multilayer, method of manufacturing, including electropolishing to smooth film conductors, P (8) 185*i*.
monolithic, dielectric isolation for, P (8) 184*h*.
solid semiconductor, with crossing conductors, P (3) 79*f*.
solid-state, method of making, P (8) 185*h*.
thin film, vacuum processing facility, P (8) 186*b*.
Circulators, ferrite, having three mutually coupled coils coupled to ferrite material, P (2) 47*f*.
Classifiers. See also *Beneficiation*.
hydrocyclone, for cement raw material, (7) 146*d*.
for materials, P (5) 133*g*.
particle, P (9) 236*d*.
Classification. See also *Separation; Separators*.
air, of ground chamotte, study, (9) 224*i*.
of borate, P (7) 160*j*.
of carbides, problem, (2) 42*i*.
of ceramics by electromagnetic techniques, (5) 131*e*.
of pores in refractories, (9) 223*f*.
of solids, pneumatically, method and apparatus, P (2) 50*a*.
of wet flocculated solid particles, by sink-float method, P (7) 161*d*.
Clays. See also *Ball clay; Fireclay; Kaolin*.
with additions of surfactants and electrolyte, rheological properties, (10) 256*g*.
additives as modifiers, (1) 12*f*.
aggregate, method of making from raw clay, P (8) 179*g*.
amine modified, and method, P (4) 106*i*.
apparent specific heat, determination, (7) 159*a*.
beneficiating, by flotation, P (11) 291*i*.
bleaching, P (3) 83*b*.
under nonoxidizing atmospheres, P (8) 190*c*.
bodies, iron-rich, mineralogy of salt glazes, (7) 154*j*.
ultrasonic dispersion, (3) 80*b*.
unfired, moisture stress, (7) 166*a*.
Bunzlau, and ware, (2) 53*f*.
catalytically active, method for manufacture, P (11) 282*d*.
colloidal, coated with acrylic acid-polyallyl sucrose copolymer, P (7) 160*h*.
from Comminges, (7) 150*g*.
compaction, factors influencing early stages, (8) 197*i*.
complexes, organometallic: VII, thermal analysis of montmorillonite-diamine and glycol complexes, (5) 137*b*.
complexometric determination of Fe, Al, Ca, and Mg in, (4) 90*h*.
coated with haloalkyl phosphorus ester and polyester resins containing, P (3) 83*b*.
concentrating, hydrocyclones design, (3) 79*j*.
cracking, during steady heating in water-saturated atmosphere, (7) 168*f*.
deposits in northeastern Alabama, (8) 189*i*.
di- and trivalent cation, repulsion of chloride ions, (7) 167*b*.
dispersion, B (1) 30*b*.
dispersions, stabilized, P (11) 292*b*.
double dilatometric analysis of, (11) 289*f*.

Clays (*continued*)
drying, development, measurement and interpretation of electrical potential gradients in, (2) 53*g*.
in Eocene neritic bar sand, (1) 24*j*.
fired, products, relation between compressive strength and modulus of rupture, (2) 40*f*.
flint, calcining facility, (4) 105*j*.
Grossalmerode pot, effect of physical structure on corrosion in molten glass, (5) 118*g*.
H-, dilute suspension of, effect of surface area on viscosity, (4) 107*g*.
high alumina, from Musakhel, (5) 123*g*.
kaolinitic, effect of mineralogical composition on some technological properties, (1) 15*e*.
listels and ornamental moldings, process for making by improved extruding device, P (11) 289*a*.
method of treating, P (9) 235*b*.
and clay produced, P (7) 161*c*.
minerals. See also specific types.
complexes, thermal decomposition, (2) 58*b*.
in Illinois coals, (8) 192*b*.
marine mudrocks, fluid-release mechanisms in compacting, and importance in oil exploration, (11) 290*j*.
and plasticity of, (5) 134*e*.
structure, B (1) 30*b*.
X-ray analysis, preparation of oriented slides for, (4) 104*c*.
moisture content, control, P (7) 160*i*.
from Muggenbach/Tambach deposit, (3) 82*f*.
natural, for enameling, (9) 216*d*.
nature, (9) 235*e*.
from Okinawa, for ceramic use, (5) 132*j*.
organo-, phenol adsorption mechanism, (1) 22*f*.
paper coating, and method for treating, P (4) 106*j*.
particles, orientation: II, studies on texture of green bodies of suspension insulators, (5) 125*i*.
plastic behavior, B (1) 30*b*.
pot, effect of molten glass composition on corrosion, (10) 252*j*.
pozzolan industry, development: III, utilization of reactive surkhi and lime-reactive surkhi mix, (10) 269*c*.
preparation in fine ceramic industry, (9) 228*c*.
processes and apparatus for granulating and drying, P (11) 288*j*.
production and testing, B (5) 142*g*.
products, efflorescence and salt retention, (2) 40*e*.
heavy, experiments on use of basalts in, (8) 179*c*.
humidifying device for, P (5) 130*f*.
vitreous, method of producing, P (7) 158*g*.
properties, base exchange effects, (4) 110*b*.
raw materials, preparation and forming, B (5) 142*c*.
red mud, process of recovering valuable components from, P (7) 161*a*.
refractory, combined grinding and drying in a shaft mill, (5) 122*j*.
from Jammu and Kashmir, (2) 42*g*.
slurries, and method of making, P (5) 133*g*.
slurry, inhibited composition, P (2) 54*b*.
rheological characteristics, determination, (9) 233*j*.
Spanish, (5) 132*i-j*.
structure and properties, (1) 16*j*.
structures, P (5) 133*h*.
surface area, measurement by dye adsorption, (1) 16*i*.
suspensions, aqueous, nonuniformity in characteristic plastic-viscous flow, (1) 27*j*.
internal mutual flocculation in, (8) 200*i*.
thixotropic structural-linked, new characteristics of complete rheological curves of, (1) 8*j*.
treatment, P (8) 190*d*.
viscosity, method of reducing, P (9) 236*b*.
-ware, heavy, technology: Vol. 1, raw materials, preparation and forming; Vol. 3, drier installations; Vol. 6, production and testing, B (5) 142*c-g*.
-water systems: III-5, cracking of clay during steady heating in water-saturated atmosphere; III-6, imbibitional swelling properties, (7) 168*f,g*.
wet plastic, process for lightweight material from, P (3) 80*f*.
whitening process, P (3) 83*d*.
Cleaning, electrical discharge, process, P (9) 233*c*.
Clinker. See *Cement; Dolomite; Forsterite; Magnesite*.
Coagulation. See *Agglomeration*.
Coal. See also *Coke; Fuels*.
ash. See *Ash*.
gas, for temporary heating of glass tank furnaces, (3) 66*j*.
Coatings. See also *Enamels; Glazes; Resins*.
acrylic acid-polyallyl sucrose copolymer, for colloidal clay, P (7) 160*h*.
alkali metal silicate, composition, P (10) 250*b*.
Al_2O_3, flame-sprayed, emissivity and electrical resistivity at higher temperatures, (3) 65*c*.
-nickel metal multilayer flame-sprayed, electrical properties of, (1) 2*h*.
aluminum spinel and platinum family, on hydrogen anode, P (5) 124*j*.
aluminum substrates with magnetic material, P (9) 230*j*.
aluminum, thin evaporated, density of, (1) 17*d*.
anodic oxide, for device fabrication in silicon: I, controlled incorporation of phosphorus, (3) 75*e*.
high resistance, on aluminum, (3) 76*a*.
Coatings, anodic oxide (*continued*)
on indium antimonide, (3) 75*e*.
apparatus, P (1) 12*e*.
application. See also *Electrostatic processes; Spraying*.
applying by vaporization, methods and devices, P (9) 233*a*.
aqueous silver, method of production, applied for one heating operation, P (5) 126*c*.
beryllia, P (3) 65*c*.
beryllide, for beryllium, P (4) 92*d*.
boron nitride, process for preparing, P (9) 226*h*.
brick surface, improved, (1) 6*j*.
carbide, applying by adhesive bonding, (9) 216*b*.
carbides, on tools, (2) 33*i*.
cathodically biased substrate from plasma of ionized coating material, apparatus, P (10) 263*a*.
cement compositions, P (4) 91*c*.
ceramic-metallizing tape, P (3) 77*e*.
ceramic, on muffler, P (2) 35*i*.
wetting and bonding with metals, (3) 65*a*.
chimney, P (1) 7*d*.
coated columbium or tantalum base metal, P (3) 65*b*.
coated superconductive ribbons, process for manufacture, P (9) 232*a*.
colored reflective composition, P (2) 38*b*.
for columbium base alloys, P (3) 65*c*.
Cr–Fe, ferrous metal substrate, P (3) 65*d*.
devices with protective glass jackets, and objects produced, P (4) 101*c*.
diamond reinforced, and method of making, P (4) 89*g*.
dielectric, plasma-sprayed for heat sinks in electronic packaging, (10) 263*b*.
dry lubricant, for preparing sheet metal surfaces, P (4) 92*e*.
electric lamp, comprising agglomerates of silica coated with pigment, P (8) 184*i*.
electric lamp bulbs, method, P (1) 5*d*.
electrical, components, method and apparatus, P (7) 156*j*.
discharge, process, P (9) 233*c*.
resistance, and manufacture, P (11) 285*e*.
resistant, for ceramic body, P (1) 10*g*.
electrostatic. See also *Electrostatic processes*.
apparatus, P (3) 80*b*.
process and apparatus, P (9) 233*c*.
for elevated temperature protection of metallic surface, P (4) 92*d*.
epitaxial, of semiconductor compound material, production, P (7) 157*i*.
structural defects, (10) 263*h*.
evaporated, detection of strain by wavefront reconstruction, (9) 233*j*.
ferrite, for metals, P (2) 48*e*.
for ferrous base alloys protection at elevated temperatures, P (4) 92*f*.
films, Al-Al_2O_3-Te, photon-modulated tunneling, (10) 271*b*.
Al_2O_3, defects near interface, (9) 229*c*.
Al_2O_3, manufacture, P (10) 264*c*.
Al_2O_3, plasma oxidized, (4) 100*b*.
Au-SiO_2, cosputtered, (10) 261*j*.
BaO, absorption bands in, (3) 83*h*.
$BaTiO_3$, preparation and properties, (4) 100*b*.
corrosion, dielectric loss spectra on zirconium, (4) 100*e*.
epitaxial, of gallium arsenide, influence of vapor composition, (7) 155*h*.
epitaxial, three-point probe method for electrical characterization, (3) 81*h*.
[001] epitaxial silicon, stacking-fault tetrahedra, (11) 301*g*.
ferrite, vacuum deposition by arc discharge, (11) 284*f*.
heteroepitaxial, of germanium on sapphire, (11) 296*g*.
indium, thermal relaxation, (4) 111*g*.
iridized, for glass, P (10) 255*h*.
PbS and CdS, vacuum deposited, (10) 262*d*.
liquid, from plastic dispersions, solutions or emulsions, process and apparatus for casting on metal sheets, P (5) 117*f*.
metallic, growth on sodium chloride substrates, (1) 19*j*.
$NiFe_2O_4$, preparing, P (10) 265*f*.
niobium carbide surface, diffusivity data on formation, (11) 293*b*.
nonglare, low specular reflecting, method for producing on glass articles, P (9) 221*c*.
oxide, on anodized zirconium, determination of refractive index and thickness from transmission interference measurements, (11) 293*a*.
oxide, deposition, (2) 46*j*.
oxide, method for forming, P (5) 117*j*.
oxide, thermally grown on silicon, structure and perfection, (8) 207*g*.
oxidized titanium, optical and structural properties, (1) 24*a*.
reactively sputtered silicon nitride, (9) 229*g*.
SiO_2, electronic conductivity, (5) 126*f*.
SiO, vacuum-deposited, nonohmic conduction, (11) 298*g*.
silver, vacuum-evaporated, X-ray diffraction study, (2) 59*e*.
single crystal, by cathodic sputtering, (4) 100*c*.
single-crystal, nucleation and initial growth, (1) 24*g*.
superconducting, parametric amplification with, (4) 100*j*
tantalum, heat treatment, (4) 100*g*.
Ta_2O_5, effect of temperature and area on conduction, (9) 229*c*.
Coatings, films (*continued*)
Ta_2O_5, formed by nonsteady potentials, (4) 111*i*.
tantalum and niobium, conductance during oxidation, (4) 100*d*.
SnPbTe, preparation, (10) 263*e*.
use of matching cleavage faces of NaCl in growth study, (8) 211*b*.
vacuum deposited, at high temperature, (2) 47*e*.
flame sprayed, (3) 65*d*; P (4) 92*f*.
fluorescent lamp, P (7) 156*e*.
fluorescent layer of electron discharge tube, P (1) 11*c*.
freeze-, of filaments of glass and SiO_2, (7) 148*k*.
germanium and silicon, thin film recrystallization, (10) 263*c*.
glass, composition for, P (1) 4*g*.
to glass fibers, P (1) 5*c*.
inorganic, process for forming on semiconductor devices, P (4) 102*i*.
method and apparatus for fusing to metal, P (2) 35*d*.
method of forming moisture-collecting, P (1) 5*j*.
nonreflective, P (4) 95*g*.
physisorption of xenon and krypton, (2) 36*j*.
SiO_2 and lead telluride, formed by reactive sputtering, (1) 9*g*.
on steel edges, (5) 117*d*.
for subsequent soldering, P (3) 68*b*.
to thermoelectric element, P (1) 5*d*.
glass fibers, method for applying forming lubricant, P (2) 39*f*.
process, P (4) 93*j*.
on glass surfaces to change transmission of radiation, (10) 251*b*.
high temperature, for aerospace applications, (11) 276*b*.
for columbium alloys, P (11) 276*b*.
protective, method of providing, P (4) 92*c*.
hot-end surface, identification–estimate of thickness using X-ray fluorescence techniques, (2) 36*i*.
light-diffusing, formation on vitreous silica bodies, P (4) 94*f*.
on quartz, P (4) 94*j*.
light impervious, for quartz tube, P (11) 287*j*.
masking device, P (10) 264*f*.
metal, by ion bombardment, P (11) 287*a*.
process for producing on ceramic body, P (10) 250*f*.
metallization, of ceramics and ceramic assembly fabricated by process, P (2) 48*c*.
process, for ceramic body surfaces, P (3) 75*c*.
metallizing, apparatus, P (10) 264*f*.
bodies of high melting point crystal materials containing aluminum oxide, P (9) 231*a*.
ceramics, (9) 229*d*.
ceramics, method and material, P (3) 79*a,b*.
for ceramics of very pure oxides, P (7) 156*i*.
luminescent screens, P (8) 185*j*.
nonmetals, P (11) 286*c*.
surfaces of ceramic body, P (2) 48*c*.
method and apparatus for vapor deposition of patterns, P (3) 78*f*.
methods of producing single crystal films on polycrystalline substrates, and devices using, P (10) 265*a*.
molybdenum, physisorption of xenon and krypton, (2) 36*j*.
nickel, pure uniform ductile, on semiconductors, P (11) 286*i*.
nonglossy surface, P (10) 250*e*.
olefin polymer, for glass surfaces, P (9) 221*e*.
oxidation resistant, method of making refractory metal structures with, P (4) 92*b*.
oxide, process for production on substantially monocrystalline body of semiconductor body, P (9) 232*f*.
properties on zirconium alloys and relevance to corrosion and hydrogen uptake, (2) 35*g*.
perforate articles, P (2) 38*a*.
phosphate layers, finely crystalline, process for application on metal surfaces, P (10) 250*e*.
photosensitive resistive, method of preparing, P (9) 217*c*.
p-type germanium with antimony, lead or alloys by electrodeposition, and product, P (9) 231*d*.
plasma-jet deposited refractory, protects spark plug having porcelain insulator, P (1) 11*j*.
plating, electroless copper, on ceramic material, P (4) 101*d*.
of gold, electroless, P (5) 127*j*.
polycrystalline, controlled deposition and growth in vacuum, P (3) 77*g*.
polycrystalline silicon, on foreign substrates, (3) 76*g*.
polyimide, with crystalline particles, P (4) 89*f*.
porcelain enamel, P (11) 276*b*.
process, P (1) 12*e*.
using liquid metal substrate holder, P (3) 79*b*.
protective, for beryllium metal, P (4) 92*e*.
composition, P (2) 35*f*.
flame sprayed, P (9) 217*c*.
for metals, B (11) 306*b*.
method of applying to metallic structure, P (8) 174*h*.
for planar devices, P (2) 49*e*.
oxidation studies of complex silicides, (7) 147*i*.
for refractory metals, (7) 147*j*.
transparent, improved, for electroluminescent structure, P (5) 127*j*.

Coatings (*continued*)
pyrolytic graphite, process, P (8) 182*a*.
radiant heat reflective, and method for application, P (2) 35*f*.
refractory, on aluminum, process, P (7) 148*a*.
for metal casting mold, P (2) 35*g*.
for metal surfaces, P (10) 250*f*.
refractory metal or carbide, method for forming on refractory materials, P (5) 117*i*.
semiconductor, with tungsten-containing glass, method and article, P (10) 264*g*.
semiconductor bodies with silicon dioxide, P (8) 184*f*.
semiconductor chips, method, P (1) 11*h*.
for semiconductor devices, stabilizing, P (10) 265*g*.
silicon carbide, process for applying to refractory metals, P (8) 174*j*.
silicon semiconductor, with indium using ion beam, P (3) 79*a*.
silicon monocrystalline layers, method of producing on monocrystalline substrates, P (9) 231*b*.
single-crystal, ferrite, preparation, (8) 183*g*.
of ferrite and garnet magnetic oxides, chemical vapor growth, (8) 183*d*.
sinter, method and apparatus, (10) 250*g*.
spray-, apparatus, P (1) 13*b*.
substrates, by cathode sputtering, apparatus, P (3) 77*j*.
tetragonal crystalline oxide, on germanium, method for forming, P (11) 286*g*.
thickness estimate by X-ray fluorescence, (2) 36*i*.
thin films, CdS, effect of oxygen on electrical properties, (10) 262*h*.
of CdTe-metal-(In, Cu, Au), (5) 126*i*.
electrical capacitor formed from, P (2) 47*c*.
evaporated, temperature coefficients of resistance, (2) 47*d*.
evaporated Permalloy, porosity and coercive force in, (11) 284*e*.
germanium, sputtered, (1) 21*i*.
growth of sodium chloride, use of matching cleavage faces, (8) 211*b*.
method of attaching leads, P (2) 48*e*.
of Ni-Fe-Mo by sputtering, P (5) 128*f*.
nucleation and growth observed in electron microscope, (1) 24*f*.
physics, B (11) 305*i*.
polycrystalline CdTe, sublimation in vacuo, (11) 301*a*.
resistors, method of forming, P (2) 48*h*; P (2) 48*i*.
superconducting, of niobium, tantalum, tantalum nitride, tantalum carbide, and niobium nitride, (3) 76*j*.
vacuum-deposited magnetic, of Fe_3O_4-B_2O_3 mixtures, (3) 77*f*.
ZnO, preparation by sputtering in oxygen and argon, (3) 76*i*.
tin, of copper surfaces by replacement plating, P (5) 129*d*.
vapor deposition of germanium on molybdenum, (9) 230*e*.
vitreous, improvement through understanding of hydrogen behavior in ceramic-metal system, (4) 91*j*.
vitreous enamel, residual strain determination, (11) 276*a*.
wear-resistant nickel phosphide, (2) 43*i*.
ZrO_2, flame-sprayed, emissivity and electrical resistivity at higher temperatures, (3) 65*c*.
Cobalt, $Co_{1.4}V_{2.4}O_4$, single crystal growth and electrical transport properties of intermediates in, (8) 206*j*.
Co^{2+}, spin resonance in YGaG, (8) 207*b*.
Co_3C, bond state of carbon atoms in, (4) 110*e*.
CoF_2, sublimation pressure, Knudsen and Langmuir measurements, (8) 201*j*.
Co_3O_4 and $CoAl_2O_4$, paramagnetic, nuclear magnetic resonance of ^{59}Co and ^{27}Al, (9) 241*f*.
cobaltous acetate tetrahydrate, thermal decomposition, (4) 111*c*.
cobaltous ion in alumina, (8) 192*e*.
chloride, thermodynamic transformation, (8) 210*j*.
monoxide, phase diagram at high temperatures, (7) 166*h*.
oxide, magnetic structure, (10) 271*c*.
single crystal, antiferromagnetic, magnetostrictive behavior in magnetic field, (9) 240*f*.
single crystal, magnetic anisotropy measurements, (8) 202*c*; new interpretation, (10) 271*f*.
structure and temperature factors, (7) 168*e*.
systems. See *Systems*.
Coke. See *Coal; Fuels*.
Coke ovens. See *Refractories*.
Colloids. See also *Silicon, dioxide gels*.
aerosols, literature, (8) 189*i*.
aquasols of crystalline zirconia and/or hafnia, P (2) 45*a*.
gel, alumina, aging in aqueous solutions for properties of trihydrates, (1) 27*i*.
mechanism of conversion to crystalline alumina hydrate, (2) 56*j*.
study on aging, (2) 56*a*.
hydrogels, silicon dioxide-alumina type spherical, method and apparatus for preparing, P (10) 259*f*.
hydrosols, thorium silicate, P (3) 75*a*.
molecular, mechanism of sorption on solids; IV, Congo red on alumina, (3) 86*h*.
particles, apparatus for determining shape using light scattering, P (4) 104*h*.
sol-gel process, for preparation of urania and urania-zirconia microspheres, (4) 97*b*.
sol process, uranium trioxide-zirconium dioxide, and product, P (9) 227*j*.

Colloids (*continued*)
sols, aqueous thoria-urania, P (9) 225*a*.
high purity alumina, manufacture from relatively low grade aluminum, P (11) 281*j*.
hydrous oxide, of urania and thoria, and process, P (10) 259*a*.
plutonium oxide, preparation, P (7) 153*g*.
thorium oxide, P (8) 182*e*.
urania, method of making, P (2) 44*b*.
uranium dioxide, process, P (7) 154*e*
uranium dioxide-zirconium dioxide preparation, P (7) 154*f*.
uranium trioxide, process, P (9) 227*i*.
stability, modern theories, (7) 165*i*.
Color. See also *Pigments; Stains*.
coloration, radio-, of borate glasses, kinetics, (8) 175*i*.
of silver containing glasses, by heat treatment at constant temperature, (4) 92*i*.
of vanadium-containing glass, (4) 92*j*.
decolorization of glass, (7) 148*e*.
developing process, of copper ruby glass, (4) 92*h*.
in heavy clay industry, (11) 279*j*.
lead-free, for porcelain and glass, (3) 74*c*.
measurement of surface, modified Lovibond tintometer using fiber optics for, (1) 14*a*.
in Mg-Zn-Ti spinels with Co^{2+} and Ni^{2+}, (11) 292*j*.
measurement. See *Colorimetry*.
-name charts, ISCC-NBS, illustrated with centroid colors, (4) 108*c*.
technology, principles, B (5) 141*e*.
Ti-Sn spinels with additions of Co^{2+} and Ni^{2+}, (11) 296*a*.
in tin spinels, effect coordination preference on development, (11) 293*h*.
Colorimetry.
colorimeter employing tristimulus values, P (8) 188*a*.
Coloring materials. See *Decoration; Pigments; Stains*.
Columbium. See also *Niobium*.
alloys, high temperature coatings for, P (11) 276*b*.
article, protected, P (5) 117*g*.
coated with silicide, for improving oxidation resistance, (10) 249*g*.
Combustion. See also *Burners; Firing; Flames; Furnaces; Heats; Kilns*.
calorimetric measurement, (8) 192*c*.
chamber, tubular, improvements, P (11) 290*d*.
process and device for improving, and regulating height of flame, P (10) 268*h*.
products, method of and apparatus for analyzing, P (3) 81*f*.
solid products buildup prevention in outlet flues of boiler furnaces, open hearth furnaces, P (2) 53*e*.
systems, measurements in, (11) 290*d*.
Comminution. See *Crushing*.
Communication, communicating technical information, guide to current uses and abuses in scientific and engineering writing, B (9) 244*i*.
technical, slides in, (9) 244*a*.
Compaction. See also *Pressing*.
of clays and sands, factors influencing early stages, (8) 197*i*.
effects, experimental, in carbonate sediments, (7) 163*d*.
of ferrite particles, method and apparatus, P (1) 11*b*.
of forsterite shapes, effect of industrial factors, (7) 151*j*.
hydrostatic, of metal powders, method and apparatus, P (8) 186*h*.
vibrational, of ceramic oxides, influence of frequency and acceleration on density during, (7) 151*e*.
Compacts, elongated powdered material composite, method of molding, P (7) 158*f*.
Composites, article, of bonded refractory metal and ceramic, P (11) 281*a*.
of ceramics, cermets, alloys, heavy alloys, and metals of different thermal expansion coefficient, P (2) 43*i*.
corrosion-inhibited sintered, of metal matrix with occluded cement, P (10) 249*a*.
fiber impregnated, high-strain fatigue, (9) 216*f*.
fiber-reinforced, stress-strain behavior and toughness, (9) 216*i*.
titanium boride bars, P (11) 281*a*.
titanium ceramic, P (4) 103*b*.
Compressibility, isothermal, of uranium monocarbide, (11) 297*e*.
of liquids, apparatus and method for measuring, P (7) 159*g*.
of LiF crystals, theoretical determination, (8) 209*b*.
of powder masses, (3) 84*j*.
Compression, linear, of α-quartz to 150 kbar, (7) 165*d*.
thermo-, wire attachments to quartz crystals, P (4) 102*j*.
Computers, applications to ceramic operations, B (11) 303*g*.
assemblies, alumina in, (1) 9*f*.
in ceramics plant, planning, (1) 12*f*.
in geology, expanding role, (11) 303*e*.
in glass manufacturing: I, glass process automation concepts; II, digital process control computer, (8) 175*e*.
program, to calculate mutual solubilities of MgO and CaO in dolomites, (3) 80*j*.
reduction of gamma spectra, for activation analysis of silicon, (2) 50*d*.
spectroscopic wavelength, remote control system for, P (1) 14*e*.
Concentration, of asbestos ore, P (9) 235*j*.
Concentrators, mineral, P (1) 16*a*.

Concretes. See also *Cement; Masonry; Mortars; Pozzolans*.
action of ammonium salts on, (2) 34*a*.
beams, reinforced, field exposure tests, (8) 174*d*.
reinforced prepacked, strength, (7) 147*a*.
chamotte, testing with sodium silicate binder in large-diameter kiln, (9) 215*c*.
continuous beams, prestressed, redistribution of moments, (11) 275*i*.
cores, cubes and beams, radioactive method for measuring density variations in, (2) 51*c*; discussion, (11) 274*i*.
cube and cylinder strength, influence of testing machine characteristics, (11) 275*c*.
diffusion of water in, at temperatures between 50° and 95°C, (3) 64*b*.
effect of mix proportions and method of testing on Poisson's ratio, (9) 214*h*.
flatwork, surface discoloration, (1) 2*e*.
fresh, moisture determination in, (11) 274*j*.
glossary of terms, (3) 64*c*.
heat-cured, effect of clinker composition on hardening, (11) 274*i*.
heat insulating, use of rhyolitic pumice for making, P (3) 73*c*.
heat resistant, determining moisture content, (5) 131*b*.
for testing blocks in soaking pit walls, (9) 225*c*.
use in parts of open-hearth furnaces, (7) 151*b*.
lightweight, process for making granulated ceramic, porous, or analogous materials, P (2) 35*a*.
lightweight and natural, core and cylinder strengths, (7) 146*j*.
optimum structure, and conditions of formation, (5) 116*h*.
prepacked, strength, (7) 147*a*.
refractory, in iron and steel industry, (7) 152*h*.
new developments, (4) 97*i*.
pneumatic gunning, (8) 180*g*.
use in slot furnaces, (5) 123*j*.
use of rhyolitic pumice for making, P (3) 73*c*.
research, new application of internal friction, (7) 146*i*.
sand, heat resistance, (10) 248*h*.
setting and curing, volume changes from 0 to 7 days, (3) 64*h*.
setting time, determining with copper-lead electrode, (9) 214*c*.
silicate, effect of electric current on properties, (8) 174*c*.
skid resistance of, laboratory studies, (4) 90*j*.
specimens, apparatus for laboratory freezing-and-thawing tests, (11) 274*h*.
structural plain, (7) 147*d*.
synthetic resin, for use as constructional building material, and methods of making, P (7) 147*e*.
tests and properties, significance, B (5) 141*a*.
thermohydraulically bonded high density, process for making, P (4) 91*f*.
Thomas blast furnace slags for use in, (4) 90*j*.
Condensers. See *Capacitors*.
Conductance, of glass immersed in molten salts, (9) 217*j*.
Conductivity, electrical, and(or) **Conduction, electric,** abrasive bodies, P (7) 145*g*.
behavior of mica at elevated temperatures, (8) 183*f*.
of beryllium fluoride glasses, (4) 93*j*.
creep-, correlations in polycrystalline BeO, (5) 134*h*.
of dehydrated phosphoric acids, (4) 107*i*.
in elongated needlelike diamond, P (7) 145*h*.
of fused $LiNO_3$-$NaNO_3$-KNO_3 eutectic, (3) 85*j*.
in glass forming nitrate melts, (8) 198*g*.
of glasslike $GeSe_2$, (3) 66*f*.
of graphite, (5) 135*e*.
of higher uranium oxides, temperature dependence of, (4) 111*a*.
of FeO_x-CaO slags, (9) 238*b*.
layers, of different types, for photosensitive device, P (2) 48*j*.
of melts, in system Na_3AlF_6-Al_2O_3-NaCl, (3) 85*j*.
of molten chromium silicides, (3) 85*a*.
of niobium dioxide, (8) 196*c*.
of oxyfluoride melts of potassium, zirconium and boron, (8) 196*e*.
phenomena, in monosilicides of iron group transition elements, (10) 270*h*.
in polycrystalline beryllium oxide, (5) 134*j*.
of pure zirconia between 1200° and 1750°C, (1) 18*c*.
and ceramic compounds of zirconium between 1500° and 2400°K, (2) 46*i*.
of NaCl, particle size dependence, (4) 108*a*.
super-, in ceramic mixed titanates, (8) 183*i*.
of several complex carbides and nitrides, (2) 56*h*.
of vanadium oxides, (7) 163*b*.
Conductivity, electronic and(or) **ionic,** of BeO, (2) 55*e*.
in calcium silicate glasses, (1) 4*a*.
in cesium and thallium silicate glasses, (11) 277*d*.
in new glass compositions, (11) 277*d*.
in NaCl-$ZnCl_2$ system, (8) 194*f*.
in thermally grown silicon dioxide films, (5) 126*f*.
Conductivity, thermal. See also *Heat*.
of $BaTiO_3$ and $SrTiO_3$ from 4.5° to 300°K, (9) 242*g*.
of bricks, method of measuring at room temperature, (2) 50*f*.
of $Ca_xBa_{1-x}TiO_3$, (7) 169*c*.
of corundum refractories, effect of porosity and structure, (9) 224*a*.

Conductivity, thermal (*continued*)
of glass in SiO_2-Li_2O-Al_2O_3-ZrO_2 system, during crystallization, (4) 93*c*.
of lithium fluoride crystals, effect of isotopes, (8) 195*c*.
measurements, low temperature system, (1) 13*j*.
measurements on metals and oxides at high temperatures, (2) 51*i*.
method, for oxidation measurements, (3) 80*h*.
of plastics with glass, asbestos and cellulosic fiber reinforcement, (9) 218*h*.
and pores, (11) 299*j*.
of portland cement paste, aggregate, and concrete down to very low temperatures, (1) 2*a*.
problem, in DTA, (10) 267*e*.
of refractories, errors in measurement due to poor temperature distribution, (5) 122*g*.
rapid determination of coefficients, (5) 123*h*.
of refractory insulating brick, (2) 41*e*.
of single crystal UO_2, (8) 209*f*.
of solid solutions of systems Bi_2Se_3-Sb_2Te_3 and Bi_2Te_3-Sb_2Se_3, (2) 57*i*.
of stabilized zirconia at high temperatures, (2) 57*i*.
of structures and insulating materials, effect of moisture on, (3) 80*i*.
Conductors, electrical. See also *Semiconductors*.
applying, on smooth vitreous surface, and article, P (7) 157*c*.
coated with silver containing oxygen, and method of making, P (7) 156*h*.
elements, solid current, method of manufacturing, P (8) 181*c*.
folded center, for reciprocal stripline ferrite phase shifter, P (2) 49*d*.
high temperature insulation for, P (8) 177*g*.
insulated, and method of making, P (9) 217*b*.
metal, methods of joining to semiconductor body, P (9) 231*c*.
photo-, device, incorporating stabilizing layers on selenium layer face, P (7) 157*d*.
layers, method of making, P (2) 48*a*.
reproducible, process for fabricating, P (10) 265*g*.
solid lubricant members, carbon based, and process and apparatus using, P (4) 101*b*.
and process and apparatus using them, P (5) 127*i*.
superconducting materials, and method of making, P (3) 79*g*.
super-, comprising niobium substrate with coating of niobium stannide and particles of ferromagnetic material, P (11) 287*i*.
hard, (10) 262*b*.
intermetallic, method of forming, P (4) 101*f*.
niobium stannide, product, P (8) 185*c*.
process for forming niobium-stannide, P (7) 157*f*.
Conferences, on physics of non-crystalline solids, B (2) 61*i*.
on role of grain boundaries and surfaces in ceramics, B (2) 60*j*.
of Spanish Ceramic Society, papers of second meeting, B (2) 62*c*.
Congresses. See *Conferences*.
Contacts, barriers on insulating CdS, (1) 9*h*.
elastic, of nominally flat surfaces, (11) 293*a*.
layer, for silicon-containing material, P (5) 127*e*.
material, catalytic, for hydrocarbon conversion process, P (8) 190*f*.
members, sintered electrical, P (8) 186*e*.
metallic ceramic composite, for semiconductor devices, P (4) 101*a*.
metallic, for semiconductor devices, P (11) 286*c*.
noncorrosive, process for ensuring, on heating rods, P (2) 53*b*.
phenomena in metallic systems and technological applications, (10) 250*h*.
semiconductor, for planar devices, P (2) 49*e*.
on semiconductor ceramic bodies of *n*-type oxidic material, P (3) 79*g*.
on semiconductors, method of making, P (11) 286*i*.
silver-lead alloy, containing dopants for semiconductors, P (5) 129*a*.
Te, on semiconductor devices, method of forming, P (11) 286*f*.
terminal, on semiconductor devices, and method of making, P (3) 79*e*.
top, for surface protected semiconductor devices, P (11) 288*c*.
Containers. See *Glass*.
Controls. See also *Instrumentation; Temperature*.
of $CaCO_3$ content in cement by automatic titrator Holderbank system, (11) 274*j*.
clinker, in cement industry, (11) 274*i*.
equipment, new process, for grate coolers for cement clinker, (11) 275*g*.
for feeding apparatus. See *Feeding apparatus*.
method for use in clay pits, research, (5) 131*e*.
remote, system for spectroscopic wavelength computer, P (1) 14*e*.
-rod, neutron -absorbing materials for, (3) 70*j*.
of wear processes of refractory linings of basic oxygen LD furnaces, (7) 151*j*.
Conveyors. See also *Materials handling*. P (5) 130*d*.
or bricks, P (3) 80*b*.
chain, for continuous drying of ceramic products, P (2) 52*d*.
for cooling granular material, P (3) 80*a*.
folded flexible, with sputtering apparatus, P (2) 49*a*.
-mixer, vibratory, P (4) 103*j*.
pneumatic, pressure loss in bent rubber hose on, (9) 232*j*.
Conveyors (*continued*)
with radioactive source and detector, for continuously weighing material on, P (1) 12*h*.
system, high temperature furnace, P (7) 160*b*.
for tunnel kiln, P (11) 290*h*.
Coolers, grate, new process control equipment for cement (11) 275*g*.
for rotary kiln, P (1) 14*i*.
rotary shaft, P (3) 83*e*.
Cooling, air-, continuous, of granulated materials, apparatus, P (7) 158*l*.
apparatus, for cement clinker, P (1) 2*c*.
for metallic and nonmetallic particles, P (5) 132*g*.
cement, method, P (11) 275*e*.
clinker in recuperators of rotary kilns, (9) 214*b*.
granular material, structure and method, P (9) 233*d*.
temperature controlled structure for, and method, P (10) 261*a*.
hot gases, chimney for, P (4) 105*c*.
liquid or semiliquid materials of low thermal conductivity, process and apparatus, P (7) 158*h*.
optical, of ruby, possibility, (5) 137*i*.
rates in splat cooling, (10) 261*i*.
Concentrators. See *Separators*.
Copper, activated strontium metaphosphate phosphors, P (8) 184*f*.
alloy for glass molds, (2) 36*h*.
(I) chloride, interaction with chlorides of indium, potassium, silver and thallium (I), (8) 200*j*.
$CuFe_2O_4$ single growth and Laue photographs, (8) 198*j*.
$CuMn_2O_4$, cation distribution, (9) 237*g*.
spinel, structure, (8) 207*j*.
ferrite, cubic-phase single crystal, ferrimagnetic resonance in, (11) 295*c*.
manganite, electrical properties, (9) 238*d*.
oxidation, mechanical stresses during, and their influence on oxidation kinetics, (7) 165*i*.
oxide, catalyst, multilayer, for treatment of exhaust gases, preparation, P (11) 291*c*.
systems. See *Systems*.
oxide-rare earth oxide catalyst compositions, alumina supported, P (2) 43*c*.
oxides, deformation at high temperatures, (2) 56*b*.
and sulfates, solid-phase interactions, (1) 28*h*.
single crystal surfaces, effect of light on formation of oxide films on, in water, (7) 166*f*.
sulfide, influence on decomposition rate of zinc sulfate at 600°C, (8) 200*e*.
surfaces, tin coating by replacement plating, P (5) 129*d*.
systems. See *Systems*.
tungstate, interaction with sodium ditungstate, (4) 108*j*.
X-irradiation, effect on surface area of calcium oxide produced by thermal decomposition, B (9) 244*f*.
Cordierite, casing, for high power fuse, P (4) 101*i*.
Cores, element, for breeder nuclear reactor, P (9) 225*d*.
foundry, method of manufacturing, P (8) 181*b*.
Corrosion, inhibition, of sulfuric acid on carbon steel, P (8) 174*j*.
of molybdenum, by molten glasses, (5) 118*f*.
of pot clays, effect of molten glass composition, (10) 252*j*.
of refractories by molten silicate glass as the solid dissolution process, (1) 7*a*.
resistance, of single crystal alumina and sintered alumina bodies to inorganic acids, (8) 180*i*.
of silicon nitride refractory by molten iron, (11) 280*j*.
slag, of siliceous fireclay brick, effect of casting conditions, (9) 224*j*.
Corundum. See also *Aluminum, oxide; Refractories*.
crystals, hydrogen etched, orientation by optical back reflection, (9) 233*j*.
synthetic, electron microscopy and diffraction: II, dislocations and grain boundaries in impurity-doped aluminum oxide, (8) 196*j*.
deformation and shrinkage during sintering, (10) 257*b*.
grains, ceramic bonded, basic and technical questions of production of grinding wheels, (3) 63*f*.
hydrothermal synthesis, effects of impurity ions: I, crystal habit, (3) 85*e*.
light rays, effect of temperature, (2) 56*d*.
particles, thermal change in Corhart refractories, (7) 152*e*.
single crystals, method of manufacturing, P (9) 226*i*.
synthetic, elastic constants, (2) 54*j*.
thermal etching, (2) 58*f*.
thermodynamic properties, a standard substance in calorimetry, (8) 210*e*.
Cracking, of clay, during steady heating in water-saturated atmosphere, (7) 168*f*.
in oxide formed on uranium in carbon dioxide at 650°C, (11) 293*c*.
Cracks, cleavage, in NaCl investigation, (1) 20*b*.
distribution, ultrasonic study in sintered beryllia, (2) 59*i*.
propagation, cleavage, within crystals by Griffith mechanism vs. dislocation mechanism, (11) 292*j*.
microscopic observation, (3) 81*h*.
two coplanar dislocation-type, interaction, (1) 20*f*.
Crazing. See *Glazes*.
Creep, behavior of silver-alumina alloys above melting point of silver, (4) 110*i*.
in beryllium oxide, (8) 194*f*.
of dense polycrystalline magnesium oxide, (1) 17*f*.
Creep (*continued*)
diffusion-controlled, of polycrystalline aluminum oxide, effect of MgO and $MgTiO_3$ doping, (5) 135*i*.
dislocation model, (9) 243*f*.
of hardened cement paste, effect of shrinkage stress, (5) 116*d*.
high-temperature, in polycrystalline BeO, (7) 164*c*.
of lightweight aggregate concrete, influence of cement paste, discussion and reply, (11) 275*d*.
mechanism in MgO brick, (10) 257*j*.
phenomena, time-dependent, in single-crystal MgO, (1) 16*f*.
radiation-induced, in graphite, (2) 55*g*.
rate, functional relation to porosity for polycrystalline ceramics, comment, (10) 270*f*.
rate tests, torsional, of refractory materials, (3) 71*i*.
of solids, (8) 203*a*.
of urania base solid solutions, (8) 192*i*.
Cristobalite. See also *Silicon, oxide*.
solid solution with $AlPO_4$ of cristobalite type, (4) 109*i*.
Crucibles. See also *Refractories*.
glass melting, model study of viscous liquids mixing in, (10) 252*g*.
glass spinning, P (1) 5*g*.
Crushing. See also *Crushing apparatus; Mills*.
and grinding plant, P (10) 269*d*.
of ore, method, P (7) 160*j*.
pulverizing solids, method and means, P (8) 190*b*.
Crushing apparatus. See also *Mills*.
automated crusher setting, P (10) 269*i*.
automatic clearing mechanism, P (10) 269*i*.
centrifugal mechanism, P (10) 269*j*.
cone or gyrating, of suspended spindle type, P (3) 83*c*.
cone-type, with shock pad between frame and adjustment ring, P (11) 291*d*.
for consolidating substances in powder form, and process, P (2) 50*b*.
crusher, P (4) 106*a,j*.
for disintegrating materials by means of liquid jets, P (9) 235*k*.
for fibrous material, P (4) 103*i*.
gas hydraulic spring for, P (8) 190*e*.
gyratory, P (5) 133*b*; P (7) 160*j*.
bowl adjusting mechanism, P (9) 235*j*.
crusher bowls, adjusting mechanism for, P (11) 291*c*.
frame for, P (5) 133*a*.
gyroscopic, of shallow height, P (11) 291*g*.
jaw, P (9) 235*i*.
for minerals, P (1) 15*i*.
jaw crusher, P (2) 54*c*; P (3) 83*d*.
pulverizer, P (8) 190*b*; P (9) 236*d*.
pulverizing, P (5) 133*f*.
rock, P (11) 292*d*.
rock, bowl support, P (1) 16*c*.
roll type rock, P (9) 236*g*.
rollers, tamping arrangement for supplying material to, P (11) 292*d*.
rotary shaft, P (3) 83*e*.
Cryolite, growth of large sapphire crystals from, (2) 55*c*.
Crystalline materials, method for controlled doping, P (8) 185*b*.
mineral compounds, apparatus for making, P (2) 53*i*.
poly-, chemical durability produced from glasses, (2) 36*f*.
films, controlled deposition and growth in vacuum, P (3) 77*g*.
method for separating grain-boundary and lattice diffusion effects, (3) 86*i*.
structures, B (9) 244*e*.
Crystallization, of barium silicate glasses, B (7) 170*j*.
catalyzed, of glasses, DTA method, (2) 37*f*.
controlled, of fused rocks, (10) 256*j*.
effects, on electrical properties of R_2O-RO-PbO-SiO_2 glass, (7) 148*f*.
of glass, B (9) 245*c*.
in Se-As_2Se_3 system, (3) 65*j*.
of glasses, controlled, for preparation of ceramics, B (7) 170*a*.
fluor-richterite composition: I, phase separation in model glass, (7) 149*a*.
internal, products of crystalline glass, (5) 118*d*.
kinetics, effect of high pressure with special reference to fused silica, (2) 36*b*.
of Li_2O-Al_2O_3-SiO_2 glasses containing TiO_2, direct observation, (3) 66*b*.
of lithia-silica glasses at high pressure, (5) 118*i*.
of melts of salts, complex formation, (11) 292*g*.
of metallurgical slags and rocks melts, effect of additives, (3) 71*j*.
micro-, of photosensitive glasses by variable-composition samples, (8) 176*g*.
of nepheline glass-ceramics, (3) 65*j*.
re-, of chrome spinel, (11) 300*a*.
of germanium and silicon thin films, (10) 263*e*.
separate, of boric acid and alkali sulfate from aqueous solution by evaporation at different temperatures, P (11) 292*e*.
of slag minerals, influence of water treatment of molten blast-furnace slags on linear rate, (1) 2*b*.
of $NaNbO_3$ from glasses in Na_2O-Nb_2O_5-SiO_2 system, (8) 175*g*.
solid state, radiation-induced process, (8) 206*a*.
of stuffed β-quartz glass-ceramics, (5) 118*k*.
of tantalum and niobium oxide films, anodically formed, electron microscope observations, (7) 163*f*.

Crystallization (*continued*)
of vitreous systems by using variable-composition samples, (8) 176*c*.
in zirconia glasses and enamels, (3) 65*j*.
Crystallography, of new compounds having hauynite structure, (8) 208*f*.
Crystals. See also specific kinds.
alkali halide, reduction of incorporated silver ions, (5) 138*b*.
alkaline earth, doping, (3) 85*a*.
atomic mechanisms for transport of charge by dislocations in NaCl type, (8) 191*a*.
(Ba,Pb)TiO_3, compositional inhomogeneity, (10) 270*g*.
(Ba,Sr)TiO_3, electron microscopic observation, (11) 294*j*.
barium titanate, chemical processes during hydrogen reduction, (2) 54*k*.
$BaTiO_3$, growth of butterfly, (9) 239*d*.
$Bi_{12}GeO_{20}$, growth and properties, (9) 239*e*.
centrosymmetric, for anomalous scattering of X rays, (1) 16*i*.
cleavage crack propagation within, by Griffith mechanism vs. dislocation mechanism, (11) 292*j*.
corundum, single method of manufacture, P (9) 226*i*.
crystalline alumina hydrate, mechanism of conversion from alumina gel, (2) 56*j*.
crystalline members, method for growing completely within solution melt, P (1) 11*c*.
crystallites, determination of size distribution, (5) 130*j*.
cubic, electric fields produced by point defects, (7) 162*j*.
defect chemistry, of pure nonstoichiometric compounds, (10) 270*k*.
defects, electron diffraction from, (8) 196*i*.
theory, B (4) 114*a*.
diamond type, irradiated, energy dependence of anisotropy of defect production in: I, experimental measurements on *n*- and *p*-type silicon; II, theoretical model, (8) 197*a*.
field calculation in UO_2, (8) 193*a*.
formation. See *Crystallization*.
GaAs, anodic behavior with increased current densities, (10) 261*i*.
growing, apparatus, P (11) 285*b*.
arc process and apparatus, P (8) 180*e*.
bibliography, from 1960 to 1965, (9) 232*i*.
epitaxially, layers of semiconductor through openings in oxide mask, P (4) 101*e*.
by evaporation of isothermal flux, (8) 187*e*.
furnace with alumina liner, P (2) 52*f*.
nucleation in diffusion, (1) 24*d*.
VO_2, (8) 203*j*.
growth, P (3) 77*h*.
above 2200°C by Verneuil method, (8) 193*b*.
of alkali halogenides, (7) 169*b*.
at bubble surfaces in glass, (3) 65*i*.
of calcite and apatite, (2) 55*e*.
and characterization of uranium-doped germanium, (9) 239*j*.
of $CuFe_2O_4$ and Laue photographs, (8) 198*j*.
defects in spinel from Verneuil process, (8) 194*g*.
dendritic, process for controlling, P (4) 102*h*.
of fluoride, (9) 239*a*.
of GaP, rapid, (10) 263*c*.
of lanthanum hexaboride, (7) 163*f*.
localized cooling, (7) 165*e*.
of $MgAl_2O_4$, (7) 164*a*.
of γ-MnS, in silicate gels, (9) 239*a*.
from molten oxides, composition diagrams, (8) 193*f*.
nature, from the melt, (9) 241*c*.
phenomenon, single crystal GaAs overgrowth onto SiO_2, (11) 298*i*.
of PrS_2, Nd_2Se_3, and $NdSe_2$, (8), 207*c*.
of rare earth orthoarsenates, (9) 237*f*.
of ruby and sapphire by Czochralski technique, (8) 199*c*.
sampler, P (11) 285*c*.
of silicon on sapphire, (1) 24*b*.
of NaCl-KCl, from melt, (9) 239*b*.
solid state techniques for alumina, (5) 134*b*.
in system Co-V-O, (8) 206*j*.
temperature fluctuations and striations, in flux growth, (7) 168*h*.
of uranium monocarbide, (8) 192*h*.
of vanadate, and properties, (10) 262*a*.
Verneuil process, steady state studies—gas-liquid and liquid-solid interfaces, (8) 207*c*.
of wustite, $Fe_{1-x}O$, (7) 162*j*.
hydrogen ion incorporation in, (3) 86*g*.
imperfections, B (9) 244*e*.
in LiF, MgO, and ruby, (1) 21*c*.
ionic, fission fragment damage, (11) 295*i*.
surface layers, concentration of impurities in, (8) 192*g*.
thermoelectric power: III, heats of transport for potassium chloride, (2) 58*g*.
lattice, defects and activators, role of quality and concentration in catalytic behavior of ZnO and TiO_2—mechanism of photochemical reactions, (1) 28*g*.
dilation, in finely divided MgO, study, (8) 208*b*.
energies, approximate method for calculation, (5) 134*c*.
parameter of LiF, theoretical determination, (8) 209*b*.
parameters, of pure nonstoichiometric compounds, (10) 270*k*.
lattices, B2-type super-, slip-induced directional order theory for, (11) 301*a*.
of unsaturated oxides, metal-to-metal binding energy in, (11) 298*e*.
PbTe, preparation, (10) 263*b*.
lead zirconate-titanate, growth, (3) 87*f*.
Crystals (*continued*)
magnesium-manganese ferrite single, domain structure, (1) 18*c*.
manufacture, P (8) 190*g*.
micro-, orientation and morphology, application of Weissenberg goniometer for determination, (7) 161*j*.
microhomogeneity in Ge single crystals, (1) 23*b*.
mixed, for elastic wave devices, P (3) 77*j*.
molecular, exciton-photon coupling, (1) 18*k*.
mono-. See *Crystals, single*.
oven, P (2) 52*f*.
perfect, theoretical strength, (8) 209*e*.
piezoelectric, evaluator, P (3) 81*k*.
point defects, effect on absorption of high energy electrons, (8) 195*k*.
polishing process, P (9) 213*g*.
purification, (8) 203*e*.
radiation-damaged inorganic, electron spin resonance spectra, B (9) 244*e*.
samarium doped CaF_2 type, chemical studies, (9) 237*a*.
semiconductor compound, P (5) 129*a*.
SiC, method of pulling, P (1) 8*e*.
preparation, (3) 87*g*.
X-ray micrographic study, (11) 303*b*.
single, flux-melt method for growing, having structure of beryl, P (11) 281*c*.
growth, effect of crucible supporting methods on, by Stockbarger method, (2) 49*i*.
methods of making, P (2) 48*f*; P (10) 266*c*.
methods of producing on polycrystalline substrates and devices using, P (10) 265*a*.
nucleation and growth by chemical transport; I, cadmium-germanium sulfide; II, zinc selenide, (1) 24*f*.
orienter, for Norelco diffractometer, (5) 131*f*.
preparation of cubic rare earth tungsten bronzes, (1) 28*c*.
production, P (4) 103*j*.
spheres, technique for obtaining powder patterns, (5) 131*g*.
TiB_2, structure, (11) 298*i*.
size, control, P (3) 77*f*.
NaCl, deformation, (9) 242*f*.
and solid state physics: Vol. I, elastic, piezoelectric, piezooptic and electrooptic constants of crystals, B (11) 305*b*.
specimens, held with polyether-base resin foam during sectioning, (11) 289*j*.
structure, P (11) 285*c*.
of compounds in ternary systems of two transition metals and silicon, (3) 84*j*.
of $Cu_2SO_3{\cdot}CuSO_3{\cdot}2H_2O$, (8) 193*c*.
of disulfide, tetramethylthiuram, (8) 193*j*.
of ErOOH, (8) 194*c*.
of HoOOH, (8) 194*c*.
of $LiNb_3O_8F$, (8) 193*g*.
of Mo_2As_3, (8) 194*e*.
of Mo_2Sb_7, (1) 17*g*.
of Ni_2P_4, (8) 193*j*.
of $NbOPO_4$, (1) 17*h*.
of oxides and their neutron irradiation behavior at 80°C, (1) 17*i*.
of potassium aluminate $K_2[Al_2O(OH)_6]$, (1) 17*a*.
of $K_{0.3}MbO_3$, (9) 237*f*.
of potassium tellurate, (8) 193*c*.
of SiC 39H, (7) 162*a*.
of silver vanadium oxide bronze, new, (8) 193*a*.
of $Na_{0.9}Mo_6O_{17}$, (9) 237*k*.
of $NaNb_3O_{18}F$ and $NaNb_3O_{18}OH$, (8) 193*h*.
refinement, of synthetic pyrope, (1) 27*j*.
of Rh_2Si_3, (8) 193*c*.
of rubidium oxalate monohydrate, (8) 193*e*.
of Ru_4Al_{13}, (8) 193*h*.
of SiAs, (8) 193*i*.
of W_2As_3, (8) 194*e*.
of $VOSO_4$, (8) 194*a*.
of YbOOH, (8) 194*c*.
structures: Vol. 5, B (11) 304*f*.
large, determination by combined X-ray diffraction and electron microscopy, (9) 238*b*.
surfaces, structure and energy: I, formal development, (8) 207*e*.
temperature factors and thermodynamic properties, (9) 242*e*.
thin film, single, method for growing on amorphous substrate, P (11) 286*h*.
transparent, device for orienting, (1) 13*h*.
WO_3, heat treatment, (3) 85*a*.
two-component, method and apparatus for growing, P (11) 286*d*.
YAG, technique for revealing dislocations in, (10) 272*i*.
zinc selenide, defects introduced during growth, (8) 208*a*.
and ZnTe, growing from vapor phase, improved method, (11) 297*e*.
Crystal chemistry, of nephelines and feldspars on Stjernöy, north Norway, (2) 56*d*.
Currents, electric, effect on properties of porous silicate and synthesis of calcium at 20°, 40°, and 60°C, (8) 174*c*.
photo-, characteristics normal to illuminated surface of vitreous selenium, (5) 134*a*.
Curium, oxides, ternary, of type M(III)X(V)O_4, reaction conditions, lattice constants, and chemical properties, (11) 299*j*.
sesquioxide, structural transformation, (8) 207*d*.
Cutting tools. See *Tools*.

Damping, mechanical, in carbon and graphite at low temperature, (2) 55*f*.
Data storage, data projects, continuing numerical, survey and analysis, B (8) 211*j*.
memories, volatile, glass devices for, P (1) 3*j*.
Data storage (*continued*)
memory, nondestructive readout magnetic, P (11) 287*c*.
memory core, ferromagnetic, method of making, P (3) 78*i*.
manufacture, P (11) 286*b*.
method of making, P (4) 101*j*.
Decals. See *Decoration*.
Decomposition, of beryllium hydroxide, preparation for sinterable beryllium oxide, (1) 27*e*.
of CrO_3, topotaxy, (2) 59*c*.
kinetics, of $CaYb_2O_4$, (8) 194*f*.
of nickel oxalate, (1) 21*c*.
of manganese sulfate to form manganous oxide and sulfur dioxide, P (4) 106*j*.
pressure, of boron carbide, (8) 194*g*.
pyrolytic, of manganous oxalate, carbon isotope effects, (8) 192*c*.
of silanes, for deposition mechanism of silica, (10) 262*j*.
of zinc oxalate, carbon isotope effects, (8) 192*d*.
radiation-induced, of some inorganic sulfates, B (9) 244*f*.
radiolytic, of crystalline alkali metal and alkaline earth bromates, B (9) 244*c*.
of sulfates, (5) 136*d*.
thermal, of brucite: I, electron and optical microscope studies, (1) 20*j*; II, kinetics in vacuum, (2) 58*a*.
of cobaltous acetate tetrahydrate, (4) 111*c*.
of dibasic calcium orthophosphate, electronic paramagnetic resonance study, (11) 295*b*.
of dye-clay mineral complexes, (2) 58*b*.
effect on morphology and texture of chrysotiles, (11) 293*i*.
of gamma-irradiated barium azide, B (9) 244*d*.
of hydrated UO_3, (2) 58*d*.
of irradiated mercuric oxalate, B (9) 244*c*.
of irradiated nickel oxalate, (8) 209*g*.
kinetics, of calcium hydroxide, (1) 21*g*.
kinetics of pyrite, (3) 86*a*.
of magnesium chromate, (4) 111*d*.
of NbO_2F, (8) 209*g*.
of osmium trichloride, (8) 209*i*.
of oxalates: III, decomposition and surface properties of zinc oxalate, (8) 209*h*.
of sulfates, for manufacture of ferrite powders, (10) 262*g*.
of xenotime, by sulfuric acid process, (3) 82*g*.
of zinc sulfate, influence of selected sulfides on rate at 600°C, (8) 200*e*.
Decoration. See also *Art and artware; Color; Engobes; Glazes*.
ceramic painting step by step, B (3) 88*e*.
gold, on glass, (10) 250*i*.
machine, or printing, articles of ware, P (1) 9*c*.
method and apparatus, including flexible conductive offset member, P (1) 5*e*.
of pottery with clay, slip and glaze, B (8) 212*a*.
resistant to detergents, (7) 154*g*.
screen, P (2) 40*c*.
apparatus, P (7) 150*e*.
of semicrystalline bodies, P (8) 177*j*.
tumbler beader, P (2) 40*c*.
underglaze, stick figures for, (5) 116*a*.
De-enameling. See *Enameling*.
Defects. See also *Crystals; Enameling; Enamels; Glass; Structure*.
detection, nonvisible penetrant methods of, and apparatus, P (11) 289*j*.
Frenkel, kinetics of recombination in anodic oxide films on tantalum, (7) 164*i*.
method of and testing agent for, P (3) 81*g*.
point, in binary compounds, (9) 241*d*.
Deflocculants. See *Electrolytes*.
Deflocculation. See *Dispersion*.
Deformation, around pressure cracks on diamond, (8) 203*a*.
bending beam, for viscosity investigations, (10) 254*d*.
bending from surface stresses in aluminum nitride thin crystals, measurements, (1) 22*d*.
of corundum during sintering, (10) 257*b*.
determination, in cast and cermet materials, (2) 50*g*.
firing, of ceramic bodies, (7) 163*f*.
high temperature, of ceramic materials, apparatus for measuring, (8) 187*d*.
of iron and copper oxides, at high temperatures, (2) 56*b*.
of MgO, generation of vacancies from, (4) 108*d*.
mechanisms, in polycrystalline graphite, (11) 293*i*.
of NaCl crystals, potential difference from, (8) 205*b*.
plastic, during cleavage of LiF, (7) 166*d*.
of polycrystalline transition metal carbides, (7) 162*a*.
of porcelain, effect of glaze composition, (3) 73*j*.
produced by compression of NaCl crystals along [011], (9) 242*f*.
properties, of polycrystalline KCl-NaCl alloy, (3) 84*g*.
of solids at very high temperatures, (8) 199*e*.
of standard prisms, measurement with elastograph, (7) 146*g*.
Dehumidifiers. See *Dryers*.
Dehydration, belt, P (2) 49*j*.
of gypsum, P (9) 235*f*.
of kaolinite, new method for determining enthalpy and entropy, (11) 298*d*.
of sheet glass, internal friction studies, (9) 218*e*.
thermal, of gypsum, infrared spectroscopic investigations, (8) 200*g*.
of silica gel, and porosity influence on content of structural water, (1) 19*g*.

Dehydroxylation. See *Decomposition, thermal.*
Delay line, single crystal quartz, P (7) 158*d*.
variable, P (2) 49*f*.
Densification, of carbonaceous bodies, P (9) 226*g*.
measurement during drying and firing of ceramic bodies, (5) 131*g*.
of soda ash by vapor hydration, P (7) 160*i*.
of titanium diboride, (8) 179*j*.
Density, bulk, of granular refractories determined by arrested absorption, (8) 179*j*.
measurement by γ-ray absorption of refractories, (2) 41*c*.
of packed particles, (10) 266*b*.
of refractory insulating brick, (2) 41*e*.
of ceramic oxides, during vibrational compaction, influence of frequency and acceleration, (7) 151*e*.
of cesium and thallium silicate glasses, (11) 277*d*.
changes in sodium borate glasses subjected to high pressure, (10) 252*h*.
comparator, Cartesian diver, (10) 267*a*.
of cord glasses at high temperatures, (10) 251*f*.
determination, of glass particles by a density gradient method, (2) 36*i*.
of refractories by gamma-radiation absorption measurement, (9) 223*g*.
dislocation, effect on low-frequency noise in germanium, (10) 262*f*.
relation to flow stress in materials deforming by Pierls-Nabarro mechanism, (10) 271*g*.
of glass, change by heating: VIII, comparative studies on glass transition characteristics of organic and inorganic glasses, (7) 148*c*.
of liquids and solutions, means for measuring, P (10) 268*d*.
measurements at high temperature, defects in PuO_{2-x}, (1) 17*c*.
of molten fluorides, system NaF-LiF-ZrF_4, (7) 162*b*.
nomograph, for powder compacts, (7) 169*h*.
of pure nonstoichiometric compounds, (10) 270*h*.
orthobaric, of pentachlorides of niobium and tantalum, (8) 204*d*.
radiant flux, calculation through focal zone of solar furnace, (5) 134*h*; (5) 137*c*.
of SiO_2-Si interface states, (5) 135*a*.
of $Na_2O \cdot B_2O_3$ and $Na_2O \cdot SiO_2 \cdot B_2O_3$ melts at 1300°C, (2) 38*e*.
surface charge, at silicon-silicon dioxide interface, effect of orientation, (11) 294*b*.
of thin evaporated aluminum films, (1) 17*d*.
variations in concrete cores, cubes and beams, radioactive method for measuring, (2) 51*c*; discussion, (11) 274*i*.
Dental ceramics, apparatus, for compaction of porcelain powders, P (1) 9*a*.
impression materials, P (3) 74*j*.
siliceous filling, P (10) 261*g*.
Deposition, cataphoretic, of luminescent materials, (8) 185*b*.
co-, mechanisms, of aluminas with electrolytic copper, (7) 165*c*.
device, vapor, P (8) 186*d*.
electro-, for coating *p*-type germanium with antimony, lead, or alloys, and product, P (9) 231*d*.
electrolytic, of actinide oxides, P (8) 181*a*.
electrostatic, of parting materials in method of bending superposed glass sheets, P (10) 255*a*.
film, magnetic control, P (9) 231*c*.
multiple slice epitaxial, of silicon in resistance heated furnace, (4) 100*i*.
of silica films, (4) 100*i*.
of silica thin film capacitors by glow discharge techniques, (9) 229*i*.
of Ta, Ta_2O_5 and TaN with controlled electrical characteristics, (2) 54*f*.
vacuum, of ferrite films by arc discharge, (11) 284*f*.
for forming superconductive niobium films, P (9) 231*d*.
specimen holder, for electron microscope operating at 10^{-8} torr, design, (11) 289*c*.
vapor, apparatus for producing pure semiconductor material by, P (11) 284*h*.
of KBr, (9) 240*b*.
of silicon, apparatus, P (11) 284*h*.
Design. See also *Art and artware; Decoration.*
Desorption, thermal, of inert gases ionically pumped into glass, (9) 218*i*.
Detectors. See also *Tubes, electron.*
electrochemical linear, and porous electrode, P (3) 78*c*.
properties of photon-modulated tunneling, (10) 262*c*.
pyroelectric infrared radiation, (9) 229*h*.
scintillation, comprising transparent tin-activated calcium iodide scintillator, P (4) 102*b*.
semiconductor-metal-semiconductor light, (10) 263*g*.
thin window drifted silicon charged particle, method of forming, P (7) 157*d*.
Devitrification, of high-silica glasses, effect of nitriding, (7) 148*f*.
of Li_2O-B_2O_3-SiO_2 glasses and Li_2O-Al_2O_3-B_2O_3-SiO_2 solder glasses, differential thermal analysis and X-ray diffraction study, (9) 217*h, j*.
of titanate glasses subjected to cosmic rays, (9) 217*g*.
Dewatering. See *Water, removal.*
Dewetting. See *Wetting.*
Diamonds, in abrasive wheels. See *Grinding apparatus.*
/bond system, coated, grinding with, (2) 33*f*.
compact abrasives, P (5) 115*h*.
crystal surfaces, clean, friction of, (11) 296*c*.
frictional anisotropy, (11) 296*g*.
crystals, pattern diamond growth on, P (5) 128*d*.
Diamonds (*continued*)
deformation around pressure cracks on, (8) 203*a*.
doping process, in gaseous electrical discharge, P (8) 185*j*.
elongated needlelike, with electrically conductive properties, preparation, (7) 145*h*.
-faced articles, method of making, P (5) 115*i*.
growing on diamond seed crystal, P (4) 103*g*.
impact strength, under different rates of strain, (8) 199*h*.
method for synthetically making, P (10) 247*g*.
milling cutters, P (5) 115*k*.
nitrogen center in, electron nuclear double resonance study, (11) 295*b*.
particles, process of infiltrating with metallic binders, P (3) 63*f*.
preparation, graphite-catalyst charge assembly for, P (8) 173*i*.
synthesis, P (9) 213*g*.
from liquid carbon, flash heating apparatus for, P (10) 266*h*.
synthetic, transmission electron microscopy, (8) 210*f*.
tool, method of preparing, P (2) 33*i*.
wheel, for space age ceramics, (7) 145*g*.
Diaspore, late, in orthonorite containing spinel xenoliths at Mill of Boddamm, Insch, Aberdeenshire (Scotland), (3) 87*d*.
refractory raw material, (3) 71*f*.
Dicalcium silicate. See *Calcium.*
Dielectrics. See also *Ferrites; Ferroelectricity; Ferroelectric materials; Ferromagnetism; Ferromagnetic materials; Glass; Porcelain, electrical; Steatite; Titanates; Whiteware.*
aging and microstructure in $BaTiO_3$-$CaTiO_3$ system, (1) 9*g*.
barium titanate, P (9) 230*g*.
effect of grinding time on dielectric properties, (1) 9*g*.
body, tubular, for adjustable capacitor, P (2) 47*f*.
boron nitride, in electrical capacitor, P (1) 10*b*.
ceramic, P (10) 263*c*.
composition having anticorona properties, P (9) 230*c*.
with conductive portions, and method of making, P (4) 100*j*.
constant measurements by reflectometer, (1) 13*j*.
constants of cupric phosphate and manganese sulfate, (9) 238*c*.
devices, P (8) 184*g*.
electrode-, interactions at high temperatures, (2) 47*a*.
investigation of $PbTiO_3$-$BaZrO_3$ system, (9) 230*c*.
isolation for monolithic circuit, P (8) 184*h*.
loss, in CaF_2 doped with oxygen ions, (11) 293*a*.
of polycrystalline material produced from glass of system Li_2O-MgO-Al_2O_3-SiO_2, (4) 93*g*.
spectra, of corrosion films on zirconium, (4) 100*e*.
losses, low frequency, in NaCl and NaBr thin films, (1) 21*g*.
materials, ceramic, P (8) 184*d*.
metal-, interfaces, barrier lowering and field penetration, (8) 183*c*.
progress: Vol. 6, B (11) 305*f*.
properties, of alumina, recent Soviet work, (9) 229*i*.
of alumina, review, (9) 229*i*.
of glasses in systems composed of TeO_2 and some phosphates, (5) 118*e*.
of high permittivity ceramics, (7) 155*i*.
of porcelain under high alternating fields, (8) 182*h*.
of SiO_2 and lead tellurium oxide glass films formed by reactive sputtering, (1) 9*g*.
of strontium titanate solid solutions containing niobia, (9) 229*c*.
research, (1) 10*e*.
strength, (11) 284*j*.
and waves, B (8) 212*b*.
window surface, method for reducing electron multipactor on, P (10) 261*i*.
Dies. See also *Extrusion.*
design, for making curved clay pipes, (3) 70*c*.
Differential thermal analysis. See *Thermal analysis.*
Diffraction. See also *Electron diffraction; Neutrons; X rays.*
contrast from elastic shear strains due to coherent phases, (8) 194*i*.
multiple electron, application to evaporating UO_{2+x}, (8) 202*i*.
neutron, investigation of WO_3, (8) 203*g*.
pattern, diffuse streak, of electron and X rays due to low frequency optical mode in tetragonal $BaTiO_3$, (9) 238*d*.
random powder, preparation of montmorillonites for, (1) 14*c*.
ultrasonic, for modulation of 10.6 μ laser radiation, (10) 271*e*.
X-ray, combined with electron microscopy for determination of large crystal structures, (9) 238*b*.
demonstration by LiF using Mn $K\alpha$ rays resulting from ^{55}Fe decay, (9) 237*j*.
of ion-exchanged type A molecular sieves, (9) 235*f*.
study of devitrification of Li_2O-B_2O_3-SiO_2 glasses and Li_2O-Al_2O_3-B_2O_3-SiO_2 solder glasses, (9) 217*h, j*.
Diffractometers. See also *Electron diffraction; X rays.*
Norelco, single crystal orienter for, (5) 131*f*.
optical, laser as light source, Fourier analysis of electron micrographs, (1) 13*j*.
X-ray powder, improved slits, (1) 13*h*.
Diffractometry, high pressure, innovations and observations, (5) 131*f*.
Diffusion, anomalous, of boron into silicon grain boundary, (11) 292*h*.
in beryllium oxide, (8) 194*f*.
of calcium in magnesium oxide, (8) 194*d*.
of carbon in tantalum monocarbide, (9) 238*e*.
coalescence, of pores in crystalline solids with boundary lattice, (5) 135*f*.
coefficient of water in water and alkaline earth chloride solutions at 25°C, (1) 18*a*.
coefficients, tracer, of alkali ions in fused alkali nitrates, (8) 201*a*.
continuous gas, method, P (1) 11*c*.
counter, of gases, in graphite, effect of back pressure, (7) 151*i*.
in defect crystalline solutions in systems CaF_2-YF_3 and NaF-LiF-MgF_2, (8) 194*h*.
donor, into GaAs from group VI compounds, (11) 293*e*.
gold, in SiO_2 and Si using MOS structure, (8) 198*i*.
of gold into silicon crystals, (9) 238*g*.
of H_2-H_2O through porous iron formed by reduction of hematite, (9) 238*g*.
-induced imperfections in silicon, (9) 238*h*.
inter-, in two-component mixture of powders of different degrees of dispersion, (3) 86*j*.
interionic, coefficients in molten silver nitrate-sodium nitrate mixtures, measurement by diaphragm-cell method, (8) 194*c*.
of ions in glass, (8) 175*c*.
lattice effect, method of separating from grain-boundary effects in polycrystalline materials, (3) 86*i*.
metallic film, for boundary lubrication, P (8) 181*h*.
Nb_3Sn layers, production, P (1) 11*d*.
of *n*-type impurity into intermetallic semiconductor body, P (8) 184*i*.
of neon, in glass melt, (11) 276*g*.
of open-hearth slags in basic refractories, (7) 151*h*.
open-type, in semiconductor by gaseous phase, P (8) 186*a*.
in oxides, (5) 135*f*.
oxygen-ion, in hematite, (1) 24*d*.
in porous silica glass, effects of adsorption, (8) 175*j*.
for producing semiconductors, P (7) 157*i*.
for production of semiconductor elements, P (7) 157*i*.
profiles, process for determination in semiconductor bodies, P (5) 128*g*.
properties of chalcogenides of transition metals: III, self-diffusion of nickel in nickel oxide, (1) 20*a*.
reaction, in systems metal-compound gas: VI, system tungsten-carbon-nitrogen, (1) 20*c*.
in system Mo-Si, (4) 109*b*.
parameters, of boron and carbon in refractory transition metals, (1) 24*i*.
selective, from impurity source, method, P (3) 79*f*.
self-, of beryllium in polycrystalline beryllium oxide, (9) 242*e*.
coefficient, of uranium hexafluoride [at 0° to 70°C], measurements, (7) 165*i*.
in molten lead and thallous chlorides, (7) 167*f*.
of oxygen in Y_2O_3 and Er_2O_3, (3) 88*a*.
of semiconductors, P (4) 102*a*.
simultaneous double, process, P (5) 129*b*.
of sodium-22 in molten sodium nitrate at constant volume, (8) 194*h*.
in NaCl-$ZnCl_2$ system, (8) 194*f*.
in system molten sodium iodide-potassium chloride, (8) 194*i*.
trace-ion, in molten alkali carbonates, (11) 302*g*.
of unlike ions into liquid sodium chloride, (8) 194*i*.
unsteady state, with variable diffusion coefficient, effect of bulk flow, (7) 162*e*.
in uranium monocarbide, (8) 194*j*.
of water in concrete at temperatures between 50° and 95°C, (3) 64*b*.
Diffusivity, data, on formation of niobium carbide surface films, (11) 293*b*.
of oxygen in solid iron, (10) 250*g*.
thermal, of $Ca_xBa_{1-x}TiO_3$, (7) 169*c*.
determination for polycrystalline graphites as function of temperature, (2) 54*h*.
measurements on metals and oxides at high temperatures, (2) 51*i*.
Dilatometers. See also *Expansion.*
analysis, thermal evolution of CPAC portland cement pastes at 25° to 1000°C, (2) 34*a*.
Dilatometry, double, of clays, kaolins, and ceramic bodies, (11) 289*f*.
Dinnerware. See also *Art and artware; Pottery; Whiteware.*
crockery, canteen, new shape, (7) 146*a*.
method for suspending during glaze firing, P (11) 283*h*.
for today's brides, (4) 89*j*.
Diodes. See also *Tubes, electron; Rectifiers.*
barrier, with metal contact, method of making, P (3) 77*d*.
diffused junction, of PbSe and PbTe, (4) 100*c*.
glass encapsulated, means and method of sealing, P (7) 156*h*.
GaAs, efficient electroluminescence at 300°K, (9) 229*d*.
n-GaAs bulk, switching and low-field breakdown, (9) 230*c*.
injection luminescent and light sensitive, with common *n* region, for photoelectronic semiconductor devices, P (2) 48*h*.

Diodes (*continued*)
laser, with metal contacts plated over sides of semiconductor, P (8) 184*j*.
low capacitance planar, P (8) 185*a*.
low voltage semiconductor reference, P (11) 285*j*.
method of forming, with high resistance substrate, P (5) 127*j*.
p-type germanium tunnel, fabrication aspects, (11) 284*e*.
passivated alloy, P (3) 79*h*.
semiconductor, with integrated mounting and small area fused impurity junction, P (4) 102*e*.
lithium-ion drift, method for production, P (10) 264*i*.
and method of making, P (7) 158*b*.
radiant, P (3) 79*e*.
silicon, method of making by alloying indium with *p*-type silicon to produce *pn* junction, P (2) 48*b*.
with solder composition attaching ohmic contacts, P (10) 265*d*.
structure in semiconductor integrated circuit, and method of making, P (10) 263*d*.
surface-barrier, for detecting high energy particles, and method of preparing, P (8) 186*a*.
symmetrical switching, method of making, P (4) 102*a*.
thin film, manufacture, P (11) 288*b*.
tunnel, P (7) 158*b*.
method of producing by double alloying, P (1) 11*h*.
with tunneling characteristic at reverse bias, P (1) 12*a*.
variable-capacitance point contact, P (5) 129*e*.
zener, element of low junction capacitance, P (3) 79*i*.
Disintegrators. See *Crushing apparatus*.
Dislocations, in cleaved MgO, (2) 54*i*.
clusters, formation during sintering of calcium fluoride, (8) 198*c*.
densities, errors measured by thin film electron microscopy, (8) 209*f*.
effect on properties of refractory oxides, (11) 293*d*.
of elementary atomic layers in strained carbon between 1000° and 2000°C, (2) 54*i*.
etch pits, in β-SiC, (3) 87*d*.
etch tunnels in quartz crystals, (8) 194*j*.
in impurity-doped aluminum oxide, (8) 196*j*.
in lithium fluoride, B (3) 88*g*.
loops, annealing by climb, (8) 191*f*.
model of creep, (9) 243*f*.
nonbasal, in sintered alumina, direct observation, (10) 270*i*.
nucleation, in sodium chloride crystals, (8) 195*a*.
in SiC crystals, X-ray study, (10) 272*h*.
sites, in BeO, (4) 107*i*.
in NaCl type crystals, atomic mechanisms for transport of charge by, (8) 191*a*.
Dispersion, anomalous, of tetragonal barium titanate, (7) 166*c*.
of asbestos, P (4) 107*a*.
dispersed, finely, substances, method and device for production, P (3) 80*e*.
dispersing apparatus for solid particles in a liquid, and method, P (10) 266*b*.
hardened materials, production, P (2) 45*k*.
infrared dielectric, of $LiNbO_3$, (8) 183*j*.
phonon, relation for magnesium oxide, (7) 166*a*.
of pigments in liquid medium, apparatus, P (10) 266*c*.
process, P (11) 288*k*.
ultrasonic, of clay bodies, (3) 80*b*.
Dissolution. See *Solutions*.
Distortions, crystal, of sericite, (5) 134*i*.
crystal, in VO_2, (9) 237*c*.
Distribution, grain-size for certain metamorphic minerals in relation to nucleation and growth, (1) 19*g*.
molecular weight, calculation from sedimentation equilibrium data, (7) 162*f*.
Dolomite. See also *Refractories*.
Dankovsk, firing in rotary kiln, (9) 224*d*.
dead-burning process, P (5) 124*j*.
distinguished from limestone by bromophenol blue, (5) 130*j*.
-insoluble residue relationships in Ten Mile Creek dolomite near Toledo, Ohio, (4) 107*j*.
mineralogical studies, (5) 119*f*.
mutual solubility of MgO and CaO in, calculation, (3) 80*j*.
particles, dissolution in primary glass melts, (3) 66*c*.
plaster. See *Plaster*.
raw, empirical methods of evaluating suitability for use in steel melting furnaces, (8) 180*b*.
slagging, system iron(II) oxide-calcium oxide-magnesium oxide as basis for determination of, (3) 64*e*.
stabilized sintered, process for manufacture, P (4) 107*b*.
Drills, bladed bur diamond, dental bur, P (7) 145*f*.
Dry pressing. See *Pressing*.
Dryers. See also *Drying*.
ceramic, charging and discharging installation, P (11) 280*b*.
for ceramic bodies, (9) 234*k*.
continuous, for ceramic products, P (2) 52*d*.
gas, P (5) 132*e*.
installation, B (5) 142*e*.
method and means for ensuring uniform flow of material through, operating on fluidized bed principle, P (2) 53*d*.
radiation, for drying floor tile, (3) 73*i*.
spray, for solutions, emulsions, and suspensions and for heat treatment of dried material, P (3) 80*d*.
Drying. See also *Dryers*.
air, with activated alumina under adiabatic conditions, (4) 103*e*.
apparatus, P (2) 52*k*.
ceramic ware, (4) 105*c*.
clay products, and apparatus, P (11) 290*b*.
clays, apparatus for measurement of moisture, (2) 53*g*.
claywares, B (8) 212*b*.
continuous, of ceramic products, P (11) 290*h*.
of granular materials, P (1) 14*h*.
flatware, new development, (9) 228*h*.
floor tile, in radiation dryers, (3) 73*i*.
glass sand, fluid process, (2) 52*g*.
granular materials, P (1) 13*a*.
hydrogel, method, P (3) 83*e*.
pottery, method and apparatus, P (11) 290*e*.
rapid, of ceramic batches, new homogeneous vaporizer unit, (2) 52*h*.
of refractory clays in shaft mill, combined with grinding, (5) 122*j*.
solids, method and means, P (8) 190*b*.
spray dried bodies, properties for dry pressing, (5) 129*h*.
wet pulverulent material in gaseous path, method and apparatus, P (11) 288*h*.
Durability, of soda-lime bottles, (10) 251*d*.
Dust. See also *Air, pollution; Particles; Powders*.
cement kiln, chemical and mineralogical composition, (7) 146*e*.
control measures in McIntyre assay dept., (4) 112*k*.
feeding means, P (2) 50*b*.
-separating apparatus, P (4) 103*f*.
separation, electrical, P (2) 50*c*.

Earthenware, bodies after firing, research on methods of detecting heterogeneities, (5) 131*d*.
bodies, use of amblygonite, (7) 155*g*.
Education, Hrazany Summer School proceedings, B (4) 114*a*.
Efflorescence, in clay products, (2) 40*e*.
Elasticity. See also *Anelasticity*.
constants, room temperature, of single crystal U_4O_9, (8) 206*d*.
of synthetic single crystal corundum, (2) 54*j*.
elastic limit, of sintered alumina bodies at room temperature, under local compression, (2) 41*i*.
elastic wave attenuation in lithium niobate, (9) 238*a*.
elastic wave and infrared light interactions with moving high-field domain in piezoelectric semiconductor, (11) 294*a*.
elastic waves, surface, direct piezoelectric coupling to, (3) 75*f*.
elastograph, for measurement of standard prisms deformation, (7) 146*g*.
of enamels, measurement, (9) 216*i*.
high-temperature, of forsterite and steatite, (7) 164*e*.
moduli, macroscopic shear, relation with micromechanical shear stress concentrations of multicomponent materials, (7) 167*i*.
of refractories, practical determination, (2) 42*h*.
modulus, of bar specimens, device for measuring, (9) 234*c*.
C_{33}, of highly oriented pyrolytic graphite, effect of fast neutron irradiation, (8) 195*g*.
dependence on structure of alkali borate glasses, (3) 66*a*.
of refractory materials for furnace and kiln construction, importance, (8) 179*j*.
of sintered tungsten carbide-cobalt alloys, (3) 85*h*.
of stabilized zirconia, (5) 135*c*.
uses for materials testing, (2) 42*f*.
photoelastic study, of internally stressed circular opening in biaxial stress field, (1) 26*g*.
photoelastic tensors, new technique for measuring magnitudes, and application to lithium niobate, (8) 203*a*.
photo-, of principal normal stresses and inversion temperature in compressed glass lead-through seals, (10) 253*c*.
properties, of trigonal selenium single crystals, (5) 135*c*.
of two-phase ceramic bodies, (2) 58*h*.
of uranium oxides at room temperature, (3) 85*i*.
viscoelastic materials, Poisson's ratio, (10) 267*a*.
wave, devices utilizing mixed crystals or potassium tantalate-potassium niobate, P (3) 77*j*.
propagation in single-domain ferroelectric lithium tantalate, (5) 135*j*.
Young's modulus, of graphite by flexural sonic waves, (2) 42*c*.
and internal friction of $5SrTiO_3 \cdot 3La_{2/3}TiO_3$ below 100°C., (1) 16*j*.
Electric arcs, ceramic arc plates having minimum density variations, P (2) 47*i*.
process for forming high melting point compounds, P (9) 230*f*.
Electrical components, glass capsules for, method of making, P (1) 6*c*.
making holes in, by vaporization, P (9) 230*e*.
method of making, P (9) 231*f*.
Electric resistors. See *Resistors, electrical*.
Electrical ceramics. See also *Electronics*.
nonlinear material, P (3) 75*c*.
and process of making, P (3) 74*i*.
progress, (7) 155*i*.
Electrical conductivity. See *Conductivity, electrical*.
Electrical properties, of alkaline earth aluminosilicate glasses, (10) 251*g*.
of alumina at high temperatures, (3) 85*b*.
Electrical properties (*continued*)
of Al_2O_3-nickel metal multilayer flame-sprayed coatings, (1) 2*k*.
of copper manganite, (9) 238*d*.
of doped $LaInO_3$, (9) 229*e*.
of electroviscous fluids, (7) 163*h*.
of epitaxial gallium arsenide, effect of orientation, (3) 85*d*.
of epitaxial germanium films vacuum deposited on semi-insulating GaAs up to thicknesses of 10^4A, (4) 100*f*.
of glass, B (4) 113*g*; B (9) 245*b*.
of glasses in system V_2O_5-CdO-P_2O_5, (8) 176*i*.
of graphite at high temperatures, (3) 84*h*.
of HfO_2, (7) 163*b*.
of $Li_xNi_{1-x}O$ single crystals, (9) 238*e*.
of $Ni_{(1-x)}Li_xO$ single crystals, (7) 163*c*.
of $Ni_{(1-x)}O$ system, (5) 135*f*.
of nonstoichiometric UO_2, (11) 294*b*.
of *p*-type ZnTe showing injection electroluminescence, (11) 294*d*.
of rare earth compounds and alloys, (3) 85*c*.
of R_2O-RO-PbO-SiO_2 glass, effects of crystallization, (7) 148*f*.
of $SrFeO_3$-$BiFeO_3$, (1) 9*i*.
of titania-containing polycrystalline semiconductors, correlations with structure properties, (1) 9*i*.
of TiO_{2-x} diffusion layers in Ti, (3) 85*d*.
of transition metal carbides of fixed composition and homogeneity domain of groups IV and V to 2500°C, (3) 87*d*.
of transition metals, effect of nonmetallic atoms, (3) 85*d*.
of UO_2, (9) 238*k*.
of $(0.13YO_{1.5}$-$0.87ThO_2)$ electrolyte, (5) 135*f*.
Electrical resistance. See *Resistance, electrical*.
Electrochemistry. See also *Corrosion*.
electrochemical devices, inert electrodes for, P (7) 147*j*.
electrochemical method, for study of kinetics of cement hardening, (4) 91*a*.
of electrolytes, molten and solid, B (1) 30*j*.
Electrodes. See also *Heating elements*.
active iron: I, iron dissolution and hydrogen evolution reactions in acidic sulfate solutions, (9) 237*d*.
alloying, to semiconductor bodies, P (7) 157*j*.
for arc welding, P (7) 147*h*.
bismuth, in molten lithium chloride-potassium chloride, kinetic study, (8) 201*f*.
calcium, method for measuring dissociation and solubility of calcium sulfate dihydrate, (10) 266*i*.
calcium-selective, with liquid ion exchanger, (9) 233*i*.
carbon or graphite, method of screw connecting, P (9) 226*a*.
catalyzed carbon, production, P (8) 182*c*.
ceramic, in fuel cell, P (4) 101*g*.
ceramic materials for MHD generators, (2) 46*i*.
connections to potassium tantalate-niobate, plasma glow method for making, P (9) 231*g*.
consumable, device for suspending and applying melting current, P (7) 160*f*.
copper-lead, for determining setting time of cement paste, mortar and concrete, (9) 214*c*.
counter-, manganese oxide, use in thin film capacitors–the TMM capacitor, (5) 126*i*.
-dielectric interactions at high temperatures, (2) 47*a*.
for electrochemical logarithmic detector units, P (4) 101*c*.
fuel cell, P (2) 44*a*.
new methods of obtaining: III, oxygen powder electrode, (5) 126*h*.
glass, apparatus and process for making, P (5) 120*a*.
for hydrogen and other cations, principles and practice, B (9) 245*g*.
with metal frame support, and method of making, P (11) 278*a*.
and method of making, P (2) 38*g*.
selective for sodium, properties, (10) 253*d*.
sodium-aluminum-silicate, silver ion response of, (11) 277*b*.
glass membrane, for measurement of cation concentration in molten salts, (3) 66*h*.
graphite, method for producing, P (1) 8*d*.
head, water cooled, for electric furnace electrodes, P (10) 269*b*.
inert, for electrochemical devices, P (7) 147*j*.
light transmitting, including *n*-type semiconductive In_2O_3, P (3) 78*a*.
method for alloying with semiconductive body, P (9) 231*d*.
potentials in fused systems: VII, effect of ion size on membrane potentials, (7) 163*e*; X, measurement of cation concentration in molten salts using glass membrane electrodes, (3) 66*h*.
semiconductor device, method of making conductive connection, P (5) 128*a*.
sintered, P (1) 11*i*.
method of producing, P (9) 226*j*.
system, for measuring electrical resistivity of porous rock sample, P (4) 104*i*.
transition metal oxide-metal, preparation, (10) 263*c*.
for use in electrochemical devices, method of treating, P (9) 226*c*.
Electroanalysis. See *Analysis*.
Electroceramics. See *Electric ceramics*.
Electrochromatography. See *Chromatography*.
Electroluminescence. See *Luminescence*.
Electroluminescent materials. See *Luminescent materials*.
Electrolysis, of high-silica glass, effect of nitriding, (7) 148*f*.

Electrolytes, action on strength of granules in cement charge, (10) 247*i*.
halogen fluoride, in electrochemical cells, (7) 163*c*.
MnO, derived from permanganic, for capacitor, P (8) 185*b*.
molten and solid, electrochemistry, B (1) 30*j*.
non-, solutions, adsorption from, on porous 96% silica glass, (8) 175*b*.
oxygen free, for use in doping and contacting semiconductor bodies, P (9) 232*f*.
$(0.13YO_{1.5}\cdot 0.87ThO_2)$, electrical properties and defect structure, (5) 135*f*.
zirconia, stabilized, in fuel cell, P (4) 101*h*.
-containing, in fuel cell, P (4) 101*g*.
Electrolytic, apparatus for treatment of glass beaded tips, P (1) 10*b*.
treatment, of quartz, P (11) 285*h*.
Electromagnets. See *Magnets*.
Electromechanical properties. See *Mechanical properties*.
Electromotive force, thermal, in electrotechnical porcelain, (5) 125*i*.
thermal, of tungsten, molybdenum and tantalum, effect of highly refractory oxides in vacuum at 1500°C, (7) 151*i*.
Electron diffraction, of Al_2O_3-KI, (2) 55*b*.
from crystal defects–Fraunhofer effects from plane faults, (8) 196*i*.
failure of first Born approximation: I, UF_6, (8) 197*i*.
for investigating structure of tantalum suboxides $TaO_{2\pm}$-(Ta_2O_5), (11) 297*d*.
patterns, diffuse scattering in, (1) 17*j*.
study and theory, of transformation from γ-Fe_2O_3 to α-Fe_2O_3, (5) 135*i*.
of synthetic corundum crystals: II, dislocations and grain boundaries in impurity-doped aluminum oxide, (8) 196*j*.
Electron probes, micro-, of some single crystal hexagonal ferrites, (9) 240*i*.
to study grain-boundary reactions in magnesia-chrome refractories: II, (1) 7*e*.
Electron tubes. See *Tubes*.
Electronic equipment, assemblies, making by bonding materials of different thermal expansion coefficient, P (5) 128*c*.
automatic +X-axis detector, marker, sorter, and collector for quartz crystal wafer blanks, P (8) 184*a*.
bonded metallic and metallized ceramic members, and method of making, P (2) 47*h*.
at Centralab for future business, (1) 9*g*.
ceramic loaded buncher for linear accelerators, P (11) 285*a*.
circuit component, and method of making, P (8) 184*j*.
circuit module, hermetically sealed thin film, P (8) 184*g*.
circulator, ferrite stripline, with closed magnetic loop path and centrally located conductive foil, P (10) 263*j*.
component package, P (7) 156*j*.
components, plated packaging for, P (8) 185*h*.
device, with closely spaced electrodes, and method of making, P (3) 78*b*.
enclosed, P (11) 285*i*.
for forming negative ions from iodine gas and lanthanum boride contact ionizer surface, (11) 285*d*.
packaged, P (8) 185*e*.
devices, glass-to-metal seals in, P (5) 137*e*.
tellurium thin film field effect solid state, P (3) 79*h*.
direct viewing storage target and fluorescent screen display structure, combined, P (11) 285*a*.
discharge device, P (3) 78*f*; P (2) 47*h*.
glow, with parallel permanent magnetic rod electrodes, P (10) 264*b*.
with grain oriented dispenser thermionic emitter, P (3) 78*j*.
high pressure, having electrodes with thorium on exposed surface, P (8) 184*h*.
high pressure, with fill including iodine, mercury, and rare earth metal, P (10) 264*c*.
low pressure gas-filled, with ceramic insulating members, P (11) 285*j*.
dosimeter, miniature radiation, method of manufacture, P (11) 286*d*.
neutron, of nickel oxide with lithium as impurity, P (8) 185*c*.
electrical device, with casing seal members comprising cavity in meeting surface, P (4) 101*b*.
electroluminescent device, with plurality of closely spaced thin wire conductors, P (3) 78*d*.
electroluminescent display device, with piezoelectrical scanning and gating means, P (3) 78*d*.
element, cryogenic Hall-effect semimetal, P (5) 127*g*.
encapsulated electrical component, P (7) 156*c*.
encapsulated impedance element, P (5) 127*j*.
epitaxial field-effect device, isolated, method of making, P (3) 78*j*.
ferrite memory cells and matrices, P (8) 184*b*.
frequency standard, passive gas cell, P (8) 185*f*.
heat sinks in packaging, plasma-sprayed dielectric coatings for, (10) 263*b*.
helical wave structure, coupled, employing remanently magnetized ferrite, P (7) 156*a*.
heterojunction device, thin film, P (10) 265*i*.
igniter, high voltage, with fluid feed through $[Al_2O_3]$ insulator core center, P (10) 264*d*.
integrated circuit device, and method, P (10) 264*e*.
magnetic memory device, method of preparing, P (8) 185*a*.
Electronic equipment (*continued*)
microcircuit wafers, method for simultaneous production of plurality of, P (10) 264*j*.
microwave power limiter, utilizing planar ferrite sphere, P (8) 185*c*.
multiplier component, multichanneled electron, method of making, P (10) 264*b*.
photosensitive device, using glass of arsenic, sulfur and halogen, and method of using device and making glass, P (8) 185*g*.
pnpn device, method of making by diffusing, P (8) 185*g*.
solid state device, field effect, having partially insulated electrode, P (5) 127*c*.
solid state devices, method and apparatus, P (9) 232*e*.
solion device, with hermetically sealed exterior of borosilicate glass, P (4) 102*h*.
stripline circulator, with means causing electrostatic capacitance between adjacent pairs of terminals equal to each other, P (10) 265*h*.
thin film device, bistable metal-niobium oxide-bismuth, P (11) 284*j*.
Electronics. See also *Electrical ceramics; Electronic equipment*.
ceramics, basic properties influence selection, (9) 228*j*.
component, thin-film, method of making, P (11) 286*b*.
components, behavior toward nuclear radiation, (11) 284*e*.
and electricity, special ceramics and use in field of, (9) 230*b*.
states, in perturbed two-dimensional graphite lattice, (9) 239*a*.
Electrons, absorption, effect of weak Bragg reflected beams, (8) 195*j*.
-beam, excitation, continuous, for room temperature super-radiance radiation in *n*-type GaAs, (5) 138*c*.
microanalyzer, to investigate oxide materials, (3) 81*a*.
pumped lasers of CdSe and CdS, (5) 135*h*.
pumped ultraviolet ZnO laser, (8) 183*j*.
for resistance measurement, (11) 284*d*.
distribution in some monoxides of transition elements, X-ray study, (9) 243*f*.
ejection, from barium oxide by noble gas ions, (3) 85*g*.
emission, secondary, of vacuum-cleaved solids, (1) 28*a*.
secondary, yields of some ceramics, (2) 56*a*.
high energy, passing through crystals, effect of point defects on absorption of, (8) 195*h*.
hot, in semiconductors, effects of phonon distribution, (5) 135*b*.
in semiconductors, theory, (10) 272*h*.
itinerant, exchange interaction among, B (11) 305*i*.
in LiF, plasma oscillation, (8) 205*c*.
low-voltage, reactions of carbon with carbon dioxide activated by, (2) 55*i*.
microanalyzer, use in glass laboratories, (10) 253*j*.
microprobe, used in elucidation of chemistry of antique ceramics, (3) 63*j*.
photoemission, from metals into silicon dioxide, (2) 55*f*.
tunneling from metal to InSb, (8) 196*c*.
Electrooptic, coefficients, in single-domain ferroelectric lithium tantalate, (5) 135*j*.
effect, anomalous polarity-dependent, in cubic ZnS and ZnTe, (10) 270*c*.
modulators, rapid vapor phase growth of high-resistivity GaP for, (10) 263*c*.
Electrophoresis, apparatus, modified, (4) 104*j*.
electrophoretic mobility, of kaolin-water suspensions with additions of basic aluminum chloride complex, (7) 154*h*.
Electrophotography. See *Photography*.
Electrostatic processes, coating, and apparatus, P (9) 233*c*.
coatings, application, P (4) 92*a*.
for deposition of coating materials, P (4) 92*a*.
powder application, P (9) 233*d*.
Elements, electric circuit of $BaTiO_3$, P (9) 230*d*.
heating. See *Heating elements*.
metal, process for producing sintered pieces on, P (2) 49*c*.
precision resistance, and method of making, P (9) 226*g*.
refractory, oxyhydrogen flame excitation of, (2) 50*i*.
trace, in marine waters by atomic absorption spectrophotometry, (10) 267*j*.
transition, of NiO, CoO, and MnO, X-ray study on electron distribution, (9) 243*f*.
Emission, efficient, high-power coherent, from HO^{3+} ions in YAG, assisted by energy transfer, (8) 195*j*.
electron, secondary, of vacuum-cleaved solids, (1) 28*a*.
secondary, yields of some ceramics, (2) 56*a*.
field, studies on kinetics of barium oxide on tungsten, (3) 85*j*.
of gas, ion bombardment-induced, from glass, (7) 148*j*.
green-edge, of CdS at 4.2° and 77°K, evidence of distant-pair recombination process, (9) 239*c*.
light, from semiconducting CdS in current oscillatory mode at 77°K, (8) 201*c*.
of ruby, (8) 196*f*.
thermo-, characteristics of alloys of isomorphous carbides, (8) 210*b*.
Emissivity, of cylindrical cavities giving near blackbody radiation, calculation, (11) 289*d*.
of flame-sprayed Al_2O_3 and ZrO_2 coatings at higher temperatures, (3) 65*c*.
spectral, of molybdenum disilicide, (5) 138*h*.
Emittance, normal spectral, rotating cylinder method for measuring, of ceramic oxide specimens from 1200° to 1600°K, (2) 51*d*.
total hemispherical, of coated wires, (4) 112*c*.
Emitters, grain-oriented thermionic, for electron discharge devices, P (2) 47*h*; P (3) 78*j*.
metallic boride cathode, rhenium supported, P (7) 157*j*.
semiconductor light, (9) 229*j*.
Enameled ware, appliance industry, porcelain enamel moves forward, (4) 92*a*.
ashtrays, for outdoors, (4) 89*j*.
hot water tanks, vitreous enamels for, P (2) 35*h*.
laundry, predicting life expectancy, (2) 35*f*.
panels. See *Building materials*.
Enameling, color versatility, (9) 217*a*.
decorative, of domestic appliances, processes, P (8) 174*j*.
direct, (3) 65*a*.
direct firing, (8) 174*h*.
direct-on, improved properties and experiences, (1) 2*h*.
less than 5% defects, (1) 2*i*.
equipment. See *Spraying*.
furnaces. See *Furnaces*.
ground coat, (7) 147*g*.
industry, mechanization, (9) 216*c*.
problems in use of stainless steels, (10) 250*e*.
with liquid flux, (4) 89*j*.
method, P (1) 3*d*.
for corrosion resistant tubular members, P (1) 3*c*.
plant, reorganizes as giant job shop, (4) 91*i*.
simplifies flow chart with center floor storage, (1) 2*f*.
porcelain, sheet steels for, (9) 216*g*.
natural materials for, (9) 216*d*.
steep-sided bowls, (4) 89*j*.
stress measurements and their significance in, (3) 65*f*.
vitreous, low carbon steel alloy for, P (2) 35*i*.
Enameling apparatus. See *Furnaces; Spraying*.
Enameling metals, aluminum, firing, (11) 273*h*.
interfacial reactions with lead oxide-bearing enamels, (3) 65*c*.
sheet, process for preparing with dry lubricant coatings, P (4) 92*e*.
adherence to low-carbon steel, (10) 250*a*.
Enamels. See also *Coatings*.
aluminum porcelain, orientation of lead antimonate and titanate crystals on surface of, (5) 117*f*.
and ceramic-metal systems, bibliography and abstracts-1966, B (8) 211*j*.
clayless suspension of, P (4) 92*e*.
coatings for metals, B (11) 306*b*.
containing reflecting beads for use as sign, P (1) 3*c*.
elasticity, measurement, (9) 216*i*.
fired, measurement of stress, (10) 249*j*.
flow characteristics of slips, (7) 147*i*.
frits. See *Frits*.
glass, durability measurement—methods for water extract analysis, (3) 80*i*.
ground-coat, thin layer, (7) 147*f*.
leaching and weathering, basic research, (3) 64*j*.
lead-oxide-bearing, interfacial reactions on fusing to steel substrates, (3) 65*e*.
measurement by bubble structure, (8) 174*h*.
melts, iron reaction with, (5) 117*h*.
mill additions, (7) 147*h*.
porcelain, electrophoretic deposition, (4) 91*i*.
flexible, works on all metals, (9) 216*f*.
low melting, of system PbO–TiO_2, (5) 117*e*.
lower cost, (2) 35*d*.
moves forward in appliance industry, (4) 92*a*.
for showers in New York City, (9) 216*f*.
pyrolyzable, from Mn and Co chelates, glass and siloxane resin, P (3) 65*f*.
for refractory insulating materials based on granite, P (11) 276*a*.
resistant to washing liquids, development, preparation, and testing, (9) 216*c*.
sheet iron, remedies for defects, (4) 92*b*.
slips. See *Slips*.
TiO_2-opacified cover coat, kinetics of opacification, (4) 92*a*.
vitreous, apparatus for testing with acid and neutral liquids and their vapors, IEI proposed standard, (11) 275*j*.
apparatus for testing with alkaline liquids, IEI proposed standard, (11) 275*j*.
for hot water tanks, P (2) 35*h*.
production of specimens for testing, IEI proposed standard, (11) 276*c*.
zirconia, crystallization processes, (3) 65*j*.
Energy, activation, for oxygen desorption from zinc oxide surfaces, (11) 292*g*.
cohesive, of LiF crystals, theoretical determination, (8) 209*b*.
converter, thermionic, P (9) 232*f*.
crystalline anisotropy, in CrO_2, (5) 134*j*.
dissociation, of alkaline earth oxides, (8) 195*b*.
energetics, of crystal lattices of silicates, (8) 196*h*.
free, formation of cerium and praseodymium monocarbides, (4) 110*d*.
formation of chromium carbide, (3) 85*j*.
formation of titanates, silicates and magnesium aluminate from measurements made with galvanic cells involving solid electrolytes, (8) 198*f*.
interfacial, between crystal and melt, theory, (10) 272*h*; (11) 302*e*.
metal-to-metal binding, in lattices of unsaturated oxides, (11) 298*e*.
mobility activation, of Nb and C in metallic niobium and its carbides, (5) 137*i*.

Energy (*continued*)
processes in adsorption and desorption of water vapor on oxide and metal powders, (5) 135*j*.
radiant, methods and devices for heating substances by, P (4) 105*f*.
radiation, transducing device, P (1) 11*d*.
sonic or ultrasonic, in combination with centrifugal energy, for removing moisture from material, method and apparatus, P (9) 233*e*.
transfer from UO_2^{2+} to Er^{3+} in glass, (10) 251*h*.
Engineering, materials, science, B (1) 31*b*.
Engineers, ceramic, complementary course for, (9) 244*a*.
ceramic, and his development, (9) 244*a*.
Engobes, engobing, in brick and stoneware industry, (3) 70*e*.
properties, (9) 228*d*.
Enthalpy. See *Heat, content*.
Entropy, of formation of boron(I) fluoride(g), (8) 199*i*.
of NaCl-type compounds, (3) 85*h*.
Equations, Nernst-Einstein, validity in alkali silicate glass systems, (11) 277*j*.
new, for calculating characteristic temperature from melting point, (3) 87*b*.
Equilibrium studies. See also *Systems*.
equilibria, gallium-gallium oxide, and activity of gallium in NiGa, (3) 83*i*.
Fe-Mn-SiO, oxygen potential diagram summarizing, at 1600°C, (3) 87*i*.
mineral, in Searles Lake evaporites, Calif., (1) 23*c*.
trivariant, and plotting diagrams of chemical potentials, (8) 210*h*.
phase, in portions of system $Zn(PO_3)_2$-$Cd(PO_3)_2$-$Mg(PO_3)_2$, (3) 87*a*.
in pseudobinary system UN-UP, (3) 71*c*.
phase diagrams, barycentric, metric properties, (11) 298*g*.
binary, of UO_2 with Al_2O_3, BeO, and MgO, (3) 83*i*.
of mixtures that are nonreactive with molybdenum: I, liquidus of sodium aluminate-alumina system; II, system calcium aluminate-alumina; III, system alumina-lanthanum oxide, (1) 25*i*.
of multicomponent systems, geometric methods, B (5) 140*h*.
plutonium-oxygen, (8) 205*c*.
of semiconducting systems, method of studying, (11) 298*f*.
(95% SiO_2 + 5% Al_2O_3)-CaF_2, (8) 204*g*.
(90% SiO_2 + 10% TiO_2)-CaF_2, (8) 204*g*.
ternary, assessment of phase composition of fireclay refractories based on, (2) 41*a*.
TiO_2-CaF_2, (8) 204*g*.
(81% TiO_2 + 19% CaO)-CaF_2, (8) 204*g*.
phase equilibria, in ternary systems of two transition metals and silicon, (3) 84*j*.
in three assemblages of kyanite-zone pelitic schists, Lincoln Mt. Quadrangle, central Vermont, (1) 25*c*.
redox equilibria, effect of glass composition on activity in glasses, (2) 36*j*.
Equipment. See *Machinery and equipment* and specific types.
Erbium, Er_2O_3, self-diffusion of oxygen, (3) 88*a*.
Erosion, gaseous, of zirconium oxide refractories, (5) 123*a*.
of high-temperature burned basic brick, slag basicity contributing to, (11) 280*f*.
Etch, pits, adsorption of dyes to, on potassium pits, chloride crystal surface, (9) 233*f*.
dislocation, in polycrystalline BeO, (7) 164*e*.
dislocation, in single-crystal and polycrystalline beryllium oxide, (4) 107*i*.
rotation on (001) surface of sodium chloride, (8) 206*e*.
thermal, of NiO crystals, (4) 111*g*.
Etching, aluminum, P (1) 3*a*.
bismuth telluride, P (11) 285*j*.
chemical, for detection of striae in GaAs, (11) 284*i*.
of silicon carbide with hydrogen, (11) 284*g*.
composition, and method, P (4) 94*e*.
by duo resist process on semiconductor wafer, P (8) 184*i*.
of GaAs with nitric acid, (4) 100*f*.
glass, method for, P (1) 5*i*.
HCl-H_2 and $GeCl_4$-H_2, of germanium substrates for epitaxial deposition, (7) 168*b*.
method, to dice semiconductor slice, P (2) 48*f*.
patterns, thermal, on germanium surface under low vacuum, (3) 77*b*.
process, P (3) 78*g*.
for removal of metallic Ga from GaP crystals, (7) 155*h*.
semiconductor elements, P (8) 185*c*.
semiconductors, P (3) 78*g*.
thermal, of single-crystal corundum, (2) 58*f*.
YAG single crystals, (10) 272*i*.
Eucryptite, beta, crystalline solutions involving Fe^{3+}, (3) 83*h*.
Europium, fused salts, extraction using molten borate ion-exchanger, P (11) 291*f*.
luminescence, in ternary system La_2O_3-Gd_2O_3-Y_2O_3, (9) 240*h*.
in luminescent compositions, P (2) 47*j*.
orthotantalates, (1) 24*b*.
oxide, longitudinal magneto-optical Kerr effect, (8) 201*g*.
nonstoichiometry, in relation to interaction with oxygen and hydrogen, (8) 203*f*.
switching properties, (8) 208*c*.
sesquioxide, heat of formation, (8) 199*i*.
sulfide, longitudinal magneto-optical Kerr effect, (8) 201*g*.
Eutectics, binary solidification, (7) 162*d*.
lamellar and rod, growth, (7) 165*b*.
Evaporation, boron nitride, source for aluminum, (1) 12*d*.
coefficient, of Be_3N_2 decomposition reaction, (10) 272*j*.
at different temperatures for separately crystallizing boric acid and alkali sulfate from aqueous solution, P (11) 292*e*.
nonequilibrium, effect on mass transport parameters of heat proof glassy materials, (8) 195*e*.
reactive, deposition of oxide films, (2) 46*j*.
vacuum, of Ge, Si, Sb, and Bi, P (7) 157*g*.
Excitation, trapping center and cross section, for radioactive self-luminous compounds, (7) 167*c*.
two-step, in erbium-doped cadmium fluoride, (2) 59*h*.
Expansion. See also *Dilatometers*.
anomalous, in firing of piezoelectric ceramics containing PbO, (7) 155*h*.
behavior of refractory blocks after different high prefirings, (10) 257*h*.
characteristics, of calcium sulfoaluminate hydrates, (5) 136*b*.
of glass. See *Glass*.
high-temperature, of forsterite and steatite, (7) 164*e*.
moisture, of structural ceramics: I, unrestrained, (5) 122*a*.
properties, imbibitional, of clay-water system, (7) 168*g*.
of refractory materials for furnace and kiln construction, importance, (8) 179*j*.
thermal, of arsenic-selenium glasses, (7) 149*d*.
coefficient, dependence on composition of gallosilicate and alumino-silicate glasses, (3) 66*a*.
coefficient, of ScB_2, X-ray determination, (2) 59*d*.
coefficients, method of forming objects with different, P (10) 250*e*.
at elevated temperatures, apparatus for measuring, (10) 266*j*.
of feldspar glasses, (2) 38*a*.
of GaSb at high temperatures, (11) 302*f*.
of glass, determination by modified Padmos method, (10) 251*j*.
high-temperature, of certain group IV and V diborides, (3) 86*f*.
of $IrAs_2$ and $IrSb_2$, high temperature X-ray study, (3) 86*g*.
of iron pyrites, (7) 169*b*.
of lithium hydrazinium sulfate, (8) 183*i*.
of magnesium oxide, (4) 111*c*.
of polycrystalline graphite, (8) 210*a*.
of potassium, rubidium and cesium wolfram bronzes, (4) 111*f*.
properties, of ceramics, P (7) 155*d*.
and related properties, of arsenic-sulfur glasses, (11) 277*g*.
of silicides, (5) 123*h*.
of sintered bodies in system ZrO_2-CeO_2, (8) 209*j*.
of TaC_x, effect of stoichiometry, (10) 271*a*.
of thorium cubic refractory compounds, (7) 169*c*.
of two-phase ceramic bodies, (2) 58*h*.
vs. fracture in fired ceramics, (4) 89*j*.
volume, of hardened cement paste due to dead-burned CaO, (2) 34*f*; discussion, (11) 274*h*.
Extraction, apparatus, reject spouts, P (9) 236*f*.
of fused salts of europium and neodymium using molten borate ion-exchanger, P (11) 291*f*.
of lithium values from brines containing calcium salts in presence of ammonia, P (5) 133*i*.
method for spectrophotometric determination of silicon traces, (10) 267*i*.
solvent, process for recovery of Be values, P (9) 236*h*.
Extruders, new high performance de-airing, for semistiff clay, (9) 232*i*.
Extrusion. See also *Dies*.
of carbon articles, P (9) 226*c*.
ceramic, control of charge for, P (8) 186*g*.
co-, for fabrication of dense UO_2, (10) 257*i*.
horizontal auger, of large pipe, (7) 150*i*.
hot, (3) 70*f*.
of liquid or semiliquid materials of low thermal conductivity, process and apparatus, P (7) 158*h*.
liquid phase, for forming refractory materials, P (8) 181*f*.
methods, P (9) 233*a*.
of non-Newtonian bodies, B (7) 170*d*.
of pipes and rods, from powders of high-melting compounds, (3) 70*h*.
shock-aided hydrostatic, control of stresses, P (5) 130*d*.
of silica and alumina powders, (3) 74*c*.

Fabrication, aspects, of *p*-type germanium tunnel diodes, (11) 284*e*.
of ceramics, new processes, (3) 80*a*.
fabricating, fission product retentive nuclear fuel body, P (3) 72*f*.
semiconductor device, P (2) 48*g*.
of ferromagnetic materials, P (3) 78*i*; P (11) 285*d*.
of magnetoresistive semiconductor film devices, P (11) 285*a*.
of metal base transistor by epitaxial growth of semicondictor material, P (9) 230*h*.
of microelectronic capacitor material, P (3) 79*h*.
of Ni and Ni-Zn ferrites, P (2) 48*f*.
Science, B (7) 169*i*.
of semiconductive device with closely spaced electrodes, P (5) 127*b*.
of single phase bodies, control of, (4) 103*c*.
of sintered compounds based on uranium and plutonium, P (2) 43*j*.
Fabrication (*continued*)
in situ, of monolith refractory lining, P (3) 72*j*.
of thin film transistor, P (2) 49*d*.
Faraday, effect, for localized electrons in insulators, (11) 295*c*.
Fatigue, high-strain, studies of composite material, (9) 216*f*.
Feeding apparatus, P (4) 103*j*.
automatic hydrocarbon, for continuous furnace and movable fire chambers, P (10) 268*j*.
bar stoker, moving, Australian development, (2) 52*d*.
in ceramic kilns, P (2) 53*c*.
continuous pneumatic, for powdered or granular material, P (7) 158*i*.
crusher, P (10) 269*c*.
weigh feeder system, (5) 120*b*.
Feldspars, activation by fluoride in cationic collector systems, (4) 105*j*.
alkali, X-ray emission microanalysis, (2) 59*i*.
coarse grinding of, increasing effectiveness, (8) 189*g*.
crystallochemical relations, on Stjernöy, north Norway, (2) 56*d*.
from granitic rocks, (10) 269*h*.
potash and calcium-soda, behavior during heating, (3) 82*d*.
replacement by alkaline waste in industrial porcelain, (3) 82*i*.
suspensions, measurement of pH, (5) 137*b*.
Feldspathic, materials lower firing temperatures, (1) 6*i*.
Ferric, Ferrous, etc. See *Iron*.
Ferric oxide. See *Iron, oxide, ferric*.
Ferric sulfate. See *Iron, sulfate, ferric*.
Ferrimagnetism. See *Ferromagnetic materials; Ferromagnetism*.
Ferrites. See also specific types.
bodies, sintered, method of producing, P (8) 185*b*; P (9) 231*f*.
circulator having three mutually coupled coils coupled to ferrite material, P (2) 47*f*.
complex single-crystal hexagonal, growth, (11) 296*a*.
composition, based on lithium ferroaluminate, P (10) 263*i*.
high resistivity, P (7) 156*g*.
method of coating metal with, P (2) 48*c*.
copper-manganese ferrites, electrical and magnetic properties, effect of different oxide additions, (10) 262*d*.
cores, apparatus for handling, P (3) 77*c*.
having rectangular hysteresis loops and long switching constants, process for producing, P (5) 128*i*.
filter-limiter, strip transmission line, with ferrite sphere beneath overlapping conductors, P (2) 49*a*.
films, vacuum deposition by arc discharge, (11) 284*f*.
growth in Indiana General's production, (9) 229*h*.
hard-magnetic, effect of water vapor on reactions, (3) 75*g*.
hexagonal, morphological features, (9) 241*b*.
lead-barium and lead-strontium, magnetic properties, (1) 22*a*.
lithium, fluxes for sintering, P (4) 101*g*.
magnesium-manganese, domain structure, (1) 18*c*.
Mn-Mg, manufacture, (10) 262*h*.
manufacture from decomposition of sulfates, (10) 262*g*.
memory cells and matrices, P (8) 184*b*.
Ni, Ni-Zn, and fabrication, P (2) 48*f*.
particles, method of and apparatus for compacting, P (1) 11*b*.
phase shifter, latching, having predetermined phase shift, P (8) 184*j*.
reciprocal latched, P (11) 287*a*.
reciprocal stripline, having folded center conductor, P (2) 49*d*.
powdered, preparation, P (11) 287*c*.
powders, comparison of methods for preparing, B (7) 170*a*.
production of, manganese oxide suitable for, P (4) 102*j*.
quality, from crude iron ore, (4) 100*c*.
shaped fine particle, and method for preparation, P (1) 11*g*.
single-crystal films, prepared by cathodic sputtering, (4) 100*c*.
single crystal hexagonal, microprobe and magnetic characterization, (9) 240*i*.
sintered, influence of furnace atmosphere on density, B (7) 170*i*.
sintering, effect of atmosphere, (7) 151*h*.
sleeve, about medial portions of radiation elements of antennas, P (4) 101*a*.
solid solutions, thermodynamic properties, calculation from experimental data of, (11) 302*i*.
sphere, planar, used in microwave power limiter, P (8) 185*c*.
with square hysteresis characteristic, causes of fast response, (10) 261*j*.
in thermal compensation process of permanent magnetization systems, P (11) 287*h*.
tuned coaxial cavity apparatus, P (2) 47*f*.
Ferroelectric materials. See also *Barium, titanate; Ferroelectricity*.
alkali niobate ceramics, hot-pressed, properties, (7) 156*b*.
ceramic composition, and applications, P (11) 285*c*.
ceramics, B (9) 244*h*.
method of temperature cycling through temperature range below the Curie point, P (1) 11*h*.
high capacitance device, P (1) 10*h*.

Ferroelectric materials (*continued*)
lithium hydrazinium sulfate, infrared spectrum, (8) 183*j*.
thermal expansion, (8) 183*i*.
lithium niobate; I, growth, domain structure, dislocations and etching; II, preparation of single domain crystals; III, single crystal X-ray diffraction study at 24°C; IV, single crystal neutron diffraction study at 24°C; V, Polycrystal X-ray diffraction study between 24° and 1200°C, (8) 197*j*, 198*a-h*.
and $LiTaO_3$, optical properties, (9) 242*c*.
Ferroelectricity. See also *Barium, titanate; Ferroelectric materials*.
domains, high field, in dark conductive CdS crystals, (3) 75*i*.
multiple, and walls, in NiO crystal, (3) 87*b*.
new dew method for revealing, (8) 203*i*.
domain wall, 180°, in $BaTiO_3$, angular energy dependence of, (11) 292*h*.
ferroelectric laser host, $Gd_2(MoO_4)_3$, (5) 136*f*.
ferroelectric zirconate-titanate, relation of lead vaporization and concentration of lead deficiencies, (3) 76*b*.
Ferromagnetic materials. See also *Ferromagnetism*.
ceramic, production, P (4) 102*i*.
compound, new, (7) 166*b*.
crystalline, coating, with uniaxial magnetic anisotropy, P (5) 128*f*.
ferrite bodies, sintered, preparation, P (10) 265*f*.
intermetallic compounds, and method of preparation, P (9) 230*j*.
manganese-zinc ferrite, of high permeability, and preparation, P (11) 285*c*.
Ferromagnetic materials, and methods of fabrication, P (3) 78*i*; P (11) 285*d*.
new, and manufacture, P (7) 157*a*.
thin film, of Ni-Fe-Mo alloy, process for cathodically sputtering, P (5) 128*f*.
Ferromagnetism. See also *Ferromagnetic materials; Magnetic materials*.
antiferromagnetic domain walls in nickel oxide, (5) 134*c*; observation, (8) 203*i*.
ferromagnetic memory core, method of making, P (3) 78*i*.
ferromagnetic phases, of alloys, microscopic examination, (5) 131*h*.
ferrimagnetic pressure transducer, P (5) 127*c*.
ferrimagnetic resonance, in copper ferrite cubic-phase single crystal, (11) 295*c*.
in single crystals of cobalt-substituted nickel ferrite, (11) 295*g*.
Fibers, boron, characteristics, (5) 122*g*.
boron, tungsten borides in, (9) 225*f*.
boron nitride, (10) 256*j*.
carbon and graphite, (1) 7*d*.
ceramic and acrylic resin blend, fireproofing by heating in oxidizing atmosphere, P (3) 72*f*.
in composite material, high-strain fatigue studies, (9) 216*f*.
flexible carbon, method for making, P (2) 44*b*.
glass. See also *Mineral wool*.
apparatus for precision fiberization, P (5) 119*i*.
apparatus for producing, P (5) 119*j*.
binder, P (9) 220*c*; P (10) 255*b*.
bonded product, and process, for preparing, P (11) 278*a*.
bundle, radiation absorption heating, P (9) 222*c*.
bundles, for light transmission, (10) 252*b*.
in composite structure, P (10) 254*i*.
coated with glass, P (1) 5*c*.
coating process for, and product, P (4) 93*j*.
combining with synthetic resin fibers, P (1) 4*f*.
continuous, apparatus for production, P (5) 119*a*.
cord, as reinforcing structure for grinding wheel, P (8) 173*h*.
drawing, study of air currents during, (3) 66*h*.
dyed and printed, and process, P (8) 177*b*.
elastomeric products for use in endless belts, method of making, P (4) 95*a*.
epoxide additive for amylaceous forming size compositions, P (4) 94*d*.
energy-conducting structures and method of making, P (1) 4*i*.
fine diameter, torsional testing techniques, (2) 38*c*.
fleeces, methods of and apparatus for producing, P (7) 150*f*.
forming, method for indication and control of operations, P (4) 94*f*.
forming tube, P (9) 220*b*.
glass for production of, P (5) 120*c*.
high-melting, and method, P (7) 149*e*.
hollow, method of making, P (2) 39*h*.
insulation, high temperature, for electrical conductors, P (8) 177*g*.
laminates, P (9) 219*i*.
manufacture, P (8) 177*j*; P (9) 220*d*.
mat, bonded, method of making, of surface treated glass fibers, P (2) 39*g*.
mat, bonded together by polyester composition, P (11) 278*c*.
mat, and method of making, P (11) 278*e*.
mat, process for impregnating with methyl methacrylate polymer, P (2) 40*b*.
mats, filamentous, method for making, P (7) 150*b*.
mats, process and apparatus, P (4) 95*c*.
method for applying forming lubricant, P (2) 39*f*.
method of forming, P (2) 39*g*.
method of making bundles, P (3) 68*f*.
Fibers, glass (*continued*)
method for producing, P (2) 39*b*; P (4) 95*d*; P (4) 95*f*.
method of treating with dry binder material, P (11) 279*h*.
multifilament strands, method for bonding bodies of, P (8) 177*h*.
multifilament strands, process for producing integrated body of, P (4) 95*d*.
neoprene-, structures, and method for preparation, P (7) 150*g*.
optic plates, method of sealing, P (5) 121*g*.
optical, image transfer device, P (1) 6*c*.
plastic composites, introduction, (9) 218*f*.
product consisting of body of, P (4) 95*f*.
product, process of making, P (8) 178*h*; P (9) 219*i*.
refractory, (3) 66*g*.
reinforced resin, method for making continuous lengths of threaded, P (2) 39*d*.
reinforced resin elongated articles, method of making, P (5) 121*a*.
reinforcing materials having improved surface characteristics, P (1) 4*j*.
reinforcements for gypsum deck, method of making, P (3) 64*g*.
reinforcements, of superior bonding and wetting characteristics, P (7) 149*j*.
short, machine for making, P (8) 177*i*.
sealing devices, fluid tight, P (1) 4*j*.
structure, (7) 148*j*.
temperature control system for high temperature melters, P (2) 40*a*.
treated and methods for treating to improve bonding relation with epoxy resins, P (11) 279*g*.
winding puts strength where needed, (4) 93*i*.
heat-softenable, apparatus for producing, P (2) 38*g*.
high-strength, high-modulus, nonlinear behavior in three-point bending, correction, (1) 23*j*.
infrared image transmitting, devices, P (4) 94*j*.
magnesium oxide, method of making, P (9) 226*e*.
product and method of manufacturing, P (8) 181*f*.
metal, give strength to base metals, (9) 216*b*.
mineral, apparatus for forming, P (9) 233*b*.
method and apparatus for de-shotting and separating, P (7) 149*h*.
panels, apparatus and methods for producing, P (11) 277*i*.
production of, P (4) 95*f*.
products made of, P (8) 178*i*.
optic devices, process for making, P (2) 40*b*.
multi-, light-conducting optical structures, method of making, P (9) 221*h*.
optical, method of confining and surfacing end portions of bundles for maximum light transmission, P (4) 94*h*.
optics, frequency responsive device, method of making, P (10) 255*h*.
used in modified Lovibond tintometer for surface color measurement, (1) 14*a*.
organic or inorganic thermoplastic, apparatus for production, P (2) 38*j,h*.
product, process and elements, P (2) 38*d*.
refractory, process for manufacturing, P (9) 226*i*.
refractory carbide, production, P (9) 227*h*.
reinforced composite materials, elastic properties of, (1) 2*g*.
in reinforced metals containing bond promoting components, P (2) 44*a*.
sheathed synthetic yarns, for abrasive coated backing, P (8) 173*g*.
silica, pre-tensioned in metal, method of producing, P (5) 117*d*.
silica-sheathed silicon carbide, manufacture and product, P (10) 259*d*.
-textured materials, effects of texture strength changes on physical properties, (9) 216*d*.
TiO_2, and preparation, P (11) 291*c*.
vitreous, method of lubricating, P (4) 94*j*.
Fibrous materials. See also *Aluminum, oxide; Asbestos; Fibers; Mineral wool; Refractories*.
disintegrating, process and apparatus, P (4) 103*i*.
Filaments. See also *Fibers, glass*.
boron, surface finishes, (1) 2*j*.
of graphite or carbides, P (3) 72*f*.
in incandescent lamps, orienting, P (4) 95*c*.
glass, P (5) 120*a*.
continuous, P (4) 94*b*.
freeze-coating, (7) 148*h*.
of "soda-free" borosilicate, P (2) 39*a*.
mono-, inorganic oxide, preparation, P (7) 153*f*.
mount, for electric incandescent lamp, P (2) 47*g*.
production, continuous, P (7) 149*a*.
silicon carbide, continuous, preparation, structure and properties, (8) 189*e*.
strands, treating and packaging, P (1) 5*g*.
tungsten, thoriated, or wire and method of making, P (1) 12*b*.
Films. See *Coatings*.
Filters, aid, of attapulgite product containing combination of fluxes, and method of making, P (1) 15*e*.
cellular ceramic, for removing gas-borne foreign bodies, P (5) 124*i*.
clay, attapulgite as aid, and production, P (2) 54*a*.
electronic, P (2) 47*g*.
elements, single crystal quartz, P (7) 158*d*.
integrated mechanical, for broad spectrum purification, P (8) 186*g*.
media, trickling, P (10) 256*g*.
piezoelectric ceramic, P (4) 102*g*.
Filters (*continued*)
piezoelectric wide bandpass, with elliptical shape, P (8) 185*h*.
presses, automatic, (9) 232*h*.
for purification of Ni solutions, (3) 65*c*.
rotary drum, P (1) 13*a*.
torsional mode ceramic band-pass, P (4) 103*a*.
Filtration, art, P (2) 49*i*.
Fine ceramics. See *Whiteware*.
Firebrick. See *Refractories*.
Fireclay. See *Refractories*.
Firing. See also *Burners; Calcination; Combustion; Flames; Furnaces; Kilns; Sintering*.
apparatus, for pulverized fuel, P (2) 52*j*.
barium titanate ceramics on bats of various materials, (2) 47*b*.
basis for determining optimum firing rate, (4) 105*c*.
cement phosphogypsum as effective mineralizer, (9) 215*d*.
ceramic body, process and device, in tunnel kiln, P (2) 53*a*.
ceramic or loose material, P (1) 14*j*.
ceramic products, processes: I, increase of Al_2O_3 content of porcelain, (1) 9*b*; III, in the presence of fluorides, (1) 9*d*.
conditions, effect on density and oxygen content of microwave magnesium manganese ferrites, (10) 262*g*.
Dankovsk dolomites in rotary kiln, (9) 224*d*.
fast, process, P (9) 234*j*.
whiteware, Europe reports progress, (4) 99*h*.
ferrites of manganese and zinc to equilibrium state, P (10) 265*h*.
grinding wheels, in tunnel furnace, P (9) 213*f*.
in heavy clay and refractories industries, 1950–64, (11) 279*j*.
industrial, Wobbe index importance in possibilities of control, (2) 52*i*.
lead zirconate-lead titanate ceramics, P (2) 48*g*.
molded objects in continuously operating furnaces, processes, P (4) 105*h*.
of piezoelectric ceramics containing PbO, anomalous expansion, (7) 155*h*.
of pipes, experiments, (9) 222*i*.
portland cement charges at high temperatures (up to 2273°K), (9) 214*c*.
rate, effect on physical properties of wall tile, (10) 261*e*.
system, Hanley demonstrates, (4) 105*d*.
temperature, effect on chrome-magnesite brick, (4) 96*j*.
Fission products, gases, behavior in uranium dioxide, (7) 151*c*
retentive nuclear fuel body, process for fabricating, P (3) 72*f*.
Flame photometry. See *Photometry*.
Flames. See also *Burners; Firing*.
of gas burner device for igniting and checking, P (9) 234*j*.
natural gas, electrical augmentation, (10) 268*f*.
oxyhydrogen, excitation of refractory elements, (2) 50*i*.
Flocculation, behavior, of silica suspensions, effect of solid content, (8) 195*i*.
internal mutual, in clay suspensions, (8) 200*i*.
Flotation. See also *Beneficiation*.
for beneficiating clay, P (11) 291*i*.
index for 1965, B (2) 60*j*.
of mica, P (1) 15*g*; P (10) 269*e*.
from pegmatites, (4) 106*f*.
method and apparatus, P (5) 133*i*.
nonmetallic, process, P (4) 106*i*.
process for silicon carbide purification, P (8) 181*c*.
selective, of mica from Georgia pegmatites, (1) 28*b*.
of silicates, role of iron, (4) 106*e*.
Flow, behavior, of glaze frits, determines quality control, (3) 74*g*.
bulk, effect on unsteady state diffusion with variable diffusion coefficient, (7) 162*e*.
characteristics, of enamel slips, problem, (7) 147*i*.
fluid, controlling, P (10) 268*c*.
phenomena, rotational, of powdered system, (11) 300*e*.
plastic, dynamics, at constant stress in NaCl single crystals, (10) 270*j*.
point determination apparatus, (2) 51*d*.
properties, of aqueous suspensions containing kaolins of varying degrees of crystallinity, (5) 136*e*.
of concentrated suspensions of kaolinite investigated by extrusion rheometer, (11) 289*h*.
of kaolin-water mixtures, effect of mechanical vibration, (7) 154*i*.
measurements, of thixotropic fluids, (7) 165*g*.
steady, of viscous fluid through tapered tube, (8) 207*c*.
ultrasonic, measurement, (7) 159*e*.
viscous, past tangential flat plate, (9) 243*d*.
in two-dimensional cavity, (9) 243*d*.
Flue gases. See *Gases*.
Fluidization, fluidized bed process, for producing pigmentary titanium dioxide, P (10) 269*f*.
fluidized bed process for titanium dioxide production, P (8) 190*e*.
fluidizing apparatus for beds of particulate solids, P (3) 71*d*.
Fluids. See also *Liquids*.
electroviscous: I, rheological properties; II, electrical properties, (7) 163*g*.
elasticoviscous, flow in conical duct, (9) 239*f*.

Fluids (*continued*)
-release mechanisms in compacting marine mudrocks, and importance in oil exploration, (11) 290*j*.
thixotropic, measurements of flow properties, (7) 165*g*.
viscous, steady flow through tapered tube, (8) 207*c*.
Fluorescein, in photoluminescent composition, P (3) 79*i*.
Fluorescence, chromium, in $LaAlO_3$-$LaGaO_3$ system, (11) 292*j*.
degree of polarization, of borosilicate glasses containing uranium, (10) 251*d*.
fluorescent properties, of red-emitting europium-activated phosphors with cathode ray excitation, (9) 229*i*.
of samarium in cerium dioxide, effect of concentration, (11) 293*g*.
X-ray, for determination of iron in mineral, (11) 289*g*.
for dynamic analysis, (11) 289*g*.
Fluorides. See also *Glass*.
activates beryl and feldspars in cationic collector systems, (4) 105*j*.
erbium-doped cadmium, two-step excitation, (2) 59*h*.
in graphite crucible composition, (7) 152*j*.
as mineralizer, effects on thermal reaction of kaolin minerals, (5) 135*a*.
molten, density and surface tension: II, system NaF–LiF-ZrF_4, (7) 162*b*.
oxy-, melts, of potassium, zirconium and boron, electrical conductivity, (8) 196*c*.
presence during firing of porcelain, (1) 9*d*.
single crystals, complex, growth by flux method, (9) 239*a*.
thermoluminescent manganese-activated calcium, method of making, P (2) 48*j*.
Fluorine, and chlorine, in silicate rocks, simultaneous determination by rapid spectrophotometry, (8) 188*b*.
compounds, thermodynamic properties: III, enthalpies of formation of hydrofluoric acid solutions, (2) 58*d*.
elemental, kinetics of reactions with zirconium carbide and zirconium diboride at high temperatures, (8) 201*j*; II, fluorination of hafnium carbide and hafnium boride; III, fluorination of silicon and boron, (8) 201*j*.
retention, effect of glass composition on, (8) 176*c*.
treatment, corrosion retarding, of glass surfaces, P (8) 176*j*.
Fluorite, phases, in systems protactinium pentoxide-rare earth oxide, (11) 295*i*.
Fluorspar, preparation, P (1) 16*b*.
Fluxes, agent, metallurgical, P (7) 153*d*.
brazing, and method of brazing, P (9) 217*b*.
fluxing materials for graphite crucibles, (2) 41*g*.
iron-containing, material for steelmaking process, P (8) 181*c*.
for steelmaking process, P (7) 153*f*.
liquid, for enameling, (4) 89*j*.
for sintering lithium ferrites, P (4) 101*g*.
strip cladding, of stainless steel, P (5) 117*i*.
used in steelmaking, P (8) 181*c*.
welding, P (11) 276*c*.
composition and method of making, P (8) 174*j*.
Fly ash. See *Ash*.
Foam, materials, from SiO_2-B_2O_3-Sb_2O_3 system, (2) 57*c*.
polyether-base resin, for holding crystal specimens during sectioning, (11) 289*j*.
Forming, ceramic, methods, B (7) 170*c*.
ceramic, processes, causes and consequences of clay particle orientation, B (1) 30*c*.
ceramic shapes from slurries, P (7) 158*j*.
electro-, split glassware molds, method and apparatus, P (2) 39*d*.
explosive, (2) 49*j*.
pellets of uranium and plutonium carbides, (11) 282*g*.
Forsterite. See also *Refractories*.
anorthite-, reactions and effect on basalt-eclogite transformation, (8) 191*f*.
high-temperature elasticity and expansivity, (7) 174*e*.
lightweights, service in lining of kiln cars, (9) 224*f*.
porcelain high frequency insulator: VI, relation between microstructure and metallizing properties; VII, effect of kaolin on properties, (2) 46*d*.
Fractionation. See *Separation*.
Fracture, behavior of materials, B (9) 244*f*.
of brittle materials, (7) 163*h*.
for brittle material, statistical theory for breakage distribution, (4) 110*h*.
fragmentation apparatus for characterization of sample compositions, P (9) 234*d*.
high temperature, studies with vacuum furnace, (1) 14*a*.
stress, relation to fracture pattern for glass rods of various diameters, (1) 4*d*.
tensile, in graphite, mechanism, (7) 151*j*.
vs. expansion in fired ceramics, (4) 89*f*.
work, and measurement in metals, ceramics and other materials, (10) 272*b*.
zones, shape and size on glass fracture surfaces, (3) 66*g*.
Freezing and thawing, tests. See *Frost resistance*.
Friction, of clean diamond, magnesium oxide and sapphire crystal surfaces, (11) 296*c*.
coefficients, in molten silver nitrate-sodium nitrate mixtures, measurement by diaphragm-cell method, (8) 194*c*.

Friction (*continued*)
composition, for high energy service, P (4) 98*f*.
internal, in magnesium oxide, due to chromium and iron, (8) 200*g*.
of mixed-alkali silicate glasses, (7) 148*i*.
new application to concrete research, (7) 146*i*.
peak, caused by water condensation on barium silicate glasses, (7) 148*j*.
of $5SrTiO_3$-$3La_2/_3TiO_3$ below 100°C, (1) 16*j*.
studies of sheet glass dehydration, (9) 218*c*.
linings, and processes for production, P (5) 124*g*.
material, P (5) 124*g*.
and articles made therefrom, P (7) 153*a*.
composition, P (5) 124*h*.
Frits, for cast-iron bathtubs, critical look at testing, (10) 249*j*.
dispensing device, for cathode ray tube, P (11) 285*e*.
and enamels with esterified surfaces, and preparation, P (10) 255*e*.
glaze, quality control by determination of flow behavior, (3) 74*g*.
opacified, method for manufacturing, P (1) 3*a*.
Frost, dilatometry, in testing durability of brick, (5) 121*j*.
Frost resistance, discussion, (11) 279*j*.
of Japanese roofing tile, (2) 40*g*.
Fuels. See also *Ash, fly; Coal; Combustion; Gases; Oil*.
burned uranium, process for reprocessing using molten bath containing ammonium nitrate, P (9) 227*f*.
cell, P (1) 10*e*.
electrode, P (2) 44*a*.
with stabilized zirconia electrolyte and nickel-silver alloy anode, P (4) 101*h*.
having zirconia-containing electrolyte and ceramic electrodes, P (4) 101*g*.
ceramic, speed nuclear age, (4) 96*g*.
ceramic nuclear, material with burnable poison, method of producing, P (8) 181*f*.
cermet nuclear, manufacture, P (3) 72*i*.
coated particle, for nuclear reactors, P (7) 153*d*.
efficient usage in brickmaking, (7) 159*j*.
gas, conversion to, in Bavarian factory, (9) 234*j*.
irradiated compact, process for reprocessing by fluorination, P (11) 282*i*.
liquid, vaporizing burners for, P (1) 15*a*.
liquid gas and light gasoline, in ceramic industry, (3) 81*j*.
material for nuclear reactors, process and apparatus for manufacture, P (2) 44*c*.
nuclear, P (3) 72*b*.
of actinide oxide, P (4) 98*f*.
body, fission product retentive, process for fabricating, P (3) 72*f*.
carbides, process for preparation, P (10) 260*h*.
carbon coated and poison particles, P (9) 225*b*.
ceramic and cermet, (3) 70*h*.
components, P (7) 153*e*.
composition, uranium carbide-tungsten, P (10) 261*b*.
elements, P (10) 260*a*.
materials, production, P (5) 125*c*; P (8) 182*a*.
of U_3CsSi_2, and method of preparation, P (11) 282*a*.
method of reprocessing and/or separating, P (9) 226*a*.
multipyrocarbon coated, and poison particles and method of preparing, P (10) 259*j*.
pyrohydrolysis of carbide-type, P (1) 8*b*.
refractory products for, P (2) 45*g*.
ThO_2-UO_2, (7) 151*g*.
uranium monocarbide-platonium mononitride, P (7) 154*f*.
uranium mononitride-sodium paste, P (11) 283*e*.
for nuclear reactors, production, P (9) 22*g*.
pulverized, apparatus for firing, P (2) 52*j*.
Fuel elements, fabrication of, designed for high-temperature operation, process, P (10) 260*f*.
microminiaturized, by vapor-deposition techniques, (4) 100*h*.
nuclear, manufacture, P (3) 72*i*.
of stainless steel coated UO_2 particles, method of producing, P (8) 181*g*.
nuclear reactor, P (1) 7*f*; P (1) 8*h*.
contains mechanically compressible mandrel, P (2) 44*b*.
production, P (2) 44*h*.
plutonium, influence of fabrication parameters on quality, (7) 151*c*.
porous, microspheres, P (8) 181*i*.
radioactive, storage, P (2) 45*i*.
reinforced, P (2) 45*g*.
reprocessing with fissionable material in carbide form spent in nuclear reactors, P (8) 181*h*.
Furnaces. See also *Burners; Fuels; Glassmaking apparatus and equipment; Kilns; Ovens; Refractories*.
P (2) 52*i*; P (4) 103*g*.
air ionization and measurement of resistivity of magnesia between 1500° and 1800°C, (1) 20*f*.
annealing, container or muffles, P (10) 268*i*.
annealing, continuous, P (3) 82*b*.
and method of annealing, P (1) 14*j*.
arc, method for controlling reactions, P (9) 235*a*.
three-phase, for melting zircon-containing refractories, (4) 97*f*.
arches, improvements in apparatus for construction, P (2) 53*b*.

Furnaces (*continued*)
atmospheres. See *Atmospheres*.
backwalls, heating, P (8) 189*a*.
baffle, P (2) 52*h*.
blast, carbon linings in bottom and well, mechanism of destruction, (9) 224*g*.
iron gutter, testing carbon blocks, (7) 152*d*.
boiler, preparation and method for preventing excessive buildup of solid products of combustion in outlet flues of, P (2) 53*c*.
charging, method and apparatus for, P (1) 15*a*.
continuous heat treat, with conveyor, P (10) 268*j*.
continuously operating, processes for firing molded objects, P (4) 105*h*.
control by fuel cell, (11) 290*b*.
crystal growing, with alumina liner, P (2) 52*f*.
cupola, P (1) 14*i*.
cyclone, P (3) 82*b*.
diffusion, P (4) 105*c*.
direct-fired oil, for enameling cast iron and steel, (8) 174*h*.
double sloping-hearth, P (2) 52*f*.
electric, P (4) 105*e*.
destruction of basic refractories in, (4) 96*h*.
for manufacture of fused quartz, P (8) 189*c*.
for treating material in controlled gas atmosphere, P (11) 290*c*.
electric arc, steelmaking, results of service tests of various types of basic brick in, (11) 281*a*.
temperature distribution, in study of highly refractory materials, (7) 160*a*.
vacuum, P (1) 15*a*.
electrical resistance, P (3) 82*c*.
enameling, comparison of various types, (10) 249*i*.
muffle and chamber, (7) 147*f*.
for fast-firing ceramic ware and fast-firing process, P (9) 234*j*.
fireplace, precast, methods of manufacture and erection, P (4) 98*i*.
flotation, automates tempering line, (9) 218*c*.
gas-fired hearths, basis for construction and use, (10) 268*f*.
glass, P (3) 67*h*.
apparatus for preventing devitrification of molten glass at joints, P (4) 93*g*.
barriers, method and device for protection, P (10) 255*f*.
bottom wall construction, P (5) 120*b*.
changing composition of glass in continuous process, P (4) 94*h*.
Dinas refractories for, (4) 96*h*.
feeder tube support and drive for, P (10) 255*a*.
forehearth construction, P (3) 67*d*.
joints, seal for and method of packing, P (11) 279*d*.
means for controlling electric currents in, P (9) 220*e*.
method and apparatus for recovery of heat, P (8) 177*f*.
and method of operation, P (4) 105*e*.
model evaluates luminous and nonluminous firing, (5) 119*g*.
operating, direct observation and photography inside, (3) 66*c*.
research for better use of refractories, (5) 123*c*.
use of fused silica, (5) 124*b*.
for working, P (9) 220*b*.
glass bending, with burner blast guide tubes, P (11) 278*h*.
glass flow, rotatable current baffle, P (9) 222*c*.
glass melting, P (9) 220*f*.
arch insulation, (10) 256*h*.
with bubblers, P (10) 255*f*.
electrical, (3) 66*g*.
silica brick in superstructure: I, corrosion by vapor of sodium salts; II, corrosion in superstructure and crowns, (5) 123*c,d*.
temperature measurement with platinum thermocouples, (1) 13*g*.
glass tank, basic refractories for, (10) 256*i*.
regenerators, design aspects, (5) 118*a*.
structure with regenerator chamber, P (9) 235*a*.
temporary heating by coal gas, (3) 66*j*.
heat shield, P (2) 52*i*.
for heat-treating minerals, P (8) 190*i*.
high frequency induction, for manufacture of fissile and/or fertile nuclear fuel carbides, P (4) 98*h*.
high temperature, P (2) 52*i*.
conveyor system, P (7) 160*b*.
for heating by means of radiant energy and plasma heat sources, P (4) 105*f*.
neutron diffraction, (1) 13*g*.
improvements, P (11) 290*d*.
industrial, refractories for, process for making, P (2) 45*c*.
laboratory, high temperature, (4) 105*e*.
high temperature, versatile, (1) 14*i*.
for high temperatures using butane gas, (10) 268*h*.
linings. See also *Refractories*.
monolithic, P (3) 73*e*.
metal, refractory linings, and their application, P (3) 73*e*.
with metal link and refractory anchor member, P (5) 124*i*.
with metal reinforced lining, P (4) 98*g*.
metallurgical, device for sampling and analysis of atmospheres, (5) 131*c*.
prefabricated taphole assembly for, P (10) 260*e*.
moving hearth, P (11) 290*f*.
multizone temperature and atmosphere, control, P (8) 189*c*.

Furnaces (*continued*)
oil, process and device for improving combustion, P (10) 268*h*.
open-hearth, bonded basic roofs development, (7) 151*f*.
parts, experience with use of heat resistant concretes, (7) 151*b*.
roofs, wear processes of basic refractory brick, (4) 98*a*.
tilting, study of conditions for fettling and wear of hearths, (5) 123*f*.
oxygen, refractory gunning, (2) 42*h*.
oxygen LD, controlling wear processes of refractory linings, (7) 151*j*.
preheater for, P (1) 15*b*.
pulverized fuel-fired, P (3) 82*a*.
recuperators, ceramic, P (10) 268*j*.
refractories for. See *Refractories*.
regenerative, hydraulically or pneumatically operated reversing apparatus, P (2) 52*j*.
rolling hearths, improvements, P (11) 290*d*.
roofs. See *Refractories*.
rotary, means for protecting internally lined exhaust openings, P (4) 105*f*.
rotary hearth, for production of burnt lime, P (4) 91*f*.
rotary tube, for calcining or burning cement, magnesia, limestone, P (10) 269*a*.
slot, highly refractory concrete in, (5) 123*j*.
solar, focal zone, calculation of radiant flux density through, (5) 134*h*; (5) 137*c*.
steel melting arc, life of linings, (9) 224*f*.
stresses, minimizing in brickwork, (8) 179*j*.
structure, for expanding heat-expandable ores, P (7) 160*a*.
tank, for glassmaking, P (8) 178*i*.
service of bakor and korvishit at Gomel'sk Glass Factory, (4) 97*j*.
vacuum, P (1) 15*a*.
for high temperature fracture studies, (1) 14*a*.
low cost 1300°C, (9) 234*i*.
vacuum electric arc, P (2) 53*e*.
veneer, wall construction, P (9) 235*c*.
wall constructions, P (2) 53*e*.
wall thickness and temperature, measurement element, P (5) 132*d*.
Fuses, electric, with separate quartz fillers having different grain sizes, P (3) 77*j*.
glass-encased electric, P (5) 127*e*.
high interrupting capacity, having casings of inorganic material, P (3) 78*a*.
high power, with ceramic casing, P (4) 101*i*.
Fusion, diagram, of SrO-Al_2O_3-ZrO_2 system, (7) 168*d*.
diagram, of systems $SmCl_3$-KCl, $SmCl_2$-KCl, $YbCl_3$-KCl and $YbCl_2$-KCl, (7) 163*i*.
for forming materials of high purity, P (5) 128*a*.
of glass particles with brief high intensity light flashes, P (11) 278*e*.
point measurement, of pure oxides with small amount of sample material, (7) 159*e*.
process for production of stoichiometric UO_2, P (8) 181*d*.
test method, improved, aids critical evaluations, (5) 131*d*.

Gadolinium, Gd^{3+} electron spin resonance, two sets in $BaTiO_3$ ceramic semiconductor, (8) 211*a*.
Gd^{3+} fluorescence, direct observation of sink-terminated concentration quenching, in calibo-1 glass, (8) 175*h*.
paramagnetic resonance in TiO_2 crystal, (7) 166*g*.
and gadolinium dicarbide, vaporization, Knudsen cell studies, (9) 240*g*.
$GdGaO_3$, high pressure synthesis, (8) 199*d*.
GdIG, near-infrared rotation as function of temperature, (8) 203*d*.
$Gd_2(MoO_4)_3$, ferroelectric laser host, (5) 136*f*.
$GdSi_2$, magnetic properties, (11) 284*d*.
hexaborides, properties, effect of nuclear radiation, (8) 195*f*.
oxide, systems. See *Systems*.
Gages, hot-cathode magnetron ionization, with photocurrent suppressor, (9) 233*h*.
Gallium, activity in NiGa and associated gallium-gallium oxide equilibria, (3) 83*i*.
GaSb, thermal expansion at high temperatures, (11) 302*f*.
antimonide systems. See *Systems*.
arsenide, bulk, infrared radiation from, (8) 200*g*.
detection of striae by chemical etching, (11) 284*i*.
diode, method of preparing, P (5) 128*g*.
diodes, efficient electroluminescence at 300°K, (9) 229*d*.
enhancement of optical second-harmonic generation by reflection phase matching, (8) 197*f*.
epitaxial, orientation effect on electrical properties, (3) 85*d*.
epitaxial films, influence of vapor composition on growth rate and morphology, (7) 155*h*.
epitaxial growth through cracks in SiO_2 masks, (11) 295*f*.
epitaxial growth on germanium substrates: I–III, (3) 85*g*.
epitaxial growth of ZnSe on, (10) 262*j*.
epitaxial layers, method of depositing, P (7) 157*d*.
etching characteristics and light figures of {111} surfaces of, (11) 295*j*.
-GaP, epitaxial growth of solid solutions, (7) 163*b*.
-GaP, GaAs-Ge, and GaP-Ge heterojunctions, preparation and properties, (3) 76*i*.
heats of fusion, (11) 296*f*.

Gallium, arsenide (*continued*)
imperfections, X-ray diffraction topographs by anomalous transmission of X rays, (11) 303*a*.
-InAs mixed crystals, preparation and properties, (9) 241*g*.
infrared and microwave radiations associated with current-controlled stability in, (11) 297*g*.
injection laser, room-temperature pulse-operated, optimum design for, (3) 76*e*.
Mn-doped, effects of Zn diffusion on, (9) 242*i*.
n-type, room temperature super-radiance radiation by continuous electron-beam excitation, (5) 137*c*.
pn junctions, copper diffused, (4) 100*d*.
preparation with controlled silicon concentrations, P (9) 231*h*.
reactions with water vapor and hydrogen chloride gas, (7) 167*g*.
semi-insulating, preparation by chromium doping, (3) 76*i*.
single crystal, overgrowth onto SiO_2, (11) 298*i*.
single crystals, anodic behavior at increased current densities in alkaline and acidic solutions, (10) 261*i*.
synthesis by vapor transport reaction, (9) 242*c*.
systems. See *Systems*.
Te-doped, cathodoluminescence and impurity variations, (7) 162*g*.
vapor-grown, incorporation of zinc in, (4) 100*h*.
variation of drift velocity with field, (11) 303*c*.
whisker crystals containing germanium core, (5) 136*e*.
zinc- and cadmium-diffused, correlation of electrical measurements with chemical analysis, (3) 84*g*.
GaSb-Ga_2Se_3 and GaSb-Ga_2Te_3 alloys, properties, (4) 110*b*.
Ga(As,P) alloys, epitaxial, determination of composition and homogeneity by X-ray diffraction and optical reflectivity, (3) 80*h*.
$GaAs_{1-x}P_x$, alloy overgrowths, strain patterns, (11) 301*g*.
preparation by vapor phase reaction, (3) 87*f*.
room-temperature injection lasers, vapor phase growth, (10) 263*i*.
vapor phase transport and epitaxial growth using water vapor, (9) 243*b*.
$(Ga_xIn_{1-x})As$ single crystals, growth by vapor phase reaction, (3) 86*c*.
$GaFeO_3$, crystal growth by flux method, (4) 107*h*.
$Ga_{2-x}Fe_xO_3$ crystals, segregation studies of Fe^{3+} in, (4) 107*h*.
metallic, method for rapid removal from GaP crystals, (7) 155*h*.
α-Ga_2O_3 single crystals, growth at 44 kbars, (5) 136*g*.
oxide, systems. See *Systems*.
phosphide, -GaAs, homogeneous and reproducible solid solutions of, preparation, (11) 299*c*.
high-resistivity, rapid vapor phase growth for electrooptic modulators, (10) 263*c*.
luminescence due to isoelectronic substitution of bismuth for phosphorus, (8) 201*i*.
method for preparation, P (5) 128*f*.
method of producing in crystalline form, P (5) 128*h*.
method for synthesis, P (4) 102*f*.
photoluminescence, radiative pair and surface recombination in, (8) 206*a*.
solution grown, solid solubility and amphoteric behavior of tin in, (4) 109*h*.
systems. See *Systems*.
vapor pressure and heat of sublimation, torsion effusion study, (7) 169*e*.
Gamma rays, linearly polarized recoil-free, for spin orientation determination, (8) 207*a*.
Garnets, calorimetric study at low temperatures, (8) 192*a*.
ferrimagnetic, compositions, P (3) 78*h*.
gadolinium iron, spin-wave spectrum, (9) 242*j*.
growth, dimensional and compositional control by mineralogical environment, (1) 18*b*.
rare-earth, crystal field parameters, (9) 237*e*.
rare earth ions in, intensity variation in paramagnetic resonance lines, (5) 136*h*.
thulium, magnetic behavior in cubic field, (9) 240*c*.
tin, Dhamrasite, (11) 290*j*.
yttrium aluminum, efficient microwave shear-wave generation, (11) 294*j*.
:Nd^{3+}, pumping by water-cooled krypton arcs, (10) 270*e*.
single crystals, polishing, etching, and dislocation distribution, (10) 272*i*.
yttrium-gadolinium-iron-aluminum-indium, magnetic properties, (5) 126*h*.
yttrium-iron, crystals grown from flux, influence of NiO on yield, (1) 19*g*.
longitudinal radio-frequency resonance, (10) 271*b*.
preselectors, P (4) 103*b*.
rods, axially magnetized, new mode in, (11) 298*e*.
silicon-doped, magnetostriction, (9) 240*d*.
single-crystal growth by combined Czochralski-molten salt solvent technique, (4) 100*e*.
Gases, adsorption, for determining surface area of finely divided substances, P (4) 104*j*.
analysis of, liberated during the tip-off of commercially available glasses, (2) 36*a*.
method and apparatus, P (2) 52*a*.
bubble producing, in glazes, (1) 9*e*.

Gases (*continued*)
combustible, flare apparatus, P (9) 234*j*.
contaminated, removal of coarse and fine particles, P (8) 186*h*.
entrapment during sintering of magnesia in argon, (2) 41*h*.
flue, alkali-laden dusts of, method and arrangement for increasing alkali content, P (8) 174*c*.
of cement kilns, method and apparatus for recovering high alkali percentage substances, P (2) 35*b*.
gaseous flow, through sintered beryllia, (4) 96*j*.
in glass, (8) 175*c*.
report on symposium, (5) 119*d*.
heated-, system with apparatus for removing gas-borne foreign bodies, P (5) 124*i*.
hot, chimney for cooling, P (4) 105*c*.
hydrocarbon combustion exhaust, oxidation catalyst for, P (2) 44*g*.
liquified petroleum, application to heavy clay industry, (11) 290*b*.
character and properties, (11) 290*d*.
inert, ionically pumped into glass, thermal desorption, (9) 218*i*.
natural, for operating tunnel kilns, (8) 189*a*.
technical aspects for using in ceramic industry, (8) 189*a*.
use in French clay products industry, (5) 122*a*.
use in porcelain industry, (4) 105*f*.
permeation, through fused-silica capsules during high temperature heat treatments, (3) 86*b*.
reacting, method of absorbing or dispensing in liquids, P (7) 158*e*.
Gels. See *Colloids; Silicon, dioxide; Tobermorite*.
Generators, ferroelectric pulse, P (10) 263*j*.
gas-fired radiant wall type infrared, P (7) 170*a*.
high-frequency ultrasonic, P (9) 231*b*.
MHD, ceramic materials for, (2) 46*i*.
Geology, computer in, expanding role, (11) 303*e*.
diabase-picrite intrusion in New South Wales, (8) 205*i*.
of carbonate sediments, (8) 201*f*.
Supai formation in Arizona, (7) 163*j*.
of Tirschenreuth, with particular reference to kaolin deposits, (3) 82*g*.
Germania. See *Germanium, dioxide*.
Germanium, anodic dissolution, kinetics, (7) 164*g*.
-containing products, free of fluorine, method of manufacturing, P (11) 286*e*.
core, in GaAs whisker crystals, (5) 136*e*.
dioxide, heat of formation, (8) 199*f*.
reaction with elemental sulfur and pyrite, (11) 300*b*.
reaction with oxides of Al, Fe, Si, Ca, and Mg, on heating, (11) 300*c*.
systems. See *Systems*.
disulfide, oxidation, (11) 298*j*.
effect of dislocation density on low-frequency noise in, (10) 262*f*.
epitaxy, in open tube HI transport system, (9) 242*b*.
films, deposition by sputtering, (10) 262*c*.
epitaxial, vacuum deposited on semiinsulating GaAs up to thicknesses of 10^6 A, electrical characteristics of, (4) 100*f*.
low-pressure sputtered, (1) 21*i*.
heteroepitaxial, on sapphire, (11) 296*g*.
$GeSe_2$, glasslike, electrical conductance, (3) 66*f*.
method for forming a tetragonal crystalline coating on, P (11) 286*g*.
n-, effect of neutron irradiation on, I: effect of radioactive irradiation on semiconductors, (1) 18*c*.
nitrides, (11) 298*f*.
oxide, viscosity-temperature relations, (1) 29*a*.
oxides, thermochemical study, using mass spectrometer, (2) 58*b*.
oxidic films on, production, P (7) 148*a*.
-silicon alloy heterojunctions, (4) 100*g*.
and silicon tetragonal disulfides, P (9) 232*f*.
single crystals, microinhomogeneities, (1) 23*b*.
uranium-doped, growth and characterization, (9) 239*j*.
substrates, HCl-H_2 and $GeCl_4$-H_2 etching, for epitaxial deposition, (7) 168*b*.
surface, under low vacuum, thermal etching patterns on, (3) 77*b*.
systems. See *Systems*.
thin films, recrystallization, (10) 263*e*.
vapor deposition, on molybdenum, (9) 230*e*.
Getters, gettering impurities in electrical devices such as incandescent lamps, P (8) 178*a*.
Gibbsite, hydrargillite, thermal transformation of alumina trihydrate, (2) 58*j*.
Glass. See also *Art and artware; Furnaces; Glass industry; Glassmaking apparatus and equipment*.
P (3) 67*f*; P (10) 255*d*.
absorption spectra of Mn^{2+}, (2) 35*j*.
adhesion of gold layer on, (10) 250*i*.
adsorption of gases, measurement, (10) 250*j*.
alkali, mixed, effect on spontaneous bubble formation in silicate melts at high temperatures, (11) 277*c*.
alkali aluminosilicate, stress formation and relaxation and mathematical description after ion exchange in connection with structural change, (2) 37*a*.
alkali borate, Cr^{3+}-Cr^{6+} equilibrium, (5) 118*h*.
dependence of elastic modulus on structure of, (3) 66*a*.
melts, binary, Cr^{3+}-Cr^{6+} equilibrium, (8) 175*f*.
Ni-containing, magnetic and optical investigations, (3) 66*a*.

Glass (*continued*)
alkali silicate, binary and ternary, study of metastable liquid-liquid immiscibility, (9) 218*f*.
Cr^{3+}-C_l^{3+} equilibrium, correction, (5) 118*h*.
solution, effect of thermal history on kinetics, (3) 66*c*.
alkali tetraborate, optical spectra of nickel, (5) 119*i*.
alkaline earth aluminosilicate, electrical properties, (10) 251*g*.
aluminosilicate, P (7) 149*e*.
dependence of thermal expansion coefficient on composition, (3) 66*a*.
in aluminosilicates, determination of, (3) 71*h*.
ampoules, inspecting for slant bottom condition, P (3) 68*c*.
manufacture, P (4) 94*f*.
method of attaching a metal hypodermic needle to, P (1) 5*h*.
analysis, for VO^{2+} by electron spin resonance, (2) 36*h*.
annealing, P (4) 93*f*.
antimony in, (2) 36*c*.
of arsenic, sulfur, and halogen, in photosensitive device, and method of making, P (8) 185*g*.
arsenic-selenium, thermal expansion, (7) 149*d*.
arsenic-sulfur, direct formation in sheet form by distillation under normal pressure, (7) 148*e*.
films, direct deposition by evaporation under normal pressure, (5) 118*f*.
infrared absorption spectra, (5) 119*d*.
thermal expansion and related properties, (11) 277*d*.
articles, with high mechanical strength, method of making, P (3) 68*h*.
method for producing nonglare, low specular reflecting films on, P (9) 221*e*.
method of removing from mold, P (8) 178*i*.
molded semivitreous, and method of making, P (8) 178*b*.
ornamenting process, by abrasive blasting, P (10) 256*d*.
partially devitrified, and method of making, P (4) 95*i*.
reshaping, P (3) 69*b*.
strengthened, P (10) 256*b*.
transparent devitrified strengthened, and method of making, P (2) 40*b*.
barium borosilicate, P (8) 176*i*.
barium-phosphate, effects of residual water, (7) 148*g*.
barium silicate, nucleation and crystallization, B (7) 170*j*.
radiation-induced defects and structure, (7) 148*e*.
batch, charging and melting method, P (9) 221*d*.
increasing melting rate, P (9) 220*a*.
method of mixing, P (3) 68*i*; P (5) 121*a*.
preparation by cement granulating methods, (3) 66*e*.
X rays measure minor ingredients, (1) 4*a*.
beads, colored reflective coating composition, P (2) 38*b*.
composition, high alkali earth oxide, P (5) 120*c*.
free flowing treatment, P (3) 67*e*.
high titanate, P (3) 68*b*.
marking materials, P (2) 39*a*.
method for forming, P (1) 5*d*.
method for manufacture, P (8) 177*d*; P (9) 221*c*.
method for production by rotating wheel, P (7) 149*j*.
in reflective sign, P (1) 3*c*.
yellow, compositions, P (3) 69*i*.
beryllium fluoride, nature of conductivity, (4) 93*j*.
bodies, radioactive fused, production, P (9) 222*b*.
bond, polyvinyl chloride resin, with secondary aminoalkyl silane primer, P (8) 178*e*.
bonding, P (1) 3*b*.
borate, action of water, (10) 253*g*.
absorption of iron, correction, (5) 119*h*.
adsorption of radioactive phosphate, (10) 253*e*.
glass formation range, (2) 36*f*.
kinetics of radiocoloration and phosphorescence, (8) 175*i*.
in B_2O_3-GeO_2 system, properties and structure, (7) 148*c*.
borosilicate, change in refractive indices under high pressure, (2) 36*d*.
containing uranium, degree of polarization of fluorescence, (10) 251*d*.
as fluxing material for graphite crucibles, (2) 41*g*.
in graphite crucible composition, (7) 152*j*.
leachable, (3) 66*j*.
borosilicate crown, effects of distribution of volume relaxation times in annealing of, (10) 251*e*.
bottles. See also *Glass, containers*.
aerosol, and method for making, P (2) 38*f*.
inspection system, P (3) 67*j*.
method for classifying, P (4) 94*e*.
breaks. See *Glass, fractures*.
Brillouin scattering spectra, (9) 217*g*.
bronze-smoke segment, P (3) 67*j*.
bubbles, analysis, error caused by gas adsorption of freshly broken glass surfaces, (11) 276*i*.
crystal growth on surfaces, (3) 65*i*.
formation, spontaneous in silicate melts of high temperatures: II, effect of wet atmospheres and behavior of mixed alkali glasses, (11) 277*c*.

Glass, bubbles (*continued*)
open, nature and cause of formation in ribbon, (8) 175*e*.
single, gas chromatograph for analyzing, (11) 276*j*.
building block, hollow, P (7) 149*f*.
bulb, assembly, P (1) 10*b*.
method and apparatus for coating, P (1) 5*d*.
methods of manufacturing, P (10) 255*j*.
calcium silicate, ionic conductivity in, (1) 4*a*.
calibo-1, direct observation of sink-terminated concentration quenching of Gd^{3+} fluorescence in, (8) 175*h*.
capacitor, (1) 3*j*.
capsules, method of making for electrical components, P (1) 6*c*.
catalyzed crystallization of, DTA method, (2) 37*f*.
cellular, and method of making, P (9) 219*b*.
-ceramics, B (11) 304*j*.
article, with glass and crystalline zones, P (4) 95*i*.
body and method of making, P (1) 5*b*.
body, preshaped two-phase, and process for making, P (2) 39*i*.
chemical compositions, (2) 36*e*.
chemical strengthening in system Li_2O-Al_2O_3-SiO_2, (4) 92*h*.
III, crystallization catalysts and types of glass used in production, (10) 252*c*.
crystallization and chemical strengthening, (3) 65*f*.
devitrified, and production, P (7) 149*b*.
effect of nucleating agents TiO_2 and ZrO_2 on separating crystal phases during production, of, (10) 251*d*.
for insulator seals, (4) 93*a*.
Li_2O-Al_2O_3-TiO_2-SiO_2, beta spodumene silica solid solution in, (10) 270*c*.
Li_2O-MgO-Al_2O_3-SiO_2, dielectric loss, (4) 93*g*.
of lithium silicate, (2) 36*f*.
lithium zinc silicate, structure and properties, (9) 218*b*.
manufacture from blast-furnace slags, P (3) 75*a*.
physical properties and relation to microstructure, (2) 36*e*.
process for production and insulating of apparatus made from, P (7) 150*c*.
products, method of preventing scum formation, P (2) 39*a*.
pseudovitreous and pseudocrystalline, formation, (11) 276*h*.
SiO_2-Li_2O-Al_2O_3-ZrO_2, variation of thermal conductivity during crystallization, (4) 93*c*.
stuffed β-quartz, crystallization and chemical strengthening, (5) 118*h*.
of system of $CaO \cdot Al_2O_3 \cdot 2SiO_2$-$2MgO \cdot 2Al_2O_3 \cdot 5SiO_2$-$CaO \cdot TiO_2 \cdot SiO_2$, effect of B_2O_3 addition on bending strength improvement, (7) 149*b*.
and ceramics, bibliography, B (8) 211*i*.
cerium-containing, preparation, P (4) 95*b*.
chemical stability influence on microhardness, (3) 66*j*.
chemically strengthened, mechanical properties at high temperatures, (1) 4*a*.
coloration, of phosphate glasses containing titania, investigations, (10) 252*j*.
colored, manufacture, P (8) 177*j*.
mixed in forehearth, P (10) 255*g*.
and process of manufacture, P (9) 219*c*.
colors, lead-free, (3) 74*c*.
commercial, analysis of gases liberated during tip-off, (2) 36*a*.
comminution, P (8) 176*i*.
compositions, P (4) 94*f*; P (5) 120*j*; P (7) 149*d*.
colorless high index, P (3) 67*a*.
effect on redox equilibria and oxygen ion activity in glasses, (2) 36*j*.
effect on retention of fluorine and on opacity, (8) 176*e*.
and electrical resistance material made therefrom, P (1) 10*g*.
low temperature, P (7) 149*g*.
neutral brown heat absorbing, P (4) 95*f*.
new, possessing electronic conductivities, (11) 277*d*.
and thermoelectric element coated therewith, P (1) 5*d*.
transparent magnetic, P (8) 179*a*.
conductance, in molten salts, (9) 217*j*.
constitution and properties, Vol. II, part 2, B (11) 303*h*.
containers, apparatus for measuring wall thickness, P (9) 219*e*.
economics of melting, (1) 3*g*; discussion, (9) 218*b*.
inspecting with lasers, P (5) 120*e*.
inspecting for line-over-finish defects, P (5) 120*e*.
production at Tropicana Products, (3) 93*c*.
with rounded top finishes, inspecting, P (9) 220*b*.
sodium sulfate and furnace atmosphere effect on fining, (1) 3*i*.
transparent, and method of making, P (4) 95*h*.
conveying and heating, on fluid support bed, P (4) 94*e*.
copper ruby, color developing process, (4) 92*h*.
cord, density at high temperatures, (10) 251*f*.
cords and knots, simple methods for investigating, (7) 148*e*.
corrosion by molten salts, (3) 65*h*.
crystalline. See also *Glass-ceramics*.
and method for making, P (10) 254*j*.
nepheline, high strength, method of making, P (8) 178*b*.

Glass, crystalline (*continued*)
surface composition and internal crystallization products, (5) 118*d*.
crystallization, B (2) 61*i*.
by variable-composition samples, (8) 276*c*.
See also *Crystallization*.
damage, laser-induced, compositional dependency, (7) 148*d*.
decolorization, (7) 148*e*.
decoration. See *Decoration*.
defects, composition of bubbles, (8) 176*a*.
homogeneity of, determination of nature and chemical composition by physical methods of analysis, (11) 276*f*.
developments, extend use to chemistry industry, (11) 277*h*.
devices for volatile-memories, (1) 3*j*.
devitrifiable, aqueous solutions, method of using and products, P (10) 254*f*.
devitrification, method for controlling rate, P (4) 94*i*.
devitrified. See also *Glass-ceramics*.
ceramic heat-resisting materials, (2) 36*c*.
DTA and X-ray diffraction studies, (9) 217*h*.
dielectric properties, in systems composed of TeO_2 and some phosphates, (5) 118*e*.
dosimetric, P (3) 67*b*.
durability, measurement—methods for water extract analysis, (3) 80*i*.
method for improving, P (1) 6*b*; P (11) 279*b*.
electrical properties, B (4) 113*g*.
effect of crystallization, (7) 148*f*.
electrochemical liquid junction structure and method of making, P (2) 38*c*.
electrodes. See *Electrodes*.
electron irradiated transparent insulating body for short-duration light source, P (2) 40*c*.
elements, molded devitrified, P (8) 178*a*.
elongated products, process for making, P (5) 121*f*.
for encapsulating semiconductor devices and resultant devices, P (5) 127*g*.
envelopes, P (4) 94*g*.
eutectic composition, in system MgO-Al_2O_3-SiO_2, (8) 176*b*.
fabric, with particulate material and pile yarns penetrating, P (8) 177*d*.
feeding mixed colorants in forehearth, P (10) 255*g*.
feldspar, thermal expansion, (2) 38*a*.
fiberizing from a rod, P (11) 279*a*.
fibers. See *Fibers, glass*.
for fiber production, P (5) 120*c*.
filamentous mats, method for making, P (5) 121*b*.
filaments. See *Filaments*.
film, insulation, method of making, P (8) 178*c*.
method for forming on surface, P (5) 120*j*.
physisorption of xenon and krypton, (2) 36*j*.
filters. See *Filters*.
fining, effect of sodium sulfate, (1) 3*i*.
flint, sulfides speed, (9) 218*k*.
finishing method, P (10) 255*h*.
flat. See also *Glass: plate, sheet, window*.
of different thicknesses, method of making, P (5) 121*d*.
manufacture, P (3) 68*d*; P (8) 177*a*; P (10) 256*b*.
method of making on molten tin, P (5) 121*e*.
method of manufacture, with reducing atmosphere, P (11) 279*d*.
method of manufacturing on bilevel forming surface, P (8) 178*f*.
method for manufacturing on molten metal bath, P (5) 121*e*; P (8) 177*c*; P (11) 279*i*.
process and plant for manufacturing on a molten metal and solid support bed, P (9) 222*a*.
float, carryover, process for removing on steel rolls, P (11) 279*b*.
process for finishing, P (2) 40*a*.
flow point determination apparatus, (2) 51*d*.
fluophosphate, P (1) 5*a*.
fluorescent, and method of making, P (9) 219*j*.
fluorine-containing porous, adsorption of ammonia on, (1) 10*g*.
fluor-richterite composition, phase separation, (7) 149*a*.
foamed, and insulating material, and process of making, P (9) 222*a*.
method of making, P (9) 221*i*.
process for the manufacture of shaped objects, P (1) 6*c*.
strong, method of producing and structure produced, P (9) 221*f*.
formation range; I, borate systems; II, silicate systems, (2) 36*f,g*; III, germanate systems, (5) 119*a*.
forming, by hot rolling, (11) 277*b*.
forming and annealing, P (7) 150*d*.
forming method, P (9) 220*d*.
fracture surfaces, shape and size of fracture, (3) 66*g*.
fusion, plagioclase, improvement in method, (10) 252*i*.
gallosilicate, dependence of thermal expansion coefficient on composition, (3) 66*a*.
gaseous inclusions in, method of determining probable sources, (1) 4*a*.
gases and water in, (8) 175*c*.
germanate systems, (5) 119*a*.
germanium, M_2O-Ga_2O_3-GeO_2, properties and structure, (9) 218*h*.
GeO_2-P_2O_5-V_2O_5, infrared spectra of, and their relation to structure and electronic conduction, (1) 3*h*.
Ge-P-Te, and method of making, P (11) 278*f*.
glare reducing, P (10) 255*d*.
glazing, method, P (7) 157*e*.

Glass (*continued*)
glazing units, manufacture, P (1) 5*j*.
gray, composition, P (4) 94*i*.
grinding. See *Grinding*.
grinding scratches, stress from, (10) 253*d*.
heat-absorbing, P (9) 220*j*.
heat resistance, increased for chemical laboratory equipment, (3) 66*h*.
heater panel, P (8) 177*g*.
high-lead, control of changes in physical properties, (5) 118*f*.
high-strength, destruction, (4) 93*b*.
articles, method of making, P (4) 95*b*.
materials, (5) 119*d*.
hollow articles, method and mold for forming, P (11) 279*e*.
hollow objects, methods of strengthening, P (3) 69*f*.
hollow ware, evaluation of strains, (10) 252*a*.
housing, dome-shaped, for deep submergence undersea lights, (10) 251*a*.
illuminator, P (1) 5*h*.
inclusions, identification and control, (2) 36*h*.
index of refraction, process for increasing, and article made, P (9) 222*f*.
insulator, electrically resistant, P (3) 67*b*.
interaction of sodium with, (8) 192*g*.
internal friction in alkali silicate, (7) 148*i*.
ions in, exchange and diffusion, (8) 175*c*.
iron phosphate, semiconduction, (11) 277*j*.
irradiated, kinetics of induced coloration and phosphorescence, (8) 175*i*.
optical processes in, (8) 175*b*.
optical properties, (8) 175*g*.
irradiation effects in, suppression by synthesis under high-pressure hydrogen, (9) 218*g*.
Jena, Carl Zeiss, 120 years, (5) 119*h*.
laboratory ware, stressed plastic valve for, P (5) 121*g*.
stressed Teflon valve for, P (9) 222*e*.
tilting still, (7) 159*c*.
water still with automatic safety switch, (7) 159*f*.
laminate with unsaturated polyester resin containing silane adhesive interlayer, P (10) 255*f*.
laminated, P (2) 38*i*.
with electrically operated instrument indicator means embedded in interlayer, P (8) 177*i*.
method of making assembly, P (1) 6*d*.
laminates, method of assembly, P (7) 150*b*.
lamination, composition, by means of epoxy resinous materials, P (9) 219*d*.
lamps, incandescent tungsten filament, modern no-dazzle and their production and use, (1) 4*b*.
lanthanum-borate, absorption and fluorescence of Nd^{3+} ion, (4) 92*i*.
laser rods, Nd^{3+}; optically pumped, effect of surface finish on temperature distribution in, (5) 135*j*.
leaching and weathering, basic research, (3) 64*j*.
lead, high, investigating melting processes, (8) 175*d*.
manufacture, P (9) 220*d*.
lead borate, radiation induced optical absorption in, relation to structure changes, (2) 37*d*.
lead-silica, viscosity, NBS Standard Reference Materials, (2) 37*i*.
leads, beaded, electrolytic apparatus for treatment of tips of, P (1) 10*b*.
lenses. See *Glass, optical*.
light deflector, P (1) 5*h*.
light-diffusing, on internal surfaces of hollow vessels, methods of and apparatus for forming, P (3) 69*d*.
lined vessels, P (1) 5*e*.
lip-tile mounting, P (3) 68*d*.
Li_2O-B_2O_3-SiO_2, and Li_2O-Al_2O_3-B_2O_3-SiO_2 solder, differential thermal analysis and X-ray diffraction study of devitrification, (9) 217*h,j*.
Li_2O-Al_2O_3-SiO_2, containing TiO_2, direct observation of crystallization, (3) 66*b*.
lithia-containing, pulverized, and petalite powder mixture, hot pressing of, (2) 37*i*.
lithia-silica, crystallization at high pressure, (5) 118*i*.
low-boron, for chemical laboratory equipment, (3) 66*h*.
low-melting, properties, in ZnO-PbO-B_2O_3-SiO_2 system, (3) 66*f*.
luminescent, articles, and method of making, P (4) 94*a*.
MgO-Al_2O_3-SiO_2, studies on eutectic glass composition, (8) 176*b*.
magnetic, transparent, compositions, P (8) 179*a*.
-making dictionary, Italian translation, B (11) 304*h*.
in tank furnace, method, P (8) 178*i*.
manufacture, P (2) 38*j*; 39*a,g*; P (5) 121*f,g*; P (8) 177*d*; P (10) 255*i*.
changing composition in continuous process, P (4) 94*h*.
manufacturing, computers and their application: I, glass process automation concepts; II, digital process control computer, (8) 175*e*.
mat, reinforced construction and method of forming, P (1) 6*d*.
material stream characteristics, method for indicating by calorimetry, P (9) 221*f*.
melting, P (4) 105*f*.
bubbler for, (3) 65*i*.
electric, (5) 118*i*.
electrical: II, types of furnaces, (3) 66*g*.
gaseous inclusions from, (1) 4*a*.
high-temperature, service of refractories, (3) 71*h*.

Glass, melting (*continued*)
reboil phenomena, (1) 4*d*.
and refining process, P (11) 279*a*.
vats having refractory bricks containing chromium oxide, P (1) 5*f*.
melts, diffusion of neon in, (11) 276*g*.
preventing scum formation, P (2) 39*a*.
primary, dissolution of lime and dolomite particles in, (3) 66*c*.
$Na_2O \cdot B_2O_3$ and $Na_2O \cdot SiO_2 \cdot B_2O_3$, volume relations at 1300°C, (2) 38*e*.
sodium silicate, dissolution kinetics of quartz spheres in, (11) 276*h*.
metal-, products of high strength, complex aluminous, manufacture, P (4) 94*b*.
-to-metal sealing. See *Seals and sealing*.
in microcircuit design, add flexibility, (5) 126*g*.
microspheres, hollow, in sintered specimens, (4) 93*a*.
mirrors. See *Mirrors*.
modern developments in, (11) 303*f*.
molds. See *Molds*.
molten, composition, effect on corrosion of pot clays, (10) 252*j*.
corrosion, effect of physical structure of Grossalmerode pot clay, (5) 118*g*.
corrosion of molybdenum by, (5) 118*f*.
metal pieces as parts for contact with, P (1) 5*b*.
method for controlling temperature, P (9) 221*d*.
method for generating currents, P (5) 120*j*.
resistivity, apparatus for measuring, P (11) 277*h*.
silicate, corrosion of refractories, (1) 7*a*.
natural, from Macusani, Peru, (10) 269*g*.
nucleated. See *Glass-ceramics*.
nitriding, effect on electrolysis and devitrification of high silica glass, (7) 148*f*.
as noncatalyst in apparatus, advantages, (10) 250*j*.
nonoxide, new, glassy state and properties, (2) 36*j*.
objects, methods of strengthening, P (4) 93*e*.
opal, surfaces, method of treating, P (2) 39*e*.
ophthalmic, bronze-smoke, composition, P (4) 93*j*.
lens, method of making, P (11) 279*d*.
lenses, multifocal, method of making molds for, P (4) 95*c*.
segment compositions, P (1) 6*g*.
tan, P (3) 69*g*.
optical, P (1) 6*a*; P (3) 69*g,h*; P (5) 121*c*; P (7) 150*a*.
blemishes, apparatus for measuring probability of presence, P (8) 176*g*.
calcium aluminate, manufacture, P (11) 278*e*.
elements, infrared transmitting, method of making, P (7) 150*c*.
lens aligning and blocking apparatus, P (1) 5*h*.
lens, miniature method of making, P (2) 39*h*.
lenses, diffusing, for spotlights with axially oriented filaments, P (10) 255*a*.
lenses for focusing infrared using silicon and zinc sulfide elements, P (5) 120*f*.
method for inspection of transparent object for defects including comparing light energy at two stations, P (9) 221*i*.
method of making light-conducting component, P (1) 6*d*.
and process for production, P (4) 95*i*.
properties. See *Optical properties*.
quality, preparation in small batches, (5) 119*a*.
resonant cavities, P (5) 121*c*.
Rosal type, changes in spectral characteristics in transformation interval, (10) 253*a*.
shutters, P (3) 69*h*.
sight glass, P (8) 179*b*.
treating quartz crystals for, P (9) 222*e*.
oxide, new, glassy state and properties, (2) 36*j*.
panels, method for severing, P (5) 121*b*.
panes, method for bending, P (1) 5*c*.
particles, determination of specific gravity by density gradient method, (2) 36*i*.
fusion with brief high intensity light flashes, P (11) 278*e*.
phosphate, composition, P (2) 39*i*.
containing ferrous iron as near infrared absorber, absorption characteristics, (4) 92*h*.
containing titania, investigations of violet coloration, (10) 252*j*.
for dosimetry of X and gamma rays, P (3) 69*i*.
fluorescent, P (5) 120*k*.
γ-ray irradiated, electron paramagnetic resonance study, (5) 118*i*.
meta-, P (9) 220*f*.
MoO_3-P_2O_5-Ag_2O and MoO_3-P_2O_5-K_2O, (11) 277*d*.
process for disposal of high level radioactive wastes, (10) 253*a*.
silver-activated, ESR studies of radiophotoluminescent centers in, (11) 276*g*.
slowly soluble, P (11) 279*f*.
striking effect due to elementary phosphorus, (7) 148*i*.
phosphorescent opal, P (4) 95*a*.
photosensitive, study of microcrystallization by variable-composition samples, (8) 176*g*.
phototropic, and method of making, P (1) 6*b*; P (3) 67*f*.
article, method of making, P (5) 121*d*; P (9) 222*a*.
display device, P (9) 219*f*.
pipe. See *Pipe*.
-plastic laminates, as light conducting systems, (10) 252*g*.

Glass (*continued*)
plate. See *Glass: flat, sheet, window*.
polishing. See *Polishing*.
polishing composition, comprising water-soluble zinc salt, P (8) 177*d*.
rare earth chlorides in, P (8) 178*j*.
porous, controlling structure, (3) 66*d*.
method of forming a moisture-collecting coating, P (1) 5*f*.
surface composition, (1) 4*i*.
potassium borate, gamma-induced absorption bands associated with Tl^+, Pb^{2+}, or Bi^{3+} in, (11) 276*i*.
pots. See *Glassmaking apparatus and equipment; Refractories*.
powders, determination of specific surface, and its relation to statistical parameters obtained from particle size analyses, (4) 93*b*.
pressure resisting, housings for undersea lights, (10) 251*a*.
printing, electrical, (5) 120*e*.
production in cupola, P (3) 69*b*.
properties, chemical and physical, effects of manganese and iron oxides, (2) 36*e*.
in system ZnO-PbO-B_2O_3-SiO_2, (3) 66*f*.
protection, during thermal treatment, process, P (3) 69*b*.
quartz, methods of manufacturing objects of, P (9) 221*i*.
rare earths in, determination by X-ray fluorescence, (10) 251*h*.
raw material, with easily volatilizable ingredients, method of treatment, P (3) 69*c*.
raw materials: I, silica deposits of Assam, Madhya Pradesh, and Orissa, (5) 119*e*.
reactions, with aqueous solutions, (2) 37*h*.
with molten borofluoride-nitrate solutions, (11) 277*i*.
reactivity with lead oxide, effect of boron coordination, (10) 251*b*.
redox equilibria, comments, (5) 119*c*.
effect of oxygen ion activity, correction, (5) 119*j*.
reflectorized marking material and method of making, P (1) 6*d*.
refractor, street light, P (8) 179*b*.
reinforced filament plastic tape, method of forming, P (5) 121*c*.
reinforcing, methods, P (7) 150*f*.
method and apparatus, P (8) 177*g*.
relaxation, electrical simulation in transformation range, (11) 276*f*.
research, at National Bureau of Standards, (8) 175*d*.
-resin coupling composition, method and apparatus for applying to glass, P (1) 5*b*.
resistance to water attack, comparison of two testing methods, (5) 118*c*.
ribbon, continuous, method for producing, P (11) 278*i*.
manufacture, P (8) 177*a*; P (10) 255*h*.
nature and cause of open bubble formation, (8) 175*e*.
protective salt bath for, P (4) 95*f*.
rods, relation of fracture stress to the fracture pattern for various diameters, (1) 4*d*.
ruby copper, principles in production, (8) 175*j*.
safety. See also *Glass, laminated*.
investigation of defect on surface, (1) 3*i*.
method for edge sealing, P (1) 5*i*.
sand. See *Sands*.
sandwiches, for optical instrument windows, method of making, P (4) 95*a*.
science and technology, general aspects, (2) 36*f*.
Se-As_2Se_3, crystallization of glass in, (3) 65*j*.
Se-Cd ruby, manufacture, (3) 66*b*.
sealing. See *Seals and sealing*.
semiconducting, Hall effect-Seebeck effect sign anomaly in, (3) 66*j*.
semicrystalline. See also *Glass-ceramics*.
semicrystalline articles, composite, method of producing, P (9) 221*d*.
semicrystalline body, decorating, P (8) 177*j*.
sheet. See also *Glass: flat, plate, window*.
annealing on decreasing temperature gas support, P (10) 255*i*.
annealing process, P (7) 150*b*.
assemblies, P (4) 93*h*.
bending, electrostatic deposition of parting materials in method of, P (10) 255*a*.
bending and annealing method, P (8) 177*g*.
bending method, P (1) 5*h*.
bending mold, pivoted, P (1) 6*c*.
bending and tempering, vertically supported with fluid pressure, P (11) 278*k*.
bent, method of producing pattern-cut, P (1) 6*e*.
clear, primary phase, (2) 37*c*.
continuous method of making, P (4) 94*b*.
dehydration, internal friction studies, (9) 218*e*.
drawing, P (9) 219*f*.
etching in hydrofluoric acid solution, P (3) 69*e*.
heating with a view to subsequent thermal treatment, process and arrangement, P (9) 222*d*.
manufacture, P (1) 5*j*; P (4) 94*c*.
manufacture, increase production capacity by changing technological parameters, (1) 3*f*.
manufacture on plurality of different fluid supports, P (11) 278*g*.
method to bend, P (5) 120*h*.
method of bending for producing vehicle window, P (9) 221*c*.
method for bending and tempering, P (1) 5*c*; P (4) 94*d*.
method of breaking out, P (5) 120*i*.

Glass, sheet (*continued*)
method of heating, P (3) 68*d*.
method for press bending, P (8) 177*f*.
method of press bending vertically supported, P (4) 95*d*.
method for uniformly heating, P (4) 94*g*.
package (carton) for, P (7) 150*a*.
with plurality of spaced wires, method of making, P (5) 121*c*.
purifying molten bath of forming operation, P (11) 278*j*.
storing, P (4) 95*g*.
thermally compensated bed for supporting, P (1) 6*e*.
thermoplastic, method of supporting with gas, P (11) 279*g*.
transverse heat absorption from, subsequent to roll forming, P (3) 69*h*.
silica, change in refractive indices under high pressure, (2) 36*d*.
effect of nonequilibrium evaporation and dissociation of vapors on mass transport parameters of, (8) 195*e*.
manufacture, P (10) 255*h*.
nitriding, (7) 148*f*.
porous, effects of adsorption on diffusion in, (8) 175*j*.
porous 96%, adsorption from nonelectrolyte solutions on, (8) 175*b*.
structure, (4) 93*b*.
silicate, absorption of iron, correction, (5) 119*h*.
cesium and thallium, ionic conduction and structure, (11) 277*d*.
chemical accelerators effect on temperature dependence of viscosity, (1) 3*g*.
chemical behavior, testing, (10) 253*f*.
containing fluorides, nucleation and crystal growth, (11) 277*f*.
energy transfer from UO_2^{2+} to Er^{3+}, (10) 251*h*.
formation range, (2) 36*g*.
ternary, calculation of viscosity from composition, (9) 217*h*.
thermodynamic approach to structure: II, ionic structure of metasilicate glasses, (2) 38*a*.
silicophosphate, structure and properties, (2) 37*e*.
silver containing: II, coloration by heat treatment at constant temperature, (4) 92*i*.
silvering, production: I, selection, cleansing, and sensitizing, (5) 119*c*.
soda-alumina-silica, surface reaction with pure molten NaOH and KOH, (3) 65*h*.
soda-lime, bottles, chemical durability, effect of heat treatment in moist atmospheres, (10) 251*d*.
effect of adsorbed water on spreading of organic liquids on, (10) 251*b*.
influence of water vapor on crack propagation, (9) 218*d*.
soda-lime-magnesia, devitrified, quartz crystals, (2) 37*c*.
soda-lime-silica, sodium oxide in, determination by flame photometry, (10) 251*i*.
surface reaction with pure molten NaOH and KOH, (3) 65*h*.
soda-zirconia-silica, surface reaction with pure molten NaOH and KOH, (3) 65*h*.
sodium borate, heats of solution, density and refractive index changes in high pressure, (10) 252*h*.
sodium borosilicate, surface reaction with pure molten NaOH and KOH, (3) 65*h*.
sodium disilicate, doped with Eu^{3+}, competitive trapping, (8) 175*b*.
Na_2O-Nb_2O_5-SiO_2, nucleation and crystallization of $NaNbO_3$ from glasses in, (8) 175*g*.
sodium phosphate, high pressure modifications, dependence of anion chain-length distribution on pressing temperature, (10) 250*j*.
sodium silicate, visible and near-infrared absorption of uranium, (7) 149*d*.
X-irradiated high purity, optical studies, (8) 175*h*.
$Na_2SiO_3 \cdot nH_2O$, vapor measurements, (10) 254*a*.
sodium trisilicate, Moessbauer studies on iron in, (10) 252*i*.
solder, in semiconductor packaging, (10) 253*i*.
solder compositions, and method of sealing, P (3) 69*f*.
soldering, preparation of joints, P (8) 178*d*.
for solid body lasers, P (9) 220*g*.
for solid-state lasers, (10) 252*e*.
solubility of Ar, N_2, CO_2, and He in, at high pressures to 10 kbars, (1) 4*d*.
spheres, reflectorizing, method of making, P (3) 69*d*.
"vacuum bubbles," (8) 176*b*.
spherules, manufacture, P (8) 177*a*.
-spinning crucibles, P (4) 94*h*.
stones, mineralogical studies, (5) 119*f*.
strength, (5) 119*b*.
effect of alkali silicate solutions on, (11) 276*i*.
increasing by treatment in molten salts, (9) 218*c*.
mechanical, process for protecting against loss, P (5) 121*g*.
statistical theory, (1) 4*f*.
and strengthening, (2) 37*j*.
strengthening, P (8) 178*i*.
chemically, method, P (8) 177*i*.
by ion exchange and articles therefrom, P (2) 39*c*.
by ion exchange: II, stress formation and relaxation in alkali aluminosilicate glasses in connection with structural changes; III, mathematical description, (2) 37*a*,*b*.
two-stage, mechanism, (10) 252*e*.

Glass (*continued*)
stress, caused by ultraviolet radiation, (5) 119*d*.
compressive effect of, (8) 175*b*.
stressed, method of making, P (3) 69*a*.
stresses from radiation, (7) 148*h*.
strip, method and plant for drawing, P (8) 178*h*.
structural, lightweight units and method of producing, P (1) 5*i*.
structure, (2) 37*d*; B (2) 61*i*; B (4) 113*g*.
Vol. V, structural transformations at high temperatures, B (5) 141*b*.
Vol. VI, properties, structure and physical-chemical effects, B (7) 171*a*.
Vol. VII, methods of studying, B (9) 245*j*.
in two- and multicomponent, (10) 253*b*.
substrate, for connector, P (2) 47*b*.
hot, process for electrostatically printing, P (3) 69*a*.
perforate, coating, P (2) 38*a*.
surface birefringence, method and apparatus for determining, P (2) 39*c*.
surface joint, method of making, P (8) 178*d*.
surface treatment, (5) 119*b*.
surfaces, coating to change radiation transmission, (10) 251*b*.
corrosion retarding fluorine treatment, P (8) 176*j*.
determination of thermal accommodation of translational energy of vapors, (1) 17*f*.
effect of abrasion, (3) 66*e*.
index of refraction, method of lowering, P (8) 178*a*.
method for increasing scratch resistance with pyrolyzing treatment and olefin polymer coatings, P (9) 221*e*.
strengthening by SO_3 treatment, (1) 4*g*.
tension, critical, (8) 175*g*.
treatment with polymers of alkali metal vinyl siliconates, P (1) 6*e*.
syringe cartridges, detection of chips, P (9) 219*f*.
hypodermic, inspecting, P (5) 120*e*.
in system Li_2O-PbO-B_2O_3, radiation shielding properties, (2) 37*f*.
in system M_2O-Ga_2O_3-GeO_2 (M = Li, Na, K), properties and structure, (9) 218*h*.
television tubes. See *Tubes*.
tellurite, (1) 4*i*.
tempered, properties, (2) 37*h*.
tempering of thin (4.5 to 5 mm), (3) 66*i*.
thermal expansion, determination by modified Padmos method, (10) 251*j*.
thermal treatment to improve properties, (5) 119*e*.
thin, samples, transmission electron microscopy of, (2) 38*d*.
tile with means for attachment, P (7) 149*e*.
titanate, subjected to cosmic rays, devitrification, (9) 217*g*.
toughened, method of making, P (3) 69*e*.
transformation, change in heat capacity of boron trioxide during, (8) 175*b*.
transformation of water in, (8) 175*i*.
transition characteristics, in organic and inorganic glasses, (7) 148*b*.
transitions, in lower aliphatic alcohols, (5) 119*b*.
treating, P (8) 179*b*.
treatment, P (10) 256*b*.
tubes. See *Tubes*.
tubing, gaging wall thickness, P (5) 120*i*.
tungsten oxide-metal metaphosphate, P (1) 6*e*.
ultrahigh-vacuum systems, bakeout procedure, (9) 217*f*.
ultraviolet absorbing green, P (10) 256*b*; effects of iron, (2) 36*d*.
ultraviolet light-absorbing, P (3) 69*h*.
vacuum vessels, nonimplosive, P (7) 150*a*.
vanadium-containing, coloration, (4) 92*j*.
vanadium pentoxide-metal metaphosphate compositions, P (1) 6*f*.
V_2O_5-CdO-P_2O_5, synthesis and study of electrical and other properties, (8) 176*i*.
viscosity, (9) 219*a*.
in tank furnace, measuring methods (3) 66*c*.
-temperature data in range 10^{13} to 10^{14} poises, rapid method for approximating, (9) 233*j*.
-temperature relation, measurement and numerical investigation: I, range of validity and properties of Vogel-Tammann-Fulcher equation, (10) 252*c*.
vitreous, silica bodies, with light-diffusing coatings, P (4) 94*f*.
vitreous materials containing mica, P (8) 179*b*.
Vycor, sorption of activated hydrogen, (9) 216*j*.
ware, annealing method, P (8) 177*f*.
hot deformable, method for handling, P (5) 121*a*.
method of increasing the durability, P (1) 6*b*.
screen decorating method, P (2) 40*c*.
thick-walled, grinding machine for, (3) 66*i*.
water reactions, (2) 37*h*.
window. See also *Glass: flat, sheet, plate*.
nuclear radiation shielding, P (2) 39*h*.
properties of tempered glass, (2) 37*h*.
wired, manufacture, P (3) 68*d*; P (5) 120*g*.
wool. See *Fibers, glass*.
yarns. See *Fibers, glass*.
X-ray diffraction patterns, (4) 93*e*.
zinc tellurite, (11) 277*g*.
zirconia, crystallization processes, (3) 65*j*.

Glass industry, batch houses, for household glass, (3) 66*c*.
chrome-containing brick in, for use in regenerator or blocks for melting tank, (9) 223*j*.
fibrous, for India, (7) 148*c*.

Glass industry (*continued*)
flat, processes and products, (5) 119*b*.
Indian, productivity, (8) 176*b*.
material handling and mixing, developments, (5) 118*c*.
Moravia Glass Works at Kyjov, preparation of glass batch by cement granulating methods, (3) 66*e*.
novel batching at Fenton Art Glass Co. jumps production 40%, (9) 218*h*.
patents: I, II, (3) 66*d*.
production at France's SOVIREL, (1) 4*e*.

Glassmaking apparatus and equipment. See also *Burners*.
for aligning hollow articles, P (1) 4*b*.
for annealing, P (3) 67*a*.
while drawn upwardly, P (3) 67*e*.
for applying glass-resin coupling composition to glass, P (1) 5*b*.
for article forming, P (2) 38*g*.
for assembling wires in a plurality of apertured parts, P (1) 5*b*.
for attachment of inserts and fixing devices in glass, P (7) 149*i*.
automatic lehr unloader, P (7) 149*i*.
for batch, consolidating, method and apparatus, P (3) 68*e*.
for beads, P (2) 38*e*; P (8) 177*d*; P (11) 278*g*.
forming, P (1) 5*d*; P (3) 67*c*.
and method, P (3) 68*g*.
production by rotating wheel, P (7) 149*j*.
bending mold for sheets, P (1) 4*f*.
for bending, panes, P (1) 5*c*.
sheets, P (3) 67*b*.
sheets, press, and method, P (3) 68*i*.
and tempering glass sheets, P (1) 5*c*.
for bending roll replacement in sheet glass drawing machines, P (7) 149*h*.
binding aid for gold trim, P (3) 67*i*.
for blending molten, P (9) 219*c*.
for blowing, and R & D, (1) 3*i*.
blowing machine having controlled blow pressure, P (1) 5*b*.
blowing mold, 200 years old, for optical effect decorative glass, (7) 146*a*.
for bottles, classifying, P (4) 94*c*.
handling, P (9) 220*h*.
inspector, with rotating photocell for scanning, P (9) 219*j*.
metering mechanism, P (1) 4*g*.
for orienting, P (11) 278*d*.
sorter, P (9) 219*a*.
sorting and method, P (1) 4*g*.
for cathode-ray tube manufacture, P (11) 278*b*.
for centrifugal molding in split molds, P (3) 67*b*.
for coating bulbs, P (9) 219*d*.
for coating continuously produced filaments, P (10) 254*h*.
coaxial disk and cylindrical rotor refiner, P (9) 219*c*.
for collecting filamentary materials, P (5) 119*h*.
for combining glass fibers with synthetic resin fibers, P (1) 4*f*.
for containers, such as ampoules, injection bottles, P (2) 39*e*.
for conveying, sheet on molten metal bath, and method, P (9) 220*f*.
tempered glass sheets, P (2) 38*b*.
for conveying and heating, on fluid support bed, P (4) 94*e*.
conveyors, pneumatic, for material handling in glass industry, (5) 118*c*.
cooking, with cooking vessel centering and holding means, P (8) 176*j*.
for covering moil from glass workpiece, and method, P (8) 177*b*.
crimper, spun glass, P (3) 69*g*.
cutter, P (1) 5*e*.
producing textured design, P (10) 254*j*.
for cutting, P (3) 67*g*.
automatic, method and apparatus, P (2) 39*b*.
lengths, from ribbon, P (7) 149*h*.
ribbon automatically, P (2) 39*c*.
sheet, P (1) 4*c*.
cylinder for bottle making, P (1) 4*h*.
decorating chuck, P (9) 219*e*.
for decorating, including flexible conductive offset member, P (1) 5*e*.
bottle, workpiece supporting and registering, P (7) 150*f*.
delivery system for molding machine, P (11) 278*i*.
dispensing plunger needle, for molten glass, P (10) 255*j*.
dolly for moving boxes, P (5) 120*d*.
drawing, with reheating means for producing flat sheets, P (4) 94*g*.
drawing chamber, for continuous manufacture of sheet glass, P (4) 94*c*.
drawing pot, method for diverting flow currents, P (10) 255*f*.
for drawing sheet, P (2) 39*j*.
for drawing strips off molten metal bath, and method, P (10) 255*j*.
for elongated products, P (5) 121*f*.
evacuated chamber for laminated assembly, P (5) 120*a*.
for fabrication of U-shaped profiles, in a continuous rolling procedure, P (2) 38*c*.
feeder, for production of fibers of heat-softenable materials, P (5) 120*e*.
feeder plunger, motion transmitting means, P (8) 178*c*.
feeder scoop gear index mechanism, P (10) 255*e*.
feeder tube centering and drive, P (10) 256*a*.
for feeding substantially untwisted multifilament strand, P (3) 68*f*.

Glassmaking apparatus and equipment (*continued*)
fiber-forming operations, indication and control apparatus, P (4) 94*f*.
for fiber reinforced resin elongated articles, P (5) 121*a*.
for fibers, P (2) 38*i*; P (9) 221*c*; P (10) 254*b*.
bushing assembly for forming, P (10) 254*g*.
continuous, P (5) 120*a*.
fine, P (5) 119*j*.
from heat-softenable material, P (2) 38*g*.
from organic or inorganic thermoplastic materials, P (2) 38*j*.
from thermoplastic material, P (2) 38*g*.
for filamentous mats, P (5) 121*b*.
for filaments, fine continuous, P (3) 67*f*.
for film, forming on surface, P (5) 120*j*.
for films, thin, and method, P (3) 68*h*.
for fire-polished glass strip production, and method, P (9) 221*a*.
flange forming fixture, P (3) 67*d*.
for flat, with dual feeding means, continuous production, P (11) 277*g*.
for flat, on molten metal bath, P (5) 121*e*; P (8) 177*c*.
fluid quenching, for producing differentially toughened zone in toughened glass, P (5) 120*g*.
for foliated or flake production, and method, P (9) 220*j*.
for forming, P (11) 278*a*.
cellular panels, P (2) 39*j*.
fibrous products, P (10) 254*i*.
flat, on liquid bath, and method, P (9) 220*h*.
fluid impinging, P (7) 149*c*.
hollow glassware, P (10) 254*i*.
I.S. type, cylinder mounting on, P (8) 177*b*.
mats, P (9) 220*a*.
neck mold and plunger unit, P (5) 121*c*.
takeout apparatus, P (5) 121*h*.
timing system for I.S.-type, P (5) 121*h*.
tube for glass fibers, P (9) 220*b*.
with self-accommodating and universal plungers, P (9) 220*d*.
for forming and collecting filaments, P (3) 67*b*; P (10) 254*h*.
for forming and collecting filamentary materials, P (1) 4*c*; P (8) 176*e*.
furnaces. See *Furnaces*.
gaging and cutting, for glass tube, P (8) 177*e*.
gas support bed, for heat treating sheets, P (10) 255*a*.
with gaseous support bed, and method for treating glass on, P (10) 254*d*.
for generating currents in molten, P (5) 120*f*.
gob chute with fluid flow means, P (11) 278*d*.
gob temperature control, P (9) 220*j*.
for grinding. See *Grinding apparatus*.
for grinding and polishing edges of panes, mirrors, P (8) 176*e*.
for grouping articles, P (2) 38*j*.
for handling, glassware and cartons, P (4) 94*i*.
hot deformable ware, P (5) 121*a*.
and transfer, P (5) 120*b*.
heater, cooler compensating, for temperature control, P (10) 254*i*.
for heating molten materials, P (2) 39*j*.
for inhibiting upward rising bubbles in molten metal bath, P (10) 254*j*.
for inspecting, P (8) 176*e*.
for inspection and sorting, having contour sensing means, P (7) 149*g*.
insulated edge roller for window glass machine, P (10) 255*g*.
lens holder, P (11) 278*d*.
for maintaining optimum speed of cutting shears when glass gob sizes are varied, P (10) 254*a*.
for making rigid mineral fiber panels, P (9) 219*e*.
for making strand package, P (2) 39*e*.
for manufacturing slivers or yarns from glass filaments, P (10) 254*c*.
for melting, P (11) 278*f*.
for melting in Pt crucible, P (2) 38*f*.
for melting and processing heat-softenable mineral materials, P (9) 219*f*.
metallic elements, adapted to come in contact with melted glass, P (8) 177*a*.
method of shearing molten charges, P (2) 39*c*.
mixer, dust-tight low cost, (5) 118*c*.
mold holder for glassware forming machine, P (1) 6*f*.
for molding articles, P (5) 119*i*.
molds. See *Molds, glass*.
molten metal bath, for removal of impurities, P (10) 255*i*.
for moving glass containers onto a moving conveyor, P (8) 176*h*.
optical, lens grinding tools, facing assembly for, P (9) 219*i*.
for optical fiber, P (2) 38*i*.
orienting device, on glazing machine, P (3) 67*j*.
orifice for forming glass fibers, P (3) 67*c*.
for packaging flat, P (5) 121*d*.
for panel severing, P (5) 121*b*.
photoelectric inspecting device, P (2) 39*i*.
for pipettes, P (7) 149*j*.
plunger with internal cooling structure, P (2) 39*g*.
polarizing elements, production, P (3) 69*c*.
for polishing. See *Polishing apparatus*.
for positioning plates during laminating, P (1) 4*d*.
for precision fiberization, P (5) 119*i*.
for press bending, P (10) 256*b*.
for press bending sheets, P (3) 67*e*; P (10) 254*c*.
for press forming and tempering, P (1) 4*e*.
press mold sensing and indicating means, P (3) 67*i*.
for press molding, P (3) 67*d*.

Glassmaking apparatus and equipment (*continued*)
press sealing, P (3) 69*j*.
for pressing, P (11) 278*c*.
reciprocating, P (10) 256*a*.
for pressure molding, P (1) 5*f*.
printing, electrostatically, on hot substrate, P (3) 69*a*.
for processing, filament-forming mineral materials, P (9) 219*j*.
heat-softenable mineral material, P (10) 254*c*.
for producing, nonthermal currents in molten body, P (3) 68*j*.
wound textile package having uniform tension, P (1) 5*g*.
for protecting withdrawing rollers of molten metal bath in glass sheet making operation, P (8) 176*h*.
for protection during thermal treatment, P (3) 69*b*.
for purifying molten bath of sheet forming operation, P (11) 278*j*.
for refining, and continuously manufacturing sheet, P (9) 219*h*.
for ribbon, continuous, producing, P (11) 278*i*.
forming, blank forming apparatus for, P (11) 278*a*.
manufacture on molten metal bath, P (8) 176*f*.
rotary fiber-forming, distribution means for, P (11) 278*j*.
for sealing hollow parts, P (3) 67*g*.
for severing, P (4) 94*c*.
shaping means, concentric foraminous, for tubes or bars, P (4) 94*a*.
shaping plunger with mercury mass condenser cooling means, P (2) 38*h*.
for shaping sheets with opposed pressing members, P (10) 255*d*.
for sheet, bending, P (5) 120*h*.
bending mold, P (9) 220*g*.
bending and tempering, P (4) 94*d*.
bending and tempering, vertically supported with fluid pressure, P (11) 278*h*.
for breaking out, P (5) 120*h*.
continuous manufacture on molten metal bath, P (8) 178*g*.
continuous production, P (8) 176*d*; P (8) 178*f*.
dismounting and remounting driving rollers, P (11) 278*d*.
drawing, angular jets in conditioning chamber, P (8) 176*c*.
drawing, enclosure means in, P (9) 219*h*.
formed on molten metal bath, method of changing equilibrium thickness, P (8) 177*h*.
forming, P (11) 279*e*.
forming on molten metal bath, P (8) 178*e*.
gaseous support bed for conveying and heat-treating, P (11) 278*f*.
handling, for glass plates, P (9) 222*d*.
maintaining width while drawing, P (3) 68*e*.
manufacturing on gas support bed, and method, P (10) 255*b*.
for press bending, P (8) 177*f*.
for press bending and tempering, P (11) 278*h*.
for producing, P (4) 93*g*.
supporting, P (8) 179*a*.
tempering, P (3) 67*j*.
tempering on gas support bed, P (3) 68*a*.
uniformly heating, P (4) 94*g*.
for vertical drawing, P (1) 4*f*.
for short fibers, P (8) 177*i*.
for shredding molten mineral materials into fibers, P (11) 277*j*.
spinner, for fibers, P (7) 149*f*.
for spinning molten, P (3) 67*h*.
split mold operating, P (9) 222*e*.
for supporting glass tubing during the drawing, P (1) 5*a*.
for tempering, bent sheets, P (3) 67*h*.
with resilient sheet support means, P (11) 278*c*.
thickness gage, P (9) 220*h*.
for toughened glass, P (3) 69*e*.
traction rolls and material handling using rolls, P (8) 179*c*.
for transforming materials by pyrogenic techniques, P (10) 254*f*.
for traversing strand material, and method, P (3) 68*a*.
for tube feeding, P (11) 278*d*.
for winding ceramic or vitreous ribbons, P (8) 177*c*.
for window sheets, and method, P (10) 255*c*.
workpiece handling for tubing, P (11) 279*h*.

Glazes. See also *Decoration*.
brown, for electrical porcelain, (3) 73*g*.
bubble producing gases in, (1) 9*e*.
bubbles in, (8) 182*g*.
ceramic, stains for, P (7) 155*d*.
composition, effect on deformation of porcelain, (3) 73*j*.
formulary, for artware, (4) 90*b*.
four, for cone 014, (4) 90*a*.
frits. See *Frits*.
glazed structures, P (2) 46*d*.
hardness, determination: II, (3) 73*j*.
how to make your own: IV, transparent glazes opaque, (4) 90*a*; V, line and ladder blends, (4) 90*b*.
lead borate, low solubility, (2) 46*e*.
opacifiers for, (8) 182*h*.
opaque, for sanitary ware, problems of SnO_2 replacement, (°0) 26°*f*.
porcelain and steatite, characteristic tension curves, (°0) 26°*c*.
reduction, (3) 74*j*.
research on eutectics and vitreous compounds of type $CaO \cdot xAl_2O_3 \cdot ySiO_2$, (5) 125*j*.

Glazes (*continued*)
salt, containing boron, zinc, and manganese, mineralogy of, (4) 96*c*.
mineralogy, on iron-rich clay bodies, (7) 154*j*.
Seger formula disadvantages and its replacement by molar concentrations, (10) 261*e*.
steatite, for single firing at 1350°C, (2) 46*g*.
surfaces, wear of, as function of time, (3) 74*h*.
and underglazes, manganese and aluminum containing pink pigments for, P (10) 261*e*.
zinc opaque, texture, (11) 283*i*.
zinc oxide as mill addition, (3) 74*i*.
Glazing, in brick and stoneware industry, (3) 70*e*.
ceramic semiconductive, method for preparation, P (8) 185*a*.
effect of pressing with friction and hydraulic presses, (5) 125*h*.
Glossaries. See *Nomenclature*.
Gold, diffusion, into silicon crystals, (9) 238*g*.
diffusivities in SiO_2 and Si using MOS structure, (8) 198*i*.
films, vacuum-evaporated, to investigate oxidation mechanism of metals, (9) 242*j*.
layer, adherence on glass, (10) 250*i*.
in silicon, effect on resistivity and diffusion in heavily doped layers, (7) 163*j*.
-SiO_2 cermet films, cosputtered, (10) 261*j*.
Goniometers, Weissenberg, for determination of orientation and morphology of microcrystals, (7) 161*j*.
Grain boundaries, effects in polycrystalline materials, method for separating from lattice diffusion effects, (3) 86*i*.
of impurity-doped aluminum oxide, (8) 196*j*.
precipitation in oxide systems, (1) 19*f*.
role in ceramics, B (2) 60*j*.
silicon, anomalous diffusion of boron into, (11) 292*h*.
Grain growth, of alumina, effects of strain energy and temperature gradient, (7) 168*a*.
of hot-pressed alumina, (7) 168*i*.
inhibition in sintered beryllium oxide bodies by addition of ZrO_2, P (1) 7*h*.
of oxides, effect of inclusions, (1) 18*g*.
in porous compacts, theory, (7) 168*j*.
Grains. See *Particles*.
Granular materials. See also *Powders*.
apparatus for conditioning, using rotating spokes and aerating cleats, P (5) 130*c*.
ceramic, porous, or analogous, process for making, P (2) 35*a*.
continuous air-cooling or heating, apparatus, P (7) 158*k*.
device for grading by weight, P (4) 103*e*.
dewatering, vibratory centrifuge for, P (5) 130*g*.
free-flowing, sampling of, P (9) 234*f*.
means for discharging from silos, P (11) 288*g*.
method and apparatus for increasing entrainment in carrier gas utilizing pressure shocks, P (8) 186*i*.
nonagglutinant, method and apparatus for grinding, P (1) 12*i*.
preheating, process and apparatus, P (7) 158*i*.
process and apparatus for treatment, P (5) 130*c*.
silica-bonded bead, process for production from solids in powder form, P (8) 187*a*.
spherical, method and apparatus for making, P (1) 12*j*.
uraniferous, with definite particle size, method for directly preparing, P (10) 259*f*.
Granulation. See also *Crushing; Grinding*.
of glass batch, (3) 66*e*.
Granulometry. See *Particle size*.
Graphite. See also *Carbon*.
ablation of, in oxygen and air at 1000° to 1400°C under flow conditions, (2) 40*i*.
articles, method of forming, P (4) 98*d*; P (7) 153*j*.
method for heat treatment, P (1) 7*j*.
-based high temperature resistant member, and method of forming, P (2) 44*g*.
boron-free, process for manufacture, P (1) 8*h*.
boron solubility in, (4) 109*i*.
-catalyst charge assembly, for preparation of diamond, P (8) 173*i*.
containing fireclay brick forming ladle bottom, service test, (9) 224*g*.
crucibles, composition of graphite, silicon carbide, ferrosilicon, borosilicate glass, and fluoride, (7) 152*j*.
fluxing materials, (2) 41*g*.
crystals, mechanism of dimensional changes under fast neutron irradiation, (8) 202*b*.
diffusion, counter of gases in, (7) 15°*i*.
electrical conductivity, (5) 135*e*.
elastic properties, measurement by flexural sonic waves, (2) 42*c*.
electrical properties, at high temperatures, (3) 84*k*.
electro-, brush, P (2) 43*j*.
electrodes, method of producing, P (1) 8*d*.
expanded, process for producing, P (9) 227*c*.
fiber-reinforced, (1) 7*d*.
flame spraying, method to produce a low friction surface, P (2) 35*c*.
graphitic materials, neutron irradiation and surface homogeneity, (2) 55*h*.
graphitization, continuous, of carbonaceous thread, method, P (8) 190*h*.
H4LM, longitudinal tensile behavior in nitrogen to 2750°C, (8) 201*h*.
high purity and nuclear reactor core, ablation in oxygen and air, (7) 151*b*.
interstitial clusters, growth, under irradiation, (8) 199*a*.
irradiated and annealed, vacancy loops, (8) 211*d*.

Graphite (*continued*)
lattice, perturbed two-dimensional, electronic states, (9) 239*a*.
lubricating composition, of increased load carrying capacity, P (4) 98*j*.
mechanical damping in, at low temperature, (2) 55*f*.
nuclear, nonirradiated and irradiated, kinetics of liquid phase oxidation, (2) 55*e*.
nuclear-grade, oxidation by nitric acid and oxygen, (10) 258*e*.
oxidation and sublimation, in simulated reentry environments, (5) 123*f*.
-phosphorus composition, P (10) 259*c*.
polycrystalline, deformation mechanisms, (11) 293*i*.
thermal diffusivity determination, as function of temperature, (2) 54*h*.
thermal expansion, (8) 210*a*.
protection against high temperatures, (2) 43*f*.
protection from oxidation at 2100°C, with iridium, (1) 7*g*.
pulverizing, method, P (1) 13*a*.
pyrolytic, coated casting mold, and method of making, P (2) 45*i*.
coated resistors, development and evaluation, (3) 75*e*.
coating for radioactive spheroids, P (5) 125*e*.
coating process, P (8) 182*a*.
highly oriented, effect of fast neutron irradiation on C_{33} elastic modulus of, (8) 195*g*.
method of forming sheets, P (4) 106*d*.
oxidation at 1400° to 1800°F and at air velocities of 25 to 100 cm/sec, (7) 166*f*.
and vitreous carbon, reorientation effects, (10) 271*g*.
radiation-induced creep, (2) 55*g*.
reaction, with hydrogen at 1200° to 1650°C, (9) 241*i*.
with oxides of thorium and zirconium, torsion effusion study, (8) 210*d*.
reactor, effect of massive neutron exposure on distortion, (2) 41*e*.
reactor structure, control of radiation effects, (3) 70*h*.
shell, in fuel element for nuclear reactors, P (2) 44*c*.
single crystals, irradiated, electron microscope observations, (2) 55*c*.
isothermal annealing studies on vacancy and interstitial loops in, (8) 201*a*.
sheets, method for making, P (2) 44*a*.
suspensions, (3) 86*b*.
tape, as thermal barrier, (10) 257*a*.
tensile fracture, mechanism, (7) 151*j*.
testing method to simulate neutron irradiation, P (2) 44*d*.
vermicular, for use in hot topping, P (7) 153*j*.
welding, P (2) 44*e*.
Grinding (*Comminution*). See also *Crushing apparatus; Mills*.
automatic, in ball mills, (8) 186*f*.
carbide, cost reduction, (1) 1*g*.
cement, method, P (11) 275*e*.
cement clinker, P (3) 64*e*.
of clinker, to extreme fineness, structural changes, (11) 275*b*.
coarse, of feldspar, increasing effectiveness, (8) 189*g*.
and crushing plant, P (10) 269*d*.
dry or wet materials, method and apparatus, P (9) 233*e*.
fine, of clinker, intensification by surfactants, (9) 214*f*.
effect on inversion behavior of quartz and quartz-mineralizer mixtures during firing, (8) 195*h*.
of glass, P (8) 176*i*.
of glazes and vitreous enamels, control, (11) 283*h*.
granular nonagglutinant materials, P (1) 12*i*.
grindability, of clinkers and clinker mixtures, results of measuring, (9) 215*i*.
determination of ores, (3) 81*d*.
of limestone and rock-salt mixture in Hardgrove mill, (5) 129*h*.
impact, P (11) 291*h*.
material in grinding mills, P (9) 233*d*.
materials of medium hardness, problems, (10) 266*c*.
method, P (8) 190*e*.
milling time of solids, change of energy content of NaCl, ZnO, and copper powder as function of, (4) 103*g*.
moist material, method of and apparatus, P (3) 80*d*.
operations, theory, (7) 158*g*.
of ore, method, P (7) 160*j*.
process, theoretical study, (5) 129*j*.
of refractory clays in shaft mill, combined with drying, (5) 122*j*.
solids in liquid, P (4) 103*g*.
vibratory method, P (4) 103*h*.
wet, of blast-furnace slags, for better use of hydraulic properties, (7) 146*b*.
wet mica, process, complete continuous, P (9) 235*j*.
Grinding (*Material removal*). See also *Abrasives; Diamonds; Polishing*.
barrel finishing, 27 different jobs, (7) 145*f*.
with coated diamond/bond system, (2) 33*f*.
diamond, device for regaining diamond grindings, P (5) 115*h*.
fluids, proper for better quartz grind, (7) 145*f*.
upgrading of glass grinding effluent, P (11) 279*g*.
Grinding apparatus. See also *Abrasives*.
abrasive machining, future, (9) 213*f*.
for brick, P (3) 70*e*.
for edges of glass panes, mirrors, P (8) 176*e*.
for glass, method, P (3) 68*a*.
Grinding apparatus (*continued*)
for glass sheet, P (3) 67*c*.
for granular nonagglutinant materials, P (1) 12*i*.
grindstones, composite abrasive, P (7) 145*f*.
for group of lens like quartz resonators, P (9) 230*b*.
for hard materials, P (2) 54*d*.
for lens, automatic, P (3) 67*i*.
for materials comprising solid particles in liquid, and method, P (10) 266*b*.
and methods, P (2) 50*a*.
pan-type granulating, nodulizer, P (11) 275*g*.
for pigments in liquid medium, P (10) 266*c*.
for thick-walled glassware, (3) 66*i*.
wheel, P (3) 63*h*.
abrasive, method of impregnating with lubricant, P (9) 213*h*.
abrasive, safe use, (8) 173*f*.
abrasive, standard marking system, (10) 247*f*.
abrasive blasting, assembly, P (2) 33*f*.
with antimony or bismuth trioxide bond, P (8) 173*f*.
ceramic, test methods and strength study, (5) 115*f*.
from ceramic bonded corundum grains, basic and technical questions on production, (3) 63*f*.
diamond, prepare properly for profits, (11) 273*g*.
electrically conductive, P (7) 145*g*.
firing in tunnel furnace, P (9) 213*f*.
with predeterminately oriented fixed replaceable abrasive segments, P (8) 173*g*.
reinforced, and reinforcing structure, P (8) 173*h*.
segmental abrasive, P (3) 63*h*.
and stones of oxide bonded $B_{13}P_2$ and method of making, P (2) 33*g*.
structure, measurement, (11) 273*f*.
wheel markings, simplified by color codings, (11) 273*f*.
Grog, alumina, quartz, and kaolin, in feldspathic melts, relation between solubility and firing temperature, (4) 97*f*.
Gunning, monolithic refractories, (9) 224*e*.
pneumatic, of refractory concrete, (8) 180*g*.
Guns. See also *Spraying*.
furnace repair, P (10) 259*j*.
Gypsum. See also *Plaster*.
α-hemihydrate crystals, mechanism of formation, (7) 165*a*.
by-product, process for removing impurities from, P (9) 216*a*.
calcining, in two stages, method and apparatus, P (7) 147*e*.
continuous calcination, P (5) 116*e*.
apparatus for, P (5) 116*b*.
deck, with glass fiber reinforced upper surface, method of making, P (3) 64*g*.
dehydration, P (9) 235*f*.
deposits in northern Indiana, (4) 105*j*.
dissociation, under pressure, results of study and significance for petrology, (10) 271*j*.
dry beneficiation, (4) 105*j*.
phospho-, as effective mineralizer for firing cement, (9) 215*d*.
plaster of Paris, bandage, P (8) 174*f*.
bandage, process improvements, P (2) 35*b*.
plasters, improvements, P (2) 35*a*.
product, P (9) 215*g*.
slurry, method of grinding and introducing set-control agent, P (8) 174*d*.
synthetic, for preparing alpha calcium sulfate hemihydrate, P (11) 275*h*.
thermal dehydration, infrared spectroscopic investigation, (8) 200*g*.

Hafnia. See *Hafnium, oxide*.
Hafnium, boride, fluorination, kinetics of reactions, (8) 201*j*.
carbide, fluorination, kinetics of reactions, (8) 201*j*.
carbides, mutual solubility with zirconium and niobium carbides, (2) 55*g*.
diboride, high-temperature thermal expansion, (3) 86*f*.
oxidation characteristics, (10) 258*c*.
oxide, crystalline, and/or zirconia, aquasols, P (2) 45*a*.
electrical properties and defect structure, (7) 163*b*.
microballoons, preparation and characterization, (7) 152*a*.
phase transformations at high temperatures, (4) 109*g*.
systems. See *Systems*.
oxides, for producing refractory metal chlorides, P (3), 72*f*.
oxidizing, oxygen gradients in, (7) 168*i*.
separating from zirconium, P (1) 15*i*.
silicate, synthesis and X-ray study, (11) 301*d*.
systems. See *Systems*.
-zirconium, ratio in zirconium minerals, X-ray spectrographic determination, (2) 60*c*.
Halides, alkali, anharmonic interactions: II, (1) 16*f*.
alkali, U centers in, temperature dependence of infrared absorption due to, (2) 57*d*.
alkaline earth, single crystals, doping, (3) 85*a*.
Hall effect, -Seebeck effect sign anomaly in semiconducting glasses, (3) 66*j*.
Hardening, cement mixture, P (5) 116*h,i*.
hydraulic, theory, (11) 275*c*.
Hardness, hot, of selected borides, oxides and carbides to 1900°C, (7) 164*f*.
indentation, effect of loading duration, (3) 85*b*.
mutual, of single-crystal magnesium oxide at high temperatures, (5) 137*j*.
of solids, (8) 200*a*.
Hardness (*continued*)
micro-, anisotropy, slip and twinning in Mo_2C single crystals, (8) 202*d*.
of glass, influence of chemical stability, (3) 66*j*.
of solids at very high temperatures, (8) 199*e*.
Health. See also *Air, pollution; Dusts; Safety; Silicosis*.
Chromate eczema from cement, (5) 116*c*.
Heat. See also *Conductivity, thermal; Temperature*.
apparent specific, of clays, determination, (7) 159*a*.
capacity, of $BeO \cdot 3Al_2O_3$ from 15° to 390°K, (8) 199*h*.
high-temperature, of cerium sesquioxide, (3) 86*f*.
capacities, of chromium silicides, (3) 86*d*.
conductivity. See *Conductivity, thermal*.
content, of beryllium(I) chloride(g), (8) 210*d*.
of $BeO \cdot Al_2O_3$ and $BeO \cdot 3Al_2O_3$ from 273° to 1173°K, (11) 300*b,c*.
of chromium silicides, (3) 86*d*.
of formation of chloroniobates and chlorotantalates of rubidium and cesium, (7) 163*i*.
and enthalpy of activation of Be_3N_2 decomposition reaction, (10) 272*j*.
of magnesium difluoride formation, (8) 198*b*.
measured, of anhydrous crystalline AlF_3 from 273° to 1173°K, (11) 298*b*.
of silicon carbide containing 12% free carbon in range 1100° to 2850°K, (8) 197*h*.
of sublimation, of solid MgF_2, (8) 211*e*.
of titanium diboride in range 273.15° to 2600°K, (8) 197*g*.
of uranium hexafluoride formation, (8) 198*a*.
of zinc difluoride formation, (8) 198*b*.
control, infrared, for glass forming molds, P (10) 255*g*.
cycling resistance, of sintered materials, (10) 258*h*.
effect on phosphate cements, (10) 248*d*.
exchange media, MgO, development, (8) 179*j*.
exchanger, composed of ceramic and metallic recuperators, method of operating, P (8) 189*c*.
countercurrent, improved design method, (5) 132*f*.
materials, (2) 36*c*.
refractory, P (8) 189*d*.
shot cleaning method for, P (3) 82*b*.
of formation, of beryllium(I) chloride(g), (8) 210*d*.
of beryllium nitride, (8) 210*e*.
of boron(I) fluoride(g), (8) 199*i*.
of cadmium difluoride, (8) 198*b*.
of calcium germanates, (8) 199*a*.
of chromium silicides, (3) 86*d*.
of crystalline and glassy phosphates, (5) 136*i*.
of compounds $KWCl_6$ and K_2WCl_7, synthesis and determination, (2) 57*c*.
of europium sesquioxide, (8) 199*i*.
of germanium dioxide, (8) 199*j*.
key data, (8) 201*f*.
of $MgAl_2O_4$, (8) 199*j*.
of silica anion radicals, (8) 196*h*.
of fusion, of InSb, InAs, GaAs, and InP, (11) 296*f*.
of hydration, of portland cement, conduction calorimeter studies, (7) 146*g*.
of immersion, of α-Al_2O_3 and γ-Al_2O_3, (7) 164*a*.
radiant, reflective coatings and method for application, P (2) 35*f*.
recovery, from furnaces for working glass, method and apparatus, P (8) 177*f*.
resistance, of molten glass, apparatus for measuring, P (11) 277*h*.
of refractory materials, apparatus for investigation at high temperatures, (2) 43*e*.
of sand concrete, (10) 248*h*.
resistance properties of refractories, experimental apparatus for investigating, (4) 96*g*.
-resistant structural element, P (3) 64*e*.
shield, P (2) 52*i*.
shields, flexible, evaluation of refractory fabrics for, (3) 71*c*.
shield structure, for electric incandescent lamp, P (2) 47*g*.
fabricating method, P (8) 181*j*.
of solution changes in sodium borate glasses subjected to high pressure, (10) 252*h*.
specific, of Co_2TiO_4, and anomaly associated with magnetic transition, (11) 301*d*.
of sublimation, of boron, (8) 194*g*; 199*g*.
of solid MgF_2, (8) 211*e*.
transfer, due to flow between two infinite plates under transverse magnetic field, (8) 199*j*.
in laminar flow of Bingham material between two parallel plates, (11) 296*e*.
of refractories, rapid determination of coefficients, (5) 123*h*.
unit, P (7) 153*e*.
transport rate, influence on differential thermal analysis, (10) 267*e*.
treating, of monocrystalline semiconductor bodies, P (8) 185*d*.
semiconductor materials, P (7) 157*a*.
treatment, of anodic oxide films on tantalum: III, conductivity profile, (4) 100*g*.
effect on mullite containing Fe_2O_3 as mixture or solid solution, (8) 195*a*.
of finely divided materials, apparatus, P (7) 160*d*.
of graphite articles, method, P (1) 7*j*.
and hot storage of building materials, (3) 70*c*.
indicating devices for, P (9) 234*d*.
in moist and dry atmospheres, effect on chemical durability of soda-lime bottles, (10) 251*d*.
of powdered products, such as lime, raw cement, minerals, P (2) 35*b*.
of synthetic mica, method and apparatus, P (10) 269*g*.
of WO_3 single crystal, (3) 85*a*.

Heaters. See also *Thermoelectricity.*
P (2) 52*d*.
catalytic infrared, P (7) 160*f*.
cooler compensating, for temperature control in glass making, P (10) 254*i*.
electrically heated, immersible of ceramic, P (10) 264*j*
for electron tubes, P (9) 231*a*.
flash, for diamond synthesis from liquid carbon, P (10) 266*h*.
infrared, P (8) 189*b*.
for powdered material, such as raw cement material, P (4) 91*d*.
pre-, for revolving tubular kilns, P (2) 53*e*.
Heating. See also *Thermoelectricity.*
continuous, of granulated materials, apparatus, P (7) 158*h*.
device, for kilns firing heavy ceramics, P (7) 160*b*.
high frequency, for melting of minerals and rocks, (10) 268*h*.
powdered metals, method, P (10) 259*g*.
pre-, apparatus, for raw cement material, P (4) 91*d*.
fragments of granular materials, process and apparatus, P (7) 158*i*.
of powdered products, such as lime, raw cement, minerals, P (2) 35*b*.
process, continuous recycle, for production of soda ash and alkali metal phosphates, P (11) 291*e*.
radiant, devices, P (9) 235*a*.
radiation absorption, of glass fibers bundle, P (9) 222*e*.
rods, process for ensuring noncorrosive contacts, P (2) 53*b*.
substances, by radiant energy and plasma heat sources, methods and devices, P (4) 105*f*.
Heating elements. See also *Electrodes; Thermoelectricity.*
P (8) 184*f*.
contact layer for silicon-containing material, P (5) 127*e*.
graphite, and method of conditioning heating surface, P (10) 259*j*.
heat-resistant and oxidation-proof, of SiC and MoS_2, P (9) 225*i*.
method for producing contact layer on silicon-containing material, P (1) 8*b*.
molybdenum disilicide, (2) 42*a*.
properties, effect of silicon carbide impurities, (5) 122*c*.
refractory, arrangement for clamping, P (7) 152*i*.
Heavy clay industry. See *Structural clay products industry.*
Helium, bubbles, contribution to expansion of neutron-irradiated BeO, (8) 192*g*.
in glasses, solubilities at pressures to 10 kbars, (1) 4*d*.
Hematite. See also *Iron, oxide, ferric.*
alpha, stable remanence and memory, (9) 237*e*.
dense, hydrogen reduction, (7) 164*f*.
metamagnetic effects, (8) 202*c*.
oxygen-ion diffusion, (1) 24*d*.
spheres, porous, generalized model for gaseous, topochemical reduction, (9) 239*i*.
structure refinement, (1) 28*b*.
Heterogeneity, chemical, causes in melts for rock castings, (5) 122*g*.
surface, effect of oxidation on, of graphitized carbons, (2) 41*e*.
Homogeneity, concentration ranges, of carbides of transition metals of groups IV and V with NaCl structure, (3) 84*d*.
of glasses, defects of, determination of nature and chemical composition by physical methods of analysis, (11) 276*f*.
in-, compositional, of $(Ba,Pb)TiO_3$ crystals, (10) 270*g*.
of semiconductor measurement with electron beam, (11) 298*d*.
of viscous liquids, method and apparatus for improving, P (10) 255*a*.
Hot tops. See *Refractories.*
Humidity. See also *Moisture; Water.*
electrical sensing element, P (3) 81*d*.
of gas entering electrical dust collector, process for regulating, P (10) 268*j*.
humidifying device, for clay products, P (5) 130*f*.
sensing apparatus, P (1) 14*c*.
sensing element, P (5) 120*d*.
Hydrates, aluminum phosphate, (3) 83*i*.
of $2CaO \cdot 3B_2O_3$, preparation, P (11) 291*a*.
tetracalcium aluminate, inner crystalline absorption of water and organic substances of, (8) 174*e*.
tetra-, cobaltous acetate, thermal decomposition, (4) 111*c*.
tri-, alumina, hydrargillite, thermal transformation, (2) 58*j*.
Hydration, of cements, contraction and porosity formation during hardening, (1) 1*j*.
of clinker and cement, formation of new compounds, (1) 2*a*.
early stage, calcium silicates in, (5) 116*b*.
heat of. See *Heat.*
of magnesia cements, (10) 248*a*.
mechanism in clinker minerals, (5) 116*c*.
nature, in pastes of portland, blast furnace slag, and pozzolan cements immersed in potable water 5 years, (2) 34*f*.
of olefins to alcohols, production of catalyst for, P (7) 161*b*.
of sodium tripolyphosphate by water vapor, (2) 46*e*.
of tricalcium aluminate and tricalcium sulfate, effect of sodium sulfite, (4) 90*e*.
vapor, for densification of soda ash, P (7) 160*i*.
Hydraulic, hydraulicity of blast furnace slag in relation to composition, (2) 34*d*.
Hydrides, boro-, alkali metal, production of, P (2) 54*c*.
of titanium and niobium, saturated mixed, crystal structure, (3) 84*b*.
Hydrocarbons, conversion process, and catalytic contact material for, P (8) 190*f*.
Hydrofluoric acid, process for production of, from sulfuric acid, fluorspar and anhydrite, P (4) 107*c*.
solutions, enthalpies of formation, (2) 58*d*.
Hydrogen, -bonded HO radicals, electron spin resonance spectra, (8) 196*e*.
bonding interaction between kaolinite surfaces and intercalated potassium acetate, hydrazine, formamide, and urea, infrared studies, (1) 20*a*.
diffusion, in ThH_2, (3) 84*d*.
H_2-H_2O, diffusion through porous iron formed by reduction of hematite, (9) 238*g*.
ion incorporation, in crystals, (3) 86*g*.
liberation, during dehydration of single crystals of magnesium and aluminum hydroxides and kaolinite, (8) 201*a*.
reaction with graphite at 1200° to 1650°C, (9) 241*i*.
reduction, of dense hematites, (7) 164*f*.
-silica reactions in refractories, (8) 179*j*.
solubility, in porous polycrystalline aluminum oxide, (9) 242*h*.
systems. See *Systems.*
zeolite Y, with improved hydrothermal stability, P (3) 83*c*.
Hydrogen ion concentration, of feldspar suspensions, measurement, (5) 137*b*.
value of hydrated calcium aluminates and alumina cement, (3) 64*d*.
Hydrolysis, experiments, of siloxane bonds at silicon dioxide surfaces, (3) 85*i*.
of metal ions: LVII, Fe(III) ion and solubility product of $Fe(OH)_{2.7}Cl_{0.3}$ in 0.5M $(Na^+)Cl^-$ medium, (11) 297*c*.
of uranyl ion, UO_2^{+2}, in Na_2SO_4 medium, (4) 110*d*.
Hydrothermal process, to prepare rare earth trihydroxides and oxide hydroxides, (11) 297*e*.
Hydrothermal synthesis. See *Synthesis.*
Hysteresis, ferroelectric, character, of $YMnO_3$, (11) 295*e*.
non-vanishing rotation, barium potassium, ferrite magnetic material exhibiting, in applied magnetic fields, P (2) 47*g*.

Ice, monocrystals, zone-melting apparatus for growing, (8) 188*i*.
Illite. See also *Clays.*
adsorption of amino acids and peptides, cation exchange and proton transfer, and physical adsorption, (7) 161*f*.
univalent cation Fithian, repulsion of chloride ions, (7) 167*j*.
Ilmenite, Indian, chemical benefication, (11) 290*j*.
Illumination, apparatus for microscope system using polarized light, P (1) 14*d*.
Immiscibility, metastable liquid-liquid, study, in binary and ternary alkali silicate glasses, (9) 218*f*.
in oxide systems, structural interpretations: IV, occurrence, extent, and temperature of monotectic, (2) 56*a*.
Impregnation, capillary, for preparation of poreless TiC, (10) 258*g*.
Impurities, concentration, in surface layers of ionic crystal, (8) 192*g*.
donor, effect on direct-indirect transition in $GaAs_{1-x}P_x$, (5) 135*g*.
effect on optical properties of yttrium iron garnet, (8) 195*a*.
ionized, effect on current from shock-loaded quartz, (5) 135*h*.
process for removing from by-product gypsum, P (9) 216*a*.
redistribution, observation during thermal oxidation of silicon using MOS structure, (9) 241*h*.
in semiconductors, method and apparatus for determining drift depth of, P (3) 78*f*.
variations, in Te-doped GaAs, (7) 162*g*.
Index of refraction. See *Refractive index.*
Indium, alloying, with *p*-type silicon to produce *pn* junction for making silicon diodes or transistors, P (2) 48*b*.
antimonide, anodic oxide films on, (3) 75*e*.
of high perfection, (9) 239*h*.
thin film, preparation from bulk indium antimonide, P (11) 287*d*.
arsenide, bulk *n*-type, microwave emission from, (3) 76*d*.
Gunn oscillations in, (8) 199*d*.
heats of fusion, (11) 296*f*.
-InSb alloys, preparation, (7) 166*i*.
systems. See *Systems.*
chloride, interaction with chlorides of potassium, copper(I), silver and thallium(I), (8) 200*j*.
interaction with sodium chloride, (4) 108*h*.
for coating silicon semiconductor, using ion beam, P (3) 79*a*.
films, thermal relaxation on insulating substrates between 4° and 300°K, (4) 111*g*.
InSb, heats of fusion, (11) 296*f*.
microwave emission, for low electric fields, (5) 137*h*.
InOOH, structure, (10) 272*f*.
InP, heats of fusion, (11) 296*f*.
In_2Se_3, polymorphism, (1) 27*a*.
oxide, light transmissive electrically conductive electrode, for flexible electroluminescent device, P (8) 184*c*.
oxide, thin flakes, method of producing, P (11) 291*j*.
-selenium, melts, X-ray phase analysis, (2) 60*e*.
systems. See *Systems.*
Indium (*continued*)
telluride, high-pressure metallic, preparation and crystal structure, (3) 86*d*.
tellurides, thermodynamic properties of, (3) 77*c*.
Infrared, -generating devices, fabricated, method of reshaping, P (7) 150*e*.
near-, rotation in GdIG as function of temperature, (8) 203*d*.
studies of hydrogen bonding interaction between kaolinite surfaces and intercalated potassium acetate, hydrazine, formamide, and urea, (1) 20*a*.
studies of quartz-kaolin-microcline reactions, (9) 224*e*.
Infrared absorption. See *Absorption.*
Infrared spectra. See *Spectra.*
Inspection. See *Quality control.*
Instrumentation. See *Controls.*
Instruments. See also specific types.
extensometer, true-strain, (5) 131*i*.
Pfefferkorn apparatus, as absolute instrument, (5) 131*j*.
photomultiplier, for measurement of brightness temperature, (5) 131*f*.
Schmidt concrete testing hammer for refractory brick evaluation, (2) 43*g*.
tonometer, for measuring water activity in clay pastes, (5) 131*h*.
turbidimeter, for sensing turbidity of continuously flowing sample, P (5) 132*b*.
Insulating material, arch, of glass melting furnaces, (10) 256*h*.
packed, earthy, nonmetallic, electrically, in transistor housing, P (1) 12*c*.
vermiculite-clay, fired properties, (7) 152*a*.
Insulation, acoustical, broad, high temperature resistant, P (2) 44*f*.
cellular thermal or acoustic, method of making from dispersion asbestos fiber, P (11) 282*f*.
Insulation, electrical. See also *Dielectrics; Glass; Porcelain.*
compositions, P (2) 47*d*.
process for manufacture, P (5) 128*i*.
flexible glass flake, process of producing, P (4) 95*c*.
high temperature, P (1) 10*j*.
of thin film glass, P (8) 178*e*.
Insulation, thermal. See also *Fibers, glass; Mineral wool; Refractories, insulating.*
materials, P (4) 99*g*.
Insulators, electrical, P (2) 46*e*.
atmosphere-resisting, P (10) 261*h*.
ceramic, for railroad traffic systems, (9) 228*b*.
mica and glass sheet, P (9) 232*d*.
Faraday effect in localized electrons, (11) 295*c*.
high-frequency, forsterite porcelain, (2) 46*d*.
high tension, nondestructive testing by ultrasonic impulse method, (8) 182*j*.
high voltage, filled with semiconductive foam gas under superatmospheric pressure, P (9) 231*c*.
hollow, process and apparatus for machining, P (11) 284*b*.
porcelain, cylindrical, and bushings, ways and means to increase mechanical strength, (2) 46*h*.
process and apparatus for rough shaping soft-paste blank for production of, P (11) 284*b*.
seals, glass-ceramics for, (4) 93*a*.
spark plug, process for producing by dry pressing, P (11) 284*b*.
suspension, studies on texture of green bodies, (5) 125*i*.
tall shell, (9) 228*d*.
Interferometers, two-beam, for analyzing ternary mixtures, methods and instruments, P (5) 132*c*.
Intermetallic compounds, transition metal-aluminum and metal-silicon, nature of atomic interaction, (1) 23*e*.
Ions. See also *Cations.*
alkali, in fused alkali nitrates, ionic mobilities and tracer diffusion coefficients, (8) 201*a*.
beam, for coating silicon semiconductor with indium, P (3) 79*a*.
bombardment, for treating semiconductor device, P (9) 231*c*.
chloride, repulsion by negatively charged clay surfaces: I, univalent cation Fithian illites; II, univalent cation montmorillonites: III, di- and trivalent cation clays, (7) 167*j,a,b*.
Cr^{3+} and Mn^{4+}, in magnesium oxide, (7) 167*h*.
complex, in molten salts—computer method for calculation of stability constants from metal-ion concentration data, (8) 192*e*.
exchange, in glass, (8) 175*c*.
kinetics, effect of tactoid formation in montmorillonite, (4) 111*i*.
of metals, with weakly acidic silanol group of silica gel, (8) 197*g*.
strengthening of alkali aluminosilicate glasses, (2) 37*i*.
exchangers, inorganic, (11) 297*h*.
molten borate, for extraction of fused salts of europium and neodymium, P (11) 291*f*.
phosphates, (1) 29*j*.
gas, noble, eject electrons from barium oxide, (3) 85*g*.
H^- and D^-, in alkaline earth fluorides, localized vibrations of, (8) 201*d*.
impurity, effect on hydrothermal synthesis of corundum, (3) 85*e*.
ionic conductivity of zirconia, some applications, (2) 47*c*.
ionic mobilities, of alkali ions in fused alkali nitrates, (8) 201*a*.
ionic model, partially, for alkaline earth oxide modules, (3) 87*j*.
Mn^{2+}, absorption in glasses, (2) 35*j*.
negative, device for forming from iodine gas and lanthanum boride contact ionizer surface, P (11) 285*d*.

Ions (*continued*)
oxygen, effect of glass composition on activity in glasses, (2) 36*j*.
partition, in ammonium alum, (8) 204*a*.
size, effect on membrane potentials, (7) 163*e*.
tetravalent cobalt, in α-Al_2O_3, (7) 168*i*.
unlike, diffusion into liquid sodium chloride, (8) 194*i*.
Iridium, $IrAs_3$, thermal expansion, high temperature X-ray study of, (3) 86*g*.
$IrSb_3$, thermal expansion, high temperature X-ray study of, (3) 86*g*.
as protection for graphite, (1) 7*g*.
silicide, structure and composition, (5) 138*a*.
Iron. See also *Enameling metals; Steel.*
absorption, in silicate and borate glasses, correction, (5) 119*h*.
chlorides, thermochemical transformations, (4) 111*j*.
cordierite, in core structure of bloated building brick, (4) 96*a*.
crude ore, for quality ferrites, (4) 100*c*.
determination, in ores and slags, (5) 130*h*.
selective, by potassium cyanide-potassium ferrocyanide reagent, (10) 267*g*.
disintegration, while dissolving in acids, (4) 91*i*.
effect in flame-photometric determination of calcium, (2) 51*b*.
effects in ultraviolet absorbing green glass, (2) 36*d*.
ferrophos, refining, P (5) 133*g*.
ferrosilicon, in graphite crucible composition, (7) 152*j*.
ferrous, as near infrared absorber in phosphate glasses, (4) 92*h*.
materials, two-stage process for derusting and protecting surfaces, P (3) 65*f*.
metal, embrittlement-free pickling, P (7) 147*i*.
metal substrate, Cr-Fe diffusion coating, P (3) 65*d*.
group oxides, effects on stabilization of ZrO, (3) 85*f*.
(III), hydrolysis in NaCl, (10) 272*d*.
(III)phosphates, precipitation effects, (3) 87*e*.
Fe(III) ion, and solubility product of $Fe(OH)_{2.7}Cl_{0.3}$ in 0.5M $(Na^+)Cl^-$ medium, hydrolysis of, (11) 297*c*.
Fe-26Cr alloys, scaling at 870° to 1200°C, (11) 300*f*.
xFe_2-TiO_4·$(1 - x)Fe_3O_4 (x > 0.5)$, magnetocrystalline anisotropy and magnetostriction, (8) 202*i*.
Fe^{3+}, in $BaTiO_3$, electron spin resonance in the rhombohedral and cubic phases, (8) 196*c*.
in $Ga_{2-x}Fe_xO_3$ crystals, segregation studies, (4) 107*h*.
Fe_3C, bond state of carbon atoms in, (4) 110*e*.
Fe_xO, magnetic properties as related to defect structure, (8) 202*g*.
FeO_{2}-CaO slags, electrical conductivity, (9) 238*b*.
Fe_2O_3, behavior on heating in refractory bodies of system kaloin-quartz-talc-Fe_2O_3, (8) 191*d*.
γ-α transformation, (8) 192*f*.
α-Fe_2O_3, crystal growth by flux method, (4) 107*h*.
precipitated from silicate melts, superparamagnetic behavior, (7) 156*d*.
δ-Fe_2O_3, structural and chemical alterations, and their effect on magnetic properties, (4) 100*d*.
γ-Fe_2O_3 particles, coercivity, (8) 192*e*.
to α-Fe_2O_3 transformation, electron diffraction study and theory, (5) 135*i*.
Fe_2O_3-Mn_2O_3, solid solutions magnetic behavior, (8) 202*f*.
Fe_2O_3-B_2O_3 mixtures, for vacuum-deposited magnetic thin films, (3) 77*f*.
Fe_2SiO_4, from 4° to 300°K, magnetic properties, (8) 207*h*.
in mineral, X-ray fluorescence method for determination, (11) 289*g*.
molten, causes corrosion of silicon nitride refractory, (11) 280*j*.
-nickel oxides, dissociation pressures, (7) 162*c*.
ores, nonmagnetic, methods of treating, P (2) 54*a*.
oxide, α-ferric, stable remanence and memory, (9) 237*e*.
effects on some physical and chemical properties of glass, (2) 36*e*.
ferric, aged, dissolution property in sulfuric acid solution, (4) 110*f*.
ferric, precipitated, structure change during aging in water, (4) 111*b*.
ferric systems. See *Systems.*
magnetic, use of kiln gas for making, P (2) 54*e*.
pigments, containing manganese, P (1) 15*h*.
recovery from treatment of serpentine with ammonium bisulfate, P (11) 292*d*.
systems. See *Systems.*
ultrafine, production by reacting ferric chloride with nitrogen dioxide, P (11) 292*c*.
wet ball-milling, B (7) 169*j*.
oxides, deformation at high temperatures, (2) 56*b*.
porous, diffusion of H_2-H_2O through, (9) 238*g*.
pyrites, thermal expansion, (7) 169*b*.
reaction study, with enamel melts, (5) 117*h*.
recovery process, from red slurries obtained in processing bauxite by Bayer process, P (4) 107*a*.
removal, from phosphoric acid, process, P (7) 148*a*.
from quartz sand by grinding in counter-flow mill, (8) 189*g*.
role, in flotation of silicates, (4) 106*e*.
in oxidation of molybdenum disilicide, (9) 242*a*.
salts, process to eliminate from raw materials, P (3) 83*c*.
scale, in highly refractory cements, (4) 97*c*.
silicides, thermophysical characteristics, (1) 29*a*.
in sodium trisilicate glasses, Moessbauer studies, (10) 252*i*.

Iron (*continued*)
solid, diffusivity of oxygen, (10) 250*g*.
solubility, permeability, and diffusivity, (10) 250*g*.
sponge, process for production, P (4) 107*d*.
in strong alkalis, spectrophotometric determination, (1) 51*i*.
sulfide, influence on decomposition rate of zinc sulfate at 600°C, (8) 200*e*.
systems. See *Systems.*
tungstate, interaction with sodium ditungstate, (4) 108*j*.
zeta Fe_2N-type sublattice order, evidence in WC at intermediate temperatures, (7) 163*b*.
zone-refined, oxidation, effect of oxygen pressure, (11) 294*c*.
Irradiation. See also *Radiation;* specific types.
beta-ray, source, (9) 230*c*.
effects in glasses, suppression by synthesis under high-pressure hydrogen, (9) 218*g*.
gamma, of α-Al_2O_3 spheres subjected to 30-k pressure, (2) 56*f*.
of graphite, growth of interstitial clusters, (8) 199*a*.
of graphite and carbon, dimensional changes from, (8) 202*b*.
induced defect bleaching in pressure deformed single crystal α-Al_2O_3, (1) 19*c*.
neutron, effects of electrical properties in vitreous carbon, (10) 271*f*.
fast, effect on Cu elastic modulus of highly oriented pyrolytic graphite, (8) 195*g*.
of graphitic materials, (2) 55*h*.
for lattice expansion in LiF crystals, (7) 165*d*.
of Linde molecular sieve 13X, (1) 23*f*.
of magnesium oxide, dose dependence of F-center production, (1) 18*e*.
of oxides and crystal structure at 80°C, (1) 17*i*.
of sapphire, (9) 241*d*.
nuclear, with ultrahigh pressure, combined effect on solid-solid phase transformations, (2) 54*i*.
radioactive, effect on semiconductors: I, effect of neutron irradiation on *n*-germanium, (1) 18*g*.
X-ray, effects of characteristics of metal-oxide-silicon structures, (9) 238*j*.
Isotopes. See also *Radioactive tracers.*
effect on lattice heat conduction of lithium fluoride, (8) 195*c*.
oxygen-, fractionations in systems containing dolomite, (1) 24*f*.
radioactive, for study of lining conditions, (9) 234*c*.

Jewelry. See *Art and artware.*
Joints, ceramic to metal, P (1) 3*b*.
filling composition, P (1) 2*c*.
furnace, P (9) 234*j*.
Junctions, electrochemical liquid, structure and method for making, P (2) 38*e*.
hetero-, GaAs-GaP, GaAs-Ge, and GaP-Ge, preparation and properties, (3) 76*i*.
germanium-silicon alloy, (4) 100*g*.
photovoltaic, simple method of making, (11) 287*f*.
pn, contacting, P (4) 100*i*.
copper diffused gallium arsenide, (4) 100*a*.
in Ge, Si, GaAs, and GaP, avalanche breakdown voltages of abrupt and linearly graded, (9) 228*i*.
having bulk breakdown only, and method of producing, P (7) 157*e*.
method of improving, P (2) 48*j*.
passivation method and product, P (4) 101*g*.
on semiconductor component, P (1) 11*e*.
semiconductor devices, and method of making, P (4) 102*f*.
semimetal devices, P (5) 129*f*.
surface gradient protected high breakdown, P (11) 287*j*.

Kaolin, calcined, acid treatment, P (8) 190*b*.
calcined, method of reclaiming from de-inking sludge residue, P (8) 190*d*.
calcined pigments from, P (7) 160*j*.
clay, coated with neutralized monomeric N,N-diallylmelamine, and polyester resins containing, P (4) 106*c*.
deposits, and exploitation, of Quessoy, (7) 160*g*.
of Georgia and S. Carolina coastal plain, mineralogical and chemical variations, (1) 23*g*.
in Tirschenreuth, (3) 82*g*.
double dilatometric analysis of, (11) 289*f*.
effect on properties of forsterite porcelain, (2) 46*d*.
Hiraki, geology, deposits and mineral composition, (3) 86*a*.
from Kemmlitz in Saxony, mineralogical and technological studies, (2) 53*j*.
of Ledce (Plzen Basin, Czechoslovakia), investigation of mineralogy and preparation of, (3) 82*j*.
minerals, containing LiF, composition of mullite in, (5) 134*f*.
infrared vibrational spectra, (1) 20*d*.
thermal reaction, effects of fluoride as mineralizer, (5) 135*a*.
mining and beneficiation, B (1) 30*b*.
raw, from Sedlec (Zettlitz) in Bohemia, heavy minerals in, (3) 82*h*.
reactions during firing, infrared study, (9) 224*e*.
suspensions, rheology, effect of introducing air bubbles, (7) 154*i*.
systems. See *Systems.*
ultramicrotome sections, the metakaolinite problem, (5) 139*a*.
-water suspensions, with additions of basic aluminum chloride complex, electrophoretic mobility, (7) 154*h*.
-water mixtures, flow properties, effect of mechanical vibration, (7) 154*i*.

Kaolinite, in clays, estimation by infrared method, (8) 187*d*.
concentrated suspensions, flow properties investigated by extrusion rheometer, (11) 289*h*.
content, determination in clay or kaolin, (5) 135*b*.
dehydration, new method for determining enthalpy and entropy, (11) 298*d*.
disordered, identification, (4) 108*f*.
filter cakes, flocculated, permeability and washing characteristics, (5) 133*b*, *d*.
main endothermal effect, temperature, (8) 209*f*.
-metakaolinite, model of solid with extremely high lattice defect concentrations, (8) 201*c*.
microstructure, (7) 150*j*.
single crystals, hydrogen liberation during dehydration of, (8) 201*a*.
surface area and crystallinity, factors in base exchange capacity, (11) 292*j*.
surfaces, infrared studies of hydrogen bonding interaction with intercalated potassium acetate, hydrazine, formamide, and urea, (1) 20*a*.
Kiln furniture, saggers, method of increasing life, (4) 97*g*.
saggers, silicon carbide, for porcelain industry, (9) 224*g*.
Kilns. See also *Burners; Furnaces; Ovens.*
P (8) 189*b*.
brick, means for holding in rotary kiln, P (10) 259*e*.
for brick, combines rapid drying and firing, (2) 52*e*.
car lubrication system, P (9) 235*c*.
cement, apparatus for alkali metal condensation in, P (3) 64*b*.
method and plant for removing alkalis from flue gas emanating from, P (9) 215*i*.
method of and apparatus for recovering alkali substances from flue gases, P (2) 35*b*.
cement shaft, reaction zone, analytical treatment, with reference to effect of CO loss, (5) 116*b*.
ceramic, improvements, P (2) 53*c*.
conditions, thermocouples in combination with mathematical model used for measuring, P (1) 14*f*.
continuous, for brick, P (10) 268*f*.
continuous sliding bat passage, and use in ceramic industry, (5) 132*d*.
cross circulation, P (2) 52*e*.
downdraft vertical, P (2) 52*g*.
drop arches for, P (1) 14*i*.
electric tunnel, for firing hard porcelain in a reducing atmosphere, (8) 189*a*.
gas, for making magnetic iron oxide, P (2) 54*e*.
glass drawing, L-block, P (5) 120*j*.
improved, for lime manufacture, (10) 268*h*.
industrial ceramic, heated by combustible liquid, P (5) 132*e*.
lime-burning, review, (5) 116*j*.
linings. See *Refractories.*
operation, P (9) 235*c*.
and related apparatus, P (11) 290*e*.
revolving tubular, preheaters for, P (2) 53*e*.
roller hearth tunnel, P (10) 268*j*.
roof construction, P (5) 132*h*.
rotary, P (2) 53*c*.
apparatus for lining, P (4) 105*h*.
basic refractory for, P (4) 98*c*.
cement production in, P (5) 116*d*.
chain for, P (1) 14*j*.
constant or variable cross section, (9) 214*b*.
cooler for, P (1) 14*i*.
feed preheating for, and like installations and to preheaters, therefor, P (1) 14*i*.
for firing chamotte, P (11) 290*h*.
improvements, and analogous chemical reactors, P (7) 160*c*.
journalling structure for, P (7) 160*c*.
for lightweight material production from wet plastic clay, (3) 80*f*.
method and apparatus for control with calcining rate meter, P (7) 160*e*.
with preheater, P (3) 82*b*.
process and apparatus for heating particulate solids in, P (11) 290*g*.
for production of burnt lime, P (4) 91*f*.
radial deformation in, (9) 234*i*.
recovery of radiant heat losses from shells of, P (3) 82*a*.
scraper, P (4) 105*h*.
wet process, automatic charting, (5) 132*c*.
rotary shaft, for calcining granular or lumpy materials, P (4) 105*h*.
shaft, production of dead-burned, refractory grain in, P (1) 8*a*.
radial velocity, of particle flow in, (7) 146*j*.
sheet metal, stilt, P (9) 235*c*.
system and method, P (1) 14*j*.
tunnel, P (10) 269*a*.
advantages, (3) 81*i*.
car, P (2) 53*d*.
cars, automatic return, (5) 132*c*.
cars, development of fully automated transport installation for, (3) 81*j*.
construction, (3) 82*a*.
design characteristics with internal width of 6 meters, (2) 52*e*.
with different fuels, heat efficiency data for firing of porcelain, (3) 74*b*.
door operator for, P (4) 105*d*.
for drying heavy ceramics, improvements, P (7) 160*d*.
fast fire, P (8) 189*c*.
for firing ceramic ware, P (1) 15*c*.
improvement, P (2) 53*a*.
indirectly heated, P (1) 14*j*.
muffled, increasing efficiency, (2) 41*j*.
open flame, conversion to oil firing, (1) 14*h*.
operating with natural gas, (8) 189*a*.
process for equalizing temperature in, and kiln, P (10) 268*i*.

Kilns, tunnel (*continued*)
process and device for firing ceramic body in, P (2) 53*a*.
study after operation for two years at 1750°C, (7) 160*b*.
two operated in modern refractories plant, (4) 97*i*.
vertical, for continuous grain calcination, P (1) 15*a*.
zigzag, (3) 81*j*.
Kinetics, of alkali silicate glasses solution, effect of thermal history, (3) 66*e*.
of anodic dissolution of germanium, (7) 164*g*.
of barium oxide on tungsten, field emission studies, (3) 85*j*.
of cement hardening, study by electrochemical method, (4) 91*a*.
dissolution, of quartz spheres in sodium silicate melt, (11) 276*h*.
of epitaxial silicon deposition by low pressure iodide process, (11) 297*f*.
of Frenkel defects recombination in anodic oxide films on tantalum, (7) 167*i*.
of glass reactions with aqueous solutions, (2) 37*h*.
growth, of discontinuous thermal oxide films, (3) 86*a*.
of liquid phase oxidation of nonirradiated and irradiated nuclear graphites, (2) 55*e*.
of liquid silicon with silica reaction, (1) 21*e*.
and mechanism of reaction between $BaCO_3$ and ZnO, (10) 271*b*.
molybdenum oxidation, at high temperature, (11) 298*a*.
of near-equilibrium reduction of wustite, (9) 240*a*.
of nickel oxalate decomposition, (1) 21*c*.
of opacification of TiO_2-opacified cover coat enamel, (4) 92*a*. of oxide film growth on zirconium, (5) 136*i*.
of photoconductivity, effect of intercrystalline barriers, (11) 294*a*.
of physicochemical processes of cement clinker formation, (9) 214*g*.
of radiocoloration and phosphorescence of borate glasses, (8) 175*i*.
of reactions, of elemental fluorine, with zirconium and zirconium diboride at high temperatures, (8) 201*j*.
of elemental fluorine: II, fluorination of hafnium carbide and hafnium boride; III, fluorination of silicon and boron, (8) 201*j*.
of magnesia, silica and alumina with melts of ternary system CaO-SiO_2-Al_2O_3, (8) 201*i*.
of uranium monocarbide with water, (11) 297*f*.
of simultaneous internal oxidation and external scale formation for binary alloys, (9) 240*e*.
sintering, study by sensitive resonant frequency technique, (4) 104*e*.
of solid state reactions, (8) 201*i*.
study of bismuth electrodes in molten lithium chloride-potassium chloride, (8) 201*f*.
theory for adiabatic reaction $A + BC \rightarrow AB + C$, (1) 23*i*.
of thermal decomposition of calcium hydroxide, (1) 21*g*.
of thermal oxidation of silicon in dry oxygen, (1) 21*j*.
of UO_2 sintering between 950° and 1500°C in dry hydrogen atmosphere, (11) 297*h*.
of wustite disintegration, (3) 86*g*.
of zirconium-carbon reaction above 2000°C, (7) 164*j*.
Krypton, physisorption on glass and molybdenum films, (2) 36*j*.
radioactive, inclusion in aluminum oxides during thermal surface changes, (2) 55*d*.
Kyanites, -andalu[illegible]te equilibrium from 700° to 800°C, (1) 21*c*.

Laboratories. See also *Research and research laboratories*.
glass, use of electron microanalyzer, (10) 253*j*.
Ladles. See *Refractories*.
Lamps. See also *Glass*.
bulb, assorting apparatus, P (9) 220*c*.
coating apparatus, P (9) 220*c*.
fluorescent, spiral groove forming device, P (10) 255*c*.
curved gas discharge, method of making, P (3) 68*h*.
electric, coating comprising agglomerates of silica coated with pigment, P (8) 184*i*.
double-ended, method of making, P (4) 95*c*.
fabricated infrared-generating devices, method of reshaping, P (7) 150*e*.
manufacture, P (5) 120*e*.
with tubular body and light transmitting closure having overlapping flange seal, P (9) 219*g*.
electric discharge, high-current seal for, P (1) 10*i*.
low-pressure, with internal elongated structure, P (3) 78*b*.
electric incandescent, P (2) 38*d*.
filament mount and heat shield structure, P (2) 47*g*.
method of producing, P (2) 39*a*.
electroluminescent, ceramic type, (1) 9*h*.
with barium titanate layer, P (2) 47*d*.
with boric acid or boric oxide used in conjunction with zinc sulfide layer, P (2) 47*e*.
with homogeneous phosphor-dielectric layer, P (3) 78*c*.
with moisture resistant vitreous light-transmitting material including 4 to 8% LiF, P (3) 78*c*.
structure having phosphor particles dispersed in modified cyano-ethylated polyvinyl alcohol resin, P (7) 156*b*.
technique for examining luminous activity of individual phosphor particles in, (4) 104*e*.
Lamps, electroluminescent (*continued*)
with transparent nickel, chromium, iron alloy metal electrode, P (10) 263*f*.
flash, manufacture, P (5) 120*f*.
fluorescent, coating, P (7) 156*e*.
high-output, with improved phosphor-coated glass structure, P (11) 285*g*.
high temperature, with reflector having mercury amalgamative material on electrode stems, P (2) 47*j*.
method and apparatus for making, P (3) 68*g*.
fluorescent electric discharge, with phosphor particles admixed with indium powder particles, P (11) 285*e*.
gas discharge, apparatus relating to evacuating and filling, P (7) 149*h*.
gaseous discharge, with internally cooled electrodes, P (7) 149*d*.
green radiation, for optical maser, P (8) 184*e*.
grooved reflector, P (3) 68*a*.
high intensity atomic spectral, P (5) 127*g*.
incandescent, differential output tubular, P (3) 77*i*.
electric, method of filling with gas and sealing, P (7) 150*a*.
gettering impurities, P (8) 178*a*.
including fluorine gas atmosphere and solid fluorinating agent, P (7) 149*f*.
manufacturing process, P (11) 279*h*.
method of orienting filaments in, P (4) 95*c*.
with TaC filament and cyanide-radical producing and halogen atmosphere, P (1) 11*a*.
tungsten filament, modern no-dazzle, (1) 4*b*.
incandescent electric, P (8) 177*h*.
mercury vapor, seasoning and sealing method, P (3) 68*e*.
metal vapor, with heat reflecting coating of calcium pyrophosphate, P (9) 220*e*.
photoflash, P (5) 121*d*.
method of making, P (8) 178*g*.
plant growth, P (2) 49*a*.
reflector arc, with arc tube support, P (11) 279*c*.
tantalum carbide incandescent, and method of manufacture, P (2) 49*b*.
tubular, method of providing, P (9) 221*h*.
Lanthanides, separating method, P (1) 15*j*.
sulfides, thermal properties, (2) 58*h*.
Lanthanons. See *Rare earths*.
Lanthanum, hexaboride, floating zone crystal growth, (7) 163*f*.
hexaboride, infrared radiation transmitting and visible radiation reflecting layer, for optical device, P (2) 48*h*.
LIII X-ray absorption spectra, in compounds with nonmetals, (4) 108*c*.
$LaAlO_3$-$LaGaO_3$, chromium fluorescence in, (11) 292*j*.
$La_2Ce_2O_7$, investigation by neutron diffraction, (7) 166*j*.
$LaInO_3$, doped, electrical properties and band structure, (9) 229*e*.
orthotantalates, (1) 24*b*.
oxidation, high-temperature, observations, (7) 167*g*.
oxide, fusion point measurement, (7) 159*e*.
phosphates, precipitation effects, (3) 87*d*.
silicates, production, (8) 205*c*.
systems. See *Systems*.
tellurides, (8) 209*g*.
X-ray L-absorption spectra of, in tetra- and hexaborides with imperfect lattices, (4) 112*e*.
Lapping, apparatus, P (1) 14*d*.
Lasers. See also *Masers*.
P (5) 120*f*.
CdS electron beam pumped, high power and efficiency, (9) 229*c*.
CdS_xSe_{1-x}, efficient visible, by electron-beam excitation, (8) 196*a*.
cathodoluminescent pumped, having cathode surrounding laser, P (8) 184*d*.
diode, with metal contacts plated over sides of semiconductor, P (8) 184*j*.
of $Pb_{1-y}Sn_ySe$ and $Pb_{1-x}Sn_xTe$, (11) 293*c*.
electron-beam pumped, of CdSe and CdS, (5) 135*h*.
GaAs injection, room-temperature pulse-operated, optimum design for, (3) 76*e*.
grooved active medium for, P (4) 101*h*.
heating, in flame spraying, P (7) 147*j*.
host crystal, calcium orthovanadate $Ca_3(VO_4)_2$, (9) 228*i*.
-induced damage in glass, compositional dependency, (7) 148*d*.
for inspecting glass containers, P (5) 120*e*.
light source for optical diffractometers—Fourier analysis of electron micrographs, (1) 13*j*.
for ultramicroscopy and light scattering by imperfections in crystals—imperfections investigation in LiF, MgO, and ruby, (1) 21*e*.
materials, P (11) 285*i*.
microprobe, to identify inclusions, (3) 80*i*.
modelocked glass: Nd, optical spectra of ultrashort optical pulses generated by, (10) 271*g*.
Nd^{3+} glass, high-repetition pulsed, (11) 287*j*.
Nd^{3+}-doped glass, mode locking of, (1) 10*c*.
properties of vapor-grown ruby, (8) 183*c*.
pulsed metal vapor, high temperature alumina discharge tube for, (1) 9*j*.
rods, Nd^{3+}: glass, optically pumped, effect of surface finish on temperature distribution in, (5) 135*j*.
ruby, with external mirrors of large spacing, (11) 300*f*.
Faraday-switched, (8) 183*i*.
internally modulated, for second-harmonic enhancement, (3) 76*e*.
quasicontinuous giant pulse, using a saturable absorber as Q switch, (1) 10*d*.
room temperature CW, single-mode operation, (5) 138*d*.
Lasers, ruby (*continued*)
study on saturation process by anomalous dispersion of, (11) 301*j*.
semiconductor devices, high power, P (5) 127*h*.
solar pumped, P (4) 102*g*.
solid body, glass for, P (9) 220*g*.
solid state, (9) 230*b*.
glass as material for, (10) 252*e*.
ultraviolet, emission in electron-beam-excited ZnS, (10) 271*a*.
versatile, and principle, (8) 184*a*.
ZnO, ultraviolet, pumped by electron beam, (8) 183*j*.
Lattice constants. See *Crystals, structure*.
Lattice defects. See *Crystals*.
Lattices. See *Crystals*.
Lavas, flows, fractionation trends of basalt magmas, (1) 18*j*.
Leaching, of enamels and glasses, basic research, (3) 64*j*.
Lead. See also *Glass; Glazes*.
activation, in sulfonate flotation of quartz, (4) 106*a*.
antimonate crystals, orientation on aluminum porcelain enamel surface, (5) 117*f*.
-barium and -strontium ferrites, magnetic properties, (1) 22*a*.
borate glaze, low solubility, (2) 46*e*.
bromide, pure molten, transport numbers by balance method, (8) 210*g*.
ternary system, (2) 57*f*.
carbonate, heats and free energies of formation, (1) 19*a*.
potentiometric determination of solubility product of, (3) 81*b*.
in ceramics, (2) 53*j*.
chloride, molten, self-diffusion, (7) 167*f*.
evaporated films, reaction of oxygen with, (8) 183*h*.
isotope 210, tests, P (7) 159*i*.
$PbAl_{12}O_{19}$, X-ray and electron microscope study, (9) 243*i*.
$Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics modified with additives, piezoelectric properties, (1) 10*c*.
PbO-PbF_2 flux crystal growth, localized cooling, (7) 165*e*.
Pb_3O_4, bonding in, and structural principles in stoichiometric lead oxides, (8) 191*g*.
PbSe and PbTe, diffused junction diodes, (4) 100*e*.
PbTe-SnTe alloys, under influence of ultrasonic agitation, solidification, (10) 263*h*.
monoxide, mass-spectrometric study of vaporization, (1) 22*f*.
red, bonding in, (8) 191*h*.
and uranium dioxide, interactions, (8) 200*d*.
yellow form, bonding in, (8) 191*h*.
orthophosphate $(Pb_3(PO_4)_2)$, $Pb_3(VO_4)_2$, and $Pb_3(AsO_4)_2$, (5) 136*j*.
oxide, ultrapure, preparation, (8) 205*a*.
oxides, process for producing, P (9) 236*h*.
semiconducting intermetallic compounds, retrograde solubility, liquidus curves in Pb-S, Pb-Se, and Pb-Te systems, (7) 167*c*.
-silica glass, viscosity, NBS Standard Reference Materials, (2) 37*i*.
sulfide, influence on decomposition rate of zinc sulfate at 600°C, (8) 200*e*.
sulfide films, high-mobility, deposited under ultrahigh vacuum equilibrium conditions, (10) 262*d*.
systems. See *Systems*.
telluride, chemical polish for, (9) 229*b*.
crystals, preparation, (10) 263*b*.
layered structure, helicon-drift current interaction, (11) 296*f*.
tellurides, thermodynamic properties, (3) 77*c*.
-tellurium matrix, for two-phase thermoelectric body, P (2) 49*f*.
titanate, crystals, orientation on aluminum porcelain enamel surface, (5) 117*f*.
powder, process for producing, P (10) 265*a*.
zirconates, texture, dependence of coupling factor and polarization behavior on, (11) 284*g*.
titanates and niobates, method of preparing and coating to form capacitor, P (10) 264*h*.
zirconate-lead titanate, ceramics, firing, P (2) 48*g*.
ceramics containing 2% (at.) bismuth, analysis of hot pressing parameters, (1) 9*f*.
materials, vaporization, (10) 272*a*.
zirconate-titanate, ceramics, effect of PbO deficiency on piezoelectric properties (10) 262*h*.
ceramics, polarity effects and charge liberation under high dynamic stress, (5) 126*e*.
ceramics, relation of lead vaporization and concentration of lead deficiencies, (3) 76*b*.
crystals, preliminary study on growth, (3) 87*f*.
process for producing dense ceramic of, P (5) 128*i*.
Lehrs. See *Furnaces; Glassmaking apparatus and equipment*.
Lenses. See *Glass, optical*.
Light, conducting systems, glass-plastic laminates as, (10) 252*g*.
deep submergence undersea, dome-shaped glass housing for, (10) 251*a*.
effect on oxide films formed on copper single crystal surfaces in water, (7) 166*f*.
infrared, and elastic wave interactions with moving high-field domain in piezoelectric semiconductor, (11) 294*a*.
modulators, semiconductor, P (4) 102*f*.
polarized, used in illuminating apparatus for microscope system, P (1) 14*d*.
rays, from magnesia and corundum—effect of temperature, (2) 56*d*.
scattering, for determining shape of colloidal particles, P (4) 104*h*.

Light, scattering (*continued*)
for determining small particle size, (3) 84*i*.
of spherical particles, (3) 86*c*.
sealed beam, with glass-beaded light reflecting shield, P (3) 69*d*.
sensor, small package, P (1) 11*i*.
short-duration, source comprising an electron irradiated transparent insulating body, P (2) 40*c*.
signal, U.S. standard for colors, (3) 66*j*.
to sound conversion by electrostrictive mixing in solids, (8) 183*g*.
source, modulated, for electro-optical analysis of spectral lines, P (4) 104*j*.
planar *pn* junction, with reflector means to collimate emitted light, P (3) 79*i*.
semiconductive alloy, having improved optical transmissivity, P (4) 102*c*.
transmission, by glass fiber bundles, (10) 252*b*.
of hot-pressed alumina, (7) 168*i*.
Lime. See also *Calcium, oxide; Glass.*
-bentonite reaction products, X-ray studies, (7) 169*e*.
burning, requirements of lime and development tendencies, (5) 116*j*.
burnt, production with rotary kiln and rotary hearth, P (4) 91*f*.
determination in chrome-bearing materials, (5) 130*h*.
particles, dissolution in primary glass melts, (3) 66*c*.
powdered, preheating and thermal treatment, P (2) 35*b*.
production, P (2) 35*a*.
quick-, raw powder, for cement clinker, P (7) 147*b*.
requirements in burning, (5) 116*j*.
-silica, body of high porosity, process of manufacturing, P (11) 284*a*.
slaking process, P (5) 117*a*.
-soda sinter process, correlation of reaction products with extractability of alumina from anorthosite, (10) 269*d*.
systems formed by, with oxides of type C rare-earth elements, (2) 57*a*.
Limestone, contact-metamorphosed, geothermometry from thermoluminescence, (11) 298*j*.
decarbonation, mechanism, (5) 116*h*.
of different structures, specific features of mineral formation during firing of charges with, (10) 248*g*.
distinguished from dolomite by bromophenol blue, (5) 130*j*.
in Hazaribagh district, Bihar, (8) 189*h*.
Madison, Wind River, Washakie, and Owl Creek Mountains, Wyoming, (8) 201*j*.
middle Devonian, in South Devon, England, petrology, (1) 25*d*.
Mid-Visean (S_2-D_1), near Hartington, Derbyshire, England, detailed study of microfacies, (8) 194*j*.
prospects of Tundapathar, Ambala district, Punjab, (8) 189*h*.
Upper Jurassic, of southern England, silica diagenesis in, (8) 206*h*.
Linings. See also *Refractories.*
brake, materials and articles made therefrom, P (7) 153*a*.
friction, for aircraft brakes, P (10) 250*d*.
Liquids. See also *Fluids.*
apparatus for reducing particle concentration in volume of, P (7) 158*h*.
compressibility, apparatus and method for measuring, P (7) 159*g*.
+ liquid systems, effect of oscillating electric fields on coalescence, (7) 162*f*.
media, pumping and deaerating, P (5) 130*e*.
reactions with solids, process and apparatus, P (2) 45*b*.
or semi-, materials of low thermal conductivity, process and apparatus for cooling, solidifying, mixing, and extruding, P (7) 158*k*.
treatment apparatus, P (4) 103*j*.
viscous, model study of mixing in crucible, (10) 252*g*.
Lithia. See *Lithium, oxide.*
Lithium, aluminum hydride, preparation, P (11) 291*b*.
aluminum silicate hydrate product, swelling, P (5) 126*b*.
bromides, ternary system, (2) 57*f*.
chloride, preparation and purification, P (1) 16*c*.
slip plane, (8) 207*e*.
chlorides, ternary reciprocal system, (2) 57*f*.
cryolite, phase transitions and structure, (10) 271*a*.
determination of trace amounts of, in silicate rocks by direct current arc spectrographic technique, (2) 50*i*.
ditungstate solvent, cerium dioxide single-crystal growth from, (4) 109*e*.
ferrites, dense, magnetic properties, (8) 183*g*.
fluxes for sintering, P (4) 101*g*.
ordered, process for growth, P (5) 128*h*.
ferroaluminate, basis for ferrite composition, P (10) 263*i*.
fluoride, cleavage, plastic deformation during, (7) 166*d*.
crystal surfaces, frictional anisotropy, (11) 296*g*.
crystals, effect of loading duration on indentation hardness, (3) 85*b*.
crystals, lattice expansion by neutron irradiation, (7) 165*d*.
crystals, theoretical determination of cohesive energy, lattice parameter, and compressibility, (8) 209*b*.
dislocations in, B (3) 88*g*.
effect on hot-pressing of MgO, (8) 195*e*.
electrons, plasma oscillation, (8) 205*c*.
Lithium, fluoride (*continued*)
lattice heat conduction, effect of isotopes, (8) 195*c*.
method of producing, P (9) 236*a*.
phosphor, thermoluminescent doubly doped, P (8) 186*b*.
as substrate in growth of thin film Permalloy, (9) 240*b*.
fluorides, ternary reciprocal system, (2) 57*f*.
hydrazinium sulfate, ferroelectric, infrared spectrum, (8) 183*j*.
ferroelectric, thermal expansion, (8) 183*i*.
$Li_xNi_{1-x}O$ single crystals, electrical properties, (9) 238*c*.
$Li_{1+x}V_2O_5$ $\pm$ λ solid solutions, and preparation of $LiVO_3$ and Li_3VO_4, (8) 208*c*.
metagallate, devices utilizing, P (2) 47*c*.
niobate, application of new technique for measuring magnitudes of photoelastic tensors, (8) 203*a*.
crystal, single-domain, acoustic attenuation at microwave frequencies, (9) 237*b*.
elastic wave attenuation, (9) 238*a*.
far infrared optical properties, (11) 295*b*.
ferroelectric: I, growth, domain structure, dislocations and etching; II, preparation of single domain crystals; III, single crystal X-ray diffraction study at 24°C; IV, single crystal neutron diffraction study at 24°C; V, polycrystal X-ray diffraction study between 24° and 1200°C, (8) 197*j*, 198*a-h*.
infrared dielectric dispersion, (8) 183*j*.
and $LiTaO_3$, ferroelectric, optical properties, temperature dependence of, (9) 242*c*.
oxide, having active absorption capacity for carbon dioxide and method of preparing, P (9) 235*j*.
recovery, from lithium-bearing ores, P (4) 107*b*.
method, P (5) 133*c*.
salts, production, P (7) 161*c*.
sulfates, in portland cement clinker, to improve physicomechanical properties, (4) 90*k*.
systems. See *Systems.*
tantalate, single-domain ferroelectric, electrooptic coefficients and elastic-wave propagation, (5) 135*j*.
values, extraction from brines containing calcium salts in presence of ammonia, P (5) 133*i*.
Lubricants, emulsifiable for glass molds, P (9) 219*h*.
graphite composition, of increased load carrying capacity, P (4) 98*j*.
impregnating in abrasive wheels, method, P (9) 213*h*.
Lubrication, boundary, metallic film diffusion for, P (8) 181*h*.
of vitreous fibers, P (4) 94*j*.
Luminescence, cathodo-, device for rapid identification of phase assemblages, (10) 267*c*.
cathodo-, of ruby, (2) 54*f*.
in Te-doped GaAs, (7) 162*g*.
due to isoelectronic substitution of bismuth for phosphorus in gallium phosphide, (8) 201*i*.
during anodic oxidation of silicon, (7) 165*f*.
electro-, ceramic type lamp, (1) 9*h*.
device, method for making, P (8) 185*f*.
device, surface-adjacent junction, P (4) 102*i*.
devices, heterojunction, P (10) 264*b*.
display device, hermetically encased, P (8) 184*f*.
flexible device, and light transmissive electrically conductive electrode material for, P (8) 184*c*.
from GaAs diodes at 300°K, (9) 229*d*.
injection, in ZnTe by avalanche breakdown, (7) 162*i*.
materials, P (2) 47*e*.
of rare-earth ions in cadmium fluoride, (5) 135*f*.
structure with improved protective transparent film, P (5) 127*j*.
of europium in ternary system La_2O_3-Gd_2O_3-Y_2O_3, (9) 240*h*.
manganese-activated, in portions of system $Zn(PO_3)_2$-$Cd(PO_3)_2$-$Mg(PO_3)_2$, (3) 87*a*.
in systems CdO-P_2O_5 and $Zn_2P_2O_7$-$Cd_2P_2O_7$, summary for system ZnO-CdO-P_2O_5, (7) 166*i*.
of molybdenyl phosphate, (11) 299*e*.
photo-, in boron doped silicon carbide, (7) 166*d*.
composition consisting of boric acid and fluorescein, P (3) 79*i*.
GaP, radiative pair and surface recombination in, (8) 206*a*.
spontaneous and coherent, in $Cd_xHg_{1-x}Te$, (5) 138*j*.
of KI/Tl single crystals, decay times, (8) 194*f*.
properties, of rare earth vanadates, (9) 240*i*.
radiophoto-, centers, in silver-activated phosphate glass, ERS studies, (11) 276*g*.
self-luminous compounds, radioactive: V, trapping center and cross section of excitation, (7) 167*c*.
thermo-, of alumina, (11) 302*d*.
of contact-metamorphosed limestone, geothermometry from, (11) 296*j*.
manganese-activated calcium fluoride, method of making, P (2) 48*j*.
Luminescent materials, P (2) 48*a*.
cataphoretic deposition, P (8) 185*b*.
compositions with europium and oxyanion-yielding ingredient aluminum, gallium, or germanium, P (2) 47*j*.
and manufacture, P (2) 48*a*.
molybdate and tungstate compositions, P (11) 285*j*.
red, product and process, P (4) 102*j*.

Machinery and equipment. See also *Materials handling* and specific types.
belt, dehydration, P (2) 40*j*.
door operator for tunnel kiln ceramic plant, P (4) 105*d*.
Machinery and equipment (*continued*)
for manufacture of plates from fiber loaded paste, such as asbestos-cement paste, P (9) 233*e*.
refrigeration cabinet, for laboratory freezing-and-thawing tests on concrete specimens, (11) 274*h*.
rotary work supporting, for use in pottery industry, P (3) 75*d*.
rotary scraping device for nodulizing drums in pelletizing plants, P (8) 190*h*.
for scoring and cutting ceramic mosaics, P (5) 125*j*.
for screening, P (2) 50*c*.
for sectioning ceramic tile, facing plates, P (5) 130*e*.
slurry pouring means, P (4) 103*j*.
for supply and atomizing of liquid in gaseous medium, P (4) 103*j*.
for suspending plates, saucers, during glaze firing, P (11) 283*h*.
tile press, outpaces glaze line, (4) 99*h*.
for treatment of liquid materials, P (4) 103*j*.
for trimming ceramics, P (10) 266*f*.
vibratory conveyor-mixer, P (4) 103*j*.
Magnesia. See *Magnesium, oxide.*
Magnesite. See also *Refractories.*
beneficiating, process of, P (5) 124*i*.
caustic burned, potentiometric studies, and properties as binder in hardened magnesium oxychloride cement, (11) 275*g*.
firing, influence of gas phase, (4) 97*d*.
method for estimation of silica in, (2) 51*c*.
for preparation of MgO, P (5) 124*i*.
Rajasthan, occurrence and refractory properties, (8) 189*j*.
sintering, effect of state of surface of particles, (10) 257*f*.
sinters, different, studies of brick from, (3) 70*h*.
evaluation with microscope and electron-beam microanalysis, (8) 197*f*.
Magnesium, aluminate, free energy of formation, from measurements made with galvanic cells involving solid electrolytes, (8) 198*f*.
heat of formation, (8) 199*j*.
hydrated, and process for preparing, P (4) 106*c*.
single crystals, stoichiometric, growth, (7) 164*a*.
aluminate, systems. See *Systems.*
-ammonium phosphates, solubility products, (5) 138*f*.
antimonide, thermodynamic properties, (11) 302*g*.
carbonate, basic, analytical studies, (11) 290*i*.
calcination, in sintering study, (1) 22*a*.
recovery from treatment of serpentine with ammonium bisulfate, P (11) 292*d*.
chromate, thermal decomposition, (4) 111*d*.
-chromium spinels, divalent chromium in, (8) 195*b*.
compounds, recovery from ores, P (2) 54*d*.
determination, by atomic absorption spectroscopy, (1) 13*g*.
in calcareous materials and silicates, (5) 130*i*.
in iron ores and slags, (5) 130*h*.
rapid, in presence of calcium and phosphate by titration with CDTA, (5) 131*b*.
difluoride, heat content of formation, (8) 198*b*.
di-, and tri-, phosphates, solubility products, (5) 138*f*.
ferrite, solid solutions, thermodynamics with magnetite, (2) 58*f*.
fluoride, articles, method of making, P (4) 98*e*.
containing boron nitride, method of making optical elements from, P (7) 150*c*.
method of molding, P (3) 68*j*.
solid, vapor pressure and heat and entropy of sublimation, (8) 211*e*.
hydroxide, coprecipitated, spinel formation from, (4) 110*c*.
and method of preparation, P (9) 226*a*.
and non-contaminated effluent solution, process for producing, P (3) 83*b*.
process for production, P (4) 107*e*.
reactive hot-pressing, (11) 300*h*.
single crystals, hydrogen liberation during dehydration of, (8) 201*a*.
in limestone, dolomite and magnesite, direct rapid iodometric determination, (7) 159*d*.
molybdites, tungstites, molybdates, and tungstates, mass-spectrometric determination of stability, (1) 22*e*.
oxide. See also *Refractories.*
burned, refractory brick of, and method of making, P (2) 45*b*.
carbon-impregnated refractive bodies, and method of making, P (2) 43*f*.
and CaO, mutual solubility in calcined dolomite, (8) 207*j*.
in cement, (10) 248*d*.
cleavage surfaces, microstructure, (1) 23*c*.
cleaved, dislocation structures, (2) 54*i*.
crystal surfaces, clean, friction of, (11) 296*e*.
crystal surfaces, frictional anisotropy, (11) 296*g*.
crystals, effect of loading duration on indentation hardness, (3) 85*b*.
crystals, explosively shocked, slip in, (8) 207*d*.
Debye-Waller factors, thermodynamic calculation, (8) 210*b*.
dose dependence of F-center production by fast neutrons, (1) 18*e*.
of different pseudostructures, reactivity, (11) 300*i*.
diffusion of Ca, (8) 194*d*.
dipole formation, transmission electron-microscopic studies on mechanisms for, (8) 210*e*.
explosively shocked, X-ray line broadening, (10) 272*f*.
fibers, method of making, P (9) 226*e*.
finely divided, study of lattice dilation, (8) 208*b*.
generation of vacancies by deformation, (4) 108*d*.
heat exchange media, development, (8) 179*j*.

Magnesium, oxide (*continued*)
high-pressure electrical behavior and equation from shock wave measurements, (1) 19*b*.
high purity, preparation from magnesium salt solutions, P (11) 282*c*.
hot-pressed, preferred orientation, (11) 299*a*.
hot-pressing, effect of LiF, (8) 195*e*.
internal friction due to chromium and iron, (8) 200*g*.
kinetics of reactions with melts of ternary system CaO-SiO_2-Al_2O_3, (8) 201*i*.
light rays, effect of temperature, (2) 56*d*.
and $MgTiO_3$ doping, effect on diffusion-controlled creep of polycrystalline aluminum oxide, (5) 135*i*.
method of preparing, P (8) 181*f*.
phonon dispersion relation, (7) 166*a*.
polycrystalline, creep of dense, (1) 17*f*.
preparation from magnesite, P (5) 124*i*.
production from alkaline earth carbonates and oxides containing impurities, P (11) 275*i*.
production for use in ferrites, P (4) 102*j*.
retention of hydroxyl groups on, (10) 271*j*.
single-crystal, mutual indentation hardness at high temperatures, (5) 137*j*.
single-crystal, time-dependent creep phenomena analysis, (1) 16*f*.
single crystals, containing nickel oxide, plastic softening at high temperatures, (10) 271*c*.
single crystals, electron microscopy on extinction and absorption of 100 kv electrons in, (11) 294*h*.
single crystals, kinking under high confining pressure, (11) 297*i*.
sintered, process for preparation, P (5) 125*b*.
sintering, (5) 137*i*.
sintering in argon, gas entrapment, (2) 41*h*.
sintering and grain growth, effect of V_2O_5, (5) 122*g*.
Spanish sintered, analysis, (5) 122*c*.
surface hydroxyl, (1) 29*f*.
surface, interaction of water, (7) 164*d*.
systems. See *Systems*.
thermal expansion, (4) 111*e*.
transmission electron-microscopic studies on surface effect on dislocation and friction stress in, (2) 59*c*.
X-ray scattering factors, experimental study, (9) 239*e*.
zero-phonon lines under uniaxial stress in, (3) 88*b*.
phosphate solutions, dissociation, (5) 138*f*.
-potassium phosphates, solubility products, (5) 138*f*.
production retort, purifying device, P (7) 154*a*.
silicide, thermodynamic properties, (11) 302*h*.
systems. See *Systems*.
tungstate, interaction with sodium ditungstate, (4) 108*j*.

Magnetic materials. See also *Ferrites; Ferromagnetic materials; Ferromagnetism*.
P (11) 286*a*.
barium potassium ferrite, exhibiting non-vanishing rotation hysteresis in applied magnetic fields, P (2) 47*g*.
ceramic, P (3) 78*d*; (9) 229*d*.
coating, on aluminum, P (9) 230*j*.
cores, for information storage and methods of making, P (5) 127*i*.
heads, annular, method of manufacturing parts of, P (10) 264*e*.
member, method of manufacturing, with coating of crystalline ferromagnetic material having uniaxial magnetic anisotropy, P (5) 128*f*.
and non-, magnetic separator for, P (3) 80*c*.
oxide, artificial, process for obtaining from dense liquors, P (2) 49*c*.
with pattern of embedded nonmagnetic material, method of making, P (10) 264*j*.
from silicate melts in system Fe_2O_3-MnO-alkali oxide-Al_2O_3-SiO_2, (3) 86*e*.
tape, composed of cobalt substituted gamma ferric oxide powder, accidental printing effect, (9) 237*a*.
thin films, process for cathodically sputtering, P (5) 128*g*.
vacuum-deposited, of Fe_3O_4-B_2O_3 mixtures, (3) 77*f*.

Magnetic properties. See also *Anisotropy; Resonance*.
of dense lithium ferrites, (8) 183*g*.
electromagnetic techniques, industrial application to ceramics, (5) 131*e*.
of $GdSi_2$, (11) 284*d*.
high-magnetic-field studies of orthorhombic and rhombohedral $Al_{2-x}Fe_xO_3$ compounds, (8) 199*c*.
of Fe_xO as related to defect structure, (8) 202*g*.
of Fe_2SiO_4 from 4° to 300°K, (8) 207*h*.
of $FeTiO_3$-α-Fe_2O_3 system, study by neutron diffraction and Moessbauer effect, (4) 110*g*.
of lead-barium and lead-strontium ferrites, (1) 22*a*.
magnetic behavior, of system Mn_2O_3-Fe_2O_3, (8) 202*f*.
of thulium garnets in cubic field, (9) 240*c*.
magnetic characterization, of some single crystal hexagonal ferrites, (9) 240*i*.
magnetic interactions of system $Sr_3Fe_2O_{6.00-6.90}$, (8) 183*e*.
magnetoacoustic birefringence in magnetite and nickel, (5) 137*b*.
magnetooptical Kerr effect, longitudinal, in EuO and EuS, (8) 201*g*.
magnetooptical study of molten salts at high temperatures, (1) 22*c*.
magnetostriction, of xFe_2-TiO_4-$(1-x)Fe_2O_4$ ($x>0.5$), (8) 202*i*.
constants, of xFe_2TiO_4-$(1-x)Fe_2O_4$, (7) 165*g*.
of silicon-doped YIG, (9) 240*d*.

Magnetic properties (*continued*)
magnetostrictive behavior of antiferromagnetic CoO single crystal in magnetic field, (9) 240*f*.
metamagnetic effects in hematite, (8) 202*c*.
of $SrFeO_3$-$BiFeO_3$, (1) 9*i*.
susceptibility, of chromium silicides, (8) 202*h*.
field-dependent, of MnO, (8) 198*j*.
lattice, of semiconductors, theory, (5) 139*c*.
of Ni-containing alkali borate glasses, (3) 66*a*.
of synthetic olivines, (5) 137*a*.
of yttrium-gadolinium-iron-aluminum-indium garnets, (5) 126*h*.

Magnetism, B (9) 244*e*.
magnetic oxide films, single-crystal, chemical vapor growth, (8) 183*d*.
magnetic sintered body, soft, and manufacture, P (10) 265*c*.
magnetic studies of semiconductor to metal transitions in Ti_2O_3 and Ti_2O_3, (10) 271*c*.
superpara-, of $MnFe_2O_4$ and α-Fe_2O_3 precipitated from silicate melts, (7) 156*d*.
in $ZnFe_2O_4$-$NiFe_2O_4$ system, (5) 138*h*.
treatise on modern theory and materials: Vol. IV, exchange interactions among itinerant electrons, B (11) 305*i*.
of V_2O_3-V_2O_3 system, (5) 137*g*.

Magnetite, apatite-, -vermiculite deposits near Sitarampur, Visakhapatram district Andhra Pradesh, (8) 189*e*.
magnetoacoustic birefringence, (5) 137*b*.
particles, rounded powdered, process for manufacture, P (7) 161*c*.
Ti-substituted, ferromagnetic crystalline anisotropy and transition temperature, (7) 163*e*.

Magnetization, remanence, stable, in α-Fe_2O_3, (9) 237*e*.
systems: permanent, process for thermal compensation by using ferrite, P (11) 287*h*.

Magnetoelectric, susceptibility measurements of polycrystalline chromium oxide, (1) 22*b*.

Magnetoplumbite, $BaFe_{12}O_{19}$, magnetic anisotropy, (9) 240*a*.

Magnetoresistance. See *Resistivity, electrical*.

Magnets, composition, two-phase ferrite, and method for preparation, P (11) 288*d*.
ferrite, P (4) 101*f*.
method of making, P (8) 185*c*.
high field superconducting, niobium-zirconium composition, P (1) 10*i*.
MnBi, method of manufacturing, P (8) 185*h*.
permanent, magnetically anisotropic, having crystalline structures, methods of making, P (3) 79*g*.
materials with strontium ferrite base, and processes for preparation, P (8) 185*g*.

Majolica, Austrian folk exhibition, (1) 1*i*.

Manganese, determination, by atomic absorption spectrometry using four solvents, (10) 267*h*.
determination in iron ores and slags, (5) 130*h*.
ferrite, spin echoes on ^{55}Mn in, (7) 167*i*.
ferrites, process for firing to equilibrium state, P (10) 265*h*.
in iron oxide pigments, P (1) 15*h*.
Mn^{3+}, in $BaTiO_3$, electron spin resonance, (8) 196*d*.
Mn^{4+} ions, in magnesium oxide, (7) 167*h*.
^{55}Mn, spin echoes on, in manganese ferrite, (7) 167*i*.
$MnFe_2O_4$, precipitated from silicate melts, superparamagnetic behavior, (7) 156*d*.
$Mn_xFe_{3-x}O_4$, Moessbauer effect, (7) 165*j*.
$Mn(OH)_2$, single crystal X-ray diffraction study, (8) 207*b*.
MnO_2-Mn_2O_3, at various temperatures, equilibrium pressures of oxygen over, (11) 295*h*.
β-MnO_2, pyrolytic, electrical resistivity, (3) 85*d*.
Mn_2O_3-Fe_2O_3 solid solutions, magnetic behavior, (8) 202*f*.
α-MnS and MnS_2, properties, (8) 205*g*.
γ-MnS crystals, growth in sodium silicate gels, (9) 239*a*.
manganous chloride, thermodynamic properties, (4) 112*a*.
manganous oxalate, pyrolytic decomposition, carbon isotope effects, (8) 192*c*.
nitrate pyrolysis, thermogravimetric study, (2) 58*i*.
oxide, counterelectrodes, use in thin film capacitors—the TMM capacitor, (5) 126*i*.
effect on some physical and chemical properties of glass, (2) 36*e*.
field-dependent magnetic susceptibility, (8) 198*j*.
phthalate, monocrystals, (1) 23*b*.
reactions with silica, (8) 206*a*.
silicide lattice, higher, nature of defects, (4) 108*j*.
silicides, thermodynamic properties, (4) 112*a*.
spectrophotometric determination, (5) 138*i*.
sulfate, process for decomposing, to form manganous oxide and sulfur dioxide, P (4) 106*j*.
systems. See *Systems*.
-zinc ferrite, equilibrium in hydrogen reduction of, (4) 107*j*.
Richter-type aftereffect, (9) 241*j*.
single crystal hexagonal, microprobe and magnetic characterization, (9) 240*i*.

Masers. See also *Lasers*.
niobate, materials, and devices made therefrom, P (2) 48*g*.
optical, green radiation lamp for, P (8) 184*e*.

Masonry, materials, silicone water repellents, P (7) 151*a*.
tile, P (3) 70*f*.
wall structures, faced, tie assembly for, P (7) 151*a*.

Materials. See also *Ceramic materials*.
amorphous, structure and properties, B (9) 244*e*.
atomistic approach to nature and properties of, B (9) 244*c*.
for compressible gasket, simple method of selecting, (11) 300*h*.
with different thermal expansion coefficients, method of forming objects of, P (10) 250*e*.
engineering, science, B (1) 31*b*.
mine sampling, mathematics for, (4) 106*b*.
pitchstone, expanded, effects of firing conditions on bulk density (Japanese), (5) 133*f*.
reclamation, P (9) 233*d*.
research, advances: Vol. 1, experimental methods, B (8) 211*i*.
arc techniques, (9) 233*g*.
science research: Vol. 3, B (2) 60*j*.
sciences, fundamental phenomena: Vol. 2, surface phenomena, B (8) 212*d*; Vol. 3, surface phenomena, B (9) 245*c*.
solid, method of treating, P (2) 48*f*.
testing, uses of elastic-modulus determination, (2) 42*f*.
textured, X-ray determination of volume fraction of phases in, (9) 243*h*.

Materials handling. See also *Conveyors; Feeding apparatus; Machinery and equipment*.
apparatus, for bulk, P (1) 12*i*.
for conveying and stacking bricks, P (3) 70*e*.
for distributing and screening particulate apparatus, P (1) 12*g*.
for feeding and transporting, P (4) 103*j*.
for grit, P (10) 266*e*.
and method for discharging receptacles, P (8) 186*j*.
for suspending plates, saucers during glaze firing, P (11) 283*h*.
automated system, for tile, P (8) 182*j*.
brick, savings by strapping with steel bands, (11) 280*a*.
bulk conveying, of free flowing solids, (11) 288*e*.
device for stacking unfired brick on carrier, P (2) 50*a*.
heated helical screw conveyors, P (11) 288*g*.
machine, P (11) 288*f*.
method and apparatus for removing blockage of material in transporting conduits, P (8) 186*i*.
method of calculating rate of discharge from hoppers and bins, (4) 106*b*.
pallet of calcium silicate, construction, P (1) 9*d*.
porous. See *Porous materials*.
pulverulent, P (7) 158*i*.
removing solids and semisolid materials from solutions, apparatus, P (1) 12*i*.
stacking apparatus, P (5) 126*a*.
transport and handling means, for finely divided material, P (3) 80*d*.
transporting cylindrical articles, apparatus, P (1) 12*j*.
transporting method, and device, P (7) 158*g*.
unloader for green ceramic ware, P (2) 46*g*.

Measurement, of consistency, P (7) 159*h*.
deflection, accuracy, (5) 130*j*.
dielectric, international comparison, (3) 76*b*.
intensity, systematic error due to continuous recording, (3) 81*g*.
international system of units, (4) 112*i*.
of magnitudes of photoelastic tensors, and application to lithium niobate, (8) 203*a*.

Measurement devices, combined specific gravity meter and contact goniometer, P (9) 234*d*.
for electrical resistance of molten glass in a tank, P (1) 5*j*.
electrochemical gage, ionic conductivity of zirconia, (2) 47*c*.
for force piezoelectric, and process of making, P (1) 11*a*.
for piezoelectric force, piezoelement, P (1) 11*b*.
thermoelectric, for rotary specimen carriers temperature, P (2) 52*a*.
for transconductance and output conductance of transistor, P (7) 156*b*.
for wall thickness of glass containers, P (9) 219*e*.
using application of Hall effect, P (2) 47*b*.

Mechanical properties, of ceramics, introductory survey, (9) 244*a*.
of chemically strengthened glasses at high temperatures, (1) 4*a*.
of MgO with NiO, plastic softening point at high temperatures, (10) 270*c*.
of refractory materials, nondestructive determination, (7) 159*j*.
thermo-, of pure oxide ceramics, (7) 152*f*.
of tungsten at high temperatures and pressures, (1) 2*g*.

Melting, apparatus, P (2) 52*d*.
container glass, economics, (1) 3*f*; discussion, (9) 218*b*.
crucible-free zone, apparatus for, P (3) 77*a*.
method and apparatus, P (7) 156*j*.
fusing coating to a metal surface, method and apparatus, P (2) 35*d*.
of high lead glass, investigating processes, (8) 175*d*.
minerals and rocks, by high frequency heating, (10) 268*h*.
point, determination of fettling and ramming specimens from hearths of basic open-hearth furnaces, (9) 223*j*.
determination at temperatures above 2000°C, (7) 159*b*.
new formula for calculating characteristic temperature from, (3) 87*b*.
vacuum induction, of nickel-base alloys, refractory-melt reactions in, (8) 180*i*.

Melting (*continued*)
zone, apparatus, P (7) 156*a*.
apparatus for growing ice monocrystals, (8) 188*i*.
crucible-free, method, P (11) 286*e*.
manufacture by segregation from a melt, P (2) 50*a*.
for production of alkali halogenide crystals, (8) 205*e*.
of silicon rods, P (10) 266*h*.
zonewise, of metals and semiconductors, P (7) 158*c*.
Melts, alkali borate, binary, Cr^{3+}-Cr^{6+} equilibrium, (8) 175*f*.
CaO-MgO-SiO_2, effect of calcium sulfides on surface tension and density, (4) 90*i*.
enamel, reaction of iron with, (5) 117*h*.
of indium-selenium, X-ray phase analysis, (2) 60*e*.
of salts, complex formation in crystallization of, (11) 292*g*.
Na_2O-B_2O_3 and Na_2O-SiO_2-B_2O_3, volume relations at 1300°C, (2) 38*e*.
solution, growing crystalline members, P (1) 11*c*.
in ternary system CaO-SiO_2-Al_2O_3, kinetics of reaction of magnesia, silica, and alumina with, (8) 201*i*.
Memory, in α-Fe_2O_3, (9) 237*e*.
Memory cores. See *Data storage*.
Memory devices. See *Data storage*.
Mercury, amalgamative material, on electrode stems of reflector for high temperature fluorescent lamp, P (2) 47*j*.
mercuric oxalate, irradiated, thermal decomposition, B (9) 244*c*.
porosimetry, application to refractory materials, (8) 179*h*.
Metallics, systems, surface and contact phenomena and technological applications, (10) 250*h*.
Metallizing. See *Coatings*.
Metalloceramic compositions. See *Cermets*.
Metallography, introductory practical, B (4) 113*f*.
metallographic preparation of dicarbides of thorium and thorium-uranium, (8) 180*f*.
Metals. See also *Enameling metals; Rare earths*.
alkali, apparatus for condensation in cement kilns, P (3) 64*b*.
pertitanates and perzirconates, process for producing, P (1) 11*c*.
baths, P (1) 12*j*.
bonding to ceramic materials, P (2) 35*i*.
-ceramics. See *Cermets*.
cleaning, P (9) 217*e*.
coated columbium or tantalum base, P (3) 65*b*.
degasification, lining for installations for, P (9) 225*j*.
degasifying, refractory linings for chambers for, P (2) 45*d*.
depositing on siliceous supports, method, P (9) 235*j*.
-dielectric interfaces, barrier lowering and field penetration, (8) 183*c*.
dioxides, mixed transition, studies on rutile-type phases, (5) 138*b*.
enameled, combining with casting stone for outdoor ashtrays, (4) 89*j*.
ferrous, passivation, and compositions therefor, P (5) 117*g*.
fiber reinforced, containing bond promoting components, P (2) 44*a*.
film, via binder of copper oxide containing glass, for ceramic, P (3) 77*d*.
-glass products of high strength, complex aluminous, manufacture, P (4) 94*b*.
hot pressing method, P (11) 282*a*.
intermetallic compound AgMg, tensile behavior, (4) 111*b*.
metallic surface, methods for elevated temperature protection, and coatings, P (4) 92*d*.
microstructure in, B (4) 113*f*.
molten, process for reducing deterioration in equipment handling, P (2) 45*f*.
oxide microspheres, method of making, P (8) 190*i*.
-oxide-silicon structures, effects of X-ray irradiation on characteristics, (9) 238*j*.
oxides, preparation, P (3) 72*e*.
surface tension, (7) 163*b*.
-oxygen technology for brazing ceramic materials, (10) 262*j*.
powdered, method of heating and forming, P (10) 259*g*.
-refractory interactions, thermochemistry, (7) 152*f*.
refractory, protection, (7) 147*j*.
scale removal, and compositions therefor, P (5) 117*g*.
surface, method and apparatus for fusing glass coating, P (2) 35*d*.
surfaces, effect of abrasion, (3) 66*e*.
preparation for enameling, P (8) 174*i*.
systems. See *Systems*.
thermal diffusivity and conductivity measurements at high temperatures, (2) 51*i*.
transition, effect of nonmetallic atoms on electrical properties of high-melting compounds of, (3) 85*d*.
state of carbon in carbides of, (4) 110*e*.
Metaphosphates. See *Phosphates*.
Mica. See also *Refractories; Vermiculite*.
biotite, efficient Brewster angle polarizer for vacuum ultraviolet, (1) 10*a*.
chlorite-biotite, equilibrium reactions in carbonate free system, (8) 192*j*.
conduction behavior at elevated temperatures, (8) 183*f*.
content, determination in clay or kaolin, (5) 135*b*.
decrepitation, two stages, (7) 169*f*.
Mica (*continued*)
flotation, P (1) 15*g*; P (10) 269*e*.
from pegmatites, (4) 106*f*.
microstructure, (7) 150*j*.
pigments, P (7) 161*d*.
power factor of, effect of thickness, (2) 46*j*.
selective flotation of, from Georgia pegmatites, (1) 28*b*.
sheet, inorganic-bonded reconstituted, P (7) 156*g*.
synthetic, materials, method of making, P (11) 286*b*.
method of making, P (9) 221*a*.
method and apparatus for heat treatment, P (10) 269*g*.
in vitreous materials, P (8) 179*b*.
Microcalorimetry. See *Calorimetry*.
Microchemistry. See *Chemistry*.
Microcline, reactions during firing, infrared study, (9) 224*e*.
Micrography, X-ray, of silicon carbide crystals, (11) 303*b*.
Microhardness. See *Hardness*.
Microscopes, in combination with microspark probe including unshielded electrode of small tip radius, P (8) 188*c*.
electron, combined with electron microanalyzer analytical applications, (10) 266*i*.
for direct observation of Ta_2O_5 and Nb_2O_5 superlattices, (9) 238*i*.
observations of irradiated graphite single crystals, (2) 55*c*.
observations on NiO bombarded by ions or electrons, (4) 109*h*.
observations of nucleation and growth of thin films, (1) 24*f*.
operating at 10^{-8} torr, design of new vacuum deposition specimen holder for, (11) 289*e*.
and optical, studies of thermal decomposition of brucite, (1) 29*j*.
process for purifying colloidal particles for subsequent structural analysis with, P (8) 188*e*.
for study of porcelain texture, (3) 74*f*.
for evaluation of magnesite sinters, (8) 197*f*.
hot-stage, wettability determination of refractories by carbon steels under, (2) 43*j*.
optical, investigation of fine pores in ceramic bodies, (10) 267*a*.
for study of porcelain texture, (3) 74*f*.
scanning electron, for characterization of surface topography, (9) 233*j*.
system using polarized light, illuminating apparatus for, P (1) 14*d*.
transmission electron-, on surface effect on dislocation and friction stress in MgO, (2) 59*c*.
X-ray and electron, study of compound Pb-$Al_{12}O_{19}$, (9) 243*i*.
study of precipitates formed by hydrolysis of iron(III) in 0.5*M* NaCl ionic medium, (10) 272*d*.
Microscopy, of alite in portland cement clinker, (1) 2*c*.
automatic reflectance, of refractories, (8) 179*j*.
of crack propagation, (3) 81*h*.
electron, of $(Ba,Sr)TiO_3$ crystals, (11) 294*j*.
of carbonates, negative replication, (10) 267*h*.
combined with X-ray diffraction for determination of large crystal structures, (9) 238*b*.
of crystallization of anodically formed tantalum and niobium oxide films, (7) 163*f*.
on extinction and absorption of 100 kv electrons in MgO single crystals, (11) 294*h*.
Fourier analysis, (1) 13*j*.
high voltage, (7) 159*g*.
of ion-exchanged type A molecular sieves, (9) 235*f*.
of precipitation of NbO from supersaturated solutions, (11) 294*j*.
of synthetic corundum crystals: II, dislocations and grain boundaries in impurity-doped aluminum oxide, (8) 196*j*.
thin film, for measuring systematic errors in dislocation densities, (8) 209*f*.
transmission, of fine-grained rocks, (2) 51*a*.
transmission, on mechanisms for dipole formation in MgO, (8) 210*e*.
transmission, of synthetic diamond, (8) 210*f*.
transmission, of thin glass samples, (2) 38*d*.
of ferromagnetic phases of alloys, (5) 131*h*.
of fused cast alumina refractories, (4) 97*h*.
of $SrTiO_3$, at low temperatures, (5) 137*g*.
ultra-, laser as light source, (1) 21*e*.
Microstructure. See *Structure*.
Microwaves, for detection of flaws in composite materials, (10) 267*g*.
emission, from bulk *n*-type indium arsenide, (3) 76*d*.
from InSb for low electric fields, (5) 137*h*.
field, relation with Sb_2S_3 single crystals, (5) 138*b*.
phonons, thin-film piezoelectric transducers used as generators and detectors of, (3) 77*d*.
Milling. See also *Crushing; Grinding*.
ball-, wet, of iron oxide, B (7) 169*j*.
blasting and/or vibratory, for restoration of museum pieces, (11) 273*h*.
conditions, effect on density and oxygen content of microwave magnesium manganese ferrites, (10) 262*g*.
particulate solids in liquids, process, P (10) 266*g*.
Mills. See also *Crushing apparatus; Grinding apparatus*.
attrition apparatus, P (1) 15*f*; P (4) 106*i*.
autogenous grinding, P (3) 83*a*.
ball, P (3) 80*e*; P (4) 103*d*.
for forming liquid suspensions of finely divided solid material, P (4) 103*c*.
Mills, ball (*continued*)
vibrating, for pulverization of refractory materials, (11) 280*j*.
vibratory, P (2) 50*c*.
ball and pebble, (10) 266*a*; (11) 288*d*.
casing with pulsating internal wall for, P (4) 106*j*.
for comminuting material, P (9) 236*c*.
counter flow for grinding iron to remove from quartz sand, (8) 189*g*.
grinding, P (10) 266*a*; P (11) 291*g*.
batch, effect of suspending-fluid viscosity on, (4) 103*f*.
and dispersing, sealing means for rotary agitator, P (9) 236*g*.
multiple compartment, P (4) 106*i*.
suction-type, P (8) 190*i*.
swinging type with plurality of grinder drums, P (7) 160*i*.
gyratory ball, P (11) 288*i*.
Hardgrove, grindability of limestone and rock-salt mixture in, (5) 129*h*.
pigment grinding, P (10) 266*f*.
roller grinding, and control for, P (11) 292*e*.
shaft, combined grinding and drying refractory clays in, (5) 122*j*.
tube, journalling structure for, P (7) 160*e*.
vibratory grinding, drum type, P (4) 104*a*.
vibro-, for determining abradability of refractories, (5) 122*i*.
vortex grinding, P (4) 107*d*.
Mineral fibers. See *Mineral wool*.
Mineralizers. See also *Fluxes*.
effect on clinker-formation process, (9) 214*g*.
phosphogypsum, for firing cement, (9) 215*d*.
Mineralogy, of garnierite and aquacreptite, (9) 241*a*.
on glass stones, (5) 119*f*.
of Lower Devonian (Helderberg) rocks of Central Hudson Valley, New York, (7) 165*e*.
of metamorphosed Wabush iron formation, southwestern Labrador, (7) 165*f*.
mineralogical composition, of cement kiln dust, (7) 146*e*.
mineralogical variations in kaolin deposits of Georgia and S. Carolina coastal plain, (1) 23*g*.
of salt glazes, on iron-rich clay bodies, (7) 154*j*.
containing boron, zinc, and manganese, (4) 96*c*.
of set high-alumina cement, (9) 214*i*.
soil clay, of Pampa plains, Argentina, (8) 207*f*.
Minerals. See also *Raw materials; Rocks;* and specific types.
ages from metamorphic and igneous rocks near Iron Mt., Mich., (1) 16*d*.
of aluminophosphate group, synthesis, (8) 208*g*.
aquacreptite, crystal structure, X-ray study, (9) 243*e*.
bleaching process, P (4) 106*g*.
clay. See *Clays*.
concentrator, P (1) 16*a*.
crystalline, apparatus for making, P (2) 53*i*.
djerfisherite, alkali copper-iron sulfide—new from enstatite chondrites, (1) 15*d*.
equilibria in Searles Lake evaporites, Calif., (1) 23*e*.
formation in CaO-Al_2O_3-SiO_2 system in presence of gypsum and CaF_2, (9) 215*a*.
fresnoite, unusual titanium coordination, (9) 239*h*.
grains in metamorphic rocks, interpretation of shape, (1) 20*g*.
helvite group, isomorphism, (1) 21*a*.
industrial, preparation, (4) 106*c*.
treatment, P (4) 107*d*.
iron-titanium oxide, and synthetic equivalents, (1) 20*i*.
material, heat-softened, method and apparatus for flowing streams, P (7) 149*i*.
metamorphic, grain-size distribution in relation to nucleation and growth, (1) 19*g*.
minute samples, X-ray spectrographic analysis, (2) 51*i*.
and ores, preparation: Vol. 1, B (11) 305*b*.
otogeny, B (7) 170*e*.
oxide, temperature and humidity in electrical separation, (4) 106*h*.
piercing, thermal mechanical, P (9) 236*i*.
powdered, preheating and thermal treatment, P (2) 35*b*.
rock-forming, introduction, B (11) 304*f*.
X-ray-emission microanalysis, (10) 272*e*.
separation, P (3) 83*e*.
unsieved heavy, rapid method for determining weight percentages, (10) 267*f*.
wealth, probability model, (4) 106*d*.
Mineral wool. See also *Fibers, glass*.
producing system and method, P (5) 121*b*.
products, apparatus and method for forming, P (10) 255*j*.
Mines and mining, clay, new techniques in technology, (5) 132*j*.
on simple control method for use in clay pits, (5) 131*e*.
and stockpile, methods and economics, (9) 235*e*.
Mirrors, aluminized, (3) 66*f*.
optically variable one-way, P (1) 6*a*.
production: I, selection, cleansing and sensitizing of glass, (5) 119*c*.
Miscibility. See also *Solubility*.
gap, in K_2SO_4-K_2O-SiO_2 system at 1300°C, (7) 165*h*.
in sulfate-ferrite melts at 1500°C, (3) 86*j*.
solid and liquid phase, of calcium metal and calcium fluoride, (11) 301*b*.
Mixers, P (8) 186*j*; P (11) 289*a*.
batch blender, P (11) 288*g*.
casing with pulsating internal wall for, P (4) 106*j*

Mixers (*continued*)
continuous, P (3) 80*a*.
with adjustable mulling wheels and plow means, P (9) 244*b*.
conveyor-, vibratory, P (4) 103*j*.
including mulling wheel with resilient tire means to facilitate wheel rotation, P (9) 233*b*.
mechanisms for elbow- and drum-type, in mixing of solids, (1) 12*f*.
mulling shoe, P (2) 50*a*.
for particulate materials, P (11) 288*f*.
Mixing, agitation process, P (7) 158*h*.
apparatus, P (10) 266*d*.
automatic, for stock materials, P (5) 130*c*.
for materials comprising solid particles in liquid, and method, P (10) 266*b*.
Dinas bodies in centrifugal runner mill model 115, (5) 123*e*.
and distributing bulk products or different materials, process and apparatus, P (11) 289*b*.
electrostrictive, in solids, for conversion of light to sound, (8) 183*g*.
glass, apparatus, P (1) 6*f*.
granular materials, P (3) 80*f*.
liquid or semiliquid materials of low thermal conductivity, process and apparatus, P (7) 158*h*.
mixedness, degree, of packed particles, (10) 266*b*.
and mulling, foundry sand, P (11) 283*d*.
mulling machine, P (1) 13*b*; P (10) 266*e*.
for nonhomogeneous product, P (11) 282*a*.
slurry, apparatus, P (2) 35*b*.
solids, mechanisms for elbow- and drum-type mixers, (1) 12*f*.
Mobility, of electrons. See *Electrons*.
Models, fluoberyllate, weakened, study of Ba_2SiO_4-Mg_2SiO_4 and Ba_2SiO_4-Ca_2SiO_4-Mg_2SiO_4 systems, (1) 29*c*.
free volume, success for transport in fused salts, (8) 208*d*.
for transport in fused salts—electrical conductance in glass forming nitrate melts, (8) 198*g*.
lost, process for production in precision casting operations, P (8) 182*b*.
Modulators, optical, employing dichroic absorption of antiferromagnetic NiF_2, P (8) 188*d*.
semiconductor light, P (4) 102*f*.
Modulus of elasticity. See *Elasticity*.
Modulus of rupture. See *Rupture*.
Moisture. See also *Humidity; Steam; Water*.
in aggregate and fresh concrete mass, (11) 274*j*.
content, automatic determination and control apparatus, P (1) 14*c*.
detection in materials, P (3) 81*d*.
effect on thermal conductivity of structures and insulating materials, (3) 80*i*.
in heat resistant concretes, determination, (5) 131*b*.
movement, of bricks and brickwork, (9) 222*j*.
removal from material by sonic or ultrasonic energy in combination with centrifugal energy, method and apparatus, P (9) 233*e*.
Molding, cold, pitch bonded shaped carbon bodies, P (3) 72*j*.
comminuted nonplastic inorganic material, P (10) 266*c*.
compositions, inorganic, of asbestos-orthophosphoric acid type, and products produced, P (9) 225*j*.
glass foot and stem part of stem type glass, P (1) 6*f*.
magnesium fluoride, P (3) 68*j*.
method, for elongated powdered material compact, P (7) 158*f*.
pressure, method and apparatus, P (1) 5*f*.
process using centrifugal forces, P (11) 289*b*.
Molds. See also *Slip casting; Slips*.
casting, hot top composition for, P (4) 98*b*.
method of producing, P (9) 226*i*; P (11) 282*c*.
production, P (5) 125*c*.
for casting toilet bowl, P (1) 9*c*.
ceramic, P (2) 46*b*.
permeable material, (1) 9*a*.
for ceramics, resins in construction, (10) 261*g*.
clay, for draping clay, (7) 145*j*.
composition, for foundry use, P (5) 124*c*.
for metal casting, P (2) 44*f*.
cored casting, method and apparatus for making, P (9) 226*c*.
cores for. See *Cores*.
design for ceramic casting, P (2) 46*c*.
for forming glass lined vessels, P (3) 69*f*.
frangible ceramic test, for metal, P (4) 98*f*.
for fused cast refractories, improved, (5) 123*d*.
glass, copper alloy for, (2) 36*h*.
for forming hollow articles, P (11) 279*c*.
with internal cooling structure, P (2) 39*g*.
and plunger, for pressing flanged articles, P (4) 95*f*.
press bending, with heat reflective surface, P (9) 222*c*.
glass forming, infrared heat control for, P (10) 255*g*.
glass sheet bending, P (9) 220*g*.
pivoted, P (1) 6*c*.
with pivoted end sections, P (2) 38*h*.
glassware, split, method and apparatus for electroforming, P (2) 39*d*.
graphite, for continuous casting, P (5) 124*i*.
method for shaping beryllium, other metals and ceramics, P (5) 124*e*.
plural wedge-shaped, with heating electrodes, P (10) 260*d*.
holder for glassware forming machine, P (1) 6*f*.
for household ceramics, replacement of plaster for manufacture, (2) 46*f*.
Molds (*continued*)
investment, combine simplicity with accuracy, (2) 41*d*.
method of removing patterns, P (11) 282*g*.
for precision casting, method of preparing, P (4) 98*g*.
metal casting, made from refractory binders, P (7) 154*c*.
refractory coated, P (2) 35*g*.
moisture-absorbant for complex shapes, P (5) 126*b*.
for multifocal ophthalmic lenses, method of making, P (4) 95*c*.
parts, electrocleaning, conductive mold rack for, P (4) 94*b*.
investment-cast in quantity at less cost, (11) 283*h*.
plaster, quality control in shop, (1) 9*e*.
pottery, metal-faced case, (9) 228*d*.
for production of silicate material blocks, (2) 39*g*.
pyrolytic graphite coated casting, method of making, P (2) 45*i*.
rack, conductive, for electrocleaning glass mold parts, P (4) 94*b*.
refractory, P (5) 125*b*.
release agent, P (1) 13*a*.
release compound for clay products, P (11) 280*c*.
shell, for casting reactive metals, method of making, P (9) 226*h*.
method of making, P (3) 72*a*.
split, apparatus for centrifugal molding in, P (3) 67*b*.
steel, effect of grading on properties of olivine sands for, (4) 96*j*.
unicast ceramic, process for metals, (2) 43*g*.
with vacuum transfer apparatus, P (4) 95*f*.
Molybdates, luminescent, of Sc, La, Eu, Gd, and Lu, P (9) 232*g*.
quinolinium and lutidinium, as reagents for phosphate precipitation, (8) 187*i*.
Molybdenum, carbide, higher, type of crystallization and composition, (8) 211*c*.
carbide, properties, effect of nuclear radiation, (8) 195*f*.
study of applicability to construction of high-power tubes, (11) 280*h*.
composition, ductile, containing spinel dispersion, P (8) 181*a*.
corrosion, by molten glasses, (5) 118*f*.
determination in natural waters, silicates, and biological materials, (2) 50*g*.
dioxide, process for production, P (11) 292*a*.
single crystals, (1) 23*a*.
disilicide, heating elements, (2) 42*a*.
high temperature oxidation, (4) 108*d*.
interaction with beryllium, (3) 86*h*.
oxidation, role of iron, (9) 242*a*.
spectral emissivity, (5) 138*h*.
fiber reinforced alumina, P (9) 226*e*.
films, physisorption of xenon and krypton, (2) 36*j*.
Mo_2As_3, crystal structure, (10) 270*d*.
Mo_4As_4, crystal structure, (10) 270*i*.
Mo_2C, effect of temperature on strength and plasticity, (3) 71*j*.
single crystal, veining substructure, (11) 303*c*.
single crystals, microhardness anisotropy, slip and twinning, (8) 202*d*.
MoO_3, oxide glasses, formed by rapid quenching methods, (11) 298*c*.
$MoSb_7$, crystal structure, (1) 17*g*.
oxide, systems. See *Systems*.
oxidation kinetics, at high temperatures, (11) 298*a*.
pentachloride, systems. See *Systems*.
silicide, sintered bodies of, P (5) 125*d*.
sintering with WSi_2 and ZrO_2, (2) 43*b*.
silicides, high-temperature oxidation, (11) 297*a*.
systems. See *Systems*.
thermal emf, effect of highly refractory oxides in vacuum at 1500°C, (7) 151*i*.
Montmorillonite, adsorption of amino acids and peptides, cation exchange and proton transfer, and physical adsorption, (7) 161*f*.
acid treated, intracrystalline swell and dye absorption, (3) 86*i*.
clay, interaction with trace element cations, dissociation of Co^{2+}, Ni^{2+}, and Mn^{2+} from respective clays at different degrees of supersaturation, (9) 240*a*.
interaction with trace element cations: III, fixation and release of cations from respective clay salts, (9) 239*j*.
minerals, production of ion exchangeable substances from, P (9) 236*a*.
-diamine, complexes, thermal analysis, (5) 137*b*.
exchange equilibria with strontium-sodium-cesium, (1) 23*c*.
group minerals from kaolinite, quartz, and various carbonates, hydrothermal synthesis, (1) 19*d*.
hydration energy, (4) 108*i*.
infrared study of ammonia reactions with, (7) 164*a*.
organophilic, formation in ion exchange, (7) 163*h*.
preparation for random powder diffraction, (1) 14*c*.
tactoid formation in, effect on ion exchange kinetics, (4) 111*i*.
univalent cation, repulsion of chloride ions, (7) 167*a*.
with urea complexes—infrared absorption study, (4) 112*f*.
-water systems, effect of $Ca(OH)_2$ on flow properties, (2) 45*j*.
Mordenite, synthesis, P (10) 260*j*.
Morphology, features of hexagonal ferrites, (9) 241*b*.
Morphology (*continued*)
of microcrystals, determination by Weissenberg goniometer, (7) 161*j*.
Mortars, cement, for casting of concrete, P (3) 64*d*.
cement, properties modified by polymer emulsion, (4) 91*c*.
effect of mix proportions and method of testing on Poisson's ratio, (9) 214*h*.
microporous chalk, composition, P (9) 215*j*.
mixes, for load-bearing brickwork, (9) 223*b*.
plaster, P (11) 275*g*.
portland cement, causes for variation in required amount of air-entraining agents in, (10) 248*f*.
rate of flow indicator, P (8) 174*f*.
refractory, P (8) 182*d*.
bonding, P (4) 99*e*.
composition, P (2) 45*f*.
sand-lime, P (7) 147*e*.
setting time, determining with copper-lead electrode, (9) 214*c*.
staining, by manganese colored brick, (1) 6*h*.
strength and watertightness, effect of surkhi fineness, (10) 256*c*.
Thomas blast furnace slags for use in, (4) 90*j*.
trowelling, P (4) 91*c*.
Mosaics, ceramic tesserae, (4) 89*j*.
process and apparatus for manufacture, P (4) 100*a*.
screens, art of making color-phosphor, P (1) 10*f*.
Mufflers, ceramic coated, P (2) 35*i*.
ceramic coated, with drainage openings, P (7) 147*h*.
Mullite. See also *Refractories*.
composition, formed in kaolin minerals containing LiF at temperatures below 900°C, (5) 134*f*.
containing Fe_2O_3 as mixture or solid solution, effect of heat treatment, (8) 195*a*.
as derived from equilibria in system CoO-Al_2O_3-SiO_2, stability, (11) 301*f*.
production, P (11) 282*i*.
Muscovite. See *Mica*.

Neodymium, fused salts, extraction using molten borate ion-exchanger, P (11) 291*f*.
Nd^{3+}-glass laser, mode-locked, PTM single-pulse selection using bleachable dye, (9) 241*h*.
Nd^{3+}: glass laser rods, optically pumped, effect of surface finish on temperature distribution in, (5) 135*j*.
Nd^{3+} ion, absorption and fluorescence in lanthanum-borate glass, (4) 92*i*.
Nd^{3+}, orthorhombic sites in $CaWO_4$, EPR measurements, (8) 197*b*.
oxide, nonstoichiometry, in relation to interaction with oxygen and hydrogen, (8) 203*f*.
selenide, single crystals, (8) 207*c*.
Neon, diffusion, in glass melt, (11) 276*g*.
Nepheline, crystallochemical relations, on Stjernöy, north Norway, (2) 56*d*.
glass-crystal transformation, and heat of formation, (1) 19*e*.
Neptunium, pentoxide, (8) 203*c*.
Neutrons, -absorbing materials, for control-rod and screening applications, (3) 70*j*.
diffraction, for investigation of $La_2Ce_2O_7$, (7) 166*j*.
for study of magnetic properties of $FeTiO_3$-α-Fe_2O_3 system, (4) 110*g*.
study of ferroelectric lithium niobate single crystals at 24°C, (8) 198*g*.
Nickel, boronized, phase composition of diffusion layer, (1) 25*c*.
chloride, thermodynamic transformation, (8) 210*j*.
chrome alloy, P (8) 178*c*.
ferrite, cobalt-substituted, single crystals, ferromagnetic resonance, (11) 295*g*.
oxygen content at 1300°C, reply to discussion of, (1) 28*g*.
single crystals, preparing on monocrystalline substrate, P (10) 265*f*.
ferrites, and fabrication, P (2) 48*f*.
iron-, oxides, dissociation pressures, (7) 162*c*.
magnetoacoustic birefringence, (5) 137*b*.
NiAs structure transformation, spinel to defect, (10) 272*a*.
Ni_3C, bond state of carbon atoms in, (4) 110*c*.
$Ni_{1-x}Li_xO$ single crystals, electrical properties, (7) 163*c*.
$Ni_{1-x}O$, electrical properties, (5) 135*f*.
Ni_2Si_3, crystal structure, with notes on Ni_3Si_2, (3) 84*b*.
optical spectra, in alkali tetraborate glasses, (5) 119*i*.
oxalate, irradiated, thermal decomposition, (8) 209*g*.
kinetics of decomposition, (1) 21*c*.
oxidation in range 900° to 1400°C, (11) 299*a*.
oxide, antiferromagnetic, optically biaxial properties, (7) 166*d*.
antiferromagnetic, X-ray diffraction micrography of twin structure of, (3) 88*a*.
antiferromagnetic domain walls in, (5) 134*c*.
antiferromagnetic domains, observation, (8) 203*i*.
bombarded by ions or electrons, electron microscope observations, (4) 109*h*.
crystal, antiferromagnetic, new birefringence pattern, (5) 137*j*.
crystal, multiple twin domains and domain walls, (3) 87*b*.
crystals, thermal pits, (4) 111*g*.
electronic structure, (7) 163*g*.
influence on yttrium-iron garnet crystals yield grown from flux, (1) 19*g*.
single crystal, X-ray topography, (9) 243*h*.
structure and temperature factors, (7) 168*f*.
systems. See *Systems*.
oxygen, photoelectric study, (7) 166*a*.

Nickel (*continued*)
phosphide, wear-resistant coatings, (2) 43*i*.
radioactive, diffusion into alumina, (2) 47*a*.
self-diffusion in nickel oxide, (1) 20*j*.
-silver alloy anode, in fuel cell, P (4) 101*k*.
spectrophotometric determination, (5) 138*i*.
systems. See *Systems*.
and -titanium and -chromium alloys, adherence and wettability on sapphire, (10) 249*g*.
-zinc ferrites, and fabrication, P (2) 48*f*.
Niobates, maser materials, and devices made therefrom, P (2) 48*g*.
Niobium, alloys, coatings for, P (3) 65*c*.
carbide, activated sintering, (3) 83*h*.
components, manufacture and applications, (10) 257*k*.
interaction with tungsten, (8) 200*b*.
polycrystalline transition, deformation, (7) 162*a*.
sintering, (10) 258*j*.
solubility in γ-iron, (5) 138*c*.
surface films, diffusivity data on formation, (11) 293*b*.
carbides, mutual solubility with zirconium and hafnium carbides, (2) 55*g*.
-carbon, variation of molar mixing volumes, (10) 272*a*.
chemistry: XXXII, reaction of tantalum with quartz, $14Ta + 5SiO_2 = 5Ta_2Si + 2Ta_2O_5$, (1) 17*d*.
XLVI, NbO_2I and TaO_2I, (2) 54*h*.
Cb-Zr and Cb-Zr-Re alloys, oxidation in oxygen at 1000°C, (9) 241*h*.
dioxide, electrical conductivity and thermoelectric power, (8) 196*c*.
films, conductance during anodic oxidation, (4) 100*d*.
superconductive, method of forming, P (9) 231*d*.
fluorides, hexavalent, (11) 296*i*.
$L\beta_2$ emission band, corrected, and bond forces in system niobium-nitrogen, (3) 84*f*.
low-pressure oxidation, at 1200° to 1700°C, (9) 240*g*.
mobility activation energy, in metallic niobium and its carbides, (5) 137*i*.
NbB_2, high-temperature thermal expansion, (3) 86*f*.
NbC_x phases, thermodynamic functions, calculation of temperature and concentration dependence of, (8) 191*j*.
Nb_2C, lower temperature modifications, (7) 165*f*.
NbO_2F, thermal decomposition, (8) 209*g*.
$Nb_{12}O_{29}$, crystal structure, (10) 270*i*.
$Nb_{11}O_{27}F$ and $Nb_{17}O_{42}F$, crystal structures, (10) 270*e*.
Nb_3Sn diffusion layers, production, P (1) 11*d*.
$Nb_{18}W_{16}O_{94}$, member of $(Mo)_xMO_2$ family of compounds, crystal structure, (10) 270*j*.
Nb-Zr-O alloys, high-niobium-content, phase studies, (11) 299*e*.
nitride, thin films, superconducting, (3) 76*j*.
nitrides, structures, (4) 110*a*.
O-O and O-N clusters in, (7) 162*k*.
ore, use of molten pyridinium chloride in treatment, (5) 124*a*.
oxide, film, anodically formed, electron microscope observations of crystallization, (7) 163*f*.
high-purity, production from pyrochlore-perovskite concentrate, (1) 15*g*.
precipitation from supersaturated solutions, electron microscopic observations, (11) 291*j*.
oxide fluorides, formed at high temperature, (8) 210*j*.
pentachlorides, orthobaric density and critical parameters, (8) 204*d*.
pentoxide, superlattices, direct observation by electron microscope, (9) 238*i*.
structure, method of protecting, P (4) 92*b*.
systems. See *Systems*.
and tantalum compounds, oxidized, with O/M = 2.33 to 2.50, (11) 299*a*.
thin films, superconducting, (3) 76*j*.
-zirconium composition for high field superconducting magnet, P (1) 10*i*.
Nitrates, molten, direct current measurement of conductivity, (3) 84*i*.
Nitrides, complex, superconducting behavior, (2) 56*h*.
of germanium, (11) 298*f*.
metallic, process for preparation, P (9) 266*j*.
oxy-, preparation from refractory oxides, (1) 27*c*.
Nitrogen, compounds, stable at high temperature in ceramic materials, (5) 133*a*.
N_2 in glasses, solubilities at pressures to 10 kbars, (1) 4*d*.
in silicon, determination by solid source mass spectrometry, (4) 104*e*.
systems. See *Systems*.
Noise, Barkhausen, induced by external stress in ferrite head of video tape recorder, (11) 284*d*.
Nomenclature, of cement terms, (3) 64*c*.
of mixed coarse-fine sediments, (4) 111*b*.
Nordstrandite, in alumina, process for producing, P (9) 227*a*.
Nozzles. See *Refractories; Spacecraft*.
Nuclear materials, fuel, hollow spherical UO_2, P (2) 72*g*.
fuel body containing uranium carbide spheroids coated with silicon carbide, P (1) 8*g*.
fuels, carbide-type, pyrohydrolysis, P (1) 8*b*.
for MHD generators, (2) 46*i*.
Nuclear power. See *Energy*.
Nucleation, of barium silicate glasses, B (7) 170*j*.
and crystal growth in silicate glasses, (11) 277*f*.
defect, role of surfaces, (10) 263*h*.
in diffusion crystal growing, (1) 24*d*.
of $NaNbO_3$ from glasses in Na_2O-Nb_2O_5-SiO_2 system, (8) 175*g*.
of silicon on sapphire, (1) 24*b*.
Nucleation (*continued*)
of single-crystal films, (1) 24*g*.
of single crystals by chemical transport: I, cadmium-germanium sulfide, (1) 24*f*; II, zinc selenide, (1) 24*f*.
of thin films, observed in electron microscope, (1) 24*f*.

Oils, fuel, in ceramic industry, (2) 52*g*.
stripping, for structures and objects made from mixtures of mortar, clay, and brick, P (11) 280*c*.
Olivine, synthetic, magnetic properties, (5) 137*a*.
X-ray emission microanalysis, (2) 59*g*.
Opals, in Eocene neritic bar sand, (1) 24*j*.
Opacification. See *Enamels; Glass; Glazes*.
Opacifiers, zircon, preparation and performance in glazes, (8) 182*h*.
Opacity, of glass, effect of composition, (8) 176*e*.
Optical devices, fiber, process for making, P (2) 40*b*.
with infrared radiation transmitting and visible radiation reflecting layer of lanthanum hexaboride, P (2) 48*h*.
for measuring reflective and emissive characteristics of a sample spectrometer, P (1) 14*e*.
utilizing Faraday rotation, P (8) 178*d*.
Optical materials, film, and applications, (9) 229*e*.
Optical properties, biaxial, in antiferromagnetic NiO, (7) 166*d*.
dichroism, in bismuth-doped single-crystal barium titanate, (7) 162*b*.
far infrared, of $LiNbO_3$, (11) 295*b*.
of ferroelectric $LiNbO_3$ and $LiTaO_3$, temperature dependence, (9) 242*c*.
of gamma-irradiated α-Al_2O_3 spheres subjected to 30-kilobars pressure, (2) 56*f*.
of glass, (8) 175*g*.
of glasses, B (9) 245*e*.
investigations, on Ni-containing alkali borate glasses, (3) 66*a*.
magneto-, Kerr effect, longitudinal, in EuO and EuS, (8) 201*g*.
measurement, of titanium dioxide pigment: I, (1) 22*j*.
of oxidized titanium films, (1) 24*a*.
studies, of samarium doped CaF_2 type single crystals, (9) 237*k*.
variations with electric field in barium-strontium titanate ceramics, (7) 156*a*.
of yttrium iron garnet, effect of impurities, (8) 195*a*.
Ores, heat-expandable, apparatus for expanding, P (7) 160*c*.
Organic compounds, glass transitions, (5) 119*b*.
lower aliphatic alcohols, glass transitions, (5) 119*b*.
Orientation, crystal, influence on oxidation of tungsten, (9) 239*k*.
crystallographic, effect on oxidation of tin, (3) 85*a*.
distribution measurement, and application to quantitative X-ray diffraction analysis, (4) 108*f*.
effect, on electrical properties of epitaxial gallium arsenide, (3) 85*d*.
effect, on surface charge density at silicon-silicon dioxide interface, (11) 294*b*.
of hydrogen etched corundum crystals by optical back reflection, (9) 233*j*.
of microcrystals, determination by Weissenberg goniometer, (7) 161*j*.
re-, effects in vitreous carbon and pyrolytic graphite, (10) 271*g*.
spin, determination by linearly polarized recoil-free γ rays, (8) 207*a*.
of stacking faults, in β-SiC, (3) 87*d*.
substrate, effect on epitaxial growth, (11) 294*i*.
effects in open tube HI transport system, (9) 242*b*.
Orthonorite, containing spinal xenoliths with late diaspore at Mill of Boddamm, Insch, Aberdeenshire (Scotland), (3) 87*d*.
Orthopyroxenes. See *Pyroxenes, ortho-*.
Orthosilicates. See *Silicates, ortho-*.
Oscillations, current, in dark conductive CdS crystals, (3) 75*i*.
Gunn, in indium arsenide, (8) 199*d*.
oscillating electric fields, effect on coalescence in liquid + liquid systems, (7) 162*f*.
plasma, of electrons in LiF, (8) 205*c*.
Oscillators, magnetically tuned ferrite cavity transistor, P (11) 286*b*.
Osumilite, formation in various silicate systems, (8) 198*d*.
Osmium, OsSbSe, OsSbTe, and OsBiSe, high pressure synthesis, (7) 164*c*.
silicide, structures and compositions, (5) 138*a*.
trichloride, thermal dissociation, (8) 209*i*.
Ovens. See also *Furnaces; Kilns*.
coke, door, P (4) 98*e*.
crystal, P (2) 52*f*.
crystal growing, heating and control system for, P (4) 100*j*.
Oxalates, thermal decomposition: III, (8) 209*h*.
Oxidation, of aluminum, in contact with mercuric iodide, (3) 77*g*.
anodic, of tantalum and niobium films, conductance during, (4) 100*d*.
of titanium in formic acid electrolytes, (3) 83*h*.
breakaway, mechanism, in zirconium alloys, (2) 35*d*.
catalyst, for hydrocarbon combustion exhaust gases, P (2) 44*j*.
characteristics of hafnium and zirconium diboride, (10) 258*c*.
of Cb-Zr and Cb-Zr-Re alloys in oxygen at 1000°C, (9) 241*h*.
of copper, mechanical stresses and their influence on oxidation kinetics, (7) 164*i*.
de-, agent for steel, P (8) 182*b*.
Oxidation (*continued*)
effect on surface heterogeneity of graphitized carbons, (2) 41*e*.
of germanium disulfide, (11) 298*j*.
of graphite, in simulated reentry environments, (5) 123*f*.
growth, evidence at oxide-silicon interface from controlled etch studies, (3) 85*h*.
high-temperature: I, thermal conductivity method for measurements, (3) 80*h*; II, molybdenum silicides, (11) 297*a*.
of lanthanum, observations, (7) 167*g*.
of molybdenum disilicide, (4) 108*d*.
kinetics, of graphitic carbon in liquid environment, (4) 110*j*.
high-temperature, of zirconium in dry oxygen, (5) 136*j*.
of particulate silicon monoxide, (5) 137*e*.
and oxide film breakaway of zirconium and alloys at high temperatures, (1) 2*j*.
of zirconium diboride and zirconium carbide at high temperatures, (3) 87*f*.
low-pressure, of niobium at 1200° to 1700°C, (9) 240*g*.
mechanism, of metals, use of vacuum-evaporated gold films to investigate, (9) 242*j*.
of zirconium in oxygen and liquid sodium, (9) 240*g*.
of zirconium in temperature range of 400° to 850°C, (7) 165*b*.
molybdenum, kinetics at high temperatures, (11) 298*a*.
of molybdenum disilicide, role of iron, (9) 242*a*.
of nickel in range 900° to 1400°C, (11) 299*a*.
of nuclear-grade graphite by nitric acid and oxygen, (10) 258*e*.
phenomena, in semiconducting $BaTiO_3$, (9) 241*i*.
of pyrolytic graphite at 1400° and 1800°F and at air velocities of 25 to 100 cm/sec, (7) 166*f*.
rates, of sulfide minerals by aqueous oxidation at elevated temperatures, (3) 82*e*.
of silicon tetrahalides, P (1) 16*a*.
studies, of complex silicides for protective coatings, (7) 147*i*.
of submicroscopic fibrous silicon carbide, (9) 241*a*.
thermal, of heavily doped silicon, (11) 302*f*.
kinetics, of silicon in dry oxygen, (1) 21*j*.
of silicon, deviations from parabolic growth, (5) 135*c*.
of silicon, observation of impurity redistribution during, using MOS structure, (9) 241*h*.
of tin, effect of crystallographic orientation, (3) 85*a*.
of $TiCl_4$, process, P (11) 291*f*.
of titanium carbide, effect of temperature and oxygen partial pressure, (5) 135*a*.
by transport through blocking pores, (9) 241*a*.
of tungsten, at high temperatures and pressures, (1) 2*g*.
influence of crystal orientation, (9) 239*k*.
of tungsten disilicide, (3) 87*g*.
of UO_2, investigation by high temperature conductometric, X-ray diffraction, and continuous weighing methods, (11) 297*b*.
of zone-refined iron, effect of oxygen pressure, (11) 294*c*.
of zirconium, at high temperatures, kinetics, (11) 301*j*.
and alloys in water vapor atmospheres containing trace amounts of oxygen at 375° and 575°C, (1) 2*k*.
Oxides. See also *Rare earths and specific types*.
alkaline earth, dissociation energies, (8) 195*b*.
ceramic, modern developments, (11) 303*f*.
rotating cylinder method for measuring normal spectral emittance from 1200° to 1600°K., (2) 51*d*.
single phase, control of microstructure, (4) 103*c*.
vibrational compaction, influence of frequency and acceleration on density during, (7) 151*e*.
pure, thermomechanical properties, (7) 152*f*.
chlorinating process, P (3) 72*f*.
composite, method of making, and resulting products, P (5) 130*b*.
crystal structure, and their neutron irradiation behavior at 80°C, (1) 17*i*.
diffusion in, (5) 135*f*.
equiatomic, of transition metals with NaCl structure, screening of metal-metal bonds in, (3) 87*j*.
film growth, on zirconium, kinetics and mechanism, (5) 136*i*.
films, anodic, on tantalum, kinetics of recombination of Frenkel defects, (7) 164*i*.
on copper single crystal surfaces in water: III, effect of light, (7) 166*f*.
deposition, by reactive evaporation, (2) 46*j*.
on germanium, production, P (7) 148*a*.
properties on zirconium alloys and relevance to corrosion and hydrogen uptake, (2) 35*g*.
thermally grown on silicon, structure and perfection, (8) 207*g*.
thin, method of forming, P (5) 117*j*.
fine particle, high purity, method of making, P (4) 106*f*.
gelled spherical particles, process for making, P (10) 269*i*.
inclusions in metals, technique for studying by using proton radioactivation of oxygen-18, (4) 104*e*.
investigation, by electron beam microanalyzer, (3) 81*a*.
-layer isolation structures, technique for obtaining, (3) 77*a*.
manufacture, P (4) 103*g*.
masking, in preferential silicon epitaxy, (3) 76*g*.
materials, apparatus for high pressure high temperature studies, (2) 50*e*.
metal, apparatus and process for production, P (9) 235*i*.

Oxides, metal (*continued*)
microspheres, method of making, P (7) 153*a*.
with perovskite-like structures, (8) 203*h*.
thin flakes, method of producing, P (11) 291*j*.
for neutronic reactor control, method of preparing, P (4) 98*g*.
phases, glassy and polymorphic, new, using rapid quenching techniques, (11) 298*c*.
powders, preparation and calcination, effects of water vapor, B (7) 169*i*.
refractory, dislocations and effect on properties of, (11) 293*d*.
-silicon interface, evidence for oxidation growth, from controlled etch studies, (3) 85*h*.
sintered white, diffuse reflection and emission of, (1) 17*h*.
sub-, vaporization, thermodynamics, (4) 112*e*.
super-, process for making, P (3) 73*a*.
systems. See *Systems*.
thermodynamic properties: I, solid solutions of ferrites, (11) 302*i*.
ternary, of americium and other rare earths of type $A(III)_xBO_3$, (11) 302*d*.
thermal diffusivity and conductivity measurements at high temperatures, (2) 51*i*.
tooling, machining with, (2) 33*i*.
transuranium, reaction with alkali oxides: I, ternary oxides of hexavalent transuranium elements, lithium and sodium: II, ternary oxides of pentavalent transuranium elements and of protactinium with lithium and sodium, (8) 206*f*, *i*.

Oxygen, ablation of graphite in, at 1000° to 1400°C under flow conditions, (2) 40*i*.
adsorbed, on zirconium dioxide mechanism of reduction with hydrogen, (5) 137*f*.
atomic, chemisorption, (7) 169*f*.
atoms, rate of combination with oxygen molecules, (7) 167*d*.
in clinker burning, (11) 275*c*.
desorption, from zinc oxide surfaces, activation energy for, (11) 292*g*.
diffusion, technique for studying in metals by proton radioactivation of oxygen-18, (4) 104*e*.
equilibrium pressures, over MnO_2-Mn_2O_3 at various temperatures, (11) 295*h*.
gradients, in oxidizing hafnium, (7) 168*i*.
in oxidizing metals, study: III, kinetics of oxidation of zirconium at high temperatures, (11) 301*h*.
ion activity, effect on redox equilibrium in glasses, correction, (5) 119*j*.
-ion diffusion, (1) 24*d*.
molecular, adsorption with electron transfer, (7) 169*f*.
negative ions, measurement of concentration and mobility in oxide-coated cathode and of capacitance variation of cathode with temperature, (3) 86*f*.
partial pressure, effect on oxidation of titanium carbide, (5) 135*a*.
potential diagram, summarizing Fe-Mn-SiO equilibria at 1600°C, (3) 87*i*.
pressure, effect on oxidation of zone-refined iron, (11) 294*c*.
reaction with evaporated films of lead, (8) 183*h*.
self-diffusion, in Y_2O_3 and Er_2O_3, (3) 88*a*.
solid solutions, in α-zirconium, X-ray studies, (3) 88*a*.
in hafnium, X-ray studies, (3) 88*b*.
solubility, permeability, and diffusivity, in solid iron, (10) 250*g*.
systems. See *Systems*.
transfer, from low to high chemical potential through an ionic membrane, (3) 88*c*.
transport, in oxide films on zirconium determined by nuclear reaction $^{17}O(^3He,\alpha)^{16}O$, (5) 139*d*.

Packaging. See also *Shipping*.
of compressible material, P (9) 221*j*.
method and apparatus for producing a wound textile package having uniform tension, P (1) 5*g*.
package, for glass sheets, P (7) 150*a*.
Pallets. See *Materials handling*.
Panels. See *Building materials*.
Paramagnetic materials. See *Magnetic materials*.
Particles. See also *Colloids*.
concentration, apparatus for reducing in volume of liquid, P (7) 158*h*.
distribution plotting apparatus, P (10) 268*a*.
fine, high voltage separation, P (7) 160*j*.
surface, properties, with special reference to specific surface, (11) 299*g*.
flow, radial velocity distribution, in shaft kiln, (7) 146*j*.
flow-through sample apparatus, for electrical study device, P (11) 289*h*.
heterogeneous, selective separation, P (4) 107*c*.
organophilic and hydrophobic, and method for preparing, P (10) 260*b*.
packed, degree of mixedness and bulk density, (10) 266*b*.
size, $BaTiO_3$, controlled, P (3) 77*h*.
dependence of electrical conductivity of NaCl, (4) 109*a*.
determination, by light scattering, (3) 84*i*.
determination of milled zircons, (2) 51*a*.
estimating by intercept method, (3) 80*i*.
influence on mechanism of solid-state reactions, (8) 200*d*.
measurements in glazes and enamels., (11) 283*h*.
reduction process, P (1) 13*b*.
size analysis, comparison of methods, (4) 104*e*.
data handling techniques, (2) 50*f*.
for determination of specific surface of glass powders and its relation to statistical parameters, (4) 93*b*.

Particles, size analysis (*continued*)
of fine abrasive powders by sedimentation techniques, (1) 1*f*.
sedimentation methods, (4) 104*c*.
size distribution, determination, (5) 130*f*.
effect on properties of Nishiyama pottery stone, (5) 125*g*.
and light scattering of spherical particles, (3) 86*c*.
distribution of powder, method of determining, P (.0) 268*d*.
solid, impacting and elutriating, process and apparatus, P (7) 158*h*.
pneumatically separating, process and apparatus, P (7) 158*h*.
spherical, light scattering and particle size distribution: I, theory; II, experimental, (3) 86*c*.
processing for making, P (10) 269*i*.
second-phase, from extraction replicas, determination of number, size, spacing, and volume fraction, (8) 194*a*.
study apparatus, aperture tube structure for, P (4) 104*h*.
Pellets, desiccant, process for preparing, P (4) 107*c*.
Periclase, high-purity, developments, (3) 71*f*.
Peridotite, high-temperature intrusion, in Lizard area, Cornwall, petrogenesis, (1) 24*j*.
Perlite, expanded, and method for formation, P (9) 235*g*.
filter aids, method of improving with phosphoric agent, P (11) 282*b*.
structures, method for formation, P (9) 223*b*.
Permeability. See also *Porosity*.
measurements, for characterizing powder compacts, B (7) 169*j*.
of oxygen in solid iron, (10) 250*g*.
Permittivity. See *Dielectrics, constant*.
Perovskites, P (7) 157*b*.
pyrochlore-, concentrate, for production of high-purity niobium oxide, (1) 15*g*.
structure, refractory compounds with structures derived from, in systems zirconia-alkaline-earth oxides, (1) 28*d*.
Petalite, ceramics, slip casting, (5) 125*g*.
powder and pulverized lithia-containing glass mixture, hot pressing of, (2) 37*i*.
Petrogeny, petrogenesis of alkaline rocks, and Na_2O-Al_2O_3-Fe_2O_3-SiO_2 system at 1 atmosphere, (2) 57*h*.
petrogenesis of high-temperature peridotite intrusion in Lizard area, Cornwall, (1) 24*j*.
petrogenetic study of Rosses Granite complex, Donegal, (7) 166*g*.
Petrology, of adamellite-porphyrite from New England bathylith (New South Wales), (1) 25*b*.
chemical of Grenville schists near Fernleigh, Ontario, (8) 192*h*.
of metamorphosed Wabush iron formation, southwestern Labrador, (7) 165*f*.
of middle Devonian limestones in South Devon, England, (1) 25*d*.
petrological sections, and semiautomatic preparation of ultrathin and large-area, (2) 51*g*.
of reactions of fused cast alumina refractories with metals and slags, (2) 42*c*.
of Simsboro formation of northeast central Texas, (8) 204*b*.
pH. See *Hydrogen ion concentration*.
Phase, boundaries, in portion of system SrO-B_2O_3, (3) 87*j*.
change of zinc sulfide and stacking sequence of new 66R polytype, (8) 204*f*.
components, of system MnSi-Si, (3) 87*a*.
composition, of diffusion layer of boronized metal, (1) 25*e*.
of silicon carbide refractories bonded with silicon nitride, (4) 97*j*.
pressure-induced, of sulfur-selenium, (3) 87*g*.
primary, of clear sheet glass, (2) 37*c*.
relationships for plutonium oxides, (4) 112*d*.
shifter, latching ferrite, having predetermined phase shift, P (8) 184*j*.
solid-, interactions between oxides and sulfates of zinc, cadmium, and copper, (1) 28*h*.
stability of silicon carbide, (8) 205*b*.
transformations, diffusionless, of zirconia at high temperatures and ultrahigh pressures, (9) 238*j*.
at high temperatures in hafnia and zirconia, (4) 109*g*.
solid-solid, combined effect of ultrahigh pressure and nuclear irradiation, (2) 54*i*.
transition, in Sr $(FeTa)_{1/2}O_3$, (9) 24 *b*.
in system $BaTiO_3$-$KNbO_3$, (3) 76*f*.
in VO_2, (4) 109*h*.
Phase diagrams. See *Equilibrium studies*.
Phase rule. See *Equilibrium studies*.
Phenols, bromo-, blue, for distinguishing limestone from dolomite, (5) 130*j*.
Phonons, drag effect, positive, in Nernst coefficient of CdS, (9) 241*e*.
transmitted, drag measurements in epitaxial silicon, (3) 88*c*.
zero-, lines, under uniaxial stress in magnesium oxide, (3) 88*b*.
Phosphates. See also *Glass* and specific types.
alkali metal, continuous recycle heating process for production of, P (11) 291*e*.
alkaline earth, sensitization of Tb^{3+} luminescence by Sn^{2+} an Cu^+ in, (3) 76*h*.
-bonded composition, high alumina refractories, P (2) 44*e*.
bonding, of zirconia, (4) 97*a*.
bonds, gunning mixes with, (4) 97*b*.
crystalline and glassy, heats of formation, (5) 136*i*.
ion exchangers, (1) 29*j*.

Phosphates (*continued*)
molybdenyl, preparation and luminescence, (11) 299*e*.
ortho-, process for production, P (8) 190*g*.
radioactive, adsorption on two ternary borate glasses, (10) 253*e*.
rocks, thermal change, (3) 82*j*.
solid, infrared absorption, with and without fluoride additions, (7) 164*i*.
systems. See *Systems*.
Phosphoric acid, dehydrated, electrical conductivity of, (4) 107*i*.
dehydrated, viscosity, (4) 112*c*.
method and apparatus, P (2) 54*d*.
process for removing iron from, P (7) 148*a*.
Phosphorus, alkaline earth halophosphate, luminescence spectra, (3) 76*c*.
cadmium halophosphate, (4) 100*c*.
calcium iodide, P (5) 127*a*.
coated articles, P (10) 265*e*.
composition for adhering powder to surface, P (8) 184*e*.
copper activated strontium metaphosphate, P (8) 184*f*.
copper activated strontium phosphate, P (9) 230*b*.
copper activated thorium phosphate, (3) 75*i*.
dielectric storage target for cathode ray tube, P (3) 79*i*.
electroluminescent, processing, P (5) 128*j*.
europium-activated, fluorescent properties, (7) 155*j*.
fiber faceplate, for cathode-ray tubes, P (7) 157*c*.
group II metal-thorium phosphate, P (8) 184*c*.
halophosphate formation, vapor transport reactions related to (10) 263*a*.
lanthanum, yttrium, or lutetium, process for preparing, P (9) 232*b*.
layer, thin porous storage, P (3) 79*i*.
orthophosphate, compositions, P (1) 11*j*.
particles, technique for examining luminous activity in functioning electroluminescent lamp, (4) 104*e*.
phosphorescence of borate glasses, kinetics, (8) 175*i*.
(III,V) oxides, from mixed crystals (P_4O_8-P_4O_7), (8) 207*i*.
rare earth oxide and vanadate, P (9) 232*g*.
red-emitting europium-activated, with cathode ray excitation, fluorescent properties, (9) 229*i*.
thermoluminescent doubly doped LiF, P (8) 186*b*.
Phosphorus, acid-wetted expandable, containing graphite composition and method of preparation, P (10) 259*c*.
controlled incorporation of, in anodic oxide films, (3) 75*e*.
diffusion in silicon, formation and composition of surface layers and solubility limits, (7) 163*g*.
elementary, causes striking effect of phosphate glass, (7) 148*i*.
incorporation in epitaxially grown silicon, radiotracer studies, (7) 167*d*.
with organic base molybdates, determination, (8) 187*f*.
systems. See *Systems*.
Photoconductive effect, and(or) **Photoconductivity,** of CdS in blocking electrodes, (5) 137*h*.
excitation spectra of (Cd,Zn)S:Ag,Cu,Cl and (Cd,Zn)(S,Se):Ag,Cu,Cl, (1) 26*e*.
kinetics, effect of intercrystalline barriers, (11) 294*a*.
layer for use in printing cathode ray tube, P (1) 11*b*.
Photoconductors. See *Conductors, electrical, photo-*.
Photoelectric cells. See *Cells*.
Photoelectric effect, investigation of nickel + oxygen system, (7) 166*a*.
Photography, inside operating glass furnaces, (3) 66*c*.
photographic images, vitrified, photoceramic process for producing, P (11) 283*j*.
Photometers. See also *Spectrophotometers*.
for complexometric titration of CaO, MgO, and Fe_2O_3 in cement materials, (9) 215*e*.
flame, multichannel integrating, (4) 104*j*.
Photometry, flame, determination of calcium, unusual effect of iron, (2) 51*b*.
flame, determination of Na_2O and K_2O in cements, (5) 116*e*.
for determination of sodium oxide in soda-lime-silica glasses, (10) 251*i*.
role of solvent, (8) 188*a*.
method and apparatus, P (5) 132*a*.
Physical chemistry. See *Chemistry*.
Physical properties, of aluminum nitride, (8) 207*i*.
of Be compounds: V, VI, (8) 210*d*.
of glass-ceramics and their relation to microstructure, (2) 36*e*.
testing apparatus, P (8) 188*d*.
of transition metal carbides of fixed composition and homogeneity domain of groups IV and V at 2500°C, (3) 87*d*.
of uranium dioxide-stainless steel cermets, (7) 151*j*.
Physicomechanical properties, of ceramic body during firing process, basis for determining optimum firing rate, (4) 105*c*.
of refractories, experimental apparatus for investigating, (4) 96*g*.
Pickling, bath, hydrochloric acid, regeneration, (10) 250*f*.
embrittlement-free, of ferrous metal, P (7) 147*i*.
spray, promotes uniform steel preparation, (9) 216*h*.
Piezobirefringence. See *Refraction, birefringence*

Piezoelectricity, piezoelectric body, manufacture, P (10) 264*e*.
piezoelectric, ceramic filter, P (4) 102*g*.
ceramic transformer, P (4) 102*g*.
ceramics, (9) 229*f*.
composition, firing, (7) 155*h*.
coupling, direct to surface elastic waves, (3) 75*f*.
device, particularly force measuring instrument and process of making, P (1) 11*a*.
properties of $Pb(Mg_{1/3}Nb_{2/3})O_3$-$PbTiO_3$-$PbZrO_3$ ceramics modified with certain additives, (1) 10*c*.
quartz crystal units, P (2) 48*j*.
uses, manufacture of ceramic bodies suitable for, P (1) 11*b*.
wide bandpass filter with elliptical shape, P (8) 185*h*.
piezoelement for piezoelectric force measuring instruments, P (1) 11*b*.
Pigments. See also *Color; Stains.*
bright, P (4) 99*j*.
cadmium, (2) 45*j*.
cadmium yellow, process for preparation, P (11) 291*g*.
calcined, from kaolin, P (7) 160*j*.
from conditioned and calcined TiO_2 particles, process for production, P (11) 292*a*.
flame, composition and process for production, P (11) 278*c*.
formed by plasma jet, improved preheater configuration, P (9) 226*e*.
infrared reflective, manufacture, P (8) 190*g*.
iron oxide, process for producing, P (11) 291*i*.
in liquid medium, apparatus for grinding and/or dispersing, P (10) 266*e*.
nacreous glass flake, compositions, P (10) 256*a*.
pink, manganese and aluminum containing, for glazes and underglazes, P (10) 261*e*.
red iron oxide, (11) 291*a*.
rutile, fluid bed process for producing and reducing accretion, P (2) 54*b*.
silica, precipitated, method and means for reducing fouling of equipment in preparation of, P (9) 236*a*.
and preparation, P (5) 133*h*; P (9) 236*g*.
and process for producing, P (11) 292*f*.
slurries, stabilized, P (3) 83*e*.
titanium, P (3) 83*f*.
from titanium dioxide and zinc oxide, process of manufacturing, P (11) 291*e*.
white, P (11) 292*e*.
zinc oxide, production, P (8) 190*h*.
Pipe. See also *Tile.*
P (9) 223*d*.
ceramic, supports, P (3) 74*j*.
clay, vitrified, quiet revolution, (2) 40*e*.
curved, design of dies for making, (3) 70*c*.
firing, experiments, (9) 222*i*.
glass, coupling for joining pipe sections of varying size, P (4) 95*b*.
transparent reinforced, P (8) 179*b*.
Japan's clay, Tokoame ships 50% of, (4) 96*c*.
machines, review of U.S., (11) 279*j*.
made from fused rock, (5) 123*g*.
piping, clayware, P (8) 179*f*.
sewer, German system–flexible layout, (1) 6*i*.
horizontal auger extrusion, (7) 150*i*.
stoneware, automatic manufacture, (3) 70*a*; (8) 179*c*.
isostatic pressing, (9) 222*i*.
straight, at Mission Clay Products Corp., (4) 96*d*.
Plagioclase, feldspars, X-ray emission microanalysis, (2) 60*a*.
fusion method, improvement, (10) 252*i*.
Plasma, arc techniques for material research, (9) 233*g*.
direct current, new spheroidizing process, (9) 234*g*.
heat, methods and devices for heating substances by, P (4) 105*f*.
jet-improved preheater configuration for pigment, P (9) 226*e*.
torch, fundamentals and applications, (5) 132*e*.
Plaster of Paris. See *Gypsum.*
Plasters, baking at low temperatures, P (1) 2*d*.
of calcium sulfate, polyvinyl acetate and starch, for wallboard joints, P (4) 91*g*.
choosing right type for molds, (11) 283*g*.
compositions, P (3) 64*g*; P (5) 117*a*.
containing polyvinyl acetate, P (5) 117*b*.
content, of portland cement, (4) 91*b*.
gypsum, improvements, P (2) 35*a*.
hardened suspensions, relations between structure and strength, (10) 248*j*.
hemihydrate, strength, (10) 248*h*.
molds. See *Molds.*
suspensions, set, relation between structure and strength, (9) 215*f*.
synthetic, set retarder, P (5) 117*b*.
treating, process, and resultant products, P (7) 147*b*.
water resistant, P (10) 249*d*.
Plasticity, cyclic torsion test, (2) 45*j*.
of high-melting point materials, temperature effect, (3) 71*j*.
Plastics. See also *Resins.*
with glass, asbestos and cellulosic fiber reinforcement, thermal conductivities, (9) 218*h*.
glass fiber composites, introduction, (9) 218*f*.
transparent, advantages over glass, (1) 4*j*.
wider choice, with cooler flame spraying, (3) 79*j*.
Plating. See *Coatings.*
Plutonium, carbides, volatility, (8) 211*h*.
determination in refractive materials by electrometric methods, (8) 187*h*.
dioxide, stabilizing method, P (10) 259*i*.
and phosphate, composition containing, P (11) 281*b*.
Plutonium (*continued*)
fabrication of sintered compounds based on uranium and, P (2) 43*j*.
filterable coprecipitate, preparation, P (3) 72*d*.
mononitride, method of preparing, P (1) 8*a*.
oxide, sol and calcined microspheres, preparation, P (7) 153*g*.
oxides, ternary, of type M(III)X(V)O_4, reaction conditions, lattice constants, and chemical properties, (11) 299*j*.
thermodynamics and phase relationships, (4) 112*d*.
phosphide, preparation by direct combination of elements, (11) 299*e*.
PuO_{2-x}, defects, –density measurements at high temperatures, (1) 17*c*.
in plutonium oxide, determination by calorimetry, (8) 187*g*.
PuS and PuP, sintering characteristics and properties, (1) 28*g*.
and uranium monoxide-type compounds: I, oxycarbides, (7) 166*b*.
systems. See *Systems.*
Poisson's ratio, in viscoelastic materials, (10) 267*a*.
Polarizers, broad band circular, utilizing pyrolytic boron nitride plate, P (7) 156*g*.
Polarization, behavior, dependence on texture of lead titanate zirconates, (11) 284*g*.
process for ceramics, P (7) 157*e*.
Polarography, in molten sodium disilicate, (2) 37*b*.
Polishing. See also *Abrasives; Diamonds.*
compound, for glass, P (4) 89*h*.
process for preparing, and product, P (4) 89*g*.
crystal glass and lead crystal glass articles, P (3) 68*j*.
crystalline silicon, process, P (9) 232*a*.
crystals, process, P (9) 213*g*.
electro-, both sides of semiconductor, P (3) 79*b*.
of glass, P (7) 150*c*.
glass, agents, with rare earth oxide, process for producing, P (7) 150*d*.
porous materials, (7) 159*b*.
process, for objects with irregular surfaces, P (9) 213*f*.
yttrium aluminum garnet single crystals, (10) 272*i*.
Polishing apparatus. See also *Abrasives; Diamonds.* P (1) 14*d*.
for bottles, ampoules, P (3) 69*j*.
for glass, method, P (3) 68*a*.
Pollucite, sintered, radioactive source, and method of production, P (11) 292*a*.
Polyelectrolytes. See *Electrolytes.*
Polymers, alkali metal vinyl siliconates, for treatment of glass surfaces, P (1) 6*e*.
emulsion, modifies properties of cement mortars, (4) 91*c*.
glassy, low-temperature excess heat capacity in, (4) 108*e*.
methyl methacrylate, for impregnating glass fiber mat, P (2) 40*b*.
Polymorphism, of In_2Se_3, (1) 27*a*.
Polyphosphates. See *Phosphates.*
Porcelain, art. See *Art and artware.*
bodies, shaping, (7) 155*a*.
colors, lead-free, (3) 74*c*.
combustion boats, semiautomatic production, (10) 261*h*.
deformation, effect of glaze composition, (3) 73*j*.
dental. See *Dental ceramics.*
electrical. See also *Insulators, electrical.*
brown glaze for, (3) 73*g*.
electrical bushing, mold, P (2) 40*e*.
electrotechnical, effect of quartz on mechanical strength, (10) 261*f*.
soret effect, (11) 301*c*.
thermal electromotive force, (5) 125*i*.
firing: I, increase of Al_2O_3 content, (1) 9*b*; III, in the presence of fluorides, (1) 9*d*.
in tunnel kilns with different fuels, heat efficiency data, (3) 74*b*.
hard, electric tunnel kiln for firing in a reducing atmosphere, (8) 189*a*.
industrial, pressing, and products obtained, P (11) 284*a*.
replacing feldspar by alkaline waste, (3) 82*i*.
industry, examination of costs, (3) 74*b*.
silicon carbide saggers for, (9) 224*g*.
use of natural gas, (4) 105*f*.
insulators and bushings, cylindrical, ways and means to increase mechanical strength, (2) 46*h*.
-like objects, process for making, P (11) 284*a*.
Meissen, in Bavarian National Museum, (7) 145*j*.
microstructure, relation to metallizing properties of forsterite porcelain, (2) 46*d*.
Russian, under the czars, (3) 63*j*.
sintering, effect of apatite and chalk additions, (9) 228*c*.
texture, study with optical and electron microscopes, (3) 74*f*.
triaxial, containing alumina and silica, comparison of strength, (8) 182*h*.
under high alternating fields, dielectric properties, (8) 182*h*.
Pores, classification, theory of volume filling for vapor adsorption, (2) 57*g*.
in crystalline solids with boundary lattice, diffusion coalescence, (5) 135*f*.
distribution, ultrasonic study in sintered beryllia, (2) 59*i*.
effect on rate of grain growth of sintered alumina, (4) 110*d*.
Pores (*continued*)
fine, in ceramic bodies, optical accentuation, (10) 267*a*.
formation in solidification, (7) 166*h*.
growth, during solarization of sintered UO_2, (7) 152*a*.
mean radius of, methods and devices for determining in microporous barriers, P (2) 52*a*.
in refractories, classification, (9) 223*f*.
size distribution, determination, (5) 130*j*.
narrow, process for preparing alumina with, P (9) 226*j*.
structure and effect of porosity on properties, methods of examining, (11) 289*j*.
and thermal conductivity, (11) 299*j*.
Porosity. See also *Permeability; Pores.*
contraction, contraction and formation during hydration hardening of cements, (1) 1*j*.
effect on properties of pores, methods of examining, (11) 289*j*.
functional relation to creep rate for polycrystalline ceramics, comment, (10) 270*f*.
influence on structural water content in silica gel and its thermal dehydration, (1) 19*g*.
Porous materials. See also *Cements; Concretes; Insulation, thermal.*
bodies, method and apparatus for infiltrating, P (7) 157*a*.
ceramic bodies, and composite members and methods of making, P (2) 46*f*.
ceramics, from bodies based on waste from asbestos-enrichment factories, (4) 96*f*.
polishing, (7) 159*b*.
thermal transpiration measurements on, (11) 290*f*.
Portland cement. See *Cement, portland.*
Potash feldspar. See *Feldspar.*
Potassium. See also *Alkalis.*
aluminate $K_2[Al_2O(OH)_6]$, crystal structure, (1) 17*a*.
aluminum silicon oxide systems. See *Systems.*
bromide, Debye-Waller factors, thermodynamic calculation, (8) 210*b*.
growth by deposition from vapor, (9) 240*b*.
bromides, ternary system, (2) 57*f*.
chloride, crystal surface, adsorption of dyes to etch pits on, (9) 233*f*.
crystals, gamma-irradiated, dichroism in R bands induced in, B (9) 244*g*.
interaction with chlorides of indium, copper(I), silver, and thallium(I), (8) 200*j*.
ionic crystals, thermoelectric power, (2) 58*g*.
melts, solubility of vanadium trioxide in, (8) 207*g*.
specific heat at low temperatures, small-size calorimeter for determining, (9) 234*a*.
chlorides, ternary reciprocal system, (2) 57*f*.
cyanide-potassium ferrocyanide reagent, for selective determination of iron, (10) 267*g*.
fluoride, systems. See *Systems.*
fluorides, ternary reciprocal system, (2) 57*f*.
molybdenum bronze, blue, $K_{0.3}MoO_3$, crystal structure, (9) 237*f*.
oxides, volatilization during burning of clinker and distribution in minerals, (10) 249*c*.
oxygenated compounds, action on zirconia, (1) 16*d*.
phosphate, systems. See *Systems.*
KCl-LiCl, direct current measurement of conductivity, (3) 84*j*.
KCl-NaCl alloy, polycrystalline, deformation properties, (3) 84*g*.
KI/Tl single crystals, decay times of luminescence, (8) 194*f*.
$KNiF_3$, ionic crystals, covalency, (10) 270*h*.
$KTaO_3$, single crystal, calcium concentration vs. net ionized donor concentration in, (5) 134*f*.
$K_2Ti_2O_5$, crystal structure, (3) 84*a*.
$KWCl_6$ and K_2WCl_7 compounds, synthesis and determination of heat formation, (2) 57*c*.
salts, effect on formation of cement clinker minerals, (10) 248*f*.
sulfates, in portland cement clinker, to improve physicomechanical properties, (4) 90*h*.
systems. See *Systems.*
tantalate-potassium niobate, for elastic wave devices, P (3) 77*j*.
titanate, fibrous, synthesis by flux evaporation method, (1) 29*g*.
volumetric determination of, in cement analysis with polarization current titration, (1) 2*b*.
wolfram bronzes, thermal expansion, (4) 111*f*.
Potters, craft, B (11) 305*a*.
journey through southern highlands, (4) 90*b*.
Pottery. See also *Archeology; Art and artware; Bodies, ceramic; Design; Dinnerware; Earthenware; Stoneware; Whiteware.*
articles, production, P (8) 183*a*.
clays, IL/MA method of assessing, (2) 50*d*.
decoration. See *Decoration.*
materials and techniques, B (9) 245*h*.
plant, Holkham, (3) 63*j*.
shaping, use of low melting point alloys, (9) 228*d*.
surface texture, (5) 125*h*.
Turkish, B (11) 306*c*.
Pottery industry, rotary work supporting machine for, P (3) 75*d*.
Potterymaking apparatus and equipment. See also *Dryers; Kiln furniture; Kilns; Materials handling; Molds.*
for throwing and turning potter's clay, P (3) 64*a*.
Powders. See also *Granular materials.*
alloy, for flame spraying, P (11) 276*d*.
behavior, compacted in die, B (7) 170*c*.
ceramic, characteristics and preparation, B (7) 169*i*.

Powders (*continued*)
characterization, to indicate mixing properties, B (7) 169*j*.
compacts, density, nomograph, (7) 169*h*.
permeability measurements as means of characterizing, B (7) 169*j*.
and sintered bodies, contact section, and values of mechanical properties related to contact section, (5) 134*g*.
dissolution, mechanism, (5) 137*c*.
ferrite, manufacture by thermal decomposition of sulfates, (10) 262*g*.
fine, determining characteristics, (2) 50*i*.
granulating, method and apparatus, P (1) 12*i*.
lead titanate, process for producing, P (10) 265*a*.
masses, compressibility, (3) 84*j*.
material, apparatus for heating, P (4) 91*d*.
metal, method and apparatus for hydrostatically compacting, P (8) 186*h*.
molding, for manufacture of molded amorphous silica bodies, P (4) 106*h*.
particle size distribution, method of determining, P (10) 268*d*.
permeability and pressibility, statistical criterion for degree of dispersity and allowance for particle shape effect on, (4) 110*g*.
powdered materials, treatment, P (1) 13*c*.
powdered samples, thermal contact for low temperature calorimetry, (1) 14*g*.
rotation flow phenomena of, (11) 300*e*.
two-component mixture, of different degrees of dispersion, investigation of interdiffusion, (3) 86*j*.
Power. See also *Energy*.
factor of mica, effect of thickness, (2) 46*j*.
Pozzolans. See also *Cements; Mortars*.
clay, industry: I, clays of India; II, manufacture of surkhi and lime-reactive surkhi mixture, (8) 174*a*.
pozzolanic admixtures, effect on cement resistance to sulfate solutions and on mechanism of SO_3 bond, (4) 90*j*.
Praseodymium, monocarbides, standard free energy of formation, (4) 110*d*.
selenide, single crystals, (8) 207*c*.
Precipitates, co-, filterable, of plutonium and uranium, preparation, P (3) 72*d*.
formed by hydrolysis of iron(III) in 0.5M NaCl ionic medium, X-ray and electron microscope study, (10) 272*d*.
Precipitation, of boron nitride from ferrous melts, (10) 258*i*.
of crystalline layers of highly pure brittle materials, P (11) 286*f*.
effects, of aluminum, lanthanum, iron(III), and thorium, phosphates, (3) 87*e*.
grain boundary, in oxide systems, (1) 19*f*.
of phosphate, quinolinium and lutidinium molybdates as reagents for, (8) 187*i*.
pyrolytic, of semiconductor material from gaseous compound, apparatus, P (3) 77*c*.
of semiconductor substance, P (11) 287*g*.
Precipitators, electrostatic, high-temperature, top closure for, P (5) 80*f*.
electrostatic, system for broad spectrum purification, P (8) 186*g*.
Presses, brick, P (11) 280*b*.
compacting, with selective ejection, P (11) 288*h*.
filter, P (1) 12*f*; P (3) 80*c*; P (10) 266*g*.
automatic, (9) 232*h*.
with automatic detachment of filter cakes, P (3) 80*b*.
plate self-shifter for, P (5) 130*c*.
pressure lid for, P (10) 266*f*.
trays, P (3) 80*b*.
heatable, P (1) 12*g*.
hydraulic, for refractory materials, choice of capacity of pump equipment, (5) 122*i*.
in refractories industry, characteristics of filling devices for, (5) 122*i*.
tablet, P (11) 280*b*.
Pressing, articles from powdered material, P (7) 158*g*.
bench scale isostatic, (7) 158*c*.
dry, Bourry diagram and drying shrinkage, (5) 121*j*.
for producing spark plug insulators, P (11) 284*b*.
properties of spray dried bodies for, (5) 129*h*.
explosive-impact direct, (3) 80*a*.
fluid amplifiers, for measurement and control of cycles, (4) 93*i*.
friction and hydraulic, effect on glazing, (5) 125*h*.
high temperature isostatic, P (1) 12*g*.
hot, apparatus, P (5) 130*c*.
of beryllia powders of different origin and thermal treatment, (10) 258*g*.
of ceramics, B (7) 170*i*.
for fabrication of dense UO_2, (10) 257*i*.
isostatic, (3) 80*a*.
of kaolin and mixtures of alumina and silica, B (7) 170*b*.
of MgO, effect of LiF, (8) 195*c*.
metals and refractories, method, P (11) 282*a*.
new technology for improved materials, (9) 232*i*.
preferred orientation in MgO, (11) 299*a*.
reactive, of magnesium hydroxide, (11) 300*h*.
uniaxial and triaxial, (3) 80*a*.
of industrial porcelain, and products obtained, P (11) 284*a*.
isostatic, (5) 129*j*; (9) 232*j*.
in ceramics, (9) 232*j*.
for improved quality, (9) 232*h*.
of stoneware pipes, (9) 232*i*.
techniques, (9) 232*i*.
time and costs study, (9) 223*d*.
pressed wood components, for use in tile plant, (3) 74*d*.
Pressing (*continued*)
protective thermocouple sheaths, (7) 152*c*.
semidry, for face brick, (3) 70*d*.
for production of shapes from semiacid raw materials, (5) 123*g*.
Pressure, back, effect on counter diffusion of gases in graphite, (7) 151*i*.
controlling, apparatus and method, P (3) 80*c*.
differences, method for direct measurement, P (4) 104*j*.
dissociation, of iron-nickel oxides, (7) 162*c*.
effect on emf of thermocouples, (7) 159*e*.
high, effect on crystallization kinetics with special reference to fused silica, (2) 36*b*.
effects on glass, (10) 252*h*.
electrical behavior and equation of magnesium oxide state during, (1) 19*b*.
high temperature studies of oxide materials, apparatus for, (2) 50*c*.
methods and apparatus, P (10) 266*a*.
research tool for solid-state physics, (9) 239*f*.
solubility of glass, (1) 4*d*.
hydrostatic, effect on elastic properties of powder metal cutting alloys, (4) 96*c*.
isostatic, effect on sintering, (8) 195*b*.
measurement, viscosity gage for, in range 10^{-6} to 10^{-4} torr, (2) 51*g*.
sublimation, of CoF_2, Knudsen and Langmuir measurements, (8) 201*j*.
ultrahigh, with nuclear irradiation, combined effect on solid-solid phase transformations, (2) 54*i*.
vapor. See *Vapor pressure*.
Probes, device, wide temperature range four point, for measuring electrical resistivity, (1) 14*b*.
micro-, for investigation of portland cement clinker, (5) 116*g*.
thermocouple, construction, P (2) 52*b*.
three-point, for electrical characterization of epitaxial films, (3) 81*h*.
Prosthetic ceramics, method of making, P (8) 183*a*.
Protons, transfer, in montmorillonite and illite adsorption of amino acids and peptides, (7) 161*f*.
Psychrometry. See *Humidity, measurement*.
Pulpstones. See *Abrasives*.
Pulverization, of refractory materials by vibrating ball mill, (11) 280*j*.
Pulverizers. See *Crushing and grinding apparatus*.
Pulverizing. See *Crushing and grinding*.
Pulverulent materials. See *Powders*.
Pumice, rhyolitic, for making heat insulating and refractory concrete, P (3) 73*c*.
Pumps, centrifugal, P (2) 49*j*.
water, with vitreous china casing, P (4) 100*a*.
Purification, apparatus for separating solid particles from gas, P (2) 50*b*.
of boron nitride, continuous process, P (8) 180*j*.
of colloidal particles for subsequent structural analysis with electron microscope, P (8) 188*c*.
of highly dispersed oxides of silicon, aluminum, titanium and/or zirconium, process, P (9) 236*j*.
of silicon carbide, by flotation process, P (8) 181*c*.
of titanium diboride, P (8) 181*g*.
zone, of materials, new variant, (8) 203*e*.
Pyrite, desulfurization, (1) 6*h*.
thermal decomposition, kinetics of, (3) 86*a*.
Pyrophyllite, roseki: I, compacted and wet ball-milled thermal properties; II, relation between specific surface area and ceramic properties of nonsericite roseki used for wall tile bodies, (7) 160*h,i*.
transformation into interstratified structure, (5) 139*c*.
treatment, P (4) 107*d*.
Pyrope, synthetic, refinement of crystal structure, (1) 27*j*.
Pyrometers; Pyrometry. See *Temperature measuring instruments*.
Pyroxenes, clino-, near diopside-hedenbergite join, X-ray-emission microanalysis, (10) 272*f*.
formation in magnesite-chrome refractories in glass furnace regenerator walls, (10) 258*c*.
ortho-, -bearing rocks of charnockitic affinities in South Savanna-Kanuku complex of British Guiana, (7) 166*e*.
X-ray emission microanalysis, (10) 272*e*.
pyro-, stability with respect to pressure, temperature and composition, (10) 272*d*.
$ZnSiO_3$, synthesis, IV: phase transition under high pressure, (1) 26*a*.

Quality control, of glaze frits by flow behavior, (3) 74*g*.
in refractories works by ultrasonic methods—possibilities, methods and aims, (2) 42*a*.
inspecting device, photoelectric glassware, P (2) 39*i*.
Quartz. See also *Glass; Refractories; Silicon, dioxide*.
acoustic wave attenuation, new measurements, (8) 191*d*.
α-, linear compression to 150 kbar, (7) 165*d*.
numerical data for acoustic surface waves in, (8) 203*h*.
-bauxite mixes, mullite refractories from, (2) 42*b*.
colored, synthesis, (4) 111*c*.
crystals, in devitrified soda-lime-magnesia glass, (2) 37*c*.
dislocation etch tunnels, (8) 194*j*.
microbalance, for measuring vapor backstreaming from mechanical pumps, (9) 234*f*.
pegmatitic, method for growth in controlled axial direction, P (3) 78*h*.
Quartz, crystals (*continued*)
thermocompression wire attachments to, P (4) 102*j*.
treating for optical uses, P (9) 222*e*.
wafer blanks, automatic +X-axis detector, marker, sorter, and collector for, P (8) 184*a*.
crystalline, infrared lattice vibration spectra, (11) 297*g*.
and fused, Brillouin scattering spectra, (9) 217*g*.
crystallization, review, (11) 298*c*.
effect on mechanical strength of electrotechnical porcelain, (10) 261*f*.
electrolytic treatment of, P (11) 285*h*.
elements, piezoelectric, P (10) 265*e*.
fillers, with different grain sizes, for electric fuse, P (3) 77*j*.
grind, proper grinding fluid, (7) 145*f*.
growth, hydrothermal: I, experimental methods, (5) 136*f*; II, growth morphology, (5) 136*g*.
light diffusing coatings on, P (4) 94*j*.
microstructure, (7) 150*j*.
natural, defects, (1) 17*b*.
for enameling, (9) 216*d*.
phenomenon of endotaxy in, (10) 271*a*.
and quartz-mineralizer mixtures, effect of fine grinding on inversion behavior during firing, (8) 195*h*.
reactions during firing, infrared study, (9) 224*e*.
sand, method of treating, P (2) 54*e*.
shock-loaded, effect of ionized impurities on current from, (5) 135*h*.
single crystal, filter elements, transducers, and delay lines, P (7) 158*d*.
spheres, in sodium silicate melt, dissolution kinetics, (11) 276*h*.
structure, role of impurities, (8) 206*c*.
sulfonate flotation, lead activation in, (4) 106*a*.
synthetic, with mechanical Q equivalent to that of natural quartz, (5) 139*b*.
systems. See *Systems*.
transformations, nature of $\alpha \rightleftharpoons \beta$, (8) 203*a*.
Quartzite, from Okinawa, for ceramic use, (5) 132*j*.
for superduty silica brick, (2) 41*b*.
Quenching, sink-terminated concentration of Gd^{3+} fluorescence in calibo-1 glass, (8) 175*h*.
Quicklime. See *Lime*.

Radiation, crystallization induced by, (8) 206*a*.
damage, on $BaTiO_3$ single crystals, (3) 87*h*.
effects, control in graphite reactor structure, (3) 70*h*.
gamma, for clinker control in cement industry, (11) 274*i*.
high-energy, effects on inorganic substances, B (9) 244*j*.
-induced creep in graphite, (2) 55*g*.
influence on reactivity and catalytic activity of solids, (8) 200*d*.
infrared, from bulk GaAs, (8) 200*g*.
and microwave, associated with current-controlled instability in GaAs, (11) 297*g*.
of refractories, (2) 41*c*.
of titanium boronitride, (1) 20*a*.
10.6 μ laser, modulation by ultrasonic diffraction, (10) 271*e*.
nuclear, effect on behavior of electronic components, (11) 284*e*.
effect on properties of high-melting compounds, (8) 195*f*.
shielding window, P (2) 39*h*.
room temperature super-radiance, in *n*-type GaAs by continuous electron-beam excitation, (5) 138*c*.
shielding materials: I, boron litharge glycerine cement, (2) 34*h*; III, boron-litharge cement, (7) 146*j*.
shielding properties of glasses in system Li_2O-PbO-B_2O_3, (2) 37*f*.
solar, apparatus to simulate, P (10) 265*e*.
source, P (10) 260*c*.
stability of nonmetallic structures, (3) 87*i*.
ultraviolet, causes stress in glass, (5) 119*d*; (7) 148*e,h*.
Radioactive materials. See also *Isotopes*.
fusion in glass bodies, P (9) 222*b*.
krypton, inclusion in aluminum oxides during thermal surface changes, (2) 55*d*.
labeling, improvements in processes, P (2) 44*h*.
of low surface area, P (5) 128*j*.
safe handling, (4) 112*i*.
wastes, high level, phosphate glass process for disposal, (10) 253*a*.
Radioactive tracers. See also *Isotopes*.
studies on incorporation of phosphorus in epitaxially grown silicon, (7) 167*d*.
Radiochemistry, of chloride-ion contamination in surface properties of precipitated alumina, (2) 57*a*.
Radiography, γ-, GAMMAMAT type apparatus, for materials testing, (2) 51*a*.
X-, of refractories, (2) 41*c*.
X-ray, developing suitable techniques for thin rock slabs, (8) 187*i*.
Radioisotopes. See *Isotopes*.
Rare earths (lanthanons). See also specific types.
compounds and alloys, selected, electric properties, (3) 85*c*.
elements, formation and properties of solid solutions with zirconia, (5) 123*a*.
type C, systems formed by lime with oxides of, (2) 57*a*.
fluorescent, method of preparing, P (3) 83*f*.
in glass, determination by X-ray fluorescence, (10) 251*h*.
ions, electroluminescence in cadmium fluoride, (5) 135*f*.

Rare earths (lanthanons), ions *(continued)*
in garnets, intensity variation of paramagnetic resonance lines, (5) 136*h*.
metals, atomic absorption studies on, (8) 191*j*.
orthoarsenates, crystal growth, (9) 237*f*.
orthovanadate fluorescent materials, P (7) 157*j*.
oxide, nonstoichiometric, preparation of new type, (8) 205*g*.
oxide-copper oxide catalyst compositions, alumina supported, P (2) 43*c*.
oxide hydroxides, hydrothermal preparation, (11) 291*c*.
oxides, recent findings, (9) 235*c*.
selenides, solid solutions formed by addition to MSe selenides of face-centered cubic NaCl type, (1) 28*i*.
silicates and aluminates, preparation and properties, (10) 271*d*.
trihydroxides, hydrothermal preparation, (11) 297*e*.
of type $A(III)_2BO_3$, ternary oxides of, (11) 302*d*.
values, separating from strontium values, P (2) 54*d*.
Raw materials. See also *Sands; Rocks.*
aluminous siliceous material fillers, for asphalt road surfacing material, production, P (7) 151*a*.
argillaceous, methods of homogenizing liquid suspensions, P (2) 54*f*.
cement, apparatus for heating, P (4) 91*d*.
apparatus for preheating, P (4) 91*d*.
determination of free silica, (4) 90*h*.
improvement by hydrocyclone, (7) 146*d*.
ceramic, review, (3) 82*e*.
homogeneous, installation for sampling, P (5) 130*g*.
increasing quality, (7) 158*e*.
metasomatic albite-granitoid, in Ograzden Mts. (Jugoslavia), (3) 82*j*.
plastic, evaluation for ceramic processes, (8) 186*g*.
process for treating to eliminate iron salts, P (3) 83*c*.
refractory, prospects for developing in Angren deposit (Russian), (5) 133*e*.
winning, (2) 53*g*.
semiacid, for production of shapes by semidry pressing, (5) 123*g*.
Reactivity, chemical, of uranium trioxide: II, UO_3 hydrates, (5) 134*d*.
reaction of solids with liquids, process and apparatus, P (2) 45*b*.
Reactors, analogous chemical, improvements, P (7) 160*c*.
burner, apparatus, P (4) 105*i*.
catalytic, refractory linings for, P (4) 99*f*.
neutronic, control, method of preparing oxides for, P (4) 98*g*.
nuclear, breeder, core element for, P (9) 225*d*.
ceramic fuels for, (4) 96*g*.
coated fuel particle, of UO_2, method of making, P (3) 72*e*.
coated particle fuels for, P (7) 153*d*.
core graphite, ablation in oxygen and air, (7) 151*b*.
cores, P (4) 98*h*.
fuel elements, P (1) 7*f*; P (1) 8*h*.
fuel element containing mechanically compressible mandrel, P (2) 44*b*.
fuel material and method of making, P (2) 44*g*.
fuel material, process and apparatus for manufacture, P (2) 44*c*.
fuel production, P (2) 44*h*.
with improved moderator material, P (11) 282*b*.
production of fuel for, P (9) 227*g*.
substantially isotropic graphitized bodies in, P (9) 227*g*.
thermal simulation of ThO_2-UO_2 microstructures, (10) 259*b*.
Reagents. See specific types.
Recrystallization. See *Crystallization.*
Rectifiers, controlled, containing electropositive protective coating, P (8) 185*d*.
controlled, having shunted emitter formed by nickel layer under aluminum layer, P (4) 100*j*.
silicon, device, P (10) 265*d*.
Recuperators. See *Furnaces; Kilns; Refractories.*
Reduction, gaseous, topochemical, of porous hematite spheres, generalized model, (9) 239*i*.
silica, rate, in reducing gases at 1500°C, (7) 167*e*.
of tungsten oxides by hydrogen, (1) 27*g*.
of wustite within wustite phase in H_2-H_2O mixtures, (1) 27*i*.
Reflectance. See *Reflection.*
Reflection, diffuse, and emission, of certain sintered white oxides, (1) 17*h*.
far infrared, of $TaBiO_3$, (3) 85*i*.
optical, for determination of composition and homogeneity of epitaxial Ga(As,P) alloys, (3) 80*h*.
spectra, of UO_2 prepared from U_3O_8 calcined under various conditions, (8) 206*b*.
Reflectometer, for dielectric constant measurements, (1) 13*j*.
Reflectors, with mercury amalgamative material on electrode stems, for high temperature fluorescent lamp, P (2) 47*j*.
Reflectivity. See *Reflection.*
Refraction, birefringence, magnetoacoustic, in magnetite and nickel, (5) 137*b*.
birefringence, surface, method and apparatus for determining in transparent material, P (2) 39*c*.
birefringence pattern, of antiferromagnetic NiO crystal, (5) 131*j*.
molar, for examining coordination of aluminum ions in tricalcium aluminate, (3) 64*b*.
Refractive index, changes in sodium borate glasses subjected to high pressure, (10) 252*h*.
Refractive index *(continued)*
of glass, process for increasing and article made, P (9) 222*f*.
of glass surfaces, method for lowering, P (8) 178*a*.
of glasses under high pressure, change in, (2) 36*d*.
of oxide films on anodized zirconium, determination from transmission interference measurements, (11) 293*a*.
precision measurements, precautions, (9) 234*b*.
of thin transparent films on silicon, measurement by index of refraction liquids, (3) 81*i*.
Refractivity. See *Refraction.*
Refractories. See also *Aircraft ceramics; Insulation, thermal; Kiln furniture; Silicon, carbide.*
P (3) 73*b*.
abradability, determination with vibromill, (5) 122*i*.
abrasion resistant, P (2) 43*b*.
abrasion test for, (10) 256*h*.
alumina, all-rammed for electric arc furnace roof, results of service tests, (11) 281*b*.
-bonded, (7) 151*b*.
high, electrical resistivity, (8) 179*j*.
high, for improved service life in ferruginous environments, P (8) 180*e*.
high, phosphate bonded, P (2) 41*e*.
lightweight, insulating, (4) 96*e*.
with phosphoric acid, (8) 182*c*.
aluminosilicate, P (1) 7*a*.
deterioration by fly ash and slag of power stations, (3) 70*i*.
glass content determination, (3) 71*h*.
monolithic, in iron and steel manufacture, (9) 223*f*.
relation between refractoriness under load and alumina content bound as mullite, (1) 7*h*.
aluminum nitride, method of sintering, P (2) 44*c*.
AlN-Al sintering in nitrogen, (7) 152*i*.
alundum, volatilization of Na_2O from, (1) 7*j*.
arch, P (11) 283*c*.
article, gastight, and method of making, P (2) 44*d*.
asbestos-phosphoric acid type, P (9) 225*j*.
baddeleyite-corundum, with optimum glass resistance, composition and structure, (3) 70*j*.
bakor, service in tank furnace at Gomel'sk Glass Factory, (4) 97*j*.
basic. See also *Refractories, chrome-magnesite;* specific kinds.
P (1) 8*c*; P (1) 8*d*; P (2) 43*e*; P (2) 45*a*; P (7) 152*j*.
diffusion of open hearth slags in, (7) 151*h*.
composition and method of preparation, P (1) 8*e*.
compositions, P (5) 124*c*.
compositions for intermediate temperature zones, P (2) 43*e*.
dead-burned, production in shaft kiln, P (1) 8*a*.
destruction in electric furnaces, (4) 96*h*.
fired dolomite, tested in LD converter, (11) 280*f*.
fired dolomite-magnesite, for charge side lining of LD converter and life of converter body, (11) 280*i*.
for furnace lining, P (1) 8*f*.
for glass tank, (10) 156*i*.
high-fired, behavior in sprung arches, (7) 151*d*.
improved, process for manufacturing, P (1) 8*i*.
magnesia-chrome, P (4) 98*c*.
method of manufacturing, P (7) 153*b*.
pitch bonded, P (9) 227*e*.
physicochemical factors, effect on lining life in oxygen converters, (9) 224*a*.
process for production, P (8) 182*b*.
in rotary kiln, P (4) 98*c*.
slagging resistance under load, (2) 43*c*.
tar-impregnated, P (7) 152*j*.
basic brick, direct bonded, production of, P (4) 99*c*.
in electric arc steelmaking furnace, results of comparative service test, (11) 281*a*.
high-temperature burned, slag basicity contributing to erosion of, (11) 280*f*.
linear change under cycled temperatures, (7) 151*h*.
or natural, containing carbon, and process for production, P (9) 225*b*.
and process of making, P (10) 259*d*.
wear processes in roofs of open-hearth furnaces, (4) 98*a*.
in basic oxygen steelmaking vessels, P (4) 98*b*.
for basic oxygen vessels, (2) 42*e*.
bauxite, role of titania, (9) 224*d*.
binder, comprising organic silicates, P (10) 260*d*.
for moldable compositions, P (9) 225*f*.
binding agent, phosphate, and manufacture, (10) 259*d*.
binding material and molds, P (2) 45*a*.
blast-furnace, linings. See *Refractories, linings.*
blocks, composite, P (1) 7*e*.
for furnace roofs, P (1) 8*f*.
large, manufacture, P (8) 181*g*.
plural tapered, and tightly fitting metal case for, P (11) 282*c*.
bodies, process for producing, P (10) 260*a*.
reinforced, P (1) 8*g*.
body, and method of making, P (3) 73*c*.
bond compositions of olivine, H_2SO_4 and H_2O, P (8) 182*c*.
boride-carbide compositions and method of making, P (10) 259*f*.
borides, hard metal, process for production, P (9) 226*d*.
brick. See also *basic* and specific types under *Refractories.*
P (5) 125*e*; P (7) 154*e*; P (10) 260*f*.
application of nondestructive testing, (2) 40*i*.
Refractories, brick *(continued)*
apparatus and method for manufacturing, P (7) 152*i*.
cased, and manufacture, P (11) 283*a*.
containing chromium oxide for glass melting vats, P (1) 5*f*.
8-radial hole center, trial manufacture and use, (9) 225*c*.
encasing method, P (8) 181*i*.
flue, for ceramic recuperators, and recuperators, P (11) 283*d*.
manufacture, P (1) 8*e*; P (8) 182*b*.
metal cladding, method and apparatus, P (8) 181*i*.
metal encased, P (8) 181*g*.
metal encased, and method of making, P (2) 44*j*.
with metal plate bonded by chloroprene-phenolic adhesive, P (10) 260*f*.
with one or more plates, P (11) 283*a*.
periclase-spinel, testing in open-hearth roofs, (5) 123*i*.
preferably basic, for industrial furnaces, P (10) 260*f*.
process for making, P (2) 45*d*.
process for manufacture, P (5) 125*a,b*.
spalling-resistant, P (4) 99*b*.
suspended, P (1) 8*g*; P (11) 283*b*.
unit, P (4) 99*f*; P (5) 125*a*.
units with hangers, P (2) 45*c*.
universal plating machine, P (3) 73*c*.
use of Schmidt concrete testing hammer for evaluation, (2) 43*g*.
wall, with comolded hanger assembly, P (9) 227*c*.
briquet, for material handling, P (4) 98*c*.
briquets, very strong, process for production, P (10) 250*b*.
burner block, P (8) 180*f*.
calcium oxide, properties, (4) 97*h*.
calcium silicate, composition, P (11) 281*c*.
carbides, sintered, P (9) 227*f*.
carbon, in bottom and well of blast furnace, mechanism of destruction, (9) 224*g*.
-bearing, P (5) 124*c*.
bodies, P (9) 225*b*.
bodies, shaped, manufacture, P (9) 226*b*.
comparative studies on high temperature coke oven coal tar pitch as binder in manufacture of, (2) 41*g*.
-graphitic materials, highly dispersed, process for obtaining, (10) 251*j*.
casing and lining, secured by anchorage assembly, P (11) 281*e*.
castable, aluminosilicate in iron and steel industry, (9) 223*f*.
casting pit, effect of casting conditions on slag corrosion of siliceous fireclay brick, (9) 224*j*.
casting process and device, P (10) 260*e*.
catalyst carrier, and method of preparation, P (5) 125*a*.
cement, barium aluminate, refractory products chemically bonded with, (5) 123*j*.
castable, P (8) 180*f*.
with high clay content, process for making and products obtained, P (11) 282*e*.
ceramic, P (2) 43*h*.
bodies, P (2) 43*h*.
chamotte-bentonite bodies, as filters for purifying Ni solutions, (3) 65*c*.
chamotte-graphite lances, use in bottoms of Bessemer converters, (9) 225*g*.
chamotte, ground, study of classification in air stream, (9) 224*i*.
chemical durability, (11) 280*i*.
chimney, for cooling hot gases, P (4) 105*c*.
chrome-alumina concretes and shapes, (9) 223*i*.
chrome-containing, in glass industry for use in regenerator or melting tank, (9) 223*j*.
chrome-magnesite. See also *Refractories, magnesite-chromite.*
determination of aluminum oxide, (3) 70*j*.
brick, effect of firing temperature, (4) 96*j*.
chemically bonded with barium aluminate refractory cement, (5) 123*j*.
determination of thermal shock resistance by nondestructive testing, (1) 41*a*.
fired, P (8) 181*b*.
chrome ore and magnesia, P (9) 227*a*.
chrome ore, plastic, P (4) 98*h*.
chrome spinel grains in slag zone of electric arc furnaces, nature of destruction, (9) 224*g*.
chrome spinel-magnesia, bond in, (8) 180*c*.
chromite and magnesia with additives, P (7) 154*c*.
chromium-bearing, bursting phenomena, (7) 151*d*.
clays. See *Clays.*
coated chimney, P (1) 7*d*.
coatings. See *Coatings.*
commercial, stability in vacuum, (8) 180*c*.
composition, P (10) 260*g*.
and bodies and methods of making, P (9) 227*b*.
and body, with chromite spinel and periclase, P (9) 227*d*.
comprising iron-group metal and particulate refractory metal oxide, P (8) 180*h*.
exothermic, P (7) 154*e*.
inert to Al, P (3) 73*d*.
and method of making body, P (10) 260*e*.
and process for manufacture, P (9) 225*f*.
and products, P (10) 260*h*.
compounds, manufacture, P (10) 259*c*.
mass spectrometry for investigation, (8) 211*a*.
thermodynamics: Vol. 1, theoretical studies; Vol. 2, thermodynamic tables, bibliography and property file, B (5) 142*h*.
concrete. See *Concrete.*
consolidated heat-treated, manufacture, P (10) 259*e*.

Refractories (*continued*)
converters, apparatus for lining, P (4) 105*g*.
corrosion by molten silicate glass as the solid dissolution process, (1) 7*a*.
corrosion-resistant, method for making, P (3) 72*h*.
corundum, chemically bonded with barium aluminate refractory cement, (5) 123*j*.
porosity and structure, effect on thermal conductivity, (9) 224*a*.
crucible reactor and method, P (10) 259*g*.
crucibles, P (4) 98*e*.
for barium titanate melts, (9) 223*h*.
or converters, P (3) 72*g*.
density determination by gamma-radiation absorption measurement, (9) 223*g*.
Dinas, for glass furnaces, (4) 95*h*.
bodies, mixing in centrifugal runner mill model 115, (5) 123*e*.
dolomite, stabilized, manufacture, P (8) 181*g*.
unfired, with high hydration resistance, (5) 123*j*.
elastic moduli of, practical determination, (2) 42*h*.
in electric furnace, laboratory study and tests, (9) 224*f*.
electric welding of, (3) 71*a*.
electrocast. See *Refractories, fused cast*.
electrocast magnesite-chrome and corundum-zirconia, applications, (2) 40*j*.
expansion behavior after different high prefirings, (10) 257*h*.
with expansion means attached, P (9) 227*e*.
fabrics, evaluation for flexible heat shields, (3) 71*c*.
fibers, and methods of making, P (7) 154*e*.
firebrick, insulating, P (7) 153*e*.
observations after long service, (9) 224*h*.
fireclay, assessment of phase composition based on ternary phase diagrams, (2) 41*a*.
new method of increasing spalling resistance, (4) 97*i*.
studies, (2) 43*d*.
torsional studies, (3) 71*i*.
fireclay brick, graphite containing, forming ladle bottom, service test, (9) 224*g*.
siliceous, effect of casting conditions on slag corrosion, (9) 224*j*.
used hot blast stove, investigations, (10) 257*d*.
fireclay runner brick and SiC-containing (20%) runner brick, comparative study when used for making killed steel, (9) 223*g*.
for firing of barium titanate ceramics, (2) 47*b*.
foamed, P (10) 259*i*.
sintered product for use in, P (10) 260*j*.
forsterite, studies on production: I, study of process variables, (2) 42*e*.
forsterite shapes, effect of industrial factors on compaction, (7) 151*j*.
foundry sand composition and method of making, P (8) 181*d*.
furnace baffle, P (2) 52*h*.
fused cast, P (3) 73*e*; P (11) 281*f*.
alumina, microscopic examination, (4) 97*h*.
alumina, petrology of reactions with metals and slags, (2) 42*c*.
containing mineral oxides, improvements in manufacture, P (5) 124*a*.
improvement in molds, (5) 123*d*.
wear resistant, with beveled edge, P (3) 73*e*.
fused rock, mechanical strength at high temperatures, (5) 123*e*.
fused silica—newest in material developments, (1) 7*d*.
glass contacting, P (9) 225*h*.
in glass furnaces, research for better use, (5) 123*c*.
grain, improvements in radioactive labeling processes, P (2) 44*h*.
granular, bulk density determined by arrested absorption, (8) 179*j*.
cooling method, P (10) 261*a*.
graphitized bodies, substantially isotropic, in nuclear reactors, P (9) 227*g*.
grogless, from nonlean clays and kaolins, (4) 97*a*.
gunning, of basic oxygen furnaces, (2) 42*h*.
formulations, P (10) 259*i*.
mixes, with phosphate bonds, (4) 97*b*.
for metallurgical furnace, method and product, P (10) 259*g*.
hard compounds, tools of future, (2) 33*i*.
in hard-porcelain kiln, aging processes, (7) 151*g*.
high-porosity, production, P (7) 153*j*.
for high output burners in steam boilers, (5) 123*j*.
hot pressed boride-nitride, P (3) 73*c*.
hot pressing method, P (11) 282*a*.
hot top, P (4) 98*a*.
bottom ring-wiper strip assembly, and method of making, P (10) 259*e*.
composition, P (4) 98*b*.
exothermic insert, P (1) 7*e*.
hot topping, method using vermicular graphite, P (7) 153*j*.
for industrial furnaces, process for making, P (2) 45*c*.
insulating. See also *Refractories, firebrick*.
brick, P (8) 181*e*.
brick, and production, P (8) 181*c*.
CerCom, for space crafts, (9) 223*i*.
heat-, fireproof materials, P (10) 259*h*.
investigation in steel plant service, (8) 180*b*.
lightweight castable, P (11) 281*k*.
materials, P (4) 99*g*.
materials, characteristics, (2) 41*c*.
process for making, P (3) 72*j*.
product, P (11) 283*a*.
slabs, manufacture, P (7) 153*g*.
insulation, unfired-ceramic flame-resistant, for rocket launching pad, P (4) 99*d*.
kaolin-quartz-talc-Fe_2O_3 bodies, behavior of Fe_2O_3 on heating in, (8) 191*d*.

Refractories (*continued*)
for kiln furniture. See *Kiln furniture*.
korvishit, service in tank furnace at Gomel'sk Glass Factory, (4) 97*j*.
ladle brick, containing 20 to 40% zircon, results of using, (9) 224*c*.
increasing life, (7) 151*c*.
manufacture in Soviet plants, (4) 95*h*.
relation between properties and decline in consumption, statistical observation, (9) 224*i*.
roseki, reinforcement by adding Cr_2O_3 to matrix, (9) 224*b*.
unfired roseki, properties and durability, (9) 224*j*.
ladle lining, concrete, of teapot type, (7) 151*e*.
ladle nozzle brick, containing zircon, results of tests, (9) 224*c*.
ladles, casting, stopper refractories in, (5) 123*e*.
intermediate, for continuous steel casting plant, (5) 123*f*.
tundish, P (10) 261*a*.
valve arrangement with stationary plug and slidable nozzle, P (7) 153*g*.
layered, and method for making, P (3) 73*a*.
lightweight, manufacture by foam process, (7) 152*c*.
method of manufacturing, P (9) 226*h*.
process for making, and resultant products, P (3) 72*j*.
lined vessels, P (5) 125*b*.
liners for flue, P (1) 7*e*.
lining furnaces and like vessels, method and apparatus, P (8) 181*b*.
linings, alumina monolith, P (2) 45*d*.
for alumina reduction cell, method of making, P (9) 225*j*.
of basic oxygen LD furnaces, controlling the wear processes, (7) 151*j*.
blast furnace, effects of burden constituents, investigation, (10) 257*b*.
of blast furnaces, properties, type of construction and life, (7) 152*d*.
for blast furnace shafts, P (10) 259*b*.
for catalytic reactors, P (4) 99*f*.
ceramic and tar bonded brick, P (11) 281*j*.
for chambers for degasifying metals, P (2) 45*d*.
friction, and processes for production, P (5) 124*g*.
furnace, P (10) 260*h*.
furnace, method for improving durability, P (8) 181*b*.
of kiln cars, service of forsterite lightweights, (9) 224*f*.
monolith, method of *in situ* fabrication, P (3) 72*j*.
monolithic, for metal furnaces, and their application, P (3) 73*e*.
oxygen converter, P (3) 72*b*.
selection, (10) 257*f*.
silica, corrosion resistance chlorinator, P (10) 259*f*.
of steel melting arc furnaces, life, (9) 224*f*.
for walls exposed to high temperatures, especially slags and molten metals, P (10) 259*j*.
magnesia, alumina titanate bonded, P (8) 180*d*.
-B_2O_3, fused cast, P (11) 282*i*.
bodies, green, strengthening, and firing without predrying, (5) 123*f*.
casting, P (10) 259*b*.
chemically bonded with barium aluminate refractory cement, (5) 123*j*.
coarse crystal material, P (9) 225*c*.
electrical resistivity, (8) 179*f*.
as heat exchange media, (8) 179*j*.
mechanism of creep, (10) 257*j*.
phosphate bonding, (1) 7*f*.
and process for making, P (2) 45*b*; P (10) 260*f*.
reducing deterioration from molten metal, P (2) 45*f*.
sintering, and effect of various factors on contraction rates, (7) 152*b*.
tar-saturated, (11) 281*f*.
technological properties: I, sintering of magnesia brick; II, effect of load on refractoriness of magnesia brick, (7) 152*b*, *c*.
unfired, process for making, P (3) 72*h*.
-zircon, P (5) 124*c*.
magnesia-chrome, casting, P (11) 283*b*.
electrical resistivity, (8) 179*j*.
grain-boundary reactions in, —application of the electron probe: II, (1) 7*e*.
manufacture, P (2) 44*i*.
ore, in basic refractory brick, P (4) 98*b*.
ore brick, degree of direct bonding, P (9) 225*d*.
magnesiochromite, reaction with calcium oxide, (5) 123*i*.
magnesite. See also *Refractories, chrome-magnesite*.
with high CaO content, (7) 151*h*.
as lining in degasification of metals, P (9) 225*j*.
Mg-Cr brick, fused cast, in backwalls of open hearth furnace, results of test, (11) 281*d*.
Mg-Cr brick, fused cast, for open-hearth furnace roofs, results of service tests, (11) 281*c*.
sintered, studies, (3) 70*h*.
magnesite brick, silicate constitution, effect on high-temperature strength, (9) 224*b*.
zonal change in properties after service in open-hearth furnace roof, (9) 225*i*.
magnesite-chrome, chemically bonded, relation of temperature and mechanical behavior, (3) 71*e*.
pyroxene formation in glass furnace regenerator walls, (10) 258*c*.
magnesite-chromite, dense, production, (7) 152*d*.
finely milled for roof brick, (5) 123*b*.
testing in open hearth roofs, (5) 123*i*.
magnesite-dolomite brick, stabilized, in converter linings, (9) 224*h*.
material handling, P (4) 98*c*.

Refractories (*continued*)
materials, P (4) 98*j*; P (8) 182*d*.
clay and analogous, processes and apparatus for granulating and drying, P (11) 288*j*.
consisting of two ceramic materials, manufacture, P (11) 282*a*.
dustable, P (10) 259*h*.
experimental apparatus for investigating physicomechanical and heat resistance properties of, (4) 96*g*.
formed by liquid phase extrusion, P (8) 181*f*.
granular, with bituminous binder, P (7) 154*a*.
of high refractoriness and good thermal shock resistance, process for making, P (10) 260*g*.
hydraulic press for, choice of capacity of pump equipment, (5) 122*i*.
joining surfaces with MnO-SiO_2-Al_2O_3 compound, P (8) 181*j*.
mercury porosimetry application to, (8) 179*h*.
method for forming refractory metal or carbide coating on, P (5) 117*i*.
nondestructive determination of mechanical properties, (7) 159*j*.
present and future aspects, (7) 152*k*.
process for manufacture, P (5) 125*a*; P (8) 182*c*.
protection, P (10) 260*c*.
pulverization by vibrating ball mill, (11) 280*j*.
recent developments, (9) 225*a*.
reinforced, P (1) 8*g*.
strength, effect of aluminum fluoride additives, (5) 122*d*.
for thermocouple protection in metallurgica industries, (10) 258*e*.
for use above 3000°F, (10) 257*i*.
melt reactions in vacuum induction melting of nickel-base alloys, (8) 180*i*.
metal, chlorides, method for producing from Zr and/or Hf oxides, P (3) 72*f*.
compounds, P (4) 99*g*.
encased, P (9) 226*c*.
interactions, thermochemistry, (7) 152*f*.
structures, method of making with oxidation resistant coating, P (4) 92*b*.
metallurgic composition, products, and method of obtaining, P (2) 45*d*.
metals, atomic absorption studies on, (8) 191*j*.
use of molten pyridinium chloride in treatment, (5) 124*a*.
for MHD generators, (2) 46*i*.
mold coating, liquidless foundry, P (5) 124*b*.
molded bodies, method for making, P (2) 44*c*.
molds. See also *Molds*.
multicomponent moisture-absorbent, method of making, P (3) 72*h*.
and refractory binding material, P (2) 45*a*.
monocrystalline high melting, materials and equipment, production, P (3) 73*a*.
monolithic, gunning, (9) 224*e*.
mortar, P (8) 182*d*; P (9) 227*f*.
mortar composition, P (2) 45*f*.
mullite, from clay-bauxite or quartz-bauxite mixes, (2) 42*b*.
new, principles in search for, (7) 152*d*.
nondestructive testing, (2) 41*c*.
nozzle, consumable, for electroslag welding, P (9) 225*c*.
construction with thermally expanding refractory insert, P (11) 282*j*.
pouring pit, (10) 258*h*.
for teeming of molten metal, P (4) 99*a*.
zircon, for continuous steel casting, (4) 97*f*.
nozzle brick, trial manufacture and use test, (9) 225*f*.
open-hearth roof brick, evaluation, (8) 179*j*.
oxides, effect on thermal emf of tungsten, molybdenum, and tantalum in vacuum at 1500°C, (7) 151*i*.
highly, activated sintering in solid phase, crystal-chemical relations in, (5) 138*g*.
method of sphering, P (1) 8*f*.
pigment via plasma jet-improved preheater configuration, P (9) 226*e*.
preparation of oxynitrides from, (1) 27*c*.
solidification temperatures, measurement, (7) 151*i*.
in oxygen converters, service conditions and nature of wear, (5) 123*b*.
particles, hollow, process for preparing, P (4) 99*a*.
pellets, high density uranium carbide-plutonium carbide, process for producing, P (11) 282*g*.
periclase, high-purity, developments, (3) 71*f*.
pitch-bonded, method of making, P (2) 45*e*.
plastic, P (5) 124*f*.
alumina-clay compositions, P (2) 44*j*.
application and results in soaking pits, (7) 151*c*.
plug-stoppers, heat resistant, P (8) 181*e*.
for pneumatic steelmaking vessels, problems with supplying, (11) 281*e*.
porous-, encapsulant for coils and coil encapsulated therewith, P (5) 124*g*.
products, method of making, P (9) 226*f*.
pouring tube for pressure pouring apparatus, P (10) 260*d*.
pressure casting, (1) 7*g*.
for producing zinc white, (9) 224*j*.
production, P (2) 45*k*.
products, P (3) 73*b*.
especially for nuclear fuels, P (2) 45*g*.
of high zirconia content, P (5) 125*c*.
for 3000°F plus, (5) 123*i*.
for protection of thermocouples from molten aluminum and zinc, (9) 224*j*.
pyrocarbon matrix, process for fabrication, P (7) 153*g*.
quality, (5) 123*j*.
ramming bodies, for high output burners in steam boilers, (5) 123*j*.

Refractories (*continued*)
ramming and fettling specimens from hearths of basic open-hearth furnaces, determining melting point, (9) 223*j*.
ramming mix, carbonaceous, P (5) 124*d*.
ramming mixes, in iron and steel industry, (7) 152*h*.
raw materials. See *Raw materials*.
reactions, hydrogen-silica, (8) 179*j*.
recuperators, refractory flue brick for, P (11) 283*d*.
refinery use, (5) 123*i*.
refractoriness under load, of magnesia brick, effect of load and change in microstructure, (7)152*c*.
of zones in used silica crown brick, (10) 258*d*.
regenerators, ceramic, traction drive for, P (4) 99*c*.
research, current, and applications, (11) 280*e*.
and current use, (7) 152*f*.
resistance, to carbon monoxide attack, control, (7) 151*f*.
roofs, bonded basic, development for open-hearth furnaces, (7) 151*h*.
and method, P (11) 283*a*.
open hearth furnace, P (9) 235*a*.
roseki brick, highly siliceous, vitrification, (9) 225*d*.
runner brick: II, firing temperature and characteristics, (9) 224*f*.
selection, (5) 123*b*.
basic principles, (4) 96*f*.
service, during high-temperature melting of glass, (3) 71*h*.
service testing, (11) 281*g*.
shapes, containing oxidized Al, P (4) 99*a*.
with embedded channel shape reinforcement, P (2) 45*g*.
and process of making, P (7) 154*b*.
production from semiacid raw materials by semidry pressing, (5) 123*g*.
silica, refractoriness under load, (10) 258*d*.
silica brick, P (10) 260*i*.
determination of thermal softening behavior, (3) 71*c*.
in superstructure of glass melting furnaces, corrosion by sodium salts vapor, (5) 123*c*, *d*.
silicon carbide, applications for, (4) 96*e*.
bonded with silicon nitride, phase composition, (4) 97*j*.
brick, investigation, (1) 7*f*.
elements, improving by metal impregnation, (1) 7*e*.
Mo infiltrated, P (4) 93*j*.
silicon nitride, corrosion by molten iron, (11) 280*j*.
production, P (5) 125*d*.
silicon oxynitride, (8) 180*b*.
sintered bodies, of molybdenum silicide, P (5) 125*d*.
sintered material, P (10) 260*i*.
sinters, highly hydration stable, of dolomite, magnesite, lime, P (1) 7*g*.
slag. See *Slags*.
slag resistance, (4) 97*g*.
slagging resistance of basic refractories under load, (2) 43*c*.
spalling resistance, new method of increasing for fireclay refractories, (4) 97*i*.
spalling of restrained, due to transient temperatures, (2) 43*d*.
stability during vacuum deoxidation of steel, (1) 7*j*.
steel casting plugs, use of sonic method for controlling quality, (9) 225*h*.
steel circular-flange inserts, replacing with graphitic articles, (9) 224*c*.
steelworks, recent advances, (7) 152*f*.
stopper, increasing life in large steel casting ladles, (5) 123*e*.
for ladle, P (3) 73*c*.
for ladle or similar receptacle, P (2) 45*h*.
structures, P (7) 154*c*.
particularly interior surfaces of industrial furnaces, process of repairing and materials used, P (11) 282*h*.
support, P (3) 73*b*.
suspended units, P (1) 8*h*.
TaN-TiB_2 compositions, and process of making, P (5) 124*e*.
for tapping spout of electric arc furnace, (11) 281*a*.
tar-bonded, containing pine tar, P (11) 283*d*.
tar-bonded dolomite, P (10) 261*a*.
tar-dolomite, in basic converter, investigations on changes in properties with increasing time in service, (10) 257*c*.
tar-impregnated, manufacture, P (10) 259*d*.
technology, European, B (4) 113*h*.
testing blocks of heat resistant concrete in soaking pit walls, (9) 225*e*.
thermal conductivity and heat transfer, rapid determination of coefficients, (5) 123*h*.
thermal resistance: I, apparatus for investigation at high temperatures, (2) 43*e*.
tile, chemically bonded, and manufacture, P (9) 225*c*.
tuyere, for refractory-lined blast furnace, P (11) 283*e*.
used, study by radioactive isotopes, (9) 234*c*.
wettability determination by carbon steels under hot-stage microscope, (2) 43*j*.
zircon, as nozzles for steel casting, (4) 97*f*.
-containing, melting in three-phase arc furnace, (4) 97*f*.
electrical resistivity, (8) 179*j*.
zirconia, gaseous erosion: I, in stream of combustion products, (5) 123*a*.
high purity, stabilization and sintering, (5) 123*e*.
stabilized, electrical resistivity, (8) 179*j*.

Refractories (*continued*)
zirconium boride, performance as thermocouple tips in Bessemer converter, (10) 253*f*.
Refractories industry, Alsey Refractories makes strong comeback, (9) 223*e*.
apparatus for production of fine-crystalline boron phosphide, P (1) 7*b*.
characteristics of filling devices for presses in, (5) 122*i*.
economics of new techniques, (9) 223*j*.
firing, 1950–64, (11) 279*j*.
in France, (4) 97*f*.
modern plants, operates two tunnel kilns, (4) 97*i*.
in Ohio Valley, (5) 122*i*.
problems, (11) 281*g*.
quality control by ultrasonic methods in Breuillet works, (2) 42*a*.
Shinagawa, products by five processes, (4) 97*d*.
in transition, (2) 42*g*.
Regenerators. See *Refractories*.
Relaxation, nuclear spin, in ruby, (9) 238*j*.
paramagnetic, of chromium ion in ruby and potassium alum, (8) 204*h*.
thermal, of indium films on insulating substrates between 4° and 300°K, (4) 111*g*.
volume, times, effects of distribution of, in annealing of BSC glass, (10) 251*e*.
Replica method. See *Microscopy*.
Research, ceramic, (2) 60*b*.
ceramic, current, (7) 169*h*.
in field of industrial high temperature technology, (2) 60*i*.
and trouble shooting, (4) 112*i*.
concrete, new application of internal friction, (7) 146*i*.
inorganic, in Canada, (11) 303*f*.
materials, advances: Vol. 1, experimental methods, B (8) 211*i*.
on methods of detecting heterogeneity in earthenware bodies after firing, (5) 131*d*.
refractory, current, (11) 280*e*.
Research and research laboratories, National Bureau of Standards, glass section, (8) 175*d*.
Royal Doulton, (11) 283*i*.
Resins, anion exchange, for determination of zinc in ferrite, (5) 135*c*.
in construction of molds for ceramics, (10) 261*g*.
glass-fiber-strengthened thermoplastic synthetic, process for producing, P (8) 178*i*.
polyester, containing kaolin clay coated with neutralized monomeric N,N-diallylmelamine, P (4) 106*c*.
Resistance, electrical. See also *Conductivity, electrical*.
coatings, and manufacture, P (11) 285*e*.
composition, and method of using to form resistor, P (11) 285*f*.
of cubic rare earth, thorium, and uranium tungsten bronzes, (9) 229*g*.
device, thin film negative, P (8) 186*c*.
element, P (5) 127*h*; P (8) 184*a*.
cermet, P (9) 230*g*.
and connections for, P (9) 230*j*.
and material, P (9) 230*h*.
and method of making, P (10) 263*e*.
of evaporated thin films, temperature coefficients, (2) 47*d*.
glass compositions, P (3) 67*b*.
material, made from glass composition, P (1) 10*g*.
measuring, P (2) 48*a*.
measurement, by electron beam, (11) 284*d*.
of molten glass in a tank, means for measuring, P (1) 5*j*.
of pure semiconductor body for electronic purposes, method of determining, P (8) 185*c*.
of sintered bodies in system ZrO_2-CeO_2, (8) 209*j*.
Resistance, skid, of concrete, (4) 90*j*.
pavement surface, expanded aggregates for use in, (4) 90*g*.
Resistivity, electrical, of flame-sprayed Al_2O_3 and ZrO_2 coatings at higher temperatures, (3) 65*c*.
of pyrolytic β-MnO_2, (3) 85*d*.
electrical, of refractories, (8) 179*j*.
wide temperature range four point probe device for measuring, (1) 14*b*.
of zirconia at high temperatures and ultrahigh pressures, (9) 238*j*.
of graphite body, method for determining anisotropy factor of, P (11) 239*i*.
high-, p-type cadmium sulfide, (9) 239*g*.
of oxides, high temperature apparatus for measurement simultaneously with X-ray diffraction analysis, (11) 295*i*.
measurement of magnesia between 1500° and 1800°C and ionization of air in furnace, (1) 20*f*.
of semiconductors, automatic apparatus for measuring, P (7) 153*g*.
Resistors, electrical, P (3) 78*a*.
bolometers, thin film semiconductor, process of preparing, P (7) 157*g*.
ceramic, contacted barrier-free with noble metal, P (8) 184*d*.
cermet film, fabrication to close tolerances, P (7) 156*d*.
with core element of high heat dissipating properties, P (3) 78*a*.
diffused, properties, (5) 126*e*.
film, method of manufacturing, P (10) 264*d*.
forming, with thin, compressed, contact portions, P (5) 127*d*.
glass-sealed, P (5) 127*e*.
method to form from electrical resistance composition, P (11), 285*f*.
method of making, P (2) 48*a*.
humidity-sensitive, P (4) 104*i*.
ohmic, two-terminal pair network damping by, (9) 230*d*.
photo-, P (5) 128*e*.

Resistors, electrical (*continued*)
precision, P (2) 49*b*.
pyrolytic graphite coated, development and evaluation, (3) 75*e*.
semiconductor, containing interstitial and substitutional ions formed by ion implantation method, P (11) 287*f*.
solid composition, of monolithic structure, method of making, P (10) 264*c*.
thermistors, silicon, P (3) 79*f*.
thermometer, apparatus for calibrating, P (8) 184*a*.
thin film, method of forming, P (2) 48*h*; P (2) 48*i*.
welded terminal, P (10) 265*i*.
Resonance, cyclotron, in CdS, (7) 162*a*.
electron nuclear double, of divalent thulium in calcium fluoride, (8) 196*c*.
study of nitrogen center in diamond, (11) 295*b*.
electron paramagnetic, in $BaTiO_3$ near Curie temperature, (7) 163*g*.
measurements of orthorhombic sites of Ce^{3+} and Nd^{3+} in $CaWO_4$, (8) 197*b*.
study of γ-ray irradiated phosphate glasses, (5) 118*i*.
electron spin, for detection of VO^{2+} in glass, (2) 36*h*.
in electron-irradiated n-type silicon carbide, (3) 85*f*.
of Fe^{3+} in $BaTiO_3$ in rhombohedral and cubic phases, (8) 196*c*.
of Gd^{3+}, two sets in $BaTiO_3$ ceramic semiconductor, (8) 211*a*.
of Mn^{2+} in $BaTiO_3$, (8) 195*d*.
of Mn^{2+}, for observation of selective exchange of cation sites in zeolites: I, Linde X, (8) 206*f*.
spectra of hydrogen-bonded HO radicals, (8) 196*e*.
studies of radiation effects in inorganic solids, (3) 85*g*.
electronic paramagnetic, study of thermal decomposition of dibasic calcium orthophosphate, (11) 295*b*.
ferrimagnetic, in copper ferrite cubic-phase single crystal, (11) 295*c*.
in garnet $Y_3Fe_{5-x}Co_{x/2}Ge_{x/2}O_{12}$, (7) 163*e*.
in single crystals of cobalt-substituted nickel ferrite, (11) 295*g*.
in spherically shaped single crystal $BaFe_{12}O_{19}$, (5) 136*d*.
frequency technique, for study of sintering kinetics, (4) 104*e*.
longitudinal radio-frequency, in YIG, (10) 271*b*.
nuclear, double, in ruby, (9) 238*j*.
nuclear magnetic, of ^{53}Cr in ferromagnetic CrO_2, (5) 137*j*.
^{51}V, in V_2O_3, (8) 211*d*.
of ^{59}Co and ^{27}Al in paramagnetic Co_3O_4 and $CoAl_2O_4$, (9) 241*e*.
paramagnetic, of Gd^{3+} in TiO_2 crystal, (7) 166*g*.
lines of rare earth ions in garnets, intensity variation, (5) 136*h*.
proton magnetic, for studying TiV alloy hydrides, (4) 109*a*.
spin, of Co^{2+} in YGaG, (8) 207*b*.
Resonators, ferrite tuned coaxial cavity apparatus, P (2) 47*f*.
thin-film CdS-quartz composite, (11) 284*e*.
Rhenium, Re_2P, crystal structure, (3) 84*b*.
Rheology, of aqueous kaolin suspensions, effect of introducing air bubbles, (7) 154*i*.
clay-water, B (1) 30*a*.
characteristics, of slurries and suspensions, determination, (9) 233*j*.
curves, of thixotropic structural-linked clay suspensions, (1) 8*j*.
of highly concentrated structured, polydisperse systems, by spherical rotary viscometer, (10) 267*j*.
of montmorillonite-water system, effect of $Ca(OH)_2$ on flow properties, (2) 45*j*.
properties, of clay paste under load, (7) 166*g*.
of clay slips, B (1) 30*b*.
of clays with additions of surfactants and electrolyte, (10) 256*g*.
of electroviscous fluids, (7) 163*g*.
of raw cement pastes, (2) 34*i*.
rheological characteristics, of cement pastes and concentrated suspension models, (4) 91*g*.
Rhodesite, splitting into fibers, (11) 298*a*.
Rhodium, silicide, structure and composition, (5) 138*a*.
Rocks. See also *Phosphates; Silicates*.
adamellite-porphyrite from New England bathylith (New South Wales), petrology, (1) 25*b*.
alkaline, petrogenesis, (2) 57*h*.
casting industry, development, (5) 122*j*.
cordierite-anthophyllite, mafic rock alteration and isochemical development, (8) 202*b*.
fine-grained, transmission electron microscopy, (2) 51*a*.
-forming minerals, X-ray emission microanalysis: II, olivines; III, alkali feldspars; IV, plagioclase feldspars, (2) 59*g*–59*h*.
fused. See also *Stone, cast*.
controlled crystallization, (10) 256*j*.
metallurgical, effect of additives on crystallization of melts of, (3) 71*j*.
metamorphic, interpretation of shape of mineral grains, (1) 20*g*.
and igneous, near Iron Mt., Mich., for ages of minerals, (1) 16*d*.
orthopyroxene-bearing, of charnockitic affinities in South Savanna-Kanuku complex of British Guiana, (7) 156*e*.
porous, measurement of electrical resistivity, P (4) 104*i*.
porous permeable, laboratory testing and evaluation for nuclear waste disposal, (10) 257*c*.

Rocks (*continued*)
post-yield mechanics, (8) 205*g*.
serpentinized ultramafic, south of Timmins, Ontario, talc-carbonate alteration, (7) 168*g*.
Rock wool. See *Mineral wool*.
Roughness. See *Surface*.
Rubidium, chloroniobates and chlorotantalates, enthalpy of formation, (7) 163*i*.
determination of trace amounts of, in silicate rocks, by direct current arc spectrographic technique, (2) 50*i*.
fluorides, recovery and separation using alcohols, P (5) 133*f*.
systems. See *Systems*.
wolfram bronzes, thermal expansion, (4) 111*f*.
Ruby. See also *Lasers; Masers*.
cathodoluminescence, (2) 54*f*.
double nuclear resonance and nuclear spin relaxation in, (9) 238*j*.
emissions, (8) 196*f*.
growth, by Czochralski technique, (8) 199*c*.
infrared absorption spectra from excited states in, (9) 239*i*.
laser, Faraday-switched, (8) 183*i*.
optical cooling, possibility, (5) 137*i*.
trigonal crystal field, analysis of experimental data, (4) 110*i*.
vapor-grown, laser properties, (8) 183*c*.
Rupture, modulus, dry, evaluation from response surface, (9) 233*j*.
modulus, relation between compressive strength and, in fired clay products, (2) 40*f*.
Ruthenium, RuBiSe, high pressure synthesis, (7) 164*c*.
silicide, structures and compositions, (5) 138*b*.
Rutile. See also *Titanium, dioxide*.
single crystal, sintering, (11) 300*j*.
sintering, initial, (7) 164*d*.
-type phases, in mixed transition metal dioxides: II, (5) 138*b*.

Safety. See also *Health*.
slip-proofing glazed ceramic surfaces, P (8) 183*b*.
Saggers. See *Kiln furniture*.
Salts, fused, conductivity, direct current measurement: I, molten nitrates, (3) 84*i*; II, KCl-LiCl, (3) 84*j*.
success of free volume model for transport in, (8) 208*d*.
viscosity measurements, (7) 169*d*.
inorganic, high temperature properties and decomposition; I, sulfates, (5) 136*d*.
melts, complex formation in crystallization of, (11) 292*g*.
molten, calorimetric investigations, (8) 192*a*.
complex ions in, (8) 192*e*.
electrochemistry, B (1) 30*j*.
magnetooptical study at high temperatures, (1) 22*c*.
treatment for increasing strength of glass, (9) 218*c*.
polar diamagnetic, additivity relations: II, salts of Mg and Zn and alkali sulfates, (1) 16*e*.
retention in clay products, (2) 40*c*.
sodium, of fatty acids, effect on viscosity of clay suspensions with ultimately broken-down structure, (7) 162*h*.
NaCl. See *Sodium, chloride*.
zeolites and lithium, production, P (7) 161*c*.
Samarium, borides, preparation and interaction with boron nitride, molybdenum, and tungsten, (8) 180*g*.
fluorescence, in cerium dioxide, effect of concentration, (11) 293*g*.
orthotantalates, (1) 24*b*.
systems. See *Systems*.
Sampling, device for semiconsolidated and unconsolidated sediments, (1) 14*d*.
of dust particles, (8) 187*f*.
of free-flowing granular materials, P (9) 234*f*.
homogeneous raw materials, installation for, P (5) 130*g*.
particulate, airborne selection of adhesive-coated materials for, (11) 289*e*.
slide rule, for application of Pierre Gy's rule, (3) 82*h*.
Sandblasting. See *Blasting*.
Sands, compaction, factors influencing early stages, (8) 197*i*.
Eocene neritic bar, opal, zeolites, and clays in, (1) 24*j*.
foundry, composition, P (1) 7*e*.
system for mulling and mixing, P (11) 283*d*.
glass, from Assam, Madhya Pradesh, and Orissa, (5) 119*e*.
fluid process for drying, (2) 52*g*.
mechanism for grading and mixing, P (3) 83*c*.
olivine, effect of grading on molding properties, (4) 96*j*.
quartz, method of treating, P (2) 54*e*.
mineralogical studies, (5) 119*f*.
treatment, P (4) 107*d*.
Sandpaper. See *Abrasives*.
Sandstones, cementation, experimental study, (8) 197*g*.
Sanidine. See *Feldspar*.
Sanitary ware, bath tub, process for slip-proofing, P (8) 183*b*.
and facing ceramics, production in Bulgaria, (11) 283*i*.
pilot shop tests new ideas, (1) 9*a*.
toilet, bowl, mold for casting, P (1) 9*c*.
construction, P (7) 155*f*.
with deformable water seal trap, P (5) 126*c*.
flush tank, P (11) 283*j*.
jet operated, P (10) 261*d*.
urinals, P (3) 75*c*.
water closets, P (3) 75*d*.

Saponite, infrared study of ammonia reactions with, (7) 164*a*.
Sapphire, adherence and wettability of nickel, nickel-titanium alloys and nickel-chromium alloys on, (10) 249*g*.
crystals, large, growth from cryolite, (2) 55*c*.
surfaces, clean, friction of, (11) 295*c*.
growth, by Czochralski technique, (8) 199*c*.
neutron irradiated, nature of dislocation loops, (9) 241*d*.
single crystals, gross imperfections, use of X-ray topography for observation and characterization, (10) 272*i*.
strengthening by precipitates containing titanium, (4) 110*j*.
synthetic, rod, as precision electrical resistor, P (2) 49*b*.
Saws, abrasive segments for, P (4) 89*h*.
cable-type stone cutting, P (4) 89*f*.
method of making, P (3) 63*f*.
Scaling, of Fe-26Cr alloys at 870° to 1200°C, (11) 300*f*.
Scandium, -containing ferrites, manufacturing technology, (10) 262*h*.
determination in silicate rocks by ion exchange-spectrophotometric method, (5) 131*a*.
oxide, absorption edge spectrum, (8) 190*j*.
ScB_2, X-ray determination of thermal expansion coefficient, (2) 59*d*.
ScOF, crystal structure, (10) 270*c*.
Scattering, diffuse, in electron diffraction patterns, (1) 17*j*.
Raman, in uranium dioxide, (8) 205*c*.
Schools. See *Education*.
Science, basic, importance to ceramic industries, (11) 292*i*.
Screening, applications, neutron-absorbing materials for, (3) 70*j*.
effect on phase and structural properties of cubic carbides, (11) 294*g*.
of fine solids, suspended in liquid, device for, P (2) 50*a*.
Screen process printing. See *Decoration*.
Screens and sieves, frustoconical, in centrifuge, with means to improve screen life, P (8) 186*f*.
ion-exchanged type A molecular, study of properties: I, gas absorption; II, X-ray diffraction and electron microscopy; III, infrared spectography, (9) 235*f*.
luminescent, method of making, P (2) 48*j*.
metallizing, P (8) 185*j*.
utilizing nonluminescent separator layers, P (3) 78*c*.
molecular, formed bodies hardened with binding agent, P (3) 83*f*.
granular material for, P (3) 83*c*.
Linde 13X, neutron irradiation, (1) 23*f*.
methods of making, P (3) 83*f*; P (5) 133*c*.
pellets for, P (3) 83*c*.
optical fiber phosphor, method of making, P (3) 68*g*.
phosphor, method of making, P (8) 185*g*.
sieving, ultrasonic, P (5) 130*f*.
wet, ultrasonic disruptor as aid, (1) 15*j*.
sifter, circulating air type, P (7) 161*d*.
with spring supported vibratory drive, P (10) 266*h*.
tensioning, P (11) 289*b*.
device, P (5) 130*c*.
vibrating, with wedge ring support, P (7) 158*j*.
vibratory conveyor, P (3) 80*g*.
Sculpture. See *Art and artware*.
Seals and sealing. See also *Bonding; Soldering*.
alumina ceramic-to-metal with sealant glass, method and article formed, P (10) 255*e*.
ceramic, for spark plug, P (3) 77*e*.
ceramic-glass, means for encapsulation of electrical devices, P (10) 263*c*.
ceramic-metal, P (10) 263*d*.
high temperature, P (2) 47*i*.
ceramic-to-metal, P (2) 47*j*.
characteristics of composite lead-in wires with copper core, (5) 126*g*.
compression ceramic-metal, P (5) 127*d*.
contact reeds in glass tube, P (2) 39*b*.
edge, method in safety glass, P (1) 5*i*.
fiber optic plates, P (5) 121*g*.
flexible, between telescopically engageable clay pipe sections, method of forming, P (8) 179*f*.
gas-filled electric incandescent lamps and discharge tubes, method, P (7) 150*a*.
gasket, compressible, simple method of selecting materials for, (11) 300*h*.
glass, chromizing molybdenum for, (1) 3*f*.
for current lead-through member, P (1) 4*h*.
glass encapsulated diodes, P (7) 156*h*.
of glass fiber devices, fluid tight, P (1) 4*j*.
glass lead-through, compressed, photoelastic investigation of principal normal stresses and inversion temperature, (10) 253*c*.
glass-to-metal, P (1) 10*h*; P (7) 157*j*.
in electronic devices, P (5) 127*e*.
resilient pressure, P (9) 230*f*.
glass parts, to form cathode ray tube envelopes, P (9) 222*d*.
hermetically, including intervening electrical conductor, P (3) 68*b*.
methods and devices, P (8) 178*a*.
heat, glass to surface of body, P (2) 38*i*.
hermetic compression, stress analysis, (1) 4*h*.
stress distribution, (7) 156*c*.
high-current, for electric discharge lamp, P (1) 10*i*.
high-lead glass composition, P (5) 120*c*.
high-purity alumina to metal, P (3) 79*d*.
insulator, glass-ceramics for, (4) 93*a*.
$MnO\text{-}SiO_2\text{-}Al_2O_3$ compound, for refractory material surfaces, P (8) 181*j*.
membrane, to target support metal ring, P (3) 69*e*.

Seals and sealing (*continued*)
metal-to-glass, method, P (9) 221*h*.
of molybdenum foil to silica glass, stresses in, (5) 126*g*.
for packing joints in glass furnace, P (11) 279*d*.
pipe, method, and preparation of composition, P (5) 116*j*.
press, apparatus, P (3) 69*j*.
pressure bonded ceramic-to-metal gradient, P (9) 231*i*.
quartz-to-metal, P (1) 10*g*; P (8) 178*j*; P (9) 232*g*.
refractory gas, P (7) 154*f*.
refractory metal-to-ceramic, P (11) 283*e*.
solder glass, compositions, P (3) 69*f*.
in semiconductor packaging, (10) 253*i*.
tubular, direct glass-Kovar, (1) 3*f*.
Sedimentation, dispersion analysis, problems, (10) 267*e*.
equilibrium data, for calculation of moments of molecular weight distribution, (7) 162*f*.
methods, in particle size analysis, (4) 104*c*.
for particle size analysis of fine abrasive powders, (1) 1*f*.
of particulate matter from liquids, P (2) 50*c*.
Sediments, carbonate, kinetics and diagenesis, (8) 201*f*.
mixed coarse-fine, terminology, (4) 111*b*.
semiconsolidated and unconsolidated, sampling device for, (1) 14*d*.
subaqueous, mechanical analysis, (8) 187*d*.
Seignetto ceramics. See *Ferroelectricity and ferroelectric materials*.
Selenide, MSe, of face-centered cubic NaCl type, solid solutions formed by addition to selenides of rare earths, (1) 28*i*.
preparation, P (5) 128*e*.
systems. See *Systems*.
titanium, gaseous products from vaporization of, (3) 75*i*.
Selenium, amorphous and hexagonal, thermodynamic properties, (2) 38*b*.
-cadmium ruby glass, manufacture, (3) 66*b*.
electrophotographic layers, capacity, (5) 134*i*.
single crystals, trigonal, elastic properties, (5) 135*c*.
systems. See *Systems*.
vitreous, illuminated surface, characteristics of photocurrent normal to, (5) 134*a*.
Semiconductors, alloying technique, P (3) 79*d*.
amorphous zinc oxide, and method of making, P (3) 77*i*.
assemblies, alloyed junction, apparatus for fabricating, P (3) 77*a*.
manufacture, P (5) 127*i*.
attaching leads, P (7) 156*f*.
barium titanate, halogen treatment, (9) 229*a*.
ceramic, two sets of ESR of Gd^{3+} in, (8) 211*a*.
bodies, coating with silicon dioxide, P (8) 184*f*.
doping and contacting process using oxygen free electrolyte, P (9) 232*f*.
elongated, tape-shaped, process and apparatus for producing from melt, P (3) 79*a*.
method of manufacturing, P (1) 11*d*.
methods of alloying material to, P (2) 48*e*.
monocrystalline, heat-treating, P (8) 185*d*.
process for determination of diffusion profiles in, P (5) 128*g*.
producing and regulating translatory movement in manufacture of, P (11) 287*i*.
tape-shaped, process for producing, P (3) 79*c*.
thallium telluride, methods of making, P (2) 48*c*.
body, intermetallic, and method of diffusing *n*-type impurity, P (8) 184*i*.
monocrystalline, process for growing epitaxial layers of semiconductor material on, P (11) 286*i*.
bulk, amplification oscillation and mixing in single piece of, P (11) 284*h*.
cadmium chalcogenide, in manufacture of semiconductor systems, P (2) 48*b*.
cadium sulfide, for use in making semiconductor devices, P (1) 11*f*.
ceramic bodies, of *n*-type oxidic material, methods of providing contacts on, P (3) 79*g*.
chips, method of selectively coating, P (1) 11*h*.
circuit, complex with low isolation capacitance, and method of manufacture, P (10) 265*b*.
solid, with crossing conductors, P (3) 79*f*.
component with a *pn* junction and cooled by a Peltier cell, P (1) 11*e*.
components, treatment, P (8) 186*d*.
composition, with negative resistance characteristics at extreme low temperatures, P (7) 158*a*.
compounds, double doping of III-V, P (1) 10*a*.
low temperature synthesis, P (7) 156*h*.
and method of making by alloying, P (1) 10*j*.
for production of thin semiconductor layers, P (3) 79*c*.
ternary, and method of preparation, P (5) 129*c*.
compound crystals, P (5) 129*a*.
contact alloy, P (8) 186*c*; P (9) 232*a*.
coupled, injection laser devices, P (5) 127*f*.
crystal growth, from domical projection, P (3) 79*d*.
crystalline, preparation of, P (3) 79*a*.
crystals, apparatus and method of determining the values of electrical parameters of, P (2) 47*g*.
dendrites, method for production, P (5) 128*j*.
devices, P (2) 49*e*; P (5) 129*c*; P (7) 158*b*; P (8) 186*d*; P (9) 232*a*.
alloy-diffused method for producing, P (7) 156*e*.
apparatus for producing, P (3) 77*b*.
bilaterally bistable, P (2) 47*h*.
bonding to substrates, P (8) 184*c*.
with closely spaced electrodes, fabrication of P (5) 127*b*.
compression bonded, P (9) 230*a*.

Semiconductors, devices (*continued*)
controllable, with negative current-voltage characteristic, and method for manufacture, P (9) 230*a*.
double diffused, method of manufacturing, P (10) 264*d*.
electrical characteristics, method of improving, and products produced, P (5) 128*b*.
electrode, method of making conductive connection, P (5) 128*a*.
epitaxial alloy, and process for making, P (3) 78*f*.
with epitaxial contour, P (10) 265*b*.
epitaxial growth, P (8) 184*b*.
of epitaxially deposited layers, P (9) 230*f*.
fabrication, P (1) 10*d*; P (1) 11*e*; P (2) 48*g*; P (4) 102*e*; P (8) 186*e*.
field effect, and method of forming, P (8) 184*b*.
field effect, with polar polymer covered oxide coating, P (3) 78*i*.
galvanomagnetic, P (8) 184*c*.
glass sealed ceramic housings for, P (10) 264*a*.
glasses for encapsulating, and resultant devices, P (5) 127*g*.
gold-impregnated, bonded contacts for, P (4) 100*g*.
group II-VI compound, preparing, P (9) 231*i*.
heterojunction, method of making, P (11) 286*j*.
high voltage, P (7) 157*f*.
housed, with thermally matched elements, P (10) 264*d*.
insulated-gate field-effect, P (5) 127*h*.
integrated, method of making, P (5) 128*b*.
integrated two transistor, P (8) 184*i*.
intermetallic compound, P (4) 101*j*.
with layer of silicon monoxide and germanium mixture, and method of fabricating, P (9) 232*b*.
manufacture, P (9) 231*d*.
metallic ceramic composite contacts for, P (4) 101*a*.
metallic contacts for, P (11) 286*c*.
method for assembly, P (2) 48*d*.
method of forming Te contacts on, P (11) 286*f*.
methods of making, P (1) 11*e,f,j*; P (2) 48*c*; P (2) 49*f*; P (4) 102*d*; P (5) 128*b,e*; P (5) 129*c*; P (7) 157*f*; P (9) 231*e,h*; P (10) 264*c,f*; P (11) 286*i*.
method of making by diffusing impurities, P (5) 128*c*.
method of making by means of carrier gas with impurities, P (11) 286*j*.
method of making using cadium sulfide semiconductors, P (1) 11*f*.
method of making utilizing vacuum welding, P (5) 128*d*.
method of manufacturing by vapor deposition, P (10) 264*f*.
method of passivating, P (4) 102*b*.
method of producing by diffusion, P (11) 287*a*.
method of producing by employing vitreous material, P (5) 128*i*.
method of treating by ionic bombardment, P (9) 231*c*.
with modifier-containing surface silicon oxide layer, P (11) 287*d*.
monolithic, methods for forming, including epitaxial growth, P (9) 231*e*.
multilayer junction, P (8) 185*d*.
negative resistance, P (10) 265*c*.
with passivated junction, P (4) 102*e*.
photoelectronic, comprising injection luminescent and light sensitive diode with common *n* region, P (2) 48*i*.
photovoltaic, P (3) 79*e*.
point contact, P (4) 102*f*.
planar, with improved emitter and base configuration, P (10) 265*e*.
planar, process for passivating, P (7) 157*g*.
with *pn* junction defined by boundary between two intersecting semiconductor layers, P (11) 287*d*.
with pressure maintained nonbonded connectors, P (1) 11*g*.
pressure sensitive, P (8) 185*i*.
process of forming inorganic glass coating on, P (4) 102*i*.
process for production use, P (1) 11*d*; P (8) 186*c*.
silicon, method of making, P (7) 157*g*.
silicon, method of manufacturing, P (9) 231*i*.
stabilizing coatings for, P (10) 265*g*.
strain sensitive, and method of making, P (10) 265*c*.
stress sensing, P (1) 12*a*.
surface-passivated alloy, and method for producing, P (11) 287*j*.
surface protected, top contact for, P (11) 288*c*.
with terminal contacts, and method of making, P (3) 79*e*.
thallium telluride, methods of making, P (2) 48*e*.
use of silicon in, P (5) 129*d*.
variable photosensitive, with graduating different operable surface area, P (4) 102*a*.
disks, method of soldering, P (2) 48*d*.
doped, process and products, P (8) 184*h*.
effect of phonon distribution on hot electrons in, (5) 135*b*.
electronic device, P (1) 10*b*.
of four-layer junction, P (1) 10*c*.
electropolishing process for both sides, P (3) 79*b*.
elements, method of etching and contacting, P (8) 185*c*.
method of making, P (3) 78*j*.
method for surface treatment, P (4) 102*e*.
production by diffusion process, P (7) 157*i*.
transistor type, with 0 temperature coefficient, P (7) 157*e*.

Semiconductors, elements (*continued*)
treating of surfaces, P (8) 186*c*.
variable negative-resistance, P (8) 186*e*.
encapsuled (monocrystalline) device with lapped surface connector, P (1) 10*c*.
encapsuled with alloy-bonded carrier plates and pressure maintained conductors, P (1) 10*d*.
encapsulating and reinforcing materials, utilizing boron nitride, P (2) 49*g*.
encapsulations, and methods and apparatus for making, P (11) 285*h*.
etching method, P (3) 78*g*.
fabricating, by masking, P (4) 101*e*.
film devices, magnetoresistive, fabrication of, P (11) 285*a*.
-film Hall devices, process for producing on oxide-metal substrate, P (9) 232*d*.
fission fragment damage, (11) 295*i*.
glass enclosed passivated, with contact means of alternate layers of chromium, silver, and chromium, P (3) 78*j*.
hard, with metal coating, P (7) 156*f*.
hot electrons in, theory, (10) 272*h*.
impurities, method and apparatus for determining drift depth of, P (3) 78*f*.
inductive, P (1) 11*a*.
insulator-, wafer, method of making, P (4) 101*h*.
integrated circuit elements, method of making, P (3) 78*j*.
lattice magnetic susceptibility, theory, (5) 139*c*.
layer-type, optical absorption edge, (10) 271*g*.
layers, epitaxial, process of pyrolytically growing on heated semiconductor substrates, P (11) 287*f*.
epitaxially growing, through openings in oxide mask, P (4) 101*e*.
masking, and etching beneath mask, P (5) 128*d*.
materials, P (9) 232*b*.
apparatus for pyrolytic precipitation from gaseous compound, P (3) 77*c*.
crystalline, method of producing on dendritic substrate, P (11) 286*h*.
crystalline, process for production, P (7) 157*h*.
doped, method and apparatus, P (9) 231*a*.
doped, process for production, P (9) 232*e*.
heat-treating, P (7) 157*a*.
method and apparatus for growing monocrystalline layers on monocrystalline substrates of, P (3) 78*f*.
method and apparatus for forming, P (7) 157*a*.
method and apparatus for producing, P (7) 157*a*.
and method of making, P (5) 129*d*.
methods of making monocrystalline bodies of, P (4) 102*g*.
method of producing by chemical transport reaction using H_2S/H_2 system, P (3) 79*e*.
method of treating bodies of, P (8) 185*c*.
mixed, method for producing homogeneous crystals of, P (10) 264*h*.
monocrystalline, preparation, P (9) 231*h*.
production of *p*-doped zone in body of, P (8) 186*b*.
pure, apparatus for producing by vapor deposition, P (11) 284*h*.
pure, process and apparatus for pyrolytic production of, P (2) 49*b*.
thallium telluride, methods of making, P (2) 48*e*.
for thermoelectric initiators, P (7) 157*k*.
measurement of homogeneity, (11) 298*d*.
members, epitaxial method of producing, using support having varyingly doped surface areas, P (3) 78*g*.
method of modifying electrical characteristic, P (.0) 164*g*.
method and device, P (11) 287*e*.
method to make, and diffusion, P (4) 102*a*.
method of making contacts on, P (11) 286*i*.
method of making by selective impurity diffusion, P (11) 286*j*.
method of producing by diffusion, P (7) 157*i*.
negative resistance device, utilizing tunnel effect, P (5) 128*d*.
p-type, process for making, P (3) 79*f*.
packaging, solder glass seals in, (10) 253*i*.
photosensitive device, including layers of different conductivity types, P (2) 48*j*.
piezoelectric, elastic wave and infrared light interactions with moving high-field domain in, (11) 294*a*.
phonon-drag thermoelectric effect, (10) 271*b*.
pn junction, method of producing, P (3) 79*e*.
pn junction devices, and method of making, P (4) 102*f*.
process, and products produced, P (5) 129*e*.
product, and method of making, P (9) 232*b*.
properties, of hot-pressed titanium dioxide, (3) 76*f*.
radioactive irradiation effect: I, neutron irradiation on *n*-germanium, (1) 18*g*.
rectifier element, stackable, having seals under compressive stress, P (3) 79*g*.
research, (1) 10*e*.
rods, apparatus for crucible-free zone melting of, P (3) 77*a*.
apparatus and method of producing by pulling from melt, P (4) 100*f*.
apparatus and process for preparing, P (9) 230*f*.
semiconducting behavior of substituted tungsten diselenide and its analogues, (7) 167*g*.
semiconducting compositions, P (4) 102*h*.
semiconducting device, electrically unsymmetrical, process for production, P (11) 287*f*.
semiconducting layers, thin, process for producing from semiconducting compounds, P (3) 79*c*.
semiconduction, in iron phosphate glasses, (11) 277*j*.
semiconductive alloy light source having improved optical transmissivity, P (4) 102*c*.

Semiconductors (*continued*)
semiconductive capacitor, and method of making, P (4) 102*c*.
semiconductive device, fabrication, P (11) 287*b*.
silicon, process of coating with indium using ion beam, P (3) 79*a*.
surfaces, stabilization, P (11) 287*h*.
silicon carbide device, P (5) 129*a*.
single crystals, process for epitaxial growth, P (4) 102*h*.
slice, method of etching to dice, P (2) 48*f*.
stabilized, mechanically and electrically, by lacquer and boric oxide layers, P (4) 102*g*.
structure, including opposite conductivity segments, P (7) 158*c*.
layered, helicon-drift current interaction, (11) 296*f*.
substances, methods of preparing, P (10) 265*a*.
superconductive articles, P (11) 287*i*.
support, metallized, and mounting structure, P (3) 78*d*.
switch, barrier layer, with symmetrical characteristics on either polarity, P (7) 158*a*.
four layer, with third layer defining continuous, uninterrupted internal junction, P (9) 230*j*.
switch devices, multiple-zone, P (5) 129*e*.
switching device, and method of manufacture, P (9) 232*c*.
systems, comprising cadmium chalcogenide semiconductors, method of making, P (2) 48*b*.
isolated base four-layer, P (1) 11*a*.
tunnel-effect, with capacitative gate across edge of *pn* junction, P (7) 158*b*.
terminals, and method, P (10) 265*c*.
titania-containing polycrystalline, correlations between structure and electrical properties, (1) 9*i*.
wafer, etching by duo resist process, P (8) 184*i*.
isolating chips, method, P (10) 264*i*.
jogging device in apparatus for treating in gas, P (4) 101*a*.
method for forming, P (3) 68*d*.
method of making composite insulator, P (3) 78*i*.
thermal printing, and method of making, P (11) 288*a*.
Separation. See also *Beneficiation; Classification; Flotation.*
of actinide and lanthanide members, P (1) 15*j*.
of basalt magmas in lava flows, (1) 18*j*.
centrifugal, of minerals, process, P (9) 236*f*.
of ceramics by electromagnetic techniques, (5) 131*e*.
convention carrier, for activation analysis of silicon, (2) 50*d*.
detection, thermal probe for, (3) 81*h*.
electrical, of oxide minerals, temperature and humidity, (4) 106*h*.
electrophoretic, of materials in localized area, method, P (11) 288*j*.
electrostatic. See *Electrostatic processes.*
fluid, process and apparatus for concentrating and separating component of, P (1) 13*b*.
heavy medium, media and process, P (4) 106*b*.
high tension, of materials, P (9) 235*h*.
high voltage, of fine particles, P (7) 160*j*.
magnetic, of particulate materials, method and apparatus, P (3) 83*c*.
mineral, from rocks with Frantz isodynamic magnetic separation, (8) 189*i*.
of minerals, P (3) 83*e*.
of mixtures of substances, process, P (1) 13*c*.
oxygen isotope, in systems containing dolomite, (1) 24*f*.
particulate matter, process, P (11) 291*f*.
pneumatic, of solid particles, process and apparatus, P (7) 158*h*.
pneumatically, of solid particles, P (3) 81*f*.
selective, of heterogeneous particles, P (4) 107*c*.
of solid particles from gas, purifying apparatus for, P (2) 50*b*.
sorting process and apparatus for two particulate materials, P (4) 103*i*.
of suspended particles from gases, method and apparatus, P (11) 288*i*.
of uranium from uranium dioxide-zirconium dioxide mixtures, P (11) 283*b*.
Separators, centrifugal, P (2) 53*j*.
centrifuge having frustoconical screen with means to improve screen life, P (8) 186*f*.
cyclonic, P (10) 266*g*.
drum type magnetic, P (9) 235*f*.
electrostatic, with coated discharge electrode, P (3) 83*c*.
electrostatic beam, heated glass cathodes in, (1) 13*f*.
filter plate, P (4) 103*f*.
hydrocyclones, for concentrating kaolins and clays, design, (3) 79*j*.
magnetic, for mixtures of magnetic and nonmagnetic material, P (3) 80*c*.
for solid materials in liquid suspensions, P (3) 80*d*.
Sericite. See also *Mica.*
crystal distortion, (5) 134*i*.
Serpentine, for forsterite refractories, (2) 42*e*.
Setting. See *Binders.*
Settling. See *Sedimentation.*
Sewer pipes. See *Pipe.*
Shales, additives as modifiers, (1) 12*g*.
expanded, manufacture, P (9) 223*a*.
oil, for producing cement, P (4) 91*c*.
Pennsylvanian, relations of depth, porosity and clay mineral orientation, (7) 168*c*.
surfaces, skid-resistant, evaluation of expanded aggregates for use in, (4) 90*g*.
Shock, thermal, rupture, of uranium ceramics, (7) 152*e*.
Shock resistance, thermal, of brittle cermets, similarity theory, (8) 206*j*.

Shock resistance, thermal (*continued*)
ceramics of Li_2O-Al_2O_3-SiO_2 system: III, hot pressing of petalite powder and pulverized lithia-containing glass mixture, (2) 37*i*; IV, slip casting of petalite ceramics, (5) 125*g*.
determination by nondestructive test methods, (2) 41*a*.
of wall tile, (3) 74*g*.
Shrinkage, of corundum during sintering, (10) 257*b*.
drying, of dry-pressed bodies, Bourry diagram, (5) 121*j*.
evaluation from response surface, (9) 233*j*.
reversible and irreversible drying, of hardened portland cement and tricalcium silicate pastes, (10) 248*e*.
stress, effect on creep of hardened cement paste, (5) 116*d*.
Sieves. See *Screens and sieves*.
Silex. See *Quartz*.
Silica. See *Silicon, dioxide*.
Silicates, alkali and alumino-, formation and occurrence in blast furnaces, (5) 122*j*.
alkali metal particles, and method of making, P (2) 46*a*.
authigenic, in marine Spencer formation at Corvallis, Ore., (7) 162*a*.
chemistry, structure model and application to, (4) 110*j*.
constitution, in magnesite brick, effect on high-temperature strength, (9) 224*b*.
crystal lattices, energetics, (8) 196*b*.
dicalcium. See *Calcium, dicalcium silicate*.
examination, by infrared spectroscopy, (11) 289*f*.
flotation, role of iron, (4) 106*e*.
free energy of formation, from measurements made with galvanic cells involving solid electrolytes, (8) 198*f*.
glasses, thermodynamic approach to structure, (2) 38*a*.
grout, P (3) 64*g*; P (7) 154*c*.
high-temperature chemistry of, B (3) 88*e*.
hydrothermal chemistry: XII, synthetic strontium aluminosilicates; XIII, synthetic barium aluminosilicates, (8) 199*g*.
industry, proceedings of eighth conference, B (5) 141*f*.
laminar, microcalorimetry in, (4) 108*i*.
material blocks, mold for, P (2) 39*g*.
materials, P (8) 190*i*.
melts, in system Fe_2O_3-MnO-alkali oxide-Al_2O_3-SiO_2, magnetic materials from, (3) 86*e*.
meta-, glasses, ionic structure, (2) 38*a*.
meta-, chemical interpretation of surface phenomena in, (4) 107*e*.
surface properties, (4) 111*d*.
molybdenum determination in, (2) 50*g*.
raw material, calcination, P (2) 35*a*.
rocks, direct current arc spectrographic technique for determination of trace amounts of lithium, rubidium and cesium in, (2) 50*i*.
solid infrared absorption, with and without fluoride additions, (7) 164*i*.
structures, criterion for stability, (5) 134*h*.
systems. See *Systems*.
thermodynamics, B (5) 142*f*.
Silicides, coatings, on columbium and tantalum, evaluation, and means for improving oxidation resistance, (10) 249*g*.
complex, oxidation studies, for protective coatings, (7) 147*i*.
mono-, of iron group transition elements, conduction phenomena, (10) 270*h*.
thermal expansion study, (5) 123*h*.
Silicon, activation analysis of, by convention carrier separations and by computer reduction of gamma spectra, (2) 50*d*.
anodic oxidation, luminescence during, (7) 165*f*.
apparatus for vapor deposition of, P (11) 284*h*.
carbide. See also *Refractories*.
α-, single crystals, growth from chromium solution, (3) 86*c*.
β-, orientation of stacking faults and dislocation etch pits in, (3) 87*d*.
boron doped, photoluminescence and polytypism, (7) 166*d*.
brick, (1) 7*f*.
characteristics produced by thermal decomposition of trimethylchlorosilane, (4) 96*g*.
chemical etching, with hydrogen, (11) 284*g*.
coating on nuclear fuel body containing uranium carbide spheroids, P (1) 8*g*.
coating, process for applying to refractory metals, P (8) 174*j*.
-containing material, method for producing contact layer on, P (1) 8*b*.
containing 12% free carbon in range 1100° to 2850°K, (8) 197*h*.
crystals, dislocations, X-ray study, (10) 272*h*.
crystals, X-ray micrographic study, (11) 303*b*.
electron-irradiated *n*-type, electron spin resonance in, (3) 85*f*.
epitaxial growth, (3) 75*i*.
foamed, insulation and properties, (4) 96*i*.
formation, (3) 72*b*.
in graphite crucible composition, (7) 152*j*.
impurities, effect on properties of heating elements, (5) 122*c*.
method to prepare, P (4) 99*b*.
Mo-SiC reactions, (11) 281*e*.
monocrystalline, method of pulling, P (1) 8*e*.
n-type, free carrier absorption, (8) 198*f*.
phase stability, (8) 205*b*.
process for making, P (5) 124*j*.
properties, effect of nuclear radiation, (8) 195*f*.
purification by flotation process, P (8) 181*c*.
saggers for porcelain industry, (9) 224*g*.
semiconductor device, P (5) 129*a*.
single crystals, preparation, (3) 87*g*.
stability in firing processes, (4) 110*d*.

Silicon, carbide (*continued*)
submicroscopic fibrous, oxidation, (9) 241*a*.
supported vanadium-containing oxidation catalyst, process for making, P (2) 45*e*.
systems. See *Systems*.
39H, crystal structure, (7) 162*a*.
very pure, process for manufacture, P (8) 190*e*.
-carbon matrix, for two-phase thermoelectric body, P (2) 49*f*.
chemistry, new results, (1) 23*i*.
compounds, P (4) 99*b*.
crystalline, process for polishing, P (9) 232*a*.
crystals, diffusion of gold into, (9) 238*g*.
deposition, epitaxial, kinetics by low pressure iodide process, (11) 297*f*.
device fabrication in, with anodic oxide films, (3) 75*e*.
diffusion-induced imperfections in, (9) 238*h*.
dioxide. See also *Cristobalite; Glass; Quartz; Quartzite; Refractories; Sands*.
adsorption and flocculation behavior, effect of solid content, (8) 195*i*.
alumina, study with high alumina content prepared by cogelling method: II, changes in surface property during preparation, (1) 15*i*.
anion radicals, heat of formation, (8) 196*h*.
bodies, molded amorphous, and molding powders for making, P (4) 106*h*.
-bonded bead granules, process for production from solids in powder form, P (8) 187*a*.
-bonded zeolitic molecular sieve granules, production of, P (4) 107*a*.
brick, determination of thermal softening behavior, (3) 71*c*.
brick, development of superduty, with indigenous raw materials, (2) 41*b*.
coating for semiconductor bodies, P (8) 184*f*.
deposition mechanism by pyrolytic decomposition of silanes, (10) 262*j*.
determination in chrome-bearing materials, (5) 130*h*.
diagenesis in Upper Jurassic limestones of southern England, (8) 206*h*.
I, extrusion; II, coherence and strength of compacts, (3) 74*c,d*.
fibers, pretensioned, in solid metal materials, P (5) 117*d*.
filaments, freeze-coating, (7) 148*h*.
films, P (2) 49*g*.
films, doped, (8) 195*e*.
films, deposition technique, (4) 100*i*.
films, thermally grown, electronic conduction, (5) 126*f*.
films, thermally grown, nonfilamentary switching action, (7) 155*j*.
finely divided, manufacture, P (5) 133*b*.
finely divided amorphous, production, P (7) 161*c*.
in fluid compositions, P (2) 54*c*.
free, determination in cement raw materials, (4) 90*h*.
fused, articles, P (5) 120*c*.
fused-, capsules, gas permeation during high temperature heat treatments, (3) 86*b*.
fused, effect of high pressure on crystallization kinetics with special reference to, (2) 36*b*.
fused, newest in refractory material developments, (1) 7*d*.
fused, optical determinations of OH, (2) 55*j*.
fused, strength, (9) 218*a*.
fused, uses, (5) 124*b*.
gel, preparation, P (9) 236*e*.
gels, influence of porosity on structural water content and its thermal dehydration, (1) 19*g*.
gels, process for preparation, P (8) 190*e*.
gels, vitrification, (8) 211*g*.
high-, foam materials, synthesis of SiO_2-B_2O_3-Sb_2O_3 materials, (2) 57*c*.
hydrophobic, as grinding aid, P (10) 266*a*.
hydrophobic wet-precipitated, process for preparing, P (9) 236*g*.
influence on hydration of $3CaO \cdot SiO_2$, (1) 19*i*.
infrared absorption spectrum discussion, (1) 18*c*.
kinetics of reaction of liquid silicon with, (1) 21*e*.
kinetics of reaction with melts of ternary system CaO-SiO_2-Al_2O_3, (8) 201*i*.
kinetics of reaction with silicon liquid, (1) 21*e*.
lamellas, production, P (9) 236*c*.
in magnesite and calcareous materials, rapid method for estimation, (2) 51*c*.
manganese reactions with, (8) 206*a*.
microstructure of forms of, (8) 180*f*.
new information and application to modern technology, (11) 298*c*.
pigmentary, apparatus for producing, P (2) 53*i*.
pigments and preparation, P (1) 16*c*; P (5) 133*h*.
reactive materials, and process of producing, P (9) 236*e*.
reactive selectively sorptive materials, and process of producing, P (9) 236*d*.
recovery from treatment of serpentine with ammonium bisulfate, P (11) 292*f*.
reduction rate in reducing gases at 1500°C, (7) 167*e*.
-Si interface states, density, (5) 135*a*.
and sodium sulfite, thermal reactions between, (8) 176*j*.
solid body, high purity, methods of forming by fusion, P (5) 128*a*.
source in soil solutions, (4) 109*d*.
structures as host compounds with crystalline solid solutions, P (1) 10*j*.
surfaces, hydrolysis experiments of siloxane bonds at, (3) 85*i*.

Silicon, dioxide (*continued*)
suspensions, amorphous and sized crystalline, flocculated by high polymers, filtration of, (8) 198*a*.
systems. See *Systems*.
thermally grown, charge distribution, (2) 54*g*.
viscosity-temperature relations, (1) 29*a*.
vitreous, and molten aluminum, reaction between, (3) 65*e*.
vitreous, production in rotary kiln, P (8) 182*e*; P (9) 227*i*.
and zirconia mixture, preparation, P (3) 83*g*.
elements, in lenses for focusing infrared, P (5) 120*f*.
epitaxial, from SiI_4, thermodynamic study of growth rate of, (11) 302*c*.
transmitted phonon drag measurements in, (3) 87*c*.
tripyramid growth, (9) 242*j*.
epitaxial growth, effect of substrate orientation, (11) 294*i*.
epitaxy, on alumina, structural effects, (8) 197*a*.
preferential, with oxide masking, (3) 76*g*.
etching, by water vapor, (4) 100*e*.
films, [001] epitaxial, stacking-fault tetrahedra, (11) 301*g*.
polycrystalline, on foreign substrates, (3) 76*g*.
fluorination, kinetics of reactions, (8) 201*j*.
-germanium matrix, for two-phase thermoelectric body, P (2) 49*e*.
and germanium tetragonal disulfides, and preparation, P (9) 232*f*.
gold in, effect on resistivity and diffusion in heavily doped layers, (7) 163*j*.
groups, as bonding agents between glass and plastic materials, (9) 216*e*.
heavily doped, thermal oxidation, (11) 302*f*.
highest purity, for electric semiconductor devices, apparatus for producing, P (10) 263*b*.
-iron alloys, stability of inclusions and formation of secondary grains, (1) 29*d*.
kinetics of thermal oxidation, in dry oxygen, (1) 21*j*.
liquid, kinetics of reaction with silica, (1) 21*e*.
low-temperature epitaxy, by sublimation onto thin alloy layers, (10) 262*f*.
monocrystalline, of high purity, method of producing, P (9) 231*b*.
monocrystalline layers, method of producing on monocrystalline substrates, P (9) 231*b*.
monoxide, films, stress, (7) 167*j*.
particulate, oxidation kinetics, (5) 137*e*.
solid, disproportionation and vaporization, (8) 195*a*.
multiple slice epitaxial deposition of, in resistance heated furnace, (4) 100*i*.
n- and *p*-type, irradiation defects, (8) 197*a*.
nitride, articles, manufacture, P (7) 153*h*.
films, prepared by reactive sputtering, evidence of hole injection and trapping in, (10) 262*j*.
high density, method of making, P (3) 72*b*.
reactively sputtered, preparation and properties, (9) 229*g*.
nitride whiskers, destruction by reaction with metals at high temperatures, (9) 223*h*.
production, P (9) 227*h*.
nucleation and crystal growth on sapphire, (1) 24*b*.
organic, as bonding agents between glass and plastic materials, (9) 216*e*.
oxide, film, thermally oxidized, optical absorption, (5) 137*a*.
films, vacuum-deposited, nonohmic conduction, (11) 298*g*.
formation and devitrification, (11) 296*b*.
glow discharge formation, (9) 229*i*.
oxides, high dispersed, process for purification, P (9) 236*j*.
preparation, P (3) 72*e*.
oxidized *p*-type, effect of oxide hydration on surface potential, (10) 262*h*.
and oxidized silicon, surface states evaluation from characteristics of surface varactor diode, (11) 295*a*.
p-type, alloying indium with, to produce *pn* junction in making silicon diodes or transistors, P (2) 48*b*.
phosphide precipitates in diffused silicon, (7) 167*g*.
rods, zone melting, P (10) 266*h*.
in semiconductor devices, P (5) 129*d*.
-silicon dioxide interface, effect of orientation on surface charge density at, (11) 294*b*.
evaluation of surface states from characteristics of *p*-type MOS diodes, (11) 295*b*.
silicophosphate glasses, structure and properties, (2) 37*e*.
single crystal, epitaxy on foreign substrates, (1) 28*e*.
small particles in, (4) 109*h*.
stacking faults, after heating in wet oxygen, (5) 136*c*.
surface, thermally oxidized, Al redistribution in, (5) 134*a*.
systems. See *Systems*.
tetrahalides, oxidation, P (1) 16*a*.
thermal oxidation, deviations from parabolic growth, (5) 135*c*.
observation of impurity redistribution using MOS structure, (9) 241*h*.
thermal oxides, rates of formation, (3) 76*a*.
thermistors, P (3) 79*f*.
thin films, recrystallization, (10) 263*e*.
thin films growth, on polycrystalline alumina ceramic, (4) 100*d*.
thin transparent films, measurement of refractive index by index of refraction liquids, (3) 81*i*.
traces, spectrophotometric determination by extraction method, (10) 267*i*.
vapor deposition on graphite, (3) 72*b*.

Silicone, rubber interlayers, stable, for glass, process for making, P (7) 150*b,f*.
Silicosis, preventive medical treatment for, (2) 60*k*; (9) 244*b*.
Siloxanes, bonds, hydrolysis experiments at silicon dioxide surfaces, (3) 85*i*.
Silver, -alumina alloys, strength and creep behavior above melting point of silver, (4) 110*i*.
antimony, systems. See *Systems*.
aqueous suspension for ceramic substrates, P (5) 126*c*.
chloride, cold work and ductile-brittle transition of, (3) 84*a*.
double-layer mechanism for complex-ion embrittlement of, (10) 270*j*.
interaction with chlorides of potassium, indium, copper(I), and thallium(I), (8) 200*j*.
solubility, in molten nitrate solvents, (8) 207*g*.
and chloride, association in molten cesium nitrate and in molten mixtures of potassium nitrate with cesium nitrate or lithium nitrate, (8) 191*j*.
epitaxial growth on MgO, direct observation, (8) 183*h*.
films, vacuum-evaporated, X-ray diffraction study, (2) 59*e*.
ions, incorporated in alkali halide crystals, reduction by hydrogen, (5) 138*b*.
nitrate, pure molten, transport numbers by balance method, (8) 210*g*.
-sodium nitrate mixtures, molten, measurement of interionic diffusion and friction coefficients by diaphragm-cell method, (8) 194*c*.
selenite, thermal stability, (11) 302*g*.
AgMg, tensile behavior, (4) 111*b*.
$AgNO_3$ and AgCl, pure molten, transport numbers by simplified weighing method, (7) 169*e*.
systems. See *Systems*.
Silvering. See *Glass*.
Single crystals. See *Crystals*.
Sintering, activated, of niobium carbide, (3) 83*h*.
activated recrystallization, of aluminum oxide, factors determining, (5) 136*d*.
of alumina: III, effect of pores on rate of grain growth, (4) 110*d*.
recent Soviet work, (9) 229*i*.
review, (9) 229*i*.
of Al_2O_3-Fe-Fe_2O_3, effect of CaO-MgO-SiO_2 mixture, (11) 280*d*.
aluminum nitride refractories, P (2) 44*c*.
apparatus, moving pallet, and method, P (10) 268*h*.
assessment, B (7) 170*f*.
behavior, anomalous, of Y_2O_3, (9) 237*f*.
of uranium dioxide, effect of properties of powders, (11) 294*d*.
of beryllia: I, influence of origin and thermal treatments on sintering behavior of beryllia powders; II, hot-pressing of beryllia powders of different origin and thermal treatment, (10) 258*f,g*.
in binary system $MoSi_2$-WSi_2, (2) 43*a*.
in binary system $MoSi_2$-ZrO_2, (2) 43*b*.
ceramic dielectric materials, by hot-pressing, (7) 156*b*.
characteristics and properties of PuS and PuP, (1) 28*g*.
of corundum, deformation and shrinkage during, (10) 257*b*.
effect of isostatic pressure, (8) 195*b*.
of ferrites, effect of atmosphere, (7) 151*h*.
high purity $BaTiO_3$, (9) 230*a*.
influence of gas phase on magnesite, (4) 97*d*.
initial, of rutile, (7) 164*d*.
kinetics, study by sensitive resonant frequency technique, (4) 104*e*.
study using reduced variables, (11) 300*j*.
of magnesia, in argon, gas entrapment, (2) 41*h*.
pure, and with nickel, (5) 137*i*.
of magnesia brick, and effect of various factors on contraction rates, (7) 152*b*.
for manufacture of ceramic articles, P (5) 130*b*.
material transport in, B (7) 170*g*.
of niobium carbide, (10) 258*j*.
of porcelain, effect of apatite and chalk additions, (9) 228*c*.
in presence of liquid phase, study of consolidation processes, (4) 110*f*.
pressure, method of monitoring procedures, P (1) 11*g*.
processes, activation and inhibition by mechanical working, (5) 133*j*.
of single crystal rutile, (11) 300*j*.
sinterability of uranium dioxide, factors' influencing, (2) 41*f*.
sintered articles from inorganic material, process, P (10) 266*e*.
sintered bodies, method of producing, P (8) 185*b*.
and powder compacts, contact section, and values of mechanical properties related to compact section, (5) 134*g*.
sintered compounds based on uranium and plutonium, fabrication, P (2) 43*j*.
sintered materials, thermal cycling resistance, (10) 258*h*.
sintered pieces, process for making on a metal element, P (2) 49*c*.
sintered products, (9) 233*a*.
sintered specimens, containing hollow glass microspheres, strength of, (4) 93*a*.
of sodium chloride, B (7) 170*h*.
study and magnesia precursor, (1) 22*a*.
of thoria powders, influence of crystallinity, (4) 109*e*.
TiO_2, effect of minor additives, (4) 107*h*.
UO_2, between 950° and 1500°, kinetics, (11) 297*h*.
vapor phase, process, P (3) 73*d*.
of yttrium oxide, (1) 28*h*.
of zirconia of high purity, (5) 123*e*.
zone temperature, measured by chromatic pyrometer, (10) 249*c*.
Size reduction. See *Crushing; Grinding*.
Slags, attack on refractories, (4) 97*g*.
basicity, contributing to erosion of high-temperature burned basic brick, (11) 280*f*.
blast-furnace, cement pastes, nature of hydration products after 5 years immersion in potable water, (2) 34*f*.
hydraulicity in relation to composition, (2) 34*d*.
for porcelain objects, P (3) 75*a*.
of system MgO-CaO-Al_2O_3-SiO_2, calcium chloride activation, (4) 90*c*.
Thomas, mineralogical properties, and use in mortars and concrete, (4) 90*j*.
water treatment influence on linear rate of crystallization, (1) 2*b*.
wet grinding for better use of hydraulic properties, (7) 146*b*.
burning sulfur from, (5) 118*a*.
FeO_x-CaO, electrical conductivity, (9) 238*b*.
liquid, in ternary system SiO_2-Al_2O_3-CaO, study of viscosity, (2) 56*d*.
metallurgical, effect of additives on crystallization of melts of, (3) 71*j*.
open-hearth, diffusion in basic refractories, (7) 151*h*.
petrology of reactions of fused cast alumina refractories with, (2) 42*c*.
phosphorites or phosphorus-containing metallurgical, to improve qualities of cement, (9) 214*a*.
of power stations, deterioration of aluminosilicate refractories, (3) 70*i*.
slagging, of dolomite, system iron(II) oxide-calcium oxide-magnesium oxide as basis for determination of, (3) 64*e*.
wool. See *Mineral wool*.
Slip casting, of commercial alumina, rational conditions, (5) 123*h*.
kinetics, of alumina by gamma-ray absorption, B (7) 170*e*.
of petalite ceramics, (5) 125*g*.
studies: VIII, effect of specific base-exchange cations on casting properties of pottery bodies; IX, effect of coagulants on casting properties of alkaline casting slips, (7) 155*c,d*.
Slips. See also *Suspensions*.
-induced directional order theory for B2-type superlattices, (11) 301*a*.
plane, primary, effect of specimen shape on selection of, (11) 294*i*.
properties, (9) 228*d*.
stabilized pigment, P (3) 83*e*.
Smelting. See *Metallurgy*.
Soapstone. See *Talc*.
Soda or Soda ash. See *Sodium, carbonate*.
Sodium. See also *Alkalis*.
aluminates, structure and properties, (1) 29*g*.
aluminum systems. See *Systems*.
bromide, systems. See *Systems*.
carbonate, caustic, conversion to soda ash, P (9) 235*f*.
dense, manufacture of, P (3) 83*d*.
process for producing from sodium bicarbonate obtained by ammonia-soda process, P (11) 291*j*.
soda ash, continuous recycle heating process for production of, P (11) 291*e*.
soda ash, densification by vapor hydration, P (7) 160*i*.
soda ash, preparation, P (11) 291*d*.
systems. See *Systems*.
chloride, (001) surface, rotation of etch pits, (8) 206*e*.
crystals, dislocation nucleation, (8) 195*a*.
crystals, investigation of matched cleavage faces, (1) 20*b*.
crystals, production of electrostatic potential differences by plastic compression and bending, (8) 205*b*.
crystals, shape change produced by compression along [011], (9) 242*f*.
interaction with indium chloride, (4) 108*k*.
matching cleavage faces, for study of thin-film growth, (8) 211*b*.
melts, solubility of vanadium trioxide in, (8) 207*g*.
particle size dependence of electrical conductivity of, (4) 109*a*.
-KCl mixed crystals, growth from melt, (9) 239*b*.
single crystals, dynamics of plastic flow at constant stress in, (10) 270*j*.
sintering, B (7) 170*h*.
and NaBr thin films, low frequency dielectric losses, (1) 21*g*.
systems. See *Systems*.
-type compounds, estimation of entropy, (3) 85*k*.
Zn doped, diffusion and conductivity, (8) 194*f*.
disilicate, molten, polarography in, (2) 37*b*.
ditungstate, interactions with tungstates of iron, magnesium and copper, (4) 108*j*.
fluoride, systems. See *Systems*.
interaction with glass, (8) 192*g*.
iodide, systems. See *Systems*.
metaborate tetrahydrate, crystalline, and process for production, P (4) 106*b*.
metasilicate fines, anhydrous, process for agglomerating, P (11) 291*d*.
molybdenum bronze, crystal structure, (9) 237*h*.
monoxide, granular, continuous production using metallic sodium in molten form, P (2) 54*b*.
niobate, systems. See *Systems*.
oxide in soda-lime-silica glasses, determination by flame photometry, (10) 251*i*.
systems. See *Systems*.
volatilization from alundum tubes in high purity hydrogen, (1) 7*j*.
volatilization during burning of clinker and distribution in minerals, (10) 249*c*.
Sodium (*continued*)
KCl-NaCl alloy, polycrystalline alloy, deformation properties, (3) 84*g*.
salts, effect on formation of cement clinker minerals, (10) 248*f*.
silicate, dissolving process, accelerating, (10) 266*c*.
protective coating composition, P (2) 35*f*.
silicofluoride, effect on viscosity of clinker liquid phase, (9) 214*j*.
$NaNbO_3$, nucleation and crystallization from glasses in Na_2O-Nb_2O_5-SiO_2 system, (8) 175*g*.
$Na_2O \cdot 2CaO \cdot 3SiO_2$, glassy and crystalline, transport processes, (10) 253*g*.
sulfate, effect on fining container-type glass, (1) 3*i*.
sulfates, in portland cement clinker, to improve physicomechanical properties, (4) 90*h*.
sulfite, effect on hydration of tricalcium aluminate and tricalcium silicate, (4) 90*e*.
and silica, thermal reactions between, (8) 176*j*.
systems. See *Systems*.
tripolyphosphate, hydration by water vapor, (2) 46*e*.
-22, diffusion in molten sodium nitrate at constant volume, (8) 194*h*.
in ultrapure silicon and silicon dioxide films, determination by activation analysis, (10) 267*c*.
Soils, mechanics, applicability of physicochemical theories, (1) 16*j*.
post-yield mechanics, (8) 205*f*.
solutions, silica source in, (4) 109*d*.
Solar furnaces. See *Furnaces*.
Soldering. See also *Seals and sealing*.
brazing, ceramic materials, metal-oxygen technology, (10) 262*j*.
flux and method of brazing, P (9) 217*b*.
tungsten carbide, P (4) 92*f*.
ceramics and palladium-nickel-titanium brazing alloy, P (1) 10*g*.
semiconductor disks, P (2) 48*d*.
Solidification, binary eutectic, (7) 162*d*.
of liquid or semiliquid materials of low thermal conductivity, process and apparatus, P (7) 158*h*.
undirectional, of $BaFe_{12}O_{19}$-$BaFe_2O_4$ eutectic, (7) 156*e*.
Solid solutions. See *Solutions, solid*.
Solid state, crystallization process, radiation-induced, (8) 206*a*.
display device, for amplifying or converting input radiation, P (11) 287*g*.
image converting, P (11) 287*h*.
lasers, glass as material for, (10) 252*e*.
reaction system MgO-$MgSiO_3$, cathodoluminescence device for rapid identification, (10) 267*c*.
reactions, influence of particle size on mechanism, (8) 200*d*.
influence of structure, (8) 200*f*.
kinetics and mechanism, (8) 201*i*.
material transport, (8) 202*b*.
switching device, P (7) 158*a,d*.
Solids, blending method and apparatus, P (8) 186*j*.
crystalline, with boundary lattice, diffusion coalescence of pores, (5) 135*f*.
elastic, with infinite row of collinear cracks and fracture criterion, (7) 162*j*.
free flowing, bulk conveying of, (11) 288*e*.
hardness and deformation properties, at very high temperatures, (8) 199*e*.
indentation hardness and creep, (8) 200*a*.
ionic, simple, application of infrared spectroscopy to order-disorder problems in, (9) 237*f*.
inorganic, electron spin resonance studies of radiation effects in, (3) 85*g*.
mechanical activation and passivation, change of energy content of NaCl, ZnO, and copper powder as function of milling time, (4) 103*g*.
non-crystalline, physics, B (2) 61*i*.
particulate, apparatus for fluidizing beds, P (3) 72*d*.
treatment, P (5) 133*h*.
pneumatically classifying, method and apparatus, P (2) 50*a*.
pulverizing and drying, method and means, P (8) 190*b*.
reaction with liquids, process and apparatus, P (2) 45*b*.
reactivity and catalytic activity, influence of radiation, (8) 200*d*.
storage and flow, (4) 103*i*.
vacuum-cleaved, secondary electron emission, (1) 28*a*.
Sols. See *Colloids*.
Solubility, of alumina, quartz, and kaolin grog in feldspathic melts, relationship with firing temperature of mixtures, (4) 97*f*.
of hydrogen in porous polycrystalline aluminum oxide, (9) 242*h*.
measurements, in system $CaSO_4$-NaCl-H_2O at 35°, 50°, 70°C and 1 atm pressure, (2) 56*b*.
mutual, of CaO and MgO in calcined dolomite, (8) 202*j*.
of MgO and CaO in dolomites, computer program to calculate, (3) 80*j*.
of zirconium, niobium and hafnium carbides, (2) 55*g*.
of niobium carbide in γ-iron, (5) 138*e*.
of oxygen in solid iron, (10) 250*g*.
products, of di- and trimagnesium phosphates, (5) 138*f*.
of magnesium-ammonium and magnesium-potassium phosphates, (5) 138*f*.
retrograde, in semiconducting intermetallic compounds—liquidus curves in Pb-S, Pb-Se, and Pb-Te systems, (7) 167*c*.
solid, in system GaSb-GaAs, (9) 242*h*.
of tin in solution grown gallium phosphide, (4) 109*h*.

Solubility (*continued*)
of thallous bromide and silver chloride in molten nitrate solvents, (8) 207*g*.
of vanadium trioxide in melts of chlorides of sodium and potassium, (8) 207*g*.
in water, of powdered glasses, comparison of tests for, (5) 118*c*.
Solutions, borofluoride-nitrate, molten, reactions with glass, (11) 277*i*.
defect crystalline, in systems CaF_2-YF_3 and NaF-LiF-MgF_2, diffusion, (8) 194*h*.
dis-, of alkaline material, process for preventing from cement articles, P (10) 249*c*.
of lime and dolomite particles in primary glass melts, (3) 66*c*.
mechanism, of binders, (7) 165*j*.
of powder, mechanism, (5) 137*c*.
property of aged ferric oxides in sulfuric acid solution, (4) 110*f*.
effluent, and magnesium hydroxide, process for producing, P (3) 83*b*.
ex-, in alumina-rich nickel-aluminum spinels, mechanism, (5) 137*d*.
Solutions, solid. See also *Equilibrium studies*.
beta spodumene, in Li_2O-Al_2O_3-TiO_2-SiO_2 glass-ceramic, (10) 270*c*.
of boron in graphite, (4) 109*i*.
of carnallite type, method of producing, P (7) 161*a*.
Cr_2O_3, hardening of Al_2O_3, (2) 54*f*.
of cristobalite and $AlPO_4$ of cristobalite type, (4) 109*i*.
crystalline, with silicon dioxide structures as host compounds, P (1) 10*j*.
crystals, partition in growth, (8) 204*j*.
formation in U_3O_8-UO_2 transformation, (4) 109*j*.
formed by addition of selenides of rare earths to MSe selenides of face-centered cubic NaCl type, (1) 28*i*.
of GaAs-GaP, homogeneous, epitaxial growth, (7) 163*b*.
homogeneous and reproducible, of GaP-GaAs, preparation, (11) 299*c*.
of $Li_{1+x}V_2O_5 \pm \lambda$, study, (8) 208*c*.
of magnesium ferrite with magnetite, thermodynamics, (2) 58*f*.
niobium-oxygen-nitrogen, dilute, clustering of interstitials, (7) 162*h*.
orthosilicate and metasilicate, in system MnO-CoO-SiO_2, activity-composition relations, (7) 161*f*.
strontium titanate, containing niobia, dielectric properties, (9) 229*c*.
in system calcium orthosilicate-neodymium orthosilicate, (4) 109*j*.
in system Fe_3O_4-Mn_3O_4, thermodynamic properties, (4) 112*b*.
TiC-WC and TiC-WC-TaC, tungsten diffusion, (2) 59*e*.
of titanium dioxide in aluminum oxide, (1) 28*i*.
urania base, creep, (8) 192*i*.
in $ZnCdSb_2$, physical properties, (11) 299*i*.
of zirconia, formation and properties with oxides of rare earth elements, (5) 123*a*.
Sonics, method, used for controlling quality of steel casting plugs, (9) 225*h*.
methods, for nondestructive testing of model brick, (3) 80*j*.
tests in research and testing laboratory, (2) 51*e*.
ultra-, attenuation in zinc oxide at room temperature, (8) 211*e*.
delay lines, ceramic piezoelectric transducers for, (9) 229*a*.
digital, delay line, P (4) 101*a*.
dispersion of clay bodies, (3) 80*b*.
impulse method for nondestructive testing of high tension insulators, (8) 182*j*.
measurement apparatus, P (8) 188*j*.
for quality control in refractories works—possibilities, methods and aims, (2) 42*a*.
sieving, P (5) 130*f*.
study of cracks and pores distribution in sintered beryllia, (2) 59*i*.
surface-wave amplification in cadmium sulfide, (5) 139*b*.
waves, flexural, for rapid measurement of elastic properties of graphite, (2) 42*c*.
Sonolation, cuts scrap reprocessing time, (9) 228*a*.
Sorel cement. See *Cement, magnesium oxychloride*.
Sorption. See also *Absorption; Adsorption*.
of activated hydrogen on Vycor glass, (9) 218*j*.
of Congo red molecular colloids on alumina, (3) 86*h*.
physical, specificity, (1) 29*b*.
Spacecraft, radome nose for missile, and method of making, P (11) 282*j*.
Spalling. See *Refractories*.
Spark plugs, P (10) 261*g*.
with concentric radially spaced electrodes, P (7) 158*b*.
electrode, P (10) 265*g*.
with improved intensifier spark gap in center electrode, P (9) 232*e*.
moisture proof connector for, P (10) 265*c*.
with porcelain insulator protected by plasma-jet deposited refractory coating, P (1) 11*j*.
Spectra, absorption, of Mn^{2+} ion in glasses, (2) 35*j*.
Brillouin scattering, of crystalline and fused quartz and glass, (9) 217*g*.
diffuse reflectance, of monoclinic ZrO_2 as function of purity, (10) 249*g*.
electron spin resonance, of radiation-damaged inorganic crystals, B (9) 244*e*.
electronic, of BeS molecule, (1) 18*d*.
of Co^{2+} as tracer in study of fluoride and oxide ions effect on structure of liquid boric oxide, (7) 168*c*.
fluorescent emission, in II–VI compounds, (9) 239*g*.
Spectra (*continued*)
gamma, computer reduction of, for activation analysis of silicon, (2) 50*d*.
gamma-ray, peculiarities, of neutron-activated Te and CdTe crystals and activation cross sections of Te isotopes, (5) 137*e*.
infrared, of ferroelectric lithium hydrazinium sulfate, (8) 183*j*.
of GeO_2-P_4O_{10}-V_2O_5 glasses and their relation to structure and electronic conduction, (1) 3*h*.
infrared absorption, of arsenic-sulfur glasses, (5) 119*d*.
from excited states in ruby, (9) 239*i*.
of silicon dioxide, discussion, (1) 18*c*.
infrared lattice vibration, of crystalline quartz, (11) 297*g*.
infrared vibrational, of kaolin group minerals, (1) 20*d*.
luminescence, of alkaline earth halophosphate phosphors, (3) 76*c*.
Moessbauer, chemical applications, (1) 17*b*.
of ^{57}Fe in distorting spinels, (7) 166*a*.
in $Mn_xFe_{3-x}O_4$, (7) 165*j*.
of sodium trisilicate glass, (10) 252*i*.
optical, of nickel in alkali tetraborate glasses, (5) 119*i*.
of ultrashort optical pulses generated by mode-locked glass:Nd lasers, (10) 271*g*.
spin-wave, of gadolinium iron garnet, (9) 242*j*.
visible and ultraviolet absorption, of UO_2, (8) 211*e*.
X-ray L-absorption, of lanthanum in tetra- and hexaborides with imperfect lattices, (4) 112*e*.
X-ray L^{III} absorption, of lanthanum and cerium in compounds with nonmetals, (4) 108*c*.
Specific gravity. See *Density*.
Specific heat. See *Heat, capacity*.
Specific surface. See *Surface*.
Spectrochemical analysis. See *Analysis*.
Spectrography, composition determination by spark source and ion microprobe mass, (1) 13*f*.
direct current arc, for determination of trace amounts of lithium, rubidium and cesium in silicate rocks, (2) 50*i*.
infrared, of ion-exchanged type A molecular sieves, (9) 235*f*.
of Mycenaean and Minoan pottery, (11) 274*f*.
X-ray, determination of hafnium-zirconium ratio in zirconium minerals, (2) 60*c*.
of minute mineral samples, (2) 51*i*.
Spectrometric analysis. See *Analysis*.
Spectrometer, flame, using ionization current detection, P (10) 268*c*.
ion-microprobe mass, vacuum system of, (3) 81*a*.
mass, for thermochemical study of germanium oxides, (2) 58*b*.
monochromators, diffracted beam, for elimination of incoherent X-rays, (1) 13*j*.
optical apparatus for measuring the reflective and emissive characteristics of, P (1) 14*e*.
Spectrometry, absorption, practical hints, B (5) 140*i*.
atomic absorption, sensitivity of manganese determination using four solvents, (10) 267*k*.
mass, determination of stability of gaseous molybdites, tungstites, molybdates, and tungstates of Mg, Ca, Sr, and Sn, (1) 22*e*.
for investigation of refractory compounds, (8) 211*a*.
of nonstoichiometric vaporization of cadmium arsenide, (8) 202*a*.
study of lead monoxide vaporization, (1) 22*f*.
study of tin oxides vaporization, (1) 22*h*.
solid source mass, for determination of nitrogen in silicon, (4) 104*e*.
Spectrophotometry. See also *Photometry*.
atomic absorption, for trace elements in marine waters, (10) 267*j*.
atomic fluorescence, investigation of experimental parameters, (4) 104*h*.
determination, of iron in strong alkalis, (2) 51*i*.
of nickel with 1-(2-pyridylazo)-2-naphthol (PAN) and nickel and manganese, (5) 138*i*.
of thorium with Arsenazo III in organic phase after extraction with di-(2-ethylhexyl)-orthophosphoric acid, (8) 188*d*.
of trace amounts of vanadium in titanium oxide, (3) 81*e*.
of vanadium in rocks, (8) 188*f*.
ion exchange-, for determination of trace quantities of scandium in silicate rocks, (5) 131*a*.
rapid, for simultaneous determination of fluorine and chlorine in silicate rocks, (8) 188*b*.
of silicon traces by extraction method, (10) 267*i*.
Spectroscopy, atomic absorption, determination of calcium and magnesium, (1) 13*g*.
He/Ne laser Raman, (11) 289*i*.
infrared, of ammonia reactions with montmorillonite and saponite, (7) 164*a*.
application to order-disorder problems in simple ionic solids, (9) 237*f*.
for silicate examination, (11) 289*f*.
of thermal dehydration of gypsum, (8) 200*g*.
reflectance, B (1) 31*a*.
X-ray emission, for examining coordination of aluminum ions in tricalcium aluminate, (3) 64*b*.
use in characterization of thin films of aluminum oxides and hydroxides, (9) 243*b*.
Spheres, micro-, actinide metal carbide, preparation, P (4) 98*i*.
micro-, containing colloidal carbon, P (10) 259*i*.
metal oxide, method of making, P (7) 153*a*; P (8) 190*i*; P (10) 259*h*.
openly porous nuclear fuel, and method of preparation, P (8) 181*i*.
oxide gel, preparation from sols, P (3) 83*a*.
Spheres, micro (*continued*)
plutonium oxide, calcined, preparation, P (7) 153*g*.
sol, apparatus for producing, P (11) 288*f*.
of urania and other materials, preparation, P (10) 260*e*.
urania and urania-zirconia, preparation by sol-gel process, (4) 97*b*.
pelletized, dry strength, (2) 54*j*.
sphering refractory oxides, P (1) 8*f*.
spheroids, radioactive, coated with pyrolytic graphite, P (5) 125*e*.
ZrO_2, preparation and structure, (10) 271*e*.
Spheroidizing, process, with direct current plasma, (9) 234*g*.
Spinel. See also *Refractories*.
alumina-rich nickel-aluminum, mechanism of exsolution, (5) 137*d*.
chemically strengthened, leached, (5) 122*i*.
chrome, recrystallization, (11) 300*a*.
crystals, grown by Verneuil process, defects in, (8) 194*g*.
to defect NiAs structure transformation, (10) 272*a*.
distorting, Moessbauer study of ^{57}Fe in, (7) 166*a*.
formation from coprecipitated hydroxides of aluminum and magnesium, (4) 110*c*.
magnesia, method of preparing, P (5) 124*d*.
magnesium, X-ray method for defining composition, (2) 60*f*.
magnesium-zinc-titanium, containing Co^{2+} and Ni^{2+} ions, formation and color development, (11) 295*j*.
tin, formation and color development, effect of coordination preference of cations, (11) 293*h*.
titanium-tin, containing Co^{2+} and Ni^{2+} ions, formation and color development, (11) 296*a*.
Spodumene, aids fast firing, improves bodies, (9) 228*b*.
Spraying. See also *Atomization*.
apparatus, electrostatic, P (8) 174*j*.
for electrostatic coating, P (3) 65*e*.
for enameling baths and other hollow articles, P (3) 65*e*.
booths, resin film for walls, (10) 266*b*.
centrifugal, equipment, P (1) 12*d*.
-coating apparatus, P (1) 13*b*.
cooler flame, widens choice of plastics, (3) 79*j*.
electrostatic. See *Electrostatic processes*.
flame, alloy powder for, P (11) 276*d*.
for bonding ceramic and metal materials, P (9) 217*e*.
employing laser heating, P (7) 147*j*.
graphite, method to produce low friction surface, P (2) 35*e*.
high temperature, of ceramic material, P (7) 147*j*.
of powdered ceramic materials, (3) 65*d*.
rods for, P (10) 250*g*.
gun, plasma flame powder, P (5) 117*e*.
material, self-fusing flame, P (5) 117*h*.
Sputtering, apparatus, including folded flexible conveyor, P (2) 49*a*.
cathode, apparatus, including plasma-confining chamber, P (3) 77*j*.
apparatus for coating substrates by, P (3) 77*j*.
method and apparatus, P (10) 264*g*.
method and apparatus using a cylindrical cathode, P (8) 185*a*.
cathodically, magnetic thin films, P (5) 128*g*.
ferromagnetic thin film of Ni-Fe-Mo alloy, P (5) 128*f*.
for deposition of germanium films, (10) 262*c*.
of metals, wherein gas flow is confined to increase the purity of deposition, P (4) 102*h*.
reactive, dielectric properties of SiO_2 and lead tellurium oxide glass films formed by, (1) 9*g*.
preparation of tantalum oxide films, (7) 156*d*.
thin-films, of tantalum nitride, in controlled atmosphere, apparatus for, P (3) 77*b*.
Stability, of metamorphic amphiboles, the tremolite-ferroactinolite series, (10) 272*b*.
of mullite as derived from equilibria in system CoO-Al_2O_3-SiO_2, (11) 301*f*.
of orthopyroxenes with respect to pressure, temperature, and composition, (10) 272*d*.
of refractories during vacuum deoxidation of steel, (1) 7*j*.
of silicon carbide in firing processes, (4) 110*d*.
thermal, of silver selenite, (11) 302*g*.
Stabilization, cubic phase, of translucent yttria-zirconia at very low temperatures, (11) 293*i*.
of layers on selenium layer face, in photoconductive device, P (7) 157*d*.
of plutonium dioxide, P (10) 259*i*.
of semiconductor, mechanically and electrically, by lacquer and boric oxide layers, P (4) 102*g*.
of silicon semiconductor surfaces, P (11) 287*h*.
of ZrO, effects of iron group oxides, (3) 85*f*.
of high purity, (5) 123*e*.
Stains. See also *Color; Pigments*.
ceramic, P (4) 100*a*.
for ceramic glazes, P (7) 155*d*.
Standards, IEI proposed, for apparatus for testing vitreous enamel with acid and neutral liquids and their vapors, (11) 275*j*.
IEI proposed, for apparatus for testing vitreous enamel with alkaline liquids, (11) 275*j*.
for production of specimens for testing vitreous enamel, (11) 276*c*.
NBS, viscosity of standard lead-silica glass, (2) 37*i*.
National Standard Reference Data System, status report, (4) 112*h*.
Stannic oxide. See *Tin, oxide*.
Statistical analysis. See *Analysis*.
Steam. See also *Moisture; Water*.
saturated, effect on strength of stoneware, (3) 73*j*.

Steatite. See also *Talc.*
glazes for single firing at 1350°C, (2) 46*g*.
high-temperature elasticity and expansivity, (7) 174*e*.
Steels. See also *Enameling metals; Iron.*
alloy, low carbon, for vitreous enameling, P (2) 35*i*.
casting plant, continuous, steel casting and intermediate ladles for, (5) 123*f*.
corrosion mechanisms—growth and breakdown of protective films in high-temperature aqueous systems—15% NaOH at 316°C, (4) 92*b*.
disintegration, while dissolving in acids, (4) 91*i*.
glass-coated, adds edge coat, (5) 117*d*.
hot working, P (11) 281*g*.
low-carbon, porcelain enamel adherence, (10) 250*a*.
-making vessels, basic oxygen, P (4) 98*b*.
preparation, uniform, spray pickling promotes, (9) 216*h*.
sheet, deep drawing, and method for producing, P (10) 250*c*.
ground coat enameled, bubble structure, (11) 275*j*.
for porcelain enameling, (9) 216*g*.
stainless, problems in using especially in enameling industry, (10) 250*e*.
Stoichiometry, effect on thermal expansion of TaC_x, (10) 271*a*.
non-, of cadmium sulfide thin films, (1) 23*j*.
in neodymium and europium oxides in relation to interaction with oxygen and hydrogen, (8) 203*f*.
of ZrO_2, and relation to tetragonal-cubic inversion in ZrO_2, (7) 166*c*.
oxygen, in compound $BaFeO_{3-x}$, (8) 204*h*.
Stokers. See *Feeding apparatus.*
Stones. See also *Rocks.*
casting, combining with enameled metal for outdoor ashtrays, (4) 89*j*.
pottery, Fukui, properties, (5) 125*j*.
Nishiyama, effect of particle size distribution on properties, (5) 125*g*.
Stoneware, alkali-resistant, production, (3) 74*e*.
industry, glazing and engobing, (3) 70*e*.
raw materials, forming and firing in USSR, (5) 125*f*.
Rhenish, current research, (3) 63*i*.
strength, effect of saturated steam, (3) 73*j*.
Storage, of granular materials, silo or bin unit for drying, P (1) 13*a*.
for radioactive fuel elements, P (2) 45*i*.
Strains, detection in evaporated films by wavefront reconstruction, (9) 233*j*.
energy, effect on grain growth of alumina, (7) 168*a*.
evaluation in hollow glassware, (10) 252*a*.
patterns, in $GaAs_{(1-x)}P_{(x)}$ alloy overgrowths, (11) 301*g*.
rate-sensitivity, and serrated yielding, (11) 300*h*.
residual, determination in vitreous enamel coatings, (11) 276*a*.
sheer, diffraction contrast from coherent phases, (8) 194*d*.
Stratifiers. See *Concentrators; Separators.*
Strength, bending, of glass-ceramics of system $CaO \cdot Al_2O_3 \cdot 2SiO_2$-$2MgO \cdot 2Al_2O_3 \cdot 5SiO_2$-$CaO \cdot TiO_2 \cdot SiO_2$, effect of B_2O_3 on improvement, (7) 140*b*.
of biaxially prestressed ceramic plates after nonuniform heating, (1) 29*g*.
compressive, of refractory materials for furnace and kiln construction, importance, (8) 179*j*.
relation between modulus of rupture and, in fired clay products, (2) 40*f*.
concrete, core and cylinder, of natural and lightweight, (7) 146*j*.
cube and cylinder, of concrete, influence of testing machine characteristics, (11) 275*e*.
dielectric, (11) 284*j*.
dry, of pelletized spheres, (2) 54*j*.
equations for fiber-reinforced composites, (1) 2*g*.
of fused portland cements as function of composition, (10) 248*h*.
of fused silica, (9) 218*a*.
glass, improvement from SO_3 treatment, (1) 4*g*.
statistical theory, (1) 4*f*.
of hemihydrate plaster, (10) 248*k*.
of high-melting point materials, temperature effect, (3) 71*j*.
high-temperature, of magnesite brick, effect of silicate constitution, (9) 224*b*.
impact, of diamond under different rates of strain, (8) 199*h*.
influence of composition and structure on, of alloys of WC-Co and TiC-WC-Co systems, (1) 19*e*.
mechanical, of cylindrical porcelain insulators and bushings, ways and means to increase, (2) 46*h*.
of electrotechnical porcelain, effect of quartz, (10) 261*f*.
of fused rock at high temperatures, (5) 123*e*.
of hot-pressed alumina, (7) 168*i*.
relation between macroscopic shear moduli and micromechanical shear stress concentrations, (7) 167*i*.
of silica and alumina powders, (3) 74*d*.
of prepacked concrete and reinforced prepacked concrete beams, (7) 147*a*.
of silver-alumina alloys above melting point of silver, (4) 110*i*.
study of ceramic grinding wheels, (5) 115*f*.
tensile, of cement paste, determination by centrifugal force, discussion, (2) 34*c*.
theoretical, of perfect crystals, (8) 209*e*.
of vitreous china bodies, improvement, (3) 74*e*.
of whiteware bodies containing alumina and silica, comparison, (8) 182*h*.
Strengthening, chemical, of Li_2O-Al_2O_3-SiO_2, glass-ceramics, (4) 92*h*.
chemical, of nepheline glass-ceramics, (3) 65*j*.
of stuffed β-quartz glass-ceramics, (5) 118*h*.
chemically, glass, P (8) 177*i*.
glass cathode-ray display tube, P (5) 121*a*.
glass objects, methods, P (7) 150*f*.
of hollow glass objects, P (3) 69*f*.
of sapphire with precipitates, (4) 110*j*.
two-stage, of glass, mechanism, (10) 252*e*.
Stresses, analysis in hermetic compression seals, (1) 4*h*.
analysis, photoelastic, on bonded interface of strip with different end configurations, (7) 159*a*.
compressive, high uniaxial, effects on glass, (8) 175*b*.
concentrations, micromechanical, in two-phase brittle-matrix ceramic systems, (9) 240*i*.
distribution, in hermetic compression seals, (7) 156*c*.
in multiphase systems: I, composites with planar interfaces, (11) 301*h*.
external, in ferrite head of video tape recorder, induces Barkhausen noise, (11) 284*d*.
flow, relation to dislocation density in materials deforming by Peierls-Nabarro mechanism, (10) 271*g*.
in glass, caused by ultraviolet radiation: II, in borosilicate glasses; III, buildup in commercial glasses; IV, effect of gamma and ultraviolet radiation commercial borosilicate glasses, (7) 148*e–h*.
in internally stressed circular opening in biaxial stress field, (1) 26*g*.
measurement in fired enamels, (10) 249*j*.
measurements, and significance in enameling, (3) 65*f*.
mechanical, during oxidation of copper, and influence on oxidation kinetics, (7) 165*i*.
micromechanical shear, concentrations, relation with macroscopic shear moduli, of multicomponent materials, (7) 167*i*.
moisture, in unfired ceramic clay bodies, (7) 166*a*.
normal, in compressed glass lead-through seals, photoelastic investigation, (10) 253*c*.
resistance, thermal, of brittle ceramics involving creep, approximate theory, (10) 270*d*.
in seals of molybdenum foil to silica glass, (5) 126*i*.
in silicon monoxide films, (7) 167*j*.
surface-scratch, in ground glass, (10) 253*d*.
Strontium, aluminate, luminescent europium activated, P (3) 78*c*.
aluminosilicates, synthetic, hydrothermal chemistry, (8) 199*g*.
barium-, titanate, mixed crystals, net pattern, (8) 203*e*.
carbonate, anhydrous, heats and free energies of formation, (1) 19*a*.
cements, (7) 147*c*.
chlorides, saturated vapor pressure, (7) 167*e*.
fluorapatite, radioactive ceramic source, method of manufacture, P (10) 270*b*.
isomorph of colemanite, process for preparation, P (10) 269*i*; P (11) 291*h*.
molybdites, tungstites, molybdates, and tungstates, mass-spectrometric determination of stability, (1) 22*e*.
oxide, systems. See *Systems.*
systems. See *Systems.*
titanate, electrocaloric effect, (8) 196*g*.
microscopic examination at low temperatures, (5) 137*g*.
solid solutions containing niobia, dielectric properties, (9) 229*c*.
thermal conductivity, (9) 242*g*.
values, separating from rare earth metal values, P (2) 54*d*.
Structural clay products. See also *Brick; Pipe; Tile.*
application of LPG, (11) 290*b*.
chemical reduction during firing, (9) 222*k*.
grouts, P (7) 150*h*.
from hand setting to automatic setting, (10) 256*f*.
heat-resistant, P (3) 64*e*.
heavy, automation of production line, (3) 70*b*.
lightweight, method for making, P (7) 150*i*.
manufacture, P (11) 280*b*.
with inclusion of fibers, P (5) 122*c*.
microstructure, (7) 150*j*.
prefabricated panels, (7) 150*k*.
scumming in, reactivity of barium carbonate in combating, (10) 256*f*.
setter bridge between dryer and tunnel kiln, (10) 256*e*.
yearbook 1966, B (1) 31*i*.
Structural clay products industry, automated roofing tile plant, (1) 6*k*.
automation of production line, (3) 70*b*.
blocks, 8 x 8 x 16 in., from brick mix at Higgins, (4) 95*j*.
Broad River leaps ahead with new Blacksburg plant, (9) 222*g*.
Carolina Lightweight Aggregate Co., Inc. builds model plant, (1) 6*h*.
color in, (11) 279*j*.
firing, 1950–64, (11) 270*j*.
French, use of natural gas, (5) 122*a*.
heavy, reduction of waste and rejects, (3) 70*g*.
modernization of small plants, (3) 80*a*.
Moland-Drysdale, builds modern addition, (9) 223*a*.
Pacific Clay Products at California, (4) 96*a*.
Port Costa, product diversification, (4) 96*b*.
review of U.S. brick and pipe machines and terminology, (11) 279*j*.
stoneware pipe, manufacture at Karl Leimer Akt.-Ges., (3) 70*a*.
Structural materials. See also *Aggregates; Brick; Building materials; Cement; Concrete; Enameled ware; Glass; Insulation, thermal; Masonry; Structural clay products.*
ceramics, moisture expansion: I, unrestrained, (5) 122*a*.
Structure, band, of doped $LaInO_3$, (9) 229*e*.
of BaO-P_2O_5 glasses, effects of residual water, (7) 148*g*.
change of precipitated ferric oxide during aging in water, (4) 111*b*.
of CoO, and temperature factors, (7) 168*e*.
of crystals. See *Crystals.*
defect, of HfO_2, (7) 163*b*.
of oxygen deficient $BaTiO_3$, (10) 270*g*.
of $(0.13YO_{1.5}$-$0.87ThO_2)$ electrolyte, (5) 135*f*.
defects, in epitaxial films, role in nucleation, (10) 263*h*.
in tungsten trioxide, influence of minor additions of tantala or niobia, (7) 168*a*.
electronic, of disordered materials, (11) 295*c*.
of TiO and NiO, (7) 163*g*.
equilibrium domain, of $BaTiO_3$, (11) 295*g*.
of glass, (2) 37*d*.
of glasses, B (9) 245*j*.
glazed, P (2) 46*d*.
influence on solid state reactions, (8) 200*f*.
ionic, of metasilicate glasses, (2) 38*a*.
micro-, of ceramic materials: II, heavy clay products, (7) 150*j*; III, forms of silica, (8) 180*f*; IV, whiteware, (9) 228*e*.
control in single phase oxide ceramics, (4) 103*c*.
of high permittivity ceramics, (7) 155*i*.
of magnesium oxide cleavage surfaces, (1) 23*c*.
physical properties of glass-ceramics and their relation to, (2) 36*e*.
role in metals, B (4) 113*f*.
of single-crystal titanium diboride, (11) 298*i*.
of stabilized and partly stabilized zirconia, (3) 86*i*.
microstructural variations with electric field in barium-strontium titanate ceramics, (7) 156*a*.
model, and application to silicates chemistry, (4) 110*j*.
of niobium nitrides, (4) 110*a*.
of NiO, and temperature factors, (7) 168*f*.
nonmetallic, radiation stability, (3) 87*i*.
of nonstoichiometric compounds, (10) 270*k*.
perovskite-like, of new compounds, (8) 203*h*.
properties, of oxidized titanium films, (1) 24*a*.
of titania-containing polycrystalline semiconductors, correlations with electrical properties, (1) 9*i*.
quartz, role of impurities, (8) 206*c*.
shear, of $WO_{2.88}$, a tungsten oxide, (8) 206*h*.
structural conversions, in two- and multicomponent glasses, (10) 253*b*.
structural investigation of $PbTiO_3$-$BaZrO_3$, (9) 230*c*.
Sublimation, of graphite, in simulated reentry environments, (5) 123*f*.
Substrates, ceramic, for electrical circuits, method for manufacturing, P (9) 231*f*.
dendritic, method of producing crystalline semiconductor material on, P (11) 286*h*.
foreign, single crystal silicon epitaxy, (1) 28*e*.
glass, for connector, P (2) 47*b*.
high resistance, for forming diode, P (5) 127*j*.
sodium chloride, growth of face-centered-cubic metals, (1) 19*j*.
-temperature measurement and control, (3) 76*i*.
Sulfates, alkali, and boric acid, separately crystallizing from aqueous solution by evaporation at different temperatures, P (11) 292*e*.
determination in presence of soluble silicate, (5) 130*j*.
-ferrite melts, miscibility gap at 1500°C, (3) 86*j*.
high temperature properties and decomposition, (5) 136*d*.
inorganic, radiation-induced decomposition, B (9) 244*f*.
role in producing efflorescence and salt retention in clay products, (2) 40*e*.
systems. See *Systems.*
thermal decomposition, for manufacture of ferrite powders, (10) 262*g*.
Sulfides, alkali copper-iron, djerfisherite—a new mineral from enstatite chondrites, (1) 15*d*.
meteoritic, niningerite, (4) 106*j*.
minerals, oxidation rates by aqueous oxidation at elevated temperatures, (3) 82*e*.
of rare-earth metals and actinides, crystal-chemical properties, (3) 84*h*.
speed flint glass fining, (9) 218*h*.
spot test detection in minerals, (8) 188*g*.
tri-, of barium and tantalum, titanium and zirconium, (11) 303*a*.
Sulfite liquor, waste, use as slurry diluent and cement plasticizer, (9) 215*f*.
Sulfur, burning, from slag glasses, (5) 118*a*.
dioxide evolution, for determination of sulfur in glass, at high temperatures, (7) 148*e*.
in glass, determination by sulfur dioxide evolution at high temperatures, (7) 148*e*.
-selenium, pressure-induced phase, (3) 87*g*.
trioxide, treatment to strengthen glass surfaces, (1) 4*g*.
transfer from low to high chemical potential through ionic membrane, (3) 88*c*.
Sulfuric acid, process, for decomposition of xenotime, (3) 82*g*.
Supersonics. See *Sonics.*
Surface, adsorption, (1) 26*g*.
area, effect on viscosity of dilute suspension of H-clays, (4) 107*g*.
of finely divided substances, method and apparatus for determining by gas adsorption, P (4) 104*i*.

Surface (*continued*)
area determination, by X-ray diffraction technique, (5) 131*j*.
cleaning method and composition, for glass-lined equipment, P (1) 3*d*.
composition of porous glass, (1) 4*i*.
of fine particles, properties with special reference to specific surface, (11) 299*g*.
finish, effect on temperature distribution in optically pumped Nd^{3+}:glass laser rods, (5) 135*j*.
finishes for boron filaments, (1) 2*j*.
flat, nominally, elastic contact of, (11) 293*a*.
glass, strengthening by SO_3 treatment, (1) 4*g*.
treatment with polymers of alkali metal vinyl siliconates, P (1) 6*e*.
low friction, method of flame spraying graphite to produce, P (2) 35*e*.
oxide, recombination of oxygen: II, catalytic activities of alkali metal tungsten bronzes, (1) 27*f*.
phenomena, B (8) 212*d*.
in metallic systems and technological applications, (10) 250*h*.
in silicate minerals, chemical interpretation, (4) 107*e*.
properties, of precipitated alumina: V, radiochemical investigation of chloride-ion contamination, (2) 57*a*.
of silicate minerals, (4) 111*d*.
of zinc oxalate, (8) 209*h*.
role in ceramics, B (2) 60*j*.
roughening, of coated body, P (1) 13*a*.
roughness of ceramics, (9) 228*c*.
rugous and abrasive, method for producing, P (5) 115*g*.
self-diffusion, B (9) 245*e*.
specific, of ceramic materials, significance and measurement, (5) 129*i*.
of nonuniformly shaped substance, determining by measuring adsorption of noble or inert gases, P (5) 132*b*.
temperature measurement and control, (7) 160*c*.
tension, of glass. See *Glass*.
topography, characterization with scanning electron microscope, (9) 233*j*.
Surface-active substances, action on pulverized ceramic materials, (5) 133*j*.
Surfactants. See *Surface-active substances*.
action of surfactants on pulverized materials, (5) 133*j*.
aqueous, of aluminum oxide and process for production, P (8) 190*c*.
containing kaolins of varying degrees of crystallinity, flow properties, (5) 136*e*.
dewatering, P (2) 50*b*.
aqueous clay, effect of alkali tannides, (7) 162*d*.
process for manufacture, P (9) 233*b*.
clay. See *Clays*.
dewatering apparatus, P (2) 49*i*.
effect, (5) 138*i*.
graphite, (3) 86*b*.
kaolin-water, with additions of basic aluminum chloride complex, electrophoretic mobility, (7) 154*h*.
liquid, of argillaceous raw materials, methods of homogenizing, P (2) 54*f*.
pumping, P (1) 13*a*.
rheological characteristics, determination, (9) 233*j*.
set plaster, relation between structure and strength, (9) 215*f*.
silica, adsorption and flocculation behavior, effect of solid content, (8) 195*i*.
amorphous and sized crystalline, flocculated by high polymers, filtration of, (8) 198*a*.
of silicate layer minerals and products made, P (9) 236*h*.
Swelling. See *Expansion*.
Switches, encapsulated thermostatic with shunt, P (1) 10*c*.
sealed, method and apparatus for making, P (2) 39*e*; P (9) 220*h*.
thermostatic, P (1) 12*b*.
Symmetry, of crystals. See *Crystals*.
Symposiums, on high temperature technology, B (5) 139*i*.
on local atomic arrangements studied by X-ray diffraction, B (9) 245*g*.
on materials sciences, B (9) 245*c*.
on materials sciences: Vol. 2, B (8) 212*d*.
refractories, (5) 123*b*.
Synthesis, of aluminum silicate whiskers, P (9) 227*h*.
of colored quartz, (4) 111*c*.
diamond, from liquid carbon, flash heating apparatus for, P (10) 266*h*.
of fibrous potassium titanate by flux evaporation method, (1) 29*g*.
of GaAs by vapor transport reaction, (9) 242*c*.
of glasses in system V_2O_5-CdO-P_2O_5, (8) 176*i*.
of $HfSiO_4$, (11) 301*d*.
high pressure, of arsenopyrite-type ternary compounds, (7) 164*c*.
of $YGaO_3$, $GdGaO_3$ and $YbGaO_3$, (8) 199*d*.
hydrothermal, crystallization conditions of fibrous amphibole in, (10) 272*g*.
of montmorillonite group minerals from kaolinite, quartz, and various carbonates, (1) 19*d*.
of PbO-V_2O_5 system, (5) 138*i*.
low temperature, of compound semiconductors, P (7) 156*h*.
of minerals of aluminophosphate group, (8) 208*g*.
of mordenite, P (10) 260*j*.
of new compounds having hauynite structure, (8) 208*f*.
of titanium nitride from sponge titanium and nitrogen or ammonia, (5) 139*a*.
Synthesis (*continued*)
of uranium monophosphide by phosphine reaction, (8) 208*h*.
Systems. See also *Equilibrium studies*.
AlCl$_3$-TlCl, (11) 301*e*.
alumina-lanthanum oxide, phase diagrams of nonreactive mixtures with molybdenum, (1) 25*a*.
Al_2O_3-SiO_2, macroliquation, (9) 240*j*.
Al_2O_3-Ti_2O_3, phase equilibria preliminary study, (1) 27*a*.
AlN-Al, sintering in nitrogen, (7) 152*i*.
$BaCl_2$-$BaWO_4$, phase diagram, (11) 301*j*.
barium chloride-potassium chloride, phase diagram, (1) 25*f*.
BaO-BeO, interactions, (4) 108*i*.
BaO-BeO-SiO_2, interactions, (4) 108*i*.
BaO-CO_2, in pressure range 0.01 to 450 atmospheres, (8) 191*b*.
BaO-$YTaO_4$-B_2O_3, phase equilibria and crystal growth, (8) 204*h*.
BaO-ZrO_2-SiO_2, at subsolidus temperatures, study, (5) 138*e*.
Ba_2SiO_4-Mg_2SiO_4 and Ba_2SiO_4-Ca_2SiO_4-Mg_2SiO_4, study of weakened fluoberyllate models of, (1) 29*c*.
$BaTiO_3$-$CaTiO_3$, dielectric aging and microstructure in, (1) 9*g*.
$BaTiO_3$-$KNbO_3$, phase transitions, (3) 76*f*.
BeO-Al_2O_3-SiO_2, investigations in high-silica region, (4) 109*j*.
binary, $3CaO \cdot Al_2O_3$-$Na_2O \cdot 8CaO \cdot 3Al_2O_3$ within system CaO-Al_2O_3-Na_2O, (3) 84*d*.
bismuth oxide-germanium dioxide, (7) 168*e*.
Bi_2O_3-MoO_3, (11) 301*e*.
Bi_2Te_3-Bi_2Se_3, (8) 108*b*.
CdO-P_2O_5, phase equilibria and manganese-activated luminescence, (7) 166*i*.
calcium aluminate-alumina, phase diagrams of nonreactive mixtures with molybdenum, (1) 25*j*.
$CaCl_2$-NaCl and $CaCl_2$-KCl, study by capacitance method, (11) 301*j*.
CaF_2-AlF_3, phase equilibria, (8) 204*j*.
CaF_2-Al_2O_3, phase equilibrium and chemical reactions, (1) 25*g*.
CaF_2-YF_3, diffusion in defect crystalline solutions in, (8) 194*h*.
calcium molybdate-rare earth niobate, study, (4) 110*e*.
calcium orthosilicate-neodymium orthosilicate, solid solutions, (4) 109*j*.
CaO-Al_2O_3-SiO_2, mineral formation in presence of gypsum and CaF_2, (9) 215*a*.
CaO-CO_2-H_2O, phase equilibria, with implications for crystal growth of calcite and apatite, (2) 55*e*.
CaO-Cr_2O_3-Al_2O_3-SiO_2, subsolidus structure, (5) 138*f*.
CaO-Dy_2O_3, (2) 57*a*.
CaO-HfO_2, (1) 21*f*.
CaO-MgO-CO_2-H_2O, melting relations with petrological applications, (1) 22*h*.
CaO-MgO-Cr_2O_3-Al_2O_3, subsolidus structure, (5) 138*f*.
CaO-MgO-Cr_2O_3-SiO_2, subsolidus structure, (5) 138*f*.
CaO-Yb_2O_3, phase equilibria, (1) 25*a*.
2CaO-SiO_2-CaF_2, (4) 111*f*.
2CaO-Fe_2O_3-MgO, phase diagram, (1) 25*k*.
$CaSO_4$-$CaSO_4 \cdot 2H_2O$, phases, (5) 116*i*.
$CaSO_4$-NaCl-H_2O, solubility measurements, at 35°, 50°, 70°C and 1 atm pressure, (2) 56*b*.
Ca_3WO_6-Sr_3WO_6, phase transition, (9) 241*d*.
CsBr with LiBr, KBr, and RbBr, (11) 293*f*.
Cs_2CO_3(Cs_2O)-V_2O_5, phase diagram, (4) 109*b*.
Cs_2CrO_4-PbCrO$_4$, Cs_2MoO_4-PbMoO$_4$, and Cs_2WO_4-PbWO$_4$, (11) 302*a*.
chlorides and bromides of sodium and cadmium, (8) 108*c*.
chromium oxide-silica, at low oxygen pressures, (3) 83*i*.
clay–water. See *Clays*.
$CoNb_{2-x}Ta_xO_6$, composition dependent order-disorder phenomena, (9) 237*b*.
CoO-Al_2O_3-SiO_2, stability of mullite, (11) 301*f*.
CoO-P_2O_5, compound formation and phase-equilibrium relations, (1) 17*e*.
CsCl-WCl_6 and CsCl-WCl_5, (1) 29*i*.
CuO-Cu_2O-CaO, equilibrium relations, (1) 18*f*.
CuO-Cu_2O-ZrO_2, equilibrium relations, (1) 18*g*.
dioxides of elements Th through Am, reactions with Nb_2O_5 and Ta_2O_5, (8) 206*c*.
dolomite-containing, oxygen isotope fractionations in, (1) 24*f*.
fused salt, $CaCl_2$-CaO, solubilities, metal content, and freezing points, (11) 292*i*.
GaSb-GaAs, solid solubility, (9) 242*h*.
germanium and gallium arsenide, pseudobinary phase diagram, (9) 241*b*.
Ge-I_2-inert gas, transpiration studies, (9) 242*j*.
GeO_2-Al_2O_3, phase equilibria, (7) 166*i*.
HfO_2-WO_2-WO_3, condensed phase relations, (5) 134*f*.
In-As-Se, (8) 208*f*.
In-InCl$_3$, fusibility diagram, (4) 108*a*.
In-InCl$_3$, vapor pressure, (4) 112*b*.
In-Sb-Zn, (4) 111*g*.
In^{3+}, H^+ ||S^{2-}, ReO_4^-, study of coprecipitation, (1) 29*i*.
InTe-InBi, quasi-binary, (8) 205*j*.
Fe-C-V, influence of vanadium on activity of carbon at 1000°C, (7) 164*h*.
FeO-Al_2O_3, phase diagram, (11) 299*b*.
ferric oxide-water, (8) 108*d*.
FeO-Fe_2O_3-ZrO_2-SiO_2, phase relations, (4) 109*g*.
Fe_2O_3-Fe_2O_3, continuous transitions, (7) 162*i*.
Fe_2O_3-Mn_3O_4, solid solutions in, thermodynamic properties, (4) 112*b*.
Systems (*continued*)
iron(II) oxide-calcium oxide-magnesium oxide, as basis for slagging of dolomite determination, (3) 64*e*.
La_2O_3-Al_2O_3, alumina-rich, liquidus in, (4) 108*e*.
La_2O_3-Gd_2O_3-Y_2O_3, ternary, luminescence of europium, (9) 240*h*.
La_2O_3-HfO_2, (8) 108*g*.
PbO-TiO_2-ZrO_2, phase equilibrium, (4) 109*f*.
PbO-V_2O_5, syntheses and X-ray studies, (5) 138*i*.
$PbTiO_3$-$BaZrO_3$, structural and dielectric investigation, (9) 230*c*.
LiAlCeO$_4$-ZnGeO$_4$, (8) 208*i*.
lithium-carbon and lithium-boron, compound formation, (11) 292*i*.
LiF-Nb_2O_5, phase analysis studies, (8) 204*d*.
LiI-KI, (2) 57*e*.
Li,K,Pb || Cl,Br, (8) 208*i*.
Li,Na || F,Cl, (8) 209*a*.
MCl-$CrCl_3$ (M = alkali metals), complex formation, (9) 237*j*.
$MgAl_2O_4$-LaAlO$_3$, (8) 209*b*.
$MgAl_2O_4$-$MgCr_2O_4$-$MgFe_2O_4$, X-ray study, (2) 60*f*.
$MgAl_2O_4$-$MgFe_2O_4$-Ca_2SiO_4, $MgAl_2O_4$-$MgFe_2O_4$-$MgCr_2O_4$-Ca_2SiO_4, $MgAl_2O_4$-$MgCr_2O_4$-$Ca_3MgSi_2O_8$, phase-equilibrium relationships, ▲ (4) 109*c*.
MgO-Al_2O_3-SiO_2-H_2O, phase relations of chlorites in, (1) 26*b*.
MgO-GeO_2-LiF, ternary phases, (9) 242*g*.
MgO-GeO_2-MgF_2, subsolidus equilibria, (1) 29*g*.
MgO-FeO-Fe_2O_3, phase equilibria, 1300°C isothermal section and extrapolations to other temperatures, (7) 166*j*.
Mg_2Si-Mg_2Sb_2, (1) 22*j*.
$MgSiO_3$-$CaMgSi_2O_6$, (2) 57*f*.
Mg_2Sn-Mg_2Sb_2, (1) 23*a*.
Mn_2O_3-Mn_2O_4-O_2, equilibria, (9) 239*c*.
MnSe-MnS, (4) 111*i*.
MnSi-Si, phase components, (3) 87*a*.
Mo-Sb, (2) 57*b*.
Mo-As, (2) 57*b*.
Mo-Bi, (2) 57*b*.
$MoCl_4$-$AlCl_3$-NaCl, (1) 29*g*.
Mo-Re-C, X-ray study of alloys in, (2) 60*f*.
multicomponent, phase diagrams, geometric methods, B (5) 140*h*.
phase diagrams, transformation of index of barycentricity of, (11) 302*h*.
of nine salts of types A and B, determination of degrees of stable diagonals, (11) 293*j*.
NiSb-Ni_2Sn_2, study of melts, (4) 110*h*.
$NiNb_{2-x}Ta_xO_6$, composition dependent order-disorder phenomena, (9) 237*b*.
NiO-P_2O_5, compound formation and phase equilibrium relations, (1) 17*e*.
Nb-Si, (2) 57*b*.
NbO_2-CrO_2, rutile-type phases, (5) 138*b*.
NbO_2-MoO_2, rutile-type phases, (5) 138*b*.
Nb_2O_5-Ta_2O_5, (8) 209*c*.
Nb_2O_5-WO_3, phase equilibria as related to crystal structure, (2) 55*b*.
β-Nb_2O_5-WO_3, double oxides, (11) 293*c*.
oxide-fluoride, of potassium, zirconium and boron, (8) 204*f*.
oxide, high-temperature chemistry of, B (3) 88*e*.
structural interpretation of immiscibility: IV, occurrence, extent and temperature of monotectic, (2) 56*a*.
periclase-wustite, phase changes during heating in air, (2) 55*a*.
phase diagram, of cobalt monoxide at high temperatures, (7) 166*h*.
$KAlF_4$, equilibria, (1) 18*e*.
$KAlSiO_4$-Mg_2SiO_4-$KAlSi_2O_6$, (5) 139*c*.
KF-BeF_2, (11) 301*g*.
KI-RbI, and KI-CsI, (11) 302*c*.
potassium metaphosphate-calcium metaphosphate, (8) 209*d*.
K_2SO_4-K_2O-SiO_2, miscibility gap at 1300°C, (7) 165*h*.
protactinium pentoxide-rare earth oxide, fluorite phases, (11) 295*i*.
quaternary reciprocal, of chlorides and bromides of lithium, sodium and potassium, (7) 167*b*.
of fluorides and chlorides of lithium, potassium and calcium, cross sections, (4) 107*f*.
of fluorides and chlorides of lithium, sodium and barium, cross sections, (11) 293*e*.
reciprocal, of bromides and iodides of potassium and lead, (7) 167*h*.
of chlorides and bromides of lithium and silver, (1) 27*b*.
of chlorides and bromides of lithium and sodium, (1) 27*c*.
of chlorides and sulfides of tin and lead, (1) 27*e*.
fused-salt, involving monovalent liquid nitrates, thermochemical study, (8) 210*b*.
possible types from 12 salts A,B,C||X,Y,Z,T (11) 299*a*.
of pyrophosphates and molybdates of lithium and potassium, (11) 300*j*.
sixfold, new types of singular stars, (8) 203*c*.
sixfold, of 12 salts L,N,H||X,Y,Z,T, degrees of stable diagonals, (11) 293*j*.
stable cross sections of fluorides and chlorides of lithium, sodium, and potassium, (1) 29*e*.
RbCl-WCl_6, RbCl-WCl_5, (1) 29*i*.
Rb_2CrO_4-PbCrO$_4$, Rb_2MoO_4-PbMoO$_4$, Rb_2WO_4-PbWO$_4$, (11) 302*a*.
RbI-CsI, (11) 302*c*.
$SmCl_3$-KCl and $SmCl_2$-KCl, fusibility diagram (7) 163*i*.
$SmCl_3$-Sm, (1) 29*i*.
$ScCl_3$-Sc, (1) 29*h*.
Sc_2O_3-B_2O_3, (2) 57*a*.
silicate, multicomponent, computation and plotting of liquidus isotherms, (7) 162*i*.

Systems (*continued*)
SiO_2-Al_2O_3-CaO, ternary, viscosity of liquid slags in, (2) 56*d*.
(64% SiO_2 + 36% CaO)-CaF_2, phase diagram, (1) 25*f*.
silver-antimony, thermodynamic study, (4) 112*c*.
silver-tellurium, phase relations, (1) 26*e*.
sodium aluminate-alumina, liquidus of, phase diagrams of nonreactive mixtures with molybdenum, (1) 25*i*.
Na_3AlF_6-Li_3AlF_6, equilibrium, reinvestigation, (9) 241*j*.
NaBr-RbBr and NaI-RbI, (11) 302*c*.
NaF-LiF-MgF_2, diffusion in defect crystalline solutions in, (8) 194*h*.
sodium iodide-potassium chloride, molten, diffusion, (8) 194*i*.
Na_2MoO_4-$CsMoO_4$, (11) 301*g*.
$(1-x)NaNbO_3$-$xKTaO_3$, (4) 111*h*.
$Na(Nb_{1-x}Ta_x)O_3$, studies, (5) 138*c*.
Na_2O-Al_2O_3-Fe_2O_3-SiO_2, at 1 atmosphere and petrogenesis of alkaline rocks, (2) 57*h*.
Na_2O-Fe_2O_3, new compound, (3) 87*b*.
Na,K||$AlCl_4$,Ta(Nb)Cl_5, thermal investigation, (2) 58*j*.
Na,Tl,Pb||I, (11) 301*h*.
spinel-silicate, phase-equilibrium relations: II, pseudosystems $MgAl_2O_4$-$MgCr_2O_4$, $MgFe_2O_4$-$MgCr_2O_4$-CaMgSiO$_4$, $MgAl_2O_4$-$MgFe_2O_4$-CaMgSiO$_4$, and $MgAl_2O_4$-$MgFe_2O_4$-$MgCr_2O_4$-CaMgSiO$_4$, (1) 25*i*.
$SrFeO_3$-$BiFeO_3$, electrical and magnetic properties, (1) 9*i*.
$Sr(FeTa)_{1/2}O_3$-$SrTiO_3$, phase transition, (9) 241*b*.
SrO-Al_2O_3-ZrO_2, subsolidus structure and fusibility diagram, (7) 168*d*.
SrO-B_2O_3, portion, phase boundaries in, (3) 87*j*.
SrO-ZrO_2, structure, (7) 168*d*.
strontium-sodium-cesium, montmorillonite exchange equilibria with, (1) 23*c*.
Ta-Bi, (2) 57*b*.
Ta-C, isolation of zeta phase, (3) 86*a*.
Ta-C, phase components, (4) 109*a*.
tantalum-selenium, variable composition phases, (11) 303*b*.
tantalum-sulfur, (5) 139*c*.
Ta-Ta_2O_5, (8) 209*d*.
tellurium-tellurium dioxide, study, (4) 111*c*.
ternary, of bromides of potassium, lithium and lead, (2) 57*f*.
of transition metals of groups IV and V and carbon, phase equilibria, (8) 205*a*.
ternary reciprocal, of fluorides and chlorides of lithium and potassium, (2) 57*f*.
TlCl-$TlCl_3$, (11) 301*i*.
thorium-carbon, phase equilibria, (1) 25*b*.
Th-U-C, high-temperature phase equilibria, in the presence of free carbon, (5) 136*a*.
SnO_2-IrO_2, in air, phase relations, (11) 299*d*.
SnS-PbS, X-ray investigation, (9) 243*c*.
Sn-Te, in region of compound SnTe, (11) 301*h*.
TiC-Ni-Cr, quasiternary, 1200°C isothermal section of phase diagram, (8) 210*i*.
TiO_2-IrO_2, in air, phase relations, (11) 299*d*.
TiO_2-NbO_2, rutile-type phases, (5) 138*b*.
TiO_2-MoO_2, rutile-type phases, (5) 138*b*.
with TiO_2 and prospects of use in new technology, (11) 302*d*.
W-Sb, (2) 57*b*.
W-As, (2) 57*b*.
W-Bi, (2) 57*b*.
W-O, $WO_{2.9}$, new phase with shear structure in, (2) 55*b*.
tungsten-rhenium-carbon, X-ray diffraction study, (5) 139*d*.
two-phase brittle-matrix, micromechanical stress concentrations, (9) 240*i*.
U-C-O, ternary diagram, (7) 168*i*.
U-Gd-C, high carbon portion, (7) 164*c*.
UN-UP, pseudobinary, phase studies, (3) 71*c*.
uranium-nitrogen, phase equilibria, (2) 56*h*.
uranium oxide-molybdenum, structure, (8) 207*j*.
UO_2-ThO_2, studies on sintered body: III, phase relations in system UO_2-ThO_2-O, (9) 242*a*.
uranium-oxygen, high temperature X-ray study in controlled atmosphere, (1) 19*c*.
V_2O_3-Cr_2O_3, crystallographic and magnetic properties (11) 293*g*.
V_2O_3-V_2O_5, phase diagram and magnetism, (5) 137*g*.
V_2O_5-SiO_2, investigation, (1) 20*d*.
V_2O_5-ThO_2, (1) 29*h*.
V_2Si-V_2Ge, (11) 301*j*.
YbCl$_3$-KCl and YbCl$_2$-KCl, fusibility diagram, (7) 163*i*.
YCl$_3$-NaCl, fusibility diagrams, (4) 107*b*.
YCl$_3$-KCl, fusibility diagrams, (4) 108*b*.
YCl$_3$-Y, (1) 29*i*.
Y_2O_3-V_2O_5, (8) 209*f*.
Zn-Sb-CdSb, diagram of pseudobinary cross section, (11) 293*a*.
ZnO-CdO-P_2O_5, summary, phase equilibria and manganese-activated luminescence, (7) 166*i*.
ZnO-MgO and ZnS-MgS, X-ray investigation, (9) 243*b*.
$Zn_2P_2O_7$-$Cd_2P_2O_7$, phase equilibria and manganese-activated luminescence, (7) 166*i*.
$Zn(PO_3)_2$-$Ca(PO_3)_2$-$Mg(PO_3)_2$, portion, phase equilibria and manganese-activated luminescence, (3) 87*a*.
Zn-S, phase of variable composition, (11) 299*h*.
zirconium-chromium-carbon, phase equilibria, (10) 271*h*.
$ZrCl_4$-$MgCl_2$-KCl, (11) 302*a*.
zirconium-molybdenum-carbon, ternary, phase equilibria, (10) 271*i*.

Systems (*continued*)
zirconia-alkaline-earth oxides, refractory compounds having structures derived from perovskite structure in, (1) 28*d*.
ZrO_2-MgO, phase relations, (7) 166*j*.
zirconia-scandium oxide, comparison with other AO_2-M_2O_3 systems, (2) 56*f*.
ZrO_2-WO_2-WO_3, condensed phase relations, (5) 134*f*.
Zr-P and Zr-As, new phases, (10) 271*g*.
Zr-W-C, phase equilibria, (8) 204*j*.
Zr-ZrO_2, diffusion coefficients and anion vacancy concentrations, (11) 293*b*.

Tableware, sorter, P (9) 228*h*.
Talc. See also *Steatite*.
-carbonate alteration of serpentinized ultramafic rocks south of Timmins, Ontario, (7) 168*g*.
conversion, into protoenstatite (γ-$MgSiO_3$) in fired pressings of soapstone, (5) 137*d*.
Tanks. See *Furnaces, glass*.
Tantalates, ortho-, of lanthanum, samarium, and europium, (1) 24*b*.
Tantalum, anodic oxide films on, heat-treatment: III, conductivity profile, (4) 100*g*.
article, protected, P (5) 117*g*.
carbide, bodies, sintered, P (8) 182*d*.
bond state of carbon atoms in, (4) 110*e*.
incandescent lamp, and method of making, P (2) 49*b*.
polycrystalline transition, deformation, (7) 162*a*.
thin films, superconducting, (3) 76*j*.
chemistry: XXXII, reaction of tantalum with quartz, $14Ta + 5SiO_2 = 5Ta_2Si + 2Ta_2O_5$, (1) 17*d*; XLVI, NbO_2I and TaO_2I, (2) 54*h*.
coated with silicide, for improving oxidation resistance, (10) 249*g*.
deposition, with controlled electrical characteristics, (2) 54*f*.
films, conductance during anodic oxidation, (4) 100*d*.
fluorides, hexavalent, (11) 296*i*.
monocarbide, diffusion of carbon in, (9) 238*e*.
monocarbides, tungsten diffusion, (2) 59*e*.
mononitride, and titanium diboride mixture, P (5) 124*e*; and zirconium diboride mixture, P (5) 124*e*.
and niobium compounds, oxidized, with O/M = 2.33 to 2.50, (11) 299*a*.
nitride, thin-films, sputtering apparatus, P (3) 77*b*.
thin films, superconducting, (3) 76*j*.
oxide films, anodic, effect of ambients and contact area on asymmetric conduction, (9) 229*c*.
anodically formed, electron microscope observations of crystallization, (7) 163*f*.
prepared by oxygen plasma anodization and reactive sputtering, (7) 156*d*.
oxide platelets, observed after oxidation, origin and identity, (7) 166*d*.
oxide, thin flakes, method of producing, P (11) 291*j*.
oxides, lower, (11) 298*a*.
pentachlorides, orthobaric density and critical parameters, (8) 204*d*.
pentoxide, superlattices, direct observation by electron microscope, (9) 238*i*.
thermal transformation, (4) 111*h*.
suboxides TaO_x-(Ta_2O_3), structure, investigation by electron diffraction, (11) 297*d*.
substitution in hexagonal tungsten bronzes, (8) 209*g*.
systems. See *Systems*.
TaB_2, high-temperature thermal expansion, (3) 86*f*.
TaC_x, thermal expansion, effect of stoichiometry, (10) 271*a*.
Ta_2O_5 films formed with nonsteady potentials, (4) 111*i*.
thermal emf, effect of highly refractory oxides in vacuum at 1500°C, (7) 151*i*.
thin films, superconducting, (3) 76*j*.
trichloride, reaction with chlorides of alkali metals in melts, (11) 300*d*.
Technetium, -containing oxides, crystal chemistry, (8) 192*j*.
Television screens. See *Screens*.
Television tubes. See *Tubes*.
Tellurides, -containing thermoelectric modules, bonding, P (4) 100*h*.
preparation, P (5) 128*e*.
thallium, semiconductor materials, bodies, devices, methods of making, P (2) 48*c*.
Tellurites, glass, (1) 4*i*.
Tellurium, crystals, neutron-activated, peculiarities of gamma-ray spectra, (5) 137*e*.
dioxide, oxide glasses, formed by rapid quenching methods, (11) 298*c*.
isotopes, activation cross sections, peculiarities of gamma-ray spectra, (5) 137*e*.
systems. See *Systems*.
thin film field effect solid state electrical devices, P (3) 79*h*.
Temperature, characteristic, new formula for calculating, from melting point, (3) 87*b*.
coefficients, of resistance of evaporated thin films, (2) 47*d*.
control. See also *Controls*.
control system for high temperature melters, P (2) 40*a*.
controlling, program apparatus, P (5) 132*a*.
cycling ferroelectric ceramics through temperature range below the Curie point, P (1) 11*h*.
dependence, of infrared absorption due to U centers in alkali halides, (2) 57*d*.
of optical properties of ferroelectric $LiNbO_3$ and $LiTaO_3$, (9) 242*c*.

Temperature (*continued*)
detector, P (4) 102*i*.
effect, on strength and plasticity of high-melting point materials, (3) 71*j*.
on oxidation of titanium carbide, (5) 135*a*.
factors of crystals, (9) 242*e*.
furnace, multizone, control, P (8) 189*c*.
gradient, effect on grain growth of alumina, (7) 168*a*.
high, high pressure studies of oxide materials, apparatus for, (2) 50*e*.
industrial, ceramic research, (2) 60*i*.
melters, temperature control system, P (2) 40*a*.
properties, of sulfates, (5) 136*d*.
technology, B (5) 139*i*.
measurement, automatic, and control, (5) 132*d*.
by sublimation of layers of radioactive material, P (10) 268*c*.
sensor, P (2) 52*a*.
solidification, of refractory oxides, measurement, (7) 151*i*.
substrate-, measurement and control, (3) 76*i*.
surface, measurement and control, (7) 160*c*.
techniques for measuring, (8) 188*h*.
transformation, of BaO-P_2O_5 glasses, effects of residual water, (7) 148*g*.
transient, causes spalling of restrained refractory materials, (2) 43*d*.
of tunnel kiln, process for equalizing, P (10) 268*i*.
Temperature measuring instruments, apparatus, P (2) 52*b*.
of brightness, by photomultiplier, (5) 131*f*.
Harman and cooling couple, comparison for *Z* determination, (3) 75*g*.
high, P (7) 159*g,h*.
for high temperature chemistry, 1000° to 3000°C, (7) 159*d*.
pyrometer, P (4) 105*a*.
chromatic, to measure temperature in sintering zone, (10) 249*c*.
high precision automatic optical, (9) 233*g*.
method for measuring transient arc electrode temperatures, (7) 159*i*.
radiation, 63, (3) 81*c*.
radiation, and temperature standard for, P (8) 188*f*.
for rotary kilns, P (10) 268*b*.
sensing probe, with means for maintaining tubular element in engagement with ceramic rod member, P (7) 159*a*.
sensors, P (8) 188*f*; (9) 234*d*.
surface, P (9) 234*f*.
thermal probe, P (3) 81*h*.
thermistor, extended range, P (8) 188*c*.
thermocouples, P (2) 53*d*; P (8) 188*h*.
assembly, P (1) 14*g*.
compared with resistance temperature detectors and thermistors, (9) 234*f*.
compensated tapped, system, P (5) 132*a*.
comprising intimately twisted wires, P (8) 188*h*.
for DTA, P (4) 105*b*.
effect of pressure on emf, (7) 150*e*.
fast response right angle, P (2) 52*b*.
flattening and reversibly bending method of making, P (2) 52*c*.
graphite, and method of making, P (5) 132*a*.
immersion assembly, P (3) 81*e*.
lance, automatic expendable, P (9) 234*c*.
with mathematical model for measuring kiln conditions, P (1) 14*f*.
for measuring high temperatures, (4) 104*f*.
method for making, P (1) 11*d*.
for multiple burner combustion control, P (4) 105*a*.
noble metal, instability in vacuo, (2) 50*f*.
noble metal, having base metal compensating leads, P (9) 234*f*; P (10) 268*a*.
platinum, for control of glass melting furnaces, (1) 13*e*.
with platinum group metal inner sheath, P (10) 268*d*.
pressure gage, P (10) 268*d*.
protection in metallurgical industries, refractory materials for, (10) 258*e*.
protection from molten aluminum and zinc by refractories, (9) 224*j*.
protective sheaths, pressing, (7) 152*c*.
reference junction compensators, (9) 234*e*.
refractory metal, calibration, (10) 266*j*.
sheaths, gas-impermeable protective, of zirconium boride, (8) 198*g*.
tungsten-osmium, and element, P (8) 188*i*.
having tungsten-rhenium alloy leg wires, P (4) 105*a*.
zirconium boride tips, performance in Bessemer converter, (10) 258*f*.
thermometer, "birdcage" resistance, (9) 233*h*.
bulb fabrication method, P (2) 39*c*.
inert, (1) 13*h*.
mercury glass, method of marking, P (8) 178*h*.
refrigerated ice bath for calibration of, (9) 233*i*.
resistance, (1) 14*d*.
resistance, and method of making, P (10) 268*a*.
resistance, system, P (4) 105*a*.
thermistor, apparatus for calibrating, P (8) 184*a*.
Tempering, of glass. See *Glass*.
Terbium, Tb^{3+} luminescence, sensitization by Sn^{2+} and Cu^{+} in alkaline earth phosphates, (3) 76*h*.
Tension, curves, of porcelain and steatite glazes, (10) 261*c*.
surface, critical, of glass, (8) 175*g*.
of liquid nitrate systems, (8) 208*d*.
of metal oxides, (7) 163*b*.
of molten fluorides, system NaF-LiF-ZrF_4, (7) 162*b*.
testing, in refractories at high temperatures, apparatus and method, (7) 151*j*.
Terminology. See *Nomenclature*.

Testing. See also *Analysis* and specific types.
apparatus, for vitreous enamel with acid and neutral liquids and their vapors, IEI proposed standard, P (11) 275*j*.
for vitreous enamel with alkaline liquids, IEI proposed standard, (11) 275*j*.
of graphite to simulate neutron irradiation, P (2) 44*d*.
machine, for evaluation of refractory fabrics for flexible heat shields, (3) 71*c*.
methods, of ceramic grinding wheels, (5) 115*f*.
nondestructive, B (7) 170*c*.
in building practice, (2) 50*h*.
determination of thermal shock resistance, (2) 41*a*.
of high tension insulators, by ultrasonic impulse method, (8) 182*j*.
magnetic perturbation scanning, (7) 159*h*.
of mechanical properties of refractory materials, (7) 150*j*.
of model brick by sonic and X-ray methods, (3) 80*j*.
of refractories, (2) 41*c*.
to refractory brick, (2) 40*i*.
pottery clays by IL/MA method, (2) 50*d*.
samples over wide temperature range with multiple-shot X-ray thermal vacuum chamber, P (11) 280*j*.
torsional, applied to fine diameter glass fibers, (2) 38*c*.
Tests, cyclic torsion, for study of plasticity, (2) 45*j*.
for lead-210, P (7) 159*i*.
Texture, strength changes, effects on physical properties of fiber-textured materials, (9) 216*d*.
Thallium, chloride, self-diffusion, (7) 167*f*.
(I) chloride, interaction with chlorides of indium, potassium, copper(I), and silver, (8) 200*j*.
systems. See *Systems*.
thallous bromide, solubility, in molten nitrate solvents, (8) 207*g*.
Thermal analysis, differential: IX, heat conduction problem; X, influence of heat transport rate; XI, central consideration of thermoanalytical systems, (10) 267*e*.
differential, of aluminum phosphate, (5) 135*e*.
apparatus, P (8) 188*b*.
apparatus for recording and regulating temperature during, P (8) 188*j*.
of CPAC portland cement pastes at 25° to 1000°C, (2) 34*a*.
of devitrification of Li_2O-B_2O_3-SiO_2 glasses and Li_2O-Al_2O_3-B_2O_3-SiO_2 solder glasses, (9) 217*h,j*.
handbook, B (1) 30*g*.
high sensitivity apparatus, and method, P (11) 289*i*.
method for studies on catalyzed crystallization of glasses, (2) 37*f*.
microanalysis apparatus, P (2) 52*a*.
of system Na,K || $AlCl_4$,Ta(Nb)Cl_4, (2) 58*j*.
of montmorillonite-diamine and glycol complexes, (5) 137*b*.
quantitative differential, apparatus, P (8) 188*e*.
sample holders for, P (5) 132*a*.
transpiration, on porous ceramic, (11) 290*f*.
Thermal conductivity. See *Conductivity*.
Thermal decomposition. See *Decomposition*.
Thermal expansion. See *Expansion*.
Thermal properties, of materials, B (9) 244*f*.
of sulfides of certain lanthanides, (2) 58*h*.
Thermal shock resistance. See *Shock resistance, thermal*.
Thermocouples. See *Temperature measuring instruments*.
Thermistors. See *Resistors, electrical*.
Thermochemistry. See *Thermodynamics*.
Thermodynamics, of alkali chloride-lead chloride liquid mixtures, (8) 210*b*.
of boron phosphide, (7) 169*d*.
calculation of Debye-Waller factors of potassium bromide and magnesium oxide, (8) 210*b*.
ceramic: I, simple approach to basics; II, interaction of sodium with glass, (8) 192*g*.
chemical, excursion from past into future, (7) 169*g*.
problems approach, B (11) 303*j*.
electrocaloric effect in $SrTiO_3$, (8) 196*g*.
investigations on molten antimony sulfide, (8) 210*d*.
of metal-refractory interactions, (7) 152*f*.
of phase and ordering reactions, progress, (8) 205*g*.
for plutonium oxides, (4) 112*d*.
properties, of amorphous and hexagonal selenium, (2) 38*b*.
of Be compounds: V, VI, (8) 210*d*.
of $BeO \cdot Al_2O_3$ and $BeO \cdot 3Al_2O_3$ from 273° to 2150°K, (11) 300*b, c*.
of $BeO \cdot 3Al_2O_3$ from 15° to 390°K, (8) 199*h*.
of cadmium, indium, tin and lead tellurides, (3) 77*c*.
of corundum, standard substance in calorimetry, (8) 210*c*.
of crystals, (9) 242*e*.
of fluorine compounds: III, enthalpies of formation of hydrofluoric acid solutions, (2) 58*d*.
of magnesium antimonide and silicide, (11) 302*g, h*.
of manganese silicides and manganous chloride, (4) 112*a*.
of nonstoichiometric thorium monocarbide, (8) 210*f*.
of solid solutions of ferrites, (11) 302*i*.
of solid solutions in system Fe_2O_4-Mn_3O_4, (4) 112*b*.
of uranium oxycarbides, (11) 302*a*.
of zinc oxide, (8) 208*d*.
of reciprocal fused-salt systems involving monovalent liquid nitrates, (8) 210*b*.
of refractory compounds, B (5) 142*h*.
Thermodynamics (*continued*)
of silicates, B (5) 142*f*.
of solid solutions of magnesium ferrite with magnetite, (2) 58*f*.
stability, of monocarbides of transition metals from subgroups IV to VI, (8) 210*h*.
for structure of silicate glasses: II, ionic structure of metasilicate glasses, (2) 38*a*.
study, of formation of compounds of types M_2TiO_3 and M_2ZrO_3, (11) 302*b*.
of germanium oxides using mass spectrometer, (2) 58*b*.
of growth rate of epitaxial silicon from SiI_4, (11) 302*c*.
of silver-antimony system, (4) 112*c*.
of suboxide vaporization, (4) 112*e*.
transformations, of chlorides of nickel and cobalt, (8) 210*f*.
Thermoelectric materials, composition, halogen doped Bi_2Te_3-Bi_2Se_3-As_2Se_3, P (7) 156*f*.
compositions of $Nb_xTa_{1-x}Si_yGe_{2-y}$, P (4) 103*a*.
$Pb_xTe_{1-x}Cr$, and device, P (9) 231*f*.
members, coextruded, P (2) 47*a*.
sintered semiconducting, process for production, P (7) 157*h*.
Thermoelectricity, device, epitaxially bonded, and method of forming, P (5) 127*b*.
device having silicon-germanium alloy thermoelement, P (1) 12*a*.
elements, of oriented graphite containing spaced bands of metal atoms, P (10) 265*h*.
power, of ionic crystals: III, heats of transport for potassium chloride, (2) 58*g*.
thermoelectric body, two-phase, comprising Si-C matrix, P (2) 49*f*.
two-phase, comprising Si-Ge matrix, P (2) 49*e*.
two-phase, comprising Pb-Te matrix, P (2) 49*f*.
thermoelectric converter composition, P (3) 79*h*.
thermoelectric effect, phonon-drag, in piezoelectric semiconductors, (10) 271*b*.
thermoelectric initiators, of semiconductor material, method of making, P (7) 157*h*.
thermoelectric measurement device of rotary specimen carriers temperature, P (2) 52*a*.
thermoelectric power, of niobium dioxide, (8) 196*c*.
thermoelectric unit, with intimate layers of gallium-induced alloy and alumina, P (11) 288*a*.
Thermogravimetry, of manganese(II) nitrate pyrolysis, (2) 58*i*.
Thermoluminescence. See *Luminescence*.
Thermometers. See *Temperature measuring instruments*.
Thermophysical properties. See *Physical properties*.
Thermoplastics. See *Plastics*.
Thermostats, switch, P (1) 12*b*.
Thickness, of oxide films on anodized zirconium, determination from transmission interference measurements, (11) 293*a*.
Thin sections. See *Microscopy*.
Thoria. See *Thorium, oxide*.
Thorium, -base alloys, fused-fluoride electrowinning, (1) 19*b*.
carbide, preparation from thorium dioxide and graphite powder, (7) 152*b*.
cubic refractory compounds, thermal expansion, (7) 169*c*.
dicarbides, metallographic preparation, (8) 180*f*.
properties, (5) 138*h*.
dioxide, fine spherical particles, process for preparing, P (8) 190*e*.
torsion effusion study of reaction with graphite, (8) 210*d*.
-UO_2, in-reactor microstructures, thermal simulation, (10) 259*b*.
-UO_2, as nuclear fuel, (7) 151*g*.
monocarbide, nonstoichiometric, thermodynamic properties, (8) 210*f*.
properties, (5) 138*h*.
oxide, composition with magnesium oxide, P (7) 154*d*.
powders, sintering: IV, crystallinity development during heating and its influence on sintering behavior, (4) 109*f*.
single crystals, slip and fracture, (4) 109*g*.
slurries, method and catalyst for combining hydrogen and oxygen in, P (7) 153*h*.
sol, P (8) 182*e*.
sols, preparation by electrodialysis, P (1) 16*a*.
phosphates, precipitation effects, (3) 87*e*.
reaction of dioxides through americium with Nb_2O_5 and Ta_2O_5, (8) 206*c*.
silicate hydrosols, P (3) 75*a*.
systems. See *Systems*.
ThH_2 composition, and diffusion of hydrogen in, (3) 84*d*.
-uranium dicarbides, metallographic preparation, (8) 180*f*.
-uranium oxide, composition with magnesium oxide, P (7) 154*d*.
Thulium, divalent, in calcium fluoride, electron nuclear double resonance, (8) 196*c*.
Tile. See also *Pipe*. P (3) 64*i*.
cement or ceramic, containing special optical areas, P (2) 40*a*.
ceramic, facing for structural elements, P (1) 6*j*.
facing plates, device for sectioning, P (5) 130*e*.
new methods of manufacturing, (9) 228*h*.
clay roof, too costly?, (1) 6*h*.
of Danto Tile Co., Japan, (4) 99*j*.
drain, method for producing and handling, P (7) 150*j*.
drainage, B (8) 212*e*.
facing, P (7) 150*i*.
manufacture, P (10) 256*g*.
flexible bonding web for, P (8) 183*a*.
floor, drying in radiation driers, (3) 73*i*.
flooring material, P (9) 228*g*.
handling system, automated, P (8) 182*j*.
Tile (*continued*)
mosaic, assembly, P (10) 261*f*.
automatic assembly of multiple units of individual pieces, machine and method, P (9) 228*g*.
machine for scoring and cutting, P (5) 125*j*.
press, fast, outpaces glaze line, (4) 99*h*.
production speeded by open planning, (1) 9*a*.
radiant, catalytically active, P (5) 132*c*.
red body, defects in relation to pressing, (5) 125*f*.
roof, automated at San Valle, (4) 96*b*.
clay, captures 95% of Japanese home market, (4) 95*j*.
roofing, Japanese, frost-resisting properties, (2) 40*g*.
sheet-backing apparatus, P (3) 75*a*.
stove, modern style, (7) 145*j*.
wall, edge trim element, P (7) 155*c*.
effect of firing rate on physical properties, (10) 261*e*.
premixed batch, (1) 8*j*.
setting methods, for glost firing, (3) 73*i*.
thermal shock resistance, (3) 74*g*.
Time, timing system for I.S.-type glassware forming machine, P (5) 121*h*.
Tin, dioxide, electron effective mass, (11) 294*g*.
molten, method of making flat glass on, P (5) 121*e*.
molybdites, tungstites, molybdates and tungstates, mass-spectrometric determination, (1) 22*e*.
oxidation, effect of crystallographic orientation, (3) 85*a*.
oxide, thin flakes, method of producing, P (11) 291*j*.
oxides, mass-spectrometric study of vaporization, (1) 22*h*.
solid solubility and amphoteric behavior in solution grown gallium phosphide, (4) 109*h*.
spinels, formation and color development, effect of coordination preference of cations, (11) 293*h*.
systems. See *Systems*.
telluride, thermodynamic properties of, (3) 77*c*.
$Sn_{1-x}Pb_xTe$ epitaxial films, with moderate carrier concentrations, reproducible preparation, (10) 263*e*.
Titanates. See also *Dielectrics* and specific types.
alkyl, production, P (9) 236*a*.
ceramic mixed, superconductivity in, (8) 183*i*.
ceramics, (1) 10*e*.
containing lithium and potassium, process for preparation, P (9) 232*b*.
energy characteristics and geochemical features, (11) 295*e*.
fibrous alkali metal, process for producing, P (9) 232*c*.
free energy of formation, from measurements made with galvanic cells involving solid electrolytes, (8) 198*f*.
preparation, containing two alkali metals, P (8) 186*a*.
stamped from continuous sheet, (4) 100*c*.
$5SrTiO_3 \cdot 3La_{2/3}TiO_3$, anomaly in Young's modulus and internal friction below 100°C, (1) 16*j*.
systems. See *Systems*.
Titania. See *Titanium, dioxide*.
Titanium, anodic oxidation, in formic acid electrolytes, (3) 83*h*.
boride, composite bars, P (11) 281*a*.
boronitride, infrared radiation, (1) 20*a*.
carbide. See also *Cermets*.
bond state of carbon atoms in, (4) 110*e*.
effect of temperature on strength and plasticity, (3) 71*j*.
oxidation, effect of temperature and oxygen partial pressure, (5) 135*a*.
polycrystalline transition, deformation, (7) 162*a*.
poreless, prepared by impregnation, (10) 258*g*.
properties, effect of nuclear radiation, (8) 195*f*.
usage will grow, (1) 7*j*.
ceramic composite bodies, P (4) 103*b*.
-containing precipitates, for strengthening of sapphire, (4) 110*j*.
coordination, unusual in mineral fresnoite, (9) 239*h*.
determination in iron ores and slags, (5) 130*h*.
diboride, crystalline, preparation by gas-phase reaction, (11) 299*b*.
diboride, densification and wear resistance, (8) 179*j*.
enthalpy and specific heat in range 273.15° to 2600°K, (8) 197*g*.
high-temperature thermal expansion, (3) 86*f*.
purifying, P (8) 181*g*.
single crystal, microstructure, (11) 298*i*.
dioxide. See also *Rutile*.
catalytic and photochemical behavior, role in quality and concentration of lattice defects and activators in, (1) 28*g*.
fibrous, of brookite crystalline structures, process for preparing, P (11) 291*c*.
fibrous, containing material, process for producing, P (10) 265*j*.
formed in flame reactor, properties, (1) 27*g*.
hot-pressed, semiconducting properties, (3) 76*f*.
in gaseous mixture, process for recovery, P (7) 161*b*.
manufacture, P (2) 54*c*.
-NiO-Sb_2O_3 compound, (2) 59*a*.
nucleating agent, effect on separating crystal phases during production of glass-ceramics, (10) 251*d*.
particles, calcined, for pigment production, P (11) 292*a*.
pigment, measurement of optical properties, (1) 22*i*.
pigmentary, fluidized bed process for producing, P (10) 269*f*.

Titanium, dioxide (*continued*)
pigmentary, manufacture, P (2) 54*a*.
production, P (1) 16*b*; P (9) 236*d*; P (11) 292*d*.
production by fluidized bed process, P (8) 190*e*.
role in bauxite refractories, (9) 224*d*.
sintering, effects of minor additions, (4) 107*h*.
solid solution in aluminum oxide, (1) 28*i*.
monocarbides, tungsten diffusion, (2) 59*e*.
nitride, from sponge titanium and nitrogen or ammonia, synthesis, (5) 139*a*.
oxidation kinetics, and structure of scale, (3) 88*a*.
oxide, electronic structure, (7) 163*g*.
highly dispersed, process for purification, P (9) 236*j*.
hydrate, preparation, P (11) 291*d*.
thin flakes, method of producing, P (11) 291*j*.
oxidized films, optical and structural properties, (1) 24*a*.
recovery of, from red slurries of bauxite, P (4) 107*d*.
recovery process, from red slurries obtained in processing bauxite by Bayer process, P (4) 107*a*.
selenides, gaseous products from vaporization of, (3) 75*i*.
suboxide, sputtering on dielectric components in preparing electron tube, P (7) 157*h*.
systems. See *Systems*.
$TiCl_4$, oxidation process, P (11) 291*f*.
TiO_{2-x}, diffusion layers on Ti, electrical studies, (3) 85*d*.
Ti_3O_5 and Ti_2O_3, magnetic studies of semiconductor to metal transitions in, (10) 271*c*.
$TiUO_5$, preparation and properties, (8) 205*i*.
TiV alloy hydrides, proton magnetic resonance method of studying, (4) 109*a*.
Titration. See also *Analysis*.
automatic derivative spectrophotometric, of iron and/or aluminum with EDTA, (1) 13*d*.
with CDTA, for rapid determination of magnesium in presence of calcium and phosphate, (5) 131*b*.
method, for rapid determination of cement binding power, (4) 91*g*.
photometric, of CaO, MgO, and Fe_2O_3 in cement materials by complexometric methods, (9) 215*e*.
stepwise, (1) 14*e*.
Tobermorite, hydrothermally synthesized, effect of isomorphous substitution, (1) 18*j*.
Tools. See also *Drills*.
abrasive, and methods of making, P (7) 145*h*.
cemented carbide, (2) 33*g*.
advances in, (3) 63*f*.
ceramic cutting, alumina, present and future, (2) 33*h*.
coating with carbides, (2) 33*i*.
cutting. See also *Abrasives*.
P (4) 89*g*.
for brick and construction materials, P (5) 130*e*.
diamond, metal bonded, process for making using spherical pellets of metallic powder-coated diamond grits, P (8) 173*g*.
method of preparing, P (2) 33*i*.
future, carbides and refractory compounds, (2) 33*j*.
grinding. See *Grinding apparatus*.
oxide, machining with, (2) 33*i*.
Topography, X-ray, for observation and characterization of gross imperfections in sapphire single crystals, (10) 272*i*.
X-ray, of single crystal NiO, (9) 243*h*.
X-ray diffraction, of imperfections in GaAs by anomalous transmission of X rays, (11) 303*a*.
Torch, powder melting, preventing flashback, P (1) 3*d*.
Trace elements. See *Elements*.
Tracers. See *Radioactive tracers*.
Transducers, ceramic, assembly, P (7) 156*j*.
ceramic piezoelectric, for ultrasonic delay lines, (9) 229*a*.
ferrimagnetic pressure, P (5) 127*c*.
piezoelectric, P (1) 11*a*.
device, P (2) 49*a*.
plate, mechanical responses, (11) 284*e*.
thin-film, used as generators and detectors of microwave phonons, with attenuation measurements in SiO_2, (3) 77*d*.
prestressed spherical electroacoustic, P (8) 185*j*.
segmented ferrite sonar, with permanent magnet bias, P (4) 102*b*.
semiconductor strain gage, P (10) 265*c*.
shape, process for making fiber optic devices, P (2) 40*b*.
single crystal quartz, P (7) 158*d*.
for underwater transponder, P (1) 12*c*.
zinc oxide film, (3) 77*g*.
Transfers. See *Decoration*.
Transformations, basalt-eclogite, effect of anorthite-forsterite and anorthite-entatite reactions, (8) 191*f*.
glass-crystal, of nepheline and wollastonite, and heat of formation of nepheline, (1) 19*e*.
"hydrothermal silica," comment, (1) 17*e*.
of index of barycentricity of phase diagrams of multicomponent systems, (11) 302*h*.
of γ-Fe_2O_3 to α-Fe_2O_3, catalytic action of mineral acids on, (8) 192*f*.
phase, in barium orthoferrate, $BaFeO_{3-x}$, (1) 26*b*.
in carbon black reduction processes of uranium oxides, (1) 26*h*.
in reduction of U_4O_9, (1) 26*i*.
of water in porous glass, (8) 175*i*.
of quartz, nature of $\alpha \rightleftarrows \beta$, (8) 203*a*.
to tridymite in presence of binary silicate liquids, (9) 242*i*.
structural, of curium sesquioxide, (8) 207*d*.
thermal, of alumina trihydrate, hydrargillite, (2) 58*j*.
of tantalum pentoxide, (4) 111*h*.
Transformations (*continued*)
thermochemical, of iron chlorides, (4) 111*j*.
thermodynamic, of chlorides of nickel and cobalt, (8) 210*j*.
$WO_3 \rightleftarrows W_{20}O_{58}$ shear, X-ray powder diffraction study, (2) 60*a*.
Transformers, piezoelectric ceramic, P (4) 102*g*.
Transitions, continuous, in system Fe_3O_4-Fe_2O_3, (7) 162*i*.
direct-indirect, in $Ga(As_{1-x}P_x)$, effect of donor impurities, (5) 135*g*.
electric and magnetic, in VO_2, (9) 237*c*.
glass, characteristics of organic and inorganic glasses, comparative studies, (7) 148*c*.
of metastable tetragonal to monoclinic zirconia, kinetics and mechanism, (7) 164*g*.
phase, under high pressure: IV, synthesis of $ZnSiO_3$ pyroxene, (1) 26*a*; V, transition of Zn_2SiO_4, 26*c*.
two higher, of WO_3, (2) 59*g*.
temperature, of Ti-substituted magnetite, (7) 163*e*.
Transistors, alloy diffused, P (11) 284*g*.
boron diffused silicon, method of making, P (2) 48*c*.
cadmium selenide thin film field effect, (9) 228*i*.
cadmium sulfide, field effect, method of making, P (9) 231*e*.
thin film, analysis of static characteristics, (4) 100*b*.
containing electropositive protective coating, P (8) 185*d*.
device, field effect, method of making, P (11) 286*i*.
with elongated base and collector current paths, P (2) 49*d*.
epitaxial, and method of manufacture, P (9) 230*h*.
field-effect, P (10) 264*a*.
with concentric interior electrode, P (3) 78*j*.
with junction parallel to (111) plane of crystal, P (4) 101*f*.
method of producing, P (8) 185*b*.
group III-V compound, P (9) 230*j*.
high frequency, P (1) 10*j*.
housing containing packed, earthy, nonmetallic, electrically insulating material, P (1) 12*c*.
InAs thin-film, high-gain, (9) 229*a*.
insulated gate field effect, process for making, P (11) 285*b*.
insulating gate thin film, having thin insulating layer overlapping thick insulating layer, P (8) 184*h*.
metal base, fabrication, P (9) 230*h*.
method of forming by diffusing recombination centers and device produced, P (8) 185*d*.
pnp germanium, producing by diffusing indium and arsenic into *p*-type substrate, P (7) 157*i*.
silicon, method of making by alloying indium with *p*-type silicon to produce *pn* junction, P (2) 48*b*.
method of manufacture, P (11) 286*d*.
surface barrier indium arsenide, P (2) 49*b*.
switching, structure, and method of making, P (11) 288*a*.
thin film, P (2) 49*c*.
fabricating, P (4) 101*f*.
and method of fabrication, P (2) 49*d*.
transconductance and output conductance, measuring device, P (7) 156*b*.
Transmission, optical, improved, in semiconductive alloy light source, P (4) 102*c*.
Transport, material, in sintering, B (7) 170*g*.
numbers, in pure molten silver nitrate and lead bromide by balance method, (8) 210*g*.
of oxygen in oxide films on zirconium determined by nuclear reaction ^{17}O (^3He,α)^{16}O, (5) 139*d*.
processes in glassy and crystalline $Na_2O \cdot 2CaO \cdot 3SiO_2$, (10) 253*g*.
properties, electrical, of intermediates in spinel system $Co_{1+\frac{1}{3}x}V_{2-\frac{2}{3}x}O_4$, (8) 206*j*.
system, open tube HI, substrate orientation effects and germanium epitaxy in, (9) 242*b*.
through blocking pores, oxidation by, (9) 241*a*.
Trapping, competitive, in sodium disilicate glasses doped with Eu^{3+}, (8) 175*b*.
Tricalcium. See *Calcium*.
Tridymite, studies, (5) 138*d*.
Triodes, solid state thin film, with graded energy band gap, P (3) 79*g*.
Trituration. See *Crushing; Grinding*.
Tubes, alumina discharge, high temperature, for pulsed metal vapor lasers, (1) 9*j*.
arc, process for fabricating, P (2) 39*j*.
cathode-ray, P (5) 127*b*; P (10) 254*h*; P (11) 284*j*.
for color television, manufacture, (8) 177*i*.
with composite multiple glass fiber face, P (9) 219*a*.
envelope, P (4) 94*d*; P (7) 149*j*.
envelopes, sealing glass parts to form, P (9) 222*d*.
faceplate, method for interchanging curvature, P (11) 279*c*.
frit dispensing device, P (11) 285*e*.
glass, P (3) 67*g*.
including faceplate comprising tapered fiber optical elements mounted in opaque mosaic, P (5) 127*c*.
manufacturing apparatus, P (11) 278*b*.
mesh assembly supported between envelope sections, P (2) 47*i*.
with metallic layer of nonuniform thickness, P (11) 284*j*.
method of covering glass wall portion, P (3) 68*c*.
method of making, P (10) 164*i*.
and other vacuumized, resistant to fracture and capable of controlled evacuation, P (10) 254*k*.
phosphor dielectric storage target for, P (3) 79*i*.
phosphor fiber faceplate for, P (7) 157*c*.
Tubes, cathode-ray (*continued*)
printing using photoconductive layer, P (1) 11*b*.
reinforced, and faceplate, P (8) 179*a*.
with screen conforming to peripheral surface of cylinder, P (4) 100*h*.
ceramic, end closures, P (2) 47*f*.
cold-cathode glow-discharge, P (2) 47*a*.
color cathode ray, with radiation-emitting index stripes, P (1) 10*j*.
color image reproducer having red phosphor combined with red-pass filter element, P (5) 127*c*.
discharge, method of filling with gas and sealing, P (7) 150*a*.
electron, heater for, P (9) 231*a*.
with inert oxide coating on envelope, P (10) 263*h*.
method of preparing, including sputtering titanium suboxide on dielectric components, P (7) 157*h*.
X-ray fluorescence analysis, (1) 4*j*.
electron discharge, double-ended, P (5) 127*g*.
method of coating fluorescent layer, P (1) 11*c*.
fluorescent, of irregular section, method for phosphor coating, P (5) 128*f*.
gaseous cold cathode indicator, having segmented electrode and insulating shield plate, P (1) 10*f*.
gaseous microwave switching, apparatus, with tube including closely packed solid ceramic alumina spheres, P (10) 264*a*.
glass, continuous, method of shaping, P (11) 279*f*.
degassing, (9) 217*g*.
gaging and cutting apparatus, P (8) 177*e*.
machine for cutting, P (9) 220*c*.
method of sealing contact reeds in, P (2) 39*b*.
methods of sealingly securing lead-in wires to, P (5) 121*i*.
glass cathode-ray display, methods of strengthening, P (5) 121*a*.
glass tubing, method of shrinking, P (10) 255*j*.
glow cathode indicator, having memory, P (8) 184*d*.
of high alumina material, end closures for, P (10) 263*h*.
picture, implosion-proof, (1) 3*f*.
recuperator, P (7) 154*a*.
television, assemblies, methods of forming and implosion guards therefor, P (7) 150*f*.
tubing, exhaust, method of tipping-off, P (8) 178*j*.
vacuum, construction, study of applicability of Mo and W carbides, (11) 280*h*.
X-ray, with field emission cathode and evaporative anode in combination with electrical pulser means, P (7) 158*c*.
X-ray diffraction, P (1) 12*a*.
Tungstates, vitreous alkali, (5) 119*e*.
systems. See *Systems*.
Tungsten, borides in boron fibers, (9) 225*f*.
bronzes, cubic rare earth, single-crystal preparation, (1) 28*c*.
hexagonal, tantalum substitution, (8) 209*g*.
carbide-based cutting alloys, effect of hydrostatic pressure on elastic properties of, (4) 96*e*.
carbide, bond state of carbon atoms in, (4) 110*e*.
brazing, P (4) 92*f*.
compositions, method and cutting tool, P (4) 89*g*.
-cobalt alloys, sintered, elastic modulus of, (3) 85*h*.
polycrystalline transition, deformation, (7) 162*a*.
study of applicability to construction of high-power tubes, (11) 280*h*.
-TiC-Co hard, sintered, containing tantalum carbide, properties, (10) 258*j*.
composition, ductile, containing spinel dispersed uniformly throughout, P (8) 181*a*.
diffusion, in monocarbides of tungsten, tantalum, titanium, and solid solutions TiC-WC and TiC-WC-TaC, (2) 59*e*.
diselenide, substituted, and its analogues, semiconducting behavior, (7) 167*g*.
disilicide, oxidation, (3) 87*g*.
interaction with niobium carbide, (8) 200*b*.
monocarbides, diffusion, (2) 59*e*.
niobium oxide, of M_n-$O_{3n-2}(ReO_3)$ series, (8) 210*h*.
oxidation, influence of crystal orientation, (9) 239*h*.
and mechanical performance at high temperatures and pressures, (1) 2*g*.
oxide, doping method, P (2) 48*f*.
-metal metaphosphate glasses, P (1) 6*e*.
$WO_{2.88}$, new phase with shear structure in W-O system, (2) 59*b*.
$WO_{2.88}$, shear structure, (8) 206*h*.
oxides, reduction by hydrogen, (1) 27*g*.
reaction diffusion with carbon and nitrogen, (1) 20*c*.
slip casting method, P (9) 227*h*.
sulfides, (11) 301*b*.
systems. See *Systems*.
tantalum oxide of the M_n-$O_{3n-2}(ReO_3)$ series, (8) 210*h*.
thermal emf, effect of highly refractory oxides in vacuum at 1500°C, (7) 151*i*.
trioxide, neutron diffraction investigation, (8) 203*c*.
oxide glasses, formed by rapid quenching methods, (11) 298*c*.
single crystal, effect of heat treatment: II, green stripes, (3) 85*a*.
structural defects, influence of minor additions of tantala or niobia, (7) 168*a*.
two higher phase transitions, (2) 59*g*.
W_2As_3, crystal structure, (10) 270*d*.
W_2C, evidence for zeta Fe_2N-type sublattice order in, at intermediate temperatures, (7) 163*b*.
with fine dispersion of carbon, method of preparing, P (7) 153*c*.

Tungsten (*continued*)
volatilization in presence of water vapor, (9) 243*e*.
Tuyeres. See *Refractories*.
Twinning, of crystals. See *Crystals*.

Ultrasonics. See *Sonics*.
Uranates, crystal structure: I, containing tetragonal (UO_2)-O_2 layers, (3) 84*b*.
Uranium, aluminides UAl_2 and UAl_{4-5}, preparation, P (2) 45*a*.
in borosilicate glasses, polarization of fluorescence, (10) 251*d*.
carbide, compact, process for forming, P (3) 73*d*.
monocrystals, process for production, P (10) 260*b*.
reaction in KCl-LiCl/zinc system, (11) 300*f*.
-refractory metal interactions at high temperature, (7) 152*g*.
spheroids coated with silicon carbide in nuclear fuel body, P (1) 8*g*.
carbides, of fissionable and fertile materials, process for making, P (2) 45*b*.
ceramics, thermal shock rupture, (7) 152*e*.
cermets, high temperature properties, (2) 41*k*.
compound, particularly uranium carbide, method for continuous casting of bars, P (11) 282*c*.
-containing material, spherical granular, of definite particle size, process for preparation, P (4) 98*i*.
dioxide, behavior of fission product gases in, (7) 151*c*.
binary phase diagrams of, with Al_2O_3, BeO, and MgO, (3) 83*i*.
coated nuclear reactor fuel particle of, and method of making, P (3) 72*e*.
crystal field calculation, (8) 193*a*.
dense, fabrication by hot-pressing and coextrusion, (10) 257*i*.
electrical properties, (9) 238*h*.
factors influencing sinterability, (1) 41*f*.
hollow spherical, nuclear fuel particles, P (3) 72*g*.
and lead monoxide, interactions, (8) 200*d*.
manufacture, P (3) 72*i*.
-molybdenum cermet bodies, preparation, (7) 152*b*.
nonstoichiometric, electrical properties, (11) 294*b*.
preparation, P (4) 98*j*.
production by flame denitration, (4) 97*c*.
Raman scattering, (8) 206*c*.
reflection spectra, prepared from U_3O_8 calcined under various conditions, (8) 206*b*.
single crystals, Moessbauer effect in ^{57}Fe in, (8) 202*g*.
single crystal, thermal conductivity and far-infrared absorption, (8) 209*f*.
sintered bodies, manufacture, P (5) 124*d*.
sintered, observation of fission fragment tracks, (3) 87*d*.
sintered, pore growth during solarization, (7) 152*a*.
sintering behavior, effect of properties of powders, (11) 294*d*.
sintering between 950° and 1500°C in dry hydrogen atmosphere, kinetics of, (11) 297*h*.
sol process, P (7) 154*e*.
stoichiometric, method to prepare, P (4) 99*b*.
stoichiometric, produced by fusion process, P (8) 181*d*.
systems. See *Systems*.
-U_3O_8, binary mixture, quantitative analysis by X-ray diffraction, (8) 179*i*.
visible and ultraviolet absorption spectra, (8) 211*e*.
-yttrium oxide-zirconium dioxide aquasol process and product, P (10) 261*a*.
fabrication of sintered compounds based on, and plutonium, P (2) 43*j*.
filterable coprecipitate, preparation, P (3) 72*d*.
hexafluoride, failure of first Born approximation in electron diffraction, (8) 197*i*.
heat content of formation, (8) 198*a*.
method of separating from bromine fluorides, P (9) 226*b*.
one-step method of converting to uranium compounds, P (10) 260*a*.
self-diffusion coefficient [at 0° to 70°C], measurements, (7) 165*i*.
microgram amounts of, with rhodamine B, absorptiometric determination, (8) 187*b*.
monocarbide, isothermal compressibility, (11) 297*e*.
crystals, control of stoichiometry in growth, (8) 192*h*.
diffusion, (8) 194*j*.
reaction with water, kinetics of, (11) 297*f*.
mononitride, mixtures, preparation and examination, (7) 152*b*.
monophosphide, synthesis by phosphine reaction, (8) 208*h*.
nitride, hexagonal, (8) 199*b*.
oxidation, investigation by high temperature conductometric, X-ray diffraction and continuous weighing methods, (11) 297*b*.
oxide, creep of solid solutions, (8) 192*i*.
formed in carbon dioxide at 650°C, cracking and carbon pickup, (11) 293*c*.
microspheres, preparation by sol-gel process, (4) 97*b*.
-molybdenum cermet bodies, properties, (7) 152*e*.
preparation and properties of new monohydrate of, (8) 205*h*.
sols, method of making, P (2) 44*b*.
systems. See *Systems*.
-zirconia microspheres, preparation by sol-gel process, (4) 97*b*.
Uranium (*continued*)
oxides, elasticity and anelasticity, at room temperature: I, stoichiometric oxide, (3) 85*i*.
higher, electrical conductivity, temperature dependence of, (4) 111*a*.
phase transformations in carbon black reduction processes of, (1) 26*k*.
quenched, of type UO_2, X-ray examination, (9) 243*a*.
oxycarbides, thermodynamic properties, (11) 302*a*.
and plutonium monoxide-type compounds: I, oxycarbides, (7) 166*b*.
separation, from uranium dioxide-zirconium dioxide mixtures, P (11) 283*b*.
trioxide, hydrated, thermal decomposition, (2) 58*d*.
hydrates, chemical reactivity, (5) 134*d*.
sol process, P (9) 227*i*.
systems. See *Systems*.
and UO_3 hydrates, (8) 211*f*.
-zirconium dioxide sol process and product, P (9) 227*j*.
$U_3C_5Si_2$, for nuclear fuel material, and method of preparation, P (11) 282*a*.
UO_{2+x}, evaporating, multiple electron diffraction, (8) 202*i*.
U_3O_8 conversion to UC, P (8) 180*j*.
U_3O_8-UO_2 transformation, solid solution formation, (4) 109*j*.
U_4O_9, phase transformations in reduction of, (1) 26*i*.
single crystal, room temperature elastic constants, (8) 206*d*.
UO^{2+}_2, in Na_2SO_4 medium, studies on hydrolysis, (4) 110*c*.
Urea, complexes with montmorillonite—infrared absorption study, (4) 112*f*.

Vacuum, chamber, multiple-shot X-ray thermal, for testing samples over wide temperature range, P (11) 289*j*.
deposited films, at high temperature, (2) 47*e*.
distillation of alkali halogenides, (7) 169*b*.
processing facility, thin film circuit, P (8) 186*b*.
ultraviolet, micaceous biotite as efficient polarizer for, (1) 10*a*.
Vacuum tubes. See *Tubes*.
Vanadates, rare earth, luminescent properties, (9) 240*i*.
Vanadium, bronzes, recent investigations: I, additive monovalent elements, (7) 167*g*; II, additive divalent and trivalent elements, (8) 206*a*.
carbide, polycrystalline transition, deformation, (7) 162*a*.
carbides, tensimetry, (2) 57*e*.
dioxide, crystal distortion and electric and magnetic transition, (9) 237*c*.
phase transition, (4) 109*h*.
single crystals, new growing method, (8) 203*j*.
influence, on carbon activity in Fe-C-V system at 1000°C, (7) 164*h*.
oxide, from ferrophos, P (5) 133*g*.
process for recovering from low grade vanadium ores or concentrates, P (3) 83*c*.
pure fused, process for producing from ammonium metavanadate, P (10) 269*j*.
oxides, electrical conductivity, (7) 163*b*.
pentoxide, crystalline and amorphous, preparation and properties, (9) 241*e*.
effect on sintering and grain growth of MgO, (5) 122*g*.
identification of trace $VO_{2.17}$, and influence of coexistence of Fe, Co, or Ni in preparing by heating in vacuum, (4) 108*g*.
-metal metaphosphate glass compositions, P (1) 6*f*.
oxide glasses, formed by rapid quenching methods, (11) 298*c*.
single crystals, optical absorption coefficients, (8) 205*j*.
systems. See *Systems*.
trioxide, results and interpretation of ^{51}V NMR in, (10) 271*i*.
solubility in melts of chlorides of sodium and potassium, (8) 207*g*.
^{51}V nuclear magnetic resonance, (8) 211*d*.
in titanium oxide, spectrophotometric determination of trace amounts, (3) 81*e*.
V_2C, lower temperature modifications, (7) 165*f*.
V_2MoO_8, crystal structure, (10) 270*d*.
VO^{2+} detection in glass by electron spin resonance, (2) 36*h*.
V_6O_{13}, phase transition, (11) 299*f*.
$VOMoO_4$, crystal structure, (10) 270*d*.
Vaporization, for applying coatings, methods and devices, P (9) 233*a*.
arc, for production of ultrafine boron nitride, (3) 71*d*.
in formation of holes in electrical material, P (9) 230*e*.
of gadolinium and gadolinium dicarbide, Knudsen cell studies, (9) 240*g*.
high temperature, properties of boron carbide, (8) 199*g*.
of lead zirconate-lead titanate materials, (10) 272*a*.
nonstoichiometric, of cadmium arsenide, mass spectrometric study, (8) 202*a*.
of solid silicon monoxide, (8) 195*a*.
suboxide, thermodynamics, (4) 112*e*.
of titanium selenides, gaseous products from, (3) 75*i*.
Vapor pressure, of alkali halide crystals, analysis, (7) 161*h*.
of Be_3N_2 decomposition reaction, (10) 272*j*.
saturated, of chlorides of Ca, Sr, and Ba, (7) 167*e*.
of solid MgF_2, (8) 211*e*.
in system In-$InCl_3$, (4) 112*b*.
Vapors, backstreaming from mechanical pumps, use of quartz crystal microbalance for measuring, (9) 234*f*.
composition, influence on growth rate and morphology of gallium arsenide epitaxial films, (7) 155*h*.
deposition, B (2) 62*f*.
apparatus including tumbler, P (5) 129*e*.
for manufacture of semiconductor device, P (10) 264*f*.
mask, P (2) 49*f*.
of material without thermal radiation of substrate, P (10) 265*a*.
of silicon on graphite, (3) 72*b*.
determination of thermal accommodation of translational energy at glass surface, (1) 17*f*.
dew method for revealing ferroelectric domains, (8) 203*i*.
dissociation, effect on mass transport parameters of heat proof glass materials, (8) 195*c*.
measurements in $Na_2SiO_3 \cdot nH_2O$ glasses, (10) 254*a*.
phase reaction, for growth of $(Ga_xIn_{1-x})As$ single crystals, (3) 86*c*.
for preparation of $GaAs_xP_{1-x}$, (3) 87*f*.
phase transport of $GaAs_{1-x}P_x$ using water vapor, (9) 243*b*.
transport reactions, related to halophosphate phosphor formation, (10) 263*a*.
for synthesis of GaAs, (9) 242*c*.
Vermiculite, apatite-magnetite-, deposits near Sitarampur, Visakhapatram district, Andhra Pradesh, (8) 189*e*.
-ceramic products, (8) 180*c*.
exfoliated, re-expanding compressed, P (2) 54*d*.
from Japan: III, fired properties of vermiculite-clay insulating materials, (7) 152*a*.
Vibration, localized, of H^- and D^- ions in alkaline earth fluorides, (8) 201*d*.
mechanical, effect on flow properties of kaolin-water mixtures, (7) 154*i*.
polishes vitrified china fast and efficiently, (9) 228*f*.
producing by impact-actuated spring system, in rotating form, P (5) 130*g*.
vibratory members, resonant and antiresonant, attached to crystal, P (8) 186*c*.
Viscometers, extrusion, entrance and wall effects during flow of concentrated suspensions, (11) 289*h*.
indentation, for small samples, (10) 267*f*.
Rheomat 15 coaxial cylinder, possibilities of using in ceramic industry, (7) 159*b*.
spherical rotary, new model, for rheological investigation of highly concentrated, structured, polydisperse systems, (10) 267*j*.
Viscosity, of clay, method of reducing, P (9) 236*b*.
of clay suspensions with ultimately broken-down structure, effect of sodium salts of fatty acids, (7) 162*h*.
of clinker liquid phase, effect of Na_2SiF_6, (9) 214*j*.
of dehydrated phosphoric acids, (4) 112*c*.
of fused boric oxide, (10) 254*c*.
gage for pressure measurement in range 10^{-6} to 10^{-4} torr, (2) 51*g*.
of glass, in tank furnace, measuring methods, (3) 66*c*.
of glasses, (9) 219*a*.
investigations by beam bending, (10) 254*d*.
of lead-silica glass, NBS Standard Reference Materials, (2) 37*i*.
of liquid slags in ternary system SiO_2-Al_2O_3-CaO, (2) 56*d*.
of magnesia cements, method of increasing, P (11) 275*f*.
measurements, on fused salts: I, theoretical principles of oscillating hollow cylinder method; II, alkali and alkaline earth chlorides, (7) 169*d*.
measuring apparatus, P (3) 81*c*.
of molten B_2O_3, (1) 4*j*.
monitoring, methods and apparatus, P (9) 234*e*.
of silicate glasses, effect of chemical accelerators on temperature dependence of, (1) 3*g*.
of $Na_2O \cdot B_2O_3$ and $Na_2O \cdot SiO_2 \cdot B_2O_3$ melts at 1300°C, (2) 38*e*.
suspending-fluid, effect on batch mill grinding, (4) 103*f*.
-temperature data, rapid method for approximating in range 10^{12} to 10^{14} poises, (9) 233*j*.
-temperature relations, in the GeO_2 and SiO_2 systems, (1) 29*a*.
of ternary silicate glasses, calculation from composition, (9) 217*h*.
Vitrification, of highly siliceous roseki brick, test, (9) 225*d*.
of silica gels, (8) 211*g*.
Volatility, of plutonium carbides, (8) 211*h*.
volatilization, of tungsten in presence of water vapor, (9) 243*e*.
Volume, changes on setting and curing of cement paste and concrete from 0 to 7 days, (3) 64*h*.
excitation of ultrathin single-mode CdSe laser, (9) 243*e*.
relations in $Na_2O \cdot B_2O_3$ and $Na_2O \cdot SiO_2 \cdot B_2O_3$ melts at 1300°C, (2) 38*e*.
Volumeter, mercury displacement, accuracy, (4) 104*b*.

Wallboard, joint treatment, dry powder for, P (5) 116*e*.
Wastes, nuclear, laboratory testing and evaluation of porous permeable rock for disposal, (10) 257*e*.
process, incineration, (1) 12*e*.
Water. See also *Humidity; Moisture; Steam*.
absorbed, effect on spreading of organic liquids on soda-lime glass, (10) 251*b*.
action on glasses in system Na_2O-B_2O_3, (10) 253*g*.
activity, in clay pastes, measurement by tonometer, (5) 131*h*.

Water (*continued*)
adsorption on beryllium oxide, (7) 161*j*.
condensation, on barium silicate glasses, causes internal friction peak, (7) 148*j*.
extract, methods for complete analysis in glass and glass enamels, (3) 80*i*.
in glass, (8) 175*c*.
interaction, with magnesium oxide surface, (7) 164*d*.
natural, for enameling, (9) 216*d*.
molybdenum determination in, (2) 50*g*.
removal, from aqueous suspensions, P (2) 50*b*.
from suspensions, apparatus, P (2) 49*i*.
-repellent products, building material compositions for manufacture, P (8) 174*a*.
repellents, silicone, for masonry materials, P (7) 151*a*.
residual, effects on transformation temperature and structure of BaO-P_2O_5 glasses, (7) 148*g*.
resistance, of ceramics at high temperatures, (3) 74*a*.
vapor, adsorption and desorption on oxide and metal powders, energy processes in, (5) 135*j*.
effect on reactions of hard-magnetic ferrites, (3) 75*g*.
effects during preparation and calcination of oxide powders, B (7) 169*i*.
etchant for silicon, (4) 100*e*.
influence on crack propagation in soda-lime glass, (9) 218*d*.
in water and alkaline earth chloride solutions at 25°C, diffusion coefficient, (1) 18*a*.
Waveguides, helical-walled, P (2) 47*k*.
Wear, of glazed surfaces, as function of time, (3) 74*h*.
resistance, of titanium diboride, (8) 179*j*.
Weathering. See also *Frost resistance.*
of enamels and glasses, basic research, (3) 64*j*.
Weighing. See also *Balances; Thermogravimetry.*
apparatus with magnet system, P (2) 50*c*.
sensitive, P (10) 268*b*.
belt conveyor, apparatus, P (10) 266*g*.
material on conveyor comprising radioactive source and detector, P (1) 12*h*.
method, simplified, for transport numbers in pure molten $AgNO_3$ and AgCl, (7) 169*e*.
nuclear, (5) 129*j*.
weight percentages of unsieved heavy minerals, rapid method for determining, (10) 267*f*.
Welding, arc, with ac power and cored electrode, P (7) 147*h*.
electric, of refractories, (3) 71*a*.
electroslag, consumable nozzle for, P (9) 225*c*.
flux and method, P (10) 250*g*.
graphite, P (2) 44*e*.
rod, flux-coated carbide, P (10) 250*c*.
submerged-arc, composition, P (9) 217*e*.
vacuum, for making semiconductor devices, P (5) 128*d*.
Wettability, of refractories by carbon steels under hot-stage microscope, (2) 43*j*.
Wetting, of aluminum oxide by chromium-nickel melts, (10) 259*b*.
cavity, process, P (11) 289*b*.
of ceramic coatings with metals, (3) 65*a*.
Wheels, potters, for children, (4) 89*j*.
Whiskers. See also *Crystals.*
alumina, process for producing, P (10) 260*j*.
aluminum silicate, synthesis, P (9) 227*h*.
beryllia, preparation, P (3) 72*c*.
boron and silicon carbide for reinforcement of plastics, (9) 225*h*.
ceramic, give strength to base metals, (9) 216*b*.
growth, P (9) 225*h*.
methods of measuring the strength and role in reinforcing metal matrices, (1) 2*j*.
silicon nitride, destruction by reaction with metals at high temperatures, (9) 223*h*.
production, P (9) 227*h*.
wire, method of bonding, P (4) 101*b*.
Whiteware. See also *Art and artware; Bodies, ceramic; Dielectrics; Dinnerware; Heating elements; Insulators, electrical; Porcelain; Pottery; Tile.*
bodies, alumina improves properties, (9) 228*a*.
containing alumina and silica, comparison of strength, (8) 182*h*.
control test, B (1) 30*c*.
cuspidine-$CaSiO_3$ composition, (10) 261*c*.
fast firing, progress in, (4) 99*h*.
microstructure, (9) 228*c*.
plants, small fine-ceramic, body preparation, (9) 228*a*.
prosthetic parts, and methods of making, P (8) 183*a*.
sink units, P (2) 46*g*.
Wire, coated, total hemispherical emittance, (4) 112*e*.
composite flame spraying, P (10) 250*c*.
lead-in, with copper core, sealing characteristics, (5) 126*g*.
Wollastonite, glass-crystal transformation, (1) 19*c*.
uses in ceramic industry, (7) 160*j*.
wet processed, potential uses, (4) 106*c*.
Wustite, disintegration, mechanism and kinetics of, (3) 86*g*.
$Fe_{1-x}O$, crystal growth, (7) 162*j*.
kinetics of near-equilibrium reduction, (9) 240*d*.
reduction within wustite phase in H_2-H_2O mixtures, (1) 27*i*.

Xenoliths, spinel, in orthonorite with late diaspore at Mill of Boddam, Insch, Aberdeenshire (Scotland), (3) 87*d*.
Xenon, physisorption on glass and molybdenum films, (2) 36*j*.
Xenotime, decomposition, by sulfuric acid process, (3) 82*g*.
X-ray, analysis, advances in: Vols. 8 and 9, B (5) 139*e*.
analysis, of clay minerals, preparation of oriented slides for, (4) 104*c*.
use in elucidation of chemistry of antique ceramics, (3) 63*j*.
contrast agent, aqueous metal iodide solution for use as, P (8) 188*a*.
determination, of thermal expansion coefficient of ScB_2, (2) 59*d*.
diffraction, for determination of composition and homogeneity of epitaxial Ga(As,P) alloys, (3) 80*h*.
high pressure, studies on barium, (3) 86*f*.
low-temperature, powder techniques, (5) 131*e*.
measurements, to study firing behavior of Ti-O_2-opacified cover coat enamel, (4) 92*a*.
micrography, of antiferromagnetic nickel oxide twin structure, (3) 88*a*.
patterns, indexing, and precise determination of Ba_2SiO_4 crystal structure, (11) 297*f*.
patterns, of various glasses, (4) 93*e*.
quantitative analysis, application of orientation distribution measurement to, (4) 108*f*.
standard powder patterns, (3) 81*f*.
tables, B (2) 62*e*.
technique for rapid surface area determination, (5) 131*j*.
diffraction analysis, application to uranium ceramics, (8) 179*i*.
to determine glass content of aluminosilicates, (3) 71*h*.
of oxides, high temperature apparatus for measurement simultaneously with electrical resistivity, (11) 296*i*.
diffraction study, of ferroelectric lithium niobate polycrystal between 24° and 1200°C, (8) 198*h*.
of ferroelectric lithium niobate single crystals at 24°C, (8) 198*c*.
single crystal, of $Mn(OH)_2$, (8) 207*b*.
of vacuum-evaporated silver films, (2) 59*e*.
emission, microanalysis of rock-forming minerals: II, olivines; III, alkali feldspars; IV, plagioclase feldspars, (2) 59*g*-60*a*.
Evan's, study of tetragonal barium titanate, (7) 166*c*.
examination of quenched oxides of uranium of type UO_2, (9) 243*a*.
determination of volume fraction of phases in textured materials, (9) 243*h*.
fluorescence, analysis of electron tube materials, (1) 4*j*.
for determination of rare earths in glass, (10) 251*k*.
techniques for estimate of thickness of coatings for glass, (2) 36*i*.
high-temperature, study in controlled atmosphere of uranium-oxygen system, (1) 19*c*.
incoherent, elimination with diffracted beam monochromators, (1) 13*j*.
investigation, of aluminum phosphate, (5) 135*c*.
of bentonites from Bhadres and Hathiki-Dhani, Barmer district, (8) 189*j*.
of system SnS–PbS, (9) 243*c*.
of ZnO-MgO and ZnS-MgS systems, (9) 243*b*.
line broadening, in explosively shocked magnesium oxide, (10) 272*f*.
measure glass batch minor ingredients, (1) 4*a*.
method for defining composition of magnesium spinel, (2) 60*f*.
methods, for nondestructive testing of model brick, (3) 80*j*.
microanalysis, in chemistry, (9) 234*b*.
phase analysis, of indium-selenium melts, (2) 60*e*.
photography. See *Photography.*
powder diffraction study of $WO_3 \rightleftharpoons W_{20}O_{58}$ shear transformation, (2) 60*a*.
scattering by centrosymmetric crystals, (1) 16*i*.
scattering factors of magnesium oxide, experimental study, (9) 239*e*.
spectrometer. See *Spectrometers.*
studies, of alloys in system Mo-Re-C, (2) 60*f*.
of aquacreptite crystal structure, (9) 243*e*.
of dislocations in SiC crystals, (10) 272*h*.
of electron distributions in some monoxides of transition elements, (9) 243*f*.
of $HfSiO_4$, (11) 301*d*.
of PbO-V_2O_5 system, (5) 138*i*.
of lime-bentonite reaction products, (7) 169*e*.
on solid solutions of oxygen in α-zirconium, (3) 88*a*.

Young's modulus. See *Elasticity.*
Ytterbium, oxide:CaO crystalline solutions, defect characterization in, and precipitation from, (3) 84*g*.
$YbGaO_3$, high pressure synthesis, (8) 199*d*.
Yttria. See *Yttrium, oxide.*
Yttrium, aluminum garnet, efficient high-power coherent emission from Ho^{3+} ions, assisted by energy transfer, (8) 195*j*.
iron garnet, effect of impurities on optical properties, (8) 195*a*.
single-crystal growth by combined Czochralski-molten salt solvent technique, (4) 100*c*.
oxide, anomalous sintering behavior, (9) 237*f*.
fusion point measurement, (7) 159*e*.
self-diffusion of oxygen, (3) 88*a*.
sintering, (1) 28*h*.
sintering at 4000°F forms transparent ceramic, (9) 224*e*.
Yttrium, oxide (*continued*)
-zirconia, translucent, cubic phase stabilization at very low temperatures, (11) 293*i*.
scaling in air, (1) 28*j*.
systems. See *Systems.*
vanadate crystals, Czochralski growth and properties, (10) 262*a*.
YGaG, spin resonance of Co^{2+} in, (8) 207*b*.
$YGaO_3$, high pressure synthesis, (8) 199*d*.
$Y_3Fe_{5-x}Co_{x/2}Ge_{x/2}O_{12}$, garnet, ferromagnetic resonance, (7) 163*e*.
$YMnO_3$, ferroelectric hysteresis character, (11) 295*e*.
single crystals, antiferromagnetic, torque measurement on, (11) 302*d*.
YOOH, crystal structure, reinvestigation, (8) 206*c*.
YVO_4:Nd, unusual crystal-field energy levels and efficient laser properties of, (11) 303*b*.
zirconate, nonexistence, (1) 23*j*.

Zeolites, agglomerates, and preparation, P (3) 83*g*.
cation sites, selective exchange observed by electron spin resonance of Mn^{2+}:I, Linde X, (8) 206*f*.
crystalline, aluminosilicate, agglomeration, P (9) 235*g*.
process for preparing, P (4) 107*b*; P (9) 236*f*.
titanosilicate, P (10) 269*e*.
zirconosilicate, P (10) 269*e*.
in Eocene neritic bar sand, (1) 24*j*.
faujasite-type crystalline, method for making, P (11) 291*j*.
group IVB metallosilicate, manufacture, P (10) 269*i*.
high-silica molecular sieve, P (11) 291*h*.
salts, production, P (7) 161*c*.
synthetic, P (8) 190*i*.
crystalline aluminoborosilicate, and preparation, P (9) 236*i*.
crystalline compositions, and preparation, P (9) 236*i*.
zeolitic molecular sieve granules, silica bonded, production of, P (4) 107*a*.
Zinc, complex compounds, with chlorides of alkali metals, (11) 292*g*.
-diffused GaAs, correlation of electrical with chemical analysis, (3) 84*g*.
diffusion, effects of Mn-doped GaAs, (9) 242*i*.
difluoride, heat content of formation, (8) 198*b*.
in ferrite, determination by anion exchange resin, (5) 135*c*.
ferrite, single crystal hexagonal, microprobe and magnetic characterization, (9) 240*i*.
ferrites, process for firing to equilibrium state, P (10) 265*h*.
oxalate, pyrolysis of, kinetics and stoichiometry, (8) 205*j*.
pyrolytic decomposition, carbon isotope effects, (8) 192*d*.
thermal decomposition and surface properties, (8) 209*h*.
oxide, amorphous, semiconductor, and method of making, P (3) 77*i*.
catalytic and photochemical behavior, role of quality and concentration of lattice defects and activators, (1) 28*g*.
effect on setting and hardening of portland cements, (7) 146*d*.
electrophotographic layers, capacity, (5) 134*i*.
film transducers, (3) 77*g*.
kinetics and mechanism of reaction with barium carbonate, (10) 271*b*.
laser, ultraviolet, pumped by electron beam, (8) 183*j*.
as mill addition in glazes, (3) 74*i*.
pigment, production, P (8) 190*h*.
sublimation and thermodynamic properties, (8) 208*d*.
surfaces, activation energy for oxygen desorption, (11) 292*g*.
thin films, preparation by sputtering in oxygen and argon, (3) 76*i*.
ultrasonic attenuation at room temperature, (8) 211*e*.
oxides and sulfates, solid-phase interactions, (1) 28*h*.
powder, protective coating composition, P (2) 35*f*.
salt, water-soluble, in glass polishing composition, P (8) 177*d*.
selenide, crystals, growing from vapor phase, improved method, (11) 297*e*.
crystals, structure, and defects introduced during growth, (8) 208*a*.
epitaxial growth on GaAs, (10) 262*j*.
nucleation and growth of single crystals by chemical transport, (1) 24*f*.
sulfate, decomposition, influence of selected sulfides on rate at 600°C, (8) 200*e*.
sulfide, electron-beam-excited, efficient ultraviolet laser emission (10) 271*a*.
elements, in lenses for focusing infrared, P (5) 120*f*.
enhancement of optical second-harmonic generation by reflection phase matching, (8) 197*f*.
layer, used with boric acid or boric oxide for electroluminescent lamp, P (2) 47*e*.
neutron-irradiated, optical absorptions, (8) 204*c*.
phase change, and stacking sequence of new 66R polytype, (8) 204*f*.
and ZnTe, cubic, anomalous polarity-dependent electrooptic effect in, (10) 270*c*.
systems. See *Systems.*
in vapor grown gallium arsenide, (4) 100*h*.

Zinc (*continued*)
$ZnCdSb_2$, solid solution in, physical properties, (11) 299*i*.
$ZnFe_2O_4$, cation distribution, as precipitated from aqueous solution, (5) 126*d*.
Zn_2SiO_4 compositions, modified, P (10) 265*b*.
ZnTe, crystals, growing from vapor phase, improved method, (11) 297*e*.
p-type, showing injection electroluminescence, electrical properties, (11) 294*d*.
Zircon. See also *Refractories; Zirconium silicate.*
milled, particle size determination, (2) 5*a*.
opacifiers, preparation and performance in glazes, (8) 182*h*.
Zirconates, hexafluoro-, stannous, P (11) 292*c*.
Zirconia. See *Zirconium, oxide.*
Zirconium, alloys, mechanism of breakaway oxidation, (2) 35*d*.
alloys, properties of oxide films on, and relevance to corrosion and hydrogen uptake, (2) 35*g*.
and alloys, oxidation kinetics and oxide film breakaway at high temperatures, (1) 2*j*.
oxidation in water vapor atmospheres containing trace amounts of oxygen at 375° and 575°C, (1) 2*h*.
boride, effect of temperature on strength and plasticity, (3) 71*j*.
gas-impermeable protective thermocouple sheaths, (8) 198*g*.
high-temperature thermal expansion, (3) 86*f*.
thermocouple tips, performance in Bessemer converter, (10) 258*f*.
carbide, kinetics of reactions of elemental fluorine at high temperatures with, (8) 20·*j*.
oxidation kinetics at high temperatures, (3) 87*f*.
carbides, mutual solubility with niobium and hafnium carbides, (2) 55*g*.
-carbon reaction, kinetics above 2000°C, (7) 164*j*.
-carbon, variation of molar mixing volumes, (10) 272*a*.
ceramic compounds, electrical conductivity of, between 1500° and 2400°K, (2) 46*i*.
compounds, formation of oxy-bridges, (11) 296*d*.
recovery from alkali metal zirconium silicates, P (1) 16*b*.
Zirconium (*continued*)
diboride, kinetics of reactions of elemental fluorine at high temperatures with, (8) 201*j*
oxidation characteristics, (10) 258*c*.
oxidation kinetics at high temperatures, (3) 87*f*.
dielectric loss spectra of corrosion films on, (4) 100*e*.
diffusion in zirconium hydride, (4) 107*h*.
dioxide-CeO_2, thermal expansion and electrical resistance of sintered bodies in, (8) 209*j*.
dioxide, as grain-growth inhibitor in beryllia bodies, P (1) 7*k*.
microballoons, preparation and characterization, (7) 152*a*.
monoclinic, diffuse reflectance characteristics as function of purity, (10) 249*g*.
nonstoichiometry, and relation to tetragonal-cubic inversion in ZrO_2, (7) 166*c*.
nucleating agent, effect on separating crystal phases during production of glass-ceramics, (10) 251*d*.
-oxygen reactions: I, molecular oxygen adsorption with electric transfer; II, chemisorption of atomic oxygen, (7) 169*f*.
torsion effusion study of reaction with graphite, (8) 210*d*.
-Y_2O_3 compositions, high temperature apparatus for simultaneous measurement of electrical resistivity and X-ray diffraction analysis of, (11) 296*i*.
high-temperature oxidation kinetics, in dry oxygen, (5) 136*j*.
hot hardness to 1900°C, (7) 164*f*.
minerals, X-ray spectrographic determination of hafnium-zirconium ratio in, (2) 60*c*.
oxidation, at high temperatures, kinetics, (11) 391*h*.
oxidation mechanism, in oxygen and liquid sodium, (9) 240*g*.
in temperature range of 400° to 850°C, (7) 165*b*.
oxide, action of oxygenated compounds of potassium on, (1) 16*d*.
-containing electrolyte, in fuel cell, P (4) 101*g*.
Zirconium, oxide (*continued*)
crystalline, and/or hafnia, aquasols, P (2) 45*a*.
cubic crystalline, process for production, P (10) 270*a*.
electrical conductivity between 1200° and 1750°C, (1) 18*c*.
electrical conductivity of pure, between 1500° and 2400°K, (2) 46*i*.
electrical resistivity and diffusionless phase transformations at high temperatures and ultrahigh pressures, (9) 238*j*.
electrolyte, stabilized, in fuel cell, P (4) 101*h*.
enamels, crystallization processes, (3) 65*j*.
glasses, crystallization processes, (3) 65*j*.
ionic conductivity, some applications, (2) 47*c*.
metastable tetragonal to monoclinic transition, kinetics and mechanism, (7) 164*g*.
partially stabilized, method of making, P (4) 89*h*.
phase transformations at high temperatures, (4) 109*g*.
phosphate bonding, (4) 97*a*.
reduction of absorbed oxygen with hydrogen, (5) 137*f*.
and silica mixture, preparation, P (3) 83*g*.
and silicic acid, production of mixtures of, P (4) 99*d*.
spheres, preparation and structure, (10) 271*e*.
stabilized, elastic modulus, (5) 135*c*.
stabilization, effects of iron group oxides, (3) 85*f*.
stabilized, thermal conductivity at high temperatures, (2) 57*i*.
stabilized and partly stabilized, microstructure, (3) 86*i*.
thin flakes, method of producing, P (11) 294*j*.
oxides, highly dispersed, process for purification, P (9) 236*j*.
for producing refractory metal chlorides, P (3) 72*f*.
phosphate, crystalline, hydrolysis, (11) 297*h*.
reaction with CO_2 and CO at 850°C, (11) 300*h*.
separating hafnium from, P (1) 15*i*.
systems. See *Systems.*
$ZrTiO_4$, crystal structure, (5) 134*j*.

CERAMIC ABSTRACTS

1967

FRANK P. REID, *Publisher and General Secretary*
HERBERT INSLEY, *Editor*
MARY J. GIBB, *Associate Editor*
GERTRUDE M. BUSICK, *Assistant Editor*
VIRGINIA BENEDICT, *Editorial Assistant*
DONNA ROOT, *Editorial Assistant*
JEANNE C. BONHAM, *Indexer*

Committee on Publications: W. J. SMOTHERS, *Chairman;*
HOWARD F. MCMURDIE, SEYMOUR L. BLUM, CLARENCE L. BABCOCK, AND, EX OFFICIO,
HERBERT INSLEY, E. E. MUELLER, AND F. P. REID

Technical Adviser: R. S. SHELDON

Compiled by

The American Ceramic Society
4055 North High Street
Columbus, Ohio 43214

ABSTRACTERS FOR 1967

Abraham Aladjem—Israel
Eugene Aleshin—U. S.
Wilfred Ashworth—England
D. J. Barbour—U. S.
M. P. Bauleke—U. S.
Gerhard Bayer—Switzerland
M. D. Beals—U. S.
K. E. Bell—Canada
Adli Bishay—Egypt
J. J. Borbas—U. S.
J. G. Brady—Canada
W. B. Campbell—U. S.
N. F. Cerulli—U. S.
G. W. Cleek—U. S.
J. J. Diamond—U. S.
F. V. DiMarcello—U. S.
Alfred Dube—Canada
R. H. Edwards—U. S.
Marie Farnsworth—U. S.
W. M. Fenton—U. S.
C. E. L. Franklin—England
Kanekoto Fujii—Japan
J. E. Gillott—Canada
F. W. Glaze—U. S.
H. T. Harrison—U. S.
H. S. Hartmann—U. S.
M. P. Haydon—U. S.
R. O. Heckroodt—South Africa
C. I. Helgesson—Sweden
R. H. Insley—U. S.
B. Z. Kamich—U. S.
Keramos, Ohio State University—U. S.
M. J. Kerper—U. S.
Herbert Kornguth—U. S.
A. M. Lacy—U. S.
M. P. Lepie—U. S.
S. A. Lindroth—Sweden
J. R. Little—U. S.
Luigi Luciani—Italy
V. V. Mirkovich—Canada
Sylva Modry—Czechoslovakia
M. K. Murthy—Canada
J. F. Nicks—Canada
A. W. Norris—England
J. J. Nunes—U. S.
L. S. O'Bannon—U. S.
V. R. Palmeri—U. S.
L. N. Perkins—U. S.
W. W. Perkins—U. S.
V. S. Ramachandran—India
Don Satas—U. S.
J. O. Semmelman—U. S.
N. W. Severin—U. S.
Kenneth Shaw—England
L. E. Shipley—U. S.
W. K. Soderstrum—U. S.
Shigeyuki Somiya—Japan
I. L. Soreghy—U. S.
K. F. Sporek—U. S.
M. A. Stett—U. S.
Helmut Stoll—Germany
J. A. Sugden—England
Yuichi Suzukawa—Japan
V. D. Svikis—Canada
Ferenc Tamas—Hungary
J. W. Taylor—Scotland
R. L. Thakur—India
Minoru Tomozawa—U. S.
T. B. Weston—Canada
J. H. Weymouth—Australia
J. B. Whitney—U. S.
D. T. Williams—U. S.
W. O. Williamson—U. S.
Kazuo Yamasaki—Japan